SL Corporation PHOTOMETRIC RESULTS

Program:	FMVSS108 (2016.02)	H/L NAS PHOTO HIGH (120%)									
H/L NAS PHOTO HIGH UB2											
Name:	CT1 NAS HL LED HIGH (OPT ASSY-LED)(2DOWN) RH#2 2025-08-04										
Number:											
Report:	Kim Jin Mo										
Test no.:											
Lamp type:	LED										
Lamp no:	PRODUCT										
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)								
Voltage:	12.8050 V	Date:	2025-08-05 오전 6:50:37								
Current:	0.00071 A	File:	CT1 NAS HL LED HIGH (OPT ASSY- LED)(2DOWN) RH#2 2025-08-04								

H/L NAS PHOTO HIGH (120%)

Function	Min	Max	l [cd]	H [°]	V [°]	Reaim I [cd]	H [°]	V [°]	N.O .K.
2U - V (120%)	1800	-	37298.5	0.00	2.00				OK
1U - 3L (120%)	6000	-	39130.5	-3.00	1.00				OK
1U - 3R (120%)	6000	-	22144.1	3.00	1.00				OK
H - V (120%)	4800 0	60000	51935.1	0.00	0.00				OK
H - 3L (120%)	1800 0	-	41898.5	-3.00	0.00				ОК
H - 3R (120%)	1800 0	-	27829.5	3.00	0.00				OK
H - 6L (120%)	6000	-	16867.0	-6.00	0.00				OK
H - 6R (120%)	6000	-	12466.0	6.00	0.00				OK
H - 9L (120%)	3600	-	8114.9	-9.00	0.00				OK
H - 9R (120%)	3600	-	7925.7	9.00	0.00				OK
H - 12L (120%)	1800	-	4878.9	-12.00	0.00				OK
H - 12R (120%)	1800	-	5672.4	12.00	0.00				OK
1.5D - V (120%)	6000	-	70574.3	0.00	-1.50				OK
1.5D - 9L (120%)	2400	-	14955.2	-9.00	-1.50				OK
1.5D - 9R (120%)	2400	-	16757.4	9.00	-1.50				OK
2.5D - V (120%)	3000	-	48997.8	0.00	-2.50				OK
2.5D - 12L (120%)	1200	-	8134.8	-12.00	-2.50				OK
2.5D - 12R (120%)	1200	-	10833.1	12.00	-2.50				OK
4D - V (120%)	-	9600	11330.9	0.00	-4.00	9030.9	0.00	-4.25	OK
MAX	-	-	75283.9	-0.20	-0.73				OK