## SL Corporation PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.1 (2016.02) SAE J588	F/T/S NAS LED [1 BULB] 2.5RH					
F/T/S NAS PH	IOTO LED [1 BULB] 2.5RH						
Name:	CT1 NAS HL LED T-SIG (STD ASSY-LED) RH #2 2025-07-02						
Number:							
Report:	Hwang Ji Hoon						
Test no.:							
Lamp type:	LED						
Lamp no:	PRODUCT						
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)				
Voltage:	13.5030 V	Date:	2025-07-02 오후 1:09:24				
Current:	0.00071 A	File:	CT1 NAS HL LED T- SIG (STD ASSY-LED) RH #2 2025-07-02				

## F/T/S NAS LED [1 BULB] 2.5RH

Function	Min	Max	l [cd]	H [°]	V [°]	N.O.K.
1min H-V	-	-	507.221	0.00	0.00	OK
10min H-V	-	-	471.999	0.00	0.00	OK
30min H-V	-	-	457.589	0.00	0.00	OK
10U - 5L	100	-	344.218	-5.00	10.00	OK
10U - 5R	100	-	343.817	5.00	10.00	OK
5U - 20L	62.5	-	124.579	-20.00	5.00	OK
5U - 10L	187.5	-	335.712	-10.00	5.00	OK
5U - V	437.5	-	435.275	0.00	5.00	NG
5U - 10R	187.5	-	337.614	10.00	5.00	OK
5U - 20R	62.5	-	198.325	20.00	5.00	OK
H - 10L	250	-	352.123	-10.00	0.00	OK
H - 5L	500	-	440.479	-5.00	0.00	NG
H - V	500	-	457.289	0.00	0.00	NG
H - 5R	500	-	409.859	5.00	0.00	NG
H - 10R	250		342.517	10.00	0.00	OK
5D - 20L	62.5	-	106.567	-20.00	-5.00	OK
5D - 10L	187.5	-	291.284	-10.00	-5.00	OK
5D - V	437.5		379.340	0.00	-5.00	NG
5D - 10R	187.5		293.786	10.00	-5.00	OK
5D - 20R	62.5	-	168.407	20.00	-5.00	OK
10D - 5L	100	-	252.460	-5.00	-10.00	OK
10D - 5R	100	-	244.655	5.00	-10.00	OK
Visibility	0.3	-	(5.422) 462.204	(-45.00) - 1.70	(- 15.00) 1.00	ОК

## ZONE

Function	Min	Max	l [cd]	H [°]	V [°]	N.O.K.
Zone_1	325	-	827.824			OK
Zone_2	625	-	979.119			OK
Zone_3	2375	-	2122.242			NG
Zone_4	625		973.916			OK
Zone_5	325	-	955.204			OK