

# SL Corporation

## PHOTOMETRIC RESULTS

Program:	KATRI Regulation No.21-2		H/L DOM PHOTO LED LOW VER013
H/L DOM PHOTO LOW			
Name:	JW1 PE HPV DOM HL LED LOW(STD ASSY-LED) LH#2 2025-09-04		
Number:			
Report:	JO WON JIN		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)
Voltage:	13.2136 V	Date:	2025-09-04 오후 10:42:43
Current:	0.00000 A	File:	JW1 PE HPV DOM HL LED LOW(STD ASSY- LED) LH#2 2025-09-04

## H/L DOM PHOTO LED LOW VER013

Function	Min	Max	I [cd]	H [°]	V [°]	N. O. K.
B50L	-	350	243.6415	-3.43	0.57	OK
BR	-	1750	213.6487	2.50	1.00	OK
75R	10100	-	25813.8000	1.15	-0.57	OK
75L	-	10600	1076.7420	-3.43	-0.57	OK
50L	-	18500	11237.3000	-3.43	-0.86	OK
50R	10100	-	26743.5800	1.72	-0.86	OK
50V	5100	-	19005.4400	0.00	-0.86	OK
25L	1700	-	10947.3700	-9.00	-1.72	OK
25R	1700	-	8827.8810	9.00	-1.72	OK
1	-	625	136.0674	-8.00	4.00	OK
2	-	625	108.2740	0.00	4.00	OK
3	-	625	131.6684	8.00	4.00	OK
4	-	625	200.2519	-4.00	2.00	OK
5	-	625	173.5583	0.00	2.00	OK
6	-	625	151.6636	4.00	2.00	OK
7	65	625	327.8213	-8.00	0.00	OK
8	125	625	190.9542	-4.00	0.00	OK
ZONE III	-	625	(102.7753) 310.7254	(2.40) -5.60	(4.00) 0.80	OK
ZONE IV	2500	-	(14806.4500) 30188.7500	(-3.95) -0.10	(-0.86) -1.72	OK
ZONE I	-	2*50R	(4933.0160) 30156.7600	(9.00) -0.10	(-5.00) -1.80	OK

## Signal

Function	Min	Max	I [cd]	H [°]	V [°]	N. O. K.
1+2+3	190	-	376.0098			OK
4+5+6	375	-	525.4738			OK