SL Corporation PHOTOMETRIC RESULTS

Program:	CMVSS108, SAE J2087	DRL NAS CANADA LED PHOTO(WITH)					
DRL NAS CANADA LED PHOTO(WITH)							
Name:	CT1 NAS HL LED DRL (STD ASSY-LED) RH #3 2025-06-30						
Number:							
Report:	Lee Bong Gyu						
Test no.:							
Lamp type:	LED						
Lamp no:	PRODUCT						
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)				
Voltage:	12.8101 V	Date:	2025-06-30 오후 10:38:51				
Current:	0.00000 A	File:	CT1 NAS HL LED DRL (STD ASSY-LED) RH #3 2025-06-30				

DRL NAS CANADA LED PHOTO(WITH)

Function	Min	Max	l [cd]	H [°]	V [°]	N.O. K.
1MIN	-	-	553.7000	0.00	0.00	OK
30MIN	-	-	536.6000	0.00	0.00	OK
5U-10L	100	2500	347.2000	-10.00	5.00	OK
5U-V	350	2500	523.6000	0.00	5.00	OK
5U-10R	100	2500	373.7000	10.00	5.00	OK
H-20L	50	2500	141.6000	-20.00	0.00	OK
H-10L	350	2500	355.2000	-10.00	0.00	OK
H-5L	450	2500	490.5000	-5.00	0.00	OK
H-V	500	2500	536.5000	0.00	0.00	OK
H-5R	450	2500	476.2000	5.00	0.00	OK
H-10R	350	2500	368.0000	10.00	0.00	OK
H-20R	50	2500	171.9000	20.00	0.00	OK
5D-10L	100	2500	278.3000	-10.00	-5.00	OK
5D-V	350	2500	402.4000	0.00	-5.00	OK
5D-10R	100	2500	281.9000	10.00	-5.00	OK
MAX	-	2500	(35.5000) 548.3000	(-30.00) -0.80	(-9.80) 2.00	OK

Function	Min	Max	l [cd]	н [°]	V [°]	N.O. K.
ZONE1	2100	-	2429.2000			OK
ZONE2	600	-	1122.3000			OK
ZONE3	600	-	1195.5000			OK