

SL Corporation

PHOTOMETRIC RESULTS

Program:	KATRI Regulation No.21-8		F/POSI DOM LED LH
F/POSI DOM LED LH			
Name:	CE FL DOM HL LED PSTN (STD ASSY-LED) LH #2 2025-03-21		
Number:			
Report:	GO YUN SOO		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL CORP.(LAB #3 LMT GO-H1660)
Voltage:	13.5150 V	Date:	2025-03-21 오전 2:32:22
Current:	0.00010 A	File:	CE FL DOM HL LED PSTN (STD ASSY-LED) LH #2 2025-03-21

F/POSI DOM LED LH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
1min H-V	-	-	67.843	0.00	0.00	OK
30min H-V	-	-	68.421	0.00	0.00	OK
10U-5L	0.8	140	48.563	-5.00	10.00	OK
10U-5R	0.8	140	47.197	5.00	10.00	OK
5U-20L	0.4	140	19.767	-20.00	5.00	OK
5U-10L	0.8	140	59.421	-10.00	5.00	OK
5U-V	2.8	140	67.806	0.00	5.00	OK
5U-10R	0.8	140	53.591	10.00	5.00	OK
5U-20R	0.4	140	22.113	20.00	5.00	OK
H-10L	1.4	140	59.710	-10.00	0.00	OK
H-5L	3.6	140	63.397	-5.00	0.00	OK
HV	4	140	68.457	0.00	0.00	OK
H-5R	3.6	140	65.457	5.00	0.00	OK
H-10R	1.4	140	53.985	10.00	0.00	OK
5D-20L	0.4	140	18.260	-20.00	-5.00	OK
5D-10L	0.8	140	47.183	-10.00	-5.00	OK
5D-V	2.8	140	54.784	0.00	-5.00	OK
5D-10R	0.8	140	43.330	10.00	-5.00	OK
5D-20R	0.4	140	19.088	20.00	-5.00	OK
10D-5L	0.8	140	30.882	-5.00	-10.00	OK
10D-5R	0.8	140	30.903	5.00	-10.00	OK
MIN/MAX	0.05	140	(0.122) 70.116	(45.00) 0.90	(-15.00) 2.40	OK