

GeoPal Scriptable Steps

API Documentation

ver 1.6

1. [Scriptable Steps](#)
 - [Scripting](#)
 - [Scripting Window](#)
2. [Scriptable Steps Api Jobs](#)
 - [getJobId](#)
 - [getJobIdentifier](#)
 - [getJobTemplateName](#)
 - [getJobTemplateId](#)
 - [getJobAddress](#)
 - [getJobCustomerId](#)
 - [getJobCustomerName](#)
 - [getJobEmployeeFullName](#)
 - [getJobEmployeeId](#)
 - [getJobPersonIdentifier](#)
 - [getJobPersonFirstName](#)
 - [getJobPersonLastName](#)
 - [getJobPersonFullName](#)
 - [getJobStatusId](#)
3. [Scriptable Steps Api Job Fields](#)
 - [getJobFieldValueByName](#)
 - [getJobFieldValueByPosition](#)
 - [getJobFieldValueByTemplateId](#)
 - [setJobFieldValueByName](#)
 - [setJobFieldValueByPosition](#)
 - [setJobFieldValueByTemplateId](#)
4. [Scriptable Steps Api Job Field File](#)
 - [downloadJobfieldFileByName](#)
 - [downloadJobfieldFileByTemplateId](#)
 - [downloadJobfieldFileByPosition](#)
5. [Scriptable Steps Api Job Workflows](#)
 - [getJobWorkflowName](#)
 - [getJobWorkflowPosition](#)
 - [getJobWorkflowValue](#)
 - [getJobWorkflowValueByName](#)
 - [getJobWorkflowValueByPosition](#)
 - [getJobWorkflowValueByTemplateId](#)
 - [getJobWorkflowActionValueByName](#)
 - [getJobWorkflowActionValueByPosition](#)
 - [getJobWorkflowActionValueByTemplateId](#)
 - [getJobWorkflowsIsActive](#)
 - [getJobWorkflowsIsActiveByPosition](#)
 - [getJobWorkflowsIsActiveByTemplateId](#)
 - [getJobWorkflowsIsActiveByName](#)
 - [getWorkflowFilePathByName](#)
 - [getWorkflowFilePathByTemplateId](#)
 - [getWorkflowFilePathByPosition](#)

[gotoJobWorkflowByName](#)
[gotoJobWorkflowByPosition](#)
[gotoJobWorkflowByTemplateId](#)
[gotoJobById](#)
[gotoJobById](#)
[gotoJobById](#)
[gotoJobByIdentifier](#)
[gotoJobByIdentifier](#)
[gotoJobByIdentifier](#)
[gotoJobByIdentifier](#)
[gotoJobList](#)
[setJobWorkflowValue](#)
[setJobWorkflowValueByName](#)
[setJobWorkflowValueByPosition](#)
[setJobWorkflowValueByTemplateId](#)
[setJobWorkflowActionValueByName](#)
[setJobWorkflowActionValueByPosition](#)
[setJobWorkflowActionValueByTemplateId](#)
[setJobWorkflowsActive](#)
[setJobWorkflowsActiveByPosition](#)
[setJobWorkflowsActiveByTemplateId](#)
[setJobWorkflowsMandatoryByName](#)
[setJobWorkflowsMandatory](#)
[setJobWorkflowsMandatoryByPosition](#)
[setJobWorkflowsMandatoryByTemplateId](#)
[setJobWorkflowsMandatoryByName](#)
[setWorkflowFileByName](#)
[setWorkflowFileByTemplateId](#)
[setWorkflowFileByPosition](#)
[forceCheckOut](#)

6. Scriptable Steps Api Create Job

[createSimpleJob](#)
[createAdvancedJob](#)
[createAdvancedJobWithFields](#)

7. Scriptable Steps Api Assets

[getAssetIdentifier](#)
[getAssetName](#)
[getBoundAssetFieldValueByAssetCompanyFieldId](#)
[getBoundAssetFieldValueByAssetCompanyFieldName](#)
[updateAssetStatus](#)

8. Scriptable Steps Api PDF

[addSignaturetoPdfField](#)
[addSignaturetoPdfSignatureField](#)
[addSignaturetoPdfAtPositionByCoordinates](#)
[addSignaturetoPdfAtPositionByCoordinates](#)
[addSignaturetoPdfAtPositionRighthandCorner](#)

[addSignaturetoPdfAtPositionRighthandCorner](#)
[openPDFApplication](#)

[9. Scriptable Steps Api Other](#)

[showMessage](#)
[showSingleChoiceList](#)
[showMultiChoiceList](#)
[showYesNoDialog](#)
[showYesNoMaybeDialog](#)
[showEnterText](#)
[showEnterNote](#)
[startPhoneDialer](#)
[showSignatureDialog](#)
[showProgressDialog](#)
[showProgressDialog](#)
[hideProgressDialog](#)
[httpSender](#)
[scanBarcode](#)

[10. Examples](#)

[Hello World](#)
[Calculation](#)
[Conditional Logic](#)
[Scoring](#)
[PDF Signature Capture](#)

Change Log

Date	Version	Changes Made	Changes By
18/12/2013	1	Initial Version	Sean O'Reilly
19/12/2013	1.1	renamed duplicate getAssetIdentifier to getAssetName	Tara Fennell
13/01/2014	1.2	New methods for pdf, creating jobs and goto jobs/job list added	Tara Fennell
10/04/2014	1.3	New methods for getting and setting jobworkflow action values	Tara Fennell
17/06/2014	1.4	Added documentation for setJobWorkflowsActi ve,	Tara Fennell

		updateAssetStatus and scanBarcode	
18/06/2014	1.5	Fixed param definition for setJobWorkflowsMa ndatoryByName what was int should have been string	Sean O'Reilly
19/06/2014	1.6	Deprecated httpSender	Sean O'Reilly

1. Scriptable Steps


This section describes what scriptable steps are.

Scripting

Scriptable steps can be used to create logic, scoring, calculation and other steps that require advanced features. Steps can be scripted using javascript. All the features of javascript can be used to update, set, and get job workflow and field values. Scriptable steps have been included since 1.3.9

Scripting Window

The scripting step can be activated by selecting Scriptable Step in the job workflow.



The script itself can be entered by clicking on the Enter Details button.

Scriptable Step:

```
var name = Geopal.getJobEmployeeFullName();  
Geopal.showMessage('Hello World ' + name);  
Geopal.setJobWorkflowValue('Said Hi to ' + name);
```

All geopal scriptable functions can be accessed through the Geopal namespace.

2. Scriptable Steps Api Jobs

getJobId

Description	Gets the geopal job id for the job. If the job has not been synced yet to the server then it is 0.
--------------------	--

Parameters	None
Returns	Int

getJobIdentifier

Description	Gets the geopal job identifier for the job.
Parameters	None
Returns	String

getJobTemplateName

Description	Gets the geopal job template name for the job.
Parameters	None
Returns	String

getJobTemplateId

Description	Gets the geopal job template id for the job.
Parameters	None
Returns	Int

getJobAddress

Description	Gets the full address of the job
Parameters	None
Returns	String

getJobCustomerIdIdentifier

Description	Gets the customer identifier
Parameters	None
Returns	String

getJobCustomerName

Description	Gets the customer name
Parameters	None
Returns	String

getJobEmployeeFullName

Description	Gets the assigned to employee's full name
Parameters	None
Returns	String

getJobEmployeeId

Description	Gets the assigned to employee's id
Parameters	None
Returns	Int

getJobPersonIdentifier

Description	Gets the job persons identifier. In the UI its called Contact.
Parameters	None

Returns	String
----------------	--------

getJobPersonFirstName

Description	Gets the job persons first name. In the UI its called Contact.
Parameters	None
Returns	String

getJobPersonLastName

Description	Gets the job persons last name. In the UI its called Contact.
Parameters	None
Returns	String

getJobPersonFullName

Description	Gets the job persons full name. In the UI its called Contact.
Parameters	None
Returns	String

getJobStatusId

Description	Gets the job's status id. You can see all job statuses via api/jobs/statuses
Parameters	None
Returns	Int

3. Scriptable Steps Api Job Fields

getJobFieldValueByName

Description	Gets a job field value by name
Parameters	String: The Job Field Name
Example	Geopal.getJobFieldValueByName('Enter Customer Id');
Returns	String

getJobFieldValueByPosition

Description	Gets a job field value by their position in the list
Parameters	int: The Job Field Position
Example	Geopal.getJobFieldValueByPosition(0);
Returns	String

getJobFieldValueByTemplateId

Description	Gets a job field value by their template id. You can find the template id of job with the api <code>api/jobtemplates/get</code> call.
Parameters	int: The Job Field Template Id
Example	Geopal.getJobFieldValueByTemplateId(999);
Returns	String

setJobFieldValueByName

Description	Sets a Job Field value by name
Parameters	string: The Job Field Name string: value

Example	Geopal.setJobFieldValueByName('Enter Details', 'new value');
Returns	None

setJobFieldValueByPosition

Description	Sets a Job Field value by position
Parameters	int: The Job Field Position string: value
Example	Geopal.setJobFieldValueByPosition(1, 'new value');
Returns	None

setJobFieldValueByTemplateId

Description	Sets a Job Field value by template id
Parameters	int: The Job Field Template Id string: value
Example	Geopal.setJobFieldValueByTemplateId(999, 'new value');
Returns	None

4. Scriptable Steps Api Job Field File

downloadJobfieldFileByName

Description	Downloads job field file by name
Available	1.7.x
Parameters	String: callbackSuccess String: callbackFailed String: name
Example	var successFileFound = function(filepath) { Geopal.showMessage(filepath);

	<pre>}; var failedFileNotFound = function(error) { Geopal.showMessage(error); }; Geopal.downloadJobfieldFileByName('successFileFound','failedFileNotFound','Customer Docket');</pre>
Returns	None

downloadJobfieldFileByTemplateId

Description	Downloads job field file by templateId
Available	1.7.x
Parameters	String: callbackSuccess String: callbackFailed int: templateId
Example	<pre>var templateId = Geopal.getJobTemplateId(); var successFileFound = function(filepath) { Geopal.showMessage(filepath); }; var failedFileNotFound = function(error) { Geopal.showMessage(error); }; Geopal.downloadJobfieldFileByName('successFileFound','failedFileNotFound',templateId);</pre>
Returns	None

downloadJobfieldFileByPosition

Description	Downloads job field file by position
Available	1.7.x
Parameters	String: callbackSuccess String: callbackFailed int: position
Example	<pre>var successFileFound = function(filepath) {</pre>

	<pre> Geopal.showMessage(filepath); }; var failedFileNotFound = function(error) { Geopal.showMessage(error); }; Geopal.downloadJobfieldFileByPosition('successFileFound','failedFileNotFo und',3); </pre>
Returns	None

5. Scriptable Steps Api Job Workflows

getJobWorkflowName

Description	Gets the current job workflow name
Parameters	None
Returns	String

getJobWorkflowPosition

Description	Gets the current job workflow position
Parameters	None
Returns	Int

getJobWorkflowValue

Description	Gets the current job workflow value
Parameters	None

Returns	String
----------------	--------

getJobWorkflowValueByName

Description	Gets a job workflow value by name
Parameters	string: The Job Workflow Name
Example	Geopal.getJobWorkflowValueByName('Pick From List');
Returns	String

getJobWorkflowValueByPosition

Description	Gets a job workflow value by position
Parameters	int: The Job Workflow Position
Example	Geopal.getJobWorkflowValueByPosition(15);
Returns	String

getJobWorkflowValueByTemplateId

Description	Gets a job workflow value by template id
Parameters	int: The Job Workflow Template Id
Example	Geopal.getJobWorkflowValueByTemplateId(999);
Returns	String

getJobWorkflowActionValueByName

Description	Gets a job workflow values by name
--------------------	------------------------------------

Parameters	string: The Job Workflow Name
Example	Geopal.getJobWorkflowActionValueByName('Pick From List');
Returns	String

getJobWorkflowActionValueByPosition

Description	Gets a job workflow value by position
Parameters	int: The Job Workflow Position
Example	Geopal.getJobWorkflowActionValueByPosition(15);
Returns	String

getJobWorkflowActionValueByTemplateId

Description	Gets a job workflow value by template id
Parameters	int: The Job Workflow Template Id
Example	Geopal.getJobWorkflowActionValueByTemplateId(999);
Returns	String

getJobWorkflowsActive

Description	Gets the current job workflow is active
Parameters	None
Returns	Boolean

getJobWorkflowsActiveByPosition

Description	Gets the current job workflow is active by position
--------------------	---

Parameters	None
Returns	Boolean

getJobWorkflowsActiveByTemplateId

Description	Gets the current job workflow is active by template id
Parameters	None
Returns	Boolean

getJobWorkflowsActiveByName

Description	Gets the current job workflow is active by name
Parameters	None
Returns	Boolean

getWorkflowFilePathByName

Description	Gets the current job workflow filepath by name
Available	1.7.x
Parameters	String: name of workflow
Example	Geopal.getWorkflowFilePathByName('Signature PDF Signed');
Returns	String

getWorkflowFilePathByTemplateId

Description	Gets the current job workflow filepath by TemplateId
Available	1.7.x
Parameters	int: template id of workflow
Example	Geopal.getWorkflowFilePathByTemplateId(512);

Returns	String
----------------	--------

getWorkflowFilePathByPosition

Description	Gets the current job workflow filepath by name
Available	1.7.x
Parameters	int: position of workflow
Example	Geopal.getWorkflowFilePathByPosition(6);
Returns	String

gotoJobWorkflowByName

Description	Goes to a job workflow by name
Parameters	string: The Job Workflow Name
Example	Geopal.gotoJobWorkflowByName('Annotate Picture');
Returns	None

gotoJobWorkflowByPosition

Description	Goes to a job workflow by position
Parameters	int: The Job Workflow Position
Example	Geopal.gotoJobWorkflowByPosition(10);
Returns	None

gotoJobWorkflowByTemplateId

Description	Goes to a job workflow by template id
--------------------	---------------------------------------

Parameters	int: The Job Workflow Template Id
Example	Geopal.gotoJobWorkflowByTemplateId(10);
Returns	None

gotoJobById

Description	Goes to a job by job id. Auto accept defaults to false and start tab defaults to TAB_STEPS
Available	1.7.x
Parameters	int: The Job Id
Example	Geopal.gotoJobById(823);
Returns	None

gotoJobById

Description	Goes to a job by job id with option to accept job. Start tab defaults to TAB_STEPS
Available	1.7.x
Parameters	int: The Job Id boolean: auto accept job
Example	Geopal.gotoJobById(823, true);
Returns	None

gotoJobById

Description	Goes to a job by job id with option to open to tab and auto accept
Available	1.7.x
Parameters	int: The Job Id int: Start tab boolean: auto accept job
Example	Geopal.gotoJobById(823,1,false);

Returns	None
Note	Start tab is affected by configuration options. If configuration options remove at tab at an index, out of bounds error may occur or wrong tab will be opened. TAB_STEPS = 0; TAB_MAPS = 1; TAB_DETAILS = 2; TAB_ASSET = 3; TAB_CRM = 4;

gotoJobByIdentifier

Description	Goes to a job by job identifier. Auto accept defaults to false and start tab defaults to TAB_STEPS
Available	1.7.x
Parameters	String: The Job identifier
Example	Geopal.gotoJobById(823);
Returns	None

gotoJobByIdentifier

Description	Goes to a job by job identifier with option to accept job. Start tab defaults to TAB_STEPS
Available	1.7.x
Parameters	String: The Job identifier boolean: auto accept job
Example	Geopal.gotoJobById('test job', true);
Returns	None

gotoJobByIdentifier

Description	Goes to a job by job identifier with option to open to tab. Auto accept defaults to false
Available	1.7.x
Parameters	String: The Job identifier int: Start tab
Example	Geopal.gotoJobById('test job', 1);
Returns	None

gotoJobByIdentifier

Description	Goes to a job by job identifier with option to open to tab and auto accept
Available	1.7.x
Parameters	String: The Job identifier int: Start tab boolean: auto accept job
Example	Geopal.gotoJobById('test job',1,false);
Returns	None
Note	Start tab is affected by configuration options. If configuration options remove at tab at an index, out of bounds error may occur or wrong tab will be opened. TAB_STEPS = 0; TAB_MAPS = 1; TAB_DETAILS = 2; TAB_ASSET = 3; TAB_CRM = 4;

gotoJobList

Description	Goes to job list
Available	1.7.x
Example	Geopal.gotoJobList();
Returns	None

setJobWorkflowValue

Description	Sets the current job workflow value
Parameters	string: new value
Example	Geopal.setJobWorkflowValue('new value');
Returns	None

setJobWorkflowValueByName

Description	Sets a job workflow value by name
Parameters	string: Job Workflow Name string: new value
Example	Geopal.setJobWorkflowValueByName('Pick From a List', 'new value');
Returns	None

setJobWorkflowValueByPosition

Description	Sets a job workflow value by position
Parameters	int: Job Workflow Position string: new value
Example	Geopal.setJobWorkflowValueByPosition(12, 'new value');
Returns	None

setJobWorkflowValueByTemplateId

Description	Sets a job workflow value by template id
Parameters	int: Job Workflow Template Id string: new value
Example	Geopal.setJobWorkflowValueByTemplateId(999, 'new value');
Returns	None

setJobWorkflowActionValueByName

Description	Sets a job workflow value by name
Parameters	string: Job Workflow Name string: new value
Example	Geopal.setJobWorkflowValueByName('Pick From a List', 'new value,new options,new everthing');

Returns	None
----------------	------

setJobWorkflowActionValueByPosition

Description	Sets a job workflow value by position
Parameters	int: Job Workflow Position string: new value
Example	Geopal.setJobWorkflowValueByPosition(12, 'new value');
Returns	None

setJobWorkflowActionValueByTemplateId

Description	Sets a job workflow value by template id
Parameters	int: Job Workflow Template Id string: new value
Example	Geopal.setJobWorkflowValueByTemplateId(999, 'new value');
Returns	None

setJobWorkflowsActive

Description	Sets a job workflow value to be active
Parameters	boolean: isActive
Example	Geopal.setJobWorkflowsActive(true);
Returns	None

setJobWorkflowsActiveByPosition

Description	Sets a job workflow value to be active by position
--------------------	--

Parameters	int: Job Workflow Position boolean: isActive
Example	Geopal.setJobWorkflowsActiveByPosition(12,true);
Returns	None

setJobWorkflowsActiveByTemplateId

Description	Sets a job workflow value to be active by template id
Parameters	int: Job Workflow Template Id boolean: isActive
Example	Geopal.setJobWorkflowsActiveByTemplateId(999, true);
Returns	None

setJobWorkflowsMandatoryByName

Description	Sets a job workflow value to be mandatory by name
Parameters	int: Job Workflow Name boolean: isMandatory
Example	Geopal.setJobWorkflowsMandatoryByName('Pick From a List', true);
Returns	None

setJobWorkflowsMandatory

Description	Sets a job workflow value to be mandatory
Parameters	boolean: isMandatory
Example	Geopal.setJobWorkflowsMandatory(true);
Returns	None

setJobWorkflowsMandatoryByPosition

Description	Sets a job workflow value to be mandatory by position
Parameters	int: Job Workflow Position boolean: isMandatory
Example	Geopal.setJobWorkflowsMandatoryByPosition(12,true);
Returns	None

setJobWorkflowsMandatoryByTemplateId

Description	Sets a job workflow value to be mandatory by template id
Parameters	int: Job Workflow Template Id boolean: isMandatory
Example	Geopal.setJobWorkflowsMandatoryByTemplateId(999, true);
Returns	None

setJobWorkflowsMandatoryByName

Description	Sets a job workflow value to be mandatory by name
Parameters	string: Job Workflow Name boolean: isMandatory
Example	Geopal.setJobWorkflowsMandatoryByName('Pick From a List', true);
Returns	None

setWorkflowFileByName

Description	Sets a job workflow file by name
Available	1.7.x
Parameters	String: name of workflow String: file path
Example	Geopal.setWorkflowFileByName('Signature PDF Signed', filepath);
Returns	None

setWorkflowFileByTemplateId

Description	Sets a job workflow file by template id
Available	1.7.x
Parameters	int: template id of workflow String: file path
Example	Geopal.setWorkflowFileByTemplateId(512, filepath);
Returns	None

setWorkflowFileByPosition

Description	Sets a job workflow file by template id
Available	1.7.x
Parameters	int: position of workflow String: file path
Example	Geopal.setWorkflowFileByPosition(2, filepath);
Returns	None

forceCheckOut

Description	Checks out of current job
Available	1.7.x
Example	Geopal.forceCheckOut();
Returns	None

6. Scriptable Steps Api Create Job

createSimpleJob

Description	Creates a job with current date and time
Available	1.7.x

Parameters	String: callbackSuccess String: callbackFailure int: templateId
Example	GeopalJobCreate.createSimpleJob('success','failed',templateId);
Returns	None

createAdvancedJob

Description	Creates a job with options
Available	1.7.x
Parameters	String: callbackSuccess String: callbackFailure String: date ->can be null String: time ->can be null String: jobIdIdentifier ->can be null int: templateId int: addressId ->can be null int: customerId ->can be null int: personId ->can be null String: assetIdentifier ->can be null
Example	<pre> var templateId = GeopalTemplate.getJobTemplateIdByName('1 Geopal Test'); var currentDate = new Date(1388844300000); var date = currentDate.getFullYear()+'-'+(currentDate.getMonth() +1)+'-'+currentDate.getDate(); var time = currentDate.getHours()+'-'+currentDate.getMinutes(); var jobIdIdentifier ='tara is testing'; var address = 1478; var customer = 9987; var person = 394; var asset = 'Test201310228'; GeopalJobCreate.createAdvancedJob('success','failed', null, null, jobIdIdentifier, templateId, address, customer, person, asset); </pre>

Returns	None
----------------	------

createAdvancedJobWithFields

Description	Creates a job with options
Available	1.7.x
Parameters	String: callbackSuccess String: callbackFailure String: date ->can be null String: time ->can be null String: jobIdIdentifier ->can be null int: templateId int: addressId ->can be null int: customerId ->can be null int: personId ->can be null String: assetIdentifier ->can be null String: jobWorkflows ->can be null String: jobFields ->can be null
Example	<pre> var templateId = GeopalTemplate.getJobTemplateIdByName('1 Geopal Test'); var currentDate = new Date(1388844300000); var date = currentDate.getFullYear()+'-'+(currentDate.getMonth() +1)+'-'+currentDate.getDate(); var time = currentDate.getHours()+'-'+currentDate.getMinutes(); var jobIdIdentifier ='tara is testing'; var address = 1478; var customer = 9987; var person = 394; var asset = 'Test201310228'; var workflows = '{"List Select 1":"test 1","List Select 2":"test 2","List Select 3":"test 3"}'; var fields = '{"testField1":"test field 1","testField2":"test field 2"}'; GeopalJobCreate.createAdvancedJobWithFields('success','failed', null, null, jobIdIdentifier, templateId, address, customer, person, asset, workflows, fields); </pre>

Returns	None

7. Scriptable Steps Api Assets

getAssetIdentifier

Description	Gets the current job asset identifier. Returns empty String if none found
Parameters	None
Returns	String

getAssetName

Description	Gets the current job asset name. Returns empty String if none found
Parameters	None
Returns	String

getBoundAssetFieldValueByAssetCompanyId

Description	Gets the current job asset field value by asset company field id. Returns empty String if none found
Parameters	int: Asset Company Field Id
Example	Geopal.getBoundAssetFieldValueByAssetCompanyId(222);
Returns	String

getBoundAssetFieldValueByAssetCompanyName

Description	Gets the current job asset field value by asset company field name. Returns empty String if none found
--------------------	--

Parameters	string: Asset Company Field name
Example	Geopal.getBoundAssetFieldValueByAssetCompanyName('take photo of asset');
Returns	String

updateAssetStatus

Description	Updates the asset status id.
Parameters	String: identifier int assetStatusId
Example	GeopalAsset.updateAssetStatus('test asset', 12);
Returns	String

8. Scriptable Steps Api PDF

addSignaturetoPdfField

Description	Adds signature image to pdf acro field by acro field name
Available	1.7.x
Parameters	String: callBackSuccess String: callBackFailed String: PDFFilepath String: signatureFilepath String: fieldName int: pageNumber
Example	GeopalPDF.addSignaturetoPdfField('success','failed', pdfFilePath , filepath,'signature', 1)
Returns	None

addSignaturetoPdfSignatureField

Description	Adds signature image to pdf acro field by acro field of type Signature
Available	1.7.x
Parameters	String: callBackSuccess

	String: callBackFailed String: PDFFilepath String: signatureFilepath int: pageNumber
Example	GeopalPDF.addSignaturetoPdfSignatureField('success','failed', pdfFilePath , filepath,1)
Returns	None

addSignaturetoPdfAtPositionByCoordinates

Description	Adds signature image to pdf at coordinates. Page number defaults to 1
Available	1.7.x
Parameters	String: callBackSuccess String: callBackFailed String: PDFFilepath String: signatureFilepath float: llx -> lower left x position float: lly -> lower left y position float: urx -> upper right x position float: ury -> upper right y position
Example	GeopalPDF.addSignaturetoPdfAtPositionByCoordinates('success','failed', pdfFilePath , filepath ,400, 22, 578, 120);
Returns	None
Note	Pdf coordinates 0,0 start from lower left hand corner unlike Androids upper left hand 0,0 coordinates

addSignaturetoPdfAtPositionByCoordinates

Description	Adds signature image to pdf at coordinates. Page number defaults to 1
Available	1.7.x
Parameters	String: callBackSuccess String: callBackFailed String: PDFFilepath String: signatureFilepath float: llx -> lower left x position float: lly -> lower left y position float: urx -> upper right x position float: ury -> upper right y position

	int: page number
Example	GeopalPDF.addSignaturetoPdfAtPositionByCoordinates('success','failed', pdfFilePath , filepath ,400, 22, 578, 120,2);
Returns	None
Note	Pdf coordinates 0,0 start from lower left hand corner unlike Androids upper left hand 0,0 coordinates

addSignaturetoPdfAtPositionRighthandCorner

Description	Adds signature image to pdf at coordinates. Page number defaults to 1
Available	1.7.x
Parameters	String: callBackSuccess String: callBackFailed String: PDFFilePath String: signatureFilePath
Example	GeopalPDF.addSignaturetoPdfAtPositionRighthandCorner('success','failed', pdfFilePath , filepath);
Returns	None
Note	Pdf coordinates 0,0 start from lower left hand corner unlike Androids upper left hand 0,0 coordinates. Rectangle position hardcoded to (400, 22, 578, 120)

addSignaturetoPdfAtPositionRighthandCorner

Description	Adds signature image to pdf at coordinates. Page number defaults to 1
Available	1.7.x
Parameters	String: callBackSuccess String: callBackFailed String: PDFFilePath String: signatureFilePath int: page number
Example	GeopalPDF.addSignaturetoPdfAtPositionRighthandCorner('success','failed', pdfFilePath , filepath,2);
Returns	None

Note	Pdf coordinates 0,0 start from lower left hand corner unlike Androids upper left hand 0,0 coordinates. Rectangle position hardcoded to (400, 22, 578, 120)
-------------	--

openPDFApplication

Description	Lanches Pdf Application
Available	1.7.x
Parameters	String: callBackFailed String: filepath
Example	<pre>var failed = function(failedMsg) { Geopal.showMessage(failedMsg); }; var openPDF = function() { GeopalPDF.openPDFApplication('failed',signaturePDFURL); };</pre>
Returns	None

9. Scriptable Steps Api Other

showMessage

Description	Shows a notification message
Parameters	string: message
Example	Geopal.showMessage('hi');
Returns	None

showSingleChoiceList

Description	Shows a single choice list
Available	1.4.x
Parameters	string: callBackEnter

	string: callBackCancel string: commaSepString string: title
Example	<pre> var success = function(item) { Geopal.showMessage(item + " was picked!"); } var cancel = function() { Geopal.showMessage('nothing was picked'); } Geopal.showSingleChoiceList('success', 'cancel', '1,2,3, 'Pick a number','message'); </pre>
Returns	None

showMultiChoiceList

Description	Shows a multiple choice list
Available	1.6.126
Parameters	string: callBackEnter string: callBackCancel string: commaSepString string: title
Example	<pre> var success = function(items) { for(var i = 0;i<items.length;i++){ Geopal.showMessage(items[i] + " was picked!"); } } var cancel = function() { Geopal.showMessage('nothing was picked'); } Geopal.showMultiChoiceList('success', 'cancel', '1,2,3, 'Pick some numbers'); </pre>
Returns	None

showYesNoDialog

Description	Shows a yes/no dialog
Available	1.5.x

Parameters	string: callBackYes string: callBackNo string: title string: message string: yesText string: noText
Example	<pre> var yes = function() { Geopal.showMessage('yes selected'); }; var no = function() { Geopal.showMessage('no selected'); }; Geopal.showYesNoDialog('yes', 'no', 'Yes No Selector', 'Please pick yes or no', 'yes text', 'no text'); </pre>
Returns	None

showYesNoMaybeDialog

Description	Shows a yes/no/maybe dialog
Available	1.5.x
Parameters	string: callBackYes string: callBackNo string: callBackMaybe string: title string: message string: yesText string: noText string: maybeText
Example	<pre> var yes = function() { Geopal.showMessage('yes selected'); } var no = function() { Geopal.showMessage('no selected'); } var maybe = function() { Geopal.showMessage('maybe selected'); } </pre>

	Geopal.showYesNoMaybeDialog('yes', 'no', 'maybe', 'Title', 'Call me maybe?', 'yes text', 'no text', 'maybe text');
Returns	None

showEnterText

Description	Shows a enter text dialog
Available	1.5.x
Parameters	string: callBackEnter string: callBackCancel string: defaultText string: title string: message
Example	<pre>var enter = function(item) { Geopal.showMessage('text entered'+item); }; var cancel = function() { Geopal.showMessage('cancelled'); }; Geopal.showEnterText('enter', 'cancel', 'default text', 'Please enter something', 'your message');</pre>
Returns	None

showEnterNote

Description	Shows a enter note dialog
Available	1.5.x
Parameters	string: callBackEnter string: callBackCancel string: defaultText string: title string: message
Example	<pre>var enter = function(item) { Geopal.showMessage('note entered'+item); };</pre>

	<pre>var cancel = function() { Geopal.showMessage('cancelled'); }; Geopal.showEnterNote('enter', 'cancel', 'default text', 'Please enter something', 'your message');</pre>
Returns	None

startPhoneDialer

Description	Shows phone number in Phone Dialer. This also ends the execution of the javascript because this starts a new activity.
Available	1.6.205
Parameters	string: callbackFailed string: phoneNumber
Example	<pre>var failed = function() { Geopal.showMessage('start phone dialer failed'); }; Geopal.startPhoneDialer('failed', '01234678');</pre>
Returns	None

showSignatureDialog

Description	Shows dialog box for signature input
Available	1.7.x
Parameters	string: callBackOK string: callBackCancel string: title string: disclaimer
Example	<pre>var ok = function(filepath) { Geopal.showMessage(filepath); }; var cancel = function() { }; Geopal.showSignatureDialog('ok','cancel','sign this','this is a disclaimer');</pre>
Returns	None

Note	White background becomes transparent.
-------------	---------------------------------------

showProgressDialog

Description	Shows progress dialog. Message defaults to “processing.....”
Available	1.7.x
Example	Geopal.showProgressDialog();
Returns	None
Note	If dialog is already showing it will close the dialog

showProgressDialog

Description	Shows progress dialog with optional message
Available	1.7.x
Parameters	String: message
Example	Geopal.showProgressDialog('Loading....');
Returns	None
Note	If dialog is already showing it will close the dialog

hideProgressDialog

Description	Hides current progress dialog.
Available	1.7.x
Example	Geopal.hideProgressDialog();
Returns	None

httpSender

Description	Retrys sending http parameters if offline
Deprecated	This method is deprecated and will not work in future versions please do not use
Available	1.7.x

Parameters	String: url String: post_params
Example	Geopal.httpSender('http://geopal-solutions.com','username=12345&password=12345')
Returns	Boolean

scanBarcode

Description	Lanches external application to scan barcode. If no app is found shows message
Available	1.10.x
Parameters	String callbackSuccess; String callbackFailure;
Example	<pre>var success = function(item) { Geopal.showMessage('barcode: '+item); }; var fail = function() { Geopal.showMessage(failed); }; GeopalBarcode.scanBarcode('success','fail');</pre>
Returns	String

10. Examples

Hello World

```
Geopal.showMessage('Hello ' + Geopal.getJobEmployeeFullName());
```

Calculation

Simple calculation

```
Geoapl.setJobWorkflowValue(10 * 10);
```

or

Multiply an entered number by 10

```
Geoapl.setJobWorkflowValue(10 * Geoapl.getJobWorkflowValueByName('Enter Number'));
```

or

Add two entered numbers together

```
var number1 = Geoapl.getJobWorkflowValueByName('Enter Number1');
var number2 = Geoapl.getJobWorkflowValueByName('Enter Number2');
Geoapl.setJobWorkflowValue(number1 + number2);
```

Conditional Logic

If a number is greater than 10 then initiate a failed action, otherwise initiate success action

```
var number = Geoapl.getJobWorkflowValueByName('Enter Number1');
if (number > 10) {
    Geoapl.setJobWorkflowValue('Failed');
    Geopal.gotoJobWorkflowValueByName('Failed Step');
} else {
    Geoapl.setJobWorkflowValue('Passed');
    Geopal.gotoJobWorkflowValueByName('Passed Step');
}
```

Scoring

Scoring formula:

item1 = 1 point

item2 = 5 points

item3 = 10 points

The list steps have been set to: item1,item2,item3

```
function value2score(value) {
    switch(value) {
        case 'item1':
            return 1;
            break;
        case 'item2':
            return 5;
            break;
        case 'item3':
            return 10;
            break;
        default:
            return 0;
    }
}
```

```
var list1 = Geopal.getJobWorkflowValueByName('List Select 1');
var list2 = Geopal.getJobWorkflowValueByName('List Select 2');
```

```
var list3 = Geopal.getJobWorkflowValueByName('List Select 3');
```

```
var score1 = value2score(list1);
```

```
var score2 = value2score(list2);
```

```
var score3 = value2score(list3);
```

```
var score = score1 + score2 + score3;
```

```
Geopal.setJobWorkflowValue(score);
```

PDF Signature Capture

```
var pdfFilePath;
```

```
var signaturePDFURL;
```

```
var openPDF = function() {  
    if (typeof signaturePDFURL=="string" ) {  
        GeopalPDF.openPDFApplication('failed',signaturePDFURL);  
    } else if(Geopal.getJobWorkflowValue()=='Signature Taken'){  
        var workflowFilepath = Geopal.getWorkflowFilePathByName('Signature PDF Signed');  
        GeopalPDF.openPDFApplication('failed',workflowFilepath);  
    } else {  
        Geopal.showMessage('pdf not found');  
    }  
};
```

```
var no = function() {
```

```
};
```

```
var successFileFound = function(filepath) {  
    pdfFilePath = filepath;  
    Geopal.showSignatureDialog('ok','cancel','sign this','this is a disclaimer');  
};
```

```
var failedFileNotFound = function(error) {  
    Geopal.showMessage(error);  
};
```

```
var failed = function(failedMsg) {  
    Geopal.hideProgressDialog();  
    Geopal.showMessage(failedMsg);  
};
```



```

var success = function(url) {
    Geopal.hideProgressDialog();
    signaturePDFURL = url;
    Geopal.setWorkflowFileByName('Signature PDF Signed', url);
    Geopal.setJobWorkflowValue('Signature Taken');
    Geopal.showYesNoDialog('openPDF', 'no', 'Pdf Created', 'Signed PDF has been created
would you like to view it','Show PDF', 'Cancel');
};

var ok = function(filepath) {
    if (typeof pdfFilePath=="string" ) {
        Geopal.showProgressDialog();
        GeopalPDF.addSignaturetoPdfAtPositionRighthandCorner('success','failed',
pdfFilePath , filepath);
    } else {
        Geopal.showMessage('pdf not found');
    }
};

var cancel = function() {

};

var overwrite = function() {
    Geopal.downloadJobfieldFileByName('successFileFound','failedFileNotFound','Customer
Docket');
};

if(Geopal.getJobWorkflowValue()=== 'Signature Taken'){
    Geopal.showYesNoDialog('overwrite', 'openPDF', 'Pdf has already been signed', 'Would
you like to overwrite it?','Overwrite PDF', 'View PDF');
} else {
    Geopal.downloadJobfieldFileByName('successFileFound','failedFileNotFound','Customer
Docket');
}

```