



GeoPal
Mobile Workforce Management

API Documentation

ver 1.13



Table of Contents

| | |
|--|----|
| Change Log..... | 4 |
| Contact Details..... | 5 |
| Sales Email..... | 5 |
| Support Email..... | 5 |
| Web..... | 5 |
| Introduction..... | 5 |
| Syntax..... | 5 |
| Sections..... | 5 |
| General API Description..... | 6 |
| Common Request Parameters..... | 6 |
| Signature..... | 6 |
| Verb..... | 6 |
| URI..... | 6 |
| Timestamp..... | 6 |
| API Key..... | 6 |
| Operation..... | 6 |
| Pull API..... | 7 |
| Jobs API..... | 8 |
| Creating a Job..... | 8 |
| Getting Job Details..... | 13 |
| Changing Job Status..... | 16 |
| Assigning A Job..... | 20 |
| Reassigning A Job..... | 21 |
| Reading a Job Template..... | 24 |
| Getting Jobs by a Specific Date Range..... | 26 |
| Employee API..... | 27 |
| Listing Employees and Getting Employee Locations and Statuses..... | 27 |
| Create an Employee..... | 29 |
| Update an Employee..... | 31 |
| Update an Employee By Identifier..... | 33 |
| Listing Employee Shifts..... | 35 |
| Listing Employee Status Logs..... | 37 |
| Get Route Replay of an Employee..... | 39 |
| Get Route Replay of Employee By Identifier..... | 41 |
| Asset Management API..... | 43 |
| Getting a list of Assets..... | 43 |
| Getting an Asset by Id..... | 45 |
| Getting an Asset by Identifier..... | 47 |
| Updating and Creating an Asset..... | 48 |
| Updating an Asset Field..... | 50 |
| Uploading a file to an Asset Field..... | 52 |
| Updating an Asset Trigger..... | 54 |
| Files API..... | 56 |
| Getting a File..... | 56 |
| Sending Job Fields..... | 58 |
| Getting Job Field Ids..... | 58 |
| Sending Job Fields In Create A Job..... | 58 |

Visual Basic Reference.....59

Java Reference.....60

PHP Reference.....61

Python Reference.....62

C# .Net Reference.....63

Change Log

| Date | Version | Changes Made | Changes By |
|----------|---------|--|--|
| 20/05/13 | 1 | Initial version | Sean O'Reilly, Lukasz Jajesnica, Gabor Zelei |
| 08/07/13 | 1.1 | New API functionality for Employees and Jobs | Gabor Zelei |
| 17/09/13 | 1.2 | New API's for reassigning Jobs, updating Job Statuses and listing Shifts | Gabor Zelei |
| 25/09/13 | 1.3 | Extended Job creation API, added new API for retrieving S3 files | Gabor Zelei |
| 25/09/13 | 1.4 | Updating code examples section. | Lukasz Jajesnica |
| 25/09/13 | 1.5 | Put params in the correct case | Sean O'Reilly |
| 26/09/13 | 1.6 | Added in version number 1.6 added in Job Fields section, updated php section | Sean O'Reilly |
| 30/09/13 | 1.7 | Updates to titles and s3file details, formatting | Sean O'Reilly |
| 15/10/13 | 1.8 | Added pages for employee status logs API | Gabor Zelei |
| 16/10/13 | 1.9 | Minor fixes to list of parameters for employee/create and employee/update | Gabor Zelei |
| 30/10/13 | 1.10 | Minor fixes to URLs | Gabor Zelei |
| 08/11/13 | 1.11 | Added section for assigning jobs | Gabor Zelei |
| 08/11/13 | 1.12 | Added just create api for jobs | Sean O'Reilly |
| 12/11/13 | 1.13 | Added asset management api's + minor changes to document structure | Gabor Zelei |

Contact Details

Sales Email

sales@geopal-solutions.com

Support Email

support@geopal-solutions.com

Web

<http://www.geopalsolutions.com/>

Introduction

GeoPal API provides you with the powerful ability to send and receive data from our system. Currently it supports two types of requests: Pull and Push. In this document you will find a general description of the API, along with code samples for the following programming languages:

- C#
- Java
- PHP
- Python
- Visual Basic .NET

Syntax

The markdown syntax used in this document is as follows:

Important information

API Method Name

A **mandatory field_name** in the request you send or receive

An `optional field_name` in the request you send or receive

Sections

This document has been organized into two main sections:

- **General API Description:** This section contains all the information about the GeoPal API in a language independent fashion. This includes the descriptions of the URLs and common request parameters used. Generic GET and PUT style calls will also be also discussed in this section.
- **API Examples:** This sections contains commented API examples in all supported programming languages.

General API Description

Common Request Parameters

When making calls to GeoPal's API, you will typically need to specify the following parameters in your call: Signature, Verb, URI, Timestamp, API key and Operation. A description of these parameters can be found below.

Signature

The Signature is a specially constructed token, converted to the lowercase and then signed with SHA256. Once constructed, it must be encoded with BASE64. You can find more information about the building block parameters of the token below.

PseudoCode:

```
VAR Signature = BASE64(  
    SHA256(  
        LOWER_CASE(  
            <VERB>+<URI>+<EMPLOYEEID>+<TIMESTAMP>  
        )  
    )  
);
```

Verb

A Verb is a specific type of request. The GeoPal API currently accepts "GET" and "PUT" values for a Verb, depending on the actual method you want to call. You can find more information about the Verb you have to use for each method in their API description tables, later in this chapter.

URI

The URI parameter is the target URL you want to send your request to. Again, you can find the actual value to set for the URI parameter in the API method description tables.

Timestamp

The current timestamp. Please refer to the [RFC 2822](#), in case you need more information.

*GeoPal expects the timestamp to be provided in the following format:
Thu, 25 Oct 2012 13:06:50 +0100*

API Key

The API key is a randomly generated 128-byte string, assigned to your company by Geopal and used for the authentication of incoming API calls.

Operation

This parameter specifies the operation type, and is only used in Push requests. Valid values for this parameter are: `job`, `job_workflow`, `job_workflow_file` or `job_field`.

Pull API

The Pull API functions allow you to retrieve data from or submit data to GeoPal by calling a URL via HTTPS, with the correct parameters and headers.

Some calls allow you to access data identified by either an "ID" or an "Identifier".

Here, the ID represents the way GeoPal identifies the resource internally. This is always a read-only integer value.

The Identifier, on the other hand, is a string of numbers and/or characters, and can freely be assigned and changed by the user. This may be identical to the primary key in your system.

Jobs API

Creating a Job

Allows creating a job in GeoPal

| Parameters | Method specific value |
|------------|--|
| URI | api/jobs/create |
| URI | api/jobs/createandassign creates and assigns the job |
| Verb | POST |
| Data Type | JSON |

| Headers | Method specific value |
|---------------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameter | Description |
|---------------------------|---|
| <u>template_id</u> | The ID of the job template to create the job from |
| job_identifier | A unique identifier for the job |
| person_id | The ID of the contact person for the job |
| person_identifier | The identifier of the contact person for the job |
| person_title | The title of the contact person for the job |
| person_first_name | The first name of the contact person for the job |
| person_last_name | The last name of the contact person for the job |
| person_phone_number | The phone number of the contact person for the job |
| person_fax_number | The fax number of the contact person for the job |
| person_mobile_number | The mobile phone number of the contact person for the job |
| person_email | The e-mail address of the contact person for the job |
| person_address_line_1 | Address (line 1) of the contact person for the job |
| person_address_line_2 | Address (line 2) of the contact person for the job |
| person_address_line_3 | Address (line 3) of the contact person for the job |
| person_city | Address (city) of the contact person for the job |
| person_postal_code | Address (postal code) of the contact person for the job |
| address_id | ID of the address where the job should be done at |
| address_identifier | Identifier of the address where the job should be done at |
| address_line_1 | The address (line 1) where the job should be done at |

| Get Parameter | Description |
|--------------------------|---|
| address_line_2 | The address (line 2) where the job should be done at |
| address_line_3 | The address (line 3) where the job should be done at |
| city | The address (city) where the job should be done at |
| postal_code | The address (postal code) where the job should be done at |
| country_id | The address (country ID) where the job should be done at |
| customer_id | The ID of the customer to do the job for |
| customer_identifier | The identifier of the customer to do the job for |
| customer_name | The name of the customer to do the job for |
| customer_phone_number | The phone number of the customer to do the job for |
| customer_fax_number | The fax number of the customer to do the job for |
| customer_web_site | The web site address of the customer to do the job for |
| customer_mobile_number | The mobile number of the customer to do the job for |
| customer_email | The e-mail address of the customer to do the job for |
| customer_address_line_1 | The address (line 1) of the customer to do the job for |
| customer_address_line_2 | The address (line 2) of the customer to do the job for |
| customer_address_line_3 | The address (line 3) of the customer to do the job for |
| customer_city | The address (city) of the customer to do the job for |
| customer_postal_code | The address (postal code) of the customer to do the job for |
| estimated_duration | The estimated time (HH:MI) the job will take to complete |
| rate_per_hour | The cost of the job per hour |
| prefered_start_date_time | The date and time to start the job at |
| prefered_stop_date_time | The date and time to finish the job by |
| priority_text | The textual representation of the job priority |
| priority_color | <p>The color label for the job.</p> <p>Accepted values are "green", "yellow", "orange", "red", "purple", "white", and "blue".</p> <p>Defaults to "white".</p> |
| job_notes | Submitter's notes for the job |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. |

| Response | Description |
|----------|--|
| | <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | <p>Details of the current company.</p> <pre>{ id: integer, name: string, mobile_main_logo_url: string }</pre> |
| job | <p>An object containing details of the new job.</p> <pre>{ id: integer, identifier: string, priority_text: string, start_date_time: dateTime / string, preferred_start_date_time: dateTime / string, created_on: dateTime / string, updated_on: dateTime / string, duration: integer, priority_color: string, rate_per_hour: integer, preferred_stop_date_time: dateTime / string, job_status_id: integer, schedule_log_id: integer, start_date: dateTime / string, end_time: dateTime / string, first_to_accept: bool, assigned_at: dateTime / string, estimated_duration: integer, ob_assigned_to: string, url: string, notes: string, job_status_change_messages: string, address: { id: integer, identifier: string, is_billing: bool, is_user: bool, is_deleted: bool, created_on: dateTime / string, updated_by: string, updated_on: dateTime / string, city: string, is_primary: bool, company_id: integer, country_id: integer, created_by: string, address_line_1: string, address_line_2: string, address_line_3: string, postal_code: string, lat: float, lng: float }, preferred_start_date_time: dateTime / string, priority_text: string, job_template: { id: integer, name: string, is_deleted: bool, default_rate_per_hour: integer, updated_on: dateTime / string, </pre> |

| Response | Description |
|----------|---|
| | <pre> priority_list: string, created_by: string, created_on: dateTime / string, review_job: bool, company_id: integer, description: string, estimate_job_duration: integer }, created_by: { id: integer, title: string, first_name: string, last_name: string }, employee: { id: integer, title: string, first_name: string, last_name: string }, company: { id: integer, name: string }, job_field_files: [], job_workflow_files: [], customer: { id: integer, company_id: integer, name: string, customer_type_id: integer, created_by: string, created_on: dateTime / string, identifier: string, industry: string, updated_on: dateTime / string, annual_revenue: integer, employees: string, ownership: string, phone_office: string, phone_alternate: string, phone_fax: string, updated_by: string, website: string, email: string, email_alternate: string, notes: string, assigned_user_id: integer, rating: integer }, person: { id: integer, identifier: string, first_name: string, last_name: string, person_type_id: integer, title: string, person_department_id: integer, created_on: dateTime / string, updated_on: dateTime / string, person_job_title_id: integer, company_id: integer, created_by: string, department: string, email: string, is_billing: bool, phone_number: string, updated_by: string, fax_number: string, home_number: string, phone_number_alternate: string, </pre> |

| Response | Description |
|----------|---|
| | <pre> mobile_number: string, email_alterdate: string, is_user: bool, is_deleted: bool, is_primary: bool, notes: string }, assigned_to: { id: integer, title: string, first_name: string, last_name: string } } </pre> |

Getting Job Details

Returns a list with all existing job templates.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/jobs/get |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameter | Description |
|---------------|--------------------------|
| <u>job_id</u> | The ID of the target job |

| Response | Description |
|----------|---|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| job | An object containing the job details. <pre>{ id: integer, identifier: string, priority_text: string, start_date_time: dateTime / string, preferred_start_date_time: dateTime / string, created_on: dateTime / string, updated_on: dateTime / string duration: integer, priority_color: string, rate_per_hour: integer, }</pre> |

| Response | Description |
|----------|---|
| | <pre> preferred_stop_date_time: dateTime / string, job_status_id: integer, schedule_log_id: integer, start_date: dateTime / string, end_time: dateTime / string, first_to_accept: bool, assigned_at: dateTime / string, estimated_duration: integer, ob_assigned_to: string, url: string, notes: string, job_status_change_messages: string, address: { id: integer, identifier: string, is_billing: bool, is_user: bool, is_deleted: bool, created_on: dateTime / string, updated_by: string, updated_on: dateTime / string, city: string, is_primary: bool, company_id: integer, country_id: integer, created_by: string, address_line_1: string, address_line_2: string, address_line_3: string, postal_code: string, lat: float, lng: float }, preferred_start_date_time: dateTime / string, priority_text: string, job_template: { id: integer, name: string, is_deleted: bool, default_rate_per_hour: integer, updated_on: dateTime / string, priority_list: string, created_by: string, created_on: dateTime / string, review_job: bool, company_id: integer, description: string, estimate_job_duration: integer }, created_by: { id: integer, title: string, first_name: string, last_name: string }, employee: { id: integer, title: string, first_name: string, last_name: string }, company: { id: integer, name: string }, job_field_files: [], job_workflow_files: [], customer: { id: integer, company_id: integer, name: string, </pre> |

| Response | Description |
|----------|---|
| | <pre> customer_type_id: integer, created_by: string, created_on: dateTime / string, identifier: string, industry: string, updated_on: dateTime / string, annual_revenue: integer, employees: string, ownership: string, phone_office: string, phone_alterate: string, phone_fax: string, updated_by: string, website: string, email: string, email_alterate: string, notes: string, assigned_user_id: integer, rating: integer }, person: { id: integer, identifier: string, first_name: string, last_name: string, person_type_id: integer, title: string, person_department_id: integer, created_on: dateTime / string, updated_on: dateTime / string, person_job_title_id: integer, company_id: integer, created_by: string, department: string, email: string, is_billing: bool, phone_number: string, updated_by: string, fax_number: string, home_number: string, phone_number_alterate: string, mobile_number: string, email_alterate: string, is_user: bool, is_deleted: bool, is_primary: bool, notes: string }, assigned_to: { id: integer, title: string, first_name: string, last_name: string } } </pre> |

Changing Job Status

Allows for changing the current status of a job.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/jobs/status |
| Verb | POST |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameters | Description |
|----------------------|--|
| <u>job_id</u> | The ID of the target job |
| <u>job_status_id</u> | <p>The ID of the job status to set the job to.</p> <p>Valid values are:</p> <ul style="list-style-type: none">- 1 for "Accepted"- 2 for "Rejected"- 3 for "Completed"- 5 for "In Progress"- 7 for "Incomplete" <p>Note: Values not listed above will cause the request to fail.</p> |
| <u>updated_on</u> | A Unix Timestamp to mark the time of the update |
| message | An optional message to include in the job notes |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | <p>A JSON array with the account details of the requestor user who made the call.</p> <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. |

| Response | Description |
|----------|---|
| | <pre>{ id: integer, name: string }</pre> |
| job | <p>An object containing the job details.</p> <pre>{ id: integer, identifier: string, priority_text: string, start_date_time: dateTime / string, preferred_start_date_time: dateTime / string, created_on: dateTime / string, updated_on: dateTime / string, duration: integer, priority_color: string, rate_per_hour: integer, preferred_stop_date_time: dateTime / string, job_status_id: integer, schedule_log_id: integer, start_date: dateTime / string, end_time: dateTime / string, first_to_accept: bool, assigned_at: dateTime / string, estimated_duration: integer, ob_assigned_to: string, url: string, notes: string, job_status_change_messages: string, address: { id: integer, identifier: string, is_billing: bool, is_user: bool, is_deleted: bool, created_on: dateTime / string, updated_by: string, updated_on: dateTime / string, city: string, is_primary: bool, company_id: integer, country_id: integer, created_by: string, address_line_1: string, address_line_2: string, address_line_3: string, postal_code: string, lat: float, lng: float }, preferred_start_date_time: dateTime / string, priority_text: string, job_template: { id: integer, name: string, is_deleted: bool, default_rate_per_hour: integer, updated_on: dateTime / string, priority_list: string, created_by: string, created_on: dateTime / string, review_job: bool, company_id: integer, description: string, estimate_job_duration: integer }, created_by: { id: integer,</pre> |

| Response | Description |
|----------|---|
| | <pre> title: string, first_name: string, last_name: string }, employee: { id: integer, title: string, first_name: string, last_name: string }, company: { id: integer, name: string }, job_field_files: [], job_workflow_files: [], customer: { id: integer, company_id: integer, name: string, customer_type_id: integer, created_by: string, created_on: dateTime / string, identifier: string, industry: string, updated_on: dateTime / string, annual_revenue: integer, employees: string, ownership: string, phone_office: string, phone_alterdate: string, phone_fax: string, updated_by: string, website: string, email: string, email_alterdate: string, notes: string, assigned_user_id: integer, rating: integer }, person: { id: integer, identifier: string, first_name: string, last_name: string, person_type_id: integer, title: string, person_department_id: integer, created_on: dateTime / string, updated_on: dateTime / string, person_job_title_id: integer, company_id: integer, created_by: string, department: string, email: string, is_billing: bool, phone_number: string, updated_by: string, fax_number: string, home_number: string, phone_number_alterdate: string, mobile_number: string, email_alterdate: string, is_user: bool, is_deleted: bool, is_primary: bool, notes: string }, assigned_to: { id: integer, title: string, </pre> |

| Response | Description |
|----------|---|
| | <pre> first_name: string, last_name: string } }</pre> |

Assigning A Job

Allows for assigning a job to an employee.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/jobs/assign |
| Verb | POST |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameter | Description |
|------------------------|---|
| <u>job_id</u> | The ID of the target job |
| <u>employee_id</u> | The ID of the employee to assign the job to |
| <u>start_date_time</u> | Start date and time for the job (YYYY-MM-DD HH:MI:SS) |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| job | An object containing the job details. (Output is the same as described for "Creating a Job") |

Reassigning A Job

Allows for reassigning a job to another employee.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/jobs/reassign |
| Verb | POST |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| GEOPAL-SIGNATURE | [reference] |
| GEOPAL-TIMESTAMP | [reference] |
| GEOPAL-EMPLOYEEID | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameter | Description |
|----------------------------------|---|
| <u>job_id</u> | The ID of the target job |
| <u>employee_reassigned_to_id</u> | The ID of the employee to assign the job to |
| <u>start_date_time</u> | Start date and time for the job (YYYY-MM-DD HH:MI:SS) |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| job | An object containing the job details. <pre>{ id: integer, identifier: string, priority_text: string, start_date_time: dateTime / string, preferred_start_date_time: dateTime / string, created_on: dateTime / string, updated_on: dateTime / string }</pre> |

| Response | Description |
|----------|--|
| | <pre> duration: integer, priority_color: string, rate_per_hour: integer, prefered_stop_date_time: dateTime / string, job_status_id: integer, schedule_log_id: integer, start_date: dateTime / string, end_time: dateTime / string, first_to_accept: bool, assigned_at: dateTime / string, estimated_duration: integer, ob_assigned_to: string, url: string, notes: string, job_status_change_messages: string, address: { id: integer, identifier: string, is_billing: bool, is_user: bool, is_deleted: bool, created_on: dateTime / string, updated_by: string, updated_on: dateTime / string, city: string, is_primary: bool, company_id: integer, country_id: integer, created_by: string, address_line_1: string, address_line_2: string, address_line_3: string, postal_code: string, lat: float, lng: float }, prefered_start_date_time: dateTime / string, priority_text: string, job_template: { id: integer, name: string, is_deleted: bool, default_rate_per_hour: integer, updated_on: dateTime / string, priority_list: string, created_by: string, created_on: dateTime / string, review_job: bool, company_id: integer, description: string, estimate_job_duration: integer }, created_by: { id: integer, title: string, first_name: string, last_name: string }, employee: { id: integer, title: string, first_name: string, last_name: string }, company: { id: integer, name: string }, job_field_files: [], job_workflow_files: [], customer: { </pre> |

| Response | Description |
|----------|---|
| | <pre> id: integer, company_id: integer, name: string, customer_type_id: integer, created_by: string, created_on: dateTime / string, identifier: string, industry: string, updated_on: dateTime / string, annual_revenue: integer, employees: string, ownership: string, phone_office: string, phone_alternate: string, phone_fax: string, updated_by: string, website: string, email: string, email_alternate: string, notes: string, assigned_user_id: integer, rating: integer }, person: { id: integer, identifier: string, first_name: string, last_name: string, person_type_id: integer, title: string, person_department_id: integer, created_on: dateTime / string, updated_on: dateTime / string, person_job_title_id: integer, company_id: integer, created_by: string, department: string, email: string, is_billing: bool, phone_number: string, updated_by: string, fax_number: string, home_number: string, phone_number_alternate: string, mobile_number: string, email_alternate: string, is_user: bool, is_deleted: bool, is_primary: bool, notes: string }, assigned_to: { id: integer, title: string, first_name: string, last_name: string } } </pre> |

Reading a Job Template

Returns a Job Template.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/jobtemplate/get |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameter | Description |
|------------------------|-----------------------------------|
| <u>job_template_id</u> | The ID of the target job template |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| template | An object containing the job template details. <pre>{ id: integer, name: string, company_id: integer, description: string, created_on: dateTime / string, created_by: string, updated_on: dateTime / string, updated_by: string, review_job: bool, priority_list: string, }</pre> |

| Response | Description |
|----------|---|
| | <pre> default_rate_per_hour: integer, is_deleted: bool, job_template_runbooks: [], estimate_job_duration: integer, job_template_fields: [{ id: integer, perm_portal: bool, is_deleted: bool, name: string, include_in_reports: bool, perm_mobile: bool, updated_at: dateTime / string, template_id: integer, created_on: dateTime / string, action: string, action_values: string, order_number: integer }], job_template_workflows: [{ id: integer, name: string, template_id: integer, created_on: dateTime / string, action_value_entered: string, is_deleted: bool, order_number: integer, optional: bool, updated_on: dateTime / string, action: string, nested_workflow_id: integer, level_number: integer, updated_at: dateTime / string, include_in_reports: bool }] } </pre> |

Getting Jobs by a Specific Date Range

Returns a detailed list of Jobs created within the target date range.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/jobsearch/ids |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameter | Description |
|-----------------------|-------------------------------------|
| <u>date_time_from</u> | Date and time to list entries from. |
| <u>date_time_to</u> | Date and time to list entries to. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| jobs | An array containing the details for all the job templates. Each object has: <pre>{ id: integer }</pre> |

Employee API

Listing Employees and Getting Employee Locations and Statuses

Returns a detailed list with all employees of the company.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/employees/all |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Response | Description |
|-----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| employees | An array containing the details for all the employees of the current company. Each object has: <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string, mobile_number: string, status: integer [0, 1, 2], lat: float, lng: float, }</pre> |

| Response | Description |
|----------|--|
| | <pre> address: string, last_updated_on: string } </pre> <p>Statuses:</p> <ul style="list-style-type: none"> - 0 for "Ready" - 1 for "Busy" - 2 for "Offline" |

Create an Employee

Creates a new employee entry in the system.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/employee/create |
| Verb | POST |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameters | Description |
|-------------------|---|
| <u>username</u> | A unique username that will allow the employee to log in to GeoPal. |
| <u>password</u> | A password to allow the employee to log in to GeoPal. |
| <u>email</u> | The new employee's e-mail address. |
| <u>first_name</u> | The new employee's first name. |
| <u>last_name</u> | The new employee's last name. |
| mobile_number | The new employee's mobile phone number. |
| identifier | A unique identifier for the new employee. |
| administrator | A boolean value (<code>true/false</code> , <code>1/0</code>) to indicate if a user is an administrator. |
| guest_user | A boolean value (<code>true/false</code> , <code>1/0</code>) to indicate if a user is a guest user. |
| mobile_user | A boolean value (<code>true/false</code> , <code>1/0</code>) to indicate if a user is a mobile app user. |
| portal_user | A boolean value (<code>true/false</code> , <code>1/0</code>) to indicate if a user is a portal user. |
| web_user | A boolean value (<code>true/false</code> , <code>1/0</code>) to indicate if a user is a web user. |
| timezone | The new employee's time zone. It may be provided in either of the following formats: 1.) Area/City – e. g.: Europe/Isle_of_Man (Preferred) 2.) Area/Zone – e.g.: US/Central 3.) Difference from GMT – e. g.: GMT+2 4.) Special formats – e. g.: CET, Zulu, etc. |

| Post Parameters | Description |
|-----------------|--|
| | If not provided, the employer's time zone will be applied. |

Note:

At least one of the user permission parameters (administrator, web_user, etc...) has to be set, otherwise GeoPal will reject new entry with an error.

| Response | Description |
|---------------|---|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| employee_data | An object with data on the newly created user. <pre>{ id: integer, identifier: string, first_name: string, last_name: string, email: string, mobile_number: string, username: string, timezone: string }</pre> |

Update an Employee

Updates data on an existing employee, based on the employee's GeoPal ID.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/employee/update |
| Verb | PUT |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameters | Description |
|-------------------|---|
| <u>id</u> | The target employee's GeoPal ID. |
| <u>username</u> | The employee's unique username for logging in to GeoPal. |
| <u>password</u> | The employee's password for logging in to GeoPal. |
| <u>first_name</u> | The employee's first name. |
| <u>last_name</u> | The employee's last name. |
| <u>email</u> | The employee's e-mail address. |
| identifier | The employee's unique identifier. |
| mobile_number | The employee's mobile phone number. |
| administrator | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is an administrator. |
| guest_user | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is a guest user. |
| mobile_user | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is a mobile app user. |
| portal_user | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is a portal user. |
| web_user | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is a web user. |
| timezone | The employee's time zone. It may be provided in either of the following formats: 1.) Area/City – e. g.: Europe/Isle_of_Man (Preferred) 2.) Area/Zone – e.g.: US/Central 3.) Difference from GMT – e. g.: GMT+2 |

| Post Parameters | Description |
|-----------------|--|
| | 4.) Special formats – e. g.: CET, Zulu, etc. |

Note:

At least one of the user permission parameters (administrator, web_user, etc...) has to be set, otherwise GeoPal will reject updating the entry with an error.

| Response | Description |
|---------------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | <p>A JSON array with the account details of the requestor user who made the call.</p> <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | <p>Details of the current company.</p> <pre>{ id: integer, name: string }</pre> |
| employee_data | <p>An object with updated data on the target user.</p> <pre>{ id: integer, identifier: string, first_name: string, last_name: string, email: string, mobile_number: string, username: string, timezone: string }</pre> |

Update an Employee By Identifier

Updates data on an existing employee, based on the employee's Identifier.

| Parameters | Method specific value |
|------------|---------------------------------|
| URI | api/employee/updatebyidentifier |
| Verb | PUT |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameters | Description |
|-------------------|---|
| <u>identifier</u> | The employee's unique identifier. |
| <u>username</u> | The employee's unique username for logging in to GeoPal. |
| <u>password</u> | The employee's password for logging in to GeoPal. |
| <u>first_name</u> | The employee's first name. |
| <u>last_name</u> | The employee's last name. |
| <u>email</u> | The employee's e-mail address. |
| mobile_number | The employee's mobile phone number. |
| administrator | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is an administrator. |
| guest_user | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is a guest user. |
| mobile_user | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is a mobile app user. |
| portal_user | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is a portal user. |
| web_user | A boolean value (<code>true/false</code> , 1/0) to indicate if a user is a web user. |
| timezone | The employee's time zone. It may be provided in either of the following formats: 1.) Area/City – e. g.: Europe/Isle_of_Man (Preferred) 2.) Area/Zone – e.g.: US/Central 3.) Difference from GMT – e. g.: GMT+2 4.) Special formats – e. g.: CET, Zulu, etc. |

Note:

At least one of the user permission parameters (administrator, web_user, etc...) has to be set, otherwise GeoPal will reject updating the entry with an error.

| Response | Description |
|---------------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | <p>A JSON array with the account details of the requestor user who made the call.</p> <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | <p>Details of the current company.</p> <pre>{ id: integer, name: string }</pre> |
| employee_data | <p>An object with updated data on the target user.</p> <pre>{ id: integer, identifier: string, first_name: string, last_name: string, email: string, mobile_number: string, username: string, timezone: string }</pre> |

Listing Employee Shifts

Returns a list of shifts in the target time frame.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/employees/shifts |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameters | Description |
|-----------------------|---|
| <u>date_time_from</u> | Shifts starting at or after this point will be listed. (YYYY-MM-DD HH:MI:SS) |
| <u>date_time_to</u> | Shifts ending at or before this point will be listed. (YYYY-MM-DD HH:MI:SS) |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| shifts | An array containing the details for all the shifts matching provided criteria. Each object has: <pre>{ employee_id: integer,</pre> |

| Response | Description |
|----------|--|
| | <pre> employee_name: string, start_address: string, start_on: dateTime / String, stop_address: string, stop_on: dateTime / String, duration: string } </pre> |

Listing Employee Status Logs

Returns a list of status log entries in the target time frame.

| Parameters | Method specific value |
|------------|---------------------------|
| URI | api/employees/status_logs |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameters | Description |
|-----------------------|---|
| <u>date_time_from</u> | Shifts starting at or after this point will be listed. (YYYY-MM-DD HH:MI:SS) |
| <u>date_time_to</u> | Shifts ending at or before this point will be listed. (YYYY-MM-DD HH:MI:SS) |
| employee_identifier | If provided, only results for this employee will be shown. |
| employee_id | If provided, only results for this employee will be shown. Note: GeoPal will check for an <code>employee_identifier</code> first; if both values are valid, the <code>employee_identifier</code> takes precedence. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |

| Response | Description |
|-------------|--|
| status_logs | <p>An array containing the details for all the employee status logs matching provided criteria.</p> <p>Each object has:</p> <pre> { id: integer, employee_id: integer, company_id: integer, status: integer, status_update_from: integer, ip_address: string, user_agent: string, updated_on: dateTime / string }</pre> <p>Status values and the source of status update are represented as integers:</p> <p>status field:</p> <ul style="list-style-type: none"> - 0 for "Ready" - 1 for "Busy" - 2 for "Offline" <p>status_update_from field:</p> <ul style="list-style-type: none"> - 0 for "system" (e.g.: expired session) - 1 for "employee" |

Get Route Replay of an Employee

Get route data within a given time period, by an employee's GeoPal ID.

| Parameters | Method specific value |
|------------|--------------------------|
| URI | api/employee/routereplay |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameters | Description |
|-----------------------|---|
| <u>employee_id</u> | The employee's GeoPal ID. |
| <u>date_time_from</u> | The date and time to list the entries from. |
| <u>date_time_to</u> | The date and time to list the entries to. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| tracks | An array of objects with information on the individual points recorded on the user's route, in the target time period. Each object has: <pre>{ employee_name: integer, address: string, lat: float, lng: float, speed: integer, }</pre> |

| Response | Description |
|----------|---|
| | <pre> heading_txt: string, signal_strength_txt: string, battery_level_percentage: integer, accuracy: integer, accuracy_type: string, tag: string, distance_travelled: integer, created_on: dateTime / String } </pre> |

Get Route Replay of Employee By Identifier

Get route data within a given time period, by an employee's Identifier.

| Parameters | Method specific value |
|------------|--------------------------------------|
| URI | api/employee/routereplaybyidentifier |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameters | Description |
|----------------------------|---|
| <u>employee_identifier</u> | The employee's Identifier. |
| <u>date_time_from</u> | The date and time to list the entries from. |
| <u>date_time_to</u> | The date and time to list the entries to. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| tracks | An array of objects with information on the individual points recorded on the user's route, in the target time period. Each object has: <pre>{ employee_name: integer, address: string, lat: float, lng: float, speed: integer, }</pre> |

| Response | Description |
|----------|---|
| | <pre> heading_txt: string, signal_strength_txt: string, battery_level_percentage: integer, accuracy: integer, accuracy_type: string, tag: string, distance_travelled: integer, created_on: dateTime / String } </pre> |

Asset Management API

We expect your Asset Identifiers to be [RFIDs](#), as this is the way you look up assets on the Mobile App.

Getting a list of Assets

Returns a paged list of all assets in the system.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/assets/getall |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameter | Description |
|---------------|--|
| limit | The amount of assets to be returned per page. Defaults to 10. |
| page | The page number to start the listing from. Defaults to 0. |
| updated_on | An optional unix timestamp. If provided, only assets modified at or after the indicated date and time will be listed. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string,</pre> |

| Response | Description |
|----------|---|
| | <pre> first_name: string, last_name: string } </pre> |
| company | <p>Details of the current company.</p> <pre> { id: integer, name: string } </pre> |
| total | The total number of assets in GeoPal. |
| has_next | A boolean value to indicate if there are additional records in the system, based on the current settings for the <code>limit</code> , <code>page</code> and <code>updated_on</code> parameters. |
| assets | <p>An array of objects representing all assets that match the given criteria. Each object has:</p> <pre> { id: integer, identifier: string, name: string, company_id: integer, asset_template_id: integer, asset_company_status_id: integer, customer_id: integer, address_id: integer, parent_id: integer, cost_price: string, selling_price: string, last_scanned_on: string / dateTime, last_scanned_by: integer, is_deleted: boolean, updated_on: string / dateTime, updated_by: integer, created_on: string / dateTime, created_by: integer } </pre> |

Getting an Asset by Id

Returns details of an Asset, based on its Id in GeoPal.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/assets/get |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameter | Description |
|-----------------|----------------------|
| <u>asset_id</u> | The ID of the Asset. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| asset | An object containing the Asset details. <pre>{ id: integer, identifier: string, name: string, company_id: integer, asset_template_id: integer, asset_company_status_id: integer, customer_id: integer, address_id: integer, parent_id: integer, cost_price: string, }</pre> |

| Response | Description |
|----------|---|
| | <pre> selling_price: string, last_scanned_on: string / dateTime, last_scanned_by: integer, is_deleted: boolean, updated_on: string / dateTime, updated_by: integer, created_on: string / dateTime, created_by: integer, address: { id: integer, identifier: string, is_primary: boolean, is_billing: boolean, is_user: boolean, address_line_1: string, address_line_2: string, address_line_3: string, city: string, postal_code: string, country_id: integer, coordinates_verified: boolean, lat: float, lng: float, boundary: string, is_deleted: boolean, company_id: integer, updated_on: string / dateTime, updated_by: integer, created_on: string / dateTime, created_by: integer }, asset_fields: [{ id: integer, asset_id: integer, asset_company_field_id: integer, company_id: integer, action_value_entered: string, s3file_id: integer, updated_on: string / dateTime, updated_by: integer, created_on: string / dateTime, created_by: integer }], asset_triggers: [{ id: integer, company_id: integer, asset_id: integer, asset_company_trigger_id: integer, assigned_date_time: string / dateTime, trigger_date_time: string / dateTime, is_active: boolean, updated_on: string / dateTime, updated_by: integer, created_on: string / dateTime, created_by: integer }] } </pre> |

Getting an Asset by Identifier

Returns details of an Asset, based on its Identifier.

| Parameters | Method specific value |
|------------|----------------------------|
| URI | api/assets/getbyidentifier |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameter | Description |
|-------------------------|------------------------------|
| <u>asset_identifier</u> | The identifier of the Asset. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| asset | An object containing the Asset details. (Same as for getting an Asset by Id) |

Updating and Creating an Asset

Updates an existing asset or creates a new one with the details provided.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/assets/replace |
| Verb | GET |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameter | Description |
|-------------------------|--|
| <u>asset_identifier</u> | The identifier of the Asset. Either the Identifier or the Id must be provided. |
| <u>asset_id</u> | The Id of the Asset. Either the Identifier or the Id must be provided. |
| asset_template_id | The Id of the Asset Template based on which to create the Asset. For new Assets, this parameter is required. For existing Assets, the Asset Template Id cannot be changed. As such, it will be ignored and may be omitted from the request. |
| asset_company_status_id | The Id of the company-defined asset status to assign to the Asset. |
| asset_name | The human-readable name of the Asset. |
| customer_identifier | The identifier of the customer associated with the Asset. |
| last_scanned_on | A unix timestamp to indicate the last time the Asset has been checked. |
| last_scanned_by | The Id of the last employee to check the Asset. |
| address_lat | The latitude coordinate of the Asset's location. |
| address_lng | The longitude coordinate of the Asset's location. |
| address_postal_code | The postal code to the Asset's location |
| address_city | The name of the city or village where the Asset is located. |
| address_line_1 | The first line of the address where the Asset is located. |
| address_line_2 | The second line of the address where the Asset is located. |

| Post Parameter | Description |
|--------------------|--|
| address_line_3 | The third line of the address where the Asset is located. |
| address_updated_on | Indicates when the Address data to the Asset has last been updated. |
| asset_fields | <p>An array or JSON encoded list of key-value pairs representing the user-defined Asset's Fields, where the Asset Field's Id acts as the key, and the Asset Field's new value to set as the value.</p> <p>E.g.:</p> <pre>{ asset_field_id_1: asset_field_new_value_1, asset_field_id_2: asset_field_new_value_2, ... }</pre> <p>Asset Fields not associated with the Asset's Template will be ignored.</p> |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | <p>A JSON array with the account details of the requestor user who made the call.</p> <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | <p>Details of the current company.</p> <pre>{ id: integer, name: string }</pre> |
| asset | <p>An object containing the Asset details.</p> <p>(Same as for getting an Asset by Id)</p> |

Updating an Asset Field

Allows for updating an individual, user-defined field of an asset.

| Parameters | Method specific value |
|------------|------------------------|
| URI | api/assetfields/update |
| Verb | POST |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameter | Description |
|-------------------------------|--|
| <u>asset_identifier</u> | The identifier of the Asset. Either the Identifier or the Id must be provided. |
| <u>asset_id</u> | The Id of the Asset. Either the Identifier or the Id must be provided. |
| <u>asset_company_field_id</u> | The Id of the corresponding Asset Company Field. |
| action_value_entered | The value to set to the selected Asset Field. Defaults to null. |

| Response | Description |
|-------------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| asset_field | An object containing the Asset Field details. |

| Response | Description |
|----------|---|
| | <pre> { id: integer, asset_id: integer, asset_company_field_id: integer, company_id: integer, action_value_entered: string, s3file_id: integer, updated_on: string / dateTime, updated_by: integer, created_on: string / dateTime, created_by: integer } </pre> |

Uploading a file to an Asset Field

Allows for updating an individual, user-defined field of an asset.

| Parameters | Method specific value |
|------------|-----------------------|
| URI | api/assetfields/file |
| Verb | POST |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameter | Description |
|-------------------------------|--|
| <u>asset_identifier</u> | The identifier of the Asset. Either the Identifier or the Id must be provided. |
| <u>asset_id</u> | The Id of the Asset. Either the Identifier or the Id must be provided. |
| <u>asset_company_field_id</u> | The Id of the corresponding Asset Company Field. |
| <u>file2upload</u> | The absolute path to the file to be uploaded. |

| Note |
|--|
| The file upload behaviour here is that of a standard single file upload via HTTP. That means that, for example, in CURL or .NET, you should prefix the file path with an "@" symbol. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |

| Response | Description |
|-------------|---|
| asset_field | <p>An object containing details on the target Asset Field.</p> <pre> { id: integer, asset_id: integer, asset_company_field_id: integer, company_id: integer, action_value_entered: string, s3file_id: integer, updated_on: string / dateTime, updated_by: integer, created_on: string / dateTime, created_by: integer }</pre> |

Updating an Asset Trigger

Allows for updating an Asset Trigger.

| Parameters | Method specific value |
|------------|--------------------------|
| URI | api/assettriggers/update |
| Verb | POST |
| Data Type | JSON |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Post Parameter | Description |
|---------------------------------|--|
| <u>asset_identifier</u> | The identifier of the Asset. Either the Identifier or the Id must be provided. |
| <u>asset_id</u> | The Id of the Asset. Either the Identifier or the Id must be provided. |
| <u>asset_company_trigger_id</u> | The Id of the corresponding Asset Company Trigger. |
| assigned_date_time | The unix timestamp indicating when the triggered Job should be assigned. Defaults to the current date and time. |

| Response | Description |
|----------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |

| Response | Description |
|---------------|--|
| asset_trigger | <p>An object containing the Asset Trigger details.</p> <pre> { id: integer, company_id: integer, asset_id: integer, asset_company_trigger_id: integer, assigned_date_time: string / dateTime, trigger_date_time: string / dateTime, is_active: boolean, updated_on: string / dateTime, updated_by: integer, created_on: string / dateTime, created_by: integer }</pre> |

Files API

Getting a File

Retrieves An Uploaded File From The System. Any s3file id can be downloaded with this call.

| Parameters | Method specific value |
|------------|---------------------------------|
| URI | api/s3files/get |
| Verb | GET |
| Data Type | Binary or JSON (see parameters) |

| Headers | Method specific value |
|--------------------------|--|
| <u>GEOPAL-SIGNATURE</u> | [reference] |
| <u>GEOPAL-TIMESTAMP</u> | [reference] |
| <u>GEOPAL-EMPLOYEEID</u> | A unique ID assigned to the requestor employee by GeoPal |

| Get Parameters | Description |
|-------------------|---|
| <u>s3_file_id</u> | The S3 file's ID in GeoPal. |
| json | A boolean value to indicate if the file metadata should be returned instead of the file contents. Defaults to false. |

| Response | Description |
|-------------------------------|--|
| status | [true/false] Indicates if there was an error on the server or not |
| tag | An URI to which the call was made to |
| employee | A JSON array with the account details of the requestor user who made the call. <pre>{ id: integer, identifier: string, title: string, first_name: string, last_name: string }</pre> |
| company | Details of the current company. <pre>{ id: integer, name: string }</pre> |
| S3file (Only if json=true) | A json string with the metadata associated with the file <pre>{</pre> |

| Response | Description |
|----------|--|
| | <pre> id: integer, uuid: string, bucket: string, file_name: string, mime_type: string, size: integer, tmp_file_name: string, tmp_file_created_on: string / dateTime, company_id: integer, is_deleted: boolean, deleted_by: integer, created_by: integer, created_on: string / dateTime, updated_on: string / dateTime } </pre> |

Sending Job Fields

Getting Job Field Ids

If you would like to get the job field ids you can use the api section on Geopal (<https://app.geopalsolutions.com/admin/api>) you can use Get All Job Templates first to find all the job template ids you currently have and then use the Get Job Template Detail function to see details about a specific template. In the json returned there is a section called job_template_fields, the ids for each of these fields are the id for the job fields.

Sending Job Fields In Create A Job

To send on job fields you need to construct a simple json array. You can use either the ids of the job fields or the job field names. If you decide to use the name then be careful when editing the template that the names then do not change and the names remain unique. The ids do not have this issue.

To construct the json array you can use a simple dictionary of ids/names and values:

```
Dim jobFieldsDict = New Dictionary(Of Integer, [String])()
jobFieldsDict(JobTemplateFieldId) = "value"
or
Dim jobFieldsDict = New Dictionary(Of String, [String])()
jobFieldsDict(JobTemplateFieldName) = "value"
```

To send those fields you can serialize the dictionary of fields like so:

```
Dim jobFieldsJson As String = JsonConvert.SerializeObject(jobFieldsDict)
Dim pairs As New NameValueCollection()
pairs.Add("template_id", jobTemplateId)
pairs.Add("job_fields", jobFieldsJson)
Dim response As [String] = geopalClient.post(pairs)
```

Visual Basic Reference

1. Creating Signature

```
Private Function GetSignature(signText As String, privateKey As String) As String
    Dim encoding As New System.Text.ASCIIEncoding()

    Dim keybytes As Byte() = encoding.GetBytes(privateKey)
    Dim signbytes As Byte() = encoding.GetBytes(signText)

    Dim hmacsha256 As New HMACSHA256(keybytes)

    Return EncodeTo64(ByteToString(hmacsha256.ComputeHash(signbytes)).ToLower())
End Function

Private Function EncodeTo64(toEncode As String) As String
    Dim toEncodeAsBytes As Byte() = System.Text.ASCIIEncoding.ASCII
    .GetBytes(toEncode)
    Dim returnValue As String = System.Convert.ToBase64String(toEncodeAsBytes)
    Return returnValue
End Function

Private Shared Function ByteToString(buff As Byte()) As String
    Dim sbinary As String = ""

    For i As Integer = 0 To buff.Length - 1
        ' hex format
        sbinary += buff(i).ToString("X2")
    Next
    Return (sbinary)
End Function
```

2. Creating a Job

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/vb.net/VBGeopalJob/Application.vb#L81>

3. Getting Job Details

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/vb.net/VBGeopalJob/Application.vb#L107>

4. Listing All Job Templates

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/vb.net/VBGeopalJob/Application.vb#L163>

5. Reading a Job Template

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/vb.net/VBGeopalJob/Application.vb#L184>

6. Getting Jobs in a Specific Date Range

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/vb.net/VBGeopalJob/Application.vb#L214>

7. Listing Employees

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/vb.net/VBGeopalJob/Application.vb#L239>

Java Reference

1. Creating Signature

```
private String getSignature(String signtext, String privateKey) {
    String test = getHMAC256(privateKey, signtext);
    return Base64.encodeBase64String(test.getBytes());
}

public String getHMAC256(String pwd, String inputdata) {
    String temp = null;
    SecretKeySpec keySpec = new SecretKeySpec(pwd.getBytes(), "HmacSHA256");
    try {
        Mac mac = Mac.getInstance("HmacSHA256");
        mac.init(keySpec);
        // update method adds the given byte to the Mac's input data.
        mac.update(inputdata.getBytes());
        byte[] m = mac.doFinal();
        // The base64-encoder in Commons Codec
        temp = new String(Hex.encodeHex(m));
    } catch (Exception e) {
        e.printStackTrace();
    }
    return temp;
}
```

2. Creating a Job

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/java/src/GeopalJobSample/MainClass.java#L88>

3. Getting Job Details

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/java/src/GeopalJobSample/MainClass.java#L114>

4. Listing All Job Templates

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/java/src/GeopalJobSample/MainClass.java#L214>

5. Reading a Job Template

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/java/src/GeopalJobSample/MainClass.java#L174>

6. Getting Jobs in a Specific Date Range

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/java/src/GeopalJobSample/MainClass.java#L244>

7. Listing Employees

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/java/src/GeopalJobSample/MainClass.java#L281>

PHP Reference

Our php client code can be found: <https://github.com/geopal-solutions/geopal-php-client>

1. Creating Signature

```
private String getSignature(String signtext, String privateKey) {  
    String test = getHMAC256(privateKey, signtext);  
    return Base64.encodeBase64String(test.getBytes());  
}
```

2. Creating a Job

<https://github.com/geopal-solutions/geopal-php-client/blob/master/src/Geopal/Geopal.php#L117>

3. Getting Job Details

<https://github.com/geopal-solutions/geopal-php-client/blob/master/src/Geopal/Geopal.php#L128>

4. Listing All Job Templates

<https://github.com/geopal-solutions/geopal-php-client/blob/master/src/Geopal/Geopal.php#L164>

5. Reading a Job Template

<https://github.com/geopal-solutions/geopal-php-client/blob/master/src/Geopal/Geopal.php#L176>

6. Getting Jobs in a Specific Date Range

<https://github.com/geopal-solutions/geopal-php-client/blob/master/src/Geopal/Geopal.php#L140>

7. Listing Employees

<https://github.com/geopal-solutions/geopal-php-client/blob/master/src/Geopal/Geopal.php#L153>

Python Reference

1. Creating Signature

```
def __generateSignatureString(self, method, uri, employee_id):  
    return method.lower() + uri + employee_id.__str__() + self.getTimeStamp()  
  
def __generateSignature(self, sign_text, private_key):  
    dig = hmac.new(private_key, sign_text, hashlib.sha256).hexdigest()  
    sign = base64.b64encode(dig)  
    return sign
```

2. Creating a Job

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/python/GeopalClient.py#L160>

3. Getting Job Details

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/python/GeopalClient.py#L172>

4. Listing All Job Templates

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/python/GeopalClient.py#L194>

5. Reading a Job Template

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/python/GeopalClient.py#L214>

6. Getting Jobs in a Specific Date Range

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/python/GeopalClient.py#L235>

7. Listing Employees

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/python/GeopalClient.py#L250>

C# .Net Reference

1. Creating Signature

```
private string GetSignature(string signtext, string privateKey)
{
    System.Text.ASCIIEncoding encoding = new System.Text.ASCIIEncoding();

    byte[] keybytes = encoding.GetBytes(privateKey);
    byte[] signbytes = encoding.GetBytes(signtext);

    HMACSHA256 hmacsha256 = new HMACSHA256(keybytes);

    return EncodeTo64(ByteToString(hmacsha256.ComputeHash(signbytes)).ToLower());
}

private string EncodeTo64(string toEncode)
{
    byte[] toEncodeAsBytes
        = System.Text.ASCIIEncoding.ASCII.GetBytes(toEncode);
    string returnValue
        = System.Convert.ToBase64String(toEncodeAsBytes);
    return returnValue;
}

private static string ByteToString(byte[] buff)
{
    string sbinary = "";

    for (int i = 0; i < buff.Length; i++)
    {
        sbinary += buff[i].ToString("X2"); // hex format
    }
    return (sbinary);
}
```

2. Creating a Job

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/csharp.net/GeopalJobSample/Main.cs#L84>

3. Getting Job Details

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/csharp.net/GeopalJobSample/Main.cs#L117>

4. Listing All Job Templates

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/csharp.net/GeopalJobSample/Main.cs#L167>

5. Reading a Job Template

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/csharp.net/GeopalJobSample/Main.cs#L188>

6. Getting Jobs in a Specific Date Range

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/csharp.net/GeopalJobSample/Main.cs#L218>

7. Listing Employees

<https://github.com/geopal-solutions/geopal-api-samples/blob/master/samples/csharp.net/GeopalJobSample/Main.cs#L243>