

# Problem Sheet 2 - Intermediate SQL (With Solutions)

George Melrose: [george\\_melrose@yahoo.com](mailto:george_melrose@yahoo.com), <https://github.com/georgemelrose>

## Introduction

These problems aim to test your intermediate SQL knowledge, building on the basic SQL concepts tested in problem sheet 1. The questions and solutions are of a more esoteric nature than problem sheet 1 yet still useful as a SQL coder. For the purposes of this series of problem sheets, a database of dummy Marathon results data has been generated. More information on the **Marathon** database is presented below.

The concepts tested in this sheet are covered by the LinkedIn learning course **Intermediate SQL for Data Scientists** - (<https://www.linkedin.com/learning/intermediate-sql-for-data-scientists/>) .

## Useful Preparatory Resources

In addition to this problem sheet, there are two useful resources you can draw upon to better understand these SQL concepts:

- **Two RMarkdown documents** - one to generate some dummy ‘Universities’ data ([https://github.com/georgemelrose/SQL\\_Practice/blob/main/0\\_generating\\_databasesstar\\_dummy\\_data.Rmd](https://github.com/georgemelrose/SQL_Practice/blob/main/0_generating_databasesstar_dummy_data.Rmd)). This was copied from the excellent SQL learning resource databasesstar ([https://github.com/bbrunm/databasesstar/tree/main/sample\\_databases/sample\\_db\\_university/sqlite](https://github.com/bbrunm/databasesstar/tree/main/sample_databases/sample_db_university/sqlite)).  
The other document is an RMD HTML going over intermediate SQL concepts and how they can be applied to databasesstar dummy data ([https://github.com/georgemelrose/SQL\\_Practice/blob/main/03\\_Intermediate\\_SQL\\_for\\_Data\\_Scientists.html](https://github.com/georgemelrose/SQL_Practice/blob/main/03_Intermediate_SQL_for_Data_Scientists.html)).
- **A video presentation** - a recording of a meeting in which I presented the **Intermediate SQL for Data Scientists** HTML , explaining varying higher level concepts- ([https://universityofcambridgecloud.sharepoint.com/sites/AD\\_Progress/SitePages/Learning-SQL-in-a-New-Format.aspx](https://universityofcambridgecloud.sharepoint.com/sites/AD_Progress/SitePages/Learning-SQL-in-a-New-Format.aspx)).

## Marathon Database

Firstly, the data to be put into the Marathon database was formulated from the following Python script - ([https://github.com/georgemelrose/SQL\\_Practice/blob/main/Dummy\\_Marathon\\_Data/marathon\\_data\\_generation.ipynb](https://github.com/georgemelrose/SQL_Practice/blob/main/Dummy_Marathon_Data/marathon_data_generation.ipynb)).

The **marathon data generation** python script generates the following tables:

1. **Runners** - Randomly generate 1000 runners with names common in their locale/country, together with their birth date and sex.
2. **Events** - The 6 Major World marathons (Berlin, Boston, Chicago,London,New York City, Tokyo), with an event per year from 2012 to 2023.
3. **Results** - Gives results for runners in hh:mm:ss format, ensuring there aren’t duplicate results for each runner per event. Prevents any results breaking either the male marathon world-record (2:00:35 Eliud



**Solution -**

```
CREATE UNIQUE INDEX idx_events_event_id ON Events(event_id);
```

A unique index is created by using the **CREATE UNIQUE INDEX** command on the event\_id column from Events - the primary key for that table.

**Q3.** - Create a composite index on the runner\_id and event\_id columns in the Training\_Plans table to improve performance for queries that frequently search for a specific runner's training plan for an event?

**Solution -**

```
CREATE INDEX idx_training_plans_runner_event ON Training_Plans(runner_id, event_id);
```

To create a *composite index*, one

**Q4.** - Add a unique index on the first\_name, last\_name, and date\_of\_birth columns in the Runners table to ensure no duplicate runner profiles are entered, even if runners have similar names?

**Solution -**

```
CREATE UNIQUE INDEX idx_runners_name_dob ON Runners(first_name, last_name, date_of_birth);
```

**Q5.** - Give the code to see all the indexes present?

**Solution -**

```
SELECT name FROM sqlite_master WHERE type = 'index';
```

**Q5.** - Give the command to see all the indexes associated with a particular table, for example 'Runners'?

**Solution -**

```
PRAGMA index_list('Runners');
```

## Views

**Q1.** - Create a view of all male runners from the Baltic States? Also write code to display all the records from this view? **Hint** - most of the code is already present in problem sheet 1. Write code to delete a view if necessary (needed if you make a mistake in your code but the view is nevertheless created)

**Solution -**

```
CREATE VIEW Baltic_Men AS SELECT * FROM Runners WHERE country in ('Lithuania', 'Latvia', 'Estonia') AND sex = 'Male';
```

```
SELECT * FROM Baltic_Men;
```

```
DROP VIEW IF EXISTS table_name;
```

**Q2.** - Create a view and display its' records, of all the Nike sponsored runners?

**Solution -**

```
CREATE VIEW Nike_Runners AS SELECT r.first_name || ' ' || r.last_name AS full_name, r.country, r.sex FROM Runners r LEFT OUTER JOIN Sponsored_Athletes sa on r.runner_id = sa.runner_id WHERE sponsor_name = 'Nike';
```

```
SELECT * FROM Nike_Runners;
```

**Q3.** - Create a view and display its' records, of the full names, finish times, and countries of UK runners who had an elite time in the Berlin Marathon (any year)? View all records from this view and write a query to highlight just the middle 5 rows, having arranged them from fastest to slowest time?

**Solution -**

```
CREATE VIEW Elite_Berlin_Brits AS SELECT r.first_name || ' ' || r.last_name  
AS full_name,r.country, re.finish_time FROM Runners INNER JOIN Results re ON  
re.runner_id = r.runner_id INNER JOIN Events e ON e.event_id = re.event_id WHERE  
event = 'Berlin Marathon' AND time_is_elite = 'True' AND country = 'United Kingdom';  
SELECT * FROM Elite_Berlin_Brits;
```

First, determine the total no.rows in the view -

```
SELECT COUNT(*) AS total_rows FROM Elite_Berlin_Brits;
```

Then as there are 15 rows, display only the middle 5 in the results query by using **LIMIT 5 OFFSET 5**.

```
SELECT * FROM Elite_Berlin_Brits ORDER BY finish_time ASC LIMIT 5 OFFSET 5;
```

**Q3. -**