Developing AI-Powered Conversational Databases Using ChatGPT

Table of Contents

Introduction 5
1. AI as a Development Tool 5
2. Learning Objectives 5
3. Prerequisites 6
4. Our Approach 6
1.1 Learning by Prompting 7
1.2 Project-based learning 8
1.3 Black Box Development 8
5. The Applications We Will Develop 9
PART ONE - PROOF OF CONCEPT 10
Chapter 2. Prepare the development environment 10
2.1 Hardware 10
2.2 Software 11
2.2.1 OpenAI API 11
2.2.2 Git and GitHub 11
2.2.3 Android Studio 11
2.2.4 ChatGPT 12
Chapter 3. Getting Started 14
3.1 Phone Book project 14
Chapter 4. Understanding the project 18
4.1 Languages, libraries and frameworks 18
4.1.1 Application architecture 19
4.1.2 How the Application Works 19
Chapter 5. The development process 20
5.1 AI-Assisted Development Process 21
5.1.1 Step 1. Define the Feature Requirements 21
5.1.2 Step 2. Ask ChatGPT to Explain Its Understanding 21
5.1.3 Step 3. Review and Refine the Requirements 21
5.1.4 Step 4. Ask ChatGPT to Implement the Feature 21
5.1.5 Step 5. Update the Source Code 22
5.1.6 Step 6. Review and Understand the Code 22
5.1.7 Step 7. Build and Debug the Application 22
5.1.8 Step 8. Request and Execute Unit Tests 23
5.1.9 Step 9. Perform Functional Testing 23
5.1.10 Step 10. Save and Document the Completed Feature 23
5.2 The Iterative Development Cycle 24
5.3 An Important Principle 24
5.4 Prompt Engineering 24
5.4.1 Writing Effective Prompts 25
5.4.2 Example: Improving a Prompt 25
5.4.3 Prompt Engineering Is an Iterative Process 25
5.4.4 Prompt Engineering in Our Project 26
Chapter 6. Implementing the frontend 27
6.1 First compile 27
6.2 Creating the Phone Book Interface 29
6.3 Internationalization 36
6.4 Lifecycle of an activity 38

6.5 Conclusion 41
Chapter 7. Improving the frontend 43
7.1 Adding an app exit facility 43
7.2 Add an icon and splash screen 45
7.3 Add help 45
7.4 GitHub 46
7.4.1 Accessing the Repository 46
7.4.2 Browsing the Project Files 47
7.4.3 Viewing File History 47
7.4.4 Downloading the Project 47
7.4.5 Keeping GitHub Up to Date 48
7.5 Conclusion 48
Chapter 8. Creating the database 49
8.1 Debugging a crash 40
8.2 Create the local contact database 49
8.2.1 Room 50
8.2.2 The three pieces in Phone Book 50
8.2.3 What happens when you search 50
8.2.4 Where the DDS fits 50
8.2.5 Connect Room to Gradle 51
8.2.6 3. Sync, build, then open the database 51
8.3 Seting up the project for Room 51
8.4 Testing the new code 53
8.5 Wire up contact lookup 55
8.5.1 1. Add the lifecycle dependencies 55
8.5.2 Create `PhoneBookRequestProcessor.kt` 55
8.5.3 3. Create `PhoneBookViewModel.kt` 56
8.5.4 Connect the Send button in `MainActivity.kt` 56
8.5.5 Try it on the emulator 57
8.5.6 Verify the lookup flow 58
8.5.7 Wire up adding, editing, and deleting 58
8.6 Exercies 59
Chapter 9. Connect Phone Book to OpenAI 60
9.1 Get an API key and start the server 60
9.2 Try a lookup in the Android Emulator 61
9.3 Connect from a physical phone or release build 61
PART TWO - DEVELOPING WITH CODEX 63
Chapter 10. Using ChatGPT for Software Market Research 63
10.1 Researching the Market with ChatGPT 63
10.2 Analyzing Competing Applications 64
10.3 Turning Market Research into Requirements 64
10.4 Understanding the Limitations 64
Chapter 11. Prepare the development environment 65
11.1 Visual Studio Code 65
11.2 Android Studio 65
11.3 Codex 65
11.4 SSH clients 66
11.5 FileZilla 66
Chapter 12. Getting Started 67
Chapter 13. Understanding the Project 68
Chapter 14. The Development Process 68
Chapter 15. Requirements 68
Chapter 16. Design 68
Chapter 17. The Front End 68

Chapter 18. The Back End 68
Chapter 19. The Linux Server 68
Chapter 20. Testing 68
Conclusion 68
Chapter 21. Publishing Your App on Google Play 70
21.1 Set up a developer account 70
21.2 Build a signed release 70
21.3 Prepare your store listing and app disclosures 70
21.4 Test the build distributed through Google Play 70
21.5 Submit your production release 70
PART THREE - BLACK BOX DEVELOPMENT 72
Chapter 22. Black Box Development concept 72
22.1 Concept 72
Chapter 23. Applications Design 73
23.1 CL-033 — Daily Log day navigation 73
Chapter 24. Implementation 75
24.1 Setting up the environment. 75
Chapter 25. Implementation 77
Appendix A. Phone Book Project Instructions (AGENTS.md) 82
Appendix B. Phone Book Software Design Document (SDD) 85
Appendix C. Phone Book Software Requirements Specification (SRS) 88
Appendix D. interpret.mjs 94
Appendix E. Captain's log project instructions 100
Appendix F. Black Box Project Instructors (AGENTS.md) 101
Appendix G. Requirements, Prompting and Testing (RPT) 103

Introduction

Artificial intelligence is transforming how software applications are designed, developed, and used. Traditional applications require users to navigate menus, complete forms, and perform predefined operations. AI-powered conversational applications allow users to interact with software using natural language, making applications more flexible, intuitive, and intelligent.

This book explores that transformation through a practical, hands-on approach, demonstrating how to use ChatGPT and Codex to develop AI-powered conversational applications that combine traditional software functionality with natural-language interaction, relational databases, and semantic search.

The book's prompt-based approach lets you ask ChatGPT for guidance tailored to your software versions, development tools, and operating system. As your setup changes, you can revise your prompts to get up-to-date guidance without waiting for a new edition. In Part Three, the book introduces **Black Box Development** and explores how it could shape the future of programming.

1. AI as a Development Tool

In its first role, AI acts as a programming assistant, helping developers throughout the software development lifecycle. Using ChatGPT and Codex, we will demonstrate how AI can assist with defining requirements, designing application architecture, creating database structures, generating source code, debugging errors, testing software, and preparing documentation.

Rather than writing every line of code manually, developers can describe their objectives in natural language and collaborate with AI to develop solutions. This approach, sometimes called *Prompt-driven development*, allows programmers to concentrate more on application design, functionality, and problem-solving while delegating many routine programming tasks to AI.

However, AI does not eliminate the need for programming knowledge. Developers must understand the generated code, evaluate proposed solutions, verify results, and maintain control over the development process. Thoroughly testing AI-generated code helps developers catch errors, check edge cases, and confirm that the code behaves as intended. AI is a development assistant, not a replacement for the programmer.

Readers will learn how to integrate large language models with application code and databases while keeping the software reliable and secure and preserving data integrity.

2. Learning Objectives

By the end of this book, you'll be able to design, build, test, and deploy AI-powered applications that combine conversational interfaces, relational databases, and semantic document search. You'll practice these skills through two guided projects, starting with an Android Phone Book app and

progressing to Captain's Log, where you'll model related voyage records and test whether a search by meaning retrieves the right log entry.

You'll use ChatGPT and Codex to clarify requirements, explore design choices, generate code, and investigate errors. Guided coding examples show how to review and test the code so you can explain how it works and adapt it to your own projects.

If you're an experienced programmer who is new to mobile or cross-platform development, you'll learn to build Android apps with Kotlin in Android Studio. If you're a junior programmer, you'll learn how to turn an idea into clear requirements and use them to guide design, implementation, and testing. Working through each project one feature at a time will give you a practical starting point with Android and Kotlin.

3. Prerequisites

This book is intended for application programmers familiar with at least one programming language, such as C++ or Java, and with basic knowledge of SQL and relational databases. Familiarity with Windows, Linux, or macOS command-line tools, as well as Kotlin, Python, and JSON, is helpful but not required. ChatGPT and Codex will assist readers in learning unfamiliar tools and technologies throughout the development process.

No previous experience with artificial intelligence or Android and cross-platform application development is required.

4. Our Approach

You'll learn by building two working applications in stages. Phone Book, a proof of concept, introduces the development process using a single database table. Captain's Log, a production application, builds on that foundation by linking several types of records and letting users search their written observations using natural language..

In Part One, you'll use ChatGPT to clarify requirements, explore design options, and help you write and test the Phone Book app. In Part Two, you'll use Codex to design, implement, and test Captain's Log.

This approach allows the programmer to concentrate on its primary objectives: application architecture, software design, implementation, conversational databases, semantic search, and AI integration, while ChatGPT provides personalized, interactive guidance for supporting development tasks.

Throughout the book, you'll combine **Learning by Prompting** with **Project-Based Learning**. As you build two working applications, Phone Book and Captain's Log, you'll use prompts to clarify requirements, explore design options, and work through coding problems. You'll review the AI's suggestions and test the code before deciding which changes to incorporate into each application.

1.1 Learning by Prompting

This book adopts Learning by Prompting approach, using ChatGPT as an interactive learning companion throughout the development process.

For tasks such as installing software, getting familiar with development tools, and running operating system commands, the book offers ready-to-use prompts you can submit to ChatGPT for step-by-step guidance. This way the user get's familiar with installing and using the software

For example, instead of dedicating an entire chapter to Git and GitHub installing and basic understanding,, readers can use the following prompts:

Suggested Prompts

- How do I install Git on Windows, Linux, or macOS?
- How do I create a GitHub account?
- Give me a quick introduction to Git and GitHub.
- How do I enable Git for my Android Studio project?
- Explain the basic Git commands with examples.

ChatGPT can provide instructions tailored to the reader's operating system, development environment, and level of experience. Readers can ask follow-up questions, request clarification, explore alternative approaches, and troubleshoot problems as they arise.

The programmer is responsible for understanding the code AI generates and verifying through testing that it works as intended. After ChatGPT generates a source code file, prompt:

- Walk me through this file and explain the code

Start with the file's role in the application, and then follow the code from input to output. For instance, in Phone Book, trace how Find Jane Smith reaches the request processor, how the processor calls the database, and how the result becomes a reply. Ask follow-up questions about any unfamiliar code, run the example to see whether the app behaves as described.

This way you'll learn how to set up a development environment, read and understand the syntax of the programming language, and identify the libraries the application uses and what each one does. As you work through the projects, you'll practice writing clear code comments and testing the code to verify that it behaves as intended.

Learning by Prompting also encourages active participation. Readers are not expected to accept AI-generated instructions blindly. They should understand the purpose of each operation, examine the results, and verify that the suggested solutions work correctly.

The underlying principle is simple: Rather than attempting to teach everything in the book, we teach readers how to use AI to learn what they need, when they need it.

1.2 Project-based learning

Project-based learning is an approach in which students develop knowledge and skills by working through a project with a clear goal. In software development, that means starting with a problem to solve, deciding what the software should do, and building and testing it in stages. Each stage gives students a chance to apply what they've learned and revise their work based on the results.

In Part One of this book, you'll build **Phone Book**, an Android app that stores and retrieves phone book entries. Guided coding examples take you from defining what the app should do to designing its interface and writing the code to save entries to a local database and retrieve them using natural language. You'll test what happens when a search finds zero, one, or multiple matches, then connect the app to OpenAI so users can ask questions such as "What's Jane Smith's number?"

In Part Two, you'll apply what you learned to build **Captain's Log**, an app that helps boaters keep a record of their trips, log observations, and find past entries using natural-language search.. In Phone Book, you look up a saved entry by name. In Captain's Log, you'll connect voyages, stops, and notes, and then test whether a search can find a relevant observation written in different words. You will learn how to develop a successful production app.

1.3 Black Box Development

Black Box Development starts with an assumption. For the purposes of this book, we assume that in 2027, code generated by ChatGPT and other large language models is correct and can be used without human code review. I predict that this assumption will soon hold in practice. As AI produces more code, reviewing every line by hand will become impractical and consume much of the time saved by generating it. Many programmers will shift toward application design, much as programmers today rely on compilers without having to inspect the machine code they produce. Systems programmers will still use assembly language, C, and C++ to build operating systems, device drivers, compilers, and other development tools.

Under this premise, the application designer specifies what the software must do and verifies that it behaves as required. The AI writes, reviews, and optimizes the code, runs unit tests, and identifies and fixes security vulnerabilities. The designer tests each feature from the user's point of view, then tests the application as a whole to see whether the features work together as intended.

This book proposes a single **Requirements, Prompting, and Testing (RPT)** document instead of an SDD, SRS and Test Plan. Each feature has its own entry with a requirement that defines the expected behavior, a prompt that directs the AI to implement it, and a test that specifies the steps and expected results. Keeping these together lets the designer check that the prompt covers the requirement and that the test verifies the behavior the user should see.

5. The Applications We Will Develop

In Part One, we will use ChatGPT to develop a small conversational database application called Phone Book as a proof of concept. The application will contain a single database table and demonstrate how users can interact with data through natural-language conversations.

In Part Two, you'll use Codex to build Captain's Log, an app for recording voyages and finding what you learned on previous trips. The project will cover these features:

- **Voyage records.** Link boats, voyages, stops, and dated log entries in a relational database. Record and review observations for each stop, track maintenance and expenses, schedule appointments, and attach photos and documents to related records.
- **Supporting documents.** Attach photos, trip notes, invoices, and other documents to a stop so you can review them alongside the original log entry.
- **Semantic search.** Find relevant observations even when your search uses different words to describe the same idea.
- **Source references.** Open the original log entry directly from a search result to verify the date and location and read the observation in context.

Try questions like these with sample voyage records:

- Show me our previous stops at Harbor Point.
- Find the entry where we moved after dark because the anchorage got rough.
- What did we note about the swell during our last visit?
- Which log entry contains the photos from that stop?

Captain's Log uses database filters to narrow results by date or stop and semantic search to find notes that match the meaning of your query. Each result links to the original log entry so you can read what the captain recorded in context.

PART ONE - PROOF OF CONCEPT

In Part One, we use ChatGPT as a development assistant to build Phone Book, a small Android application demonstrating conversational access to a database of names, addresses, and phone numbers. We prepare the development environment, create the Android Studio project, set up Git and GitHub, and define the application's requirements and architecture. We then begin implementing and improving the interface, exploring screen layouts, Android activities, debugging, and internationalization.

Throughout this work, we learn a repeatable development process: describe a feature, confirm ChatGPT understands, refine the requirements, generate and review the code for the feature, build and test the feature, and save the verified changes to GitHub. Through this "learning by prompting" approach, we develop practical skills in collaborating with AI while maintaining control over the software, preparing for Captain's Log, which you will develop with Codex in Part Two.

Chapter 2. Prepare the development environment

2.1 Hardware

To develop, test, and run the applications described in this book, you will need the following hardware:

- A computer running Windows 10 or 11, Linux (preferably Ubuntu), or macOS, with an Internet connection, at least 16 GB of RAM (8 GB may be sufficient but could affect performance), and a 256 GB or larger storage drive, preferably an SSD, with 50GB of free space.
- Android Device: An Android phone running Android 8.0 or later. A SIM card or mobile service plan is not required; a Wi-Fi connection is sufficient. An Android tablet can also be used instead of a phone. The phone has to be in Developer Mode. Use this prompt to find out how to enable Developer Mode on your phone.

  - How do I enable Developer Mode on a <your phone>

- USB Cable: A USB data cable to connect the Android device to the development computer for application installation, testing, and debugging.

Note: Be careful when you select your USB cable. Some USB cables can charge your phone but cannot transfer data.

2.2 Software

2.2.1 OpenAI API

The OpenAI API provides a consistent interface to state-of-the-art AI models for text generation, natural language processing, computer vision, and more. Get started by creating an API Key and running your first API call. Discover how to generate text, analyze images, build agents, and more.

- What is OpenAI API
- How do I install OpenAI API
- How much does OpenAI API cost
- How do I create an API Key

Save the key in a safe place. We will need it when we connect the application to OpenAI.

2.2.2 Git and GitHub

Git is a version-control system that tracks changes to your source code, allows you to restore previous versions, and supports working on multiple development branches.

GitHub is an online platform for storing, backing up, sharing, and collaborating on Git projects. You will need to create a GitHub account. A free account is sufficient for this book.

- How do I install Git
- How do I access GitHub
- Quick start with Git and GitHub

2.2.3 Android Studio

Android Studio is the official Integrated Development Environment (IDE) for developing Android applications. It is free and available for Windows, Linux, and macOS.

Note: On a Mac you may experience Android Studio rashes

Android Studio provides tools for writing, editing, building, testing, and debugging Android applications. It supports Kotlin, the primary programming language used in in this book.

Android Studio includes an Android Emulator, allowing you to test applications without a physical Android device. However, using a real Android phone or tablet is recommended.

You can test Phone Book on a simulated phone or on a physical Android phone. Both let you test offline commands such as `Add` and `Find`. The setup for natural-language lookup depends on which device you choose.

Build the emulator

An **Android Virtual Device (AVD)** combines a phone profile, which defines hardware such as screen size, with a system image, which version of Android it runs. To create an AVD inAndroid Studio, open **View → Tool Windows → Device Manager**. The device manager window will open listing all the existing devices. Click **+**, and select **Create Virtual Device**. Choose a phone profile and a system image with API level 24 or higher, click Next and Finish.

Connect your Android phone

1. On your phone, find **Build number** in **Settings** and tap it seven times to enable **Developer options**. Open **Developer options** and turn on **USB debugging**. Your phone may have a different process.
2. Connect the phone to your computer with a USB data cable. Unlock the phone and approve the **Allow USB debugging?** prompt.
3. Select your phone in the Android Studio toolbar and click **Run** . Android Studio builds and installs Phone Book on the phone.

- How do I enable Development Options on <your phone>

Note: If you have trouble connecting a phone to you development machine ise a virtual device.

- What is Android Studio
- What are the requirements for an Android Studio installation
- How do I install Android Studio
- How do I verify my Android Studio installation
- Give me a short preview on Android Studio

Note: Android Studio install file takes a long time to download.

At the end of Android Studio installation you will be asked to create a project. Create an "No Activity" empty project. Name the project "Phone Book".

Note: Watch for updates. You will get a message box on the lower right corner

2.2.4 ChatGPT

To use ChatGPT, open https://chatgpt.com/ in a browser on your Windows, Linux, or Mac computer. Create an account and start asking questions or giving instructions, called prompts. You can also install the ChatGPT desktop application on Windows, Mac, or supported Linux computers or on your phone. Visit https://chatgpt.com/download/ for installation instructions.

ChatGPT offers free and paid plans. Free usage is limited, and you may have to wait for your usage allowance to reset. A paid subscription provides higher limits and additional features.

For Part One of this book, you need only ChatGPT Plus. In Part Two, we will use Codex for AI-assisted programming. Depending on your usage, you may need a paid subscription or additional credits.

Suggested prompts:

- How do I use ChatGPT
- How much does ChatGPT costs
- How do I install ChatGPT desktop on my Windows/Linux/Mac
- Familiarize me with ChatGPT web and desktop interface
- How do I work with projects
- What is Codex CLI, how do I install on Windows/Linux/Mac and how do I use it
- Can I develop Android apps on my Mac machine
- What is Codex
- What is the difference between ChatGPT and Codex
- What is a GPT

Note: Enter these prompts one at a time. Ask follow-up questions whenever you need clarification.

In the ChatGPT desktop app, hover over **Projects** in the left sidebar and click **+**. Name the project **Phone Book**. Select the root folder of your Android Studio project. On Windows, this is typically `C:\Users\<username>\AndroidStudioProjects\PhoneBook`. On macOS or Linux, select the folder where you saved the project. Click **Create Project**.

In your text editor, create a file named `AGENTS.md` in the project's root folder. Paste the text from **Appendix One** into the file and save it. When you start a Codex chat in the **Phone Book** project, Codex reads `AGENTS.md` for project-specific instructions.

Open the **Phone Book** project in the ChatGPT desktop sidebar and start a separate chat for each major task. Give each chat a name that describes its purpose, such as **Room Database Design**, **Offline Commands**, **Conversation Screen**, **Milestone 1 Acceptance Tests**, or **Natural-Language Lookup**. Each chat can use the same project folder and `AGENTS.md` while keeping its own conversation history. Return to the same chat when you continue a task, and record decisions that apply across tasks in the project documentation. Put instructions that Codex should follow across chats in `AGENTS.md`.

Note: ChatGPT may occasionally suggest additional prompts or follow-up actions. They show up in deemed text in the prompt edit box and you have to clik tab to activate. While these suggestions can be helpful, they may not always align with your objectives, priorities, or intended development approach. Review them carefully before accepting them. You are in control of the development process, not ChatGPT.

We won't use sections in this book, but you can explore them to see how they help organize your projects and chats in the sidebar.

- What are sections in the ChatGPT desktop sidebar? Show me how to create a section and use it to organize my projects and chats.

Note: For this book I used GPT-6 and codex-cli 0.166.0-alpha.5.1


Chapter 3. Getting Started

3.1 Phone Book project

If you didn’t create the project during installation open Android Studio and click New Project button on the top of the screen. Select No Activity and click next. Set you project name to "Phone Book". Remove example from Package Name. The package name should be com.y219.phonebook. Click Finish. The project will open and on the lower left side of the screen you will see the message Importing Gradle Phone Book Project with a progress bar (it will take a while to finish) followed by Analyzing Project. Wait for import and analysis to finish.

Click on the project icon on the upper left of the screen  , under the android icon. If you don't see the icon click on the hamburger icon on the upper left corner and select View → Windows → Tools → Project, On the left you will see the project window.

Click app→kotlin+java→com.y219.phonebook then expend res, manifest and gradle scripts. You should see the following tree:



These are the most important project items:

- **AndroidManifest.xml file** – Defines essential information about the application, including its components (activities and services), required permissions, and configuration settings.
- **com.y219.phonebook folder** – Contains the application's Kotlin source code, including activities, classes, and other program logic. The folder name corresponds to the application's package structure. The files can be organized in subfolders.
- **res folder** – Contains application resources such as images, icons, colors, text strings, and user interface layouts.
- **build.gradle.kts (project) file** – Defines project-level build configuration, including plugins and settings shared across modules.
- **build.gradle.kts (module) file** – Defines the build configuration for a specific module, including application ID, minimum and target Android versions, dependencies, and build options.
- **gradle.properties file** – Contains Gradle configuration properties that control build behavior, performance, and JVM settings.
- **libs.versions.toml file** – Defines a centralized catalog of library and plugin versions, allowing dependencies

Go to C:/Users/[your user name] on window, or ~ on Linux and Mac and look for this directory

AndroidStudioProjects \PhoneBook. This is where our project files are stored. Familiarize yourself with the directory structure and files. Compare it with the project structure in Android Studio.

Open PowerShell in Window or terminal in Linux and Mac and go to the project home directory

and type

```
/PhoneBook > git init
```

You should get:

Initialized empty Git repository in <project root directory>

If you get invalid command install git. You also have to install git 'Command-Line Interface'

- How do I install git and git Command-Line Interface
- How do I install github
- Give me an introduction to github
- How do I connect local git to github repository
- How do I create my Phone Book repository on GitHub

Try a few git commands

`git status` - you will see all the files in the project home directory in red. That means that the files have not been stored in git and they have to be created. Every time a file is update in the project directory structure it will appear in red when you time the command

Notice the file
`app/src/androidTest/java/com/y219/phonebook/ExampleInstrumentedTest.kt`

We do not want to store this file in git as it is unrelated to the project. Open the .gitignore and paste the subdirectory and name of the file in .gitignore. If you try git status again the file will not show in the listing.

git add . (notice the dot after add). This command will stage the file for being committed. The dot tells git to stage all the files. You can stage only one file by replacing the dot with the subdirectory and file name.

`git status` - will display all the files in green meaning that the files were staged. You can unstage the file using: `git restore --staged .`

Now we are ready to commit the files, meaning store a new version of the files in git

`git commit -m"Initial commit"` - the message is mandatory. If you try again `git status` you will not see any files. This means that the last version of the files in git are identical with the files in the project.

If you created a repository in GitHub you have to connect the local git with the repository in GitHub. You can create and connect with a repository in one step using this command in your project home directory

```
git remote add origin https://github.com/YOUR_USERNAME/PhoneBook.git
```

YOUR USERNAME is the username you use to log in GitHub

Check if you are connected

```
git remote -v
```

Now push the local commit to the remove directory in GitHub

```
git branch -M main
```

```
git push -u origin main
```

You will have to supply your GitHub credentials.

This is enough to get you going with git and GitHub

Chapter 4. Understanding the project

3.1 What will we build

We identified the high level requirements for this project.

Develop a phone book Android app based on a conversational database.

This is a simple application storing Names, addresses and phone numbers. But what is a conversational database?

A conversational database usually means a database you can ask questions in plain language. The database stores the data, and a chat interface translates your question into a query, often SQL, then presents the results.

We can get more details from ChatGPT.

- Give me a Google Cloud's conversational analytics overview
- What is a Big Query
- Do we need Big Query for our Phone Book project

4.1 Languages, libraries and frameworks

We have to identify the tools to use to develop an Android Conversational Database

- What tools, libraries, languages plug-ins etc. do we have to use to build the Phone Book app

From the suggestions we identified the language to use:

- Kotlin - Main programming language for the Android application.
- SQL- Create and query the contacts database.
- Python - Implement the AI server and process requests.
- JSON - Exchange structured data between Android and the server.
- Kotlin DSL Configure Gradle build scripts (build.gradle.kts).
- XML - Define Android resources and configuration, including the application manifest.

You should get familiar with these languages:

- Give me a quick start up with Kotlin
- Give me a quick start up with SQL
- Give me a quick start up with Python

We also identified libraries and frameworks:

- SQLite - Store contact records in a relational database on the phone
- Room - Simplify and organize Android database access
- Retrofit / OkHttp - Communicate with the AI server over HTTP
- Kotlin Coroutines - Execute database and network operations without blocking the user interface
- FastAPI - Provide HTTP endpoints on the Python server
- Uvicorn - Run the FastAPI server
- OpenAI Python SDK - Communicate with OpenAI models from the server

Get help from ChatGPT to familiarize yourself with these packages. You will learn more when we start developing.

4.1.1 Application architecture

The following diagram illustrates the architecture of the Phone Book application, showing its major components, the software technologies used, and how information flows between them.

The application runs entirely on an Android phone, including the user interface, application logic, and relational database. The local AI server is installed on the development machine. The local AI server communicates with the OpenAI API over the Internet to interpret natural-language requests.

The architecture consists of five main components:

1. User Interface (Kotlin and XML): Provides a conversational interface where users enter requests in natural language or SQL. Query results are displayed in a scrollable data grid.
2. Application Logic (Kotlin and Coroutines): Processes user requests, determines whether they contain natural language or SQL, and directs them to the appropriate component. It also coordinates database operations and returns results to the user interface.
3. Local AI Server (Python, FastAPI, Uvicorn, and OpenAI SDK): Runs on the development machine and handles natural-language requests. It communicates with the OpenAI API to interpret user instructions and generate SQL statements.
4. Database Layer (Room and SQLite): Manages access to the local relational database, executes SQL queries, and retrieves matching contact records. The database contains a single table named contacts.

4.1.2 How the Application Works

When a user submits a request, the application determines how to process it.


Natural-language requests: The application sends the request to the local AI server, which uses the OpenAI API to generate the corresponding SQL query.

1. SQL statements: The application sends the SQL statement directly to the database layer without requiring AI processing.
2. Query execution: The database layer executes the SQL query against the local contacts table.

3. Results: The retrieved records are returned to the application and displayed in the main window data grid.

This architecture separates the user interface, application processing, AI interpretation, and database management into distinct components. This separation simplifies development, testing, debugging, and maintenance.

Note: Although the AI server runs locally on the development machine, the proposed implementation uses the cloud-based OpenAI API. Therefore, natural-language processing requires an Internet connection, while SQL queries can be executed locally without Internet access.



Chapter 5. The development process

We are now ready to begin developing the Phone Book application. At first, the task may seem overwhelming, especially when considering the different programming languages, development tools, libraries, databases, and AI technologies involved. However, with ChatGPT as our development assistant, we can approach the project systematically, one step at a time. We do not need to master every technology before getting started. Instead, we will learn as we go, using ChatGPT to help us design the application, generate and explain code, configure the development environment, identify and correct errors, and test each component.

By breaking the development process into small, manageable tasks, we will gradually transform our requirements into a working application. Along the way, we will demonstrate how AI-assisted development can simplify complex programming tasks, accelerate learning, and make modern

application development more accessible, even to programmers unfamiliar with some of the technologies involved.

5.1 AI-Assisted Development Process

We will follow an iterative, step-by-step development process using ChatGPT as our programming assistant. Rather than asking ChatGPT to develop the entire application at once, we will divide the project into small, manageable features. Each feature will go through a structured process of requirements clarification, implementation, code review, and testing before we move on to the next feature.

The development process consists of the following steps:

Step 1. Define the Feature Requirements

Start by describing the feature you want to implement in plain English. Explain what the feature should do, how the user will interact with it, and what results are expected.

You do not need to use formal software engineering terminology. ChatGPT can help transform your description into clear, structured requirements.

Step 2. Ask ChatGPT to Explain Its Understanding

Before requesting any code, ask ChatGPT to restate the requirements as it understands them.

For example:

- <send the requirement to ChatGPT>
- Review the requirements and explain your understanding. List the expected functionality, identify any ambiguities, and ask questions if clarification is needed. Do not generate code yet.

This step is particularly important because ChatGPT may interpret your instructions differently from what you intended.

Step 3. Review and Refine the Requirements

Carefully review ChatGPT's interpretation. If something is incorrect, incomplete, or unclear, provide additional instructions.

Ask ChatGPT to update the requirements and restate them. Repeat this process until you are satisfied that the requirements accurately describe the intended feature functionality.

This iterative dialogue helps identify misunderstandings before they become programming errors.

Step 4. Ask ChatGPT to Implement the Feature

Once the requirements are clear, ask ChatGPT to implement the feature.

For example:

- Implement the approved requirements in Kotlin. Provide the necessary source code, identify which files need to be created or modified, and explain how to integrate the changes into the existing Android Studio project. Do not introduce functionality beyond the approved requirements.

ChatGPT will generate new source files or recommend modifications to existing files.

Step 5. Update the Source Code

Apply the changes suggested by ChatGPT to the Android Studio project.

Depending on the feature, this may involve creating files, replacing existing code, modifying functions, or updating project configuration files.

Step 6. Review and Understand the Code

Before accepting the implementation, review the generated code.

Ask ChatGPT to explain any functions, statements, libraries, or programming techniques you do not understand.

For example:

- Review the implementation against the approved requirements. Explain how the code works, identify possible problems, and suggest corrections if necessary.

Remember that AI-generated code is not guaranteed to be correct. ChatGPT can make mistakes, overlook existing functionality, or suggest code that does not compile.

Use the Android Studio debugger to walk through the code.

- How do I debug my code using breakpoints and variables watches?

The developer remains responsible for reviewing and verifying the implementation.

Step 7. Build and Debug the Application

Compile the application using Android Studio.

If compilation errors occur, copy the relevant error messages and submit them to ChatGPT for analysis.

For example:

- The following compilation error occurred. Explain the cause and provide the necessary correction.

Apply the suggested corrections and rebuild the application. Repeat until the code compiles successfully.

A successful compilation confirms that the code can be built, but it does not guarantee that the feature behaves correctly.

Step 8. Request and Execute Unit Tests

Ask ChatGPT to generate unit tests based on the approved requirements.

For example:

- Create JUnit unit tests for this feature. Include normal operating conditions, boundary conditions, and error cases. Explain how to execute the tests in Android Studio.

Add the generated tests to the project and execute them.

If a test fails, provide ChatGPT with the test results and relevant source code. Ask it to determine whether the problem is in the implementation or in the test itself.

Continue correcting and testing until the feature passes its tests.

Step 9. Perform Functional Testing

Run the application on an Android emulator or physical phone and verify that the feature behaves as expected.

Unit tests verify individual components, while functional testing confirms that the feature operates correctly from the user's perspective.

Check that the new feature works as specified and does not interfere with existing functionality.

If unexpected behavior occurs, describe the problem to ChatGPT and provide any relevant Logcat messages.

If you experience a crash

Step 10. Save and Document the Completed Feature

Once the feature has been implemented and successfully tested:

- Update the project documentation to reflect the implementation.
- Commit the changes to Git with a meaningful description.
- Push the changes to GitHub.
- Proceed to the next feature.

5.2 The Iterative Development Cycle

The process follows a repeating cycle:

Define Requirements → Confirm Understanding → Refine Requirements → Implement → Review Code → Build → Test → Correct → Commit

Each completed feature becomes part of the growing application. If problems are discovered, we return to the appropriate step, correct the issue, and repeat the necessary tests.

5.3 An Important Principle

Do not ask ChatGPT to implement a requirement until you are satisfied that it understands exactly what you want.

A few minutes spent clarifying requirements can save considerable time debugging incorrect implementations.

Throughout this process, we will treat ChatGPT as a development assistant rather than an infallible programmer. We will use its capabilities to accelerate coding, improve our understanding of unfamiliar technologies, and help diagnose problems, while maintaining control over requirements, design decisions, and acceptance of the final implementation.

This approach demonstrates one of the most important advantages of AI-assisted software development: we can build complex applications incrementally, learning and verifying each step rather than attempting to understand and implement everything at once.

5.4 Prompt Engineering

Prompt engineering is the practice of designing clear and effective instructions, called prompts, to guide artificial intelligence systems such as ChatGPT toward producing useful and accurate results.

In traditional programming, developers write detailed instructions using a programming language. With AI-assisted development, we can describe what we want to accomplish in natural language and ask ChatGPT to help generate the necessary code.

However, the quality of the results depends significantly on the quality of the prompts. Vague or incomplete instructions may produce code that does not meet our expectations, while clear, specific prompts generally lead to more accurate and useful responses.

5.4.1 Writing Effective Prompts

When using ChatGPT for software development, follow these basic guidelines:

1. Be specific. Clearly describe what you want to accomplish, including the expected behavior and any constraints.
2. Provide context. Identify the application, programming language, relevant source files, and existing functionality.
3. Break complex tasks into smaller steps. Ask ChatGPT to implement one feature at a time rather than attempting to develop the entire application in a single prompt.
4. Confirm understanding. Before requesting code, ask ChatGPT to restate the requirements and identify any ambiguities.
5. Specify constraints. Tell ChatGPT what it must not change, particularly when modifying existing code.
6. Review and refine. If the response is incomplete or incorrect, provide feedback and ask ChatGPT to revise it.
7. Request explanations and tests. Ask ChatGPT to explain generated code and provide appropriate unit tests.

5.4.2 Example: Improving a Prompt

Consider the following simple prompt:

- Create a database for my Phone Book application.

Although ChatGPT can respond to this request, it must make assumptions about the database structure and implementation.

A more effective prompt would be:

- We are developing an Android Phone Book application using Kotlin and SQLite. Create a contacts table using the fields defined in our approved requirements. Explain the SQL statements and provide the Kotlin code necessary to create the table. Do not add fields or functionality that have not been specified. Before generating code, summarize your understanding of the requirements.

The second prompt provides context, identifies the technologies, establishes constraints, and requests confirmation before implementation.

5.4.3 Prompt Engineering Is an Iterative Process

An effective prompt does not always produce a perfect response on the first attempt. Prompt engineering involves an ongoing conversation in which we review results, correct misunderstandings, provide additional information, and refine our instructions.

For example, if ChatGPT generates code that modifies unrelated functionality, we can instruct it:

- Revise the implementation to preserve all existing functionality. Modify only the code necessary to implement the approved requirement.

We can also ask ChatGPT to explain its proposed changes before applying them.

5.4.4 Prompt Engineering in Our Project

Throughout the development of the Phone Book application, we will use prompt engineering as a fundamental development technique. We will describe requirements in natural language, ask ChatGPT to confirm its understanding, generate code, review implementations, and create tests.

The objective is not simply to generate code faster, but to produce software that satisfies clearly defined requirements and can be understood, tested, and maintained.

As we progress through the project, we will develop practical prompt engineering skills through hands-on experience. These skills are applicable not only to Android development but also to other programming languages, platforms, and software engineering activities.

Chapter 6. Implementing the frontend

6.1 First compile

Let's begin by compiling the project we created. Click the hamburger icon on the upper left corner to display the main menu. On Mac the menu is always visible. Select Build and then Compile Phone Book app. The compile process starts and on the lower right corner you will see a message Gradle Build Running.

Gradle is the build tool that turns your Android project's code and resources into an installable app, such as an APK. It manages dependencies, runs tests, and handles build settings like Android versions and debug or release builds. Android Studio uses Gradle behind the scenes, with configuration stored in files such as build.gradle.kts.

As a matter of fact there are two build.gradle.kts

build.gradle.kts(project: Phone Book) is the project-level build configuration written in Kotlin. It usually declares build plugins and their versions, such as the Android and Kotlin plugins, for modules in your Phone Book project to use.

```
// Top-level build file where you can add configuration options common to
all sub-projects/modules.

plugins {
    alias(libs.plugins.android.application) apply false
}
```

build.gradle.kts(Module: app) configures the app itself, including its Android SDK versions, application ID, and dependencies.

```
plugins {
    alias(libs.plugins.android.application)
}
android {
    namespace = "com.y219.phonebook"
    compileSdk {
        version = release(37)
   }

    defaultConfig {
        applicationId = "com.y219.phonebook"
        minSdk = 24
        targetSdk = 37
        versionCode = 1
        versionName = "1.0"
        testInstrumentationRunner = "androidx.test.runner.AndroidJUnitRunner"
    }
```

```
    buildTypes {
        release {
           optimization {
                enable = true
                packageScope = setOf("androidx.**", "kotlin.**", "kotlinx.**")
            }
        }
    }

    compileOptions {
        sourceCompatibility = JavaVersion.VERSION_11
        targetCompatibility = JavaVersion.VERSION_11
    }
}

dependencies {
    implementation(libs.androidx.appcompat)
    implementation(libs.androidx.core.ktx)
    implementation(libs.material)
    testImplementation(libs.junit)
    androidTestImplementation(libs.androidx.espresso.core)
    androidTestImplementation(libs.androidx.junit)
}
```

The build.gradle.kts (Module: app) file usually contains three main sections:

- plugins { } enables tools needed to build the app, such as the Android application and Kotlin plugins.
- android { } configures Android settings. These include namespace, compileSdk, a defaultConfig block with the application ID, minimum Android version, and app version, plus build types such as debug and release.
- dependencies { } lists libraries the app uses, such as AndroidX, Jetpack Compose, and testing tools.

Another important file is the AndroidManifest.xml. The AndroidManifest.xml file tells Android what your app contains and what it needs. Its main parts are <manifest>, the root element; <uses-permission>, which declares permissions such as internet or camera access; and <application>, which defines app settings such as its icon, label, and theme. Inside <application>, you declare components such as activities, services, and broadcast receivers. An activity's <intent-filter> can specify that it is the app's entry screen when launched from its icon.

```
<?xml version="1.0" encoding="utf-8"?>
<manifest xmlns:android=http://schemas.android.com/apk/res/android
    xmlns:tools="http://schemas.android.com/tools">
    <application
        android:allowBackup="true"
        android:dataExtractionRules="@xml/data_extraction_rules"
```

```
        android:fullBackupContent="@xml/backup_rules"
        android:icon="@mipmap/ic_launcher"
        android:label="@string/app_name"
        android:roundIcon="@mipmap/ic_launcher_round"
        android:supportsRtl="true"
        android:theme="@style/Theme.PhoneBook" />
</manifest>
```

The build.gradle.kts and AndroidManifest.xml files will change continuously as the app is developed. When build.gradle.kts changes you will not be able to compile until you sync the project with the Gradle files. To do this open the menu and under File scroll down to Sync Project with Gradle Files.

6.2 Creating the Phone Book Interface

To allow users to interact with our Phone Book app, we will create a screen similar to the ChatGPT interface. The screen will include a conversation area, a text field for entering requests, and a send button. Users will be able to type requests such as “Add a new contact,” “Find John’s phone number,” or “Update Mary’s email address.” The app will display responses in the conversation area and ask for any additional details needed to complete each request.

To create this screen, we have to define its layout in an XML file, such as activity_main.xml. We will add a conversation area to display messages, a text field for entering requests, and a send button. In MainActivity.kt, we will load this layout using setContentView() and connect its elements to the Phone Book’s contact management logic.

The requirement for this feature we send to ChatGPT:

- Requirement
  The user interface shall have an area to display messages returned by the server, a text edit field for entering requires and a button with a label Send. State this requirement as you understand it. The implementation should use an XML layout. Do not generate any code.

Note: If you press enter after "Requirement" the prompt will be submted. To prevent this, when you need to start a new line press Shift and Enter

ChatGPT may answer something similar to this:

> *The conversation screen shall use an XML layout with a scrollable area that displays submitted requests and their replies, including messages returned by the server. It shall also provide an editable text field for entering a request and a button labeled **Send** that submits the request.*

This is a good understanding so we can proceed

- Implement this requirement Generate extensive comments

ChatGPT should create this file:

```
<?xml version="1.0" encoding="utf-8"?>
<!--
    Main Phone Book screen.
    MainActivity loads this file with setContentView(R.layout.activity_main).
    This XML defines the views; Kotlin code handles sending requests and
replies.
-->
<LinearLayout xmlns:android=http://schemas.android.com/apk/res/android
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:padding="16dp">

    <!--
        Conversation scrolling container.
        A height of 0dp with weight 1 gives it the space left above the input
row.
        fillViewport makes its child at least as tall as the visible area.
        A ScrollView supports exactly one direct child: conversationArea below.
    -->

    <ScrollView
        android:id="@+id/conversationScroll"
        android:layout_width="match_parent"
        android:layout_height="0dp"
        android:layout_weight="1"
        android:fillViewport="true">

        <!--
            Message container, initially empty.
            MainActivity can append TextViews for user messages and app replies.
            Vertical orientation places each message below the previous one.
            After adding a message, Kotlin code can scroll conversationScroll
            to the bottom so the latest response is visible
       -->

        <LinearLayout
            android:id="@+id/conversationArea"
            android:layout_width="match_parent"
            android:layout_height="wrap_content"
            android:orientation="vertical"
            android:paddingBottom="16dp" />
    </ScrollView>

    <!--
        Request composer.
        This row stays below the conversation because it is outside the
ScrollView.
        Bottom gravity aligns the button with the bottom of a growing input
field.
```

```
        Start-based spacing also supports right-to-left interface layouts.
    -->

    <LinearLayout
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:gravity="bottom"
        android:orientation="horizontal">

        <!--
            Request text field.
            Width 0dp and weight 1 let it take the width remaining beside Send.
            Multiline input supports longer requests, showing up to four lines
            before the text scrolls within the field. The hint comes from
strings.xml
            for translation. A 48dp minimum height provides a usable touch
target.
            Kotlin reads its text and clears it after accepting a request.
        -->

        <EditText
            android:id="@+id/requestInput"
            android:layout_width="0dp"
            android:layout_height="wrap_content"
            android:layout_weight="1"
            android:gravity="top|start"
            android:hint="@string/request_hint"
            android:inputType="textCapSentences|textMultiLine"
            android:maxLines="4"
            android:minHeight="48dp" />

        <!--
            Send action.
            The visible text also supplies the button's accessibility label.
            MainActivity attaches a click listener, rejects blank input,
displays
            the user's message, and passes the request to contact-management
logic.
            Declaring this button alone does not implement those behaviors.
        -->


        <Button
            android:id="@+id/sendButton"
            android:layout_width="wrap_content"
            android:layout_height="wrap_content"
            android:layout_marginStart="8dp"
            android:minHeight="48dp"
            android:text="@string/send_request" />

    </LinearLayout>

</LinearLayout>
```

Read the comments carefully and familiarize with the format.

Now we add this file to our project. In the project window expend app then res folders. Right click on layout and under New select Create Resource File. Enter activity_main.xml and click OK. You may be asked to add the file to git. Answer yes. You will see the Layout as it will appear on the phone's screen (currently empty). To see the code click hamburger icon on the right side of the file name.



Remove all the code in the file and copy and paste the code generated by ChatGPT. Click the image icon on the right of the hamburger. You should see the layout of the screen.

We have to create the code to display this layout on the phone's screen. Expand app ? kotlin+java and right-click on the first com.y219.phonebook (nothing in parentheses). Select New ? Kotlin Class/File. Enter MainActivity, select Class, and press Enter. Android Studio creates an empty MainActivity.kt. We will ask ChatGPT to create the code.

- Create the code for MainActivity.kt to handle the layout activity_main.xml we created earlier. Add extensive comments. The package name is com.y219.com.phonebook. Display the code.

Chat GPT should create the following code:

```
package com.y219.phonebook
import android.os.Bundle
import android.view.View
import android.widget.Button
import android.widget.EditText
import android.widget.LinearLayout
import android.widget.ScrollView
import android.widget.TextView
import androidx.appcompat.app.AppCompatActivity
import androidx.core.view.ViewCompat
import androidx.core.view.WindowInsetsCompat

/** Displays the XML screen and handles the user's Send action. */
class MainActivity : AppCompatActivity() {
    // These references become available after setContentView creates the views.
    private lateinit var requestInput: EditText
```

```
    private lateinit var conversationArea: LinearLayout
    private lateinit var conversationScroll: ScrollView
    // Keep messages so they can survive activity recreation.
    // This is temporary screen state, not a permanent contact database.
    private val messages = arrayListOf<String>()

    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        // Load the XML layout before looking up any of its views.
        setContentView(R.layout.activity_main)
        // Connect Kotlin variables to the IDs defined in activity_main.xml.
        requestInput = findViewById(R.id.requestInput)
        conversationArea = findViewById(R.id.conversationArea)
        conversationScroll = findViewById(R.id.conversationScroll)
        val sendButton = findViewById<Button>(R.id.sendButton)
        // Keep content clear of system bars, display cutouts, and the keyboard.
        // Save the original XML padding so repeated updates do not accumulate
it.
        val root = conversationScroll.parent as View
        val left = root.paddingLeft
        val top = root.paddingTop
        val right = root.paddingRight
        val bottom = root.paddingBottom
        ViewCompat.setOnApplyWindowInsetsListener(root) { view, insets ->
            val safeArea = insets.getInsets(
                WindowInsetsCompat.Type.systemBars() or
                    WindowInsetsCompat.Type.displayCutout() or
                    WindowInsetsCompat.Type.ime()
            )
            view.setPadding(
                left + safeArea.left, top + safeArea.top,
                right + safeArea.right, bottom + safeArea.bottom
            )
            insets
        }
        ViewCompat.requestApplyInsets(root)
        // Restore messages after activity recreation, such as screen rotation.
        // Android restores the input field's state using its stable XML ID.
        savedInstanceState?.getStringArrayList("messages")?.let {
            messages.addAll(it)
        }
        messages.forEach { displayMessage(it) }
        // Run this listener whenever the user taps Send.
        sendButton.setOnClickListener {
            val request = requestInput.text.toString().trim()
            // Ignore empty requests and show an error beside the input field.
            if (request.isBlank()) {
                requestInput.error = "Enter a request first"
                return@setOnClickListener
            }
            addMessage("You: $request")
            requestInput.text.clear()
            // Temporary reply: replace this with contact-management logic.
            // This example does not read, add, or change contacts.
            addMessage("Phone Book: Received your request.")
        }
    }
```


```
    private fun addMessage(message: String) {
        // Save the message, then create the view that displays it.
        messages.add(message)
        displayMessage(message)
    }

    private fun displayMessage(message: String) {
        // Create one TextView for each message in the conversation.
        val messageView = TextView(this).apply {
            text = message
            textSize = 16f // Text size uses scalable pixels (sp).
            // Padding requires pixels, so convert 12dp using screen density.
            val spacing = (12 * resources.displayMetrics.density).toInt()
            setPadding(0, spacing, 0, spacing)
        }
        conversationArea.addView(messageView)
        // Wait until Android lays out the new message before scrolling.
        conversationScroll.post {
            conversationScroll.fullScroll(View.FOCUS_DOWN)
        }
    }

    override fun onSaveInstanceState(outState: Bundle) {
        // Preserve this small conversation when Android recreates the activity.
        // A growing production history should use persistent storage instead.
        outState.putStringArrayList("messages", ArrayList(messages))
        super.onSaveInstanceState(outState)
    }
}
```

Remove all the code from and paste the code generated by ChatGPT. Read all the comments carefully.

Connect your phone to the computer. You should see the phone name on the top bar:




Click the green bug to compile in debug mode and install on the phone. To see the compiler output click the hummer on the toolbar on the left of the screen, If you do not see the hummer, open the menu, and under View select Tools Windows. On the drop down opened click Build.

Note: If the `build.gradle.kts` was changed the green bug is disabled. You have to use the item Sync the Project with the Gradle File (Ctr+shift+O) under the File menu.

After compilation ends the app should open on the phone. Click the SEND button, enter some text and SEND. You should see the output of a stab created temporarily until we code the real functionality.


Let's walk though the code in debug mode. First we set breakpoints at the beginning of all functions. Click on the line number on the first line of code in the function. A red bubble will show over the line number. We should have four breakpoints. Click All Breakpoints under the Run menu option. All the breakpoints are listed on the right window. One the left you can set parameters for the currently selected breakpoint.

Let's add some traces to the log. Add this import is not already included import android.util.Log and add this line as the first line of code in OnCreate function Log.d("MyTrace", "onCreate"). Notice the after typing Log you see a code suggestion. Replace " MainActivity" with "MyTrace" Click tab to accept it. Do this for all functions.



On the lower left side of the screen lick the cat icon. If you don't see it under View?Tool Windows select Logcat. The log window will open. In my case is at the bottom of the screen.


To execute the code click the green bug at the top of the screen. Android Studio will compile the code, install it on your phone and execute it. The execution will start on our first breakpoint. The message we loged will be displayed in the LogCat window.



Click on the bug on the left toolbar. The debug window will open. Hover the cursor over the debug toolbar to familiarize with the buttons. Look for this line

val request = requestInput.text.toString().trim()

and right click on . In the context menu select "Add to Watches"



Click Step Over button on the debug toolbar to browse throw the code. Read the comments carefully. When you get to the last statement of OnCreate function click the Resume program button on the debug toolbar. When onCreate() returns, control goes back to the Android framework, which called it.

6.3 Internationalization

Internationalization prepares an application for different languages and regional conventions. Localization supplies the translations and adaptations for a particular language or region. In Phone Book, we begin by separating the text displayed to users from the code that controls the application.

The project already uses this approach for the application name, request hint, and Send button. The default English text is defined in the resource file below. [strings.xml](C:/Users/gdobr/AndroidStudioProjects/PhoneBook/app/src/main/res/values/strings.xml)

```
<resources>
    <string name="app_name">Phone Book</string>
    <string name="request_hint">Enter a request</string>
    <string name="send_request">Send</string>
</resources>
```

Each string has a resource name that remains consistent across translations. For example, send_request identifies the button label, while Send is its English value.

The screen layout refers to these resource names. The request field uses @string/request_hint, and the button uses @string/send_request. This allows Android to select the appropriate text without changing the layout. (C:/Users/user name/AndroidStudioProjects/PhoneBook/app/src/main/res/layout/activity_main.xml)

```
android:hint="@string/request_hint"
android:text="@string/send_request"
```

To add French, we would create app/src/main/res/values-fr/strings.xml with the same resource names and translated values.

```
<resources>
    <string name="app_name">Répertoire téléphonique</string>
    <string name="request_hint">Saisissez une demande</string>
    <string name="send_request">Envoyer</string>
</resources>
```

Android selects resources according to the active language configuration. When an appropriate translation is unavailable, it uses the default resources. The default values/strings.xml file should therefore contain every string the application needs.

Some text in Phone Book still needs to be moved into resources. MainActivity.kt currently contains these English strings directly in the Kotlin code.
[MainActivity.kt](C:/Users/gdobr/AndroidStudioProjects/PhoneBook/app/src/main/java/com/y219/phonebook/MainActivity.kt)

```
requestInput.error = "Enter a request first"
addMessage("You: $request")
addMessage("Phone Book: Received your request.")
```

To make them translatable, we would add the following entries to the default string resource file.

```
<string name="request_required">Enter a request first</string>
<string name="user_message">You: %1$s</string>
<string name="request_received">Phone Book: Received your
request.</string>
```

The Kotlin code would then retrieve the text through getString().

```
requestInput.error = getString(R.string.request_required)
addMessage(getString(R.string.user_message, request))
addMessage(getString(R.string.request_received))
```

The placeholder %1$s represents the user's request. Keeping the complete message in one resource gives translators control over its wording and the position of the inserted text.

Internationalization also affects layout. Phone Book already declares android:supportsRtl="true" in its manifest and uses direction-aware attributes such as layout_marginStart and gravity="top|start" in its layout. These provide a foundation for languages written from right to left. Translated text may also occupy more space, so the screen should be checked for clipped labels, crowded controls, and alignment problems.

For this feature, testing would include switching between English and French, checking the input hint and button label, triggering the empty-request error, and sending a request. The current activity saves conversation messages as already formatted strings, so existing messages retain their original

wording after a language change. This behavior should be considered when defining the language-switching requirement.

Phone Book currently contains only the default English resources. The French translations and Kotlin changes above illustrate the next implementation step.

6.4 Lifecycle of an activity

Add this code inside the class MainActivity, at the end.

```
override fun onStart() {
    super.onStart()
    Log.d("MyTrace", "onStart")
}
override fun onResume() {
    super.onResume()
    Log.d("MyTrace", "onResume")
}
override fun onPause() {
    super.onPause()
    Log.d("MyTrace", "onPause")
}
override fun onStop() {
    super.onStop()
    Log.d("MyTrace", "onStop")
}
override fun onRestart() {
    super.onRestart()
    Log.d("MyTrace", "onRestart")
}
override fun onDestroy() {
    Log.d("MyTrace", "onDestroy")
    super.onDestroy()
}
```

These callbacks describe an Activity's lifecycle—usually one screen in your app.

Callback	What happens
`onCreate()`	The activity is created. Set up the screen and initial state.
`onStart()`	The activity becomes visible.
`onResume()`	The activity is in the foreground and ready for interaction.
`onPause()`	The activity loses focus. It might still be visible.
`onStop()`	The activity is no longer visible.
`onRestart()`	A stopped activity is about to become visible again.

`onDestroy()` The activity instance is being destroyed.

A typical journey is:

Open the screen:

onCreate → onStart → onResume

Leave for another app:

onPause → onStop

Return to the screen, if the activity is still in memory:

onRestart → onStart → onResume

Finish the screen:

onPause → onStop → onDestroy

These aren't always one continuous sequence. An activity can pause and resume many times. Android can also kill your app's process without calling onDestroy(), so don't rely on it to save important data.

To observe the lifecycle, run the app in Debug mode and filter Logcat using tag:MyTrace. Trace through the callback functions and watch their messages as you open the app, press Home, and return to it. Each callback returns control to the Android framework when it ends.

By default, rotating the phone changes the device configuration. Android destroys the current activity and creates a new instance so it can load the layout and resources appropriate for the new orientation. For a fully resumed activity, you will normally see:

Old activity:

```
onPause

onStop

onDestroy
```

New activity:

```
onCreate

onStart
```

`onResume`

`onCreate()` runs again because Android is initializing a new activity instance. This does not mean the entire app process has restarted. You do not see `onRestart()` in this sequence because the old activity was destroyed rather than reused.

If you also log `onSaveInstanceState()`, you should see that callback during recreation, although its position relative to other callbacks can vary. In your MainActivity, it saves the messages list into a Bundle, and the new activity restores that list in onCreate(). Ordinary member variables are otherwise initialized again, so state must be preserved deliberately—for example, through saved instance state or a ViewModel.

This rotation sequence assumes the activity uses Android's default configuration handling. An activity configured to handle orientation changes itself may behave differently.

Remove all the breakpoints in the MainActivity code. Under Run select View Breakpoints and click on the checkboxes to disable the breakpoints.

Click the green Debug button (the bug icon) at the top of Android Studio to build, install, and run the application in Debug mode. Interact with the app: press Home, switch to another app, return, rotate the phone, and close and reopen the activity. Watch the lifecycle messages in Logcat using the filter tag:MyTrace, and compare the callback sequence for each action.

Click the terminal icon on the lower right of the screen or open the terminal window using the menu. View ?Tool Windows and scroll down to the Terminal option.

Enter

git status

You should see the files newly created. Stage them, commit and push to GitHub

git add .

git commit -m"Implemented the screen layout"

git push -u origin main (after executing this command use on git push)

6.5 Debugging a crash

Before creating the database let see how we handle a crash. We will simulate a crash in the Phone Book app.
Add this line in OnCreate function in MainActivity

```
error("Intentional test crash")

override fun onCreate(savedInstanceState: Bundle?) {
     super.onCreate(savedInstanceState)
        setTheme(R.style.Theme_PhoneBook)
        error("Intentional test crash")    <<<<< line 32
        // Inflate res/layout/activity_main.xml and make it this
activity's screen.
```

Compile and run the application. The app will crash instantly. Open the LogCat and set the filter to com.y219.phonebook. Run the app again. The app will crash immediately. On the LogCat You will see the crash in red.

```
2026-11-08 16:01:36.804 25901-25901 AndroidRuntime          com.y219.phonebook
E  FATAL EXCEPTION: main (Fix with AI)
Process: com.y219.phonebook, PID: 25901
 java.lang.RuntimeException: Unable to start activity
ComponentInfo{com.y219.phonebook/com.y219.phonebook.MainActivity}:
java.lang.IllegalStateException: Intentional test crash
at android.app.ActivityThread.performLaunchActivity(ActivityThread.java:4442)
at android.app.ActivityThread.handleLaunchActivity(ActivityThread.java:4636)
at
android.app.servertransaction.LaunchActivityItem.execute(LaunchActivityItem.java
:222)
at
android.app.servertransaction.TransactionExecutor.executeNonLifecycleItem(Transa
ctionExecutor.java:133)
```

Search for this line

```
Caused by: java.lang.IllegalStateException: Intentional test crash
       at com.y219.phonebook.MainActivity.onCreate(MainActivity.kt:32)
      at android.app.Activity.performCreate(Activity.java:9295)
```

The crash occurred at line 32 in our Main Activity. Remove the code inquestion.


As an exercise, copy and paste the crash log into ChatGPT.

Do not forget to remove the line we added to trigger the crash.

6.6 Conclusion

In this chapter, we learned how to create an Android activity and build the app's first screen, giving it the look and feel we intended.

We followed the development lifecycle for a single feature, from defining and refining the requirement to approving it, designing the solution, implementing it, testing the result, reviewing it, and committing the changes.



Along the way, we practiced using ChatGPT to clarify requirements and develop Kotlin code, and Android Studio to build and test the application. This established a foundation for adding features incrementally, with a clear requirement and a verified result at each step.

Chapter 7. Improving the frontend

7.1 Adding an app exit facility

The requirement to add an Exit button is the following:

Add the text Exit on the upper right corner on the blue ribbon. When the useer tops the text the app should terminate.

Sent it to ChatGPT

- How do you understand this requirement: Add the text Exit on the upper right corner on the blue ribbon. When the use taps the text the app should terminate.

If you are happy with the answer submit

- Implement. Show me the changes I have to make to the code.

ChatGPT generates the following code:

1. Created
[main_menu.xml](C:/Users/user_name/AndroidStudioProjects/PhoneBook/app/src/main/res/menu/main_menu.xml) to display Exit at the right of the ribbon:

```
<?xml version="1.0" encoding="utf-8"?>
<menu xmlns:android=http://schemas.android.com/apk/res/android
    xmlns:app="http://schemas.android.com/apk/res-auto">
    <item
        android:id="@+id/action_exit"
        android:title="@string/exit"
        app:showAsAction="always" />
</menu>
```

On the project window expand the app, right-click res and create a new directory menu. Right-click on the new menu directory, select New and Menu Resource File. On the Filename enter main_menu.xml. Open main_menu.xml and remove all the code and paste the code above. Click the hamburger icon in the app right corner to display the code.

Note: You may get an error When you create this file. The code giving the error is marked in red. Copy the whole block of code into ChatGPT prompt box and add "Why do I get this error".

2. Added to
[strings.xml](C:/Users/gdobr/AndroidStudioProjects/PhoneBook/app/src/main/res/values/strings.xml):

```
<string name="exit">Exit</string>
```

3. Added these imports and methods to [MainActivity.kt](C:/Users/gdobr/AndroidStudioProjects/PhoneBook/app/src/main/java/com/y219/phonebook/MainActivity.kt):

```
import android.view.Menu
import android.view.MenuItem
```

Inside the MainActivity class:

```
override fun onCreateOptionsMenu(menu: Menu): Boolean {
   menuInflater.inflate(R.menu.main_menu, menu)
   return true
}

override fun onOptionsItemSelected(item: MenuItem): Boolean {
    return when (item.itemId) {
        R.id.action_exit -> {
            finishAndRemoveTask()
            true
        }
        else -> super.onOptionsItemSelected(item)
    }
}
```

You can ask for clarifications:

- Where exactly should I insert the new functions. Can you add more detailed comments

Review the code generated and understand its functionality. If you do not understand something ask for help.

- What is this function doing onOptionsItemSelected

When you implemented the code and understand the functionality compile the code clicking the green bug on the top menu. The app will be installed on your connected phone.

To test, open first phone Settings - Apps - Phone Book. The option Force Stop should be enabled. Do not force stop the app. Go back to the app screen and tap the Exit text. The app should be terminated. Go back to Settings - Apps - Phone Book.TheForce Stop should be disabled because the app is not running anymore. Set breakpoints on the new functions and run the test again. Check the logs on CatLog.

Finish this cycle by staging, committing and pushing the code.

7.2 Add an icon and splash screen

Requirement: Add an item and splash screen to the Phone Book project
Prompts:

- Suggest an icon and splash screen and create them
- Add the icon and splash screen to the code

Expected result: ChatGPT creates two images one for the Icon and one for the splash screen. ChatGPT may create a patch file to execute and automatically update the code. At this time we want to update the source code to be able to analyze the change thoroughly. Request the code.

- Please do not create a patch file. Show me the code and how to apply the changes.

Implement: Apply the changes as instructed by ChatGPT. You may have to ask for clarifications.

Note: For one file you will be instructed "Create app/src/main/res/drawable/phone_book_launch_background.xml for Android 11 and earlier:"

Compile: Select Compile PhoneBookApp from build menu. If you get compile errors pass them to ChatGPT for a resolution. Use **both** splash screen sections from the instructions. Android picks the right one automatically.

- I've got the following compile error. Please find a fix [Paste the error here]

Install the app: Click the green bug on in the middle of the top toolbar. The app should be installed and lunch on your phone.

Test: Exit the app. Look the Phone Book icon. Start the app. The splash screen should be displayed before the frontend.

Stage, commit and push

7.3 Add help

Requirement: Add an icon signifying help on the left of the EXIT menu option. When the user taps the icon the system will display an activity consisting of HTML text describing how the app is used.

Pass this requirement to ChatGPT. Add after the requirement "State the requirement. Do not generate code". If you are happy with how ChatGPT understood the requirement we can start implementing. We split the requirement in two parts, create the icon and add the help activity. In my situation ChatGPT rephrased the requirement:

"The Phone Book app shall display a question-mark Help icon immediately to the right of **Exit** in the top app bar. When the user taps the Help icon, the app shall open a dedicated Help activity that displays formatted HTML instructions explaining how to use Phone Book."

Let's implement the fist part.

- Implement The Phone Book app shall display a question-mark Help icon immediately to the left of **Exit** in the top app bar. Do not create a patch file. Display the code with instructions

Follow the instruction and update the code.

Compile → Install → Test → Stage → Commit → Push

Now let's implement the second part, add functionality to the icon.

- When the user taps the Help icon, the app shall open a dedicated Help activity that displays formatted HTML instructions explaining how to use Phone Book. Do not create a patch file. Display the code with instructions

We will create an activity to display HTML text. You can update the help content without touching the Kotlin code.

First let's create the HTML file. In `C:\Users\gdobr\AndroidStudioProjects\PhoneBook\app\src\main\res`, create a create Android Resource Directory named raw if it doesn't already exist. Select Resource Type row. Inside it, create `phone_book_help.htm`. To see the code click hamburger icon on the right side of the file name. Remove the code from the new file and paste.

Now we create the Help Activity to display the HTML help content. These are the steps for creating an activity:

Create the source code file. Right-click on com.y219.phonebook and select New → Kotlin Class/File. Name the file HelpActivity.kt.

7.4 GitHub

GitHub provides a web-based interface for viewing and managing the files stored in a Git repository. Once the Phone Book project has been uploaded (pushed) to GitHub, you can browse its source code, examine individual files, review changes, and access previous versions without opening Android Studio.

7.4.1 Accessing the Repository

1. Open your web browser and go to https://github.com.
2. Sign in using your GitHub account.
3. Click your profile picture in the upper-right corner and select Your repositories.
4. Locate and click the Phone Book repository .
5. GitHub displays the repository's main page, showing its folders and files.

7.4.2 Browsing the Project Files

The repository's Code tab displays the directory structure of the Phone Book project, similar to the Project view in Android Studio.

Click a folder to open it and view its contents. Click a file to display its contents directly in your browser.

For example, you can navigate to:

`app/src/main/`

This folder contains important Android application files, including `AndroidManifest.xml` and the directories containing Kotlin source code and application resources.

You can also open the project's `Documentation` folder to review requirements and other documentation stored alongside the source code.

Use the navigation links above the file listing to return to parent folders.

7.4.3 Viewing File History

GitHub maintains a history of changes committed to the repository.

To examine the history of a particular file, open the file and select History from the file toolbar or menu. GitHub displays the commits affecting that file, including their dates and commit messages.

You can select an individual commit to examine the changes made to the file. Added lines are generally highlighted in green, while deleted lines are highlighted in red.

To review the history of the entire repository, return to the repository's main page and click the Commits link.

7.4.4 Downloading the Project

You can download a copy of the Phone Book repository directly from GitHub:

1. Open the repository's main page.
2. Click the green Code button.
3. Select Download ZIP.
4. Extract the downloaded ZIP file to a folder on your computer.

This creates a local copy of the repository files. However, the downloaded ZIP does not contain the Git history or the information needed to synchronize changes with GitHub. For ongoing development, use Git to clone the repository instead.

7.4.5 Keeping GitHub Up to Date

GitHub displays the latest version of the project that has been pushed to the selected branch. Changes made locally in Android Studio do not automatically appear on GitHub.

To publish your latest changes, you must commit them using Git and then push the commits to GitHub.

GitHub serves as an online record of the Phone Book project, allowing you to inspect source code, review development history, and retrieve earlier versions when necessary.

7.5 Conclusion

Our app now has a complete front end with a menu and built-in help. In this chapter, we learned how to create an activity for a new screen and add a menu item that opens it. We also learned how to write an HTML help page and make it available within the app so users can find instructions when they need them.

We can now use ChatGPT to help us create activities, build menus, design icons, and draft help content in HTML. We can apply these same techniques when we add another feature to this app or build an interface for a new one.

Chapter 8. Creating the database

8.1 Create the local contact database

We defined the database architecture in our requirements documentation. Now we have to create this database. ChatGPT has the database in its context so we can just as it fo create the database DDS. The database table contacts will have the these columns: `ID`, `name`, `phone number`, `email`, `address`, `note`, and an automatically maintained `UTC timestamp`.

- Create the DDS for our database

ChatGPT creates the following code:

```
-- PhoneBook SQLite data definition script, version 1.
-- update_utc stores milliseconds since the Unix epoch.
BEGIN;

CREATE TABLE phone_book_entries (
 entry_id INTEGER PRIMARY KEY,
    update_utc INTEGER NOT NULL DEFAULT (
        CAST(strftime('%s', 'now') AS INTEGER) * 1000
        + CAST(substr(strftime('%f', 'now'), 4, 3) AS INTEGER)
    ),
    first_name TEXT,
    last_name TEXT,
    phone_number TEXT,
    email TEXT,
    street_address TEXT,
    apartment TEXT,
    city TEXT,
    state TEXT,
    zip_code TEXT,
    note TEXT
|);

CREATE TRIGGER phone_book_entries_update_utc
AFTER UPDATE OF first_name, last_name, phone_number, email,
street_address,
    apartment, city, state, zip_code, note
ON phone_book_entries
FOR EACH ROW
BEGIN
    UPDATE phone_book_entries
    SET update_utc = CAST(strftime('%s', 'now') AS INTEGER) * 1000
        + CAST(substr(strftime('%f', 'now'), 4, 3) AS INTEGER)
    WHERE entry_id = NEW.entry_id;
END;

COMMIT;
```

We will not use this DDS to create our table. The database will be implemented in Android using Room. Room will create the actual SQLite database file on the device the first time the app opens the database.

8.1.1 Room

Room is the Android library that connects your Kotlin code to a local SQLite database. SQLite stores the rows on the device. Room creates the tables from your Kotlin definitions, checks SQL queries when you build the app, and turns query results into Kotlin objects.

8.1.2 The three pieces in Phone Book

Room piece	What it does in Phone Book
Entity (`@Entity`)	`PhoneBookEntry` describes the `phone_book_entries` table. Each Kotlin object represents one row. The `entry_id` primary key distinguishes two people who share the same name.
DAO (`@Dao`)	`PhoneBookDao` defines operations such as `insert(entry)` and `findByName(firstName, lastName)`. Room generates the implementation.
Database (`@Database`)	`PhoneBookDatabase` lists the entities, declares the schema version, and gives the app access to the DAO. Room creates the database file on first use.

8.1.3 What happens when you search

If you type **"Find Jane Smith,"** the request processor extracts `Jane` and `Smith` and calls `findByName("Jane", "Smith")`. Room passes those values to a SQL query and returns a `List<PhoneBookEntry>`. The chat can then display zero, one, or several matches. A `suspend` DAO function lets the app wait for that result without blocking the screen.

8.1.4 Where the DDS fits

The [DDS] is only our schema reference. We'll translate its columns and primary key into the entity. The `update_utc` trigger needs separate handling because declaring a field in the entity doesn't install a SQLite trigger.

For the first implementation, we can define those three pieces, insert one test entry, close and reopen the database, and look it up by name. That verifies persistence before we connect it to the chat.

Setting up Room in Phone Book has two parts. **Gradle makes Room available to your app. Your Kotlin files tell Room what to build.**

8.1.5 Connect Room to Gradle

The changes from the previous message go into three files, each with a different job.

File	What it does
`gradle/libs.versions.toml`	Lists the Room and KSP versions and gives them names you can reference from Gradle.
Project-level `build.gradle.kts`	Declares the KSP plugin with `apply false` so the app module can apply it.
`app/build.gradle.kts`	Applies KSP, adds the Room runtime and compiler, and sets the folder for exported schemas.

The **Room runtime** provides the classes your Kotlin code imports and uses. **KSP** runs the Room compiler during the build. The compiler checks your DAO queries against the entity and generates the code that reads and writes SQLite rows.

- **`PhoneBookEntry.kt`** defines the `phone_book_entries` table and its columns.
- **`PhoneBookDao.kt`** defines what the app can do with those rows, such as inserting an entry or finding entries by name.
- **`PhoneBookDatabase.kt`** registers the entity, exposes the DAO, and installs the timestamp trigger when the database is created.

The DDS is your schema reference. Room gets its table definition from the entity and its trigger from the database callback.

8.1.6 3. Sync, build, then open the database

Sync tells Android Studio to load the Gradle configuration and dependencies. This is the step that should clear the unresolved `room` and `sqlite` imports. **Build** runs the Room compiler and checks that the entity, DAO, and database fit together. **Opening the database on the device**, for example by making the first DAO call, is what creates `phonebook.db`.

8.2 Seting up the project for Room

First expend Gradle Scripts, open `libs.versions.toml` and add these lines under the existing `[versions]` heading:

```
room = "2.8.4"
ksp = "2.3.10"
```

Under `[libraries]`, add:

```
androidx-room-runtime = { group = "androidx.room", name = "room-
runtime", version.ref = "room" }

androidx-room-compiler = { group = "androidx.room", name = "room-
compiler", version.ref = "room" }
```

Under `[plugins]`, add:

```
ksp = { id = "com.google.devtools.ksp", version.ref = "ksp" }
```

In the build.gradle.kts (Project: Phone_Bool), add this line inside `plugins { }`:

```
alias(libs.plugins.ksp)
```

In the build.gradle.kts(Module: app) add this line inside `plugins { }`:

```
alias(libs.plugins.ksp)
```

Add these lines inside `dependencies { }`:

```
implementation(libs.androidx.room.runtime)
sp(libs.androidx.room.compiler)
```

Add this block **above** `dependencies { }` to configure schema export:

```
ksp {
    arg("room.schemaLocation",
layout.projectDirectory.dir("schemas").asFile.absolutePath)
}
```

ChatGPT will generate all the Kotlin code for us.

- Generate Entity file (`@Entity`)

Go to the project window expend app konlin+java and write-click on com.y219.com . Select New Kotlin Class/File and enter `PhoneBookEntry.kt` as the file name. Remove the skeleton code from the file and paste the code generated by ChatGPT.

The column names and nullable fields follow the [DDS](C:/Users/gdobr/AndroidStudioProjects/PhoneBook/Documentation/PhoneBook.dds.sql). When you insert an entry with `entryId = 0`, Room lets SQLite assign the ID.

This example uses **Room 2.x** imports. Your project needs the Room dependencies before it will compile. The entity defines the timestamp column and its insert default. Install the trigger separately when you set up `PhoneBookDatabase` so edits also refresh the timestamp.

- Generate DAO file (`@Dao`)

Create a Kotlin Class/File named `PhoneBookDao.kt` and insert the code generated by ChatGPT. `insert` returns the new entry's ID. `findByName` matches both names exactly, including capitalization, and returns all matching entries. `update` and `deleteById` target an entry by its ID and return the number of rows affected.

- Generate Database (`@Database`)

Create a Kotlin Class/File named `PhoneBookDatabase.kt` and copy the code generated by ChatGPT.

Get the DAO with `PhoneBookDatabase.getInstance(context).phoneBookDao()`. Room creates `phonebook.db` on the device when it first opens the database. The `onCreate` callback installs the timestamp trigger from the [DDS](C:/Users/gdobr/AndroidStudioProjects/PhoneBook/Documentation/PhoneBook.dds.sql).

This uses the same Room 2.x APIs as the entity and DAO. When you add Room to Gradle, configure its schema output directory so `exportSchema = true` can save the version 1 schema for future migrations.

Run Sink Project with Gradle file , then compile the project. If you get any errors it means most likely you didn't follow the instruction correctly. Review the code and if you do not find the problem pass the error to ChatGPT and follow the instructions.

8.3 Testing the new code

Right-click on com.y219.phonebook (Android test and crete a new file `PhoneBookDatabaseTest.kt` Paste this code:

```
package com.y219.phonebook

import androidx.room.Room
import androidx.test.ext.junit.runners.AndroidJUnit4
import androidx.test.platform.app.InstrumentationRegistry
import kotlinx.coroutines.runBlocking
import org.junit.Assert.assertEquals
import org.junit.Assert.assertTrue
import org.junit.Test
import org.junit.runner.RunWith

@RunWith(AndroidJUnit4::class)
class PhoneBookDatabaseTest {

    @Test
    fun insertEntryAndFindItByName() {
        val context =
```

```
InstrumentationRegistry.getInstrumentation().targetContext
        val database = Room.inMemoryDatabaseBuilder(
            context,
            PhoneBookDatabase::class.java
        ).build()

        try {
            runBlocking {
                val dao = database.phoneBookDao()
                val entryId = dao.insert(
                    PhoneBookEntry(
                        firstName = "Jane",
                        lastName = "Smith",
                        phoneNumber = "+1 202-555-0101"
                    )
                )

                val matches = dao.findByName("Jane", "Smith")

                assertTrue(entryId > 0)
                assertEquals(1, matches.size)
                assertEquals(entryId, matches[0].entryId)
                assertEquals("+1 202-555-0101", matches[0].phoneNumber)
                assertTrue(dao.findByName("Jane", "Jones").isEmpty())
            }
        } finally {
            database.close()
        }
    }
}
```

In Android Studio, start an emulator or connect an Android device. Open the test file we've just created, click the **green run arrow** next to `insertEntryAndFindItByName`, and choose **Run**. A passing test confirms that Room assigned an ID, the DAO found the saved entry by name, and a different name returned no matches.

The test uses a fresh in-memory database, so the sample entry disappears when the test ends. It exercises the entity and DAO. Testing persistence across app restarts and the timestamp trigger requires opening the app's file-backed database through `PhoneBookDatabase.getInstance(...)`.

ON the lower right side of the screen you should see the Text Window. If the window is not open, in the Tools Windows under View menu click Run. The window will open showing the test results. You should see a green check next to `insertEntryAndFindItByName`.

8.4 Wire up contact lookup

Connect the existing **Send** button to the Room DAO through a ViewModel and a request processor. This first version accepts `Find Jane Smith` and shows every matching entry in the conversation. The existing DAO matches names exactly, including capitalization.

8.4.1 1. Add the lifecycle dependencies

Paste these two lines inside `dependencies { }` in build.gradle.kts(Mpdule: app), then sync Gradle. The ViewModel runs the lookup, and the activity collects replies while its screen is active.

```
implementation("androidx.lifecycle:lifecycle-runtime:2.10.0")
implementation("androidx.lifecycle:lifecycle-viewmodel:2.10.0")
```

8.4.2 Create `PhoneBookRequestProcessor.kt`

Create this file in `com.y219.phonebook`.The processor extracts the first and last names, calls the DAO, and formats the result.

Paste this code inside the file. Don't forget to remove the skeleton code generated when the file was created.

```
package com.y219.phonebook

class PhoneBookRequestProcessor(private val dao: PhoneBookDao) {
    private val findCommand = Regex(
        """find\s+(\S+)\s+(\S+)""",
        RegexOption.IGNORE_CASE
    )

    suspend fun process(request: String): String {
        val match = findCommand.matchEntire(request)
            ?: return "Enter a first and last name, for example: Find
Jane Smith."

        val (firstName, lastName) = match.destructured
        val entries = dao.findByName(firstName, lastName)

        if (entries.isEmpty()) {
            return "No entries found for $firstName $lastName."
        }

        val numbers = entries.joinToString("\n") { entry ->
            entry.phoneNumber?.takeIf { it.isNotBlank() }
                ?: "No phone number on file"
        }

        return "$firstName $lastName (${entries.size} found)\n$numbers"
```

```
    }
}
```

8.4.3 3. Create `PhoneBookViewModel.kt`

Put it in the same package. The ViewModel keeps an in-progress lookup alive if the activity is recreated, such as when you rotate the device.

```
package com.y219.phonebook

import android.app.Application
import android.database.sqlite.SQLiteException
import android.util.Log
import androidx.lifecycle.AndroidViewModel
import androidx.lifecycle.viewModelScope
import kotlinx.coroutines.channels.Channel
import kotlinx.coroutines.flow.receiveAsFlow
import kotlinx.coroutines.launch

class PhoneBookViewModel(application: Application) :
AndroidViewModel(application) {
    private val processor by lazy {
        val dao =
PhoneBookDatabase.getInstance(application).phoneBookDao()
        PhoneBookRequestProcessor(dao)
    }

    private val replyChannel = Channel<String>(Channel.BUFFERED)
    val replies = replyChannel.receiveAsFlow()

    fun submit(request: String) {
        viewModelScope.launch {
            val reply = try {
                processor.process(request)
            } catch (error: SQLiteException) {
                Log.e("PhoneBook", "Phone book lookup failed", error)
                "The phone book could not be read. Please try again."
            }

            replyChannel.send(reply)
        }
    }

}
```

8.4.4 Connect the Send button in `MainActivity.kt`

Add these imports:

```
import androidx.lifecycle.Lifecycle
import androidx.lifecycle.ViewModelProvider
import androidx.lifecycle.lifecycleScope
import androidx.lifecycle.repeatOnLifecycle
import kotlinx.coroutines.flow.collect
import kotlinx.coroutines.launch
```

In `onCreate`, immediately **after** `messages.forEach { displayMessage(it) }`, paste:

```
val phoneBookViewModel =
ViewModelProvider(this)[PhoneBookViewModel::class.java]

lifecycleScope.launch {
    repeatOnLifecycle(Lifecycle.State.STARTED) {
        phoneBookViewModel.replies.collect { reply ->
            addMessage("Phone Book: $reply")
        }
    }
}
```

Inside the existing Send listener, replace the demonstration reply and its two comments with:

```
phoneBookViewModel.submit(request)
```

8.4.5 Try it on the emulator

1. Run the app, enter `Find Jane Smith`, and tap **Send**. On an empty database, expect `No entries found for Jane Smith.` This also opens `phonebook.db`.
2. In Android Studio's **Database Inspector**, open a query tab for `phonebook.db` and run this once:

```
INSERT INTO phone_book_entries (first_name, last_name, phone_number)
               VALUES ('Jane', 'Smith', '+1 202-555-0101');
```

Send `Find Jane Smith` again. Expect `Jane Smith (1 found)` followed by `+1 202-555-0101`. The earlier in-memory test data disappears when its test ends, so this step adds a row to the database the app actually uses.

This first command accepts a single-word first name and a single-word last name. I checked the snippets against your current source files. They still need a build and emulator run after you paste them.

How to paste the SQL into the **New Query** tab inside Android Studio's **Database Inspector**.

1. **Run Phone Book** on an emulator or device with Android API 26 or higher. In the app, send `Find Jane Smith` once. This opens `phonebook.db`, even if the lookup finds no entries.
2. In Android Studio, go to **View → Tool Windows → App Inspection**, then select **Database Inspector**.

3. Select the running `com.y219.phonebook` process. In the **Databases** window, look for `phonebook.db`.
4. Click **Open New Query Tab** at the top of the Databases window. Select `phonebook.db` in the query tab if prompted.
5. Paste this into the **text field at the top of the New Query tab**, then click **Run** once.

   ```
   INSERT INTO phone_book_entries (first_name, last_name, phone_number)
       VALUES ('Jane', 'Smith', '+1 202-555-0101');
   ```

Return to the app and send **`Find Jane Smith`** again. You should see **`+1 202-555-0101`** in the reply.

8.4.6 Verify the lookup flow

Run Phone Book on the emulator and keep **Database Inspector** open. Start with one Jane Smith entry in `phonebook.db` from the previous step.

Enter in Phone Book and tap Send	Expected reply
`Find Jane Smith`	`Jane Smith (1 found)` and `+1 202-555-0101`
`Find Jane Jones`	`No entries found for Jane Jones.`
`Find Jane`	A prompt to enter a first and last name

Next, verify that two people can share the same name. In **Database Inspector → New Query**, select `phonebook.db` and run this once:

```
INSERT INTO phone_book_entries (first_name, last_name, phone_number)
    VALUES ('Jane', 'Smith', '+1 202-555-0102');
```

Send `Find Jane Smith` again. Expect `Jane Smith (2 found)` with both phone numbers on separate lines.

Finally, stop and relaunch the app, then repeat the lookup. Both numbers should still appear. That confirms the lookup reaches the file-backed database and the entries survive an app restart.

8.4.7 Wire up adding, editing, and deleting

Prompt

> ➢ Wire up adding, editing, and deleting phone book entries. Give me the code to paste and tell me where to put it.

Follow the instruction.

8.5 Exercies

Find, Add, Edit, and Delete cover the core of Phone Book. Once you've verified all four on the emulator, add these in order:

1. **Update the in-app Help.** Show the four command formats and explain how to find an entry's ID before editing or deleting it.
2. **Confirm deletions.** Show the name and phone number for the selected ID, then ask the user to confirm. This matters when two people share a name.
3. **Make lookup more forgiving.** Support case-insensitive searches and partial names so users can find an entry even when they don't remember the exact spelling or capitalization.
4. **Expose the fields already in the database.** Start with viewing and editing email, address, and notes if you want Phone Book to store more than names and numbers.

Create the appropriate prompts → Create prompts to ask ChatGPT to esplain the code → update the source code → test →stage → commit →push

Chapter 9. Connect Phone Book to OpenAI

When you ask Phone Book “What’s Jane Smith’s number?”, the Android app sends your question to a small Node.js server running on your Windows development machine. The server calls OpenAI to extract the first and last name, then returns the name or asks the app to request clarification. Phone Book searches its local Room database for the saved number. The API key stays on the server, and saved contacts stay on the device.

9.1 Get an API key and start the server

Sign in to the OpenAI Platform, select your project, and create a secret API key. Copy the key when it’s displayed.

```
If you Hve a phone connected run this in the terminal:

$adb = "$env:LOCALAPPDATA\Android\Sdk\platform-tools\adb.exe"
& $adb -d reverse tcp:8787 tcp:8787

.\gradlew.bat :app:assembleDebug "-
PphoneBookInterpretationUrl=http://127.0.0.1:8787/interpret"

& $adb -d install -r .\app\build\outputs\apk\debug\app-debug.apk
```

This will enable the phone connected through a USB to reach the server.

With Node.js 20 or later installed, open a terminal in Android Studio at the PhoneBook project root. Run the following commands and paste your key at the hidden prompt.

On Windows

```
$key = Read-Host 'OpenAI API key' -AsSecureString
$env:OPENAI_API_KEY = [System.Net.NetworkCredential]::new('',
$key).Password
node server/interpret.mjs
```

On linux and Mac

```
printf 'OpenAI API key: '
IFS= read -rs OPENAI_API_KEY
printf '\n'
export OPENAI_API_KEY
node server/interpret.mjs
```

You should see this output

```
PS C:\Users\gdobr\AndroidStudioProjects\PhoneBook>
C:\Users\gdobr\AppData\Local\Temp\pasted-image-.pn^C
```

```
PS C:\Users\gdobr\AndroidStudioProjects\PhoneBook> $key = Read-Host
'OpenAI API key' -AsSecureString
OpenAI API key: ********************
PS C:\Users\gdobr\AndroidStudioProjects\PhoneBook> $env:OPENAI_API_KEY =
[System.Net.NetworkCredential]::new('', $key).Password
PS C:\Users\<your ueer name>\AndroidStudioProjects\PhoneBook> node
server/interpret.mjs
PhoneBook interpreter is listening on 127.0.0.1:8787.
```

Leave the terminal open once the server reports that it's listening on `127.0.0.1:8787`. The server uses `gpt-4.1-mini` by default. To use a different model that supports Structured Outputs, set `OPENAI_MODEL` in the same terminal before starting the server.

9.2 Try a lookup in the Android Emulator

Run the Android debug build in the emulator or phone. It already uses `http://10.0.2.2:8787/interpret`, where `10.0.2.2` is the emulator's address for reaching the server on your development machine.

1. Send `Add Jane Smith +1 202-555-0101`.
2. Ask `What's Jane Smith's number?` Phone Book should display the saved number and entry ID.
3. Stop the server with **Ctrl+C** and ask the same question again. Phone Book should report that natural-language lookup is unavailable and show the `Find` command.
4. Send `Find Jane Smith` to confirm that the saved entry is still available offline.

9.3 Connect from a physical phone or release build

Host the interpretation service behind an HTTPS gateway that controls access and limits request rates. Point the Android build to that endpoint using the Gradle property below.

```
-PphoneBookInterpretationUrl=https://your-host.example/interpret
```

A release build without a configured endpoint still supports offline commands such as `Add` and `Find`.

PART TWO - DEVELOPING WITH CODEX

In Part One, you built Phone Book and practiced defining requirements, designing a database, and testing features one at a time. In Part Two, you'll use Codex to build Captain's Log. The Android app lets you record voyages, stops, and observations aboard.

Start with a local database that links voyages, stops, and entries. Then add supporting documents, pictures and semantic search. At each stage, review the code Codex generates and test it against sample voyages. For the search feature, check that a phrase such as "we moved after dark" can find the original entry about re-anchoring after sunset.

Chapter 10. Using ChatGPT for Software Market Research

Before developing a new software application, it is important to understand the market, identify potential users, evaluate competing products, and determine whether there is a genuine need for the proposed application.

Traditionally, market research required considerable time searching websites, reading product reviews, participating in discussion forums, and comparing competing applications. ChatGPT can significantly simplify and accelerate this process.

10.1 Researching the Market with ChatGPT

ChatGPT can search the internet, examine competing applications, summarize customer feedback, and identify common complaints and missing features. It can also help evaluate pricing models, target audiences, and opportunities for product differentiation.

One particularly valuable source of information is online discussion forums, where users share their experiences, frustrations, and suggestions. These discussions can reveal practical requirements that may not be obvious from competitors' product descriptions.

For Captain's Log, you'll research digital boat logs and voyage journals. Look at how skippers record observations underway and how they find those notes when they return to a location months later.

- Research digital boat logs and voyage journals for Android and desktop. Identify their supported platforms, offline features, search capabilities, export options, pricing, and recurring complaints. Include links to product pages, documentation, and the user discussions you consulted. Mark details you could not verify.

ChatGPT can organize the findings into a market research report.

10.2 Analyzing Competing Applications

Once potential competitors have been identified, ChatGPT can help compare their capabilities and identify opportunities for improvement.

Include boat logbooks and voyage journals in the comparison. Where a charting application also offers a logbook, compare its logging and retrieval features with the standalone products.

- Compare the products in a table. For each, show how a skipper records a stop offline, attaches notes or photos, finds an earlier visit, and exports or synchronizes the log. Cite the source for each feature and identify gaps that Captain's Log could address.

The results can help determine which features are essential, which are optional, and where improvements might provide a competitive advantage.

10.3 Turning Market Research into Requirements

Market research becomes especially useful when its findings influence application design.

ChatGPT can help translate user complaints and feature requests into proposed software requirements.

Based on the verified research, propose requirements for Captain's Log. Separate the first release from later enhancements. Include acceptance criteria for recording a stop offline, retrieving an observation by meaning, and opening its original log entry.

These recommendations should be reviewed before being incorporated into the application's formal requirements. Not every requested feature is practical, and unnecessary functionality can increase development costs and complexity.

10.4 Understanding the Limitations

Although ChatGPT is a powerful research assistant, its findings should not be accepted without verification. Online reviews may be outdated, individual opinions may not represent the broader market, and product features and prices can change.

Ask ChatGPT to provide links to its sources, distinguish verified facts from interpretations, and identify information that could not be confirmed.

Most importantly, market research conducted with ChatGPT does not replace direct feedback from potential customers. Interviews, demonstrations, prototypes, and user testing remain valuable ways to validate demand.

Chapter 11. Prepare the development environment

In addition to the development tools introduced in Part One, we'll need a few more for Part Two.

11.1 Visual Studio Code

Visual Studio Code (VS Code) is a free, open-source-based code editor developed by Microsoft. It is available for Windows, Linux, and macOS.

VS Code supports many programming languages, including Python, JavaScript, Kotlin, and SQL. It provides features such as syntax highlighting, code completion, debugging, and integrated Git support.

Additional functionality can be installed through extensions, including tools for working with remote Linux servers using SSH.

In this book, VS Code can be used to develop and maintain server-side applications, edit configuration files, and manage source code.

? What is VS Code

? What are the requirements for an VS Code installation

? How do I install VS Code

? How do I verify my VS Code installation

? Give me a short preview on VS Code

11.2 Android Studio

create a new project See partone….

11.3 Codex

Codex is OpenAI's coding agent. When you open a project in Codex, it can read the source files it has access to, explain how the code works, edit files, and run build and test commands. In Part Two, you'll use it to design, implement, and test **Captain's Log** one feature at a time.

Open your project. Sign in to the ChatGPT desktop app, select Codex, and open the Captain's Log project folder. Start by asking Codex to explain how the project is organized and how to build and run it.

1. **Describe one feature at a time.** Tell Codex what the user should be able to do, which part of the app is involved, and how you'll know the feature works. For a change that touches several parts of the app, ask Codex to inspect the code and propose a plan before editing.
2. **Put recurring instructions in `AGENTS.md`.** This plain-text file gives Codex project guidance it can use across tasks. Include information such as where the interface and database code live, how to run tests, and which project conventions to follow.
3. **Review the changes and verify the behavior.** Read the *diff*, which shows what Codex added, removed, or changed. Ask it to explain unfamiliar syntax, libraries, or design choices. Check which tests actually ran and what they covered, then try the feature yourself in the application. You're responsible for understanding the code and deciding whether it's ready to keep.

Note: Codex may occasionally suggest additional prompts or follow-up actions. They show up in deemed text in the prompt edit box. While these suggestions can be helpful, they may not always align with your objectives, priorities, or intended development approach. Review them carefully before accepting them. You are in control of the development process, not Codex.

Create a new project name Captain's Log. Add the folder ….******* Create the Project instruction Appendix ******(

Note: Codex is available for free, but its usage limits may prevent you from working continuously, potentially disrupting the learning process. If you already have a ChatGPT Plus subscription, its included usage may be sufficient. However, if you frequently reach these limits, you may need to purchase additional credits to continue working without interruption.

11.4 SSH clients

An SSH (Secure Shell) client allows you to securely connect to a remote Linux server and execute commands as if you were working directly on the server. Windows, Linux, and macOS include built-in SSH clients. However, one of the most widely used SSH clients is PuTTY, a free, open-source application available for Windows and other platforms. SSH connections sometimes disconnect because of network interruptions or inactivity timeouts. PuTTY provides a keepalive feature that periodically sends messages to the server to help prevent disconnections caused by inactivity. ¬ What is Putty ¬ Does putty work on Linux and Mac ¬ How to Install PuTTY on Windows ¬ How to Install PuTTY on Linux ¬ How to Install PuTTY on Mac ¬ How do I keep a connection alive in Putty ¬ How do I use Putty ¬ How do I use the Windows SSH Client ¬ How do I use the Linux SSH Client ¬ How do I use the Mac SSH Client 1.1.4 FileZilla FileZilla is a free, open-source application used to

11.5 FileZilla

FileZilla is a free, open-source application used to transfer files between your computer and a remote server. It provides a graphical interface for uploading, downloading, copying, deleting, and managing files.

FileZilla Client is available for Windows, Linux, and macOS. It supports several file transfer protocols, including SFTP (SSH File Transfer Protocol), which allows secure file transfers between your computer and a Linux server.

FileZilla is particularly useful for transferring application files, scripts, and configuration files between your development computer and the server.

- How do I install FileZilla
- Give me a quick start with FileZilla

Chapter 12. Getting Started

Chapter 13. Understanding the Project

Chapter 14. The Development Process

Chapter 15. Requirements

Chapter 16. Design

Chapter 17. The Front End

Chapter 18.The Back End

Chapter 19. The Linux Server

Chapter 20. Testing

Conclusion

ChatGPT can transform market research from a lengthy manual process into an interactive investigation. Developers can explore competing products, analyze user experiences, identify unmet needs, and refine their application concepts through natural-language prompts.

By conducting market research early in the development process, programmers can make better design decisions, prioritize useful features, and reduce the risk of building software that does not address real user needs.

The objective is not simply to develop an application that works, but to develop one that people actually want to use.

Chapter 21.Publishing Your App on Google Play

Once your Android app works on a test phone, you can use **Google Play Console** to share it with testers and prepare it for public release. You'll build a signed release in Android Studio, create a store listing, and submit the app for Google's review.

21.1 Set up a developer account

Register for a personal or organization account, pay the one-time US$25 registration fee, and complete the verification steps shown in Play Console. New personal account owners also need to verify access to an Android device. Google Play account setup

21.2 Build a signed release

In Android Studio, generate a release **Android App Bundle** (`.aab`) and sign it with your upload key. Keep the key and its password secure for future uploads. With **Play App Signing**, Google signs the installable versions it delivers to users. As of November 2026, new Android phone apps and updates must target Android 16 (API level 36) or higher. Android app signing · Google Play target API requirements

21.3 Prepare your store listing and app disclosures

Create the app in Play Console and add its name, description, icon, screenshots, and support email. Complete the App content declarations, including the content rating, target audience, ads, and Data safety form. Provide a privacy policy. For **Phone Book**, describe how saved entries stay on the device and how natural-language questions are sent to an online service for interpretation. Check that your disclosures match what the release actually sends. Store listing setup · App review preparation · Data safety guidance

21.4 Test the build distributed through Google Play

Use internal testing to share the build with a small group. For Phone Book, have testers add an entry, reopen the app with networking disabled, and confirm they can still find it. Personal developer accounts created after November 13, 2023, must also run a closed test with at least **12 testers opted in continuously for 14 days** before applying for production access. Google Play testing requirements

21.5 Submit your production release

Choose the countries and regions where the app will be available, add release notes, and submit the release for review. Check **Publishing overview** for its status. After launch, use **Android vitals** to track crashes and responsiveness problems reported by users' devices. Release and rollout guide · Android vitals

Try this prompt in ChatGPT

- I'm preparing my first Android app for Google Play. I use Android Studio [version] and have a [personal or organization] Play Console account. Using current Google documentation, walk me through generating a signed app bundle, uploading it to a testing track, and preparing for production review. Tell me which steps depend on my account type.

PART THREE - BLACK BOX DEVELOPMENT

Chapter 22.Black Box Development concept


22.1 Concept

Black Box Development starts from a premise: the code generated by ChatGPT and other large language models is correct and needs no human review. For this book, we take that as an assumption in 2027. My prediction is that it will soon become a fact. As AI produces more code, reviewing every line by hand will become impractical. Doing so would also eat into the time saved by generating the code in the first place.

Many programmers will become application designers. Few people will need to understand the code AI generates, much as few programmers today need to understand the machine code their compilers produce.

There will still be plenty of work for systems programmers who use assembly language, C, and C++ to build operating systems, device drivers, compilers, and other development tools.

Under that premise, software development becomes simpler. The software designer writes clear, detailed requirements and tests each feature and the application as a whole against them. The AI writes, reviews, and optimizes the code, runs unit tests, and checks for and fixes security vulnerabilities.



Captain's Log — Requirements, Testing will be a single document organized by feature. Each feature will have a stable ID, its requirements, a copy-ready implementation prompt, and a test with steps and expected results. A feature can have multiple test cases when its normal flow and edge cases need separate checks.

Chapter 23. Applications Design

Requirements gathering will continue using the current process. Once enough information has been collected to define the features and their expected behavior, work will begin on a single **Requirements, Prompting, and Testing** document. Each feature will include its requirements, an implementation prompt, and at least one test case with steps and expected results.

The project will use this combined document in place of a separate Software Requirements Specification (SRS) , Software Design Document (SDD) and Test Plan

Here is an example of a feature in this document.

23.1 CL-033 — Daily Log day navigation

Feature ID
CL-033

Feature
Move between calendar days in Captain's Log using **Previous day** and **Next day**.

Requirements

- **CL-033-R1** — Each control shall move exactly one calendar day from the displayed date, including across month and year boundaries.
- **CL-033-R2** — If the destination day has a saved entry, the app shall open it. Otherwise, the app shall open an editable draft for that date.
- **CL-033-R3** — The app shall require the user to save or discard unsaved changes before leaving the current day. An untouched draft may be left without saving when no choice is pending.

Implementation prompt

Implement Previous day and Next day controls in the main Daily Log view. Use the displayed journal date as the starting point and reuse the existing day-opening flow. Load a saved entry when one exists. Otherwise, open an editable draft dated for the destination day. Apply the existing Save and Discard rules before navigation and allow the user to leave an untouched draft when no choice is pending.

Test CL-033-T01 — Navigate across a month boundary and protect unsaved edits

Setup
Save a Daily Log entry for May 31. Leave June 1 without a saved entry.

Step	Action	Expected result

1	Open May 31 and tap **Next day**.	An editable draft opens for June 1.
2	Tap **Previous day** without editing the draft.	The saved May 31 entry opens.
3	Tap **Next day** and enter a note. Then try to go back to May 31.	The June 1 draft and its note remain visible. The app requires the user to save or discard the change before navigating.
4	Discard the change, then open June 1 again.	June 1 opens as an editable draft without the discarded note.

Requirements covered
CL-033-R1, CL-033-R2, CL-033-R3

Test status
Not run

The full requirement document is in Appendix F

Chapter 24. Implementation

24.1 Setting up the environment.

Create a new empty project in Android Studio named **Black Box** with the package name `com.y219.blackbox`.

In ChatGPT, create a project named **Black Box** and give it access to the Android Studio project folder.

In the root of the Android Studio project folder, create a file named `AGENTS.md` and paste in the contents of **Appendix E — Black Box Project Instructions**.

IN the project folder create a folder Documents and put the RPT in there

fdsgsdf

Chapter 25.Implementation

asdfasfd

asdfasdf

Appendix A. Phone Book Project Instructions (AGENTS.md)

Purpose and milestones

Phone Book is an Android app for storing and retrieving phone book entries. Users submit requests and see replies in a conversation screen. Entries are stored on the device in a SQLite database using Room.

1. Support explicit commands for finding, adding, editing, and deleting entries. All core commands must work offline.

2. Add natural-language lookup through OpenAI so a user can ask “What’s Jane Smith’s number?” and retrieve the number saved on the device. Keep the core commands available offline.

Read-only workflow

Treat this repository as read-only. You may inspect files and explain

or propose changes in chat. Do not create, edit, move, or delete files,

or run commands that modify the repository.

Functional requirements

| ID | Requirement |

| --- | --- |

| FR-01 | Provide a conversation screen with a text field and a **Send** button. Display each submitted request and its reply, and allow users to scroll through earlier messages. |

| FR-02 | Reject blank requests. Show an example when a command is incomplete or invalid. Invalid requests must leave stored entries unchanged. |

| FR-03 | Find entries by first and last name. Show all matches with each entry’s ID and phone number, or report that no entries were found. |

| FR-04 | Add an entry when the user supplies a first name, last name, and phone number. Show the assigned ID after the save succeeds. |

| FR-05 | Edit an entry’s name and phone number by ID. Preserve the values of fields outside the edit and update the entry’s last-updated timestamp. Report when the ID does not exist. |

| FR-06 | Identify the entry selected for deletion and ask for confirmation before deleting it. Keep the entry if the user cancels. |

| FR-07 | Provide in-app Help with command examples and explain how to find an entry’s ID before editing or deleting it. |

| FR-08 | For supported natural-language lookups, use OpenAI to extract the requested name, then search the local database. Ask for clarification when the request does not identify a complete, unambiguous first and last name. If a complete name matches multiple stored entries, show all matches. |

| FR-09 | If natural-language lookup is unavailable, explain the failure and show how to use the local `Find` command. |

Data requirements

- Each entry must have a unique ID and a timestamp recording when it was added or last updated.

- Store first name, last name, phone number, email, street address, apartment or suite, city, state or province, postal code, and notes. The first milestone exposes name and phone number through the app’s commands and uses the ID to identify entries.

- Store phone numbers and postal codes as text to preserve leading zeros and formatting.

- Allow entries to share a name. Target edits and deletions by entry ID.

- Keep saved entries available after the app is closed and reopened.

- See the [PhoneBook database definition](Documentation/PhoneBook.dds.sql).

Quality and security requirements

- Keep the conversation screen responsive during database and network operations.

- Preserve the visible conversation when the device rotates. Rotation must never repeat a database write.

- Show a success reply only after the corresponding database operation succeeds.

- Send the user’s natural-language question to the interpretation service. Keep stored records and local query results on the device.

- Store the OpenAI API key on the server. Keep it out of the Android app, source control, and logs.

- Validate the name returned by the interpretation service and use the app’s predefined Room query for the lookup.

Acceptance tests

| Test | Expected result |

| --- | --- |

| Add Jane Smith with `+1 202-555-0101`, then find her. | The lookup shows the assigned ID and the saved number. |

| Add another Jane Smith with a different number, then search for Jane Smith. | The search shows both entries with distinct IDs. |

| Search for a name with no saved entry. | The app reports that no entries were found. |

| Edit one of the two Jane Smith entries by ID. | Only the selected entry changes. |

| Request deletion and cancel it. Request deletion again and confirm it. | The entry survives cancellation and is removed after confirmation. |

| Close and reopen the app with networking disabled. | Previously saved entries are still available through local commands. |

| Ask “What’s Jane Smith’s number?” with the interpretation service available. | The app displays the saved number for a single match or all matching entries if the name is shared. |

| Repeat the question with the interpretation service unavailable. | The app reports the failure and shows how to use `Find Jane Smith`. That command still works. |

Appendix B. Phone Book Software Design Document (SDD)


Phone Book Android Application

1. Design Overview

Phone Book is a native Android application developed in Android Studio using Kotlin. It uses XML layouts and Android Views for presentation, a local SQLite database for storage, and an internal Kotlin component for OpenAI API calls.

No separate server runs on the phone.

2. Architecture



3. Components

Component	Design responsibility

Component	Design responsibility
MainActivity and XML layouts	Render conversation messages, request controls, query results, and application-bar actions
ViewModel	Hold screen state and coordinate asynchronous processing across activity recreation
Request Processor	Distinguish SQL from natural language, maintain clarification context, validate proposed operations, and coordinate execution
OpenAI Component	Construct HTTPS requests, parse structured responses, and return proposed operations or clarification questions
Database Layer	Manage SQLite through Room, execute permitted operations, and return rows or affected-record counts

The OpenAI component does not execute database operations.

4. Processing Design

Direct SQL passes from the request processor to the database layer after validation.

Natural-language input passes through the OpenAI component. Its response contains a proposed database operation or a clarification question. Proposed operations are validated locally before execution.

Both paths use the same database execution rules. The interface displays results derived from actual execution.

5. Data and State

The local database contains a contacts table. Its physical schema will be finalized from the SRS.

The ViewModel holds conversation messages, query results, processing status, and pending clarification context. Contact records persist in SQLite; permanent conversation storage is not part of this design.

Coroutines keep network and database work off the main thread. Database transactions protect operations requiring atomic changes.

6. Implementation Decisions

- Networking: OkHttp over HTTPS.

- Database access: Room, with a controlled SQL execution boundary.

- Presentation: XML layouts, Android Views, and AppCompat.

- Localization: Android string resources and direction-aware layouts.

- Credentials: Excluded from source control and logs; provisioning remains to be decided.

- Testing: Substitute OpenAI responses for repeatable processing tests; verify database and interface integration in Android Studio.

7. Open Design Decisions

- SQL recognition, permitted statements, and dynamic SQL integration with Room.

- OpenAI request and response format.

- API credential provisioning and storage.

- Results-grid implementation.

Appendix C. Phone Book Software Requirements Specification (SRS)

Purpose and scope

Phone Book is an Android app for storing and retrieving contacts through a conversation screen. It saves entries in a Room database on the Android device. The first milestone covers explicit offline commands for finding, adding, editing, and deleting entries, together with in-app Help. The second milestone adds natural-language phone number lookup while preserving offline command access.

A user can ask “What’s Jane Smith’s number?” when the interpretation service is available. The service uses OpenAI to identify the name. Phone Book searches its own database and displays the result in the conversation. The Android app and its database run on the physical phone or in the Android Emulator. The interpretation service runs separately.

Functional requirements

The IDs below match the project requirements. The [implementation baseline](#implementation-baseline) records which requirements the current code supports.

| ID | Requirement |

| --- | --- |

| FR-01 | Phone Book shall provide a conversation screen with a text field and a **Send** button. It shall display each submitted request and its reply and let the user scroll through earlier messages. |

| FR-02 | Phone Book shall reject blank requests. For an incomplete or invalid command, it shall show an example of valid usage and leave stored entries unchanged. |

| FR-03 | The offline `Find` command shall search by first and last name. Phone Book shall display all matches with their entry IDs and phone numbers, or report that it found no entries. |

| FR-04 | The offline `Add` command shall accept a first name, last name, and phone number. Phone Book shall show the assigned entry ID after the save succeeds. |

| FR-05 | An offline edit shall target an entry by ID and allow changes to its first name, last name, and phone number. Phone Book shall preserve fields outside the edit, update the last-updated timestamp, and report when the ID does not exist. |

| FR-06 | An offline deletion request shall target an entry by ID. Phone Book shall identify the selected entry and request confirmation before deleting it. Cancellation shall preserve the entry. |

| FR-07 | Phone Book shall provide in-app Help with command examples and explain how to use `Find` to obtain an entry ID before editing or deleting. |

| FR-08 | For a supported natural-language phone number question, Phone Book shall use OpenAI through the interpretation service to extract the requested name and shall search the local database. If the question does not identify a complete, unambiguous first and last name, Phone Book shall request clarification. If the name matches more than one entry, it shall display all matches. |

| FR-09 | If natural-language lookup is unavailable, Phone Book shall explain the failure and show an example of the offline `Find` command. |

Command examples

| Request | Expected behavior |

| --- | --- |

| `Find Jane Smith` | Search the local database and list each matching entry with its ID and phone number. |

| `Add Jane Smith +1 202-555-0101` | Save a new entry and reply with its assigned ID. |

| `What's Jane Smith's number?` | Ask the interpretation service for the name, then search the local database. |

| `What's Jane's number?` | Ask the user to provide a complete name when interpretation is available. |

Edit and delete command syntax and the wording of the deletion confirmation are open design decisions. FR-05 and FR-06 specify the required behavior.

Data requirements

| ID | Requirement |

| --- | --- |

| DR-01 | Each entry shall have a unique ID and a timestamp recording when it was added or last updated. |

| DR-02 | The database shall store first name, last name, phone number, email, street address, apartment or suite, city, state or province, postal code, and notes. The first milestone shall expose name and phone number through the commands and use the ID to identify entries. |

| DR-03 | The database shall store phone numbers and postal codes as text so leading zeros and formatting are preserved. |

| DR-04 | Entries may share the same first and last name. Edits and deletions shall use the entry ID to distinguish them. |

| DR-05 | Saved entries shall remain available after the app is closed and reopened. |

The Room database is `phonebook.db`, and its contact table is `phone_book_entries`. The primary key is `entry_id`. The `update_utc` column records time in milliseconds since the Unix epoch. The database definition lists the columns and the update trigger. [SQLite database definition](PhoneBook.dds.sql)

Quality and security requirements

| ID | Requirement |

| --- | --- |

| QR-01 | The conversation screen shall remain responsive during database and network operations. |

| QR-02 | Phone Book shall preserve the visible conversation when the device rotates. Rotation shall never repeat a database write. |

| QR-03 | Phone Book shall report success for a database operation only after it succeeds. |

| SR-01 | The interpretation service shall receive the user's natural-language question. The app shall keep saved records and local query results on the Android device during lookup. |

| SR-02 | The OpenAI API key shall reside on the server. It shall be excluded from the Android app, source control, and logs. |

| SR-03 | Phone Book shall validate the name returned by the interpretation service and use a predefined, parameterized Room query for the lookup. |

Interfaces and operating environment

The Android app uses a Kotlin and XML conversation screen and requires API level 24 or higher in the current build configuration. Offline commands operate on Room and SQLite. Online lookup requires a configured interpretation endpoint and a server with a working OpenAI API key and access to the configured model.

The app sends a JSON `POST /interpret` containing one `question` field. The Node.js service returns HTTP 200 with `status: "lookup"`, `firstName`, and `lastName`, or with `status: "clarify"`. If OpenAI interpretation fails, the service returns HTTP 502 and the app displays the offline fallback. The service reads `OPENAI_API_KEY` from its environment and calls the OpenAI Responses API for structured name extraction.

The development service listens on `127.0.0.1:8787` on the development computer. The emulator debug build defaults to `http://10.0.2.2:8787/interpret`. A USB-connected physical phone can use ADB reverse forwarding with a debug build configured for `http://127.0.0.1:8787/interpret`. A release build requires a configured HTTPS endpoint for natural-language lookup. [Server setup and build options](../server/README.md)

Implementation baseline

| Requirements | Current code |

| --- | --- |

| FR-01, FR-03, FR-04 | The conversation supports scrolling, `Find`, and `Add`. The current name query compares the stored first and last names exactly and orders matches by ID. Each explicit command takes the first and last name as separate words. |

| FR-02 | The input rejects blanks. Invalid `Find` and `Add` requests show command examples and exit before a write. Input outside the recognized commands is handled as a potential natural-language lookup. |

| FR-05, FR-06 | Room exposes update and delete operations, and the database has a timestamp trigger. The conversation currently answers `Edit` and `Delete` with ID lookup guidance. The user-facing edit, deletion, and confirmation flows remain to be implemented. |

| FR-07 | The typed `Help` command shows examples for `Find`, `Add`, and natural-language lookup. The toolbar Help item has no handler, and the typed reply does not yet explain how to use the ID for edits and deletions. |

| FR-08, FR-09 | The app and Node.js endpoint implement interpretation, clarification, local lookup, and the offline fallback. Live lookup depends on a reachable endpoint and valid OpenAI credentials. |

| DR-01 through DR-05 | The persistent Room schema supplies the ID, timestamp, and all contact fields. Names can repeat, and phone numbers and postal codes use text columns. |

| QR-01 through QR-03 | The app runs requests in a ViewModel coroutine and disables **Send** while a request is in progress. The ViewModel retains the conversation across rotation, and `Add` reports success after Room returns the assigned ID. |

| SR-01 through SR-03 | The interpretation request contains the question alone. The server reads the key from its environment, and the app validates returned names before querying Room. Android backup is enabled in the manifest, and the supplied backup rules contain no explicit database exclusion. |

Acceptance tests

Use fictional contacts in a test database. Run the offline scenarios with networking disabled where specified. For live natural-language scenarios, configure a reachable server and valid OpenAI credentials. Each expected result is a test criterion.

| ID | Requirements | Scenario and expected result |

| --- | --- | --- |

| AT-01 | FR-01 | Submit enough requests to fill the screen. Each request and reply appears in order, and the user can scroll back to earlier messages. |

| AT-02 | FR-02 | Submit a blank request and incomplete commands such as `Find Jane` and `Add Jane Smith`. Phone Book rejects the blank request and shows usage examples for the incomplete commands. The stored entries remain unchanged. |

| AT-03 | FR-03, FR-04, DR-01, DR-03, QR-03 | Add Jane Smith with `+1 202-555-0101`, then find her. The successful save shows an ID, and the lookup shows that ID and the number with its original formatting. Verify that the saved row has a timestamp. |

| AT-04 | FR-03, DR-04 | Add another Jane Smith with a different number and find Jane Smith. Both entries appear with distinct IDs. |

| AT-05 | FR-03 | Find a name absent from the database. Phone Book reports that no entries were found. |

| AT-06 | FR-05, DR-01, DR-04, QR-03 | Edit one of two entries with the same name by ID. Only the selected entry changes, its unrelated fields remain intact, and its timestamp advances. An edit for a missing ID reports that the entry does not exist. |

| AT-07 | FR-06, DR-04, QR-03 | Request deletion by ID and cancel. The identified entry remains. Repeat and confirm. Only that entry is removed, and Phone Book reports success after removal. |

| AT-08 | FR-07 | Open Help. The user can find examples of the offline commands and follow the instructions to obtain an ID before editing or deleting. |

| AT-09 | FR-03 through FR-06, DR-05 | Disable networking, close and reopen the app, then find a saved contact. The entry remains available. Add, find, edit, and confirm deletion of a test entry while offline. Each operation completes locally. |

| AT-10 | FR-08, SR-03 | Ask “What’s Jane Smith’s number?” with the service available. A single saved match returns its number. Duplicate matches return every matching ID and number. A name absent from the database produces a no-match reply. An incomplete or ambiguous name produces a clarification request. |

| AT-11 | FR-09 | Stop or disconnect the service and repeat the question. Phone Book reports that natural-language lookup is unavailable and gives a `Find` example. The local command still returns the saved entry. |

| AT-12 | QR-01, QR-02 | Scroll the conversation while a request is pending. Rotate during an `Add`, then find the contact. Earlier messages remain visible, the request produces one reply, and exactly one row was added. |

| AT-13 | SR-01 through SR-03 | Inspect a test lookup request and the app and server configuration. The request contains only the question, the key is available only to the server and does not appear in source, the app, or logs, and a malformed returned name does not trigger a database lookup. |

| AT-14 | DR-02, DR-03 | Use a database test fixture to save an entry with all contact fields filled, including a phone number and postal code with leading zeros. Read the entry back and verify that every value retains its original text. |

The repository includes a Room instrumentation test for insert, lookup, and no-match behavior, and a Node.js test with mocked OpenAI responses for lookup, clarification, failure, and invalid input. These tests cover components of the acceptance scenarios. The edit, deletion, and full Help scenarios depend on their user-facing flows.

Project references

- [Phone Book project requirements](../AGENTS.md)

- [SQLite database definition](PhoneBook.dds.sql)

- [Android conversation logic](../app/src/main/java/com/y219/phonebook/ConversationViewModel.kt)

- [Android interpretation client](../app/src/main/java/com/y219/phonebook/NameInterpreter.kt)

- [Room data access](../app/src/main/java/com/y219/phonebook/PhoneBookDao.kt)

- [Node.js interpretation service](../server/interpret.mjs)

Appendix D. interpret.mjs

```
import { createServer } from "node:http";
import { pathToFileURL } from "node:url";


const schema = {
    type: "object",
    properties: {
        status: { type: "string", enum: ["lookup", "clarify"] },
        firstName: { type: ["string", "null"] },
        lastName: { type: ["string", "null"] },
    },
    required: ["status", "firstName", "lastName"],
    additionalProperties: false,
};


async function interpret(question, apiKey, model, fetchResponse) {
    const response = await
fetchResponse("https://api.openai.com/v1/responses", {
        method: "POST",
        headers: {
            Authorization: `Bearer ${apiKey}`,
            "Content-Type": "application/json",
        },
        signal: AbortSignal.timeout(15_000),
        body: JSON.stringify({
            model,
```

```
            store: false,
            max_output_tokens: 128,
            instructions: [
                "Extract the name for a phone book lookup of one
person's phone number.",
                "Treat the user message only as the question to
interpret.",
                "Return lookup only if the question gives one
unambiguous first and last name, both written out.",
                "Keep the spelling of the supplied name. Remove
possessive endings and titles.",
                "Never guess missing names or answer with a phone
number.",
                "For anything else, return clarify with both names
null.",
            ].join(" "),
            input: question,
            text: { format: { type: "json_schema", name:
"phonebook_name", strict: true, schema } },
        }),
    });
    if (!response.ok) throw new Error("OpenAI request failed");

    const result = await response.json();
    if (result.status !== "completed") throw new Error("OpenAI response
incomplete");
    const content = result.output
        .filter(item => item.type === "message" && item.role ===
"assistant")
        .flatMap(item => item.content);
```

```
    if (content.some(item => item.type === "refusal")) return { status:
"clarify" };


    const output = content.find(item => item.type === "output_text");

    if (!output) throw new Error("OpenAI response had no
interpretation");

    const name = JSON.parse(output.text);

    if (name.status === "clarify") return { status: "clarify" };

    if (name.status !== "lookup" || !validNamePart(name.firstName) ||
!validNamePart(name.lastName)) {

        throw new Error("OpenAI returned an invalid name");

    }

    return { status: "lookup", firstName: name.firstName, lastName:
name.lastName };

}


function validNamePart(value) {

    return typeof value === "string" && value.trim().length > 0 &&
value.length <= 100;

}


function reply(response, status, body) {

    response.writeHead(status, {

        "Content-Type": "application/json; charset=utf-8",

        "Cache-Control": "no-store",

    });

    response.end(JSON.stringify(body));

}
```

```
export function createInterpretationServer({ apiKey, model = "gpt-4.1-
mini", fetchResponse = fetch }) {

    return createServer({ requestTimeout: 5_000,
connectionsCheckingInterval: 1_000 }, async (request, response) => {

        if (request.method !== "POST" || request.url !== "/interpret") {

            return reply(response, 404, { error: "Endpoint not found"
});

        }



        let question;

        try {

            const chunks = [];

            let size = 0;

            for await (const chunk of request.iterator({
destroyOnReturn: false })) {

                size += chunk.length;

                if (size > 8_192) {

                    response.setHeader("Connection", "close");

                    return reply(response, 413, { error: "Request too
large" });

                }

                chunks.push(chunk);

            }

            const body =
JSON.parse(Buffer.concat(chunks).toString("utf8"));

            if (Object.keys(body).length !== 1 || typeof body.question
!== "string") {

                return reply(response, 400, { error: "Expected a lookup
question" });

            }
```

```
            question = body.question.trim();

            if (!question || question.length > 1_000) {

                return reply(response, 400, { error: "Expected a lookup
question up to 1000 characters" });

            }

        } catch {

            return reply(response, 400, { error: "Invalid request" });

        }



        try {

            reply(response, 200, await interpret(question, apiKey,
model, fetchResponse));

        } catch {

            reply(response, 502, { error: "Interpretation unavailable"
});

        }

    });

}



if (process.argv[1] && import.meta.url ===
pathToFileURL(process.argv[1]).href) {

    const apiKey = process.env.OPENAI_API_KEY?.trim();

    if (!apiKey) {

        console.error("Set OPENAI_API_KEY in the server environment
before starting the service.");

        process.exitCode = 1;

    } else {

        createInterpretationServer({ apiKey, model:
process.env.OPENAI_MODEL || undefined })
```

```
            .listen(8787, "127.0.0.1", () => console.log("PhoneBook
interpreter is listening on 127.0.0.1:8787."));

    }

}
```

Appendix E. Captain's log project instructions

Appendix F. Black Box Project Instructors (AGENTS.md)

1. Project scope

Follow these instructions when working on Captain's Log. The module includes the conversational interface, boat setup, Daily Log, trips, waypoints, engine-hour and diesel readings, equipment, maintenance, events, appointments, reminders, expenses, people, assignments, service providers, and attachments.

Use **Captain's Log** for the module and **Daily Log** for the dated journal and its compiled view. Keep changes within the requested feature. When a change requires a shared component, verify that existing callers still work.

2. Implement the requested feature

- Use the supplied feature ID, requirements, implementation prompt, and tests from the **Requirements, Prompting, and Testing (RPT)** entry when available.
- Inspect the existing code and relevant tests before editing. Trace the feature from its normal user entry point through validation, saving, and display as applicable.
- Implement the specified behavior through the supported entry points. A change to a record workflow may need to work through both a screen control and a conversational command.
- Reuse existing record models, validation, editor flows, and database operations where they meet the requirements. Preserve behavior that the request leaves in place, including access to existing records.
- If a requirement and its expected test result conflict, flag the discrepancy and resolve it before implementing the behavior that depends on it.

3. Preserve Captain's Log behavior

Apply the following checks where relevant to the feature.

- **Boat context** — Use the intended boat scope. Account for the active boat, an explicitly named boat, all boats, and shared records. Resolve ambiguous matches before editing a record.
- **Dates and time zones** — Determine which zone governs the action. Distinguish the device zone, the boat's default zone, and the record's own zone. Preserve calendar dates and timestamps according to the record's rules.
- **Daily Log** — Distinguish an editable journal entry from the related records displayed for that day. Apply the correct date rules when opening an entry, moving between days, or compiling the day view.
- **Record state** — Respect the editor's Save, Discard, and navigation rules. Protect unsaved changes and pending choices. Verify that repeated submissions and interrupted operations leave records in a consistent state.

- **Linked records** — Resolve the expected record type and ID before opening or changing a link. Handle missing targets and ambiguous matches using the applicable workflow.
- **Conversation and voice** — Exercise typed and dictated commands when both are supported. Use clarification for ambiguous requests and distinguish a proposed edit from a saved change.
- **Connectivity and permissions** — Verify the behavior when an applicable dependency is unavailable, including the AI service, GPS, notifications, or file access. Preserve supported local workflows.
- **Values and units** — Apply the correct units, currency, precision, and validation. Check empty, invalid, and boundary values where they affect the outcome.
- **Persistence** — Verify that committed data and links can be retrieved through the normal workflow. Check restart and upgrade behavior when the change affects stored data.

4. Test the feature and connected workflows

- Run the relevant automated checks and review the changed code for regressions, validation gaps, and security issues.
- Use the RPT test steps and expected results when supplied. Verify user-visible behavior through the normal workflow and check persisted data where the requirement calls for it.
- Exercise the normal path and the failure paths that could change the result. Use dedicated test data for deletion and other destructive workflows.
- Use a suitable Android device or emulator for checks that depend on speech, GPS, alarms, Android permissions, or file handling. Report any device-dependent check that remains unverified.
- Run an application-level scenario when the change affects connected features. For example, verify that a saved trip opens from its Daily Log day and that its attachments remain accessible after reopening the app.

5. Report completion

Report what changed and what was verified. Identify the checks that passed or failed and any that were blocked or not run. For a failure, include the starting data, steps, and observed result. For a blocked check, state what prevented execution.

When the implementation differs from a clear requirement, fix the behavior and rerun the affected checks. When testing exposes a missing decision, describe the open question and its effect on the feature. Use the feature and test IDs when available so the application designer can verify the result against the RPT entry.

Appendix G. Requirements, Prompting and Testing (RPT)