

MOCCASIN: converting MATLAB ODE models to SBML

Journal:	Bioinformatics
Manuscript ID	Draft
Category:	Applications Note
Date Submitted by the Author:	n/a
Complete List of Authors:	Gómez, Harold; ETH Zürich, Department of Biosystems Science and Engineering Hucka, Michael; California Institute of Technology, Computing and Mathematical Sciences Keating, Sarah; European Molecular Biology Laboratory – European Bioinformatics Institute (EMBL-EBI) Iber, Dagmar; ETH Zürich, Department of Biosystems Science and Engineering Sealfon, Stuart; Icahn School of Medicine at Mount Sinai, Department of Neurology
Keywords:	Computational biology, Simulation, Mathematical modeling, Algorithms
SCHOLARONE™ Manuscripts	

Bioinformatics, YYYY, 0–0
doi: 10.1093/bioinformatics/xxxxx
Advance Access Publication Date: DD Month YYYY
Application Note

Systems biology

MOCCASIN: converting MATLAB ODE models to SBML

Harold F. Gómez^{1,*}, Michael Hucka^{2,*}, Sarah M. Keating^{3,*}, Dagmar Iber¹, Stuart Sealfon⁴

¹Department of Biosystems Science and Engineering, ETH Zürich, Basel, 4058, CH, ²Computing and Mathematical Sciences, California Institute of Technology, Pasadena, CA 91125, USA, ³European Molecular Biology Laboratory, European Bioinformatics Institute (EMBL-EBI), Hinxton, Cambridge, CB10 1SD, UK, ⁴Department of Neurology, Icahn School of Medicine at Mount Sinai, Mount Sinai Medical Center and School of Medicine, New York, NY 10029, USA

*To whom correspondence should be addressed.

Associate Editor: XXXXXXX

Received on XXXXX; revised on XXXXX; accepted on XXXXX

Abstract

Summary: MATLAB is popular in biological research for creating and simulating models that use ordinary differential equations (ODEs). However, sharing these models with non-MATLAB users and other software environments is often problematic. A community standard such as SBML can serve as a neutral exchange format, but translating MATLAB ODE models into SBML format is challenging – especially for legacy models never written with translation in mind. We developed MOCCASIN (*Model ODE Converter for Creating Awesome SBML Interoperability*) to help with this task. MOCCASIN can convert ODE-based MATLAB models of biochemical reaction networks into SBML format.

Availability and implementation: MOCCASIN is available under the terms of the LGPL 2.1 license (http://www.gnu.org/licenses/lgpl-2.1.html). Source code, binaries and test cases can be freely obtained from https://github.com/sbmlteam/moccasin.

Supplementary information: More information is available at https://github.com/sbmlteam/moccasin.

Contact: moccasin-dev@googlegroups.com

1 Introduction

MATLAB is a general-purpose numerical computing environment whose powerful features have attracted many researchers. It has been the substrate for countless models as well as software tools written in its object-oriented programming language. Despite its popularity, there are reasons why MATLAB programs are not themselves a desirable format for exchanging, publishing or archiving computational models in biology. These include the lack of biological semantics in MATLAB programs, which makes clear interpretation of programs as models of biological processes more difficult; the fact that MATLAB is proprietary and expensive, which makes it unsuitable as a universal format for open scientific exchange; and the fact that model details are often intertwined with program implementation details, which makes it difficult to determine which parts constitute the essence of a model.

SBML (the Systems Biology Markup Language) is an open format for representing models in systems biology (Hucka et al., 2003). Designed to resolve incompatibilities between systems that use different formats to describe models, SBML is neutral with respect to modeling framework and computational platform. This helps make models portable across tools, and ensures that models as research products can persist regardless of changes to any particular software tool or operating system. Unfortunately, translating models from MATLAB to SBML is not straightforward. Some MATLAB toolboxes (e.g., Schmidt and Mats, 2006; Keating et al., 2006) offer SBML capabilities; however, they have limited utility for translating legacy models, lack support for the latest SBML releases, and must be used from the start of a modeling project to have an effect.

These issues led us to develop MOCCASIN (Model ODE Converter for Creating Awesome SBML INteroperability), a stand-alone tool that can take ODE models written in MATLAB and export them as SBML files. MOCCASIN is written in Python and does not require access to MATLAB. To develop it, we drew on recent advances in the inference of biochemical reaction networks (Fages et al., 2015). The result allows for richer SBML that can also be used for qualitative analyses where knowledge of the reaction network behind a system of ODEs is required.

2 Implementation

MOCCASIN features a modular architecture comprised of (1) a module that parses MATLAB files; (2) a module that extracts the ODE-based model and produces a model with explicit ODEs; (3) a module that infers the biochemical reactions implied by the ODEs and produces SBML output with biochemical reactions for kinetics; (4) a command line interface; and (5) a graphical user interface Python developers can use as few or as many modules as they desire.

2.1 Parsing module

MATLAB is difficult to parse fully (Doherty et al., 2011): the language is complex and idiosyncratic, and there is no published definition of its syntax rules. We did not attempt to develop a complete parser for MATLAB; instead, we leveraged the fact that MOCCASIN's input is already expected to be syntactically valid MATLAB (because users are converting working code), and thus MOCCASIN's parser can be simpler and make more assumptions. The parser creates an internal representation that is essentially an embellished Abstract Syntax Tree (AST).

2.2 Converter module

The AST is processed to recognize specific constructs. The approach centers on finding a call to one of the MATLAB odeNN family of solvers (e.g., ode45, ode15s, etc.). Once this is found, the converter inspects the AST for the definitions of the arguments to the call; these are expected to be either a matrix or the handle of a function that returns a matrix. If it is a function (which must be found elsewhere in the same file), MOCCASIN inspects the parsed function body. The rows of the matrix or the function's return values are assumed to define the ODEs of the user's model. MOCCASIN translates this and generates either an SBML (using SBML "rate rules") or XPP (Ermentrout, 2002) representation. For SBML, MOCCASIN makes use of libSBML (Bornstein et al., 2008); to generate XPP, it directly implements the necessary translation.

2.3 BIOCHAM module

Encoding a model's ODE equations in a one-to-one fashion using SBML's "rate equations" is sufficient to ensure simulation reproducibility, but the translated model is not ideal if the original system of ODEs actually represents a biochemical reaction network. Reconstructing this network captures the underlying model more productively and enables subsequent application of analyses that require biochemical reactions (e.g., Gay et al., 2014). To export SBML models with fully resolved reaction networks, MOCCASIN sends the converter's output via web services to BIOCHAM, a modeling environment that incorporates a state-of-the-art algorithm for reconstructing and inferring the complete reaction model from a given set of ODEs (Fages et al., 2015). Due limitations in the XPP format and the BIOCHAM service, the result lacks some components present in the original model. MOCCASIN therefore post-processes the output from BIOCHAM to add initial assignments, references to the time variable (if used in the original model), and other pieces. All components of the initial MATLAB ODE model are thus captured, and each reaction in the SBML output is fully characterized with well-identified reactants, products and modifiers.

2.4 Command-line interface

MOCCASIN provides a cross-platform command-line interface (CLI) that facilitates scripting and automation.

2.5 Graphical user interface

The GUI interface is implemented with a cross-platform GUI toolkit. The interface provides a straightforward way for users to input MATLAB files, set MOCCASIN options such as the type of output (SBML or XPP), view the resulting output, and save the converted file.

Future work

The MATLAB input currently must conform to certain simple forms and make limited use of MATLAB features. Future enhancements will (1) expand the set of MATLAB constructs that can be interpreted; (2) support models spread over several MATLAB input files; (3) generate SED-ML (Simulation Experiment Description Markup Language; Waltemath et al., 2011) files, to encode procedural aspects that cannot be expressed in SBML; and (4) directly implement the BIOCHAM reaction inference algorithm (Fages et al., 2015), to streamline the translation process.

Acknowledgements

The authors thank Thomas B. Kepler, Franz-Josef Elmer, Bernd Rinn and Jannik Vollmer for helpful discussions and implementation ideas.

Funding

This work was supported by *Modeling Immunity for Biodefense* contracts from the National Institutes of Health (contract HHSN266200500021C and HHSN272201000053C, awarded to Stuart Sealfon and Thomas B. Kepler, respectively) and by the Swiss Institute of Bioinformatics.

Conflict of Interest: none declared.

References

Bornstein, B.J. et al. (2008) LibSBML: an API Library for SBML. Bioinformatics, 24, 880-881.

Doherty, J., Hendren, L., & Radpour, S. (2011). Kind analysis for MATLAB. In Proceedings of OOPSLA'11.

Ermentrout, B. (2002) Simulating, analyzing, and animating dynamical systems: a guide to XPPAUT for researchers and students. Society for Industrial Mathematics.

Fages, F. et al. (2015) Inferring Reaction Systems from Ordinary Differential Equations. Theoretical Computer Science, 22 (4): 514-515.

Gay, S. et al. (2014) On the Subgraph Epimorphism Problem. Discrete Applied Mathematics, 162: 214–228.

Hucka, M. et al. (2003) The systems biology markup language (SBML): a medium for representation and exchange of biochemical network models. *Bioinformatics*, 19, 524-531.

Keating, S.M. et al. (2006) SBMLToolbox: An SBML Toolbox for MATLAB Users. Bioinformatics, 22 (10): 1275–1277.

Schmidt, H., and Mats J. (2006) Systems Biology Toolbox for MATLAB: A Computational Platform for Research in Systems Biology. *Bioinformatics*, 22 (4): 514–515.

Waltemath, D., et al. (2011). Reproducible computational biology experiments with SED-ML – the simulation experiment description markup language. BMC Systems Biology, 5 (1): 198.