









LOCATION: Spadina Ave & Nassau St MODE/COMMENT: SAP with TSP*, PR , 2 Wire Polara APS & LPI TCS: 278 PREPARED BY / DATE: Lina Elmorshedy/ November 12, 2024 CHECKED BY / DATE: Intesham Ahmad / November 12, 2024 IMPLEMENTATION DATE: November 13, 2024		ATO (DISTRICT) / WARD: 1 (Toronto & East York) / 11 COMPUTER SYSTEM: TransSuite CONTROLLER/CABINET TYPE: Peek ATC-1000 / ITS CONFLICT FLASH: Red & Red DESIGN WALK SPEED: 0.9 m/s (FDW based on full crossing at 1.1 m/s) CHANNEL/DROP: 4054/2 CONTROLLER FIRMWARE: 3.018.1.2976							
NEMA Phase		OFF	AM	PM	NGHT	WKND	Special	Phase Mode	Remarks
		All Other Times	6:30-9:30 M-F	15:00-19:00 M-F	23:00-6:30 Daily	10:00-19:00 Sat & Sun	Events Plan	(Fixed/Demanded/Callable)	
	Local Plan	Pattern 1	Pattern 2	Pattern 3	Pattern 4	Pattern 5	Pattern 16		
	Split Table	Split 1	Split 2	Split 3	Split 4	Split 5	Split 16		
1	 WLK 6 FDW 7 MIN 3.0 MAX1 3.7 AMB ALR SPLIT							SB fully protected U-Turn Callable/extendable by stopbar loop	Pedestrian Minimums: NSWK = 8 sec; NSFD = 7 sec EWWK = 8 sec; EWFD = 27 sec The following grades were used to calculate the AMB intervals: North Leg = -1.4% South Leg = 1.0% East Leg = 0.0% West Leg = -0.5%
2	Spadina Ave  WLK 8 FDW 7 MIN 15 MAX1 26 AMB 3.0 ALR 3.5 SPLIT							Fixed POZ activated by Request Loop (Transit max extension of 30 secs in Green/Walk)	EB phase is callable by vehicle and/or pedestrian actuation. If a vehicle call and/or a pedestrian call is received, the pedestrian minimums will be served. The EWWK & EWFD are only displayed on the pedestrian signal heads if a vehicle and/or pedestrian call is received. Signal cycles to side street if there is N/S U turn demand.
3	 NOT USED WLK FDW MIN MAX1 AMB ALR SPLIT								Overlap A & B are only displayed with phase 2 & 6 respectively only when no NSLA's *See back for TSP Instruction TSP enabled on December 22, 2021 Leading Pedestrian Interval-EWWK comes up 5 sec before vehicle green
4	Nassau St  WLK DLY 5 WLK 8 FDW 27 MIN 30 MAX1 30 AMB 3.0 ALR 4.3 SPLIT							Callable by Stopbar loop and/or Pushbutton; Extendable by stopbar loop Split shown includes 5 secs of EW LPI	Script #2 is used for TSP operation at this location in conjunction with firmware version 3.018.1.2976 APS tones, Cuckoo is on during 8 seconds of NSWK & Canadian Melody is on during 8 seconds of EWWK when no arrows are displayed and when activated by a pushbutton. Extended push activation = 1 sec
5	 WLK 6 FDW 6 MIN 3.0 MAX1 4.2 AMB ALR SPLIT							NB fully protected U-Turn Callable/extendable by stopbar loop	
6	Spadina Ave  WLK 8 FDW 7 MIN 15 MAX1 26 AMB 3.0 ALR 3.5 SPLIT							Fixed POZ activated by Request Loop (Transit max extension of 30 secs in Green/Walk)	
7	 NOT USED WLK FDW MIN MAX1 AMB ALR SPLIT								
8	Nassau St  WLK DLY 5 WLK 8 FDW 27 MIN 30 MAX1 30 AMB 3.0 ALR 4.3 SPLIT							Callable by pushbuttons Split shown includes 5 secs of EW LPI	
Overlap A	 WLK FDW MIN MAX1 3.0 AMB 3.5 ALR SPLIT							NBTGA (Parent Phase 2)	
Overlap B	 WLK FDW MIN MAX1 3.0 AMB 3.5 ALR SPLIT							SBTGA (Parent Phase 6)	
	CL OF	90 23	90 28	90 10	82 11	90 22	100 10		

Notes:

LOC: Spadina Ave & Nassau St

MODE: SAP with TSP* & PR & LPI

TCS: 278

PREPARATION DATE (TIMING CARD): February 18, 2022

OFFSET CORRECTION PARAMETERS

2.3.4 O.C. Extend / Reduce (Max. time added & subtracted in sec.) From page 1

	Ø1	Ø2	Ø3	Ø4	Ø5	Ø6	Ø7	Ø8	[Cycle]	[Slop]
OFF										
Split 1	Ext.	--	34	--	--	--	34	--	90	11
	Rdc.	--	11	--	--	--	11	--		
AM										
Split 2	Ext.	--	34	--	--	--	34	--	90	11
	Rdc.	--	11	--	--	--	11	--		
PM										
Split 3	Ext.	--	34	--	--	--	34	--	90	11
	Rdc.	--	11	--	--	--	11	--		
NGHT										
Split 4	Ext.	--	36	--	--	--	36	--	82	4
	Rdc.	--	4	--	--	--	4	--		
WKND										
Split 5	Ext.	--	34	--	--	--	34	--	90	11
	Rdc.	--	11	--	--	--	11	--		
Special										
Split 16	Ext.	--	38	--	--	--	38	--	100	11
	Rdc.	--	11	--	--	--	11	--		

Pattern 16
25 s
25 %

Pattern 1
22 s
25 %

Pattern 2
22 s
25 %

Pattern 3
22 s
25 %

Pattern 4
10 s
19 %

Pattern 5
22 s
25 %

Pattern 4 OC Thres set to standard value but controller could take up to three cycles to get back in sync during -TSP Recovery due to limited available time.

Screen 2.1.9.2 Advanced I/O Scripts

Script #2 "TCS278Delay2"

Provides additional run delay time to TSP Run 2 during Patterns 1 and 3 using the ELAPSE time function.

Script #3 "TSPFilterAY"

Used to block TSP calls in Phase 2/6 late in the cycle during unused time, and in Phase 1/5 and 2/6 AMB/ALR. Script #2 is a work around with firmware 3.18.2976.

TSP calls can be checked on Screen 1.2.4 at all times.

T.S.P. PARAMETERS

PREPARED: Dinesh

TSP RUN # 2

TSP RUN # 6

NB Thru

SB Thru

2.8.2 Transit Run Parameters

ATC Green Extend Mode (Equivalent TTC Algorithm)	Mode 2	Mode 2
	A	A

2.8.3 Transit Action Plan 1 (Used for all Patterns)

Run Enable (X = Yes)	X	X
Run Config = 1	Recovery = 2 (O.C. with delay)	

2.8.4 Transit Run Configuration 1

Delay / Extend / Fail	5 / -- / 235	-- / -- / 235
Max Req During Offset Corr	I	I
CALLS (and Extends)	Ø 2/6	Ø 2/6
Reduces (Truncates)	--	--

In Pattern 1 and 3, an additional run delay of 2s and 6s respectively applied to TSP Run #2 using the TCS278Delay2 script

	Ø1	Ø2	Ø3	Ø4	Ø5	Ø6	Ø7	Ø8
2.8.6 TSP Split Tables: 1, 2, 3, 4, 5, 16.								
GRN EXT (SDW Extension)	--	--	--	--	--	--	--	--
GRN RDC (Reduction)	--	--	--	--	--	--	--	--
WLK EXT (Walk Extension)	--	30	--	--	--	30	--	--

Notes:

ATC Mode	0	2	3	4
TTC Algor'm	B-2	A	C	D
Extensions	SDW	Walk	W/SDW	W/SDW

TSP SUMMARY

Maximum Green Extensions:
NSG: 30 s Green/Walk

TSP Loop Legend

Request (Thru)

Cancel (Thru)

TCS0278.xlsx

11/13/2024