# Table of Contents

1. Willy-Web . . . . . 2
   1.1. Setup Wifi connection . . . . . 2
   1.2. Web platform . . . . . 2

**Welcome**

**Project Willy**

- Willy
- Publicity
- Sponsors

**Startup Willy**

- Driving Willy
- Remote
- Willy Web

**Configuration**

- GIT Setup
- Ubuntu
- Remote
- Wiki

**ROS**

- Introduction to ROS
- Navigation

**Technical**

- Development Guide
- Findings
- Hardware
- Known Bugs
- Parameters
- Software

**Web interface**

- Development Guide
- SAD
- RosNodeJs
- Interaction

**Research**

- Hardware
- Peripherals
- Sensors
- Social interaction

- Software
- Web interface

**Design**

- Background
- Design Guide
- Technical
- Realisation

**Status and Advice**

- Status
- Todo & Advice

**Archive**

- (2016/2) Initial design
- (2017/1) Base & Functionalities
- (2017/2) Research


# 1. Willy-Web

## 1.1. Setup Wifi connection

Before any form of connection can be realized, a wireless connection is required. When the power switch is turned on, the router will setup a wifi access point. Connection with the access point can be set with the following data.

SSID: Willy WPA2-password: See password file.

## 1.2. Web platform

Visit http://192.168.0.100 in your browser. Login using the password found in the password file to authenticate. After this authentication you can enter your name and start using the platform.