Harmonic oscillator action

This is the Lagrangian for a harmonic oscillator.

$$L = \frac{m}{2}(\dot{x}^2 - \omega^2 x^2)$$

Show that

$$S = \int_0^T L \, dt = \frac{m\omega}{2\sin\omega T} \left((x_b^2 + x_a^2)\cos\omega T - 2x_b x_a \right)$$

where $T = t_b - t_a$.

This is the Euler-Lagrange equation.

$$\frac{d}{dt}\frac{\partial L}{\partial \dot{x}} = \frac{\partial L}{\partial x}$$

From L we have

$$\frac{d}{dt}\frac{\partial L}{\partial \dot{x}} = m \ddot{x}, \quad \frac{\partial L}{\partial x} = -m \omega^2 x$$

and by Euler-Lagrange

$$\ddot{x}(t) = -\omega^2 x \tag{1}$$

The well-known solution to (1) is

$$x(t) = A\sin(\omega t) + B\cos(\omega t)$$

We have the following boundary conditions.

$$x(0) = x_a, \quad x(T) = x_b \tag{2}$$

Solve for B.

$$B = x(0) = x_a$$

For x(T) we have

$$x(T) = A\sin(\omega T) + B\cos(\omega T)$$

Solve for A.

$$A = \frac{x(T) - B\cos(\omega T)}{\sin(\omega T)} = \frac{x_b - x_a\cos(\omega T)}{\sin(\omega T)}$$

Hence the equation of motion is

$$x(t) = A\sin(\omega t) + B\cos(\omega t) = \frac{x_b - x_a\cos(\omega T)}{\sin(\omega T)}\sin(\omega t) + x_a\cos(\omega t)$$
(3)

Differentiate x(t) to obtain velocity $\dot{x}(t)$.

$$\dot{x}(t) = \frac{d}{dt}x(t) = \omega \left(\frac{x_b - x_a \cos(\omega T)}{\sin(\omega T)}\cos(\omega t) - x_a \sin(\omega t)\right)$$
(4)

The action is

$$S = \frac{m}{2} \int_0^T (\dot{x}^2 - \omega^2 x^2) dt$$
$$= \frac{m}{2} \left(\int_0^T \dot{x}^2 dt - \int_0^T \omega^2 x^2 dt \right)$$

Use integration by parts to solve the first integral. Let $u = v = \dot{x}$ so that

$$\dot{u} = \ddot{x}, \quad \int v \, dt = x$$

The integral transforms as

$$\int_0^T \dot{x}^2 dt = \int_0^T uv \, dt$$

$$= \left(u \int v \, dt \right) \Big|_0^T - \int_0^T \dot{u} \left(\int v \, dt \right) \, dt$$

$$= \dot{x}(T)x(T) - \dot{x}(0)x(0) - \int_0^T \ddot{x}x \, dt$$

Hence

$$S = \frac{m}{2} \left(\dot{x}(T)x(T) - \dot{x}(0)x(0) - \int_0^T \ddot{x}x \, dt - \int_0^T \omega^2 x^2 \, dt \right)$$

The remaining integrals cancel by $\ddot{x} = -\omega^2 x$ from equation (1) leaving

$$S = \frac{m}{2} (\dot{x}(T)x(T) - \dot{x}(0)x(0))$$
 (5)

From the boundary conditions (2)

$$S = \frac{m}{2} \left(x_b \dot{x}(T) - x_a \dot{x}(0) \right)$$

From equation (3)

$$\dot{x}(0) = -\frac{\omega x_a \cos(\omega T)}{\sin(\omega T)} + \frac{\omega x_b}{\sin(\omega T)}$$
(6)

and

$$\dot{x}(T) = \frac{\omega x_b \cos(\omega T)}{\sin(\omega T)} - \frac{\omega x_a}{\sin(\omega T)}$$
 (7)

Hence

$$S = \frac{m\omega}{2\sin(\omega T)} \left(\left(x_b^2 + x_a^2 \right) \cos(\omega T) - 2x_b x_a \right) \tag{8}$$