

CLAUDE CODE · EXPERIMENTAL

# Agent teams in Claude Code

Multiple Claudes working as  
peers — not one agent delegating.  
Here's how to run a real team.

## THE DIFFERENCE

# Teams ≠ subagents

A subagent reports back to you.

Agent teammates work independently AND message each other directly. One lead coordinates; the peers self-organize.

## 01 · SETUP

# Turn it on

It's experimental — needs Claude Code v2.1.32+.

- `export`  
`CLAUDE_CODE_EXPERIMENTAL_AGENT_TEAMS=1`
- (or set it in settings.json env)
- check: `claude --version`

## 02 · JUST ASK

# Create a team

Describe the team in plain English; the lead spawns the teammates.

- 'Create a team of 3 to review PR #142:
- security, performance, test coverage'

## 03 · HOW THEY COORDINATE

# Shared task list

The lead posts tasks; teammates self-claim them. Dependencies auto-unblock when a prerequisite finishes — no babysitting.

## 04 · DIRECT MESSAGING

# They talk to each other

Any teammate can message any other by name, delivered automatically — the lead doesn't relay. Jump into any teammate (Shift+Down) to steer it.

## 05 · TIES INTO SUBAGENTS

# Reuse your roles

Spawn a teammate from a subagent type you already defined (e.g. security-reviewer) — same tools allowlist + model. Define a role once, use it both ways.

## IN THE WILD

# A real example

Debug by competing hypotheses:  
'Spawn 5 teammates to test  
different theories for this bug.  
Have them argue to disprove each  
other, then update the findings  
doc with the consensus.'

KEEP IT REAL

# Know the tradeoffs

Teams burn far more tokens (each is a full context). Two teammates on one file = overwrites — give each its own files. Experimental: one team at a time, no teammate resume yet.



DO THIS TODAY

# When to reach for it

Subagents = 'do X, report back.'

Agent teams = big work where peers own pieces and challenge each other. Try it on your next multi-angle review. Save this.

**Follow Noblerr →**