

CLAUDE CODE

Make your agent format, guard & notify itself

3 hooks you set once in
.claude/settings.json. They run on
every session, automatically.

THE GAP

"Please be careful" is not a guardrail

Prompts get forgotten. Hooks don't. A hook is a shell command Claude Code runs automatically on an event: before a tool, after an edit, when it stops.

THE SHAPE

Where hooks live

One JSON object. Event maps to
matcher maps to command.

- File: `.claude/settings.json`
- `hooks > PostToolUse > matcher: "Edit|Write"`
- `type: "command", command: "..."`

HOOK 1

Auto-format every file it edits

PostToolUse on Edit|Write. The agent writes, Prettier fixes. Zero diffs about spacing.

- matcher: Edit|Write
- jq -r '.tool_input.file_path' \
- | xargs npx prettier --write

HOOK 2

Block dangerous edits

PreToolUse runs a script. exit 2 blocks the call and the reason is fed back to Claude, so it self-corrects.

- grep path for .env / package-lock.json
- echo "Blocked: \$FILE" >&2
- exit 2 # cancels the tool call

HOOK 3

Ping you when it needs input

The Notification event. Stop babysitting the terminal.

- event: Notification
- `osascript -e 'display notification ...'`
- Linux: `notify-send 'Claude Code' '...'`

THE KICKER

deny beats -- dangerously-skip- permissions

A PreToolUse deny blocks the tool even in bypass mode. Hooks can tighten what the agent may do. They can never loosen it.

CHEAT SHEET

Which events can block (exit 2)

- PreToolUse -> blocks the tool call
- UserPromptSubmit -> blocks the prompt
- Stop -> keeps Claude going
- PostToolUse -> can't block, only warns



YOUR MOVE

Wire one hook today

Start with auto-format. Add the guard tomorrow. Follow Noblerr for more Claude Code builds.

Follow Noblerr →

Noblerrnoblerr.com