

## AI AUTOMATION

# Ask your Postgres questions in plain English

Wire Claude straight into your database with one command. No SQL, no waiting on the data team.

## THE GAP

# Every metric routes through one engineer

'What's revenue this month?'  
becomes a ticket. Someone writes  
SQL, the answer lands tomorrow.  
The bottleneck is the workflow,  
not the data.

## THE WIRE-UP

# One command connects Claude to your DB

Uses the @bytebase/dbhub MCP server over stdio. Point the DSN at your database.

- `claude mcp add --transport stdio db -- \`
- `npx -y @bytebase/dbhub \`
- `--dsn "postgresql://USER:PASS@host:5432/db"`

NOW ASK

# Plain-English questions, real queries

Claude reads your live schema and writes the SQL for you.

- "What's our total revenue this month?"
- "Show me the schema for the orders table"
- "Find customers who haven't bought in 90 days"

## SAFETY 1

# Use a READONLY database user

Put a read-only role in the DSN.  
The agent can query everything  
and write nothing. No accidents,  
ever.

- `--dsn "postgresql://readonly:pass@host:5432/analytics"`

## SAFETY 2

# Make it team-ready with project scope

Project scope writes a `.mcp.json` at the repo root. Check it in; every teammate gets the same connection.

- `claude mcp add --scope project db -- \`
- `npx -y @bytebase/dbhub --dsn "..."`
- `# commit .mcp.json`

## VISIBILITY

# See what's connected anytime

Lists every MCP server, its status, and lets you authenticate remote ones.

— /mcp



## CHEAT SHEET

# From zero to plain-English queries

Screenshot this.

- 1. `claude mcp add --transport stdio db -- \`
- `npx -y @bytebase/dbhub --dsn "postgres://..."`
- 2. readonly user in the DSN
- 3. `/mcp` to confirm -> then just ask





NOBLERR

# Anyone can ask. No bottleneck.

We build read-only data agents for teams. If every metric still goes through one engineer, that's a choice — comment **AUTOMATE** for the build.

**Follow Noblerr →**

---

Noblerrnoblerr.com