

Practical work no. 1 – Documentation

Specifications

We shall define a class named **DirectedGraph** representing a directed graph.

The class **DirectedGraph** will provide the following methods:

- `def __init__(self, number_of_vertices=0, number_of_edges=0):`
 - The class constructor
- `def __str__(self):`
 - Returns the string representation of current graph
- `def get_edges_costs(self):`
 - Returns the dictionary (of edges and their cost) of the graph
- `def get_inbound_vertices(self):`
 - Returns the dictionary of the inbound vertices of the graph
- `def get_outbound_vertices(self):`
 - Returns the dictionary of the outbound vertices of the graph
- `def get_number_of_vertices(self):`
 - Returns the number of vertices for current graph
- `def get_number_of_edges(self):`
 - Returns the number of vertices for current graph
- `def add_vertex(self, vertex_to_add):`
 - Precondition: vertex must not already exist in graph
 - Add a new vertex to current graph
 - Returns: True (if vertex can be added) ; False (otherwise)
- `def remove_vertex(self, vertex_to_remove):`
 - Precondition: vertex must already exist in graph
 - Remove a vertex from current graph
 - Returns: True (if vertex can be removed) ; False (otherwise)

- `def add_edge(self, vertex1, vertex2, cost):`
 - Precondition: edge must not already exist in graph
 - Add an edge to current graph
 - Returns: True (if edge can be added) ; False (otherwise)
- `def remove_edge(self, vertex1, vertex2):`
 - Precondition: edge must already exist in graph
 - Remove an edge from current graph
 - Returns: True (if edge can be removed) ; False (otherwise)
- `def update_edge_cost(self, vertex1, vertex2, cost):`
 - Precondition: edge must already exist in graph
 - Updates the cost of the edge represented by the (start edge, destination_edge)
- `def parse_vertices(self):`
 - Iterator for the vertices of graph
- `def parse_inbound_vertices(self, vertex):`
 - Iterator for the inbound vertices of given vertex
- `def parse_outbound_vertices(self, vertex):`
 - Iterator for the outbound vertices of given vertex
- `def get_in_degree(self, vertex):`
 - Precondition: Vertex must exist
 - Returns the in degree of vertex or -1 if it doesn't exist
- `def get_out_degree(self, vertex):`
 - Precondition: Vertex must exist
 - Returns the out degree of vertex or -1 if it doesn't exist
- `def make_copy_of_current_graph(self):`
 - Makes a copy of current graph and returns the last copy from the list of copies.

Implementation

The class **DirectedGraph** is initialized with the following data:

- `self._nr_vertices` = the number of vertices for current graph
- `self._nr_edges` = the number of edges for current graph
- `self.inbound_vertices` = a dictionary made for keeping the inbound vertices for each vertex
- `self.outbound_vertices` = a dictionary made for keeping the outbound vertices for each vertex

- `self.edges_costs` = a dictionary made for keeping track of each edge (the key) and its cost (the value).

The **external functions** are:

- `def generate_random_graph(num_vertices, num_edges):`
 - Generates a random graph using the given number of vertices and edges
 - Returns the random graph
- `def read_from_file(file_name):`
 - Precondition: File must exist
 - It receives the `file_name` from which the current graph should be read
- `def write_in_file(file_name,given_graph):`
 - It receives as parameters the name of the file where it writes the graph and the graph that has to be written.