What have we learned from the Case Histories

- Earth materials have a range of physical properties.
- Application of geophysics is carried out in a 7 Step process.
 Physical property of the target must be different from host material
- Knowledge of a single physical property does not uniquely identify a material. Interpretation was aided by using multiple surveys.
- Examples:
 - Gravel quaries: conductivity, elastic parameters
 - Karst investigations: density, conductivity
 - Mining: conductivity, chargeability

MAGNETIC SURVEYING

Principles for using Geophysics

Interpret geophysical results

Geoscientific /
Engineering
Question

What is the problem to be solved?

Physical Properties

Physical Properties


Physical Processing

Inversion

Some motivating examples for the use of magnetic susceptibility


- Geologic mapping
- Ore deposits
- Geotechnical problems
- Unexploded ordnance
- Buried foundations
- Archeology


Need for Magnetics: Geologic mapping



Geology contacts can be inferred from mag maps.

Need for magnetics: Mineral exploration






Need for Magnetics: UXO










Magnetic materials and Magnetization

 Earth materials are built up of minerals that behave as small magnets





Bar Magnet




North pole and South pole (dipole)

 Dipole moment m is related to the strength of the magnet

Field lines extend from the north pole to the south poles

Magnetic materials and Magnetization

 Earth materials are built up of minerals that behave as small magnets



- Strength of each magnet is given by the magnetic moment $m_i \ A$ - m^2


• Magnetization $M = \frac{\Sigma m_i}{Volume}$

Units: A/m dipole moment per unit volume


When the particles are randomly distributed M can be zero

Small magnets in presence of large ones


Opposite poles attract



Like poles repel




Small magnets align with fields of a larger magnet




Magnetic Susceptibility: K

□ Ability for a rock to become "magnetized" when an external magnetic field is applied.

Units: dimensionless







 $\ \, \square \, \, \text{Magnetization:} \ \, M = \frac{\Sigma m_i}{Volume}$

Units: Dipole moment per unit volume

Magnetic Susceptibility of Rocks




Magnetic Survey



Subsurface

Physical Property:





Earth's Magnetic field

Geomagnetic dynamo.


 Complicated inside the earth near the core.

Outside the earth it looks like a magnetic field due to a dipole.





Magnetics – Earth's field




Magnetic fields and definitions

 \vec{B} : Magnetic Flux Density $(Wb/m^2 = \text{Tesla})$

 \vec{H} : Magnetic Field (A/m)

$$\vec{B} = \mu \vec{H}$$

$$\mu = \text{magnetic permeability}$$
 $\mu = \mu_0(1 + \kappa)$




Magnetic permeability of free space:

$$\mu_0 = 4\pi \times 10^{-7}$$


Magnetics – Earth's field

- Link to GPG
- How is the field described anywhere?
 - X, Y, Z
 - Inclination, Declination, Magnitude
- Compass? Inclination?
- Declination?





Earth's field strength vs. anomalies.


Earth's Magnetic Field




Earth's magnetic field: Strength |B| Inclination I Declination D








 $\mathbf{B_{max}} = 70,000 \text{ nT}$ $\mathbf{H_{max}} = 55.7 \text{A/m}$ $\mathbf{B_{min}} = 20,000 \text{ nT}$ $\mathbf{H_{min}} = 15.9 \text{A/m}$




http://www.ngdc.noaa.gov/cgi-bin/seg/gmag/igrfpg.pl

Magnetic Survey




Subsurface

Physical Property:




Basics of Magnetics Surveying


Earth's magnetic field is the source:



Materials in the earth become magnetized $\vec{M} = \kappa \vec{H}$ (dipole moment per unit volume)



 Magnetized rocks create anomalous (compact object looks like a magnetic dipole)



 The anomalous field is a vector. To view we project it onto specific directions (x, y, z)

Magnetic Applet

Simulating the field due to prisms

Define a 3D prism


Our model is a rectangular prism. Parameters to define this prism are given below:


- dx: length in Easting (x) direction (meter)
- · dy: length in Northing (y) direction (meter)
- · dz: length in Depth (z) direction (meter) below the receiver
- · depth: top boundary of the prism (meter)
- pinc: inclination of the prism (reference is a unit northing vector; degree)
- · pdec: declination of the prism (reference is a unit northing vector; degree)

You can also change the height of the survey grid above the ground

• rx h: height of the grid (meter)

Green dots show a plane where we measure data.





Magnetic applet

Based on the prism that you made above, below Magnetic applet computes magnetic field at receiver locations, and provide both 2D map (left) and profile line (right).


For the prism, you can alter:

· sus: susceptibility of the prism


Parameters for the earth field are:

- · Einc: inclination of the earth field (degree)
- . Edec: declination of the earth field (degree)
- Bigrf: intensity of the earth field (nT)

For data, you can view:



Computing G Computing G



True

Interactive and live ... click here