

# UNCERTAINTY IN GEO-SCIENCE: A WORKSHOP ON HAZARD ANALYSIS

Prof. Abani Patra

University at Buffalo

15-17 March , 2016

# OUTLINE

Problem Definition

LHS

PCQ

Instructions for LHS script

Instructions for PCQ script

# Problem Statement

Study of physical phenomena involved with uncertainty in input parameters:

- **Intrusive:** change the original governing equation.
  - Polynomial Chaos Stochastic Galerkin.
  - Perturbation methods
  - ...
- **Non-intrusive:** *do not* change the original governing equation.
  - Monte Carlo & LHS
  - Important sampling Methods
  - Non-intrusive spectral projection (NISP)
  - ...

# Latin Hypercube Sampling (LHS)

Generating a sample set of uncertain values from equally probable intervals of the probability density function.

- 1 Select the pdf
- 2 Select the number of samples
- 3 Divide the pdf function into equal probability intervals.
- 4 Generate random samples on each interval.

## **Advantage:**

- Much less number of samples require for convergence compared to MC
- No need to change the original solver (like any other non-intrusive method)

# Polynomial Chaos Quadrature (PCQ)

The basic idea comes from projection theory that each function can be written as an expansion of a series of orthogonal function:

$$h(\eta) = \sum_i a_i \psi_i(\eta) \quad (1)$$

So any uncertain parameter in the model can be expressed as above. The inner product of  $h(\eta)$  and  $j$ th basis function is

$$\langle h(\eta), \psi_j(\eta) \rangle = \langle \sum_i a_i \psi_i(\eta), \psi_j(\eta) \rangle \quad (2)$$

Due to linear property of the inner product and orthogonality of basis:

$$\langle h(\eta), \psi_j(\eta) \rangle = a_i \langle \psi_i(\eta), \psi_j(\eta) \rangle \quad (3)$$

$$a_i = \frac{\langle \psi_i(\eta), \psi_j(\eta) \rangle}{\langle h(\eta), \psi_j(\eta) \rangle} \quad (4)$$

# Polynomial Chaos Quadrature (PCQ)

The integration is then approximated using the concept of the quadrature points.

By definition, inner product with respect to certain distribution is:

$$\begin{aligned} \langle h(\eta), \psi_j(\eta) \rangle &= \int_{-\infty}^{\infty} h(\eta) \psi_j(\eta) p(\eta) d\eta \\ &= \sum_i h(\eta_i) \psi_j(\eta_i) w_i \end{aligned} \tag{5}$$

$$\langle \psi_j(\eta), \psi_j(\eta) \rangle = \sum_k \psi_j(\eta_k) \psi_j(\eta_k) w_k \tag{6}$$

# Instructions for LHS script

To run LHS\_UQ you just need to do the following:

- Open a python interpreter by typing python on your terminal.
- To load the LHS\_UQ function type: `from LHS import LHS_UQ`
- To run the function you need to provide the following arguments by typing:  
`LHS_UQ(num_samples , min_wat_cont , range_wat_cont , min_temp ,range_temp):`
  - 1 number of samples
  - 2 minimum of water content
  - 3 range of water content
  - 4 minimum of temperature
  - 5 range of temperature

# Instructions for PCQ script

The basic procedure of running the PCQ script:

- Generate sample points and quadrature weight
- Run simulation with sampled parameters
- Parse output file and extract desired properties
- Prepare for coefficient computing
- compute coefficient by PCQ (or by solving system of equations)
- Plot plume height (or mass loading) as a function of random parameters
- Plot histogram of plume height (or mass loading) for specific distribution of input parameters



# Instructions for PCQ script

- **Generate sample points and quadrature weight:**
  - The Gaussian Quadrature points generator should be called accordingly based on distribution that you selected: Hermite for Gaussian, Legendre for Uniform, Leguerre for Gamma, and Jacobi for Beta (modify `smplingx=...`)
  - Transfer and scale sample points (do not need modification)
- **Run simulation with sampled parameters:**

Leave it as it is
- **Parse output file and extract desired properties:**

Leave it as it is
- **Prepare for coefficient computing:**

Leave it as it is
- **compute coefficient by PCQ (or by solving system of equations):**

Leave it as it is

# Instructions for PCQ script

- **Plot plume height (or mass loading) as a function of random parameters:**  
Maybe need to modify the xlabel and ylabel, title...
- **Plot histogram of plume height (or mass loading) for specific distribution of input parameters:**  
You can try different number of bins ect. depends on you.

THANK YOU ...