

EECS 391

Intro to AI

Constraint Satisfaction Problems

L8 Tue Sep 26, 2017

What we've covered so far

- Problem solving with search
 - many ways to define problem spaces
 - many different algorithms to find solutions
 - Uniformed search: BFS, DFS, UCS, DLS, ID DFS, BDS
 - Informed search: Heuristics, Greedy BFS, A*, RBFS, IDA*, SMA*
 - Local search: Hill Climbing, stochastic HC, local beam search (book: SA, GA)
- Main idea: problem solving is defined by searching in a space of states
- Game Playing
 - ways to define game trees, utility, stochastic games
 - Minimax, alpha-beta pruning, evaluation functions
- Today: Constraint Satisfaction Problems (CSPs)

Note: Much of this lecture was written out on the board.

Key concepts today

- introducing constraint satisfaction problems (CSPs)
- defining and representing CSPs
- backtracking search for CSPs
- heuristics for reducing size of the search space
 - minimum remaining values
 - degree heuristic
- types of constraint satisfaction problems


Constraint satisfaction example: Map coloring



How do we assign colors to each region so that no neighboring regions have the same color?

Using a graph to represent constraints

- no connected nodes can have same color
- all we need to do is find a valid (i.e. consistent) assignment



Backtracking search

Equiv. to DFS but only
one successor at a time:
 $O(m)$ vs $O(bm)$ memory

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
 return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure
 if $assignment$ is complete **then return** $assignment$
 $var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)
 for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**
 if $value$ is consistent with $assignment$ **then**
 add $\{var = value\}$ to $assignment$
 $inferences \leftarrow$ INFERENCE(csp , var , $value$)
 if $inferences \neq failure$ **then**
 add $inferences$ to $assignment$
 $result \leftarrow$ BACKTRACK($assignment$, csp)
 if $result \neq failure$ **then**
 return $result$
 remove $\{var = value\}$ and $inferences$ from $assignment$
 return $failure$

Backtracking search

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
 return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure

if $assignment$ is complete **then return** $assignment$

$var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)

for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**

if $value$ is consistent with $assignment$ **then**

 add $\{var = value\}$ to $assignment$

$inferences \leftarrow$ INFERENCE(csp , var , $value$)

if $inferences \neq failure$ **then**

 add $inferences$ to $assignment$

$result \leftarrow$ BACKTRACK($assignment$, csp)

if $result \neq failure$ **then**

return $result$

 remove $\{var = value\}$ and $inferences$ from $assignment$

return $failure$

only need one: complete & valid

Backtracking search

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure
if $assignment$ is complete **then return** $assignment$

$var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)

for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**

if $value$ is consistent with $assignment$ **then**

add $\{var = value\}$ to $assignment$

$inferences \leftarrow$ INFERENCE(csp , var , $value$)

if $inferences \neq failure$ **then**

add $inferences$ to $assignment$

$result \leftarrow$ BACKTRACK($assignment$, csp)

if $result \neq failure$ **then**

return $result$

remove $\{var = value\}$ and $inferences$ from $assignment$

return $failure$

If not, try
assigning
another variable.
The order of
consideration will
be important.

Backtracking search

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure
if $assignment$ is complete **then return** $assignment$

$var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)

for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**

if $value$ is consistent with $assignment$ **then**

add $\{var = value\}$ to $assignment$

$inferences \leftarrow$ INFERENCE(csp , var , $value$)

if $inferences \neq failure$ **then**

add $inferences$ to $assignment$

$result \leftarrow$ BACKTRACK($assignment$, csp)

if $result \neq failure$ **then**

return $result$

remove $\{var = value\}$ and $inferences$ from $assignment$

return $failure$

Loop to search for the next valid assignment. The order of values considered will also be important.

Backtracking search

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
 return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure
 if $assignment$ is complete **then return** $assignment$

$var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)

for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**

if $value$ is consistent with $assignment$ **then**

 add $\{var = value\}$ to $assignment$

$inferences \leftarrow$ INFERENCE(csp , var , $value$)

if $inferences \neq failure$ **then**

 add $inferences$ to $assignment$

$result \leftarrow$ BACKTRACK($assignment$, csp)

if $result \neq failure$ **then**

return $result$

 remove $\{var = value\}$ and $inferences$ from $assignment$

return $failure$

Add new assignment if consistent with constraints.
--

Backtracking search

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
 return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure
 if $assignment$ is complete **then return** $assignment$
 $var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)
 for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**
 if $value$ is consistent with $assignment$ **then**
 add $\{var = value\}$ to $assignment$
 $inferences \leftarrow$ INFERENCE(csp , var , $value$)
 if $inferences \neq failure$ **then**
 add $inferences$ to $assignment$
 $result \leftarrow$ BACKTRACK($assignment$, csp)
 if $result \neq failure$ **then**
 return $result$
 remove $\{var = value\}$ and $inferences$ from $assignment$
 return $failure$

This uses constraint propagation (next lecture) to reduce the size of the search space.

Backtracking search

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
 return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure
 if $assignment$ is complete **then return** $assignment$
 $var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)
 for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**
 if $value$ is consistent with $assignment$ **then**
 add $\{var = value\}$ to $assignment$
 $inferences \leftarrow$ INFERENCE(csp , var , $value$)
 if $inferences \neq failure$ **then**
 add $inferences$ to $assignment$
 $result \leftarrow$ BACKTRACK($assignment$, csp)
 if $result \neq failure$ **then**
 return $result$
 remove $\{var = value\}$ and $inferences$ from $assignment$
 return $failure$

Use recursion to continue down search tree and expand solution.

Backtracking search

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
 return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure
 if $assignment$ is complete **then return** $assignment$
 $var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)
 for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**
 if $value$ is consistent with $assignment$ **then**
 add $\{var = value\}$ to $assignment$
 $inferences \leftarrow$ INFERENCE(csp , var , $value$)
 if $inferences \neq failure$ **then**
 add $inferences$ to $assignment$
 $result \leftarrow$ BACKTRACK($assignment$, csp)
 if $result \neq failure$ **then**
 return $result$
 remove $\{var = value\}$ and $inferences$ from $assignment$
 return $failure$

If we made it here, it means the assignment resulted in an inconsistency, so we have to remove it.

Backtracking search

function BACKTRACKING-SEARCH(csp) **returns** a solution, or failure
 return BACKTRACK($\{ \}$, csp)

function BACKTRACK($assignment$, csp) **returns** a solution, or failure
 if $assignment$ is complete **then return** $assignment$
 $var \leftarrow$ SELECT-UNASSIGNED-VARIABLE(csp)
 for each $value$ **in** ORDER-DOMAIN-VALUES(var , $assignment$, csp) **do**
 if $value$ is consistent with $assignment$ **then**
 add $\{var = value\}$ to $assignment$
 $inferences \leftarrow$ INFERENCE(csp , var , $value$)
 if $inferences \neq failure$ **then**
 add $inferences$ to $assignment$
 $result \leftarrow$ BACKTRACK($assignment$, csp)
 if $result \neq failure$ **then**
 return $result$
 remove $\{var = value\}$ and $inferences$ from $assignment$
 return $failure$

And finally, this means no solution could be found.

Algorithmic design




Berkley Mills
Lambda Chair

- What if algorithms could “design” chairs?
- Arthur Harsuvanakit and Brittany Presten of Autodesk’s generative design lab

- Use Autodesk’s Dreamcatcher


Define



Generate




Explore



Fabricate



- Given constraints:
 - seat is 18” off floor; can hold 300 lbs; arms are clear of human body
- Algorithm:
 - shaved dead weight; adjusted joint placement to improve strength
 - could select interesting designs and iterate from there
- Result:
 - 18% less material; stronger

A close-up photograph of a wooden chair, specifically focusing on the seat and the intricate, organic structure of the legs and backrest. The wood is a light, warm brown color with a visible grain. The design is highly sculptural, with the legs and backrest pieces curving and branching out like natural bone or antlers. The seat is a simple, flat wooden plank. The background is a plain, light gray.

The “bone” chair

The “bone” chair

