

# **IBM MICROSERVICE I SESSION 1**


**TEXAS SKILLS DEVELOPMENT FUND  
TRAINING PARTNERSHIP**




# Course Overview

- The evolution of containers
  - VM, Containers, Docker, Kubernetes, OpenShift
- Container Security
- Hands-on Lab
- Istio & KNative

# N-Tier Architecture



# Linux (OS) Architecture



# Containers vs. Virtual Machines

- VM
  - Abstraction –OS, memory, storage
  - Image – OS or Entire App Fabric (incl. target app)
  - Completely isolated host & VMs
- Require more resources to scale
- [Containers vs. Virtual Machines](#)
  - [What's the Difference?](#)
- Container
  - Occupy part of existing m/c
  - Share Kernel & lib files
  - Self contained images
  - Less Resources
  - Faster to scale
- Too many microservices can result in bloat

# Containers Transform



**Monolith**



**N-Tier**



**Microservices**

**Applications**



**Datacenter**



**Hosted**



**Hybrid**

**Infrastructures**



**Waterfall**



**Agile**



**DevOps**

**Processes**


# DevOps

- Developers

- Package application and all of its dependencies
- Deploy to any environment in seconds and enable CI/CD
- Easily access and share containerized components

- Operations

- Sandboxed application processes on a shared Linux OS kernel
- Simpler, lighter, and denser than virtual machines
- Portable across different environments




# Critical features for both Dev and Ops





# Container Architecture




# Open Container Initiative

- Image Format Specification
- Interoperable tools to run containers
  - Building, transport, preparation
- Image Layout, Manifest
- Image Index
- Filesystem Layers
- Image Configuration
- Annotations
- Conversion
- Considerations
  - Extensibility
  - Canonicalization

[image-spec/spec.md at master · opencontainers/image-spec · GitHub](https://github.com/opencontainers/image-spec/blob/master/spec.md)

# Enterprise Needs

## Container Runtime



## Challenges

- Inter-services communication
  - > 100s
- Application Management over all associated containers
  - Container elasticity (scale up/down)
  - Service performance management
  - Release Train

# Kubernetes – Features & Needs

## Features

- Orchestrate containers across multiple hosts.
- Maximize resources needed to run enterprise apps.
- Control and automate application deployments and updates.
- Mount and add storage to run stateful apps.
- Scale containerized applications and their resources on the fly.
- Declaratively manage services, which guarantees the deployed applications are always running as designed
- Health-check and self-heal apps with auto-placement, auto-restart, auto-replication, and autoscaling.


## Needs

- Registry, e.g. Docker Registry.
- Networking – OpenvSwitch, intelligent edge routing.
- Telemetry - Kibana, Hawkular, and Elastic.
- Security - LDAP, SELinux, RBAC, OAUTH with multitenancy layers.
- Automation - Ansible playbooks for installation and cluster life cycle management.
- Services, through a rich catalog of popular app patterns

[What is Kubernetes?](#)

# Kubernetes Service Patterns


- Foundational
- Health Probe
- Predictable Demands
- Automated Placement
- Structural
  - Init Container & Sidecar
- Behavioral
  - Batch Job, Stateful Discovery
- Higher-level
  - Controller, Operator




# Kubernetes + OpenShift

- Developer
  - Built-in CI/CD workflow platform
  - Command-line interfaces
    - Node, Java, Ruby, Perl, PHP, Python
    - Odo – create, push, watch
- Operator
  - Leverage existing infrastructure
    - Physical, virtual
    - On-premise & Cloud
    - Hybrid & Multi-Cloud

- OpenShift Operator Framework
  - Community & Certified




- Operator SDK
- Operator package manager



- Operator metering

# OpenShift Features

## What's included




# Red Hat OpenShift Container Platform

- Set of modular components and services
  - Red Hat CoreOS and Kubernetes.
- PaaS capabilities
  - Remote management, increased security, monitoring and auditing, application life-cycle management, and self-service interfaces for developers.
- An OpenShift cluster = Kubernetes cluster + OpenShift management tools
  - CLI, web console for productive workflows and easy to execute common tasks

Term	Definition
Infra Node	Node server - infrastructure services (monitoring, logging, or external routing)
Console	A web UI to interact with cluster resources.
Project	OpenShift's extension of Kubernetes' namespaces Allows UAC definition for resources



# OpenShift & K8s Architecture



## Container Orchestration Software (Docker, Openshift & Kubernetes)




### Automate:

- Configuration
- Provisioning
- Availability
- Scaling
- Security
- Resource allocation
- Load balancing
- Health monitoring



### Application Environment w/ Multiple Containers




# Kubernetes & OpenShift

[Kubernetes Explained](#)

[What is OpenShift?](#)

[Kubernetes and OpenShift: What's the Difference?](#)



# OpenShift Architecture

- Base - Red Hat CoreOS
  - Immutable operating system for container execution
- CRI-O - Kubernetes Container Runtime Interface to enable using OCI compatible runtimes
  - CRI-O can use any container runtime that satisfies CRI
  - rune (used by the Docker service), libpod (used by Podman) or rkt (from CoreOS).
- *Resources*
  - Describe multi-container applications connection
- *Etcd* - distributed key-value store
  - Configuration and state information in cluster
- *Custom Resource Definitions (CRDs)*
  - resource types stored in Etcd
  - Form the state and configuration of all resources managed by OpenShift

# OpenShift Architecture

- PaaS infrastructure functions - networking and authorization
  - RHOCP uses the basic container infrastructure from Kubernetes and the underlying container runtime for most internal functions
  - Most RHOCP internal services run as containers orchestrated by Kubernetes
- Runtimes and x-PaaS - base container images for developers
  - Preconfigured with a particular runtime, e.g., JBoss EAP and ActiveMQ.
  - *Red Hat OpenShift Application Runtimes (RHOAR)* - runtimes optimized for cloud native applications in OpenShift.
  - Red Hat JBoss EAP, OpenJDK, Thorntail, Eclipse Vert.x, Spring Boot, and Node.js.
- DevOps tools and user experience
  - RHOCP provides web UI and CLI management tools
  - OpenShift web UI and CLI tools - REST APIs

# OpenShift, K8s Resource Types

- OpenShift
  - Deployment config
  - Build config
  - Routes
- Kubernetes
  - Pods
  - Services
  - Replication Controllers
  - Persistent Volumes
  - PV Claims
  - ConfigMaps
  - Secrets

# Networking

- Each container in a Kubernetes cluster has an IP address assigned from an internal network
  - Accessible only from the node running the container
  - Container's ephemeral nature, IP addresses are constantly assigned and released.
- Kubernetes *software-defined network (SDN)*
  - Internal container networks from multiple nodes
  - Allows containers from any pod, inside any host, to access pods from other hosts
  - Access to the SDN only works from inside the same Kubernetes cluster
- Containers inside Kubernetes pods should not connect to each other's dynamic IP address directly
- Services resolves this problem by linking more stable IP addresses from the SDN to the pods. If pods are restarted, replicated, or rescheduled to different nodes, services are updated, providing scalability and fault tolerance.
- External access to containers – NodePort attribute; not scalable
- *OpenShift Route* resources – external access scalable and simpler
  - Route defines external-facing DNS names and ports for a service
  - A router (ingress controller) forwards HTTP and TLS requests to the service addresses inside the Kubernetes SDN
  - The only requirement is that the desired DNS names are mapped to the IP addresses of the RHOCP router nodes.





Accenture



ViaVarejo



Runtastic



Walls.io



Proshore



all



TOKIGAMES  
TECH



Ericsson



DBS C2E



The Walt  
Disney ...



ConnectedM  
obility



Nuxeo



DevSecOps



DevOps



Samsviran



STS



Infrastructure



Interhyp AG



TECLO-  
INOMERA



system



Hazeorid



Node  
backend



Melio  
Consulting



BI X Digital  
Lab



Vungle



Shpock



Cloud9 IDE



Streamdata.i  
o



dotgroup



Prattle



Huia



API  
Evangelist



datahub



Ukuli Data



CXDA



Red Hat  
Developer ...



CSAG



Thybit



budikom.net



Intelinvest



Mobile  
Enterprise



Codecraft  
Solutions



LooWID



Digistarters



Obsdeck  
Software

# OpenShift Business Value

**636%**  
five-year ROI

**10 months**  
to payback

**20% higher**  
DevOps and development  
team productivity

**Almost 3x**  
more new features

**29% faster**  
application development  
life cycles

**\$21.62M**  
in higher annual revenue

**22% fewer**  
VMs required

**21% more efficient**  
IT infrastructure teams

[https://www.redhat.com/rhdc/managed-files/cl-idc-business-value-openshift-analyst-material-f28051-202104-en\\_0.pdf](https://www.redhat.com/rhdc/managed-files/cl-idc-business-value-openshift-analyst-material-f28051-202104-en_0.pdf)

# OpenShift Labs

- [Red Hat OpenShift on IBM Cloud](#)
- [Develop in a preconfigured OpenShift environment available for four hours at no charge](#)
- [Getting started with Red Hat OpenShift](#)

# Quay

- [Quay Documentation](#)
- Can use GitHub credentials

# Podman

- [Podman](#)
- What is Podman?
  - Simply put: **alias docker=podman**
  - [What is podman?](#)
- [podman/README.md at master · containers/podman \(github.com\)](#)
  - [Podman commands](#)
    - Search, pull, images
    - registry\_name/user\_name/image\_name:tag
  - [Run command](#), [Inspect \(configuration\)](#)
    - Interactive terminal and detach modes, environment variables
- [Red Hat Universal Base Image \(container\)](#)

# Podman



- Podman is a daemonless, open source, Linux native tool
  - Find, run, build, share and deploy applications using Open Containers Initiative (OCI) Containers and Container Images
- Podman provides a command line interface (CLI) similar to Docker
  - Alias Docker to Podman (alias docker=podman)
  - OCI compliant Container Runtime
  - Interface with the operating system and create the running container
  - Indistinguishable from any other common container engine
- Podman manages the entire container ecosystem
  - Pods, containers, container images, and container volumes using the libpod library

# Red Hat Container Catalog

- Over 5000 images
- [Red Hat Ecosystem Catalog](#)