

CryptoWorks21: Post-quantum cryptography

Assignment

(Due date: August 08, 2017)

Javad Doliskani and Geovandro Pereira

July 26, 2017

Problem 1

Consider the definition of the Rainbow signature scheme (slide 24 from the set of MPKC slides available at [cw21-post-quantum-II.pdf](#)). Also consider the UOV signature scheme magma implementation provided at [uov-impl.mag](#). Now, extend the UOV implementation to the simplest case of Rainbow, i.e., a two layer Rainbow with parameters given in the toy example (slide 26) w.r.t the following operations:

- a) Key pair generation
- b) Sign
- c) Verify

P.S.: You can use the Magma website to test your code: <http://magma.maths.usyd.edu.au/calc/> and the online documentation to learn about the Magma language itself <http://magma.maths.usyd.edu.au/magma/handbook/>.

Problem 2

- a) Implement the Mersenne LH cryptosystem using your favorite language. Use the parameters $n = 1279$, $h = 17$. The prime is defined as $p = 2^n - 1$. The original reference can be obtained at <https://eprint.iacr.org/2017/481.pdf>
- b) (Bonus) For a given security parameter λ , i.e. to have λ bits of classical security, it is needed that $\binom{n-1}{h-1} \geq 2^\lambda$. Explain.