

Post-quantum cryptography II

Geovandro C. C. F. Pereira

Institute for Quantum Computing
University of Waterloo

Agenda

- Multivariate quadratic Public Key Cryptosystems (MPKC)

Multivariate quadratic public key cryptosystems (MPKC)

Why quadratic?

Given a system of cubic (or higher degree) equations

$$x_1 x_2 x_3 + 2x_1 x_3 - 3x_2^2 x_3 - 7 = 0$$

.....

$$-x_1 x_2 + x_1 x_3 + 6x_3^3 - 7 = 0$$

Multivariate quadratic public key cryptosystems (MPKC)

Why quadratic?

Given a system of cubic (or higher degree) equations

$$x_1 \mathbf{x_2 x_3} + 2x_1 x_3 - 3\mathbf{x_2^2 x_3} - 7 = 0$$

.....

$$-x_1 x_2 + x_1 x_3 + 6\mathbf{x_3^3} - 7 = 0$$

- One can always do **degree reduction** or **linearization** by introducing new variables $\mathbf{x_4} = x_2 x_3$ and $\mathbf{x_5} = x_3^2$

Multivariate quadratic public key cryptosystems (MPKC)

Why quadratic?

Given a system of cubic (or higher degree) equations

$$x_1 x_2 x_3 + 2x_1 x_3 - 3x_2^2 x_3 - 7 = 0$$

.....

$$-x_1 x_2 + x_1 x_3 + 6x_3^3 - 7 = 0$$

- One can always do **degree reduction** or **linearization** by introducing new variables $x_4 = x_2 x_3$ and $x_5 = x_3^2$

$$x_1 x_4 + 2x_1 x_3 - 3x_2 x_4 - 7 = 0$$

.....

$$-x_1 x_2 + x_1 x_3 + 6x_3 x_5 - 7 = 0$$

Multivariate quadratic public key cryptosystems (MPKC)

Why quadratic?

Given a system of cubic (or higher degree) equations

$$x_1 x_2 x_3 + 2x_1 x_3 - 3x_2^2 x_3 - 7 = 0$$

.....

$$-x_1 x_2 + x_1 x_3 + 6x_3^3 - 7 = 0$$

- One can always do **degree reduction** or **linearization** by introducing new variables $x_4 = x_2 x_3$ and $x_5 = x_3^2$

$$x_1 x_4 + 2x_1 x_3 - 3x_2 x_4 - 7 = 0$$

.....

$$-x_1 x_2 + x_1 x_3 + 6x_3 x_5 - 7 = 0$$

- Solve the quadratic system for the new variables and backtrack.

Multivariate quadratic public key cryptosystems (MPKC)

Notation

Let \mathbb{F}_q denote a finite field of q elements where q is a prime power. A generic quadratic map $p : (\mathbb{F}_q)^n \rightarrow \mathbb{F}_q$ can be represented by a quadratic polynomial

$$p(x_1, \dots, x_n) = \sum_{1 \leq i < j \leq n} \alpha_{ij} x_i x_j + \sum_{1 \leq i \leq n} \beta_i x_i + \gamma$$

where $\alpha_{ij}, \beta_i, \gamma \in \mathbb{F}_q$.

Multivariate quadratic public key cryptosystems (MPKC)

Notation

- For many MPKC cryptosystems the linear and constant terms of p do not contribute to security and therefore can be omitted.

Multivariate quadratic public key cryptosystems (MPKC)

Notation

- For many MPKC cryptosystems the linear and constant terms of p do not contribute to security and therefore can be omitted.
- That means we can use a purely quadratic map f of form:

$$(x_1, \dots, x_n) \mapsto \sum_{1 \leq i \leq j \leq n} \alpha_{ij} x_i x_j$$

Multivariate quadratic public key cryptosystems (MPKC)

Notation

- For many MPKC cryptosystems the linear and constant terms of p do not contribute to security and therefore can be omitted.
- That means we can use a purely quadratic map f of form:

$$(x_1, \dots, x_n) \mapsto \sum_{1 \leq i \leq j \leq n} \alpha_{ij} x_i x_j$$

- A useful matrix representation can also be used:

$$[x_1, \dots, x_n] \begin{bmatrix} \alpha_{11} & \alpha_{12} & \dots & \alpha_{1n} \\ 0 & \alpha_{22} & \dots & \alpha_{2n} \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \alpha_{nn} \end{bmatrix} \begin{bmatrix} x_1 \\ \vdots \\ x_n \end{bmatrix} = \sum_{1 \leq i \leq j \leq n} \alpha_{ij} x_i x_j$$

Multivariate quadratic public key cryptosystems (MPKC)

\mathcal{MQ} problem: **NP-hard** [Patarin and Goubin 1997]

- Given a system of m random quadratic equations in n variables over a finite field \mathbb{F}_q of any characteristic

$$\begin{cases} p_1(x_1, \dots, x_n) = y_1 \\ p_2(x_1, \dots, x_n) = y_2 \\ \dots \dots \dots = \dots \\ p_m(x_1, \dots, x_n) = y_m \end{cases}$$

Multivariate quadratic public key cryptosystems (MPKC)

Public key sizes

- Usually, public keys P consist of m quadratic polynomials of shape:

$$p_i(x) = [x_1, \dots, x_n] \begin{bmatrix} \alpha_{11}^{(i)} & \alpha_{12}^{(i)} & \dots & \alpha_{1n}^{(i)} \\ 0 & \alpha_{22}^{(i)} & \dots & \alpha_{2n}^{(i)} \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \alpha_{nn}^{(i)} \end{bmatrix} \begin{bmatrix} x_1 \\ \vdots \\ x_n \end{bmatrix}$$

Multivariate quadratic public key cryptosystems (MPKC)

Public key sizes

- Usually, public keys P consist of m quadratic polynomials of shape:

$$p_i(x) = [x_1, \dots, x_n] \begin{bmatrix} \alpha_{11}^{(i)} & \alpha_{12}^{(i)} & \dots & \alpha_{1n}^{(i)} \\ 0 & \alpha_{22}^{(i)} & \dots & \alpha_{2n}^{(i)} \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \alpha_{nn}^{(i)} \end{bmatrix} \begin{bmatrix} x_1 \\ \vdots \\ x_n \end{bmatrix}$$

- Thus, the number of elements is

$$mn(n+1)/2 \stackrel{m \approx n}{\approx} O(n^3)$$

Multivariate quadratic public key cryptosystems (MPKC)

Public key sizes

- Usually, public keys P consist of m quadratic polynomials of shape:

$$p_i(x) = [x_1, \dots, x_n] \begin{bmatrix} \alpha_{11}^{(i)} & \alpha_{12}^{(i)} & \dots & \alpha_{1n}^{(i)} \\ 0 & \alpha_{22}^{(i)} & \dots & \alpha_{2n}^{(i)} \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \alpha_{nn}^{(i)} \end{bmatrix} \begin{bmatrix} x_1 \\ \vdots \\ x_n \end{bmatrix}$$

- Thus, the number of elements is

$$mn(n+1)/2 \stackrel{m \approx n}{\approx} O(n^3)$$

- In general, for degree d polynomials, the size is $O(n^{d+1})$.

Multivariate quadratic public key cryptosystems (MPKC)

Public key sizes

- Usually, public keys P consist of m quadratic polynomials of shape:

$$p_i(x) = [x_1, \dots, x_n] \begin{bmatrix} \alpha_{11}^{(i)} & \alpha_{12}^{(i)} & \dots & \alpha_{1n}^{(i)} \\ 0 & \alpha_{22}^{(i)} & \dots & \alpha_{2n}^{(i)} \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \alpha_{nn}^{(i)} \end{bmatrix} \begin{bmatrix} x_1 \\ \vdots \\ x_n \end{bmatrix}$$

- Thus, the number of elements is

$$mn(n+1)/2 \stackrel{m \approx n}{\approx} O(n^3)$$

- In general, for degree d polynomials, the size is $O(n^{d+1})$.
 - \Rightarrow not a good idea to have high degree polynomials.

Multivariate quadratic public key cryptosystems (MPKC)

Public key sizes

- Usually, public keys P consist of m quadratic polynomials of shape:

$$p_i(x) = [x_1, \dots, x_n] \begin{bmatrix} \alpha_{11}^{(i)} & \alpha_{12}^{(i)} & \dots & \alpha_{1n}^{(i)} \\ 0 & \alpha_{22}^{(i)} & \dots & \alpha_{2n}^{(i)} \\ \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & \alpha_{nn}^{(i)} \end{bmatrix} \begin{bmatrix} x_1 \\ \vdots \\ x_n \end{bmatrix}$$

- Thus, the number of elements is

$$mn(n+1)/2 \stackrel{m \approx n}{\approx} O(n^3)$$

- In general, for degree d polynomials, the size is $O(n^{d+1})$.
 - \Rightarrow not a good idea to have high degree polynomials.
 - Stick to $d = 2$.

Multivariate quadratic public key cryptosystems (MPKC)

(Generic) Encryption

- Public key:

$$P = \{p_1(x_1, \dots, x_n), \dots, p_m(x_1, \dots, x_n)\}$$

Multivariate quadratic public key cryptosystems (MPKC)

(Generic) Encryption

- Public key:

$$P = \{p_1(x_1, \dots, x_n), \dots, p_m(x_1, \dots, x_n)\}$$

- To encrypt a document $d_1, \dots, d_n \in (\mathbb{F}_q)^n$, evaluate

$$(c_1, \dots, c_m) = (p_1(d_1, \dots, d_n), \dots, p_m(d_1, \dots, d_n))$$

Multivariate quadratic public key cryptosystems (MPKC)

(Generic) Encryption

- Public key:

$$P = \{p_1(x_1, \dots, x_n), \dots, p_m(x_1, \dots, x_n)\}$$

- To encrypt a document $d_1, \dots, d_n \in (\mathbb{F}_q)^n$, evaluate

$$(c_1, \dots, c_m) = (p_1(d_1, \dots, d_n), \dots, p_m(d_1, \dots, d_n))$$

- To decrypt, a trapdoor is needed to solve the system for \mathbf{x} :

$$x_1, \dots, x_n = P^{-1}(c_1, \dots, c_m)$$

Multivariate quadratic public key cryptosystems (MPKC)

(Generic) Signature

- Public key P :

$$P = \{p_1(x_1, \dots, x_n), \dots, p_m(x_1, \dots, x_n)\}$$

Multivariate quadratic public key cryptosystems (MPKC)

(Generic) Signature

- Public key P :

$$P = \{p_1(x_1, \dots, x_n), \dots, p_m(x_1, \dots, x_n)\}$$

- Private key: a trapdoor to compute P^{-1}

Multivariate quadratic public key cryptosystems (MPKC)

(Generic) Signature

- Public key P :

$$P = \{p_1(x_1, \dots, x_n), \dots, p_m(x_1, \dots, x_n)\}$$

- Private key: a trapdoor to compute P^{-1}
- To sign a document $D \in \{0, 1\}^*$, compute the hash $\{h_1, \dots, h_m\} = H(D)$ and

$$\sigma = (x_1, \dots, x_n) = P^{-1}(h_1, \dots, h_m)$$

Multivariate quadratic public key cryptosystems (MPKC)

(Generic) Signature

- Public key P :

$$P = \{p_1(x_1, \dots, x_n), \dots, p_m(x_1, \dots, x_n)\}$$

- Private key: a trapdoor to compute P^{-1}
- To sign a document $D \in \{0, 1\}^*$, compute the hash $\{h_1, \dots, h_m\} = H(D)$ and

$$\sigma = (x_1, \dots, x_n) = P^{-1}(h_1, \dots, h_m)$$

- To verify σ , recompute $\{h_1, \dots, h_m\} = H(D)$ and check

$$p_i(\sigma) \stackrel{?}{=} h_i, \quad 1 \leq i \leq m$$

Multivariate quadratic public key cryptosystems (MPKC)

MPKC **Trapdoor**

- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps

Multivariate quadratic public key cryptosystems (MPKC)

MPKC **Trapdoor**

- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps
- Let $\mathcal{F} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ an invertible quadratic (central) map

Multivariate quadratic public key cryptosystems (MPKC)

MPKC Trapdoor

- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps
- Let $\mathcal{F} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ an invertible quadratic (central) map
- The map given by $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$ will be the public key

Multivariate quadratic public key cryptosystems (MPKC)


MPKC Trapdoor

- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps
- Let $\mathcal{F} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ an invertible quadratic (central) map
- The map given by $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$ will be the public key

Multivariate quadratic public key cryptosystems (MPKC)

MPKC Trapdoor


- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps
- Let $\mathcal{F} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ an invertible quadratic (central) map
- The map given by $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$ will be the public key



Multivariate quadratic public key cryptosystems (MPKC)

MPKC Trapdoor

- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps
- Let $\mathcal{F} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ an invertible quadratic (central) map
- The map given by $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$ will be the public key




- \mathcal{P} is random-looking and believed to be hard to invert.

Multivariate quadratic public key cryptosystems (MPKC)

MPKC Trapdoor

- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps
- Let $\mathcal{F} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ an invertible quadratic (central) map
- The map given by $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$ will be the public key




- \mathcal{P} is random-looking and believed to be hard to invert.
 - ▶ \mathcal{S} scrambles the variables

Multivariate quadratic public key cryptosystems (MPKC)

MPKC Trapdoor

- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps
- Let $\mathcal{F} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ an invertible quadratic (central) map
- The map given by $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$ will be the public key




- \mathcal{P} is random-looking and believed to be hard to invert.
 - ▶ \mathcal{S} scrambles the variables
 - ▶ \mathcal{T} mixes the polynomials

Multivariate quadratic public key cryptosystems (MPKC)

MPKC Trapdoor

- Let $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$ and $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ be two invertible linear maps
- Let $\mathcal{F} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ an invertible quadratic (central) map
- The map given by $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$ will be the public key



- \mathcal{P} is random-looking and believed to be hard to invert.
 - ▶ \mathcal{S} scrambles the variables
 - ▶ \mathcal{T} mixes the polynomials
- Related to the Isomorphism of Polynomials problem.

Multivariate quadratic public key cryptosystems (MPKC)

Isomorphism of Polynomials Problem (**IP-problem**)

Two systems of equations/polynomials $\mathcal{U}, \mathcal{V} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ are called **isomorphic** (up to linear transforms) iff \exists linear maps $\mathcal{L}_1, \mathcal{L}_2$ s.t.

$$\mathcal{U} = \mathcal{L}_1 \circ \mathcal{V} \circ \mathcal{L}_2$$

IP is in **NP** \cap **co-NP** !

Multivariate quadratic public key cryptosystems (MPKC)

Isomorphism of Polynomials Problem (**IP-problem**)

Two systems of equations/polynomials $\mathcal{U}, \mathcal{V} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ are called **isomorphic** (up to linear transforms) iff \exists linear maps $\mathcal{L}_1, \mathcal{L}_2$ s.t.

$$\mathcal{U} = \mathcal{L}_1 \circ \mathcal{V} \circ \mathcal{L}_2$$

IP is in **NP** \cap **co-NP** !

- In practice, the security of MPKC rely on a related problem that captures the concept of equivalent keys:

Multivariate quadratic public key cryptosystems (MPKC)

Isomorphism of Polynomials Problem (**IP-problem**)

Two systems of equations/polynomials $\mathcal{U}, \mathcal{V} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^m$ are called **isomorphic** (up to linear transforms) iff \exists linear maps $\mathcal{L}_1, \mathcal{L}_2$ s.t.

$$\mathcal{U} = \mathcal{L}_1 \circ \mathcal{V} \circ \mathcal{L}_2$$

IP is in **NP** \cap **co-NP** !

- In practice, the security of MPKC rely on a related problem that captures the concept of equivalent keys:

Extended Isomorphism of Polynomials (**EIP-problem**)

Given a public key $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$, find a map $\overline{\mathcal{F}}$ isomorphic to \mathcal{P} , i.e.,

$$\mathcal{P} = \overline{\mathcal{T}} \circ \overline{\mathcal{F}} \circ \overline{\mathcal{S}}$$

for some invertible $\overline{\mathcal{T}}$ and $\overline{\mathcal{S}}$, and $\overline{\mathcal{F}}$ inherits the trapdoor structure of \mathcal{F}

Important attacks

- **Direct attacks:** try to solve the public system.

Important attacks

- **Direct attacks:** try to solve the public system.
 - ▶ Encryption: given the ciphertext $c \in \mathbb{F}_q^m$, solve

$$\mathcal{P}(\mathbf{x}) = c$$

for the message $x \in \mathbb{F}_q^n$.

Important attacks

- **Direct attacks:** try to solve the public system.

- ▶ Encryption: given the ciphertext $c \in \mathbb{F}_q^m$, solve

$$\mathcal{P}(\mathbf{x}) = c$$

for the message $x \in \mathbb{F}_q^n$.

- ▶ Signature: given the hash $H(M) = h \in \mathbb{F}_q^m$ solve

$$\mathcal{P}(\mathbf{x}) = h$$

for the signature $x \in \mathbb{F}_q^n$.

Important attacks

- **Direct attacks:** try to solve the public system.

- ▶ Encryption: given the ciphertext $c \in \mathbb{F}_q^m$, solve

$$\mathcal{P}(\mathbf{x}) = c$$

for the message $x \in \mathbb{F}_q^n$.

- ▶ Signature: given the hash $H(M) = h \in \mathbb{F}_q^m$ solve

$$\mathcal{P}(\mathbf{x}) = h$$

for the signature $x \in \mathbb{F}_q^n$.

- Attacks are exponential when $m \approx n$

Important attacks

- **Direct attacks:** try to solve the public system.

- ▶ Encryption: given the ciphertext $c \in \mathbb{F}_q^m$, solve

$$\mathcal{P}(\mathbf{x}) = c$$

for the message $x \in \mathbb{F}_q^n$.

- ▶ Signature: given the hash $H(M) = h \in \mathbb{F}_q^m$ solve

$$\mathcal{P}(\mathbf{x}) = h$$

for the signature $x \in \mathbb{F}_q^n$.

- Attacks are exponential when $m \approx n$
- Grobner bases complexity $f(q, m, n)$:

$$f(q, m, n) = O \left(m \cdot \binom{n + d_{reg} - 1}{d_{reg}}^\omega \right)$$

where d_{reg} is degree of regularity of the system and $2 < \omega \leq 3$.

(cont. Important attacks ...)

- **Minrank** attacks. Find a low rank quadratic map.

MinRank

Given a set of n matrices M_i , find a nontrivial solution a_1, \dots, a_n s.t.

$$\sum_{i=1}^n a_i M_i$$

is of minimum rank.

Finding a low rank matrix implies that we have less independent equations
 \Rightarrow more variables per equation can make the system easier to solve.

Multivariate quadratic public key cryptosystems (MPKC)

Encryption: Requires $m \geq n$

- To encrypt a document $\mathbf{d} \in (\mathbb{F}_q)^n$, evaluate

$$\mathbf{c} = \mathcal{P}(\mathbf{d}) \in \mathbb{F}_q^m$$

Multivariate quadratic public key cryptosystems (MPKC)

Encryption: Requires $m \geq n$

- To encrypt a document $\mathbf{d} \in (\mathbb{F}_q)^n$, evaluate

$$\mathbf{c} = \mathcal{P}(\mathbf{d}) \in \mathbb{F}_q^m$$

- To decrypt, compute

Multivariate quadratic public key cryptosystems (MPKC)

Encryption: Requires $m \geq n$

- To encrypt a document $\mathbf{d} \in (\mathbb{F}_q)^n$, evaluate

$$\mathbf{c} = \mathcal{P}(\mathbf{d}) \in \mathbb{F}_q^m$$

- To decrypt, compute
 - ▶ $\mathbf{x} = \mathcal{T}^{-1}(\mathbf{c}) \in \mathbb{F}_q^m$

Multivariate quadratic public key cryptosystems (MPKC)

Encryption: Requires $m \geq n$

- To encrypt a document $\mathbf{d} \in (\mathbb{F}_q)^n$, evaluate

$$\mathbf{c} = \mathcal{P}(\mathbf{d}) \in \mathbb{F}_q^m$$

- To decrypt, compute

- ▶ $\mathbf{x} = \mathcal{T}^{-1}(\mathbf{c}) \in \mathbb{F}_q^m$

- ▶ $\mathbf{w} = \mathcal{F}^{-1}(\mathbf{x})$

Multivariate quadratic public key cryptosystems (MPKC)

Encryption: Requires $m \geq n$

- To encrypt a document $\mathbf{d} \in (\mathbb{F}_q)^n$, evaluate

$$\mathbf{c} = \mathcal{P}(\mathbf{d}) \in \mathbb{F}_q^m$$

- To decrypt, compute

- ▶ $\mathbf{x} = \mathcal{T}^{-1}(\mathbf{c}) \in \mathbb{F}_q^m$

- ▶ $\mathbf{w} = \mathcal{F}^{-1}(\mathbf{x})$

- ▶ $\mathbf{z} = \mathcal{S}^{-1}(\mathbf{w})$

Multivariate quadratic public key cryptosystems (MPKC)

Encryption: Requires $m \geq n$

- To encrypt a document $\mathbf{d} \in (\mathbb{F}_q)^n$, evaluate

$$\mathbf{c} = \mathcal{P}(\mathbf{d}) \in \mathbb{F}_q^m$$

- To decrypt, compute
 - ▶ $\mathbf{x} = \mathcal{T}^{-1}(\mathbf{c}) \in \mathbb{F}_q^m$
 - ▶ $\mathbf{w} = \mathcal{F}^{-1}(\mathbf{x})$
 - ▶ $\mathbf{z} = \mathcal{S}^{-1}(\mathbf{w})$
- If $m \geq n$ (not undetermined) then we ensure that \mathcal{F} is more or less injective and decryption is not mapped to many different plaintexts.

Encryption: The Matsumoto-Imai'88 **trapdoor**

- Define the central map to be

$$\mathcal{F} = \phi \circ \overline{\mathcal{F}} \circ \phi^{-1}$$

Encryption: The Matsumoto-Imai'88 trapdoor

- Define the central map to be

$$\mathcal{F} = \phi \circ \overline{\mathcal{F}} \circ \phi^{-1}$$

- $\phi : \mathbb{F}_{q^n} \rightarrow \mathbb{F}_q^n$ s.t.

$$a_n x^n + a_{n-1} x^{n-1} + \cdots + a_0 \mapsto (a_n, a_{n-1}, \cdots, a_0)$$

Encryption: The Matsumoto-Imai'88 trapdoor

- Define the central map to be

$$\mathcal{F} = \phi \circ \overline{\mathcal{F}} \circ \phi^{-1}$$

- $\phi : \mathbb{F}_{q^n} \rightarrow \mathbb{F}_q^n$ s.t.

$$a_n x^n + a_{n-1} x^{n-1} + \cdots + a_0 \mapsto (a_n, a_{n-1}, \cdots, a_0)$$

- and $\overline{\mathcal{F}} : \mathbb{F}_{q^n} \rightarrow \mathbb{F}_{q^n}$ defined by

$$\overline{\mathcal{F}} : X \mapsto X^{q^\theta+1}$$

Encryption: The Matsumoto-Imai'88 trapdoor

- Define the central map to be

$$\mathcal{F} = \phi \circ \overline{\mathcal{F}} \circ \phi^{-1}$$

- $\phi : \mathbb{F}_{q^n} \rightarrow \mathbb{F}_q^n$ s.t.

$$a_n x^n + a_{n-1} x^{n-1} + \cdots + a_0 \mapsto (a_n, a_{n-1}, \cdots, a_0)$$

- and $\overline{\mathcal{F}} : \mathbb{F}_{q^n} \rightarrow \mathbb{F}_{q^n}$ defined by

$$\overline{\mathcal{F}} : X \mapsto X^{q^\theta+1}$$

- Notice that $X^{q^\theta+1}$ is a quadratic transformation since q^θ is linear (q^θ -Frobenius).

Encryption: The Matsumoto-Imai'88 trapdoor

- Define the central map to be

$$\mathcal{F} = \phi \circ \overline{\mathcal{F}} \circ \phi^{-1}$$

- $\phi : \mathbb{F}_{q^n} \rightarrow \mathbb{F}_q^n$ s.t.

$$a_n x^n + a_{n-1} x^{n-1} + \cdots + a_0 \mapsto (a_n, a_{n-1}, \cdots, a_0)$$

- and $\overline{\mathcal{F}} : \mathbb{F}_{q^n} \rightarrow \mathbb{F}_{q^n}$ defined by

$$\overline{\mathcal{F}} : X \mapsto X^{q^\theta+1}$$

- Notice that $X^{q^\theta+1}$ is a quadratic transformation since q^θ is linear (q^θ -Frobenius).
- The quadratic transformation takes place in the big "hidden field" \mathbb{F}_{q^n} instead of the vector space over the smaller field, i.e., \mathbb{F}_q^n

(cont. ...)

Encryption: The Matsumoto-Imai'88 **trapdoor**

- Notice that for the quadratic map

$$\overline{\mathcal{F}} : X \mapsto X^{q^\theta+1}$$

to be invertible, the element $q^\theta + 1$ should be invertible since

$$(X^{q^\theta+1})(q^\theta+1)^{-1} = X.$$

(cont. ...)

Encryption: The Matsumoto-Imai'88 **trapdoor**

- Notice that for the quadratic map

$$\overline{\mathcal{F}} : X \mapsto X^{q^\theta + 1}$$

to be invertible, the element $q^\theta + 1$ should be invertible since

$$(X^{q^\theta + 1})(q^\theta + 1)^{-1} = X.$$

- The necessary condition for multiplicative inverses in $\mathbb{F}_{q^n}^*$ is

$$\text{GCD}(q^\theta + 1, q^n - 1) = 1$$

(cont. ...)

Encryption: The Matsumoto-Imai'88 **trapdoor**

- Notice that for the quadratic map

$$\overline{\mathcal{F}} : X \mapsto X^{q^\theta + 1}$$

to be invertible, the element $q^\theta + 1$ should be invertible since

$$(X^{q^\theta + 1})(q^\theta + 1)^{-1} = X.$$

- The necessary condition for multiplicative inverses in $\mathbb{F}_{q^n}^*$ is

$$\text{GCD}(q^\theta + 1, q^n - 1) = 1$$

- Therefore the quadratic map is invertible. The KeyGen, encryption and decryption for MI are done as generically explained before.

(cont. ...)

Encryption: The Matsumoto-Imai'88 **trapdoor**

- Later, MI was shown to be insecure by Patarin using linearization.

(cont. ...)

Encryption: The Matsumoto-Imai'88 **trapdoor**

- Later, MI was shown to be insecure by Patarin using linearization.
- Some variants were introduced as attempts to recover security.

(cont. ...)

Encryption: The Matsumoto-Imai'88 trapdoor

- Later, MI was shown to be insecure by Patarin using linearization.
- Some variants were introduced as attempts to recover security.
 - ▶ 2000, Patarin suggests **Hidden Field Equations (HFE)** encryption with a slightly modified trapdoor:

$$X \mapsto \sum_{i,j}^A \alpha_{ij} X^{q^i + q^j} + \sum_i \beta_i X^i + \gamma$$

(cont. ...)

Encryption: The Matsumoto-Imai'88 trapdoor

- Later, MI was shown to be insecure by Patarin using linearization.
- Some variants were introduced as attempts to recover security.
 - ▶ 2000, Patarin suggests **Hidden Field Equations (HFE)** encryption with a slightly modified trapdoor:

$$X \mapsto \sum_{i,j}^A \alpha_{ij} X^{q^i + q^j} + \sum_i \beta_i X^i + \gamma$$

- ▶ Later, Kipnis and Shamir showed that A cannot be too small otherwise minrank+linearization attacks apply.

(cont. ...)

Encryption: The Matsumoto-Imai'88 trapdoor

- Later, MI was shown to be insecure by Patarin using linearization.
- Some variants were introduced as attempts to recover security.
 - ▶ 2000, Patarin suggests **Hidden Field Equations (HFE)** encryption with a slightly modified trapdoor:

$$X \mapsto \sum_{i,j}^A \alpha_{ij} X^{q^i + q^j} + \sum_i \beta_i X^i + \gamma$$

- ▶ Later, Kipnis and Shamir showed that A cannot be too small otherwise minrank+linearization attacks apply.
- ▶ But if A is increased decryption becomes too slow.

(cont. ...)

Encryption: The Matsumoto-Imai'88 trapdoor

- Later, MI was shown to be insecure by Patarin using linearization.
- Some variants were introduced as attempts to recover security.
 - ▶ 2000, Patarin suggests **Hidden Field Equations (HFE)** encryption with a slightly modified trapdoor:

$$X \mapsto \sum_{i,j}^A \alpha_{ij} X^{q^i + q^j} + \sum_i \beta_i X^i + \gamma$$

- ▶ Later, Kipnis and Shamir showed that A cannot be too small otherwise minrank+linearization attacks apply.
- ▶ But if A is increased decryption becomes too slow.
- ▶ 2003, Faugere and Joux improved the attacks using **F4** and made the system impractical.

Multivariate quadratic public key cryptosystems (MPKC)

Signature: The UOV **trapdoor**, Kipnis, Patarin, and Goubin 1999

- Goal: $\mathcal{F}^{-1}(h) = (x_1, \dots, x_n)$

Multivariate quadratic public key cryptosystems (MPKC)

Signature: The UOV **trapdoor**, Kipnis, Patarin, and Goubin 1999

- Goal: $\mathcal{F}^{-1}(h) = (x_1, \dots, x_n)$
- Let $o, v \in \mathbb{N}$, define $n = o + v$ and $m = o$

Multivariate quadratic public key cryptosystems (MPKC)

Signature: The UOV **trapdoor**, Kipnis, Patarin, and Goubin 1999

- Goal: $\mathcal{F}^{-1}(h) = (x_1, \dots, x_n)$
- Let $o, v \in \mathbb{N}$, define $n = o + v$ and $m = o$
- Write the quadratic polynomials as the following:

$$p(x_1, \dots, x_n) = \underbrace{\sum_{i=1}^v \sum_{j=i}^v \alpha_{ij} x_i x_j}_{v \times v \text{ terms}} + \underbrace{\sum_{i=1}^v \sum_{j=v+1}^n \beta_{ij} x_i x_j}_{v \times o \text{ terms}} + \sum_{i=1}^n \gamma_i x_i + \delta$$

where (x_1, \dots, x_v) are the *vinegar* variables and (x_{v+1}, \dots, x_n) are the **oil** variables.

Multivariate quadratic public key cryptosystems (MPKC)

Signature: The UOV **trapdoor**, Kipnis, Patarin, and Goubin 1999

- Goal: $\mathcal{F}^{-1}(h) = (x_1, \dots, x_n)$
- Let $o, v \in \mathbb{N}$, define $n = o + v$ and $m = o$
- Write the quadratic polynomials as the following:

$$p(x_1, \dots, x_n) = \underbrace{\sum_{i=1}^v \sum_{j=i}^v \alpha_{ij} x_i x_j}_{v \times v \text{ terms}} + \underbrace{\sum_{i=1}^v \sum_{j=v+1}^n \beta_{ij} x_i x_j}_{v \times o \text{ terms}} + \sum_{i=1}^n \gamma_i x_i + \delta$$

where (x_1, \dots, x_v) are the *vinegar* variables and (x_{v+1}, \dots, x_n) are the **oil** variables.

- Notice *oil* variables are **not mixed** with themselves. // Easier to see using matrix notation.

Multivariate quadratic public key cryptosystems (MPKC)

How to invert the UOV trapdoor

- To invert guess at random the vinegars $(x_1, \dots, x_v) \in_R \mathbb{F}_q^v$

Multivariate quadratic public key cryptosystems (MPKC)

How to invert the UOV trapdoor

- To invert guess at random the vinegars $(x_1, \dots, x_v) \in_R \mathbb{F}_q^v$
- For $1 \leq k \leq o$

$$p_k(x_1, \dots, x_n) = \underbrace{\sum_{i=1}^v \sum_{j=i}^v \alpha_{ij}^{(k)} x_i x_j}_{v \times v \text{ terms}} + \underbrace{\sum_{i=1}^v \sum_{j=v+1}^n \beta_{ij}^{(k)} x_i x_j}_{v \times o \text{ terms}} + \sum_{i=1}^n \gamma_i x_i^{(k)} + \delta^{(k)}$$

which is a linear system of equations on the *oils*.

Multivariate quadratic public key cryptosystems (MPKC)

How to invert the UOV trapdoor

- To invert guess at random the vinegars $(x_1, \dots, x_v) \in_R \mathbb{F}_q^v$
- For $1 \leq k \leq o$

$$p_k(x_1, \dots, x_n) = \underbrace{\sum_{i=1}^v \sum_{j=i}^v \alpha_{ij}^{(k)} x_i x_j}_{v \times v \text{ terms}} + \underbrace{\sum_{i=1}^v \sum_{j=v+1}^n \beta_{ij}^{(k)} x_i x_j}_{v \times o \text{ terms}} + \sum_{i=1}^n \gamma_i x_i^{(k)} + \delta^{(k)}$$

which is a linear system of equations on the *oils*.

- Solve the system in at most $O(o^3)$ using Gaussian elimination to find (x_{v+1}, \dots, x_n) .

Multivariate quadratic public key cryptosystems (MPKC)

How to invert the UOV trapdoor

- To invert guess at random the vinegars $(x_1, \dots, x_v) \in_R \mathbb{F}_q^v$
- For $1 \leq k \leq o$

$$p_k(x_1, \dots, x_n) = \underbrace{\sum_{i=1}^v \sum_{j=i}^v \alpha_{ij}^{(k)} x_i x_j}_{v \times v \text{ terms}} + \underbrace{\sum_{i=1}^v \sum_{j=v+1}^n \beta_{ij}^{(k)} x_i x_j}_{v \times o \text{ terms}} + \sum_{i=1}^n \gamma_i x_i^{(k)} + \delta^{(k)}$$

which is a linear system of equations on the *oils*.

- Solve the system in at most $O(o^3)$ using Gaussian elimination to find (x_{v+1}, \dots, x_n) .
- If the system has no solution, try another guess for (x_1, \dots, x_v)

How to invert the UOV trapdoor

- This system $o \times o$ has a solution with very high probability

$$1 - \left(\prod_{i=0}^{n-1} (q^o - q^i) \right)^{-1}$$

How to invert the UOV trapdoor

- This system $o \times o$ has a solution with very high probability

$$1 - \left(\prod_{i=0}^{n-1} (q^o - q^i) \right)^{-1}$$

- Security note: in practice pick $\mathbf{v} \approx 2\mathbf{o}$.

How to invert the UOV trapdoor

- This system $o \times o$ has a solution with very high probability

$$1 - \left(\prod_{i=0}^{n-1} (q^o - q^i) \right)^{-1}$$

- Security note: in practice pick $\mathbf{v} \approx 2\mathbf{o}$.
 - ▶ The case where $o \leq v$ (balanced oil and vinegar) was broken by Kipnis and Shamir in 1998.

How to invert the UOV trapdoor

- This system $o \times o$ has a solution with very high probability

$$1 - \left(\prod_{i=0}^{n-1} (q^o - q^i) \right)^{-1}$$

- Security note: in practice pick $v \approx 2o$.
 - ▶ The case where $o \leq v$ (balanced oil and vinegar) was broken by Kipnis and Shamir in 1998.
 - ▶ Complexity of the attack for $v > o$ is $O(q^{v-o} \cdot o^4)$

UOV parameter sizes [from A. Petzoldt, 2017]

security level (bit)	scheme	public key size (kB)	private key size (kB)	hash size (bit)	signature (bit)
80	UOV(GF(16),40,80)	144.2	135.2	160	480
	UOV(GF(256),27,54)	89.8	86.2	216	648
100	UOV(GF(16),50,100)	280.2	260.1	200	600
	UOV(GF(256), 34,68)	177.8	168.3	272	816
128	UOV(GF(16),64,128)	585.1	538.1	256	768
	UOV(GF(256),45,90)	409.4	381.8	360	1,080
192	UOV(GF(16),96,192)	1,964.3	1,786.7	384	1,152
	UOV(GF(256),69,138)	1,464.6	1,344.0	552	1,656
256	UOV(GF(16),128,256)	4,644.1	4,200.3	512	1,536
	UOV(GF(256),93,186)	3,572.9	3,252.2	744	2,232

How to invert the UOV trapdoor

- UOV was proposed in 1999 and has not suffered major attacks.
- Faster than ECDSA to sign. $2 - 4\times$ faster to sign, $10 - 20\times$ faster for verifying.
- Signature sizes are less than 1KiB
- Public keys are large: tens or hundreds KiB

Multivariate quadratic public key cryptosystems (MPKC)

Rainbow signature

- Proposed by Ding and Schmidt 2005.
- It is a generalization of UOV.
- Idea: split private quadratic maps into layers.
 - ▶ Solve more but smaller systems of equation.
 - ▶ *Vinegars* for the next layer will be the the *vinegars* + *oils* from the previous one.

Multivariate quadratic public key cryptosystems (MPKC)

Rainbow signature

- Assume integer chain $0 < v_1 < \dots < v_u < v_{u+1} = n$

Multivariate quadratic public key cryptosystems (MPKC)

Rainbow signature

- Assume integer chain $0 < v_1 < \dots < v_u < v_{u+1} = n$
- Let $V_i = \{1, \dots, v_i\}$ and $O_i = \{v_i + 1, \dots, v_{i+1}\}$, $o_i = v_{i+1} - v_i$ be sets.

Multivariate quadratic public key cryptosystems (MPKC)

Rainbow signature

- Assume integer chain $0 < v_1 < \dots < v_u < v_{u+1} = n$
- Let $V_i = \{1, \dots, v_i\}$ and $O_i = \{v_i + 1, \dots, v_{i+1}\}$, $o_i = v_{i+1} - v_i$ be sets.
- The central map \mathcal{F} consists of $m = n - v_1$ polynomials $f^{v_1+1}, \dots, f^{(n)}$

$$f^{(k)} = \sum_{i,j \in V_\ell} \alpha_{ij}^{(k)} x_i x_j + \sum_{i \in V_\ell, j \in O_\ell} + \beta_{ij}^{(k)} x_i x_j + \sum_{i \in V_\ell \cup O_\ell} \gamma_i^{(k)} x_i + \delta^{(k)}$$

where ℓ is the only integer s.t. $k \in O_\ell$.

Multivariate quadratic public key cryptosystems (MPKC)

Rainbow signature

- Assume integer chain $0 < v_1 < \dots < v_u < v_{u+1} = n$
- Let $V_i = \{1, \dots, v_i\}$ and $O_i = \{v_i + 1, \dots, v_{i+1}\}$, $o_i = v_{i+1} - v_i$ be sets.
- The central map \mathcal{F} consists of $m = n - v_1$ polynomials $f^{v_1+1}, \dots, f^{(n)}$

$$f^{(k)} = \sum_{i,j \in V_\ell} \alpha_{ij}^{(k)} x_i x_j + \sum_{i \in V_\ell, j \in O_\ell} \beta_{ij}^{(k)} x_i x_j + \sum_{i \in V_\ell \cup O_\ell} \gamma_i^{(k)} x_i + \delta^{(k)}$$

where ℓ is the only integer s.t. $k \in O_\ell$.

- Choose invertible linear maps $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ and $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$

Multivariate quadratic public key cryptosystems (MPKC)

Rainbow signature

- Assume integer chain $0 < v_1 < \dots < v_u < v_{u+1} = n$
- Let $V_i = \{1, \dots, v_i\}$ and $O_i = \{v_i + 1, \dots, v_{i+1}\}$, $o_i = v_{i+1} - v_i$ be sets.
- The central map \mathcal{F} consists of $m = n - v_1$ polynomials $f^{v_1+1}, \dots, f^{(n)}$

$$f^{(k)} = \sum_{i,j \in V_\ell} \alpha_{ij}^{(k)} x_i x_j + \sum_{i \in V_\ell, j \in O_\ell} \beta_{ij}^{(k)} x_i x_j + \sum_{i \in V_\ell \cup O_\ell} \gamma_i^{(k)} x_i + \delta^{(k)}$$

where ℓ is the only integer s.t. $k \in O_\ell$.

- Choose invertible linear maps $\mathcal{T} : \mathbb{F}_q^m \rightarrow \mathbb{F}_q^m$ and $\mathcal{S} : \mathbb{F}_q^n \rightarrow \mathbb{F}_q^n$
- Public key is $\mathcal{P} = \mathcal{T} \circ \mathcal{F} \circ \mathcal{S}$.

Rainbow central map with 2 layers

$$F^{(k)} =$$

	v_1	v_2	n	
				$-v_1$
				$-v_2$
				$-n$

$v_1 + 1 \leq k \leq v_2$

$$F^{(k)} =$$

	v_1	v_2	n	
				$-v_1$
				$-v_2$
				$-n$

$v_2 + 1 \leq k \leq n$

- $x_1, \dots, x_{v_1}, x_{v_1+1}, \dots, x_{v_1+\alpha_1}$ will be the vinegars x_1, \dots, x_{v_2} for the second layer.

Rainbow (2 layers): Toy example [from A. Petzoldt, 2017]

- \mathbb{F}_7 , $(v_1, o_1, o_2) = (2, 2, 2)$, $m = n - v_1 = 4$
- Central map $\mathcal{F} = (f^{(3)}, f^{(4)}, f^{(5)}, f^{(6)})$ with

$$f^{(3)} = x_1^2 + 3x_1x_2 + 5x_1x_3 + 6x_1x_4 + 2x_2^2 + 6x_2x_3 + 4x_2x_4 + 2x_2 + 6x_3 + 2x_4 + 5$$

$$f^{(4)} = 2x_1^2 + x_1x_2 + x_1x_3 + 3x_1x_4 + 4x_1 + x_2^2 + x_2x_3 + 4x_2x_4 + 6x_2 + x_4$$

$$f^{(5)} = 2x_1^2 + 3x_1x_2 + 3x_1x_3 + 3x_1x_4 + x_1x_5 + 3x_1x_6 + 6x_1 + 4x_2^2 + x_2x_3 + 4x_2x_4 + x_2x_5 + 3x_2x_6 + 3x_2 + 3x_3x_4 + x_3x_5 + 2x_3x_6 + 2x_3 + 3x_4x_5 + x_5 + 6x_6$$

$$f^{(6)} = 2x_1^2 + 5x_1x_2 + x_1x_3 + 5x_1x_4 + 5x_1x_6 + 6x_1 + 5x_2^2 + 3x_2x_3 + 5x_2x_5 + 4x_2x_6 + x_2 + 3x_3^2 + 5x_3x_4 + 4x_3x_5 + 2x_3x_6 + 4x_3 + x_4^2 + 6x_4x_5 + 3x_4x_6 + 4x_4 + 4x_5 + x_6 + 2$$

- Goal: Compute the preimage $\mathbf{x} \in \mathbb{F}_7^6$ for $\mathbf{y} = (6, 2, 0, 5)$ under \mathcal{F} .

Rainbow: Toy example [from A. Petzoldt, 2017]

(cont. ...)

- Choose random values for the Vinegar variables x_1 and x_2 , e.g. $(x_1, x_2) = (0, 1)$ and substitute them into the polynomials $f^{(3)}, \dots, f^{(6)}$.

$$\tilde{f}^{(3)} = 5x_3 + 6x_4 + 2, \tilde{f}^{(4)} = x_3 + 5x_4,$$

$$\tilde{f}^{(5)} = 3x_3x_4 + x_3x_5 + 2x_3x_6 + 3x_3 + 3x_4x_5 + 4x_4 + 2x_5 + 2x_6,$$

$$\tilde{f}^{(6)} = 3x_3^2 + 5x_3x_4 + 4x_3x_5 + 2x_3x_6 + x_4^2 + 6x_4x_5 + 3x_4x_6 + 4x_4 + 2x_5 + 5x_6 + 1.$$

- Set $\tilde{f}^{(3)} = y_1 = 6$ and $\tilde{f}^{(4)} = y_2 = 2$ and solve for x_3, x_4
 $\Rightarrow (x_3, x_4) = (3, 4)$
- Substitute into $\tilde{f}^{(5)}$ and $\tilde{f}^{(6)}$
 $\Rightarrow \tilde{\tilde{f}}^{(5)} = 3x_5 + x_6 + 5, \tilde{\tilde{f}}^{(6)} = 3x_5 + 2x_6 + 1$
- Set $\tilde{\tilde{f}}^{(5)} = y_3 = 0$ and $\tilde{\tilde{f}}^{(6)} = y_4 = 5$, solve for x_5 and x_6
 $\Rightarrow (x_5, x_6) = (0, 2)$

A pre image of $\mathbf{y} = (6, 2, 0, 5)$ is given by $\mathbf{x} = (0, 1, 3, 4, 0, 2)$.

Rainbow parameter sizes [from A. Petzoldt, 2017]

(cont. ...)

security level (bit)	parameters $\mathbb{F}, v_1, o_1, o_2$	public key size (kB)	private key size (kB)	hash size (bit)	signature (bit)
80	GF(16),17,20,20	33.4	22.3	160	228
	GF(256),19,12,13	25.3	19.3	200	352
100	GF(16),22,25,25	65.9	43.2	200	288
	GF(256), 27,16,16	57.2	44.3	256	472
128	GF(16),28,32,32	136.6	87.6	256	368
	GF(256),36,21,22	136.0	102.5	344	632
192	GF(16),45,48,48	475.9	301.8	384	564
	GF(256),58,33,34	523.5	385.5	536	1,000
256	GF(16),66,64,64	1,194.4	763.9	512	776
	GF(256),86,45,46	1,415.7	1,046.3	728	1,416

References I



Patarin, Jacques and Louis Goubin (1997).
“Trapdoor one-way permutations and multivariate polynomials”.



Kipnis, Aviad, Jacques Patarin, and Louis Goubin (1999).
“Unbalanced oil and vinegar signature schemes”.



Ding, Jintai and Dieter Schmidt (2005).
“Rainbow, a new multivariable polynomial signature scheme”.