huff: A Python package for Market Area Analysis

Thomas Wieland
Freiburg, Germany
ORCID: 0000-0001-5168-9846
EMail: geowieland@googlemail.com

02 March 2026

Summary

Market area models, such as the *Huff model* and its extensions, are widely used to estimate regional market shares and customer flows of retail and service locations. Another, now very common, area of application is the analysis of catchment areas, supply structures and the accessibility of healthcare locations. The `huff` Python package provides a complete workflow for market area analysis, including data import, construction of origin-destination interaction matrices, basic model analysis, parameter estimation from empirical data, calculation of distance or travel time indicators, and map visualization. Additionally, the package provides several methods of spatial accessibility analysis. The package is modular and object-oriented. It is intended for researchers in economic geography, regional economics, spatial planning, marketing, geoinformation science, and health geography. The software is openly available via the Python Package Index (PyPI); its development and version history are managed in a public GitHub Repository and archived at Zenodo.

Statement of need

Market area models are used in economic geography, regional economics, spatial planning, geoinformation science, and marketing, enabling the analysis and forecasting of market areas and customer flows for retail and service locations. The classical and most popular approach is the *Huff model* (Huff 1962, 1963, 1964) and its numerous derivates and extensions, such as the *Multiplicative Competitive Interaction (MCI) Model* (Nakanishi and Cooper 1974, 1982; Cooper and Nakanishi 1983). See the "Mathematical appendix" section for the structure of the mentioned models. Typical research applications include examining the influence of store attributes and transport costs on consumer store choice, forecasting the revenue of new locations, or predicting the impact of new locations on existing ones (De Beule et al. 2014; Fittkau 2004; Li and Liu 2012; Mensing 2018; Oruc and Tihi 2012; Suárez-Vega et al. 2015; Wieland 2015, 2018a).

In health geography, such models are used to analyse catchment areas with respect to medical practices and hospitals (Bai et al. 2023; Fülop et al. 2011; Jia 2016; Latruwe et al. 2023; Rhein et al. 2025; Wieland 2018b), and they are also increasingly being linked to methods for analyzing the supply structure and accessibility of health locations (Liu et al. 2022; Rauch et al. 2023; Subal et al. 2021). Moreover, market area models are also applied to other location-related contexts such as airports or recreation facilities (Wang et al. 2022; Wang et al. 2026).

There are several major challenges in model-based market area analyses:

- The calibration of the Huff model based on observed data on consumer behavior and/or store sales is difficult because the model is nonlinear in its weighting parameters (Huff 2003; Wieland 2017). In this context, the MCI model (Nakanishi and Cooper 1974, 1982; Cooper and Nakanishi 1983) has been developed as an econometric estimation technique based on a linearization (*log-centering transformation*). As this approach requires empirical market shares for fitting, it is applied in cases where customer-store interaction data was obtained by surveys or secondary data (Baviera-Puig et al. 2016; Latruwe et al. 2023; Oruc and Tihi 2012; Suárez-Vega et al. 2015; Wieland 2015, 2018a). Several other researchers developed and used nonlinear iterative fitting approaches, especially when no empirical customer-store interactions are available, but only total sales of the locations investigated (De Beule et al. 2014; Güßefeldt 2002; Haines Jr et al. 1972; Li and Liu 2012; Liang et al. 2020; Mensing 2018; Orpana and Lampinen 2003; Wieland 2017). Due to the pronounced sensitivity of market area models to weighting schemes, the availability of multiple calibration approaches is essential in market area analysis.

- Researchers must choose and compare appropriate weighting functions, which may be chosen based on theoretical considerations and may result in substantially different results. Nowadays, for input variables such as travel time, several weighting functions (e.g., power, exponential, logistic) are used, and the model results are compared using goodness-to-fit metrics (Bai et al. 2023; Latruwe et al. 2023; Li and Liu 2012; Orpana and Lampinen 2003). It is, thus, necessary that, within the market area analysis workflow, several weighting functions are available, and that there are options to compare different model specifications based on fit metrics.

- Calculating travel times may be time consuming because these are based on graph theory network analysis and require real street networks (Huff and McCallum 2008). Therefore, market area analysis typically requires GIS (Geographic Information System) support and/or access to an API providing calculations based on input origins and destinations. It is extremely helpful for researchers if they can also complete this part of the market area analysis workflow within the analysis tool.

The huff package for Python v1.8.x essentially provides the following features:

- *Data management and preliminary analysis*: Users may load customer origins and supply locations from point shapefiles (or CSV, XLSX). Attributes of customer origins and supply locations (variables, weightings) may be set by the user. The next step is to create an *interaction matrix* with a built-in function, on the basis of which all implemented models can then be calculated. Within an interaction matrix, *transport costs* (distance or travel time between customer origins and supply locations) may be calculated with built-in methods.
- *Basic Huff model analysis*: Given an interaction matrix, users may calculate probabilities and expected customer flows with respect to customer origins, and total market areas of supply locations.
- *Parameter estimation based on empirical data*: Given empirical data on customer flows, regional market shares, or total sales, users may estimate weighting parameters of market area models. Model parametrization may be undergone using the econometric approach in the *MCI model* (if regional market shares are available) or by Maximum Likelihood optimization using regional market shares, customer flows, or total market areas.
- *Accessibility analysis*: The package includes methods of accessibility analysis, which may be combined with market area analysis (especially empirical estimation of weighting parameters), namely *Hansen accessibility* (Hansen 1959) and *Two-step floating catchment area analysis (2SFCA)* (Luo and Wang 2003).
- *GIS tools*: The library also includes auxiliary GIS functions for market area analysis (buffer, distance matrix, overlay statistics) and clients for OpenRouteService (Neis and Zipf 2008) and OpenStreetMap (Haklay 2008) for simple maps, with all of them being implemented in the market area analysis functions but are also able to be used stand-alone.

State of the field

To the best of our knowledge, no open-source Python package currently provides market area analysis and parameter estimation for the Huff or MCI model. No open-source software package currently exists that covers the entire workflow of market area analyses, as described in the "Statement of need" section. Some but not all of the functionalities mentioned are implemented in R packages: Both the `SpatialPosition` package (Giraud and Commenges 2025) and the `huff-tools` package (Pavlis et al. 2014) provide basic Huff Model analyses with two parameters, calculation of air distances, and map visualization. The R package `MCI` (Wieland 2017) focuses on model fitting based on empirical data, but does not provide processing of geospatial data and the calculation of distances or travel times. Accessibility analysis via two-step floating catchment area analysis is implemented in the R package `accessibility` (Pereira and Herszenhut 2024). The (almost) complete workflow for market area analyses using the Huff/MCI model is currently only implemented in proprietary GIS

software, namely the *ArcGIS Business Analyst* by *ESRI* (Esri 2025; Huff and McCallum 2008).

Software Architecture

The `huff` package is organized into a modular architecture that separates core modeling functionality from auxiliary helper modules. All model-related classes, methods and functions are implemented in the `models` module. Supporting functionalities are provided in separate modules, organized thematically. For example, the `ors` module provides an OpenRouteService client for retrieving travel time matrices and isochrones, which may be directly accessed from the `models` module. This design allows auxiliary functions to be used independently of the core models (stand-alone). In order to harmonize the data and outputs while processing, the `config` module includes configurations for all functions and definitions of default column names, suffixes and prefixes, and model terminology.

The `huff` library follows an object-oriented design. The class structure reflects the conceptual actors of a spatial market: Customer demand locations are represented by the `CustomerOrigins` class and supply locations by the `SupplyLocations` class. Their connection is established via an interaction matrix containing all possible origin-destination combinations and the corresponding data, such as travel times and location attributes. It is created from the location data using the built-in function `create_interaction_matrix()` from the `models` module, resulting in an instance of the `InteractionMatrix` class. All implemented model analyses may be calculated from an `InteractionMatrix` object, with the individual steps of the model calculations being methods of this class, e.g., `transport_costs()` for adding distances or travel times, `probabilities()`, `flows()`, and `marketareas()` for Huff model calculations, or `mci_fit()` for a MCI model analysis. These model analyses return objects of specific classes for each model, e.g., `HuffModel` and `MCIModel` for Huff and MCI models, respectively. All mentioned classes include `summary()`, `show_log()`, and, in relevant cases, `plot()` methods.

This structure was chosen to ensure a consistent workflow and a unified data structure, regardless of which model analysis is to be performed. The typical workflow for a basic Huff analysis (without empirical parameter estimation) consists of the following steps: (1) Load geospatial data of customer origins and supply locations, (2) Define their attributes and weightings, (3) Create an interaction matrix from origins and destinations, including the calculation of distances or travel time, (4) Calculate regional market shares, expected customer flows, and total market areas of all supply locations (This workflow is shown in the *Examples* section of the package README.MD). Advanced model analyses (e.g., including empirical calibration) require further steps (See the examples folder in the corresponding GitHub repository).

Research impact statement

The `huff` package is currently used in a health geography project at the Wuerzburg university hospital which deals with the catchment areas of pe-

diatric oncology care; a paper on this topic is currently in the review process. Given the rising number of scientific studies using market area models - particularly for non-retail purposes such as health geography - and the widespread use of Python as a programming language, it is to be expected that the `huff` library will see frequent adoption in related research projects.

Software development history statement

Due to data confidentiality requirements, the early development of the `huff` library took place in a private repository; the public repository was initialized more recently to provide open access for reproducibility and review. The `huff` Python package has been publicly developed and published via the [Python Package Index] (https://pypi.org/project/huff/) since April 2025. As of submission, it has undergone 44 releases, showing continuous improvement and feature additions. The library is actively used: since its first release (version 1.0.0) in April 2025, it has been downloaded approximately 23,700 times from the Python Package Index (source: pepy.tech, accessed March 02, 2026).

AI usage disclosure

No AI tools were used for software design, implementation, or decision-making. The Continue agent in Microsoft Visual Studio Code (with model GPT-5 mini) was used to generate initial docstrings, which were subsequently reviewed and adapted by the author. The manuscript text was written without the use of AI tools.

Mathematical appendix

In the basic Huff model, the utility of supply location j for the customers in customer origin i, U_{ij} is (Huff 1962):

$$U_{ij} = A_j^{\gamma} t_{ij}^{-\lambda}$$

where A_j is the attraction (size) of supply location j, t_{ij} is the travel time from i to j, and γ and λ are weighting parameters.

Given I customer origins ($i = 1, 2, ..., I$) and J supply locations ($j = 1, 2, ..., J$), the interaction probability (or market share) of origin i with respect to location j, equals:

$$p_{ij} = \frac{U_{ij}}{\sum_{j=1}^{J} U_{ij}}$$

The expected customer or expenditure flows from customer origin i to supply location j, E_{ij}, is:

$$E_{ij} = p_{ij} C_i$$

where C_i is the customer or expenditure potential in origin i.

The total market area of location j, T_j, equals (Huff 1964):

$$T_j = \sum_{i=1}^{I} E_{ij}$$

The Multiplicative Competitive Interaction Model is formalized as follows (Nakanishi and Cooper 1974):

$$p_{ij} = \frac{\prod_{h=1}^{H} A_{h_j}^{\gamma_h}}{\sum_{j=1}^{J} \prod_{h=1}^{H} A_{h_j}^{\gamma_h}}$$

where A_{h_j} is the h-th characteristic of supplier j, and γ_h is the corresponding weighting coefficient.

The log-centering transformation of the MCI model equals (Nakanishi and Cooper 1974):

$$\log\left(\frac{p_{ij}}{\widetilde{p}_i}\right) = \sum_{h=1}^{H} \hat{\gamma}_h \log \frac{A_{h_j}}{\widetilde{A}_{h_j}} + \log\left(\frac{\epsilon_{ij}}{\widetilde{\epsilon}_i}\right)$$

where $\widetilde{p}_i$, $\widetilde{A}_{h_j}$, and $\widetilde{\epsilon}_i$ are the geometric means of p_{ij}, A_{h_j}, and ϵ_{ij}, with ϵ_{ij} being the stochastic error term.

The inverse log-centering transformation is (Nakanishi and Cooper 1982):

$$\hat{p}_{ij} = \frac{\exp \sum_{h=1}^{H} \hat{\gamma}_h \log \frac{A_{h_j}}{\widetilde{A}_{h_j}}}{\sum_{j=1}^{J} \exp \sum_{h=1}^{H} \hat{\gamma}_h \log \frac{A_{h_j}}{\widetilde{A}_{h_j}}}$$

where $\hat{p}_{ij}$ is the estimated interaction probability (or market share) of origin i with respect to location j.

References

Bai, Lingyao, Zhuolin Tao, Yang Cheng, Ling Feng, and Shaoshuai Wang. 2023. "Delineating hierarchical obstetric hospital service areas using the Huff model based on medical records." *Applied Geography* 153: 102903. https://doi.org/10.1016/j.apgeog.2023.102903.

Baviera-Puig, Amparo, Juan Buitrago-Vera, and Carmen Escriba-Perez. 2016. "Geomarketing models in supermarket location strategies." *Journal of Business Economics and Management* 17 (6): 1205–21. https://doi.org/10.3846/16111699.2015.1113198.

Cooper, Lee G., and Masao Nakanishi. 1983. "Standardizing Variables in Multiplicative Choice Models." *Journal of Consumer Research* 10 (1): 96–108. https://doi.org/10.1086/208948.

De Beule, Matthias, Dirk Van den Poel, and Nico Van de Weghe. 2014. "An Extended Huff-Model for Robustly Benchmarking and Predicting Retail Network Performance." *Applied Geography* 46: 80–89. https://doi.org/10.1016/j.apgeog.2013.09.026.

Esri. 2025. *ArcGIS Business Analyst*. Released. https://www.esri.com/en-us/arcgis/products/arcgis-business-analyst/overview.

Fittkau, Dirk. 2004. "Beeinflussung regionaler Kaufkraftströme durch den Autobahnlückenschluß der A 49 Kassel-Gießen - Zur empirischen Relevanz der New Economic Geography in wirtschaftsgeographischen Fragestellungen." Dissertation, Georg-August-Universität Göttingen. https://doi.org/10.53846/goediss-3024.

Fülop, Gerhard, Pascal Kopetsch, and Christian Schöpe. 2011. "Catchment areas of medical practices and the role played by geographical distance in the patient's choice of doctor." *The Annals of Regional Science* 46 (3): 691–706. https://doi.org/10.1007/s00168-009-0347-y.

Giraud, Timothée, and Hadrien Commenges. 2025. *SpatialPosition: Spatial Position Models*. Released. https://doi.org/10.32614/CRAN.package.SpatialPosition.

Güßefeldt, Jörg. 2002. "Zur Modellierung von räumlichen Kaufkraftströmen in unvollkommenen Märkten." *ERDKUNDE* 56 (4): 351–70. https://doi.org/10.3112/erdkunde.2002.04.02.

Haines Jr, George H., Leonard S. Simon, and Marcus Alexis. 1972. "Maximum Likelihood Estimation of Central-City Food Trading Areas." *Journal of Marketing Research* 9: 154–59. https://doi.org/10.2307/3149948.

Haklay, Mordechai. 2008. "OpenStreetMap: User-Generated Street Maps." *IEEE Pervasive Computing* 7 (4): 12–18. https://doi.org/10.1109/MPRV.2008.80.

Hansen, Walter G. 1959. "How Accessibility Shapes Land Use." *Journal of the American Institute of Planners* 25 (2): 73–76. https://doi.org/10.1080/01944365908978307.

Huff, David L. 1962. *Determination of Intra-Urban Retail Trade Areas*. Real Estate Research Program, Graduate Schools of Business Administration, University of California.

Huff, David L. 1963. "A Probabilistic Analysis of Shopping Center Trade Areas." *Land Economics* 39 (1): 81–90. https://doi.org/10.2307/3144521.

Huff, David L. 1964. "Defining and estimating a trading area." *Land Economics* 28 (4): 34–38. https://doi.org/10.2307/1249154.

Huff, David L. 2003. "Parameter Estimation in the Huff Model." *ArcUser* 6: 34–36.

Huff, David L., and Bradley McCallum. 2008. *Calibrating the Huff Model Using ArcGIS Business Analyst*. ESRI White Paper, September 2008. ESRI.

Jia, Peng. 2016. "Developing a Flow-Based Spatial Algorithm to Delineate Hospital Service Areas." *Applied Geography* 75: 137–43. https://doi.org/10.1016/j.apgeog.2016.08.008.

Latruwe, T, M Van der Wee, P Vanleenhove, K Michielsen, S Verbrugge, and D Colle. 2023. "Improving inpatient and daycare admission estimates with gravity models." *Health Services and Outcomes Research Methodology* 23 (4): 452–67. https://doi.org/10.1007/s10742-022-00298-4.

Li, Yingru, and Lin Liu. 2012. "Assessing the Impact of Retail Location on Store Performance: A Comparison of Wal-Mart and Kmart Stores in Cincinnati." *Applied Geography* 32 (2): 591–600. https://doi.org/10.1016/j.apgeog.2011.07.006.

Liang, Yunlei, Song Gao, Yuxin Cai, Natasha Zhang Foutz, and Lei Wu. 2020. "Calibrating the dynamic Huff model for business analysis using location big data." *Transactions in GIS* 24 (3): 681–703. https://doi.org/10.1111/tgis.12624.

Liu, Linggui, Han Lyu, Yi Zhao, and Dian Zhou. 2022. "An Improved Two-Step Floating Catchment Area (2SFCA) Method for Measuring Spatial Accessibility to Elderly Care Facilities in Xi'an, China." *International Journal of Environmental Research and Public Health* 19: 11465. https://doi.org/10.3390/ijerph191811465.

Luo, Wei, and Fahui Wang. 2003. "Measures of Spatial Accessibility to Health Care in a GIS Environment: Synthesis and a Case Study in the Chicago Region." *Environment and Planning B: Planning and Design* 30 (6): 865–84. https://doi.org/10.1068/b29120.

Mensing, Matthias. 2018. "Lebensmittel-Onlinehandel - Alternative Zur Zukünftigen Versorgung Der Bevölkerung Ländlicher Räume?" Dissertation, Rheinisch-Westfälische Technische Hochschule Aachen. https://doi.org/10.18154/RWTH-2019-02683.

Nakanishi, Masao, and Lee G. Cooper. 1974. "Parameter estimation for a Multiplicative Competitive Interaction Model: Least squares approach." *Journal of Marketing Research* 11 (3): 303–11. https://doi.org/10.2307/3151146.

Nakanishi, Masao, and Lee G. Cooper. 1982. "Technical Note — Simplified Estimation Procedures for MCI Models." *Marketing Science* 1 (3): 314–22. https://doi.org/10.1287/mksc.1.3.314.

Neis, Pascal, and Alexander Zipf. 2008. "OpenRouteService.org Is Three Times "Open": Combining OpenSource, OpenLS and OpenStreetMap." *GIS Research UK Conference (GISRUK 2008).*

Orpana, Tommi, and Jouko Lampinen. 2003. "Building Spatial Choice Models from Aggregate Data." *Journal of Regional Science* 43 (2): 319–48. https://doi.org/10.1111/1467-9787.00301.

Oruc, Nermin, and Boris Tihi. 2012. "Competitive Location Assessment – the MCI Approach." *South East European Journal of Economics and Business* 7 (2): 35–49. https://doi.org/10.2478/v10033-012-0013-7.

Pavlis, Michail, Les Dolega, and Alex Singleton. 2014. *Huff-Tools.* Released. https://github.com/alexsingleton/Huff-Tools/.

Pereira, Rafael H. M., and Daniel Herszenhut. 2024. *Accessibility: Transport Accessibility Measures.* Released. https://doi.org/10.32614/CRAN.package.accessibility.

Rauch, Sebastian, Stephane Stangl, Tobias Haas, Jürgen Rauh, and Peter Ulrich Heuschmann. 2023. "Spatial Inequalities in Preventive Breast Cancer Care: A Comparison of Different Accessibility Approaches for Prevention Facilities in Bavaria, Germany." *Journal of Transport & Health* 29: 101567. https://doi.org/10.1016/j.jth.2023.101567.

Rhein, Michael von, Joel Hauser, Lucas Haldimann, Reto Jörg, and Oliver Gruebner. 2025. "Imbalanced access to pediatric primary care in Switzerland: geographic differences and modeled future challenges." *European Journal of Pediatrics* 184: 648. https://doi.org/10.1007/s00431-025-06441-w.

Suárez-Vega, Rafael, José Luis Gutiérrez-Acuña, and Manuel Rodríguez-Díaz. 2015. "Locating a supermarket using a locally calibrated Huff model." *International Journal of Geographical Information Science* 29 (2): 217–33. https://doi.org/10.1080/13658816.2014.958154.

Subal, Julia, Piret Paal, and Jukka M. Krisp. 2021. "Quantifying spatial accessibility of general practitioners by applying a modified huff three-step floating catchment area (MH3SFCA) method." *International Journal of*

Health Geographics 20: 9. https://doi.org/10.1186/s12942-021-00263-3.

Wang, Huimin, Xiaojian Wei, and Weixuan Ao. 2022. "Assessing Park Accessibility Based on a Dynamic Huff Two-Step Floating Catchment Area Method and Map Service API." *ISPRS International Journal of Geo-Information* 11 (7). https://doi.org/10.3390/ijgi11070394.

Wang, Yao, Liushan Lin, Xiaodong Meng, Meilin Zhu, and Changcheng Kan. 2026. "Measuring airport catchment areas via the Huff gravity model calibrated with mobile location data—Evidence from the Yangtze River Delta region." *Journal of Transport Geography* 131: 104552. https://doi.org/10.1016/j.jtrangeo.2026.104552.

Wieland, Thomas. 2015. *Räumliches Einkaufsverhalten und Standortpolitik im Einzelhandel unter Berücksichtigung von Agglomerationseffekten - Theoretische Erklärungsansätze, modellanalytische Zugänge und eine empirisch-ökonometrische Marktgebietsanalyse anhand eines Fallbeispiels aus dem ländlichen Raum Ostwestfalens/Südniedersachsens.* MetaGIS.

Wieland, Thomas. 2017. "Market Area Analysis for Retail and Service Locations with MCI." *The R Journal* 9: 298–323. https://doi.org/10.32614/RJ-2017-020.

Wieland, Thomas. 2018a. "Competitive locations of grocery stores in the local supply context - The case of the urban district Freiburg-Haslach." *European Journal of Geography* 9 (3): 89–115. https://www.eurogeojournal.eu/index.php/egj/article/view/41.

Wieland, Thomas. 2018b. "Modellgestützte Verfahren und "big (spatial) data" in der regionalen Versorgungsforschung II: Räumliche Interaktionsmodelle." *Monitor Versorgungsforschung* 11 (3): 59–64. https://doi.org/10.24945/MVF.03.18.1866-0533.2083.