







Items	Descriptions
	31. Check the event details.  Note: Script behaviors that are not in the baseline are blocked by OBAD when it is set to Enforce mode. User login activities, application behaviors, and network access are only monitored. Even in “Enforce” mode, those controls only generate events and do not block. In Strict mode, the entire Process Tree must match the baseline.
Expected Results	StellarProtect blocked unapproved script behaviors and alerted on unapproved Network Access



Lab5: CPSDR-Cyber Physical System Detection and Response



Table 9 CPSDR-Cyber Physical System Detection and Response




Items	Descriptions
Lab Case	CPSDR-Cyber Physical System Detection and Response
Scope	StellarProtect Operations Behavior Anomaly Detection (OBAD) is the behavior detection module of StellarOne. In this lab we will evaluate the OBAD behavior detection for “User Login” and “Applications”; including “Gray Detections”. Lastly, we will evaluate the “Isolation mode”
Steps	Lab scenario: CPSDR Lab scenario 1 A Hacker compromises an endpoint in the OT Environment (e.g. the LabConsole vm) 2 The hacker remotely creates a schedule task to target endpoint (the Win7 vm) try to steal credential account information 3 The hacker remotely creates a schedule task to target endpoint (the Win7 vm) try to implanted the ransomware  4 The scheduled task launches and starts a PowerShell script try to listed the user accounts 5 The scheduled task launches and starts a batch file try to implanted a ransomware 1. Verify that the Operations Behavior Anomaly Detection is still in “Enforce” mode with “Strict” enabled. Operations Behavior Anomaly Detection ⓘ ☐ Learn: Establish the Baseline to enable behavioral analysis in Detect and Enforce modes. ☐ Detect: Log events when abnormal activities are detected. ☒ Enforce: Log events when abnormal activities are detected, and automatically block unexpected Script Behavior changes. To block activities against Application Behavior and Network Access, the agent's Suspicious Objects Blocklist and Network Access Blocklist must be created first. ☒ Strict mode: Less tolerance for deviation between running behaviors and the Baseline. This may generate more events.

Items	Descriptions
	2. Check the configuration from the Agent console.  3. Log in to the LabConsole vm. 4. Open a cmd with Administrator rights and run the following commands to create two scheduled tasks as the user "hacker."  5. CD \Users\txone\desktop\Training\Stellar 6. In the following commands, "XX:XX" represents the time that the scheduled task will launch. The time is in 24-hour format. For this lab, set it to 3-5 minutes later than the current time.


Items	Descriptions																				
7.	<code>net use \\192.168.23.24 12345678 /user:hacker</code>																				
8.	<code>at \\192.168.23.24 XX:XX cmd.exe /c</code> <code>"C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe -ep bypass</code> <code>C:\Users\txone\Desktop\Training\powershell\powershell\script\psscriptdemo-</code> <code>win7-v2.ps1"</code>																				
9.	<code>Copy ransomdemo.bat \\192.168.23.24\C\$</code>																				
10.	<code>at \\192.168.23.24 XX:XX + 5 cmd.exe /c "C:\ransomdemo.bat"</code>																				
11.	Check the result of your cmd . Two scheduled tasks should have been created on the Win7 vm.																				
																					
12.	Wait for the two scheduled tasks to trigger.																				
13.	Log on to the Win7 vm and launch the Task Scheduler. (type “sched” in the windows search box). You will see that two new scheduled tasks have been created.																				
	 <table><thead><tr><th>Name</th><th>Status</th><th>Triggers</th><th>Next Run Time</th><th>Last Run Time</th></tr></thead><tbody><tr><td>{B6F007F...</td><td>Ready</td><td>When the task is created or modified</td><td>3/7/2019 2:41:36</td><td></td></tr><tr><td>AT1</td><td>Ready</td><td>At 3:10 AM on 3/11/2026</td><td>3/11/2026 3:10:00</td><td></td></tr><tr><td>AT2</td><td>Ready</td><td>At 3:20 AM on 3/11/2026</td><td>3/11/2026 3:20:00</td><td></td></tr></tbody></table>	Name	Status	Triggers	Next Run Time	Last Run Time	{B6F007F...	Ready	When the task is created or modified	3/7/2019 2:41:36		AT1	Ready	At 3:10 AM on 3/11/2026	3/11/2026 3:10:00		AT2	Ready	At 3:20 AM on 3/11/2026	3/11/2026 3:20:00	
Name	Status	Triggers	Next Run Time	Last Run Time																	
{B6F007F...	Ready	When the task is created or modified	3/7/2019 2:41:36																		
AT1	Ready	At 3:10 AM on 3/11/2026	3/11/2026 3:10:00																		
AT2	Ready	At 3:20 AM on 3/11/2026	3/11/2026 3:20:00																		



Items	Descriptions
	14. After the scheduled task was supposed to be run, check the StellarProtect Agent Logs in StellarOne. There should be multiple events triggered. The first one is Event ID 4870: Abnormal User Logon Detected by OBAD. Click on the “Action” button to check the event details.  15. One of the events should be a “Abnormal User Login” event. This is because the user account “Hacker” is not in the “Approved Login Account” list for remote logon. The source IP is 192.168.23.196. 




Items	Descriptions
	16. After the abnormal user logon event. You will also see a "4877: Abnormal inbound network traffic detected by OBAD" event. This event indicates that OBAD has identified inbound SMB traffic that deviates from the baseline. The timestamp of this event matches the abnormal user login.  17. The first scheduled task created event "4872 Unrecognized Application Detected by OBAD". Click on the "Action" button to see the details.  18. There will also be an "Unrecognized application" event for the program c:\Windows\system32\taskeng.exe. This is the Windows system task scheduler service.



Items	Descriptions
	 19. Click on the action button of event “4866 Script Behavior Blocked by OBAD” to check the event details.  20. The PowerShell script that the hacker tried to run is not in the list of Approved Script Behaviors and got blocked as well.  21. For the second scheduled task. There are multiple “4871 Suspicious application behavior detected by OBAD” events. Click on the “Action” button to see the details of these events.

Items	Descriptions																																				
	22. The event log a ransomdemo.bat tried to execute a script using mshta. With mshta.exe HTML Applications (HTA files) can be executed. HTA files are similar to HTML files but are executed as scripts, which can include JavaScript, VBScript, and other scripting languages. Notice that the timestamp is the same as defined in the schedule task. Violated Policy Information Policy Name Policy ID Policy Description Violated Rules ID System binary proxy execution (mshta) TXPSIRT_ransom_proc_c09 - • proc_c09-1 Policy Name Policy ID Policy Description Violated Rules ID Hide file from file system TXPSIRT_ransom_proc_c29 - • proc_c119-003																																				
	23. mshta was also blocked by OBAD as shown in the following event: “4866 Script behavior blocked by Operations Behavior Anomaly Detection”. <table><tr><th>Time ↓</th><th>Level</th><th>Event Type</th><th>Function Type</th></tr><tr><td>2026-03-11T03:21:25Z</td><td>Warning</td><td>4872 Unrecognized application detected by Operations Behavior An...</td><td>SP</td></tr><tr><td>2026-03-11T03:21:25Z</td><td>Warning</td><td>4872 Unrecognized application detected by Operations Behavior An...</td><td>SP</td></tr><tr><td>2026-03-11T03:20:00Z</td><td>Warning</td><td>4871 Suspicious application behavior detected by Operations Beha...</td><td>SP</td></tr><tr><td>2026-03-11T03:20:00Z</td><td>Warning</td><td>4872 Unrecognized application detected by Operations Behavior An...</td><td>SP</td></tr><tr><td>2026-03-11T03:20:00Z</td><td>Warning</td><td>4871 Suspicious application behavior detected by Operations Beha...</td><td>SP</td></tr><tr><td>2026-03-11T03:19:59Z</td><td>Warning</td><td>4866 Script behavior blocked by Operations Behavior Anomaly Dete...</td><td>SP</td></tr><tr><td>2026-03-11T03:19:59Z</td><td>Warning</td><td>4872 Unrecognized application detected by Operations Behavior An...</td><td>SP</td></tr><tr><td>2026-03-11T03:15:39Z</td><td>Warning</td><td>4877 Abnormal inbound network traffic detected by Operations Beh...</td><td>SP</td></tr></table>	Time ↓	Level	Event Type	Function Type	2026-03-11T03:21:25Z	Warning	4872 Unrecognized application detected by Operations Behavior An...	SP	2026-03-11T03:21:25Z	Warning	4872 Unrecognized application detected by Operations Behavior An...	SP	2026-03-11T03:20:00Z	Warning	4871 Suspicious application behavior detected by Operations Beha...	SP	2026-03-11T03:20:00Z	Warning	4872 Unrecognized application detected by Operations Behavior An...	SP	2026-03-11T03:20:00Z	Warning	4871 Suspicious application behavior detected by Operations Beha...	SP	2026-03-11T03:19:59Z	Warning	4866 Script behavior blocked by Operations Behavior Anomaly Dete...	SP	2026-03-11T03:19:59Z	Warning	4872 Unrecognized application detected by Operations Behavior An...	SP	2026-03-11T03:15:39Z	Warning	4877 Abnormal inbound network traffic detected by Operations Beh...	SP
Time ↓	Level	Event Type	Function Type																																		
2026-03-11T03:21:25Z	Warning	4872 Unrecognized application detected by Operations Behavior An...	SP																																		
2026-03-11T03:21:25Z	Warning	4872 Unrecognized application detected by Operations Behavior An...	SP																																		
2026-03-11T03:20:00Z	Warning	4871 Suspicious application behavior detected by Operations Beha...	SP																																		
2026-03-11T03:20:00Z	Warning	4872 Unrecognized application detected by Operations Behavior An...	SP																																		
2026-03-11T03:20:00Z	Warning	4871 Suspicious application behavior detected by Operations Beha...	SP																																		
2026-03-11T03:19:59Z	Warning	4866 Script behavior blocked by Operations Behavior Anomaly Dete...	SP																																		
2026-03-11T03:19:59Z	Warning	4872 Unrecognized application detected by Operations Behavior An...	SP																																		
2026-03-11T03:15:39Z	Warning	4877 Abnormal inbound network traffic detected by Operations Beh...	SP																																		
	24. Click on the “Action” button to see the event details.																																				



Items	Descriptions
	 25. Those events describe an intrusion incident. A suspicious user “Hacker” tried to remotely launch an unauthorized PowerShell script and a mshta script via a scheduled task. Investigate what happened on the Win7 VM: 1. Open the cmd.exe with Administrator rights and run the following commands: 2. CD \Windows\System32\Tasks 3. Check the scheduled tasks directory: dir /a/od/tc Notice that two scheduled tasks have been created “At1.job” and “At2.job” They were both created at the time that the hacker user logged in.



Items	Descriptions
	 4. Run the command “type at1” to check the content of the first scheduled task. You can see that the scheduled task tries to execute a PowerShell with the same filename as from the logs.  5. Run the command “type at2” to check the content of the second scheduled task. You can see that the scheduled task tries to execute a batch file located in C:\.


Items	Descriptions
	 <pre> Administrator: Command Prompt C:\Windows\System32\Tasks>type at2 <?xml version="1.0" encoding="UTF-16"?> <Task version="1.0" xmlns="http://schemas.microsoft.com/windows/2004/02/mit/task"> <RegistrationInfo /> <Triggers> <TimeTrigger> <StartBoundary>2026-03-11T03:20:00</StartBoundary> </TimeTrigger> </Triggers> <Principals> <Principal id="Author"> <UserId>@atServiceAccount</UserId> <LogonType>InteractiveToken</LogonType> <RunLevel>HighestAvailable</RunLevel> </Principal> </Principals> <Actions Context="Author"> <Exec> <Command>cmd.exe</Command> <Arguments>/c C:\ransomdemo.bat</Arguments> </Exec> </Actions> </Task> C:\Windows\System32\Tasks> </pre> 6. Run the command “dir c:\ransomdemo.bat /a/tc” and verify the timestamp of the file. This is the time when the hacker transferred the ransomdemo.bat first, then created the 2nd scheduled task.  <pre> Administrator: Command Prompt C:\>dir c:\ransomdemo.bat /a/tc Volume in drive C has no label. Volume Serial Number is E48B-F7A9 Directory of c:\ 03/11/2026 03:14 AM 195 ransomdemo.bat 1 File(s) 195 bytes 0 Dir(s) 47,062,331,392 bytes free </pre> 7. Open the Windows Event Viewer utility (eventvwr.exe), select the Security logs and click on the “Filter Current Log...”. 

Items	Descriptions
	8. Enter 4624 to filter all of the successful login events.  You'll see a logon event with the user "hacker" at the logon time that is before than the creation time of schedule task. The source IP address is 192.168.23.196. Next to sending events to StellarOne, the Agent also writes the same events in the Windows Event system. 

Items	Descriptions
	9. Timeline of the attack. The Timeline analysis Isolate the victim for further investigation 1. Select the agent WIN7, click Protection. 2. Select “Configure Isolation Mode” option, then click on the Confirm button.


Items	Descriptions
	3. Select “Enable”, check the “I understand the potential impact....”, then click on the Confirm button.  4. An “Isolation Mode” icon will appear under “Protection”.  5. Also, on the Agent Console on the Win7 vm, the “Isolation Mode” icon will be displayed. All traffic on this endpoint will be blocked, except traffic between the StellarProtect agent and StellarOne.



Items	Descriptions
	 6. To verify this, open the browser and try to access the web server at 192.168.23.196. Access should be blocked.  7. Disable the isolation mode for Win7. 8. The “isolation mode” completely isolated the Win7 endpoint. However, there is also a more <i>fine-grained</i> way to restrict access to/from the victim. This can be done with the Network Access Restrictions rules in the policy. Here access-rules can be created based on IP address, Port and Direction.




Items	Descriptions
	
Expected Results	StellarProtect detects an unauthorized user logon and an unauthorized application. "Isolation mode" isolates the VM from the network.

Lab6: Application Lockdown with SPLM

Table 10 Application Lockdown with SPLM




Items	Descriptions
Lab Case	Application Lockdown with SPLM
Scope	StellarProtect (Legacy Mode) Both Agents, SP and SPLM, do support Application Lockdown. In this lab we will evaluate Application Lockdown and Maintenance Mode on SPLM. We will also manually update the “Approved List”.
Steps	- Log in to the WinXP vm Log in credentials: User: txone Password: 12345678 - Open the StellarProtect Legacy Mode agent console and verify that Application Lockdown is enabled according to the StellarOne policy.  The screenshot shows the TXOne StellarProtect (Legacy Mode) console interface. The title bar indicates it is logged in as Administrator. The main area displays a large green checkmark and the text 'Protection Enabled'. Below this, there are two sections: 'Real-Time Protection' and 'Application Lockdown (Enforce)'. The 'Application Lockdown (Enforce)' section is highlighted with a red box and shows a status of 'Since 3/11/2026 2:09:49 AM'. At the bottom, there is a table with two rows: 'StellarOne registration' with a green checkmark, and 'StellarOne group name' with the value 'HVAC'.



Items	Descriptions
	3. Select the "Approved List" and verify the Approved list has been created.  4. Open Internet Explorer and browse to http://192.168.23.196/Training/Stellar/. 5. Download "Applications.zip" and unzip the file to path "C:\Users\txone\Desktop\Training\". Note: The file is downloaded over HTTP. It may remain at 99% completion for a while before the download task is finished.  6. Execute the hfs.exe.




Items	Descriptions
	 7. The hfs.exe will be blocked by the Application Lockdown function of StellarProtect Legacy Mode because hfs.exe is not in the approved list.  8. Check the Application lockdown event log from the StellarOne web UI. Click on the “Action” button to check the event details. 



Items	Descriptions
	9. Execution of hfs.exe was blocked by StellarProtect (Legacy Mode) because the file is not in the Approved list. Click on the Action button to see the details. Event Details < 2026-03-11T06:31:45Z Action Print Ignore Delete Quarantine Add to Approved List Event Information Time 2026-03-11T06:31:45Z Level Warning Event ID 2509 Event Type File access blocked: C:\Documents and Settings\bone\Desktop\Training\Applications\hfs.exe Block Reason File not found in approved list Detail Access image path: C:\WINDOWS\explorer.exe Access user: WINXP\bone Mode: Locked Reason: Not in Approved List From StellarOne, add a new file to the Approved Applications list of an Agent. 1. Check the Application lockdown event log from the StellarOne web UI. 2. Click on the “Action” button of the hfs.exe block event. Event Type Function Type Endpoint Action 2509 File access blocked. File not found in Approved List SPLM WINXP 4872 Unrecognized application detected by Operations Be... SP WIN7 4872 Unrecognized application detected by Operations Be... SP WIN7 10497 Isolation Mode stopped SP WIN7 3. To add hfs.exe to the Approved List of applications, click the 'Add to Approved List' button. Before proceeding, it is essential to understand why this file was blocked. Hfs.exe may be a newly added file, or its hash may have changed due to an uncontrolled update. In such cases, whitelisting is generally acceptable. However, a change in the file's hash could also indicate that it has been compromised by malicious activity. If so,



Items	Descriptions								
	whitelisting the file would pose a significant security risk to your system. Event Details 2026-03-11T06:31:45Z Action Print Ignore Delete Quarantine Add to Approved List Event Information Time 2026-03-11T06:31:45Z Level Warning Event ID 2509 Event Type File access blocked: C:\Documents and Settings\txone\Desktop\Training\Applications\hfs.exe Block Reason File not found in approved list Detail Access image path: C:\WINDOWS\Explorer.exe Access user: WINXP\txone								
4.	Enable the “Apply the same action to other log-events from the same file” option then click on the “Confirm” button. Confirm Action Do you want to add the unknown file to the Approved List? ☒ Apply the same action to other event logs from the same file Confirm Cancel								
5.	StellarOne will deploy command to the WinXP VM. Command Deployment Date and Time 2026-03-11T06:41:08Z Event The EventAction was applied to the agent(s) All Status (1) ▾ <table><thead><tr><th>Endpoint ▾</th><th>IP Address</th><th>Group</th><th>Status</th></tr></thead><tbody><tr><td>WINXP</td><td>192.168.23.25</td><td>HVAC</td><td>Completed at 2026-03-11T06:41:17Z</td></tr></tbody></table>	Endpoint ▾	IP Address	Group	Status	WINXP	192.168.23.25	HVAC	Completed at 2026-03-11T06:41:17Z
Endpoint ▾	IP Address	Group	Status						
WINXP	192.168.23.25	HVAC	Completed at 2026-03-11T06:41:17Z						



Items	Descriptions
	6. Return to the agent console and search for the file hfs.exe in the Approved List.  7. Execute hfs.exe again from the WinXP vm. It should now start fine.  From the Agent Console, add an Application to the Approved List 1. Go to agent console and search the file putty.exe from the Approved list. It should not be there. 




Items	Descriptions
2.	Execute putty.exe under Application folder. In some of cases, it may take up to 1 minute before you get a response, but it should not be able to run. 
3.	Check the agent logs in the StellarOne web UI to verify that the file putty.exe was blocked by Application Lockdown.
4.	In the Agent Console on the windows VM, open the Approved List and click the "Add Item" button. 



Items	Descriptions
	5. Select “Manually browse and select files”.  6. Select “Specific applications”.  7. Browse to the file “Putty.exe” from the Application folder. 

Items	Descriptions
	8. Check the file “putty.exe” and click “OK”.  9. Click “Approve”, then click on “Close”. 


Items	Descriptions
	10. Run putty.exe again. Now it should run fine.  Use Maintenance Mode to update the approved list. Install the Notepad++ application 1. Search for Notepad++.exe in the Approved list from the Agent console. It should not be there. 

Items	Descriptions
	Enable Maintenance Mode - Log in to the StellarOne web UI. - Choose the Agent WinXP and click on the “Protection” button.  - Select the “Configure Maintenance Mode” and click on the “Confirm” button. 

Items	Descriptions
	5. Configure the maintenance Mode (Start Now for 1 hour).  6. Make sure the Agent “Command Deployment” Status has completed.  7. Check the Agent console. The yellow wrench badge should be added. 


Items	Descriptions
	Notepad++ installation 1. Log in to the WinXP vm. 2. With maintenance mode enabled, execute the file npp.7.8.8.Installer.exe from the Application Folder under the Training Folder on the Desktop.  3. Follow the installation instructions and accept the default settings. “Check” Run Notepad++ v7.8.8 after the installation has completed.  After the Notepad++ installation has completed 1. Disable the Maintenance Mode from StellarOne web UI (follow the same steps as when you enabled it).



Items	Descriptions										
	Configure Maintenance Mode (1) To allow all application/file updates during the specified period, enable Maintenance Mode settings. To reduce risk of infection, run applications from trusted sources. Notice that the malware scanning will be launched by default after the maintenance period. Enable Disable Confirm Cancel 2. Check the Agent Console and verify that the wrench mark has disappeared. TXOne StellarProtect (Legacy Mode) (Logged in as Administrator) stellarProtect txOne networks Overview Approved List Password Operations Settings About ✓ Protection Enabled Real-Time Protection Since 3/11/2026 7:03:30 AM Application Lockdown (Enforce) Since 3/11/2026 7:03:30 AM 3. Verify that Notepad++.exe has been added to the approved list in the agent. TXOne StellarProtect (Legacy Mode) Approved List notepad++.exe Add Item Delete Item Check Hash <table><tr><th></th><th>Application</th><th>Full Path</th><th>Date</th><th>Hash Ma</th></tr><tr><td>☒</td><td>notepad++.exe</td><td>C:\Program Files\Notepad++\not...</td><td>3/11/2026 7:17:...</td><td></td></tr></table>		Application	Full Path	Date	Hash Ma	☒	notepad++.exe	C:\Program Files\Notepad++\not...	3/11/2026 7:17:...	
	Application	Full Path	Date	Hash Ma							
☒	notepad++.exe	C:\Program Files\Notepad++\not...	3/11/2026 7:17:...								




Items	Descriptions
	4. Launch Notepad++ It should run fine.  The screenshot shows the TXOne StellarProtect (Legacy Mode) interface. At the top, there's a search bar containing 'notepad++.exe'. Below it are buttons for 'Add Item', 'Delete Item', and 'Check Hash'. A table lists the 'Approved List' with columns for Application, Full Path, Date, and Hash Match. The first entry is 'notepad++.exe' with the full path 'C:\Program Files\Notepad++\notepad++.exe' and a date of '3/11/2026 7:17:17'. Below the table, a Notepad++ window titled 'new 1 - Notepad++' is open, showing a blank document with a menu bar (File, Edit, Search, View, Encoding, Language, Settings, Tools, Macro, Run) and a toolbar. The status bar at the bottom of Notepad++ shows 'Ln : 1 Col : 1 Sel : 0 0' and 'Windows (CR LF) UTF-8'.
Expected Results	● StellarProtect (Legacy Mode) blocks the execution of applications that are not in the approved list. ● The Approved List can be manually updated either from StellarOne or from the Stellar Agent. It will be automatically updated when maintenance mode is used.


Lab7: Setup an exception path for Application Lockdown

Table 11 Setup an exception path for the Application Lockdown

Items	Descriptions
Lab Case	Setup an exception path for the Application Lockdown
Scope	StellarProtect (Legacy Mode) In this lab we will evaluate how to exclude specific files or entire directories can from Application Lockdown. This ensures that the excluded files can always run, or that all files within the excluded folders are always allowed to run.
Steps	Update an exception path for Application Lockdown 1. On the WinXP vm. 2. Open Internet Explorer and browse to http://192.168.23.196/Training/Stellar/. 3. If you skipped Lab 6, please download "Application.zip", unzip the files, and manually add hfs.exe to the Approved List. 4. Download "mgmt_tools.zip" and unzip the file to path "C:\Users\txone\Desktop\Training\". 5. Execute Anydesk_6.2.exe. It should not be able to run. Because we know that files in this folder regularly change, we will exclude the folder from Application Lockdown. This ensures that everything in this folder is always allowed to run. 


Items	Descriptions
	6. Go to the StellarOne web UI. Select the HVAC group and open the policy. 7. Select the Function type: “StellarProtect (Legacy Mode)” and add the following Exception Path for the application lockdown: “C:\Documents and Settings\txone\Desktop\Training\Mgmt_tools”  8. Click on the “+Add” button, select the “Folder” option and enter the exception path “C:\Documents and Settings\txone\Desktop\Training\Mgmt_tools”. 




Items	Descriptions
	9. Click "OK".  10. Return to the Agent list and sync the policy settings to the agents under the HVAC group.  11. Verify that the policies have been successfully applied to the WinXP agent. 



Items	Descriptions
	12. Return to the WinXP vm and execute the Anydesk_6.2.exe again. The AnyDesk utility should run OK. 
Expected Results	Application Lockdown allows exclusions for specific files or entire directories. This ensures that the excluded files can always run, or that all files within the excluded folders are always allowed to run.



Lab8: User-defined Suspicious Objects (UDSOs)



Table 12 User-defined Suspicious Objects (UDSOs)

Items	Descriptions						
Lab Case	Configure User-defined Suspicious Objects (UDSOs)						
Scope	StellarProtect (Legacy Mode) In this lab, we want to prevent the execution of a specific exe-file on any endpoint in the group; regardless of any setting in any other Stellar security control... To achieve this, we will create a User-defined Suspicious Object (UDSO) for the HVAC group. We will use the WinXP VM (with SPLM), but the behavior is the same with SP.						
Steps	Add a new UDSO for StellarProtect (Legacy Mode) 1. Log in to the WinXP vm. 2. Go to the folder C:\Users\txone\Desktop\Training\Mgmt_Tools. 3. Use the HashMyFiles_32.exe tool to calculate the SHA1 of the file hfs.exe. <table><thead><tr><th>Filename</th><th>SHA1</th><th>MD5</th></tr></thead><tbody><tr><td>hfs.exe</td><td>d0c4192b65e36553f6fd2b83f3123f6ae8380dac</td><td>9e8557e98ed1269372ff0ace91d6</td></tr></tbody></table>	Filename	SHA1	MD5	hfs.exe	d0c4192b65e36553f6fd2b83f3123f6ae8380dac	9e8557e98ed1269372ff0ace91d6
Filename	SHA1	MD5					
hfs.exe	d0c4192b65e36553f6fd2b83f3123f6ae8380dac	9e8557e98ed1269372ff0ace91d6					

Items	Descriptions
	4. Right-click on the hfs.exe file in the HashMyFiles utility and select the options “Copy SHA1”.  5. In the StellarOne web UI and add the hfs.exe SHA1 to UDSO list for the policy of the “HVAC” group. Then synchronize the StellarProtect (Legacy Mode) policies with the agents. 6. Click on the “Add” button.  7. Paste the file hfs.exe SHA1 value and click “OK”. 

Items	Descriptions
	8. Verify the SHA1 value has been added to the UDSO list. 
	9. Push the policies to the agents in the “HVAC” group. 
	10. After the policies have been applied to the WinXP agent, return to the WinXP vm and execute the hfs.exe utility. It should be blocked by StellarProtect (Legacy Mode), even though it was in the “Approved Applications” list.




Items	Descriptions
	 11. Open the Approved List in the Agent Console and search for hfs.exe. Hfs.exe remains in the Approved List but the UDSO (User-Defined Suspicious Object) has a higher priority than any other security control (like Application Lockdown).  12. In the StellarOne web UI, go to Logs > Agent Event > StellarProtect (Legacy Mode). 13. Check the log-events. There will be an event "8016 Suspicious program execution blocked". Click on the "Action" button to view the event details.



Items	Descriptions
	 14. The file hfs.exe was blocked because it is restricted by UDSO, even though it is still listed in the Approved List. 
Expected Results	StellarProtect (Legacy Mode) can use “User Defined Suspicious Objects Lists” to prevent files from being executed; regardless of any setting in any other Stellar security control.



Lab9: Updating virus patterns in air gapped networks

Table 13 Updating virus patterns in air gapped networks

Items	Descriptions
Lab Case	Updating virus patterns in air gapped networks
Scope	StellarOne In this lab we will evaluate how to update anti-virus patterns if StellarOne has no access to the TXOne active-update servers on the internet. Pattern files can be retrieved from an internal website or, in StellarOne version 3.2 or higher, they can be manually import as well.
Steps	In air gapped environments, virus patterns can be uploaded to your local StellarOne in 2 ways: 1. Using a local update source for StellarOne. This would be a local web server to where you manually copy the pattern files that you download from https://my.txone.com. 2. Manually uploading the downloaded pattern files directly to StellarOne. This requires StellarOne version 3.2 or higher. Updating the virus pattern via a local web server as the update source 1. Access the antivirus pattern file "TXOne_Anti-Virus_Pattern_for_Stellar_250617_1.zip" in the folder <code>\Desktop\Training\Stellar</code>. 2. Unzip the virus pattern zip file to <code>\Desktop\Training\Stellar</code>. 3. A directory named "Anti-Virus_Pattern_for_Stellar" should have been created under the <code>\Desktop\Training\Stellar</code> folder.

Items	Descriptions
	 4. Launch HFS web server management console.  5. Limit the HFS web server speed to 2000KB/s. It is important, otherwise the HFS web server may get overloaded.  6. With the Chrome browser, go to http://192.168.23.196 and navigate to the web folder /Training/Stellar/Anti-Virus_Pattern_for_Stellar.

Items	Descriptions
	 7. Copy the URL: http://192.168.23.196/Training/Stellar/Anti-Virus_Pattern_for_Stellar 8. In the StellarOne web UI, go to Administration > Download/Updates > StellarOne. 9. Click on the “Scan Component Update Source” button 10. Check the current version of virus patterns.  11. Click on “Scan Component Update Source” and at “Other update source, paste the URL of the web folder. 12. Click “Confirm”.

Items	Descriptions
	 13. Click the "Update Now" button.  14. You can check the HFS web server management UI, where a pattern download process will be displayed. 