

StellarOne

Administrator Guide

Version 5.0
Patch 2



TXOne Networks Incorporated reserves the right to make changes to this document and to the product described herein without notice. Before installing and using the product, review the readme files, release notes, and/or the latest version of the applicable documentation, which are available at:

<https://my.txone.com/>


TXOne Networks, StellarOne, and Stellar Agent are trademarks or registered trademarks of TXOne Networks Incorporated. All other product or company names may be trademarks or registered trademarks of their owners.

Copyright © 2026. TXOne Networks Incorporated. All rights reserved.

Document Part No.: APEMxxxxx/24xxxxAPEMxxxxx/24xxxx

Release Date: April 2026

Protected by U.S. Patent No.: Patents pending.




Privacy and Personal Data Collection Disclosure

Certain features available in TXOne Networks products collect and send feedback regarding product usage and detection information to TXOne Networks. Some of this data is considered personal in certain jurisdictions and under certain regulations. If you do not want TXOne Networks to collect personal data, you must ensure that you disable the related features.

Data collected by TXOne Networks is subject to the conditions stated in the TXOne Networks Global Privacy Notice:

<https://www.txone.com/privacy-policy/>




Contents

.....	viii
Preface.....	ix
About the Documentation.....	x
Audience.....	x
Document Conventions.....	x
Terminology.....	xi
Chapter 1. Introduction.....	15
About TXOne Stellar.....	16
Key Features and Benefits.....	17
Product Matrix.....	18
What's New.....	20
Chapter 2. Getting Started.....	23
About the Web Console.....	24
Comparison of License Formats.....	24
Opening StellarOne Management Console.....	25
Chapter 3. Dashboard.....	29
About the Dashboard Screen.....	30
Widget Manager.....	32
About the Widget.....	33
Security Monitoring.....	33
Widget for At-Risk Endpoints.....	33
Widget for CPSDR.....	34
Widgets for Monitoring Agents.....	36
Vulnerability.....	38
Asset Management.....	39
Widgets displaying managed asset status.....	39
Widgets displaying key features settings.....	42
StellarOne Status.....	44
Widgets for Monitoring Disk Usage.....	45
Widgets for Monitoring CPU & Memory Usage.....	46
Policy Controls.....	46
Chapter 4. Endpoint Management.....	49
About the Agents Screen.....	50
Agent Status Settings.....	54
Add Groups.....	59
Edit Description for Agents.....	60


Organize Agents/Groups.....	60
Transfer Agents to Another StellarOne.....	61
Assign Update Agents.....	63
Search for Agents/Groups.....	64
Upgrade from Discover Edition to Protect Edition.....	67
Protection.....	67
Configure Maintenance Mode.....	68
Enable Smart Trusted Program List.....	70
Update Approved List.....	71
Maintenance Mode/Approved List: Use Case.....	71
Scan Now.....	71
Configure Isolation Mode (Stellar Agent (Windows) Only).....	73
Configure Emergency Stop Mode.....	74
Update.....	75
Update Agent Components.....	75
Deploy Agent Patches.....	75
Check Connections.....	76
Apply Policies.....	77
Collect Event Logs.....	77
Agent Export/Import Settings.....	79
Import Agent Settings.....	80
Export Agent Settings.....	82
Export Selected Agents Info.....	82
Export all Agents Info.....	83
Chapter 5. Policy Configuration.....	85
Settings for the Agent/Group Policy Screen.....	86
Set Policy Refresh Interval.....	87
Set Agent User Interface Preferences.....	88
Export/Import Exclusions Settings.....	89
Agent View and Policy Settings.....	105
Go to the Agent View.....	105
Agent Policy Settings.....	108
Baseline.....	160
Situational Awareness.....	172
Vulnerabilities.....	174
Group Policy Settings.....	175
Go to the Group Policy Screen.....	176
Group Policy Settings.....	176

Global Policy Settings.....	178
Chapter 6. Logs.....	179
Agent Events.....	180
About Agent Events Screen.....	180
Agent Events Filtering.....	182
Agent Event Actions.....	182
Server Events.....	186
About Server Events Screen.....	187
Server Events Log Filtering	188
System Logs.....	189
About System Logs Screen.....	189
Audit Logs.....	190
About Audit Logs Screen.....	191
Audit Log Filtering	192
Chapter 7. Administration.....	193
Account.....	194
Account Management.....	194
Single Sign-On.....	202
Notification.....	206
SMTP Settings and Notification.....	207
Scheduled Report.....	208
Syslog Forwarding	209
Import CA Certificates via CLI	209
Update.....	210
Proxy Settings.....	210
Downloads/Updates.....	211
Importing Firmware.....	217
License.....	217
System.....	234
System Time.....	234
Log Purge.....	235
Importing SSL Certificate.....	236
OT Intelligent Trust.....	237
Service Integration.....	237
StellarOne Pool.....	238
Chapter 8. Getting Help and Troubleshooting.....	241
Troubleshooting Resources.....	242
Self-Diagnosis.....	242

Collect Debug Log.....	247
Using the Support Portal.....	247
Threat Encyclopedia.....	248
Contacting TXOne Networks.....	248
Speeding Up the Support Call.....	248
Other Resources.....	249
Download Center.....	249
Appendix A. Appendices.....	251
Log Descriptions.....	252
Log Descriptions for Stellar Agent (Windows).....	252
Log Descriptions for Stellar Agent (Windows-Legacy).....	282
Server Event Log Descriptions for StellarOne.....	343
Agent Event Log Descriptions for Stellar Agent - Protect Edition (Linux).....	346
Syslog Content - CEF.....	353
Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) Syslog Content - CEF.....	354
StellarOne Server Event Format (Console Log).....	369
StellarOne Syslog Content - CEF.....	370
Index.....	a



This documentation introduces the main features of the product and/or provides installation instructions for a production environment. Read through the documentation before installing or using the product.




Preface

This guide introduces TXOne StellarOne™ and covers all aspects of product management.

Topics in this chapter include:

- [About the Documentation \(on page x\)](#)
- [Audience \(on page x\)](#)
- [Document Conventions \(on page x\)](#)
- [Terminology \(on page xi\)](#)



About the Documentation

TXOne StellarOne™ documentation includes the following:

Documentation	Description
Readme file	Contains a list of known issues and basic installation steps. It may also contain late-breaking product information not found in the other documents.
Installation Guide	A PDF document that discusses requirements and procedures for installing StellarOne
Administrator Guide	A PDF document that discusses StellarOne agent installation, getting started information, and server and agent management
Online Help	HTML files that provide "how to's", usage advice, and field-specific information
Knowledge Base	An online database of problem-solving and troubleshooting information. It provides the latest information about known product issues. To access the Knowledge Base, go to the following websites: https://kb.txone.com/

Audience

TXOne StellarOne™ documentation is intended for administrators responsible for StellarOne management, including agent installation. These users are expected to have advanced networking and server management knowledge.

Document Conventions

The documentation uses the following conventions.

Table 1. Document Conventions

Convention	Description
UPPER CASE	Acronyms, abbreviations, and names of certain commands and keys on the keyboard
Bold	Menus and menu commands, command buttons, tabs, and options

Table 1. Document Conventions (continued)

Convention	Description
<i>Italics</i>	References to other documents
<code>Monospace</code>	Sample command lines, program code, web URLs, file names, and program output
Navigation > Path	The navigation path to reach a particular screen For example, File > Save means, click File and then click Save on the interface
 Note:	Configuration notes
 Tip:	Recommendations or suggestions
 Important:	Information regarding required or default configuration settings and product limitations
 Warning:	Critical actions and configuration options

Terminology

The following table provides the official terminology used throughout the TXOne StellarOne™ documentation:

Terminology	Description
server	The StellarOne console server program
server endpoint	The host where the StellarOne server is installed

Terminology	Description
agents	The host running the Stellar Agent program
managed agents managed endpoints	The hosts running the Stellar Agent program that are known to the StellarOne server program
target endpoints	The hosts where the StellarOne managed agents will be installed
Administrator (or StellarOne administrator)	The person managing the StellarOne server
StellarOne (management) console	The user interface for configuring and managing StellarOne settings and the agents managed by StellarOne
CLI	Command Line Interface
license activation	Includes the type of StellarOne server installation and the allowed period of usage that you can use the application
primary license	The license that determines the StellarOne server edition. When a Discover add-on license is in use, the primary license is always a StellarICS license.
add-on license	An additional license entitlement applied alongside the primary license. An add-on license provides a separate seat pool but does not change the server edition.
Discover agent	A managed agent running Discover Edition. Discover agents provide visibility only and do not perform real-time protection.
protection agent	A managed agent that is not running Discover Edition, such as an agent running Protect Edition.
hard expiration date	The expiration date of a license plus its grace period. A license or add-on license remains effective until its hard expiration date is reached.

Terminology	Description
agent installation folder	The folder on the host that contains the Stellar Agent agent files. If you accept the default settings during installation, you will find the installation folder at one of the following locations: C:\Program Files\TX0ne\StellarProtect C:\Program Files\TX0ne\StellarProtect (Legacy Mode)

Chapter 1. Introduction

This chapter introduces TXOne StellarOne™ and how it manages the agents providing Cyber-Physical System Detection and Response (CPSDR), multi-method threat prevention, operations lockdown, and trusted peripheral control protection to your assets.

An overview of management functions is provided. This manual will focus on its use for Stellar Agent™: an OT-compatible, high performance and zero touch endpoint protection solution, and Stellar Agent (Windows-Legacy)™: a simple, no-maintenance solution to lock down and protect fixed-function computers, helping protect businesses against security threats and increase productivity.

Topics in this chapter include:

- [About TXOne Stellar \(on page 16\)](#)
- [Key Features and Benefits \(on page 17\)](#)
- [What's New \(on page 20\)](#)

About TXOne Stellar

TXOne Stellar provides a context-focused security solution for OT endpoints and cyber-physical systems (CPS), aiming to defend operation stability with continuous detection and response aligned to the specific requirements of the OT domain.

TXOne Stellar platform is composed of the centralized management console server and unified agents apt for legacy OT devices and modern cyber-physical systems.

- StellarOne™, designed to streamline administration of the agents installed on modernized systems and legacy systems, along with its intuitive centralized management, consistent policy enforcement, and action-oriented alerts that empower security teams of all sizes and skill levels to successfully mature their organization's security posture.
- Stellar Agent™ / Stellar Agent (Windows-Legacy) / Stellar Agent (Linux), using a single-agent design that delivers seamless asset-centric protection and ensures coverage for modern CPS and legacy OT devices throughout their entire asset lifecycle. The lightweight unified agent simplifies security by combining CPS Detection and Response (CPSDR), threat prevention, operations lockdown, device control.
 - CPSDR: Embodied within the advanced Operations Behavior Anomaly Detection feature, which establishes a unique baseline of each agent-device during practicable operating states and performs deviation analysis by means of an expansive industrial application repository and ransomware detection engine to defend against unexpected changes that may impact stability.

Moreover, TXOne Stellar brings the contextualization of security into an operation-led view to allow both the operation and security teams to achieve their goals without needing to compromise. To illustrate, if a device suddenly tried to start launching different applications, it would be blocked from doing so.

From the operation view, this may be an unplanned auto-update that, if run, would take the device offline to reboot. From a security view, this could be an attempt to access an encryption library that is about to be used to execute ransomware. By applying the operation context, both security and operation-initiated changes can be detected, and appropriate responses are taken.

In both cases, CPSDR stopped the incident before it could occur. The security team followed up and resolved the ransomware infection in a different part of the environment. The operation team could schedule the required update to run during planned maintenance period.

- Multi-Method Threat Prevention: Provides advanced threat scan on the basis of ICS root of trust and operations-focused machine learning to secure the agent-devices against known and unknown malware threats without compromising operational availability.
- Operations Lockdown: For fixed-function and devices with limited patching availability, operations lockdown enforcement prohibits unauthorized changes, including alterations to registry and function parameters.
- Trusted Peripheral Control: Unauthorized access from external sources, such as USB devices, is configurable and controlled to reduce physical access threats.

Leveraging an expansive OT application and certificate library and exclusive ransomware detection engine, TXOne Stellar maintains CPS operational integrity through behavioral anomaly detection and eliminates configuration drift for legacy and fixed-use assets with device lockdown. Security teams can confidently deliver detection and response outcomes across the OT terrain, with TXOne Stellar effectively strengthen organization's security posture while maintaining its business operations stability.

Key Features and Benefits

The TXOne StellarOne™ management console provides following features and benefits.

Table 2. Features and Benefits

Feature	Benefit
VDS (Vulnerability Detection Service)	VDS (Vulnerability Detection Service) is a security visibility feature that enables Stellar agents, including the Discover Edition, to automatically collect endpoint and asset information and report it to the StellarOne console. The console then cross-references this data against a regularly updated vulnerability pattern database to identify known vulnerabilities (CVEs) affecting those endpoints. Each detected vulnerability is also assigned a severity level so that administrators can quickly identify high-risk assets and prioritize remediation efforts. Vulnerability data is surfaced through the StellarOne console and dashboard, providing centralized visibility into the organization's security posture — whether used alongside full protection agents or as a standalone assessment tool.
Cyber-Physical System Detection and Response (CPSDR)	The CPSDR requires a deep understanding of what the expected behaviors for each device are. Embodied within the advanced Operations Behavior Anomaly Detection feature, which primarily defends against unexpected changes that may impact operational stability by comparing daily operation processes and behaviors with a unique baseline of each agent-device and performing comprehensive behavioral analysis not only via identifying baseline deviation but also using TXOne Networks' exclusive industrial application repository and ransomware detection engine.
Dashboard	The Dashboard provides an overview of the CPS situational awareness and agent deployment status at the centralized control level, along with the monitored asset status and StellarOne console's system status. Administrators can check deployed agent status easily, have quick access to the detected events for further investigation or actions if needed, and generate security reports related to specific agent activity for specified periods.
Centralized Agent Management	StellarOne allows administrators to perform the following tasks:

Table 2. Features and Benefits (continued)

Feature	Benefit
	• Monitor Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) agent status • Examine connection status • View configurations • Collect agent logs on-demand • Turn agent Application Lockdown on or off • Enable or disable agent Device Control • Configure agent Maintenance Mode settings • Update agent components • Initialize the Approved List • Deploy agent patches • Add trusted files and USB devices • Export agents information • Import/Export agents configuration settings and import agent Approved list • Export agents Approved List
Centralized Event Management	On endpoints protected by Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) agents, administrators can monitor status and events, as well as respond when files are blocked from running. StellarOne provides event management features that let administrators quickly know about and take action on the blocked-file events.
Server Event Auditing	Operations performed by StellarOne web console accounts are logged. StellarOne records an operating log for each account, tracking who logs on, who deletes event logs, and more.

Product Matrix

The StellarOne management console works with a variety of different Stellar Agent Editions and license types. As this Administrator Guide includes information on available features across all Agent Editions and license types, it is important that users read the below product matrix carefully to understand which features will be available based on the edition and license used.

Table 3. Product Matrix for Protect Edition

Agent Type	Windows	Windows-Legacy	Linux
Required License	ICS, Kiosk, or OEM	ICS, Kiosk, or OEM	ICS
Real-time Scan	Yes (Except for OEM License)	Yes (Except for OEM License)	Yes
Scheduled Scan	Yes (Except for OEM License)	Yes (Except for OEM License)	Yes
On-demand Scan	Yes (Except for OEM License)	Yes (Except for OEM License)	Yes
Application Lockdown	Yes (Except for Kiosk License)	Yes	No
USB Device Management	Yes	Yes	No
OT Application Safeguard	Yes	No	No
Operations Behavior Anomaly Detection	Yes	Yes (Except for Kiosk/OEM License)	No
Trusted Certificate	Yes	Yes	No
Installed Application Record	Yes	Yes (Except for Kiosk/OEM Licenses)	No
Vulnerability Detection	Yes (Except for Kiosk/OEM Licenses)	Yes (Except for Kiosk/OEM Licenses)	Yes
USB Device Access Detection	Yes	Yes	No
Login Activity Record	Yes (Except for Kiosk/OEM Licenses)	Yes (Except for Kiosk/OEM Licenses)	No
Network Flow Record	Yes (Except for Kiosk/OEM Licenses)	No	No
Network Access Restrictions	Yes (Except for Kiosk/OEM Licenses)	No	No

Table 4. Product Matrix for Discover Edition

Agent Type	Windows	Windows-Legacy
Required License	ICS or Discover	ICS or Discover
Real-time Scan	No	No
Scheduled Scan	Log Only	Log Only
On-demand Scan	Log Only	Log Only
Application Lockdown	No	No
USB Device Management	Log Only	Log Only
OT Application Safeguard	No	No

Table 4. Product Matrix for Discover Edition (continued)

Agent Type	Windows	Windows-Legacy
Operations Behavior Anomaly Detection	No	No
Trusted Certificate	No	No
Installed Application Record	Yes	Yes
Vulnerability Detection	Yes	Yes
USB Device Access Detection	Yes	Yes
Login Activity Record	Yes	Yes
Network Flow Record	Yes	No
Network Access Restrictions	No	No

**Note:**

Discover Edition agents can also operate under a StellarICS license with a StellarDiscover add-on license applied. In that configuration, Discover Edition agents draw from a dedicated Discover add-on seat pool instead of consuming StellarICS seats. See [About the Discover Add-on License \(on page 224\)](#) for more details.

What's New

TXOne StellarOne™ 5.0 provides following new features and enhancements.

Table 5. What's New in TXOne StellarOne™ 5.0

Feature	Description
Discover add-on license	A StellarDiscover license can be applied as an add-on to an existing StellarICS primary license, giving Discover agents a dedicated seat pool so they do not consume StellarICS seats.
Discover Edition	Support for the new visibility-focused Discover Edition of Stellar Agent
VDS integration visibility	New security monitoring widgets leveraging VDS (vulnerability/detection source)
New dashboard widgets for asset management	Additional widgets on the StellarOne dashboard focused on asset-centric views
New widget: Threat type count per agent	Dashboard widget that aggregates threat detections by type per agent

Table 5. What's New in TXOne StellarOne™ 5.0 (continued)

Feature	Description
New remote emergency stop feature	Ability to remotely emergency stop protection from StellarOne
Random distribution of Agent Scan Component Update Schedule	Randomly distribute agent component update schedule across an hour. This reduces server load, allowing more agents to update.

Chapter 2. Getting Started

This chapter introduces how to access and configure the StellarOne web-based management console.

Topics in this chapter include:

- [About the Web Console \(on page 24\)](#)
- [Opening StellarOne Management Console \(on page 25\)](#)

About the Web Console

TXOne StellarOne is a management console with web GUI for users to access via web browsers. StellarOne is packaged in an Open Virtual Appliance (OVA) or Virtual Hard Disk v2 (VHDX) format and supports 4 types of platforms: VMware ESXi, VMware Workstation, Windows Hyper-V systems, and AWS EC2.



Note:

Supported browsers:

- Google Chrome 87 or later versions
- Microsoft Edge 79 or later versions
- Mozilla Firefox 78 or later versions

For users who log on StellarOne for the first time, please refer to [Opening StellarOne Management Console \(on page 25\)](#).

For more details about the installation for StellarOne, please refer to the *StellarOne Installation Guide*.

Comparison of License Formats

StellarOne recognizes two formats of product license purchased from TXOne Networks or from a TXOne Networks authorized reseller.

Table 6. Comparison of Two Different License Formats

		License Key	Activation Code
Length		19 characters	37 characters
Example		FIJN-HPYB-XXXX-XXXX	TE-24RF-Q9UN9-S9QQN-XXX XX-XXXXXX-XXXXXX
New license	Online	√	√
	Offline	License File	√
License renewal	Online	√	√
	Offline	License File	N/A

**Note:**

A License Key is required for downloading a License File.

Opening StellarOne Management Console

1. For VMware or Hyper-V system, launch the StellarOne instance and then run the OOBЕ process in the setup CLI.
 - a. Use the default credentials when logging on for the first time:

- Username: txuser
- Password: txone

- b. Change the default credentials to your desired username and password.

**Important:**

To enhance security, it is recommended to create a safe username and strong password.

**Note:**

For StellarOne instance deployed from AMI on AWS EC2 platform, or on the Microsoft Azure platform, the OOBЕ process is not required.

2. Open a web browser and enter the StellarOne address in the following format: `https://<targetserver IP address>`. The logon screen appears.
3. Enter your credentials (user ID and password).

Use the default credentials of administrator when logging on for the first time:

- User ID: admin
- Password: txone

4. Click **Log On**.
5. If this is the first time the StellarOne instance being logged on, follow procedures below to complete the initial settings.
 - a. The **Login Information Setup** window appears and prompts you to change password. Confirm your password settings by:
 - specifying your new password in the **New Password** text field.
 - specifying the password again in the **Confirm Password** text field.

**Note:**



- For StellarOne 1.2 or above, the default login name is always `admin` and can not be changed by the user.
- For StellarOne 1.0/1.1, in addition to changing the password, the user is also required to change the default login name in this step. The new login name cannot be `admin`, `administrator`, `auditor` or `root`.

-
- Click **Confirm**. You will be automatically logged out. The **Log On** screen will appear again.
 - Log on again using your new credentials. The **License Activation** window appears.
 - StellarOne recognizes two license formats (**License Key** and **Activation Code**) available from different sales channels. See [Comparison of License Formats \(on page 24\)](#) first to find the license format that matches the given license data.
 - See the following instructions for how to activate license depending on the network environment.

- **StellarOne has Internet connection**

- Click **License Key**.
- Specify the License Key or Activation Code in the text field.

- **StellarOne has NO Internet connection**

- If the given license format is Activation Code, click **License Key** and specify the Activation Code in the text field.
- If the given license format is License Key, use it to download the License File (a .txt file). See [Getting the License File \(on page 222\)](#) for the detailed procedures. After getting the License File, click **License File** and import it.

- Click **Apply**.
- A success message appears. The license information also appears at the bottom of the **License Activation** window. Check if it matches the given license data.



Note:

See [Resolving Licensing Issues \(on page 244\)](#) if licensing related error messages appear.



Note:

The **License Activation** window accepts the StellarOne server's primary license only. If you intend to use a StellarDiscover add-on license, first activate the StellarICS primary license here, then apply the StellarDiscover add-on license from **Administration > License** after you complete the initial setup.

h. Click **Continue**.

i. The **End User License Agreement and TXOne OT Intelligent Trust** window appears. Click the links to read the documents carefully and click the checkboxes to proceed to next step.



Note:

It is recommended to enable **TXOne OT Intelligent Trust** to enhance security deployment. See [OT Intelligent Trust \(on page 237\)](#) for more details.

j. Specify the time settings such as the **Date and Time** as well as the **Time Zone**, and then click **Continue**.

k. The StellarOne console is ready for use now.



Note:

After the initial settings are completed, the StellarOne allows various user accounts to log on remotely via a web browser.

6. (Optional) You can change your password by clicking the ID icon at the top right corner of the screen, and then selecting **Change Password**.

7. (Optional) For security reasons, you can manually log off by clicking the ID icon at the top right corner of the screen.

a. A pop-up **Log Off** window appears. Click **Yes** to log out of StellarOne.



Note:

You will be automatically logged off the console if no operations are performed within 30 minutes.

Chapter 3. Dashboard

This chapter provides an overview of the StellarOne web console's dashboard and introduces how to configure the dashboard settings.

Topics in this chapter include:

- [About the Dashboard Screen \(on page 30\)](#)
 - [Widget for CPSDR \(on page 34\)](#)
 - [Widgets for Monitoring Agents \(on page 36\)](#)
 - [Widgets for Monitoring Disk Usage \(on page 45\)](#)
 - [Widget Manager \(on page 32\)](#)

About the Dashboard Screen

The **Dashboard** provides an overview of security monitoring, asset management, and StellarOne console's system status. Click the **Dashboard** tab in the top navigation bar of the StellarOne web console. The **Dashboard** screen with three tabs of **Security Monitoring**, **Asset Management**, and **System Status** appears.

Figure 1. About The Dashboard Screen

Function	Description
Security Monitoring	This page displays one widget related to Cyber-Physical Systems (CPS) security monitoring, along with five widgets for monitoring the agent events: • At-Risk Endpoints • Dynamic Visibility of Cyber-Physical System Security • Top Endpoints with Blocked Events • Blocked Event History • Top Blocked Files • Top Endpoints with Threat Events See Widget for CPSDR (on page 34) and Widgets for Monitoring Agents (on page 36) for more details.  Note: By default the Security Monitoring tab page is set as the landing page of the Dashboard screen.
Vulnerability	This page displays five widgets related to vulnerabilities on connected endpoints: • Detected Vulnerabilities • VSAR Vulnerability Severity • Vulnerability Distribution: OS vs. Application • Number of Endpoints Affected per CVE • Endpoints with the Most Critical and High Vulnerabilities
Policy Controls	This page displays nine widget related to policy controls:

Function	Description
	• Agent Component Status • Real-Time Protection Settings • Application Lockdown Settings • Operations Behavior Anomaly Detection Settings • Device Control Settings • Maintenance Mode Settings • Emergency Stop Mode Settings • Isolation Mode Settings • Self-management Mode Settings
Assets	This page displays three widget related to assets: • Deployment Status • Agent Connection Status • Agent Version
StellarOne Status	Under this tab, you can check StellarOne console's system status related to: • Disk Usage (1st HDD) • Disk Usage (2nd HDD) • CPU Usage • Memory Usage See Widgets for Monitoring Disk Usage (on page 45) for more details.

Function	Description
Tab Settings	DASHBOARD Security Monitoring Asset Management System Status + Add a new dashboard by clicking the plus icon to the right of the tabs.  Note: You can have up to 10 dashboards. If you've reached the limit, delete existing dashboards to create new ones. : To edit a dashboard, mouse over the name of the target dashboard and click the arrow that appears. You can rename or delete the selected dashboard.
Widget Manager	This button allows you to add desired widgets to the selected dashboard. See Widget Manager (on page 32) for more details.
Create a PDF	This button allows you to create a PDF report containing all of the information currently shown on your Dashboard widgets.

Widget Manager

The number of widgets you can add to a dashboard depends on the dashboard page layout. Once the number of widgets exceeds the maximum number the dashboard can accommodate, you must remove a widget from the dashboard or add the widget to another dashboard.

1. Go to **Dashboard** in the navigation at the top of the web console.
2. Click the **Security Monitoring**, **Vulnerability**, **Assets**, **Policy Controls**, or **StellarOne Status** dashboard.



Note:

You can add dashboard by clicking the [+](#), specifying the dashboard title in the text field, and clicking **Add** to add a new dashboard.

3. Click the **Widget Manager** button, and then the screen for adding or removing widgets appears.
4. Select to add one or more widgets to the dashboard. You can also deselect to remove one or more widgets from the dashboard.
5. Click the **Apply Changes** button to complete the task.

About the Widget

You can determine how often the widget data will be updated and specify the time period of the data for the widgets to display.

1. Click the **Refresh** icon at the top right corner of the target widget to display the up-to-date data.
2. The drop-down menu at the top right corner of each widget provides two functions:

- a. **Widget Settings**

- **Time Period:** allows you to select a specific timeframe, which determines the number of the detected threats or baseline deviations to display (The default value is **Last 7 days**).
- **Auto Refresh Settings:** allows you to configure the auto refresh frequency (The default value is **Every 30 seconds**).

- b. **Remove Widget:** allows you to remove the widgets from the dashboard.

3. On the chart widgets such as **Blocked Event History** or **Operations Behavior Anomaly Detection Settings**, click an entry on the legend to show or hide data for the associated setting.
-



Tip:

- To move a widget, click and hold on the title bar of the widget and drag it to various locations on the page.
 - To resize a widget, mouse over the bottom right corner of the widget and a diagonal resize pointer appears. Drag it to resize the widget.
-

Security Monitoring

This section provides an overview of the **Security Monitoring** dashboard and introduces how to configure the associated settings.


Five widgets for displaying Cyber-Physical Systems (CPS) situational awareness and security posture, or the critical agent events can be added to this dashboard.

Topics in this section includes:

- [Widget for At-Risk Endpoints \(on page 33\)](#)
- [Widget for CPSDR \(on page 34\)](#)
- [Widgets for Monitoring Agents \(on page 36\)](#)

Widget for At-Risk Endpoints

This first widget at the top of the **Security Monitoring** shows the at-risk endpoint and their associated data.



- **At-risk endpoint detected:** This chart displays the trend of the number change of detected at-risk endpoints according to the detected severity.
- **Total at-risk endpoints and their associations:** Click the tabs to display the respective data.
 - **At-Risk Endpoint** tab: Displays the at-risk endpoints. Click the **Endpoint** name on the tab to open the endpoint's **Situational Awareness** page. See [Situational Awareness \(on page 172\)](#) for more information. Clicking the number of the **Event Triggered** will display the categorized number of events in the **Threat Detection and Response** section. See [Threat Detection and Response \(on page 173\)](#) for more details.
 - **Groups with At-Risk Endpoints** tab: Click the tab to display the agent groups with at-risk endpoints.
 - **Triggered Rules** tab: Click the tab to display the triggered rules with the mapped MITRE ID.

Widget for CPSDR

Dynamic Visibility of Cyber-Physical Systems Security: This widget serves as the quantifying indicators of the detected threats and baseline deviations collected from the managed agents with CPSDR features enabled. Not only does it dynamically display the number of agent events triggered by detected threats, suspicious activities, and baseline deviations detected within a specified time period, but also provides actionable alerts for detected threats, as well as prioritizes suspicious activities that require additional investigation.

This widget facilitates security monitoring by means of a tiered structure with funnel-based framework:

1. Event triage:
 - **Threats:** When potential threats are detected, preventative actions are taken on behalf of SOC analysts and alerts displayed if further actions are required, enabling security personnel to work efficiently by prioritizing their time on what matters most.
 - **Suspicious Activities:** By filtering out most of the "noise" from a high volume of non-critical events and resolving the most critical incidents, suspicious activities that may lead to advanced persistent threat by a sophisticated adversary are escalated to the higher tier of investigation.
 - **Baseline Deviations:** Based on the baseline fingerprint of each agent-device established during practicable operating states, baseline deviation analysis is performed using an expansive industrial application repository and exclusive threat detection engine to defend against unexpected changes that may impact stability.
2. Investigation: The second tier for **Suspicious Activities** provides descriptive analysis for SOC analysts to track and identify the sources of these activities, facilitating the work of generating detailed report and recommendations for remediation.

The following table describes the items available on this widget:

Item	Description
Threats	Click the links to be directed to the associated agent events for more details or actions: • Actions required: The specified actions have been taken on the detected threats but more actions are required to prevent the threats. • Prevented: The specified actions have been taken on the detected threats.
Suspicious Activities	Click the  icon in the Suspicious Activities box to expand the content that prioritizes suspicious activities requiring additional investigation. • Top Detection Rules Triggered: Displays the most detection rules triggered by the suspicious events, accompanied with the MITRE ID mapping, endpoints, and the triggering events. • Top Endpoints with Triggered Rules: Displays the endpoints with the most detection rules triggered, accompanied with the description, IP address, function type (Stellar Agent (Windows) or Stellar Agent (Windows-Legacy)), triggered rules, and triggering events.
Baseline Deviation	Click the  icon to links to open the associated agent events below for more details or actions: • Top Script Behavior Baseline Deviations: Displays detected anomalies associated with unrecognized monitored process or script-based fileless attacks. • Top Login Account Baseline Deviations: Displays detected anomalies associated with unrecognized user accounts or unexpected login activities. • Top Application Baseline Deviations: Displays detected anomalies associated with unrecognized applications or unexpected application running behaviors. • Top Network Baseline Deviations: Display detected anomalies associated with unrecognized network traffics. Click the number in the list will open the following:

Item	Description
	- Number in the Endpoint column: Listing the endpoints with deviations below for your further actions. - Number in the Event Triggered: The filtered Agent Event screen will be opened. Refer to About Agent Events Screen (on page 180) for more information.

Widgets for Monitoring Agents


Three widgets for monitoring agent events can be added to the **Security Monitoring** dashboard.

- **Top Endpoints with Blocked Events**: This widget displays the endpoints with the most blocked events.
 1. Click an endpoint name to be directed to the **General Info** page for more details about the endpoint.
 2. Click a value on the chart to be directed to the relevant agent events for more details..

Table 7. Widget: Top Endpoints with Blocked Events

Column	Description
Endpoint Name	Name of the endpoint
Description	Description assigned to the endpoint
IP Address	IP address of the endpoint
Blocked Events	Total number of events blocked on the endpoint

- **Blocked Event History:** This widget displays a summary of blocked events for the specified time period.



1. Click a value on the chart to be directed to the relevant agent events for more details.
 2. Click an entry on the legend to show or hide data for that event type.
- **Top Blocked Files:** This widget displays a list of files that triggered the most blocked events.

Table 8. Widget: Top Blocked Files

Column	Description
File Name	Name of the file that triggered the blocked events
File Hash	SHA1 hash of the file that triggered the blocked events
Block Type	Protection feature that triggered the blocked events
Endpoints	Total number of the endpoints that reported the blocked events triggered by the file
Blocked Events	Total number of the blocked events triggered by the file

- **Top Endpoints with Threat Events:** This widget displays a list of endpoints with the highest threat events.

Table 9. Widget: Top Endpoints with Threat Events

Column	Description
Endpoint	Name of the endpoint. Click on the endpoint name to show more information about the agent.
Description	Description assigned to the endpoint.
IP Address	IP address of the endpoint.
Threat Events	The number of threat events. Click on the value to breakdown the events with respect to Threat Type.

Vulnerability

This section provides an overview of the **Vulnerability** dashboard and introduces how to configure the associated settings. By default, the **Vulnerability** dashboard displays five widgets:

Name	Description
Detected Vulnerabilities	A historical view of total vulnerabilities detected across all managed endpoints.
VSAR Vulnerability Severity	A pie chart indicating distribution of critical, high, medium, and low vulnerabilities detected.
Vulnerability Distribution: OS vs. Application	A pie chart indicating distribution of vulnerabilities across OS, OT apps, and non-OT apps.
Number of Endpoints Affected per CVE	A table showing which CVEs have affected the largest number of endpoints.
Endpoints with the Most Critical and High Vulnerabilities	A table showing which endpoints have the highest number of VSAR vulnerabilities.

What is VSAR (Vulnerability Situational Awareness)?

Vulnerability Situational Awareness Rating (VSAR) is a TXOne-proprietary indicator used to highlight vulnerabilities that may pose especially high real-world risk and urgency to your environment. It is not just a copy of CVSS. Instead, VSAR is an adjusted risk rating that combines:

- CVSS scores (2.0 / 3.x / 4.0 from NVD)
- EPSS (Exploit Prediction Scoring System) – likelihood a vulnerability will be exploited
- Ongoing monitoring of real-world events by the TXOne Threat Research Team

VSAR factors include:

- Age of the vulnerability
- Attack detection in the wild
- Known exploits in the wild
- Impact assessment
- Publicly available exploit/POC information
- Real-world attacker and threat scenarios



Note: Stellar Agent (Windows & Windows-Legacy) versions 1.2 to 3.0 only support software CVE detection. Agent versions 3.1 and newer support both OS and software CVE detection.



Note: For fresh Stellar Agent installs, StellarOne receives CVE data immediately, for existing agents, CVE data will be visible on StellarOne within 24 hours.

Asset Management

This section provides an overview of the **Asset Management** dashboard and introduces how to configure the associated settings.

Eight widget for displaying managed asset status and associated features settings can be viewed on this dashboard.

Topics in this section includes:

- [Widgets displaying managed asset status \(on page 39\)](#)
- [Widgets displaying key features settings \(on page 42\)](#)

Widgets displaying managed asset status

The following table describes the widgets used to display the status of the managed endpoints.

Name	Description
Deployment Status	Displays and summarizes the current status of agent deployment on the managed endpoints. See Deployment Status Widget (on page 40) for more details.
Agent Version Status	Provides an overview of the current agent versions installed on the managed endpoints. See Agent Version Status Widget (on page 41) for more details.
Agent Connection Status	Provides an overview of the availability status for agents installed on the managed endpoints. See Agent Connection Status Widget (on page 41) for more details.

Deployment Status Widget

This widget displays and summarizes the current status of agent deployment on the managed endpoints.

The following table describes the items available on this widget:

Table 10. About the Deployment Status Widget

Item	Description
Deployed	The number of the license seats used
Available Seats	The number of the remaining license seats. This figure is not displayed when a StellarDiscover add-on license is applied.
Inactive agents	The number of agents that do not hold a license seat
Status Bar	Displays current deployment status and license usage by number and percentage. The status bar is not displayed when a StellarDiscover add-on license is applied.
Agents breakdown table	Lists deployed and inactive agent counts separately for each agent edition. See the following table.

Table 11. About the Agents Breakdown in the Deployment Status Widget

Column	Description
Agents	The agent edition: Protect Edition or Discover Edition
Deployed	The number of agents of that edition currently deployed
Inactive	The number of agents of that edition that do not hold a license seat

**Note:**

When the StellarICS primary license expires, all agents become inactive, including Discover agents. When only the StellarDiscover add-on license expires and the StellarICS primary license remains valid, Discover agents are re-evaluated against the StellarICS seat quota. See [Discover Add-on Seat Allocation \(on page 227\)](#) for more details.

Agent Version Status Widget

This widget provides an overview of the current agent versions installed on the managed endpoints.

The following table describes the items available on this widget:

Table 12. About the Agent Version Status Widget

Item	Description
Drop-down menu	Displays the agent versions installed on the managed endpoints
Pie chart	Displays the distribution of agent versions installed

Agent Connection Status Widget

This widget provides an overview of the availability status for agents installed on the managed endpoints..

The data is represented in the pie chart and corresponding figures will appear when you mouse over the specific area of the pie chart.

See the following example to understand what the figures mean:

- **Online: 800 (80%):** Agents installed on the 800 (80% of 1,000 in total) managed endpoints are online.
- **Offline: 200 (20%):** Agents installed on the 200 (20% of 1,000 in total) managed endpoints are offline.

The following table describes the items available on this widget:

Table 13. About the Agent Connection Status Widget

Item	Description
Pie Chart	Displays the number and percentage of agent component update status categorized as Online and Offline: • Online: By default: the criteria of showing Online status is the agents have been connected with StellarOne within 7 days. • Offline: By default, the criteria of showing Offline status is the agents have been disconnected from StellarOne for more than 7 days.
Manage Agent Connection Status	The link will direct you to Manage Agent Connection Status for customizing the criteria of showing different agent connection status. See Manage Agent Connection Status (on page 54) for more details.

Widgets displaying key features settings

Four widgets respectively provide an overview of the associated feature settings applied to the managed endpoints by number and percentage.

The data is represented in the pie chart and corresponding figures will appear when you mouse over the specific area of the pie chart. See the following examples to understand what the figures mean.

Example 1:

- **On: 800 (80%):** The feature is enabled on 800 endpoints (80% of 1,000 in total).
- **Off: 200 (20%):** The feature is disabled on 200 endpoints (20% of 1,000 in total).

Example 2:

- **Enforce: 500 (50%):** The feature is enabled and set to "Enforce" mode on 500 endpoints (50% of 1,000 in total).
- **Detect: 400 (40%):** The feature is enabled and set to "Detect" mode on 400 endpoints (40% of 1,000 in total).
- **Disable: 100 (10%):** The feature is disabled on 100 endpoints (10% of 1,000 in total).

Table 14. About the Widgets Displaying Features Settings

Name	Description
Real-Time Protection Settings	Provides an overview of the Real-Time Protection settings applied to the managed endpoints by number and percentage. The Real-Time Protection settings include: • On: The Real-Time Protection is enabled. Persistent and ongoing file scan is running on the group of endpoints. • Off: The Real-Time Protection is disabled.
Application Lockdown Settings	Provides an overview of the Application Lockdown settings applied to the managed endpoints by number and percentage. The Application Lockdown settings include: • Enforce: The files not in the Approved List will be blocked and corresponding events will be generated on the group of endpoints.. • Detect: The files not in the Approved List will be allowed and corresponding events will be generated on the group of endpoints.. • Disable: The Application Lockdown is turned off.  Note: The Stellar Agent (Windows-Legacy) provides only two modes for Application Lockdown settings, ON and OFF, which correspond respectively to Enforce and Detect in the widget.
Operations Behavior Anomaly Detection Settings	Provides an overview of the Operations Behavior Anomaly Detection settings applied to the managed endpoints by number and percentage. The Operations Behavior Anomaly Detection Settings settings include:

Table 14. About the Widgets Displaying Features Settings (continued)

Name	Description
	• Learn: In the group of endpoints, the agents are collecting behavioral patterns from the installed devices to establish a baseline. • Detect: In the group of endpoints, the agents identify and send alerts for any unexpected changes or security threats by analyzing current behaviors against the baselines. • Enforce: In the group of endpoints, the agents take preventative action on detected baseline deviations to defend operation stability and security. • Disable: The Operations Behavior Anomaly Detection Settings is turned off.
Device Control Settings	Provides an overview of the Device Control settings applied to the managed endpoints by number and percentage. The Device Control settings include: • On: The Device Control is enabled. Only the devices added in the trusted list have permanent access to the group of endpoints. • Off: The Device Control is disabled.

StellarOne Status

This section provides an overview of the **System Status** dashboard and introduces how to configure the associated settings.


Four widget for displaying console's system status can be viewed on this dashboard.

Topics in this section includes:


- [Widgets for Monitoring Disk Usage \(on page 45\)](#)
- [Widgets for Monitoring CPU & Memory Usage \(on page 46\)](#)

Widgets for Monitoring Disk Usage

- **Disk Usage (1st HDD):** This widget displays the current total size of the first disk and amount used for the OS partition.




- **Disk Usage (2nd HDD):** This widget displays the current total size of the second disk and amount used for the System, Database, and Other partition.




Widgets for Monitoring CPU & Memory Usage

- **CPU Usage:** This widget displays the percentage of the total CPU capacity used.



- **Memory Usage:** This widget displays the percentage of the total memory consumed.



Policy Controls

This section provides an overview of the **Policy Controls** dashboard and introduces how to configure the associated settings.

Nine widgets can be viewed on this dashboard:

1. **Agent Component Status:** Provides an overview of the component update status for agents installed on the managed endpoints. The data is represented in the pie chart and corresponding figures will appear when you mouse over the specific area of the pie chart. See the following example to understand what the figures mean:
 - **Up-to-date: 800 (80%):** The agent components are up to date on 800 endpoints (80% of 1,000 in total).
 - **Out-of-date: 200 (20%):** The agent components are out of date on 200 endpoints (20% of 1,000 in total).

The following table describes the items available on this widget:

Item	Description
Pie Chart	Displays the number and percentage of agent component update status categorized as Out-of-date and Up-to-date: ◦ Out-of-date: By default, the criteria of showing Out-of-date status is the agent components haven't been updated for more than one week. ◦ Up-to-date: By default: the criteria of showing Up-to-date status is the agent components have been updated within one week.  Note: This widget displays only the agents that appear Online in the Agent Connection Status widget. See Agent Connection Status Widget (on page 41) for more details.
Manage Agent Component Status	The link will direct you to Manage Agent Component Status (on page 55) to view or configure the agent component status settings.
Learn more	This link will direct you to the TXOne StellarOne Online Help for more details about the agent component status widget and associated settings.

2. **Real-Time Protection Settings**: Provides an overview of the Real-Time Scan settings applied to the managed endpoints by number and percentage.
3. **Application Lockdown Settings**: Provides an overview of the Application Lockdown settings applied to the managed endpoints by number and percentage.
4. **Operations Behavior Anomaly Detection Settings**: Provides an overview of the Operations Behavior Anomaly Detection settings applied to the managed endpoints by number and percentage.
5. **Device Control Settings**: Provides an overview of the Device Control settings applied to the managed endpoints by number and percentage.

6. **Maintenance Mode Settings:** An overview of the Maintenance Mode Settings applied to the managed endpoints.
7. **Emergency Stop Mode Settings:** An overview of the Emergency Stop Mode Settings applied to the managed endpoints.
8. **Isolation Mode Settings:** An overview of the Isolation Mode Settings applied to the managed endpoints.
9. **Self-management Mode Settings:** An overview of the Self-management Mode Settings applied to the managed endpoints.

Chapter 4. Endpoint Management

This chapter introduces how to manage Stellar Agent (Windows), and Stellar Agent (Windows-Legacy) agents via StellarOne web console.

Topics in this chapter include:

- [About the Agents Screen \(on page 50\)](#)
- [Upgrade from Discover Edition to Protect Edition \(on page 67\)](#)
- [Protection \(on page 67\)](#)
- [Update \(on page 75\)](#)
- [Agent Export/Import Settings \(on page 79\)](#)

About the Agents Screen

The StellarOne console facilitates agent management by allowing you to organize agents into various groups and build up multi-level hierarchy among the groups (parent groups above child groups), forming an agent/group tree structure. On the **Agents** screen, you can deploy one-time commands to the selected groups and/or agents for performing immediate actions.

Click the **Agents** tab in the top navigation bar of the StellarOne web console. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.



Note:

All agents are under the **All** group by default.

Table 15. Toolbar

Tools	Description
+Add Group	This tool allows you to create groups according to location, type, or purpose for better multi-agent management. See Add Groups (on page 59) for more details.
Organize	This tool allows you to edit description for agent(s), move agent(s) to another group, and delete agent(s)/group(s). See Edit Description for Agents (on page 60) and Organize Agents/Groups (on page 60) for more details.
Protection	This tool allows you to configure Maintenance Mode/Isolation Mode, update Approved List when the Application Lockdown feature is enabled, and customize file scan settings. See Configure Maintenance Mode (on page 68) , Update Approved List (on page 71) , Scan Now (on page 71) , and Configure Isolation Mode (Stellar Agent (Windows) Only) (on page 73) for more details.
Update	This tool allows you to update components and deploy patches for agents, as well as check connections with endpoints, apply group/agent policies immediately, and collect event logs (Windows-Legacy only). See Update Agent Components (on page 75) , Deploy Agent Patches (on page 75) , Check Connections (on page 76) , Apply Policies (on page 77) , and Collect Event Logs (on page 77) for more details.
Import/Export	This tool allows you to export an agent config file (Windows-Legacy only) or Approved List (Windows-Legacy only), and then import it to apply the settings specified in the config file or Approved List to a batch of target agents/groups. You can also export information about the selected or all agents. See Agent Export/Import Settings (on page 79) for more details.

Table 15. Toolbar (continued)

Tools	Description
Global Policy	Because groups and agents do not always inherit policies from their parent groups, settings such as Trusted Certificates and User-Defined Suspicious Objects often need to be configured repeatedly for each non-inherited group or agent. With Global Policy, Trusted Certificates and User-Defined Suspicious Objects can be applied automatically to all groups and agents, except agents in Self-Management mode.

Table 16. Column Headings

Headings	Description
<i>Name</i>	•  : Indicates a group •  : Indicates an agent and its connection status is Online •  : Indicates an agent and its connection status is Offline •  : Indicates an agent is assigned as an update agent and its connection status is Online •  : Indicates an agent is assigned as an update agent and its connection status is Offline  Note: The criteria of displaying Online and Offline status depend on how long the agent has been disconnected from StellarOne. By default, the agent will appear Offline after disconnected from StellarOne for more than 7 days. See Manage Agent Connection Status (on page 54) for more details. •  : Indicates the agent's license has expired and needs to be renewed
<i>IP Address</i>	Displays the IP Address of the endpoint (one IP address corresponds to a single agent)

Table 16. Column Headings (continued)

Headings	Description
<i>Protection</i>	•  : Indicates the Application Lockdown is enabled •  : Indicates the Real-Time Scan is enabled •  : Indicates the agent is in maintenance mode •  : Indicates a maintenance period has been scheduled but not started yet •  : Indicates all the agent protection features are disabled and the endpoint may be vulnerable to security threats •  : Indicates the protection provided by the agent has been fully disabled, which is triggered by the local user via the Stop protection button on the local console. The endpoint may be vulnerable to security threats. •  : Indicates the Isolation Mode is enabled.
<i>Agent Edition</i>	Displays agent edition used: • Discover • Protect
<i>Agent Type</i>	Displays agent types for Stellar Agent (Windows): • Win: for devices with Windows 7 or later versions • Win-L: for devices with legacy platforms such as Windows XP/2000 • Linux: for supported Linux distributions
<i>Policy Inheritance</i>	• Inherited: Indicates the policy settings for the agent/group are inherited from its parent group • Customized: Indicates the policy settings for the agent/group are customized by administrators •  Self-managed: Indicates the agent/group is free from the StellarOne web console's policy management and its feature settings should be configured on the local console •  : Indicates the agent's feature settings synchronize with the StellarOne console policy settings •  : Indicates the agent's feature settings do not synchronize with the StellarOne console policy settings

Table 16. Column Headings (continued)

Headings	Description
<i>Critical Vulnerability</i>	Displays the amount of CVEs with critical severity that are found on a particular agent during the VDS scan.
<i>Agent Version</i>	Displays the firmware version of the agent
<i>Component Status</i>	Displays the component update status of the agent: •  Up-to-date: Indicates the components installed on the agent have been updated within a specified duration •  Out-of-date: Indicates the components installed on the agent have not been updated for more than a specified duration  Note: By default, the component status will appear Out-of-date after 1 week. See Manage Agent Component Status (on page 55) for more details.
<i>Last Connection</i>	Displays the last time the agent was connected with StellarOne
<i>Actions</i>	Under this heading, you can: • click  , the Policy icon, for linking to the General Info policy page. • click the three dots More actions menu, for organizing agents and renaming/removing groups. See Edit Description for Agents (on page 60) and Organize Agents/Groups (on page 60) for more details.

Table 17. Other Tools

Tool	Description
Filter	This tool allows you to quickly find the agents/groups by sorting and searching. See Filter Options for Agents/Groups (on page 64) for more details.

Table 17. Other Tools (continued)

Tool	Description
Table Display Settings	This tool allows you to customize the table display settings by: • going back and forth between the display pages • selecting how many agents/groups to be displayed per page and specifying only certain contents to be displayed in the Customize Table Display setting
Agent Status Settings	This tool allows you to view or change current configuration for the agent status settings, which determines the associated agent status displayed on the Agents screen and the information displayed in the corresponding widgets on the Dashboard screen. Available options include: • Manage Agent Connection Status: Specify the duration (by days) to determine whether the agents should be categorized as Online, Offline, or removed from StellarOne. See Manage Agent Connection Status (on page 54) for more details. • Manage Agent Component Status: Specify the duration (by a day, week, or month) to determine whether the agent component update status should be categorized as Up-to-date or Out-of-date. See Manage Agent Component Status (on page 55) for more details. • Refresh: Manually refreshing the agent status for the latest outputs

Agent Status Settings

This section introduces how to configure the following agent status settings:

- [Manage Agent Connection Status \(on page 54\)](#)
- [Manage Agent Component Status \(on page 55\)](#)
 - [Correlated Settings for Agent Component Status \(on page 56\)](#)
 - [Configuring Agent Component Status Settings— Use Case \(on page 58\)](#)

Manage Agent Connection Status

The configuration of **Manage Agent Connection Status** determines the connection status of each single agent displayed on the **Agents** screen, as well as the overall availability status of all the managed agents displayed in **Agent Connection Status** widget on the **Dashboard** screen.

The criteria of displaying **Online**, **Offline**, and removal of the agent depend on how long the agent has been disconnected from StellarOne. By default, the agent will appear **Offline** after disconnected from StellarOne for more than 7 days and basically never be removed from StellarOne no matter how long the disconnection lasts. In other words, by default the agent will always appear **Online** if it has been connected to StellarOne within 7 days.

You can also customize the settings to fit your environment needs. See the following instructions for how to change the configuration:

1. Go to **Agents** in the top navigation bar of the StellarOne web console.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Find the settings icon  on the right side of the screen.
4. Click  and select **Manage Agent Connection Status** from the drop-down menu.
5. The configuration window appears. In **Appear Offline after** drop-down menu, specify the time frame after which the agent connection status will display offline if the agent has been disconnected. Available time period for selection includes:
 - 1 day
 - 2 days
 - 3 days
 - 7 days (Default)
 - 14 days
 - 30 days
6. In **Remove from StellarOne after**, specify the time frame after which the agent will be removed from StellarOne managed agents list if disconnected for more than the specified duration. Available time period for selection includes:
 - Never (Default)
 - 1 month
 - 2 months
 - 3 months
 - 6 months
 - 12 months

See the sections below for more details about the correlated settings to consider and use case when configuring the agent connection status settings.

Manage Agent Component Status

The configuration of **Manage Agent Component Status** determines the component update status of each single agent displayed on the **Agents** screen, as well as the overall component update status of all the managed agents displayed in **Agent Component Status** widget on the **Dashboard** screen.

The criteria of displaying **Up-to-date** or **Out-of-date** depend on how long the agent components have or have not been updated. By default, the status of agent components will always appear **Up-to-date** if they have been updated within 1 week. In other words, by default the status of agent components will appear **Out-of-date** if they haven't been updated for more than 1 week.

You can also customize the settings to fit your environment needs. See the following instructions for how to change the configuration:

1. Go to **Agents** in the top navigation bar of the StellarOne web console.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Find the settings icon  on the right side of the screen.
4. Click  and select **Manage Agent Component Status** from the drop-down menu.
5. The configuration window appears. In the **Appear Out-of-date after** drop-down menu, specify the time frame after which the status of agent components will display out-of-date if they haven't been updated. Available time period for selection includes:
 - 1 day
 - 1 week (Default)
 - 1 month
 - 2 months



Important:

- It is recommended to take the agent component update schedule specified in the agent/group policy settings into consideration before you adjust the configuration of **Manage Agent Component Status**. See [Correlated Settings for Agent Component Status \(on page 56\)](#) and [Configuring Agent Component Status Settings— Use Case \(on page 58\)](#) for more details.
 - If you enable **Defer Component Update** in the agent component update schedule, the agent or group deployed with the previous components version will be categorized as **Up-to-date** in the widget. See [Agent Component Update Schedule \(on page 152\)](#) for more details.
-

Correlated Settings for Agent Component Status

Changes of several settings can impact the **Agent Component Status** widget. Properly configuring the correlated settings determines if the widget can accurately reflect your environment.

See the following table for an overview of the correlated settings and factors to consider:

Table 18. Correlated Settings and Relevant Details

Setting	Location	Frequency or Duration	Factor to consider
Scan Component Update Schedule (StellarOne)	Administration > Downloads/Updates > StellarOne	Frequency options: • Daily (Default) • Weekly • Monthly • Start Time: 20:00 (Default)	Data transmission bandwidth  Note: See Recommended Bandwidth for StellarOne Components Update (on page 58) for more details.
Agent Component Update Schedule	Agents > All: target agent/group Policy page	Frequency options: • Daily (Default) • Weekly • Monthly • Start Time: 00:00 (Default)	
Manage Agent Component Status	Agents > Status Settings	Duration options: • 1 day • 1 week (Default) • 1 month • 2 months  Note: By default, the agent component status will appear out-of-date after 1 week.	The frequency specified in Agent Component Update Schedule

Table 18. Correlated Settings and Relevant Details (continued)

Setting	Location	Frequency or Duration	Factor to consider
Manage Agent Connection Status	Agents > Status Settings	Duration options: • 1 day • 2 days • 3 days • 7 days (Default) • 14 days • 30 days  Note: By default, the agent connection status will appear Offline after 7 days.	The duration specified in Manage Agent Component Status

Recommended Bandwidth for StellarOne Components Update

See the following table for the recommended data transmission bandwidth for StellarOne components update.

Method	Recommended Bandwidth (On Average)
Full load	75 MB (if the components loading takes place every 15 days)
Incremental load	200 KB (if the components loading takes place within 14 days)

Configuring Agent Component Status Settings— Use Case

The following section describes a use case that requires the StellarOne admin to configure the correlated components update and agent component status settings.

Scenario: You have a group of agents that are scheduled for maintenance **at the first day of every month**. Since the update frequency is fixed to "monthly", you'll need to change the default settings (daily) to **Monthly** for the **Agent Component Update Schedule**, to prevent the updates from impacting on the asset operations. Furthermore, since monthly component update is viewed "normal" for this group of assets, you'll also need to change the default settings (1 week) to at least **1 month** for the **Agent Component Status** widget, so the group of assets can appear up-to-date within the determined update frequency that fits your environment.

See the following procedures as the recommended practice:

1. Go to **Scan Component Update Schedule (StellarOne)**, select the frequency you want StellarOne to download the latest scan component. It is recommended to select **Daily** or **Weekly** if the data transmission bandwidth is limited. Refer to [Recommended Bandwidth for StellarOne Components Update \(on page 58\)](#) for more information.

**Note:**

See [Configuring Scan Component for StellarOne \(on page 212\)](#) for more detailed configuration procedures.

2. Go to **Agent Component Update Schedule**, specify the frequency StellarOne will apply the latest scan components to the managed group of agents. It is recommended to select **Monthly**. However, you may need to adjust the network bandwidth between the agents and StellarOne for smooth updates. Refer to [Recommended Bandwidth for StellarOne Components Update \(on page 58\)](#) for more information.



Note: See [Agent Component Update Schedule \(on page 152\)](#) for more detailed configuration procedures.

3. Go to **Agents > Settings > Manage Agent Component Status** to specify **1 month**. The agent component status will appear up-to-date if the components have been deployed to the managed agents within 1 month.

**Note:**

It is recommended to specify a larger or the same value for the time frame compared with that of the frequency set in **Agent Component Update Schedule**; otherwise, the group of the agents would appear out-of-date.

4. Since the **Agent Component Status** widget only displays agents that appear **Online** in the **Agent Connection Status** widget, if the group of agents may be disconnected to StellarOne for more than the duration specified in the **Manage Agent Connection Status** settings, it'd be better to go to **Agents > Settings > Manage Agent Connection Status** to specify **30 days** after which the agents will appear offline if disconnected with StellarOne.

Add Groups

1. Go to **Agents** in the top navigation bar of the StellarOne web console.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Click the **+Add Group** button in the toolbar.
4. The **Add New Agent Group** window appears. Specify the group name in the text field.

**Note:**

- The maximum length limitation of a group name is 50 characters.
- The maximum number of group levels is 15 levels.

5. Click **Confirm** to add the group.

Edit Description for Agents

To edit description for agents, which will appear on the main screen of the local agent, follow below procedures.

1. Go to **Agents** in the top navigation bar of the StellarOne web console.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. There are two ways to edit descriptions for agent(s):
 - To edit description for multiple agents at the same time, click the checkboxes next to the target agents. Click the **Organize** tool on the toolbar.
 - To edit description for a single agent, find the target agent and click its three dots **More actions** menu under the **Actions** header.
4. A drop-down menu appears. Click **Edit Description** and then a window appears.
5. Specify the description for the agent(s) in the text field.
6. Click **Confirm** to complete this task.

Organize Agents/Groups

You can organizing agents/groups by:

- renaming groups
- removing groups
- removing agents from groups
- moving agents to another group

1. Go to **Agents** in the top navigation bar of the StellarOne web console.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. To rename a group, click the three dots **More actions** menu of the target group under the **Actions** header. A drop-down menu appears. Select **Rename** and then a pop-up window appears. Delete the old group name and replace it with a new one. Click **Confirm** to complete this task.



Note:

Groups at the same level can not have the same group name.

4. There are two ways to remove groups or agents:

- To remove multiple agents or groups at the same time, click the checkboxes next to the target agents or groups. Click the **Organize** tool on the toolbar and select **Delete**. Click **Confirm** to remove the agents/groups.

**Important:**

- To remove agent(s): The agent(s) will be unregistered from the server.
- To remove group(s): The group(s) and the configuration of the group(s) will be removed.

- To remove a single agent or group, click the three dots **More actions** menu of the target agent/group under the **Actions** header. A drop-down menu appears. Select **Delete** to remove the agent/group.

**Important:**

To remove groups with child groups/agents, please remove the child groups/agents from the target groups first.

5. There are two ways to move agent(s) to another group:

- To move multiple agents to another group at the same time, click the checkboxes next to the target agents. Click the **Organize** tool on the toolbar.
- To move a single agent to another group, click the three dots **More actions** menu of the target agent under the **Actions** header.

A drop-down menu appears. Select **Move** and then a pop-up window appears. Select the group and click **Confirm** to complete this task.

Transfer Agents to Another StellarOne

Other than the ways mentioned in the previous section to organize your agents, you can also transfer agents to another StellarOne server.

**Important:**



- It is strongly recommended **not** to transfer agents to a StellarOne server with lower version than the agents.
- Policy of the agents cannot be transferred. Before transferring, ensure that the group and policy is configured at the destination server.
- When transferring agents to a new StellarOne server, the agents' baseline setting will be transferred, too. However, if a toggle of a baseline is manually turned off after the item is added to the baseline, the setting will not be transferred. For example, if the toggle of a Script Behavior is off in the original server (the behavior is not permitted), when transferred to the new server, the said Script Behavior will still be included in the baseline, but the toggle will be set at on (the behavior is permitted). Pay attention and note of the toggle status of the baseline activities before transferring agents.
- After you have completed configuring the groups and policy at the destination server, add the said StellarOne to the **StellarOne Pool**. See [StellarOne Pool \(on page 238\)](#) for instructions.

-
1. Go to **Agents** on the top navigation bar of the StellarOne web console.
 2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
 3. To transfer agents, select the agent(s) by checking the box(es) next to it(them).
 4. Click the **Organize** tool on the toolbar then select **Transfer**.
 5. On the **Specify a Destination Server** window, check if the selected agents is being transferred to a **New StellarOne** server or an **Existing StellarOne with new server address**.

- Transfer to an **Existing StellarOne with new server address**

Select this option when the destination is an existing StellarOne with a changed server address. Specify the new **Server Address** then click **Next**.

- Transfer to a **New StellarOne**

Select this option when the destination is a StellarOne server you have added to the **StellarOne Pool** by following the instructions on [StellarOne Pool \(on page 238\)](#).

Select a **Server Name** in the drop-down list, and then select a **Parent Group**. Click **Next**.



Note:

Ensure that the destination **Parent Group** contains the same immediate child groups (with matching group names) as the agents you are transferring. You do not need to replicate the entire group hierarchy up to the 'All' group, only the relevant child groups for the transferred agents must exist in the destination **Parent Group**.

-
6. Confirm the information of this transfer on the screen. Click **Transfer**, and then **Close**.



Note:



When you transfer Discover agents to another StellarOne server, the seat pool the transferred agents draw from is determined by the destination server:

- If the destination server has a StellarICS license with an effective StellarDiscover add-on license, the transferred Discover agents use Discover add-on seats and do not consume StellarICS seats.
- If the destination server has a StellarICS license without an effective StellarDiscover add-on license, the transferred Discover agents consume StellarICS seats.

This applies regardless of whether the source server is a StellarICS environment or a StellarDiscover-only environment. Before transferring, confirm that the destination server has sufficient seats in the relevant pool; agents that exceed the seat quota at the destination are set to Inactive. See [Discover Add-on Seat Allocation \(on page 227\)](#) for more details.

Assign Update Agents

To effectively utilize the resource of the StellarOne server, you can assign agents as component update replay agents. So instead of connecting to the StellarOne server for component updates, the agents will receive updates from the assigned agents serving as update source.

Follow the instructions below to assign an agent as an **Update Agent**.

1. Go to **Agents** on the top navigation bar of the StellarOne web console.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents/groups managed by StellarOne.
3. Here are ways to assign **Update Agents**.
 - Select it(them) by checking the box(es) next to it(them). Click the **Organize** tool on the toolbar and select **Update Pool > Set as Update Agent**.



Note: To add the assigned Update Agent to a Update Pool, see [Manage Update Agents \(on page 216\)](#) for instructions.

- Select it(them) by checking the box(es) next to it(them). Click the **Organize** tool on the toolbar and select **Update Pool > +Create Update Pool**. Then click **Create** after specifying a **Pool Name**. This way will create a new **Update Pool** with the selected agent as an **Update Agent** in the pool.



Note: See [Manage Recipient Groups \(on page 216\)](#) for further instructions on how to add recipient groups.

- Select it(them) by checking the box(es) next to it(them). Click the **Organize** tool on the toolbar and select **Update Pool > Add to Existing Pools**. On pop-up window that appears, select a existing pool and then click **Confirm**. This way will assign the selected agents as **Update Agents** in an existing **Update Pool**.



Tip: To revoke an Update Agent, on the **Agent** screen, select an agent by checking the box next to it. Click the **Organize** tool on the toolbar and select **Update Pool > Revoke Update Agent**.



- Note:**
- An Update Agent can only be assigned to one Update Pool.
 - Only agents running Stellar Agent v3.2 or higher can be assigned as a Update Agent.
 - If an Update Agent is unavailable for components update, StellarOne will act as the update source to ensure uninterrupted deployment.

Search for Agents/Groups

1. Go to **Agents** in the top navigation bar of the StellarOne web console.
2. At the top-right corner of the screen, search for specific endpoints by selecting criteria from the drop-down list and specify additional search criteria as required.

Filter Options for Agents/Groups

Figure 2. Filter Options for Agents/Groups




Table 19. Filter Options for Agents/Groups

Options	Descriptions
	This icon provides four filter options:

Table 19. Filter Options for Agents/Groups (continued)

Options	Descriptions
	• Active Agents: the agents holding a license seat, from either the primary license seat pool or the Discover add-on seat pool • Inactive Agents: the agents that do not hold a license seat • Ungrouped Agents: the agents that are not grouped • Update Agents: the agents that are assigned as an Update Agent
Name	The name of the agent. When the Name filter is selected, another filter will appear to the right. If you would like to perform a partial search, select Contains , then type the text in the search box to the right to perform the search. Or search for agents with the same name, select Find duplicates .
IP Address	The IP address of the agent. When the IP Address filter is selected, another filter will appear to the right. If you would like to perform a partial search, select Contains , type the IPv4 address in the search box to the right to perform the search. Or search for agents with the similar IP, select Find duplicates .
IP Range	Type the IPv4 address range.
Group	The name of the group. Please ensure that you select the available group.
Policy Inheritance	Three options -- Customized , Inherited , and Self-managed , are available for selection.
Policy Deployment	The status of policy deployment from StellarOne to Agents. Select Completed or In Progress .
Operations Behavior Anomaly Detection	Find the target agents by the modes of the Operations Behavior Anomaly Detection. Four modes are available for selection: Learn , Detect , Enforce , or Disabled .
Connection Status	Select to show the Online or Offline agents.
Component Status	Select to show the agents with component status Out-of-date or Up-to-date .

Table 19. Filter Options for Agents/Groups (continued)

Options	Descriptions
Agent Version	Type the build version of the target agents.
Last Component Update	Click then select a period to filter the time when the agent had the Last Component Update .
Last Connection	The last time the agents were connected with StellarOne. Select the default time period or select Custom range to specify a time period. Default time period available for selection includes: • Last 1 hour • Last 24 hours • Last 7 days • Last 30 days
Agent Type	Select Stellar Agent (Windows) , Stellar Agent (Windows-Legacy) or Stellar Agent (Linux)
Operating System	Select an operating system of the target endpoints.
Transfer Status	Select to show the transfer status if the agents are being transferred to a different server. Available filter options include: • No Status • Failed • In Progress • Successful
Description	Type the full or partial description to query specific endpoints.
Agents with CVE	Type the exact ID of a CVE.
Smart Trusted Program List	Select to filter agents by Smart Trusted Program List status. Available filter options include: • Enabled • Disabled
Agent Edition	Select to filter agents based on edition, e.g. Discover or Protect.
Protection	Seven options to filter agents based on their protection status:

Table 19. Filter Options for Agents/Groups (continued)

Options	Descriptions
	• Protection Disabled • Real-Time Protection Enabled • Application Lockdown Enabled • Maintenance Mode Enabled • Maintenance Mode Scheduled • Isolation Mode Enabled • Emergency Stopped

Upgrade from Discover Edition to Protect Edition

In addition to upgrading to Protect Edition in the Stellar Agent console, it is also possible to upgrade remotely via the StellarOne console. Follow the below steps to upgrade to Protect Edition.



Note:

A StellarICS license is required to upgrade to **Protect Edition**.

When a StellarDiscover add-on license is applied, upgrading an agent from Discover Edition to Protect Edition moves that agent out of the Discover add-on seat pool and into the StellarICS seat pool. If StellarICS seats are insufficient after the upgrade, the upgraded agent becomes Inactive. Confirm that StellarICS seats are available before upgrading. See [Discover Add-on Seat Allocation \(on page 227\)](#) for more details.

1. Click the **Agents** tab in the top navigation bar of the StellarOne web console.
2. Click the **All** group on the **Agents** screen.
 - a. The **Agents** screen displays a list of endpoints managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Protection** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Upgrade from Discover Edition to Protect Edition** option.
6. Check the **I understand that upgrading is irreversible** checkbox.
7. Click **Upgrade**.
8. A **Command Deployment** page will appear.
 - a. The status of the upgrade will show under the **Status** column.
9. The **Command Deployment** page can be closed at any time.

Protection

The **Protection** tool sends one-time commands to endpoints for triggering immediate actions, allowing you to configure Maintenance Mode, update Approved List when the Application Lockdown feature is enabled, and customize file scan settings.

Topics in this chapter include:

- [Configure Maintenance Mode \(on page 68\)](#)
- [Update Approved List \(on page 71\)](#)
- [Scan Now \(on page 71\)](#)
- [Configure Isolation Mode \(Stellar Agent \(Windows\) Only\) \(on page 73\)](#)
- [Configure Emergency Stop Mode \(on page 74\)](#)

Configure Maintenance Mode

To perform approved file updates or system maintenance on endpoints, you can configure Maintenance Mode for it to execute for a specified period of time. During the Maintenance Mode, the agents allows all file executions and adds all files that are created, executed, or modified to the Approved List. Besides, the agents can ensure the execution of these applications are under the protected conditions by performing malware scanning before adding new or changed files to the Approved List. You can also define the action to take after suspicious files are detected.



Important:

Before using Maintenance Mode, apply the required updates on the following supported platforms for Stellar Agent (Windows-Legacy) agents:

- For Windows 2000 Service Pack 4, apply the update KB891861 from the Microsoft Update Catalog website.
- For Windows XP SP1, upgrade to Windows XP SP2.



Note:

- If you change the policy settings of Application Lockdown, Multi-Method Threat Prevention (Stellar Agent (Windows)), OT Application Safeguard (Stellar Agent (Windows)), or Threat Prevention (Stellar Agent (Windows-Legacy)) during maintenance period, the policy settings will not be implemented until the maintenance period is ended.
- During the maintenance period, you cannot perform agent patch updates on endpoints. In addition, Stellar Agent (Windows-Legacy) does not support Windows updates that require restarting an endpoint during the maintenance period.
- To run an installer that deploys files to a network folder during the maintenance period, Stellar Agent (Windows-Legacy) must have access permission to the network.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Protection** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Configure Maintenance Mode** option.

6. Click **Confirm**.
7. The configuration window appears. You may add a comment for future reference. Please read the notice carefully before you check the **Disable** or **Enable** button.

- Click **Disable > OK** to end Maintenance Mode. This will cancel the scheduled maintenance period on endpoints.
- a. A warning message appears. Please read carefully before proceeding to next step.

**Important:**

If the Maintenance Mode is ended, the endpoint will start blocking the execution of files that are not recognized by the Application Lockdown or OT Application Safeguard.

- b. Click **OK** to end Maintenance Mode. A pop-up window appears showing the deployment status of stopping Maintenance Mode on endpoints.
- Click **Enable** to start the Maintenance Mode settings. Please go to *Step 8* for next procedure.

**Important:**

To reduce risk of infection, run only applications from trusted sources on endpoints during the maintenance period.

8. The schedule configuration window appears. Do one of the following for scheduling Maintenance Mode.

**Note:**

- Agents can start one scheduled maintenance period at a time. If you configure a new maintenance period, the system overwrites the existing maintenance schedule that has not started yet.
 - When the agent is about to leave Maintenance Mode, restarting the endpoint prevents Stellar Agent (Windows-Legacy) from adding files in the queue to the Approved List.
-

- Click the **Schedule** button, and then click the edit icon to select the start date and specify the start time for Maintenance Mode. After that, specify the duration of the maintenance period in **Maintenance duration**.
 - Click the **Start now** radio button, and then specify the duration of the maintenance period in **Maintenance duration**.
9. Click **Confirm** to deploy the settings to the selected agents or groups.
 10. The **Command Deployment** window appears showing the deployment status. Click the **Close** button to close the window.

**Note:**

On the **Agents** screen, in the **Protection** column of the selected agents/groups:

- The  will appear indicating a maintenance period has been scheduled but not started yet if you select **Schedule** in *Step 8* and deploy related settings.
- The  icon will appear indicating the agents/groups are currently in maintenance mode if you select **Start now** in *Step 8* and deploy related settings.

Enable Smart Trusted Program List

The Smart Trusted Program List is an intelligent, administrator-controlled feature in StellarOne that automatically detects and adds programs incompatible with the Stellar Agent (Windows) to the Trusted Program List, helping prevent performance issues and operational disruptions. When enabled, this feature updates the list immediately, ensuring that listed programs bypass Stellar's abnormal activity monitoring and do not generate logs. Administrators retain full control, they can review, remove, or disable automatically added exceptions, and all such actions are clearly logged for transparency. To view the current list, navigate to Agents and select Import/Export > Export Trusted Program list.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Protection** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Smart Trusted Program List** option.
6. Click **Confirm**.
7. The configuration window appears. Please read the notice carefully before you check the **Disable** or **Enable** button.
8. Check **I understand that enabling Smart Trusted Program List will reduce Stellar's protective ability** and click **Confirm**.
9. The command will now be deployed to the agents, and you can monitor the status on-screen.

Command Deployment

Date and Time

2025-11-13T16:21:47+08:00

Event

Send command <Enable/Disable Auto Trusted Program List> to agents

All Status (2) ▾

Endpoint ↓	IP Address	Group	Status
ST-WIN10X64	10.8.151.79	All	☐ Deploying...
ST-WIN10ENT-X86	10.8.151.160	All	☐ Waiting for agent response

Close

Update Approved List

This function allows you to update the Approved List on selected agents/groups by several simple clicks. Updating the Approved List performs an inventory scan on selected endpoints and adds any new applications found on the endpoints to the global Approved List. The Approved List must be periodically updated so the newly-added applications can run on the endpoints when the Application Lockdown feature is turned on.

After setting up the Approved List, you can also add new programs by enabling Maintenance Mode, and the new or modified files will be added to the Approved List.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Protection** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Update Approved List** option.
6. Click **Confirm**.
7. A pop-up **Update Approved List** window appears. Click **OK** to start the Approved List update process.



Warning:

Do not restart or turn off the endpoint(s) during the update. The update process may take more than 30 minutes to complete.

8. The **Update Approved List** window appears showing the update status. Click the **Close** button to close the window.

Maintenance Mode/Approved List: Use Case

It is recommended to install or update an application while the agent device is under Maintenance Mode to make sure the application is added to the Approved List. If an application is installed or updated and not recognized by Stellar, the system will generate agent event 5888 (refer [Agent Event Log Descriptions for Stellar Agent \(Windows\) \(on page 252\)](#) for log details) to alert you about the incident. When this happens, you can try the following:

1. Follow the instructions in the previous section [Update Approved List \(on page 71\)](#) to update the agent's Approved List. After the application is added to the approved list, the system will allow the process and won't generate a warning event log.
2. Follow the instructions in [Configure Maintenance Mode \(on page 68\)](#) to schedule a Maintenance Mode period and perform the installation or update the application again for Stellar to add the application to the Approved List.

Scan Now

You can manually initiate **Scan Now** on selected endpoints and deploy the scan settings on one or several target endpoints.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Protection** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Scan Now** option.
6. Click **Confirm**.
7. The configuration window appears.
8. The configuration window consists of four sections: **Files to Scan**, **CPU Usage**, **Scan Action**, and **Scan Exceptions**.



Note:

The Stellar Agent (Windows-Legacy) agents will automatically attempt to download the latest components before starting a scan. A **Component Update Before the Scan** toggle is available for you to determine whether the endpoints should continue with the scan if the component update is unsuccessful.

- a. In the **Files to Scan** section, click **All local folders** to scan all files in detail; click **Default folders (Quick Scan)** for a general scan; or click **Specific folders** to specify the paths to the folders for scan.



Tip:

Under the **Specific folders** option, click the "+" or "-" icon to add or delete paths to the specific folders.

- (Optional) Check **Scan removable drives** to allow scanning files in removable drives
 - (Optional) Check **Scan compressed files** and select the **Maximum compression layers** between 1 and 20 for the compressed files.
 - (Optional) To skip files over a certain size, check **Skip files larger than** and specify the file size between 1 and 2048 MB. Files exceeding the specified file size will not be scanned.
 - (Optional and Stellar Agent (Windows) only) Check **Aggressive scan (include all OT applications and CA files)** to allow scanning files in existing trusted list.
 - (Optional, Stellar Agent (Linux) only) To skip network drive scan, check **To Skip network drives, such as NFS, SMB**. CIFS from 1.0 to 3.1.1 and NFS from 3.0 to 4.2 are supported.
- b. The **CPU Usage** settings allow you to select the appropriate mode of CPU usage to balance between the scan and the available CPU resources depending on situations. There are two options available:
 - Click **Normal** to reduce the impact on the service performance, which allows you to perform other tasks while scanning but the scan may take longer to complete.
 - Click **High** to reduce scan time, which requires higher CPU usage and may affect the system performance.

- c. In the **Scan Actions** section, for Stellar Agent, you can pre-define the action to take after threats are detected. For both On-Demand Scan and Predictive Machine Learning Analysis, you can select **Quarantine** to place the suspicious or infected files detected in an isolated folder for further checking. Select **No action - Only Log Events** to produce only a readout of results with no actions taken on the suspicious files.
- d. (Optional) The **Scan Exclusions** section allows you to exclude certain folders, files, or file extensions from being scanned.

- **File Extension:** Specify the file extension of certain files that do not require scanning.

**Note:**

- Stellar Agent (Windows) supports only local paths for Scan Exclusions. Remote paths such as an URL or \\[Host name] are not supported.
- It is not required to add "." or "*" in front of the file extension.

-
- **File hash (SHA-256):** Specify the hash value of a file that does not require scanning.
 - **File path:** Specify the path to a file that does not require scanning.
 - **Folder and subfolder:** Specify the path to a folder that does not require scanning.
 - **Threat name:** Specify the name of a threat that does not require scanning.
 - **Regular expression:** Specify a regular expression that does not require scanning. When **Regular expression** is selected, further specify the **Path** or **Threat Name** in the next drop-down list.
-

- e.  **Tip:**

Click the "+" or "-" icon to add or delete paths to the specific folders/files or file extensions for specific file types .

9. Click **Confirm** to deploy the settings to the selected endpoints.
10. The **Command Deployment** window appears showing the deployment status. Click **Close** to close the window.

Configure Isolation Mode (Stellar Agent (Windows) Only)

To limit certain endpoints from accessing the available network, you can enable Isolation Mode. During the isolation period, the endpoints will be blocked from incoming and outgoing network connections, with the exception of connecting to StellarOne the management server.

You can restore the network connection by disabling Isolation Mode.

**Important:**



It is suggested to identify and take the preventive measures to avoid possible impact on operation or security risk before enabling Isolation Mode.

Procedure

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Protection** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Configure Isolation Mode** option.
6. Click **Confirm**.
7. The configuration window appears. Please read the notice carefully before you select **Enable** or **Disable**.
 - Click **Enable** to start the Isolation Mode. This will block the selected endpoints from accessing the available network.
 - Click **Disable** to end the Isolation Mode. This will permit the selected endpoints to restore the available network connection.
8. Check **I understand the potential impact associated with enabling or disabling the Isolation Mode**, and then click **Confirm** to deploy the settings to the selected agents or groups.
9. The **Command Deployment** window will appear showing the deployment status. Click the **Close** button to close the window.
10. After you enable Isolation Mode for certain agents, you can go to the Agents screen and check their Protection column. A  icon will appear, indicating the selected agents/groups are in Isolation Mode.

Configure Emergency Stop Mode

Emergency Stop allows admins/operators to remotely stop or resume all protection features on agents (Stellar Agent (Windows) and Stellar Agent (Windows-Legacy)) when an emergency impacts operations — e.g., compatibility or performance issues — without needing to uninstall the agent. Follow the below steps to configure Emergency Stop Mode.

1. Click the **Agents** tab in the top navigation bar.
2. Click the **All** group on the Agents screen to display the list of managed endpoints.
3. **Select one or more endpoints** (agents or groups) by clicking the checkboxes next to them.
4. Click the **Protection** button from the toolbar at the top of the Agents screen.
5. Select **Configure Emergency Stop Mode** from the drop-down menu.
6. In the pop-up window, select **Activate Emergency Stop Mode** or **Exit Emergency Stop Mode**.
7. **Enter a comment** in the comment field, this step is not optional.
8. **Confirm** the action.
9. A **Command Deployment** window will appear showing the status of the command being sent to the selected agents. You can close this window at any time.

Update

This section introduces how to implement immediate update for the agents via StellarOne web console.

Topics in this section include:

- [Update Agent Components \(on page 75\)](#)
- [Deploy Agent Patches \(on page 75\)](#)
- [Check Connections \(on page 76\)](#)
- [Apply Policies \(on page 77\)](#)
- [Collect Event Logs \(on page 77\)](#)



Note:

Only Stellar Agent (Windows-Legacy) supports the Collect Event Logs feature.

Update Agent Components

You can update agent components on selected endpoints via StellarOne web console. TXOne Networks recommends updating agent components regularly to protect the endpoints against the latest security threats.

1. Click the **Agents** tab in the top navigation bar of the StellarOne web console.
 2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
 3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
 4. Click the **Update** button from the Tool Bar at the top of the **Agents** screen.
 5. A pop-up window appears. Click **Update Agent Components** option.
 6. Click **Confirm**.
 7. The **Update Agent Components** window appears. Click **OK** to start the update.
-



Important:

Do not restart or turn off the endpoints during the update. The update process may take some time to complete.


8. The **Command Deployment** window appears showing the update status. Click the **Close** button to close the window.

Deploy Agent Patches

You can deploy patch files for agents on selected endpoints via StellarOne web console. TXOne Networks recommends updating agent patches regularly to protect the endpoints against the latest security threats.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Update** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Deploy Agent Patches** option.
6. Click **Confirm**.
7. A pop-up **Deploy Agent Patches** window with the patch list appears. Select the version of the patch for deployment and click the checkbox next to it.

Figure 3. Select the Patch Version



Deploy Agent Patches (1) X

Apply the following patch:

File Name	Version
☐ 2.0.1133-txone_sp_full_patch_win_en.zip	2.0.0.1133

You can import new patches for the agent on the [Update](#) page.

OK Cancel

**Note:**

By clicking the **Update** link, you will be directed to the [Downloads/Updates \(on page 211\)](#) page for importing new patches for agents.

8. Click **OK** to start the patch deployment process for the agents. Click the **Close** button to close the window.

Check Connections

You can check the connection status of the selected agents.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Update** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Check Connections** option.
6. Click **Confirm**.

7. A pop-up **Command Deployment** window with the endpoint list appears. The **Status** column shows if the agents are successfully connected to the StellarOne server.

**Note:**

If the status shows **Unsuccessful**, check the network connectivity of the disconnected agents.

8. Click **Close** to close the window.

Apply Policies

You can manually apply policy updates to the selected endpoints.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Update** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Apply Policies** option.
6. Click **Confirm**.
7. A pop-up **Command Deployment** window with the endpoint list appears. The **Status** column shows if the StellarOne policies are successfully applied to the target agents.

**Note:**

- If the status shows **Unsuccessful**, check the network connectivity of the disconnected agents.
- By default, agents automatically synchronize with StellarOne policies every 20 minutes. If you want to adjust the policy sync interval, see [Set Policy Refresh Interval \(on page 87\)](#) for specifying how often the StellarOne policy is applied to selected agent/group.

8. Click **Close** to close the window.

Collect Event Logs

Logs contain information about agent activity. **Collect Event Logs** updates the StellarOne database with the latest information from the selected agents.

**Note:**

Only Stellar Agent (Windows-Legacy) supports this function.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select the target agents by clicking the checkboxes next to them.
4. Click the **Update** button from the Tool Bar at the top of the **Agents** screen.

5. A pop-up window appears. Click the **Collect Event Logs** option.
 6. Click **Confirm**.
 7. A pop-up **Command Deployment** window with the endpoint list appears. The **Status** column shows if the event logs are successfully collected.
 8. Click **Close** to close the window.
-



Note:

StellarOne will update the date and time displayed in the **Last Connection** column on the **Agents** screen after each Stellar Agent (Windows-Legacy) agent successfully sends logs and status to StellarOne.

9. Go to **Logs > Agent Events** for viewing the collected event logs of the selected agents. Refer to [Agent Events \(on page 180\)](#) for more detailed instructions if needed.
-



Note:

By default, the selected agents will only send back the **Warning** and **Critical** level logs.

10. (Optional) Choose one of the ways to add the **Information** level logs in the collected event logs.
-



Note:

The log volume may surge if the **Information** level logs are included in the collected event logs.

- On the StellarOne console, export the agent's configuration file and change the value of `InformationLog Enable` to `yes`. Import the modified configuration file to the selected agent. Refer to [Export Agent Configurations \(on page 82\)](#) and [Import Agent Configurations \(on page 80\)](#) for more detailed instructions.

Figure 4. Snippet of the Configuration File

```
<Log>
  <EventLog Enable="yes">
    <Level>
      <WarningLog Enable="yes"/>
      <InformationLog Enable="yes"/>
    </Level>
  </EventLog>
</Log>
```

- On the target Stellar Agent (Windows-Legacy) agent, open the `StellarSetup.ini` file in the installer package and change the value of `Level_InformationLog` to 1. Be sure to save the changed file and run the installation again.

Figure 5. Snippet of the StellarSetup.ini File

```
[legacy_EventLog]
Enable = 1
Level_WarningLog = 1
Level_InformationLog = 1
```

**Note:**

Only after you change the event log setting for the target agents and apply the **Collect Event Logs** action to them, will the **Information** level logs be sent to StellarOne.

Agent Export/Import Settings

This section introduces how to apply the import/export actions to the agents via StellarOne web console.

Topics in this section include:

- [Export Agent Settings \(on page 82\)](#)
- [Import Agent Settings \(on page 80\)](#)
- [Export Selected Agents Info \(on page 82\)](#)
- [Export all Agents Info \(on page 83\)](#)

**Note:**



- Except for exporting Approved List, Stellar Agent (Windows) does not support the export or import of other agent settings.
- The export of agent settings are only available for individual agents. When you select any group from the list, the functions are unavailable.

Import Agent Settings

You can remotely apply new agent settings to the selected agents from the StellarOne web console. This feature allows you to:

- Remotely overwrite the agent configuration
- Remotely overwrite the Approved List

Remember to prepare a customized agent configuration or Approved List file first before you start the import:

1. Export and download an agent configuration file or the Approved List.
2. Customize the downloaded file.



Note:

To ensure a successful import, verify that the file to import meets the following requirements:

- The Approved List file must be in the CSV format with UTF-8 encoding and file size ideally less than **120 MB**.
- The agent configuration file must be in the XML format with the file size ideally less than **1 MB**.

Import Agent Configurations

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select the target agents by clicking the checkboxes next to them.
4. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
5. Click the **Import Agent Configurations** option.
6. Click **Confirm**.
7. A pop-up **Import Agent Configurations** window appears. Click **Select File**.
8. Select the file to import and click **OK**.
9. A pop-up **Command Deployment** window appears. The **Status** shows if the agent configurations are imported to the target endpoints successfully.
10. Click **Close** to close the window.

Import Approved List

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select the target agents by clicking the checkboxes next to them.
4. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
5. Click the **Import Approved List** option.
6. Click **Confirm**.
7. A pop-up **Import Approved List** window appears. Click **Select File**.
8. Select the file to import and click **OK**.



Note:

The switch toggle, **Replace the trusted hash value of existing applications with that in the imported Approved List.**, is used for overwriting the existing trusted hash values in the original Approved List. By default, the toggle is switched off.

9. A pop-up **Command Deployment** window appears. The **Status** shows if the new Approved List is imported to the target endpoints successfully.
10. Click **Close** to close the window.

Import Trusted Program List

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select the target agents by clicking the checkboxes next to them.
4. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
5. Click the **Import Trusted Program List** option.
6. Click **Confirm**. A pop-up **Import Trusted Program List** window appears.



Note:

- Download the template from the **Example** URL to make sure you have specified the trusted programs with the correct input value and file format. After downloading, edit and then save the file in your local drive.
- The trusted program list supports up to 1000 entries.

7. To import the list, click **Select File**.
8. Select the file to import and click **OK**.
9. A pop-up **Command Deployment** window appears. The **Status** shows if the new Trusted Program List is imported to the target endpoints successfully.



Note:

If a list is successfully imported, the entries will replace the existing ones. The process is irreversible.

10. Click **Close** to close the window.

Export Agent Settings

You can remotely obtain the Stellar Agent (Windows-Legacy) agent configuration settings or the Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) Approved List by exporting and downloading them from the StellarOne console.

Export Agent Configurations

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select the target agent by clicking the checkbox next to it.
4. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
5. Click the **Export Agent Configurations** option.
6. Click **Confirm**.
7. A pop-up **Command Deployment** window appears. The **Status** shows if the agent configuration is exported successfully.
8. Click the **Download** link to download the target agent's configuration file.

Export Approved List

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select the target agent by clicking the checkbox next to it.
4. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
5. Click the **Export Approved List** option.
6. Click **Confirm**.
7. A pop-up **Command Deployment** window appears. The **Status** shows if the agent's Approved List is exported successfully.
8. Click the **Download** link to download the target agent's Approved List.

Export Trusted Program List

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select the target agent by clicking the checkbox next to it.
4. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
5. Click the **Export Trusted Program List** option.
6. Click **Confirm**.
7. A pop-up **Command Deployment** window appears. The **Status** shows if the agent's Trusted Program List is exported successfully.
8. Click the **Download** link to download the target agent's Trusted Program List.

Export Selected Agents Info

This function allows you to export selected agents' information about endpoint description, IP address, license status, policy settings, etc.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select one or more endpoints (agents or groups) by clicking the checkboxes next to them.
4. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
5. A pop-up window appears. Click the **Export Selected Agents Info** option.
6. Click **Confirm**.
7. A .csv file is downloaded.

Export all Agents Info

This function allows you to export all agents' information about endpoint description, IP address, license status, policy settings, etc.

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
4. A pop-up window appears. Click the **Export all Agents Info** option.
5. Click **Confirm**.
6. A .csv file is downloaded.

Chapter 5. Policy Configuration

This chapter introduces how to configure Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) policy settings at the agent and/or group level via StellarOne web console.

Topics in this chapter include:

- [Settings for the Agent/Group Policy Screen \(on page 86\)](#)
- [Agent View and Policy Settings \(on page 105\)](#)
- [Group Policy Settings \(on page 175\)](#)
- [Global Policy \(on page 178\)](#)

Settings for the Agent/Group Policy Screen

Table 20. Options Available on the Agent/Group Policy Screen

Options	Agent	Group
Agent Type	N/A	The tab allows you to switch between Stellar Agent (Windows) , Stellar Agent (Windows-Legacy) , and Stellar Agent (Linux) .
Policy Inheritance	The toggle allows you to enable or disable the policy inheritance from the parent group. • If this toggle is on, policy settings for the agents/groups are inherited from the parent group. The Inherited status will be displayed in the Policy column on the Agents screen. • If this toggle is off, the StellarOne administrators can create a custom policy based on current policy settings. The Customized status will be displayed in the Policy column on the Agents screen.	
Custom Exceptions	N/A	At the group level, after enabling Policy Inheritance , the Custom Exceptions option will appear, which is used to create custom exceptions to the inherited policy. See Create Custom Exceptions to the Inherited Policy (on page 177) for more details.
Self-management	The toggle allows you to enable or disable the agent's self-management. When the toggle is on, the agent will be set free from StellarOne console's policy management and the on-site operators can configure the agent's policy settings on their own.	
Tab pages	You can switch among the pages related to the General Info , Policy page, Baseline , and Situational Awareness at the agent level.	Only the Policy page is available at the group level.
Import Exceptions	You can export and import the policy-based exceptions list used for Application Lockdown, (Multi-Method) Threat Prevention, OT Application Safeguard (Stellar Agent (Windows) only), Operations Behavior Anomaly Detection, and Device Control.	

Table 20. Options Available on the Agent/Group Policy Screen (continued)

Options	Agent	Group
Export Exceptions	See Export/Import Exclusions Settings (on page 89) for more information.	
Set this tab as default view	Set a specific tab (e.g. Windows or Windows-Legacy) as the default tab.	
Settings	• Set Policy Refresh Interval: You can specify how often the StellarOne policy, dashboard and Baseline data sync are applied to the agent/group. See Set Policy Refresh Interval (on page 87) for more details. • Agent User Interface Preferences: You can customize the user interface settings, such as the display of pop-up notifications and right-click scan accessibility on the managed endpoints. See Set Agent User Interface Preferences (on page 88) for more information.	

Set Policy Refresh Interval

You can specify how often the StellarOne policy, dashboard and the Baseline data sync are applied to the specific agent.

1. See [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group setting.
2. Find the settings icon in the upper-right corner of the screen.
3. Click the settings icon and the **Set Policy Refresh Interval** window appears.
4. Click the **Refresh Interval** menu and select among the given options:
 - **5 Minutes**
 - **10 Minutes**
 - **20 Minutes** (default setting)
 - **60 Minutes**



Important:

Frequent refresh might interfere with your work and increase network traffic. See the following table as the recommended policy refresh interval regarding the number of agents managed:

Policy Refresh Interval	No. of Agents Managed
5 minutes	5,000
10 minutes	10,000
20 minutes	20,000
60 minutes	60,000

5. Click **Save** to complete the setting.

Set Agent User Interface Preferences

You can customize the user interface settings, such as the display of pop-up notifications and right-click scan accessibility on the managed endpoints via StellarOne at the agent or group level.

1. See [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group setting.
2. Find the settings icon in the upper-right corner of the screen.
3. Click the settings icon and the **Agent User Interface Preferences** window appears.
4. Four preference settings are available:
 - **Display a pop-up notification for a detected threat:** If enabled, a pop-up window will appear on the local console whenever malware is detected. More details about the threat and the infected file will be provided to the local user for further investigation.
 - **Display a pop-up notification for a blocked USB device:** If enabled, a pop-up window will appear on the local console whenever a blocked USB device is detected. The local administrator can grant one-time access to the blocked USB device via the pop-up notification.
 - **Display a pop-up notification for blocked processes and applications:** If enabled, a pop-up window will appear on the local console whenever a blocked process or application is detected.



Note:

The blocking occurs when USB device control has been enabled. See [Device Control \(on page 155\)](#) for more details.

- **Add the scan with TXOne Stellar option to the Windows context menu:** If enabled, a scan option will be added to the right-click context menu. Agent users can run a right-click scan for the selected file, folder, or drive.
5. Click **Save** to complete the setting.

Export/Import Exclusions Settings

Exporting and importing exclusions settings allow you to move the associated settings listed below from one group to another:

- **Application Lockdown**

- Excluded Paths
- Trusted Hash Values
- Write Protection Rules (Stellar Agent (Windows-Legacy) only)

- **(Multi-Method) Threat Prevention**

- Real-Time Scan Exclusions
- Scheduled Scan Exclusions

- **OT Application Safeguard** (Stellar Agent (Windows) only)

- Files / Folders
- Authorized Process

- **Operations Behavior Anomaly Detection**

- Policy-based Watchlist
- Policy-based Approved Login Accounts
- Policy-based Approved Applications
- Policy-based Approved Network Access (Stellar Agent (Windows) only)

- **Device Control**

- Trusted USB Device

It is recommended to refer to the [Agent Policy Settings \(on page 108\)](#) to configure the associated exclusions settings first, and then export the exclusions file from the agent/group as an template to modify (if needed) and import it to a batch of target agents/groups.

Export Exclusions

You can remotely obtain the policy-based exclusions list of a single agent or group of agents by exporting and downloading it from StellarOne.

1. Navigate to the target agent or group, and then go to its **Policy** page. For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.
2. Click the **Policy** tab and a downward arrow appears.
3. Click the arrow and a drop-down menu appears.
4. Select **Export Exclusions**.
5. Find the exported exclusions list in your downloads folder.

**Note:**

The exported exclusions list is editable depending on your needs. See [Exclusions Configuration File \(on page 90\)](#) for the complete exclusions configuration file and associated parameters as a reference to modify the exclusions list.

Exclusions Configuration File

The exclusions configuration file uses the XML format to specify parameters used by Stellar Agent (Windows) and Stellar Agent (Windows-Legacy).

**Important:**

Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) only supports exclusions configuration files in the UTF-8 file format.

Exclusions Configuration File Parameters

The configuration file contains sections that specify parameters used by Stellar Agent (Windows), and the Stellar Agent (Windows-Legacy) agent.

The `Product` parameter defines the configuration file is used by Stellar Agent (Windows) or Stellar Agent (Windows-Legacy).

Table 21. Configuration File Sections and Descriptions

Section	Description	Additional Information
Configuration	Container for the Configuration section	
Feature	Container for the Feature section	
ApplicationLockDown	Parameters to configure the agent features and functions	Application Lockdown Section (on page 91)
RealTimeScan		Real-Time Scan and Scheduled Scan Section (on page 96)
ScheduleScan		

Table 21. Configuration File Sections and Descriptions (continued)

Section	Description	Additional Information
Obad		Operations Behavior Anomaly Detection Section (<i>on page 99</i>)
DeviceControl		Device Control Section (<i>on page 102</i>)
Safeguard		OT Application Safeguard Section for Stellar Agent (Windows) (<i>on page 102</i>)
		 Note: Only Stellar Agent (Windows) supports this function.

Application Lockdown Section

The following table lists the parameters to configure Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) Application Lockdown exclusions.

Table 22. Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) Application Lockdown Section Parameters

Parameter	Settings	Value	Description
ApplicationLockDown: Container for Application Lockdown			
ExceptionPath: Container for the exception path			
ExceptionPathList: Container for the exceptions list			
ExceptionPath	Type	regex	Use the regular expression to specify the file that will be excluded from Application Lockdown monitoring
		file	Use the file path to specify the file that will be excluded from Application Lockdown monitoring

Table 22. Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) Application Lockdown Section Parameters (continued)

Parameter	Settings	Value	Description
		folder	Use the folder path to specify the files within the folder that will be excluded from Application Lockdown monitoring
		folderandsub	Use the folder path to specify the files within the folder and its subfolders that will be excluded from Application Lockdown monitoring
	Path	<exception_path>	Files specified by using regular expressions or file/folder paths are treated as lockdown exclusions
TrustedHash: Container for the trusted hash list			
PredefinedTrustedHash	HashType	sha1	The Hash field contains a SHA1 value. <i>Stellar Agent (Windows-Legacy) only.</i>
		sha256	The Hash field contains a SHA-2 value. <i>Stellar Agent only.</i>
	Type	updater	File matched by this hash value is treated as a Trusted Update. <i>Stellar Agent (Windows-Legacy) only.</i>

Table 22. Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) Application Lockdown Section Parameters (continued)

Parameter	Settings	Value	Description
		lockdown	File matched by this hash value is not treated as a Trusted Update.
	Hash	<SHA-2_hash_value>	Hash value of this file
		<SHA-1_hash_value>	
	Note	<note>	Add a note for the file matched by this hash value
WriteProtection: Container for the Write Protection section. <i>Stellar Agent (Windows-Legacy) only.</i>			
Exceptionlist	Type	File	Use the file path to specify the file that can be written by all processes or specific process
		Folder	Use the folder path to specify the files within the folder that can be written by all processes or specific process
		FolderAndSubFolder	Use the folder path to specify the files within the folder and its subfolders that can be written by all processes or specific process
		RegKey	Use the registry key to specify the files within the folder that can be written by all processes or specific process

Table 22. Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) Application Lockdown Section Parameters (continued)

Parameter	Settings	Value	Description
			The registry key can be abbreviated or expanded as shown below: • HKLM (HKEY_LOCAL_MACHINE)\test • HKCC (HKEY_CURRENT_CONFIG)\test • HKCR (HKEY_CLASSES_ROOT)\test • HKCU (HKEY_CURRENT_USER)\test • HKU (HKEY_USERS)\test
		RegKeyAndSubKey	Use the registry key and its subkeys to specify the files within the folder and its subfolders that can be written by all processes or specific process
		RegVa lue	Use the registry value to specify the files that can be written by all processes or specific process

Table 22. Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) Application Lockdown Section Parameters (continued)

Parameter	Settings	Value	Description
	Path	<exception_path>	Use the corresponding path type to specify Write Protection exclusions
	Process	<process_path>	Use the process path to specify specific process that can write the specified file
List: Container for the Write Protection List			
List	Type	File	Use the file path to specify the file
		Folder	Use the folder path to specify the file
		FolderAndSubFolder	Use the folder path to specify the files within the folder and its subfolders
		RegKey	Use the registry key to specify the files within the folder
		RegKeyAndSubKey	Use the registry key and its subkeys to specify the files within the folder and its subfolders
		RegVaLue	Use the registry value to specify the file

Table 22. Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) Application Lockdown Section Parameters (continued)

Parameter	Settings	Value	Description
	Path	<path>	Use the corresponding path type to specify Write Protection list
	Process	""	

Real-Time Scan and Scheduled Scan Section

The following table lists the parameters to configure Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) Real-Time Scan exclusions.

Table 23. Real-Time Scan and Scheduled Scan Section Parameters

Parameter	Settings	Value	Description
RealTimeScan: Container for the Real-Time Scan			
ExceptionPathList: Container for the Real-Time Scan path exceptions list			
ExceptionPath	Type	folder	Use the folder path to specify the files within the folder that will be excluded from Real-Time Scan monitoring
		file	Use the file path to specify the file that will be excluded from Real-Time Scan monitoring
		extension	Use the file extension to specify the file that will be excluded from Real-Time Scan monitoring

Table 23. Real-Time Scan and Scheduled Scan Section Parameters (continued)

Parameter	Settings	Value	Description
		regexp	Use the regular expression to specify the threat name that will be excluded from Real-Time Scan monitoring
	Path	<exception_path>	Files specified by using file extensions or file/folder paths are treated as real-time scan exclusions
ExceptionHashList: Container for the Real-Time Scan hash exceptions list			
ExceptionHash	Type	sha256	Use the file sha256 value to specify the file that will be excluded from Real-Time Scan monitoring
	Hash	<exception_hash>	Specify by using the hash value that are treated as real-time scan exclusions
ExceptionThreatList: Container for the Real-Time Scan threat exceptions list			
ExceptionThreat	Type	threat	Use the threat name to specify the threat that will be excluded from Real-Time Scan monitoring
		regexp	Use the regular expression to specify the threat name that will be excluded from Real-Time Scan monitoring

Table 23. Real-Time Scan and Scheduled Scan Section Parameters (continued)

Parameter	Settings	Value	Description
	Threat	<exception__threat>	Specify by using the threat name that are treated as real-time scan exclusions
ScheduleScan: Container for the Scheduled Scan			
ExceptionPathList: Container for the Scheduled Scan path exceptions list			
ExceptionPath	Type	folder	Use the folder path to specify the files within the folder that will be excluded from Scheduled Scan monitoring
		file	Use the file path to specify the file that will be excluded from Scheduled Scan monitoring
		extension	Use the file extension to specify the file that will be excluded from Scheduled Scan monitoring
		regexp	Use the regular expression to specify the threat name that will be excluded from Scheduled Scan monitoring
	Path	<exception_path>	Files specified by using file extensions or file/folder paths are treated as Scheduled scan exclusions
ExceptionHashList: Container for the Real-Time Scan hash exceptions list			

Table 23. Real-Time Scan and Scheduled Scan Section Parameters (continued)

Parameter	Settings	Value	Description
ExceptionHash	Type	sha256	Use the file sha256 value to specify the file that will be excluded from Scheduled Scan monitoring
	Hash	<exception_hash>	Specify by using the hash value that are treated as Scheduled scan exclusions
ExceptionThreatList: Container for the Real-Time Scan threat exceptions list			
ExceptionThreat	Type	threat	Use the threat name to specify the threat that will be excluded from Scheduled Scan monitoring
		regexp	Use the regular expression to specify the threat name that will be excluded from Scheduled Scan monitoring
	Threat	<exception__threat>	Specify by using the threat name that are treated as Scheduled scan exclusions

Operations Behavior Anomaly Detection Section

The following table lists the parameters to configure Stellar Agent (Windows) or Stellar Agent (Windows-Legacy) Operations Behavior Anomaly Detection exclusions.

Table 24. Operations Behavior Anomaly Detection Section Parameters

Parameter	Settings	Value	Description
obad: Container for the Operations Behavior Anomaly Detection exceptions list			

Table 24. Operations Behavior Anomaly Detection Section Parameters (continued)

Parameter	Settings	Value	Description
Script: Container for the Script behavior in Operations Behavior Anomaly Detection			
WatchList: Container for the Policy-based Watchlist settings			
MonitoredProcess	(InnerText)	<process_path>	Used to specify commonly-abused applications.  Note: By default, the agent monitors the specific high-risk applications such as Powershell.exe, wscript.exe, cscript.exe, mshta.exe, and psexec.exe.
Account: Container for Account behavior in Operations Behavior Anomaly Detection			
ApprovedList: Container for the Policy-based Approved Login Accounts			
ApprovedAccount	Domain	<domain>	Use to specify the domain from where the user logs in
	User	<user name>	Use to specify the user name of the logged-in user
	IpAddress	<ip address>	Use to specify the IP address from where the user logs in

Table 24. Operations Behavior Anomaly Detection Section Parameters (continued)

Parameter	Settings	Value	Description
	LogonType	<logon_type>	Use to specify the logon type
	CreatedTime	<timestamp>	The timestamp when the exclusion setting is configured
Application: Container for Application behavior in Operations Behavior Anomaly Detection			
WatchList: Container for the Policy-based Approved Applications			
ApprovedApp	Path	<file_path>	Use a file or folder path to specify the application that will be excluded from monitoring
		<folder_path>	
	PathType	folder	Use the folder path to specify the files within the folder that will be excluded from monitoring
		file	Use the file path to specify the file that will be excluded from monitoring
	CreatedTime	<timestamp>	The timestamp when the exclusion setting is configured
Network: Container for the Network Access in Operations Behavior Anomaly Detection			
ApprovedList: Container for the Policy-based Approved Network Access. (<i>Stellar Agent only.</i>)			
ApprovedNetwork	IpAddress	<ip address>	Specifies remote IP address of the connection

Table 24. Operations Behavior Anomaly Detection Section Parameters (continued)

Parameter	Settings	Value	Description
	Direction	<NETWORK_CONNECTION_DIRECTION_direction>	Specifies the direction of this connection: inbound or outbound
	Port	<port number>	Specifies the destination port number of the connection
	Description	<texts>	Provides the descriptions of this connection
	CreatedTime	<timestamp>	The timestamp when the setting is configured

Device Control Section

The following table lists the parameters to configure Stellar Agent (Windows) or Stellar Agent (Windows-Legacy) Device Control exclusions.

Table 25. Device Control Section Parameters

Parameter	Settings	Value	Description
DeviceControl: Container for the Device Control exceptions list			
TrustedUsbDeviceList: Container for trusted USB devices			
TrustedUsbDevice	VendorId	<device vendor ID>	Specify at least one of the device information for USB that will be excluded from monitoring.
	ProductId	<device product ID>	
	SerialNumber	<device serial number>	

OT Application Safeguard Section for Stellar Agent (Windows)

The following table lists the parameters to configure Stellar Agent (Windows) OT Application Safeguard exclusions.

Table 26. OT Application Safeguard Section Parameters

Parameter	Settings	Value	Description
Safeguard: Container for the OT Application Safeguard settings			
Protected: Container for protected files and folders			
Target	Type	folder	Use a file or folder path to specify the file(s) to protect
		file	
	Path	<file_path>	Use the file/folder path to specify the file(s) that will be excluded from monitoring
		<folder_path>	
	OnlyExecutable	true	Only protect the PE files(.exe and .dll) under the selected folder and its subfolder(s).
		(omitted)	All files inside the selected folder will be protected.
Authorized: Container for the OT Application Safeguard exceptions list			
Process	(InnerText)	<process_path>	Used to specify an authorized process that can modify the protected OT applications.  Important: By adding the authorized process, you may set other applications to be trusted and change the protected files/folders previously

Table 26. OT Application Safeguard Section Parameters (continued)

Parameter	Settings	Value	Description
			 defined as well as the PE files for OT applications detected by agents.

Import Exclusions

You can remotely apply new exclusions list to the selected agents from StellarOne. This feature allows you to remotely overwrite the exclusions list of the target agents/group.

Remember to prepare an exclusions list before you start the import:

1. Export and download an exclusions list.
2. Customize the downloaded file if needed.
1. Navigate to the target agent or group, and then go to its **Policy** page. For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.
2. Mouse over the **Policy** tab and a downward arrow appears.
3. Click the arrow and a drop-down menu appears.
4. Select **Import Exclusions**.
5. A pop-up window appears. Click **Select File**.



Note:

The imported file will overwrite only the customized exclusions. The exclusions inherited from the parent group will not be overwritten.

6. Select the file to import and click **Import**.

7. The **View Import Result** window appears indicating the result of importing the exclusions list. The following table describes the status icons:

Icon	Description
	Successfully overwrote the corresponding exclusions of the target agents/group.
	Failed to overwrite the corresponding exclusions of the target agents/group.
	Unable to overwrite the corresponding exclusions of the target agents/group because they are inherited exclusions, which cannot be overwritten.

Agent View and Policy Settings

The agent view provides four tab pages at the agent level, including:

- **General Info:** Displays the system information, scan components, applied policy settings (Windows-Legacy only), and installed path/hotfix (Windows-Legacy only).
- **Policy:** Provides the configuration page for policy settings. See [Agent Policy Settings \(on page 108\)](#) for more details.
- **Baseline:** Displays the agent baseline established during the learning period set from the **Operations Behavior Anomaly Detection**. See [Baseline \(on page 160\)](#) for more details.
- **Situational Awareness:** Provides the overview and access to the detailed information to the risks detected against the established baseline. See [Situational Awareness \(on page 172\)](#) for more details.
- **Vulnerabilities:** Provides an overview of vulnerabilities found on the agent, and categorizes them based on critical, high, medium, and low. See [Vulnerabilities \(on page 174\)](#) for more details.


Topics in this chapter include:

- [Go to the Agent View \(on page 105\)](#)
- [Agent Policy Settings \(on page 108\)](#)
- [Baseline \(on page 160\)](#)
- [Situational Awareness \(on page 172\)](#)
- [Vulnerabilities \(on page 174\)](#)

Go to the Agent View

Go to a specific agent view to check the agent details or configure the agent policy settings.

Follow the instructions below to go to the agent view.




1. Click the **Agents** tab in the top navigation bar of the StellarOne web console.
2. Click the **All** group, and then a screen displays the second level of groups/agents managed by StellarOne.
3. Navigate to the target agent.
 - To view the agent policy settings, click the link (**Inherited**, **Customized**, or **Self-managed**) in the **Policy Inheritance** column. The **Policy** tab page appears.
 - To view the agent information, click the **Policy** icon in the **Actions** column. The **General Info** tab page appears.
4. You can switch between the **General Info**, **Policy**, **Baseline**, or **Situational Awareness** tab pages as needed.
5. See [Settings for the Agent/Group Policy Screen \(on page 86\)](#) for more information.


Finding the Target Agent

You can use the filter tool provided on the **Agents** screen to list all the **Active Agents**, and then do an advanced search to quickly find the target agent for checking its details or policy configuration.

1. On the **Agents** screen, click the  icon and select the **Active Agents**.




2. The screen displays all the active agents.




3. Click the filter dialog box for an advanced search. You'll need to type directly in the search box or choose from the filter menu depending on the selected filter option.
4. See below as an example of how to find a specific agent in the specified group.

- a. Select **Group** from the filter menu.




- b. Click the filter menu and a **Select a group** window appears.




- c. Click the radio button next to the target group or type the group name in the **Group Name** text field.

- d. Click **Confirm**.
- e. Click the search icon.



- f. The screen displays the target agent. Click the link in the **Policy** column or  icon in the **Actions** column for checking the agent details or policy configuration.



Agent Policy Settings

This section introduces the configuration page for policy settings at the agent level.

Topics in this section include:

- [Operations Behavior Anomaly Detection \(on page 108\)](#)
- [Other Key Features for Stellar Agent \(Windows\) \(on page 126\)](#)
- [Other Key Features for Stellar Agent \(Windows-Legacy\) \(on page 140\)](#)
- [Common Policy Settings for Stellar Agent \(Windows\)/Stellar Agent \(Windows-Legacy\) \(on page 152\)](#)

Operations Behavior Anomaly Detection

The **Operations Behavior Anomaly Detection** strengthens security resilience and operation stability by leveraging Cyber-Physical System Detection and Response (CPSDR). It collects behavioral patterns in the OT environment and identifies any unexpected changes or abnormal behaviors that could impact the operation.

This feature primarily defends against unexpected changes that may impact operational stability by comparing daily operation processes and behaviors with a unique baseline of each agent-device and performing comprehensive behavioral analysis not only via identifying baseline deviation but also using TXOne Networks's exclusive industrial application repository and ransomware detection engine.

Navigate to the target agent or group, and then go to its **Policy** page. For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

Scroll down and find the **Operations Behavior Anomaly Detection** pane.

Figure 6. Operations Behavior Anomaly Detection

Operations Behavior Anomaly Detection ⓘ

☐ **Learn:** Establish the Baseline to enable behavioral analysis in Detect and Enforce modes.

☐ **Detect:** Log events when abnormal activities are detected.

☒ **Enforce:** Log events when abnormal activities are detected, and automatically block unexpected **Script Behavior** changes. To block activities against **Application Behavior** and **Network Access** the agent's Suspicious Objects Blocklist and Network Access Blocklist must be created first.

☐ **Strict mode:** Less tolerance for deviation between running behaviors and the Baseline. This may generate more events.

☐ **Disable**

[> Learn more](#)

⚠ All agent-devices must start with the "Learn" mode to establish their own baseline fingerprints before entering the "Detect" or "Enforce" mode. The agents (e.g. newly-added agents) will learn first and then automatically switch to the specified mode according to the policy.

Learning time

▼

 Script Behavior

☒

Protect the endpoints against script-based or fileless attacks.

▼

 User Login

☒

Defend the endpoints against credential-based attacks.

▼

 Application Behavior

☒

Keep the endpoints secure against malicious application attacks.

▼

 Network Access

☒

Monitor network access for the managed endpoints.

The **Operations Behavior Anomaly Detection** provides four normal modes for four pillars of protection. In addition, there is a special mode under two of the normal modes. See the details below for more information.

Four Normal Modes:

- **Learn:** In this mode, the agents collect behavioral patterns from the monitored devices to establish baseline fingerprints.



Important:

TXOne Networks recommends setting the target agents to the **Learn mode** first to establish their own baseline fingerprints before they can perform automated behavioral analysis in the **Detect** or **Enforce** mode. See [Use Case \(on page 119\)](#) for more details.

- **Detect:** In this mode, the agents identify and send alerts for any unexpected changes or security threats by analyzing current behaviors against the fingerprint baseline at the agent-device and central management levels.
 - **Strict mode:** This special mode appears when you select the **Detect** mode. Enabling the **Strict mode** reduces the level of the fingerprint baseline deviation permitted; in other words, it performs stricter comparison between the established baseline and currently-running operational behaviors. In more dynamic operating environments where devices and access behaviors are more subject to change, this may generate more events.
- **Enforce:** In this mode, the agents block unexpected script behavior changes against the fingerprint baseline.



Note: To block activities against Application Behavior and Network Access, the agent's Suspicious Object Blocklist and Network Access Blocklist must be created first.

- **Strict mode:** This special mode appears when you select the **Enforce** mode. Enabling the **Strict mode** reduces the level of the fingerprint baseline deviation allowed; in other words, it performs stricter comparison between the established baseline and currently-running operational behaviors. In more dynamic operating environments where devices and access behaviors are more subject to change, this may generate more events and require more preventative actions to be taken.
- **Disable:** The Operations Behavior Anomaly Detection can also be disabled if needed, but it is recommended to have this function enabled to maintain security against behavior anomalies.

Learning time:

When **Detect** or **Enforce** mode is selected, the **Learning time** option becomes available. You can specify the learning period for the target agents/group from the **Learning time** menu. The agents that have not established their own baselines will then start learning and once the learning period ends, they will automatically switch to the predefined **Detect** or **Enforce** mode.

See [Setting the Learning Time \(on page 115\)](#) and [Setting the Learning Time - Use Case \(on page 116\)](#) for more information.

Four Pillars of Protection:

- **Script Behavior:** Protects the endpoints against script-based fileless attacks when enabled. By comparing the list of script behaviors and monitored process in the baseline with those running for daily operations, unrecognized monitored process or unexpected script behaviors will be detected as anomalies and trigger event notifications or be blocked.
 - **Approved Script Behaviors in Baseline:** Click this link to go to the **Baseline** page for viewing the approved script behaviors and relevant details stored in the baseline at the agent level. See [Approved Applications \(on page 164\)](#) for more information.
 - **Policy-based Watchlist:** Click this link to manually add commonly-abused applications used in operations and processes to the Monitored Application list for strengthening security monitoring. See [Policy-based Watchlist \(on page 117\)](#) for more information.
- **User Login:** Defends the endpoints against credential-based attacks when enabled. By comparing the list of user accounts and login activities in the baseline with those used for daily operations, unrecognized user accounts or unexpected login activities will be detected as anomalies and trigger events.
 - **Approved Login Accounts in Baseline:** Click this link to go to the **Baseline** page for viewing the approved user accounts and relevant details stored in the baseline at the agent level. See [Approved Login Accounts \(on page 163\)](#) for more information
 - **Policy-based Approved Login Accounts:** Click this link to manually add approved user accounts and relevant details used in operations and processes to avoid false alerts. See [Policy-based Approved Login Accounts \(on page 117\)](#) for more information.
- **Application Behavior:** Safeguards the endpoints against malicious application attacks. By comparing the list of applications and application behaviors in the baseline with those running for daily operations, unrecognized applications or unexpected application behaviors will be detected as anomalies and trigger incident notifications.
 - Check the box of **Do not log events in Detect and Enforce mode for application with trusted certificates that were manually added** to exclude the applications with manually imported certificates from being scanned and logged.

**Note:**

Refer to [Trusted Certificates Settings \(on page 159\)](#) for more information and instructions on importing the trust certificates for applications.

- **Suspicious Objects Blocklist:** Click this link to view the applications that have been added to the Suspicious Objects Blocklist, which will be blocked from running on the endpoint unless removed from the blocklist.

**Note:**

The **Suspicious Objects Blocklist** appears only when **Operations Behavior Anomaly Detection** is set to **Enforce** mode.

- **Approved Applications in Baseline:** Click this link to go to the **Baseline** page for viewing the approved applications and relevant details stored in the baseline at the agent level. See [Approved Applications \(on page 164\)](#) for more information.
- **Policy-based Approved Applications:** Click this link to manually add approved applications and relevant details used in operations and processes to avoid false alerts. See [Policy-based Approved Applications \(on page 118\)](#) for more information.
- **Network Access:** Prevent the traffic of unauthorized TCP/UDP network from accessing the endpoints. By comparing the Blocklist and the authorized networks, the unauthorized network will be regarded as abnormality, blocked and recorded.
 - **Network Access Blocklist:** Click to view the list of networks that have been blocked from accessing the agents. The traffic of the listed network to the agents will be blocked unless it is removed from the list.



Note: The Network Access Blocklist appears only at the agent level when **Operations Behavior Anomaly Detection** is set to **Enforce** mode, and only applies to the agent where the blocklist is configured.

- **Approved Network Access in Baseline:** Click this line to go to the Baseline page for viewing the approved network access and relevant details stored in the baseline at the agent level. See [Approved Network Access \(on page 166\)](#) for more details.
- **Policy-based Approved Network Access:** Click this link to manually add approved networks and relevant details used in operations and processes to avoid false alerts. See [Policy-based Approved Network Access \(on page 118\)](#) for more details.

The four pillars of protection can be individually toggled on for guarding separate vulnerability points, or you can choose to enable them all and set in the **Strict mode** for maximum defense.

**Note:**

For more details on how the **Strict mode** works for the three pillars, see [Strict Mode \(on page 121\)](#) and [Strict Mode - Use Case \(on page 123\)](#).

The following table illustrates how the four pillars work in the **Learn**, **Detect**, and **Enforce** modes.

Table 27. An example of how Operations Behavior Anomaly Detection works

Operations Behavior Anomaly Detection	Script Behaviors	User Login	Application Behavior	Network Access
Learn	Stores the approved script behavior listed below in the baseline: For example: explorer.exe → cmd.exe → (monitored process or script)	Stores the login account listed below in the baseline: For example: • Username: admin • Domain: TX One	Stores the application behavior listed below in the baseline: For example: • Application: Google Chrome • Behavior: 1	Store the connection/session details listed below in the baseline. For example: • Direction: inbound • Remote IP: 10.1.1.1 • L4 Protocol: TCP • L7 Protocol: HTTPS  Note: Details for learned fields please refer to Approved Network Access (on page 166) for details.
Detect	Sends alerts for the unexpected change: For example: cmd.exe → explorer.exe → (monitored process or script)	Sends alerts for the unexpected change: For example: Username: admin1	Sends alerts for the unexpected changes: For example: Behavior: 2	Send alerts for the unexpected changes in the following fields: For example: • Direction: inbound • Remote IP: 10.1.1.1 • Port: "22" • L4 Protocol: TCP • L7 Protocol: "SSH"  Note: Fields that are not monitored for changes:

Table 27. An example of how Operations Behavior Anomaly Detection works (continued)

Operations Behavior Anomaly Detection	Script Behaviors	User Login	Application Behavior	Network Access
				 Application Name, Application Path, Local IP, Subnet prefix length, MAC address, Gateway IP.
Enforce	- Sends alerts for the unexpected changes - Automatically blocks the unexpected changes For example: cmd.exe → explorer.exe → (monitored process or script)	Sends alerts for the unexpected change: For example: Username: admin1	- Sends alerts for the unexpected changes - Provides the action that allows users to manually add detected applications to the Suspicious Objects Blocklist from the generated events For example: Behavior: 2  Note:	- Send alerts for the unexpected changes in connection details.  Note: The information for the following fields are monitored: Direction, Remote IP, Remote/Local Port, L4 Protocol, L7 Protocol. - Provides the action that allows users to manually add detected connections to the Network Access Blocklist from the generated events.

Table 27. An example of how Operations Behavior Anomaly Detection works (continued)

Operations Behavior Anomaly Detection	Script Behaviors	User Login	Application Behavior	Network Access
			 See Add to Suspicious Objects Blocklist (on page 184) for how to add the applications to the Suspicious Objects Blocklist	

Setting the Learning Time

When the **Detect** or **Enforce** mode of **Operations Behavior Anomaly Detection** is selected, the **Learning time** option becomes available. You can specify the learning period for the target agents/group from the **Learning time** menu. The agents that have not established their own baselines will then start learning and once the learning period ends, they will automatically switch to the predefined **Detect** or **Enforce** mode.

See the following instructions for how to set the learning time.

1. Go to **Agents > Policy**, scroll down and find the **Operations Behavior Anomaly Detection** pane. Select **Detect** or **Enforce**.
2. The **Learning time** section appears.
3. Scroll down and determine which security pillars (**Script Behavior**, **User Login**, **Application Behavior**, or **Network Access**) you want to enable. Ensure you toggle on at least one of them for the agent-device to establish the associated baseline.



Note: The four security pillars can be individually toggled on for guarding separate vulnerability points, or you can choose to enable them all for the complete protection.

4. Specify the learning period for the target agent-device from the **Learning time** menu.

5. A progress bar displaying how many days left for learning will appear on the **Agents** screen or the **General Info** page for the agent-device. See [About the Agents Screen \(on page 50\)](#) for more information.



Note:

- The learning time counts only when the target agent-device is powered on.
- If you toggle on the security pillars separately, though the learning period is specified and fixed, the actual learning time displayed on the progress bar varies depending on when the last pillar is enabled. Besides, the agent switches to the predefined **Detect** or **Enforce** mode for the security pillars separately. See the following use case for more details.

Setting the Learning Time - Use Case

See the example below for how the learning time works if the security pillars are enabled separately.

1. Three days ago, you've enabled the **Detect** mode for **Operations Behavior Anomaly Detection**, toggled on the **Script Behavior**, and set the **Learning time** to 3 days.
2. This morning, you enabled the **User Login** and then the agent started establishing the baseline of the approved login accounts.
3. If you had not enabled the **User Login** today, the learning progress bar displayed on the **Agents** screen should have disappeared and the status should have changed to **Detect**. However, the progress bar still exists because you enabled the **User Login** today (without changing the learning period, which was set to 3 days).
4. For now, the agent is multitasking for the **Operations Behavior Anomaly Detection** function:
 - The **Script Behavior** baseline has been established and the agent is actually detecting any anomalies now. You may refer to the following sections for relevant events: for Stellar Agent, see [Agent Event Log Descriptions for Stellar Agent \(Windows\) \(on page 252\)](#) and for Stellar Agent (Windows-Legacy), see [Agent Event Log Descriptions for Stellar Agent \(Windows-Legacy\) \(on page 283\)](#)
 - The agent is now establishing the **User Login** baseline. The learning progress bar on the **Agents** screen indicates there are 3 days left for learning before entering the **Detect** mode.
5. Moreover, if you changed the learning time to 7 days while enabling the **User Login** today, the agent would start updating the baseline for **Script Behavior**; on the other hand, it would start establishing the baseline for **User Login**. To elaborate, since the agent has already collected the script behaviors for 3 days, the actual learning time for **Script Behavior** was extended to 4 days only. As for the **User Login**, the actual learning time was set to 7 days.

Policy-based Watchlist and Approved Items

You can specify policy-based watchlist for monitoring fileless attacks, or policy-based approved login accounts or applications to avoid false alerts at the agent or group level.

Related settings include:

- [Policy-based Watchlist \(on page 117\)](#)
- [Policy-based Approved Login Accounts \(on page 117\)](#)
- [Policy-based Approved Applications \(on page 118\)](#)
- [Policy-based Approved Network Access \(on page 118\)](#)

Policy-based Watchlist

By default, Stellar agents monitor Powershell.exe, wscript.exe, cscript.exe, mshta.exe, and psexec.exe when the **Operations Behavior Anomaly Detection "Detect" or "Enforce"** mode is enabled with the **Script Behavior** toggled on. In addition to the default monitored applications, you can also manually add commonly-abused applications used in operations and processes to the **Policy-based Watchlist** for strengthening security monitoring.

See the following instructions for how to add applications to the **Policy-based Watchlist**.

1. Go to **Agents > Policy**, scroll down and find the **Operations Behavior Anomaly Detection** pane. Select **Operations Behavior Anomaly Detection Learn, Detect, or Enforce**.
2. Toggle on the **Script Behavior**.
3. Click **Script Behavior** to expand this section.
4. Find and click the **Policy-based Watchlist**.
5. Click **+Add** and then specify the application to be monitored.
6. Click **Add** and the added application appears in the **Monitored Application** list.
7. Click **Close** to close the window.



Tip:

To delete the added application one by one, click the Delete icon in the **Actions** column; to delete multiple applications, click the checkboxes next to them and then click **Delete > Confirm**.

Policy-based Approved Login Accounts

You can manually add approved user accounts and relevant details used in operations and processes into the **Policy-based Approved Login Accounts** to avoid false alerts.

See the following instructions for how to add the approved user accounts to the **Policy-based Approved Login Accounts**.

1. Go to **Agents > Policy**, scroll down and find the **Operations Behavior Anomaly Detection** pane. Select **Operations Behavior Anomaly Detection Learn, Detect, or Enforce**.
2. Toggle on the **User Login**.
3. Click **User Login** to expand this section.
4. Find and click the **Policy-based Approved Login Accounts**.
5. Click **+Add** and then specify the user account and relevant information.

6. Click **Add** to add the approved user account.
7. Click **Close** to close the window.



Tip:

To delete the added user accounts one by one, click the Delete icon in the **Actions** column; to delete multiple user accounts, click the checkboxes next to them and then click **Delete > Confirm**.

Policy-based Approved Applications

You can manually add approved applications used in operations and processes into the **Policy-based Approved Applications** to avoid false alerts.

See the following instructions for how to add the approved applications to the **Policy-based Approved Applications**.

1. Go to **Agents > Policy**, scroll down and find the **Operations Behavior Anomaly Detection** pane. Select **Operations Behavior Anomaly Detection Learn, Detect, or Enforce**.
2. Toggle on the **Application Behavior**.
3. Click **Application Behavior** to expand this section.
4. Find and click the **Policy-based Approved Applications**.
5. Click **+Add** and then specify the path to the application and relevant information.
6. Click **Add** to add the approved application.
7. Click **Close** to close the window.



Tip:

To delete the added applications one by one, click the Delete icon in the **Actions** column; to delete multiple user accounts, click the checkboxes next to them and then click **Delete > Confirm**.

Policy-based Approved Network Access

You can manually add approved network access that is used in operations and processes into the **Policy-based Approved Network Access** to avoid false alerts.

See the following instructions for how to add the approved network access to the **Policy-based Approved Network Access**.

1. Go to **Agents > Policy**, scroll down and find the **Operations Behavior Anomaly Detection** pane. Select **Operations Behavior Anomaly Detection Learn, Detect, or Enforce**.
2. Toggle on the **Network Access**.
3. Click **Network Access** to expand this section.
4. Find and click the **Policy-based Approved Network Access**.
5. Click **+Add** and then specify traffic direction, the IP address, port number, and the associated description in the corresponding text fields.



Tip: IP address and port number can be left empty to match any IP or port.

6. Click **Confirm** to add the approved network access.
 7. Click **Close** to close the window.
-

**Tip:**

To delete the added networks one by one, click the Delete icon in the **Actions** column; to delete multiple network access settings, click the checkboxes next to them and then click **Delete**.

Use Case

The **Operations Behavior Anomaly Detection** embodies the CPSDR concept and has a deep understanding of what the expected behaviors for each device are from learning the behaviors of each agent-device first. Every agent continuously analyzes its host device to establish and maintain a unique baseline fingerprint. Then in real-time, unexpected behaviors and deviations from this fingerprint can be detected at the individual agent level and then secondarily at the centralized control level to inform wider instability issues and prompt preventative actions.

See the following procedures as the recommended practice when you start using the **Operations Behavior Anomaly Detection**:

1. Toggle on the **Learn** mode of the **Operations Behavior Anomaly Detection** on the Policy page. Ensure that you toggle on the **Script Behaviors**, **User Login**, **Application Behavior**, and **Network Access** as well.
 2. Deploy all the required configuration, features, updates, or fixes, and run all the daily operation processes during the **Learn** mode.
-

**Note:**

If the Application Lockdown is enabled, ensure you turn on the maintenance mode when performing these deployments.

- a. Toggle on the **User Login**:

- i. Use the required user accounts to log into the agent-device.
 - ii. Ensure you also log in from different IP addresses or domains if it is required during your daily operation processes.
-

**Note:**

You can also manually add approved user accounts and relevant details used in the operations and processes into the **Policy-based Approved Login Accounts**.

- b. Toggle on the **Application Behaviors**:

- Run the applications required for daily operation processes.
- Download required applications or execute updates or fixes required for existing applications on the agent-device.



Note:

You can also manually add approved applications used in the operations and processes into the **Policy-based Approved Applications**.

c. Toggle on the **Script Behavior**:

- Run the scripts required for your daily operation processes.
- Run the scripts accompanied with parameters.



Note:

By default, Stellar Agent (Windows) monitors the commonly-abused script running applications such as Powershell.exe, wscript.exe, cscript.exe, mshta.exe, and psexec.exe. Ensure you manually add other commonly-abused applications used in your daily operation processes to the **Policy-based Watchlist** for strengthening security monitoring.

d. Toggle on the **Network Access**:

- Connect to various network services that are required for daily operation processes.
- If the endpoint agent hosts network services, connect to the endpoint agent from all other potential endpoints.
- Check for application updates if auto-update is configured and updates introduce network traffic.
- Add rules to Policy-based Approved Network Access for protocols that likely generate false alerts, such as Delivery Optimization, File & Printer Sharing, etc.

3. After all the operation processes have been executed and learned, switch to the **Detect** mode and check if any events will be triggered by the normal daily operations.



Note:

- You can check the Agent event logs to see if there's any anomalous operation or process detected. See [Agent Events \(on page 180\)](#) for more details.
- See [Strict Mode \(on page 121\)](#) and [Strict Mode - Use Case \(on page 123\)](#) for more details on using the **Strict mode**.

4. Switch to the **Enforce** mode for activating preventative actions (Script Behaviors only). If any unexpected script execution occurs, it should be blocked.



Note: If you also enable the **Strict mode**, only the exact script running processes (with exact parameters) that have been learned and stored in the baseline will be allowed. You can check the **Baseline > Script Behaviors** page to make sure the specific full operation processes (parameters included) have been added in the agent baseline.

Strict Mode

The **Strict mode** under the **Detect** or **Enforce** mode is used for stronger threat protection. Enabling **Strict mode** reduces the level of baseline fingerprint deviation allowed; in other words, it performs stricter comparison between the established baseline and currently-running operational behaviors.



Note:

In more dynamic processes where devices and access behaviors are more subject to change, this may generate more events. See [Strict Mode - Use Case \(on page 123\)](#) for information.

To enable **Strict mode**, set the **Operations Behavior Anomaly Detection** to **Detect** or **Enforce** mode, and then toggle on specific pillars of protection for guarding separate vulnerability points or simply enable them all for maximum defense.

See below for more details on how the four pillars work in **Strict mode**.

Script Behaviors: In the **Strict mode**, the operation process and the monitored process or script must exactly match the approved full operation process stored in the baseline; otherwise, events will be generated or the process will be blocked.

See below as an example of how the **Strict mode** works for the **Script Behaviors**.

1. When you select the **Learn** mode under the **Operations Behavior Anomaly Detection**, the following full operation process is learned:
 - explorer.exe → cmd.exe → powershell.exe → script.ps1
2. When you switch to the **Detect** or **Enforce** mode without turning on the **Strict Mode**, Stellar Agent (Windows) will not block recognized program calls with unidentified script; the following process is allowed:

- explorer.exe → cmd.exe → powershell.exe → NEWscript.ps1



Note:

The NEWscript.ps1 does not count as an unrecognized script in the process when the **Strict Mode** is turned off.

3. When the **Strict Mode** is turned on, no matter it's under the **Detect** or **Enforce** mode, the following process is not allowed:

◦ explorer.exe → cmd.exe → powershell.exe → NEWscript.ps1

**Note:**

The NEWscript.ps1 is detected as an unrecognized script that will trigger alerts or be blocked when **Strict Mode** is enabled.

4. In conclusion, when **Strict Mode** is turned on, only the exact process (the process learned in *Step 1*) is allowed:

◦ explorer.exe → cmd.exe → powershell.exe → script.ps1

Table 28. Example: Script Behaviors - Strict Mode ON/OFF

	Script Behaviors			Operations Behavior Anomaly Detection			
	Approved Operation	Monitored Process		Detect	Enforce	Detect	Enforce
		Monitored Application	Script	Strict mode: OFF		Strict mode: ON	
Process learned and stored in the baseline	explorer.exe→cmd.exe→	powershell.exe→	script.ps1	Allowed			
Operation process changed	cmd.exe→explorer.exe→	powershell.exe→	script.ps1	Events	Blocked	Events	Blocked
Monitored application changed	explorer.exe→cmd.exe→	cscript.exe→	script.ps1	Events	Blocked	Events	Blocked
Script changed	explorer.exe→cmd.exe→	powershell.exe→	NEWscript.ps1	Allowed		Events	Blocked

User Login: In the **Strict mode**, the user accounts and the login activities must exactly match the approved user accounts stored in the baseline; otherwise, events will be generated.

Application Behavior: In the **Strict mode**, the application behaviors must exactly match the approved application behaviors stored in the baseline; otherwise, events will be generated.

Network Access: Strict mode is always enabled for the Network Access settings. Network connections must exactly match baseline with the following five configured fields: Direction, Remote IP, Port, L4Protocol, and L7Protocol; otherwise, events will be generated.

See [Strict Mode - Use Case \(on page 123\)](#) for the description of how you can use the **Strict mode** to maximize its effectiveness.

Strict Mode - Use Case

As **Strict mode** performs stricter comparison between the established baseline and currently-running operational behaviors, it does not allow too much deviations from the baseline and thus may be more appropriate to be used for static environments that is intended to remain unchanged by users and administrators. For example, it may be a shared deployment environment with permanent infrastructure, where all the features and fixes are deployed once at the end of a planned release cycle.

Facing the growing prevalence of script-based attacks such as fileless malware or PowerShell abuse, the behavioral pattern identification along with parameter recognition for defending unknown threats adds an extra layer of protection without impacting the operational stability.

To illustrate: the global policy may restrict the use of PowerShell. However, one device uses PowerShell for regular system updates and there is a specific command run to complete the process. The agent for this device can allow PowerShell to be used for this specific process. No individual policy override is needed, and any other use of PowerShell on other devices will still be blocked.

See the following procedures as the recommended practice:

1. Organize the agents in the static environment as a group and set the **Operations Behavior Anomaly Detection "Learn"** mode as one of the group policy settings. Ensure that you toggle on the **Script Behaviors**.
2. Deploy all the required configuration, features, updates, or fixes, and run all the daily operation processes during the learning period.



Note:

If the Application Lockdown is enabled, ensure you turn on the maintenance mode when performing the deployments.

-
3. For the specific agent-device that uses PowerShell as the regular system update tool, check the **Baseline > Approved Script Behaviors** page to make sure the specific full operation process with parameter identification has been included in the agent baseline.

4. After all the operation processes have been executed and learned, switch to the **Detect** mode and check if any events will be triggered by the normal daily operations. When you run the PowerShell command on the specific agent and other agent-devices in the same group; one should treat it as a normal behavior and the other ones should treat it as anomalies and trigger events.



Note:

You can check the Agent event logs to see if there's any anomalous operation or process detected. See [Agent Events \(on page 180\)](#) for more details.

5. Switch to the **Enforce** mode and enable the **Strict mode** for activating preventative actions. For most of the devices, the use of PowerShell should be blocked; for the specific device, only the exact process for running the PowerShell that have been learned and stored in the baseline will be allowed.

Migration/Upgrade from Previous Version - Use Case

For StellarOne migrated or upgraded from versions earlier than 3.0 to version 3.0 or later, see the following use case.



Note:

After you migrate or upgrade StellarOne from versions earlier than 3.0 to version 3.0 or later, please also upgrade the managed agents to the corresponding version. Though StellarOne provides backward compatibility to support agents with earlier versions, new features or enhanced functionalities should not be applicable on some agents with earlier versions.


1. If the original policy setting of the **Operations Behavior Anomaly Detection** was set to the **Detect** or **Enforce** mode, after migrated or upgraded from versions earlier than 3.0 to version 3.0 or later, the StellarOne would retain the previous setting and the **Script Behavior** toggle would be automatically turned on.
 2. After then, if you enable the **User Login**, **Application Behavior**, or **Network Access**, the agent automatically starts learning by collecting the related behavioral and operation patterns performed on the device to establish its baseline fingerprint for **User Login**, **Application Behavior**, or **Network Access**.
-



Note:

The learning of the **User Login**, **Application Behavior**, and **Network Access** does not change the original policy setting of the **Operations Behavior Anomaly Detection**.

3. In the **Operations Behavior Anomaly Detection** pane, find and set the **Learning time**.

**Note:**

- See the [Use Case \(on page 119\)](#) for the recommended practice as you start using the **Operations Behavior Anomaly Detection** and evaluate the proper learning period for the agent-device.
- The learning time counts only when the agent-device is powered on.

4. Go to the **Agents** screen. You can find the the learning progress bar displayed in the **Operations Behavior Anomaly Detection** column for the agent-device. Mouse over the progress bar to check how many days left for learning. See [About the Agents Screen \(on page 50\)](#) for more information.

**Note:**

In addition to the progress bar displayed on the **Agents** screen, you can also check the learning progress on the **General Info** page for the agent-device.

5. After learning, the agent-device will automatically switch to the specified mode according to the original policy settings.

Sizing Table - 2nd Disk Space Requirement

The StellarOne requires an external disk for storing system configurations and event logs. To ensure the storage requirement for the agent baselines is fulfilled, see the following table for the required external disk space depending on the number of the installed agents and for executing the **Operations Behavior Anomaly Detection** feature.

Table 29. Sizing Table - 2nd Disk Space Requirement for Operations Behavior Anomaly Detection

Max. No. of Agents	Min No. of vCores	Memory Size	1st HDD Space	2nd HDD Space (Recommended)*
30,000	10	32 GB	45 GB	520 GB
20,000	8	16 GB		420 GB
15,000	8	16 GB		320 GB
10,000	8	16 GB		220 GB
5,000	8	16 GB		170 GB
1,000	4	16 GB		120 GB
500	4	12 GB		120 GB



Note:

According to the table, If you want to deploy 25,000 agents and run **Operations Behavior Anomaly Detection**, you'll need to prepare a 2nd HDD of at least 520 GB capacity.

Other Key Features for Stellar Agent (Windows)

Other key features provided by Stellar Agent (Windows) agent include:

- [Application Lockdown \(on page 127\)](#)
- [Multi-Method Threat Prevention \(on page 131\)](#)
- [OT Application Safeguard \(on page 137\)](#)
- [DLL Injection Prevention \(on page 138\)](#)
- [Network Access Restrictions \(on page 139\)](#)

See [Common Policy Settings for Stellar Agent \(Windows\)/Stellar Agent \(Windows-Legacy\) \(on page 152\)](#) for how to configure Agent Component Update Schedule, Device Control, User-Defined Suspicious Objects, Agent Password, Agent Patch deployment, and Trusted Certificate Settings for Stellar Agent (Windows) agent.

Application Lockdown

When Application Lockdown is turned on, the agent will only be able to access applications that are in the Approved List.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Go to the **Application Lockdown** pane.
4. Three modes are available for selection:
 - **Detect:** When an application not in the Approved List launches, it is allowed and users will receive a notification.
 - **Enforce:** When an application not in the Approved List launches, it is blocked and users will receive a notification.
 - **Disable:** Application Lockdown is turned off.



Note:

- For how to configure exclusion settings for the Approved List, see [Excluded Paths Settings \(on page 128\)](#) and [Trusted Hash Values Settings \(on page 129\)](#).
- For how to configure trusted hash values settings for the Approved List, see [Trusted Hash Values Settings \(on page 129\)](#).

5. If you enable the "Detect" mode or "Enforce" mode, the sub-features listed below will appear. By default, the sub-features are enabled. Click the toggles to disable them if needed.
 - **DLL/Driver Lockdown:** Prevents unapproved DLLs or drivers from being loaded into the memory of protected endpoints.
 - **Script Lockdown:** Prevents unapproved script files from being run on protected endpoints.
 - **Intelligent Runtime Learning:** Allows runtime executable files that are generated by applications in the Approved List.

Excluded Paths Settings

When **Application Lockdown** is enabled, the Agent will only be able to access applications that are in the Approved List. However, the **Excluded Paths** allows you to configure lockdown exclusion settings for the Approved List.

1. Go to **Agents > All**.
 2. Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Excluded Paths** at the bottom of the **Application Lockdown** pane.
 - For adding exception paths:
 - a. Click the **+Add** button, and then a pop-up window appears.
 - b. Select among **File**, **Folder**, or **Regular Expression** and input the required information in the corresponding text field.
-



Note:

The **Excluded Paths** function supports only the real path and hardlink path.

- c. Click **Add** to complete adding the exception paths for the Approved List.
- For editing existing exception paths:
 - a. Find the exception path to be edited and click the corresponding Edit icon under the **Actions** header.
 - b. A pop-up window appears. Select among **Folder**, **File**, or **Regular Expression** and edit in the corresponding text field.
 - c. Click **Save** to complete editing the exception paths for the Approved List.
- For deleting multiple existing exception paths:
 - a. Click the checkboxes next to the existing exception paths.
 - b. Click the **Delete** button next to the **+Add** button.
 - c. A warning message window appears. Click **Confirm** to delete the selected items.
- For deleting single existing exception path:
 - a. Find the exception path to be deleted and click the corresponding Delete icon in the **Actions** column.
 - b. A warning message window appears. Click **Delete** to delete the selected item.

Trusted Hash Values Settings

When **Application Lockdown** is enabled, the Agent will only be able to access applications that are in the Approved List. However, the **Trusted Hash Values** allows you to configure trusted hash values for the Approved List.

Calculate Hash Values

Use **File Hash Generator** to calculate hash values before adding trusted hash values.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Trusted Hash Values** at the bottom of the **Application Lockdown** pane.
4. The **Trusted Hash Values** windows appears. Find and click **File Hash Generator** to download the tool.
5. Execute WKFileHashGen.exe from the downloaded folder. The **File Hash Generator** screen will appear.
6. Use any of the following methods to select files and calculate hash values:
 - Drag and drop folders or files to the **File Hash Generator** screen.
 - Click the drop-down button and click **Add Files** to select the files to add.
 - Click the drop-down button and click **Add Folder** to add all the files in the selected folder.



Tip:

Only executable, script, and installer files are supported. Mouse over the **Supported file types** for more details.



Note:

Hash values will appear in the SHA-1 and SHA-256 columns.

7. For a single file, right-click the item and select **Copy SHA-1** or **Copy SHA-256**. For multiple files, click **Export All** to generate a list of hash values



Note:



- To ensure that all necessary files are calculated for hash values, it is advisable to add the root folder of the target application(s) to the **File Hash Generator** for calculation.
 - By clicking the **Add Folder** button, only the installer files, script files, and files in the PE (Portable Executable) format will be calculated.
 - For the single hash value, see [Add Trusted Hash Values \(on page 130\)](#) for how to add the copied hash value to the trusted hash value list.
 - For multiple hash values, see [Import Trusted Hash Values \(on page 130\)](#) for how to import the file containing the hash values to the trusted hash value list.
-

8. Click **Exit** to close the tool.

Add Trusted Hash Values

1. Go to **Agents > All**.
 2. Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Trusted Hash Values** at the bottom of the **Application Lockdown** pane.
4. Click the **Add** button and fill in the hash values and notes.

Import Trusted Hash Values

1. Go to **Agents > All**.
 2. Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Trusted Hash Values** at the bottom of the **Application Lockdown** pane.
 4. Click the **Import** button to import the .txt file containing a batch of hash values.
-



Note:

See [Calculate Hash Values \(on page 142\)](#) for generating the file containing the list of multiple hash values

Edit Trusted Hash Values

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Trusted Hash Values** at the bottom of the **Application Lockdown** pane.
4. Find the trusted hash value to be edited and click the corresponding Edit icon in the **Actions** column.
5. The **Edit Trusted Hash Value** dialog window appears.
6. After modification, click the **Save** button to complete the settings.

Remove Trusted Hash Values

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Trusted Hash Values** at the bottom of the **Application Lockdown** pane.
4. To delete multiple existing trusted hash values:
 - a. Click the checkboxes next to the existing trusted hash values.
 - b. Click the **Delete** button next to the **Import** button.
 - c. A warning message window appears. Click **Confirm** to delete the selected items.
5. To delete single existing trusted hash values:
 - a. Find the trusted hash value to be deleted and click the corresponding Delete icon in the **Actions** column.
 - b. A warning message window appears. Click **Confirm** to delete the selected item.

Multi-Method Threat Prevention

The Multi-Method Threat Prevention provides advanced threat scan to secure the endpoints without interrupting the endpoints's operations via machine learning and ICS root of trust. Related settings include:

- [Real-Time Protection \(on page 132\)](#)
- [Scheduled Scan \(on page 133\)](#)
- [Advanced Settings \(on page 134\)](#)

Real-Time Protection

Real-time Protection protects agents from known security threats in real time. As soon as malicious files or activities are detected, detection events are recorded and preconfigured prevention actions are taken.

In this pane, it has the following 2 features.

- [Real-Time Scan \(on page 147\)](#)
- [Ransomware Behavior Monitor \(on page 133\)](#)

Real-Time Scan

Real-Time Scan provides persistent and ongoing file scan for the endpoints. Each time a file is received, opened, downloaded, copied, or modified, **Real-Time Scan** always scans the file for security assessment. After performing the **Real-Time Scan**, users can proceed to access the file if it does not pose a security threat. However, if a security risk or possible virus/malware has been detected during the scanning, associated events indicating the name of the infected file and the specific security risk will be generated for further investigation.

Moreover, a persistent scan cache is maintained and reloaded each time the **Real-Time Scan** is executed. The **Real-Time Scan** tracks any changes made to files or folders that have occurred until the function is disabled and the files are unloaded and removed from the scan cache.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the Policy page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Go to the **Real-Time Protection** section in the **Multi-Method Threat Prevention** pane.
4. Toggle on the **Real-Time Protection** and click **Real-Time Scan**.



Note:

See [Advanced Settings \(on page 134\)](#) for instructions on how to configure the types of the files to be scanned, the action to take after possible security risk is detected, and the scan exclusion list.

Predictive Machine Learning

The **Predictive Machine Learning** uses intelligent machine learning technology to correlate threat information and perform an in-depth file analysis for emerging unknown security risk detection through digital DNA fingerprinting, API mapping, and other file properties. **Predictive Machine Learning** also performs a behavioral analysis on unknown or low-prevalence processes to determine if an emerging or unknown threat is attempting to infect your network. **Predictive Machine Learning** is a powerful tool that helps protect your assets and network environment against unidentified threats and zero-day attacks.

To enable **Predictive Machine Learning**, find and click the check box next to it in the section of **Real-Time Scan** in the **Multi-Method Threat Prevention** pane.

Ransomware Behavior Monitor

The Ransomware Behavior Monitor is a security feature that detects and prevents potential ransomware activity. It works by monitoring system behaviors for patterns commonly associated with ransomware. When suspicious activity is identified, the system can take predefined actions, helping safeguard your data by stopping ransomware threats before they cause significant harm.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note: For instructions on how to go to the Policy page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Go to the **Real-Time Protection** section in the **Multi-Method Threat Prevention** pane.
4. Toggle on the **Real-Time Protection** and then click **Ransomware Behavior Monitor**.

Scheduled Scan

You can customize a regular antivirus scan schedule for elevating vulnerability scanning to its potential, as well as providing less burden on technical operators.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Go to the **Scheduled Scan** in the **Multi-Method Threat Prevention** pane.
4. Toggle the **Scheduled Scan** on.
5. Click the **Schedule** button. A **Schedule** window appears.
6. Select one of the radio buttons listed below for determining the scan frequency.

- **Daily:** Perform scanning every day
- **Weekly:** Perform scanning every week (by default it's set as **every Sunday**)
- **Monthly:** Perform scanning every month (by default it's set as **on day 01**)



Important:

Since not every month contains the date 29th, 30th, or 31st, e.g., February only has 28 days (29 days on a leap year), TXOne Networks recommends NOT selecting the date 29th, 30th, or 31st for monthly update frequency. This helps prevent the system from bypassing the update in the month that does not contain the date 29th, 30th, or 31st.

7. Specify the scan start time in the **Start Time** field (by default it's set as **00:00**).
 8. Click **Confirm** to complete the setting.
-



Note:

- a. See [Advanced Settings \(on page 134\)](#) for instructions on how to configure the types of the files to be scanned, the action to take after possible security risk is detected, and the scan exclusion list.
 - b. You can also toggle on or off the **Predictive Machine Learning Analysis**. See [Predictive Machine Learning \(on page 133\)](#) for more information.
-

Advanced Settings

The **Advanced Options** allows you to configure the types of the files to be scanned, CPU usage setting, the action to take after possible security risk is detected, and the scan exclusion list.



Note:

CPU usage setting is not available for **Real-Time Scan**.

Advanced Options for Real-Time Scan

1. Go to **Agents > Policy > Multi-Method Threat Prevention**.
2. Click the **Advanced Settings** in the **Real-Time Scan** section.
3. The **Advanced Settings** configuration window appears.
4. The configuration window consists of two sections: **Files to Scan** and **Scan Actions**.
5. In the **Files to Scan** section:

- Check **Scan compressed files** and then select **Maximum layers** between 1 and 20 for the compressed files.
 - To skip scanning files over a certain size, check **Skip files larger than** and specify the file size between 1 and 2048 MB. Files exceeding the specified file size will not be scanned.
6. In the **Scan Actions** section, you can pre-define the action to take after threats are detected during the scanning for **Real-Time Scan** and **Predictive Machine Learning Analysis**. Select **Quarantine/Block** to quarantine incoming malicious files and block the execution of malware. Select **No action - Only log events** to produce only a readout of results with no actions taken on the suspicious files.
 7. Click **Confirm** to complete the settings.

Advanced Options for Scheduled Scan

1. Go to **Agents > Policy > Multi-Method Threat Prevention**.
2. Click the **Advanced Settings** in the **Scheduled Scan** section:
3. The **Advanced Settings** configuration window appears.
4. The configuration window consists of three sections: **Files to Scan**, **CPU Usage**, and **Scan Action**.

- a. In the **Files to Scan** section, click **All local folders** to scan all files in detail; click **Default folders (Quick Scan)** for a general scan; or click **Specific folders** to specify the paths to the folders for scan.



Tip:

Under the **Specific folders** option, click the "+" or "-" icon to add or delete paths to the specific folders.

- (Optional) Check **Scan removable drives** to allow scanning files in removable drives
 - (Optional) Check **Scan compressed files** and select the **Maximum layers** between 1 and 20 for the compressed files.
 - (Optional) To skip files over a certain size, check **Skip files larger than** and specify the file size between 1 and 2048 MB. Files exceeding the specified file size will not be scanned.
- b. The **CPU Usage** settings allow you to select the appropriate mode of CPU usage to balance between the scan and the available CPU resources depending on situations. There are two options available:

- Click **Normal** to reduce the impact on the service performance, which allows you to perform other tasks while scanning but the scan may take longer to complete.
 - Click **High** to reduce scan time, which requires higher CPU usage and may affect the system performance.
- c. In the **Scheduled Scan Action** section, you can pre-define the action to take after threats are detected during the scanning for **On-Demand Scan** and **Predictive Machine Learning Analysis**. Select **Quarantine/Block** to quarantine incoming malicious files and block the execution of malware. Select **No action - Only log events** to produce only a readout of results with no actions taken on the suspicious files.
- d. (Optional) The **Scan Exclusions** section allows you to exclude certain folders, files, or file extensions from being scanned. Refer to the next section for more information.
5. Click **Confirm** to complete the settings.

Scan Exceptions

The **Scan Exceptions** settings allow you to exclude certain files, folders, or file extensions from being scanned when running **Real-Time Scan** or **Scheduled Scan**

1. Go to **Agents > Policy > Multi-Method Threat Prevention**.



Note:

For Stellar Agent (Windows-Legacy), go to **Agents > Policy > Threat Prevention**

2. Find and click the **Real-Time Scan Exceptions** or **Scheduled Scan Exceptions**.
3. The configuration window appears. Click **Add** to add a certain file, folder, or file extension that will be excluded from being scanned.
4. The configuration window appears. Choose from the menu to add scan exclusions:
 - **File Extension:** Specify the file extension of certain files that do not require scanning.



Note:

- Stellar Agent (Windows) supports only local paths for Scan Exclusions. Remote paths such as an URL or \\[Host name] are not supported.
- It is not required to add "." or "*" in front of the file extension.

- **File hash (SHA-256):** Specify the hash value of a file that does not require scanning.

- **File path:** Specify the path to a file that does not require scanning.
 - **Folder and subfolder:** Specify the path to a folder that does not require scanning.
 - **Threat name:** Specify the name of a threat that does not require scanning.
 - **Regular expression:** Specify a regular expression that does not require scanning. When **Regular expression** is selected, further specify the **Path** or **Threat Name** in the next drop-down list.
5. Click **Add** to complete the settings.

**Tip:**

Click the "+" or "-" icon to add or delete the folder/file paths or file extensions.

OT Application Safeguard

OT Application Safeguard is an industrial-based change control protection. This feature ensures the Stellar Agent (Windows)-recognized OT applications can be updated without being blocked or restricted. In addition, you can enable OT application protection to secure recognized OT application executable binary files.

To enable **OT Application Safeguard**, go to **Agent > Policy**, scroll down to find and toggle on the **OT Application Safeguard** at the left side of the screen.

Upon launch, Stellar Agent (Windows) will auto-detect currently-installed OT applications and put them under protection. The recognized OT applications will be shown on the **Baseline** tab page. Follow the instructions to view the identified OT applications.

1. Go to **Agent > Policy**, scroll down to find and toggle on the **OT Application Safeguard** at the left side of the screen.
2. Find and click the **OT Applications**
3. The **Baseline** screen appears.
4. Check the OT Applications automatically recognized by the Stellar Agent (Windows) agent.

**Important:**

- Be sure to enable the **Maintenance Mode** before installing new OT applications. After the installation process completes, disable the **Maintenance Mode** and then Stellar Agent (Windows) will auto re-scan the newly-added OT applications. Any new applications found will be added into the OT Application Safeguard list. See [Configure Maintenance Mode \(on page 68\)](#) for how to enable this function.
- Be sure to enable the **Learn** mode of **Operations Behavior Anomaly Detection** before installing new OT applications. After the installation process completes, the Stellar Agent (Windows) agent will add the new OT applications into the **OT Applications** list displayed on the agent's **Baseline** page. See [Operations Behavior Anomaly Detection \(on page 108\)](#) for more details.

5. You can also manually add the installation path for the application into the Safeguard's protection list.

- a. Go to the **Policy** page and scroll down and find the **OT Application Safeguard** at the left side of the screen.
- b. Make sure the **OT Application Safeguard** toggle is switched on.
- c. Click **File/Folder**, and then the configuration window appears.
- d. Click the **+Add** button, and then select **Folder** or **File** and specify the folder or file path in the corresponding text fields.



Note:

By default, Stellar Agent (Windows) will only protect the PE files (.exe and .dll) under the selected folder and its subfolder(s).

- e. There are three different types of Protection Coverage you can select for each folder:
 - i. **All items, existing and new:** Protects all existing and newly added items within the selected folder and its subfolders, allowing only authorized processes to add or modify files and preventing deletion or renaming of the protected folder chain.
 - ii. **Recorded items only:** Protects all items recorded at the time of policy sync within the selected folder while allowing any application or process to add new items and modify unrecorded files.
 - iii. **Recorded executable files only:** Protects all items recorded at the time of policy sync as well as any newly added items within the selected folder and its subfolders, allowing only authorized processes to add or modify files and preventing deletion or renaming of the protected folder chain.
 - f. Click **Add** to complete the setting.
6. You can also add user-defined authorized processes.
- a. Go to **Policy > OT Application Safeguard**, and then click the **Authorized Processes**.
 - b. The configuration window appears. Click the **+Add** button, and then specify the authorized processes in the corresponding text fields.



Important:

By adding the authorized process, you may set other applications to be trusted and change the protected files/folders previously defined as well as the PE files for OT applications detected by agents. Please note if any malicious file has been set into the authorized process, Stellar Agent (Windows) cannot prevent this file from modifying the OT applications since it has been already excluded from the Stellar Agent (Windows)'s monitoring process. Make sure the user-defined authorized process is safe before adding it.

- c. Click **Add** to complete the setting.

DLL Injection Prevention

The **DLL Injection Prevention** provides protection against DLL hijacking attacks.

**Note:**

Only x86 platform supports DLL injection Prevention.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.

**Note:**

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Scroll down and find the **DLL Injection Prevention** at the left side of the screen.
4. Toggle on **Block DLL Injection** to enable it.

Network Access Restrictions

The **Network Access Restrictions** allows users to manually add restricted network access, to which the managed endpoints will not be permitted to connect.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.

**Note:**

For instructions on how to go to the Policy page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **Network Access Restrictions** pane.
4. Click **Add**. The **Network Access Restriction** window will appear.
5. Specify the IP address, port number, traffic direction, and the associated description in the corresponding text fields.

**Note:**

- The IP address only accepts IPv4 addresses, but it accepts CIDR notation.
- Leave the IP address or the port number fields blank to match any address or port.

6. Check **I am aware that blocking the network access may impact the operations**.

**Important:**



- It is suggested to identify and take preventative measures to avoid possible impact on operation before you add restrictions to the network access.
- Connections to ports for DHCP, DNS are not blocked by Network Access Restrictions. This ensures the connectivity between StellarOne and the agents.

-
7. Click **Add** to complete this task.
 8. (Optional) To remove a network access restriction, select the target item and click the **Delete** button next to the **+Add** button.
 9. A pop-up **Notification** window will appear. Click **Confirm** to delete the selected item.

Other Key Features for Stellar Agent (Windows-Legacy)

Other key features provided by Stellar Agent (Windows-Legacy) agent include:

- [Application Lockdown \(on page 140\)](#)
- [Threat Prevention \(on page 146\)](#)

See [Common Policy Settings for Stellar Agent \(Windows\)/Stellar Agent \(Windows-Legacy\) \(on page 152\)](#) for how to configure Agent Component Update Schedule, Device Control, User-Defined Suspicious Objects, Agent Password, Agent Patch deployment, and Trusted Certificates Settings for Stellar Agent (Windows-Legacy) agent.

Application Lockdown

When Application Lockdown is turned on, the agent will only be able to access applications that are in the Approved List.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

-
3. Go to the **Application Lockdown** pane.
 4. Three modes are available for selection:
 - **Detect:** When an application not in the Approved List launches, it is allowed and users will receive a notification.
 - **Enforce:** When an application not in the Approved List launches, it is blocked and users will receive a notification.
 - **Disable:** Application Lockdown is turned off.



Note: See the [Excluded Paths Settings \(on page 141\)](#), [Trusted Hash Values Settings \(on page 142\)](#), and [Write Protection Rules Settings \(on page 145\)](#) for how to configure the exclusions for the Approved List.

5. If you enable **Application Lockdown**, the sub-features listed below will appear. Select to enable them if needed.

- **DLL/Driver Lockdown**: Prevents unapproved DLLs or drivers from being loaded into the memory of protected endpoints.
- **Script Lockdown**: Prevents unapproved script files from being run on protected endpoints.
- **Write Protection**: Block unauthorized changes to items defined in the Write Protection Rules.
- **Fileless Attack Prevention**: Detects and blocks unapproved process chains and arguments that may lead to a fileless attack event.
- **Intelligent Runtime Learning**: Allows runtime executable files that are generated by applications in the Approved List.

Excluded Paths Settings

Excluded paths are used to point Stellar Agent (Windows-Legacy) to your file or file folder directly so that it can approve the file's execution.

Add a File, Folder, or Regular Expression as an Excluded Path

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **Excluded Paths** section from the **Application Lockdown** pane.
4. Click the **Add** button and the **Add Excluded Path** dialog window will appear.
5. Select one of the exception types: **File**, **Folder**, or **Regular Expression**.
6. Input the file system path for your exception.
7. Click the **Add** button to add a single exception path and the settings will be saved.

Edit Excluded Path

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **Excluded Paths** section from the **Application Lockdown** pane.
4. Check the check box next to the exception path you want to edit.
5. Click the **Edit** button and the **Add Excluded Path** dialog window will appear.
6. After modification, click the **Save** button to save the settings.

Remove Excluded Path

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **Excluded Paths** section from the **Application Lockdown** pane.
4. Check the check box next to the Exception Path you want to remove.
5. Click the **Delete** button and the **Remove Excluded Path** dialog window will appear.
6. Click the **Delete** button to remove the selected entries.

Trusted Hash Values Settings

When **Application Lockdown** is enabled, the Agent will only be able to access applications that are in the Approved List. Use hash values to remotely allow applications and files to run on managed endpoints.

Calculate Hash Values

Use **File Hash Generator** to calculate hash values before adding trusted hash values.

1. Find and click the **Trusted Hash Values** in the **Application Lockdown** pane.
2. A pop-up window appears. Find and download the **File Hash Generator** tool.
3. Execute `WKFileHashGen.exe` from the downloaded folder. The **File Hash Generator** screen will appear.
4. Use any of the following methods to select files and calculate hash values:
 - Drag and drop folders or files to the **File Hash Generator** screen.
 - Click the drop-down button and click **Add Files** to select the files to add.
 - Click the drop-down button and click **Add Folder** to add all the files in the selected folder.



Tip:

Only executable, script, and installer files are supported. Mouse over the **Supported file types** for more details.



Note:



Hash values will appear in the SHA-1 and SHA-256 columns.

- For a single file, right-click the item and select **Copy SHA-1** or **Copy SHA-256**. For multiple files, click **Export All** to generate a list of hash values
-



Note:

- To ensure that all necessary files are calculated for hash values, TXOne Networks suggests adding the root folder of the target application to the **File Hash Generator** for calculation.
 - By clicking the **Add Folder** button, only the installer files, script files, and files in the PE (Portable Executable) format will be calculated.
 - For the single hash value, see [Add Trusted Hash Values \(on page 143\)](#) for how to add the copied hash value to the trusted hash value list.
 - For multiple hash values, see [Import Trusted Hash Values \(on page 143\)](#) for how to import the file containing the hash values to the trusted hash value list.
-

- Click **Exit** to close the tool.

Add Trusted Hash Values

- Go to **Agents > All**.
 - Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

- Find and click the **Trusted Hash Values** in the **Application Lockdown** pane.
- Click the **Add** button and fill in the hash values and notes.
- (Optional) Select **Installer** to automatically add all files created or modified by the trusted installer to the Approved List.

Import Trusted Hash Values

- Go to **Agents > All**.
 - Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Trusted Hash Values** in the **Application Lockdown** pane.
 4. Click the **Import** button to import the .txt file containing a batch of hash values.
-



Note:

See [Calculate Hash Values \(on page 142\)](#) for generating the file containing the list of multiple hash values.

Edit Trusted Hash Values

1. Go to **Agents > All**.
 2. Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Trusted Hash Values** in the **Application Lockdown** pane.
 4. Find the trusted hash value to be edited and click the corresponding Edit icon in the **Actions** column.
 5. The **Edit Trusted Hash Value** dialog window appears.
 6. After modification, click the **Save** button to complete the settings.
 7. (Optional) Select **Installer** to automatically add all files created or modified by the trusted installer to the Approved List.
-

Remove Trusted Hash Values

1. Go to **Agents > All**.
 2. Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find and click the **Trusted Hash Values** in the **Application Lockdown** pane.
4. To delete multiple existing trusted hash values:

- a. Click the checkboxes next to the existing trusted hash values.
 - b. Click the **Delete** button next to the **Import** button.
 - c. A warning message window appears. Click **Confirm** to delete the selected items.
5. To delete single existing trusted hash values:
- a. Find the trusted hash value to be deleted and click the corresponding Delete icon in the **Actions** column.
 - b. A warning message window appears. Click **Confirm** to delete the selected item.

Write Protection Rules Settings

Write Protection Rules settings allow you to protect the details in certain files or folders from being changed by unauthorized users or applications. Set **Write Protection Rules** to remotely allow changes to certain files or folders on managed endpoints.

Add a File, Folder, Registry Key, or Registry Key and Value to Write Protection Rules

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **Write Protection Rules** section from the **Application Lockdown** pane.
4. Click the **Add** button and the **Add Write Protection Rules** dialog window will appear.
5. Select an exception **Process Type**:
 - **No Process can write**: Select this to prevent a **File, Folder, or Registry Key** specified in the line below from being modified by any process then enter the value accordingly.
 - **All process can write**: Select this to allow a **File, Folder, or Registry Key** specified in the line below to be able to modified by all process then enter the value accordingly.
 - **Specify a process that can write**: Select this to allow a process specified immediate to the right to modify a **File, Folder, or Registry Key** specified in the line below, and then enter the value accordingly.
6. Click the **Add** button and the settings will be saved.

Edit Write Protection Rules

1. Go to **Agents > All**.
 2. Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **Write Protection Rules** section from the **Application Lockdown** pane.
4. Click the pencil icon of the entry type you want to edit, and the **Add Write Protection Rules** dialog window will appear.
5. After modification, click the **Save** button to save the settings.

Remove Write Protection Rules

1. Go to **Agents > All**.
 2. Navigate to the target agent or group, and then go to its **Policy** page.
-



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **Write Protection Rules** section from the **Application Lockdown** pane.
4. Check the trash bin icon of the entry you want to remove. Click the **Confirm** button to remove the selected entries.
5. Or, you can check more than one entry then click the **Delete** button to delete them.

Threat Prevention

The **Threat Prevention** persistently scan new and changed files to provide security assessment for maximum protection against malware. Related settings include:

- [Real-Time Protection \(on page 132\)](#)
- [Scheduled Scan \(on page 148\)](#)
- [Advanced Settings \(on page 148\)](#)

Real-Time Protection

Real-time Protection protects agents from known security threats in real time. As soon as malicious files or activities are detected, detection events are recorded and preconfigured prevention actions are taken.

In this pane, it has the following 2 features.

- [Real-Time Scan \(on page 147\)](#)
- [Ransomware Behavior Monitor \(on page 133\)](#)

Real-Time Scan

Real-Time Scan provides persistent and ongoing file scan for the endpoints. Each time a file is received, opened, downloaded, copied, or modified, **Real-Time Scan** always scans the file for security assessment. After performing the **Real-Time Scan**, users can proceed to access the file if it does not pose a security threat. However, if a security risk or possible virus/malware has been detected during the scanning, associated events indicating the name of the infected file and the specific security risk will be generated for further investigation.

Moreover, a persistent scan cache is maintained and reloaded each time the **Real-Time PScan** is executed. The **Real-Time Scan** tracks any changes made to files or folders that have occurred until the function is disabled and the files are unloaded and removed from the scan cache.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **Real-Time Protection** in the **Threat Prevention** pane.
4. Toggle **Real-Time Protection** on to enable the function then check **Real-Time Scan**.



Note:

See the [Advanced Settings \(on page 148\)](#) for instructions on how to configure the types of the files to be scanned, the action to take after possible security risk is detected, and the scan exclusion list.

Ransomware Behavior Monitor

The Ransomware Behavior Monitor is a security feature that detects and prevents potential ransomware activity. It works by monitoring system behaviors for patterns commonly associated with ransomware. When suspicious activity is identified, the system can take predefined actions, helping safeguard your data by stopping ransomware threats before they cause significant harm.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note: For instructions on how to go to the Policy page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Go to the **Real-Time Protection** section in the **Threat Prevention** pane.
4. Toggle on the **Real-Time Protection** and then click **Ransomware Behavior Monitor**.

Scheduled Scan

You can customize a regular antivirus scan schedule for elevating vulnerability scanning to its potential, as well as providing less burden on technical operators.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.

**Note:**

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Go to the **Scheduled Scan** in the **Threat Prevention** pane.
4. Toggle the **Scheduled Scan** on.
5. Click the **Schedule** button. A **Schedule** window appears.
6. Select one of the radio buttons listed below for determining the scan frequency.
 - **Daily**: Perform scanning every day
 - **Weekly**: Perform scanning every week (by default it's set as **every Sunday**)
 - **Monthly**: Perform scanning every month (by default it's set as **on day 01**)

**Important:**

Since not every month contains the date 29th, 30th, or 31st, e.g., February only has 28 days (29 days on a leap year), TXOne Networks recommends NOT selecting the date 29th, 30th, or 31st for monthly update frequency. This helps prevent the system from bypassing the update in the month that does not contain the date 29th, 30th, or 31st.

7. Specify the scan start time in the **Start Time** field (by default it's set as **00:00**).
8. Click **Confirm** to complete the setting.

**Note:**

See [Advanced Settings \(on page 148\)](#) for instructions on how to configure the types of the files to be scanned, the action to take after possible security risk is detected, and the scan exclusion list.

Advanced Settings

The **Advanced Settings** allows you to configure the types of the files to be scanned, CPU usage setting, the action to take after possible security risk is detected, and the scan exclusion list.

**Note:**

CPU usage setting is not available for **Real-Time Scan**.

Advanced Options for Real-Time Scan

1. Go to **Agents > Policy > Threat Prevention**.
2. Click the **Advanced Settings** in the **Real-Time Scan** section.
3. The **Advanced Settings** configuration window appears.
4. The configuration window consists of three sections: **Files to Scan**, **Scan Action**, and **Scan Exclusions**.
5. In the **Files to Scan** section:
 - Check **Scan compressed files** and select the **Maximum layers** between 1 and 20 for the compressed files.
 - To skip scanning files over a certain size, check **Skip files larger than** and specify the file size between 1 and 2048 MB. Files exceeding the specified file size will not be scanned.
6. In the **Scan Actions** section, you can pre-define the action to take after threats are detected during the scanning. Select **Quarantine/Block** to quarantine incoming malicious files and block the execution of malware. Select **No action - Only log events** to produce only a readout of results with no actions taken on the suspicious files.
7. Click **Confirm** to complete the settings.

Advanced Options for Scheduled Scan

1. Go to **Agents > Policy > Threat Prevention**.
2. Click the **Advanced Settings** in the **Scheduled Scan** section:
3. The **Advanced Settings** configuration window appears.
4. The configuration window consists of three sections: **Files to Scan**, **CPU Usage**, and **Scan Action**.

**Note:**

The Stellar Agent (Windows-Legacy) agents will automatically attempt to download the latest components before starting a scan. A **Component Update** toggle is available for you to determine whether the endpoints should continue with the scan if the component update is unsuccessful.

- a. In the **Files to Scan** section, click **All local folders** to scan all files in detail; click **Default folders (Quick Scan)** for a general scan; or click **Specific folders** to specify the paths to the folders for scan.
-



Tip:

Under the **Specific folders** option, click the "+" or "-" icon to add or delete paths to the specific folders.

- (Optional) Check **Scan removable drives** to allow scanning files in removable drives
 - (Optional) Check **Scan compressed files** and select the **Maximum layers** between 1 and 20 for the compressed files.
 - (Optional) To skip files over a certain size, check **Skip files larger than** and specify the file size between 1 and 2048 MB. Files exceeding the specified file size will not be scanned.
 - (Optional, Stellar Agent (Linux) only) To skip network drive scan, check **To Skip network drives, such as NFS, SMB**. CIFS from 1.0 to 3.1.1 and NFS from 3.0 to 4.2 are supported.
- b. The **CPU Usage** settings allow you to select the appropriate mode of CPU usage to balance between the scan and the available CPU resources depending on situations. There are two options available:
- Click **Normal** to reduce the impact on the service performance, which allows you to perform other tasks while scanning but the scan may take longer to complete.
 - Click **High** to reduce scan time, which requires higher CPU usage and may affect the system performance.
- c. In the **Scan Action** section, you can pre-define the action to take after threats are detected. Select **Quarantine** to place the suspicious or infected files detected in an isolated folder for further checking. Select **No action** to produce only a readout of results with no actions taken on the suspicious files.
-



Note:

The Stellar Agent (Windows-Legacy) agents provide more choices such as:



- **Use ActiveAction:** The pre-configured scan actions, which are best to use if you are not familiar with scan actions or if you are not sure which scan action is suitable. ActiveAction uses recommended actions, meaning you do not have to spend time configuring scan actions. Virus writers constantly change the way virus/malware attack endpoints. ActiveAction settings are updated to protect against the latest threats and the latest methods of virus/malware attacks.
- **Clean, or delete if the clean action is unsuccessful:** To delete the target file if it cannot be recovered.
- **Clean, or quarantine if the clean action is unsuccessful:** To quarantine the target file if it cannot be recovered.
- **Clean, or ignore if the clean action is unsuccessful:** To ignore the target file if it cannot be recovered.

5. Click **Confirm** to complete the settings.

Scan Exceptions

The **Scan Exceptions** settings allow you to exclude certain files, folders, or file extensions from being scanned when running **Real-Time Scan** or **Scheduled Scan**

1. Go to **Agents > Policy > Multi-Method Threat Prevention**.



Note:

For Stellar Agent (Windows-Legacy), go to **Agents > Policy > Threat Prevention**

2. Find and click the **Real-Time Scan Exceptions** or **Scheduled Scan Exceptions**.
3. The configuration window appears. Click **Add** to add a certain file, folder, or file extension that will be excluded from being scanned.
4. The configuration window appears. Choose from the menu to add scan exclusions:

- **File Extension:** Specify the file extension of certain files that do not require scanning.



Note:

- Stellar Agent (Windows) supports only local paths for Scan Exclusions. Remote paths such as an URL or \\[Host name] are not supported.
- It is not required to add "." or "*" in front of the file extension.

- **File hash (SHA-256):** Specify the hash value of a file that does not require scanning.

- **File path:** Specify the path to a file that does not require scanning.
 - **Folder and subfolder:** Specify the path to a folder that does not require scanning.
 - **Threat name:** Specify the name of a threat that does not require scanning.
 - **Regular expression:** Specify a regular expression that does not require scanning. When **Regular expression** is selected, further specify the **Path** or **Threat Name** in the next drop-down list.
5. Click **Add** to complete the settings.



Tip:

Click the "+" or "-" icon to add or delete the folder/file paths or file extensions.

Common Policy Settings for Stellar Agent (Windows)/Stellar Agent (Windows-Legacy)

Common policy settings for Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) agent include:

- [Agent Component Update Schedule \(on page 152\)](#)
- [External Device Management \(on page 154\)](#)
- [User-Defined Suspicious Objects \(on page 157\)](#)
- [Agent Password \(on page 157\)](#)
- [Patch \(on page 158\)](#)
- [Trusted Certificates Settings \(on page 159\)](#)

Agent Component Update Schedule

You can configure the component update schedule for the agents via the StellarOne web console; thus the system can run component update automatically at the assigned time frequency.



Note:

StellarOEM license edition does not support this function.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. On the **Policy** page, find the **Schedule Update** in the **Agent Component Update Schedule** pane.

4. (Optional) Click **Go to StellarOne Scan Component Update Schedule** and view the current settings of StellarOne's component update schedule.

**Tip:**

You can determine the agent's component update schedule by referring to the StellarOne console's component update schedule first.

**Note:**

Only users logged in with administrator or operator account can edit the StellarOne component update schedule.

5. Toggle on the **Schedule Update**. Radio buttons for setting the **Frequency** and **Start Time** appear.

- Click **Daily** to perform the agent component update every day
- Click **Weekly** to perform the agent component update every week

**Note:**

The default setting for **Weekly** update is **every Sunday**.

- Click **Monthly** to perform the agent component update every month

**Note:**

The default setting for **Monthly** update is **on day 01**.

**Important:**

Since not every month contains the date 29th, 30th, or 31st, e.g., February only has 28 days (29 days on a leap year), TXOne Networks recommends selecting **The last day of the month** for monthly update frequency. This helps prevent the system from bypassing the update in the month that does not contain the date 29th, 30th, or 31st.

6. Click **Start Time** to specify the exact time to perform the agent component update based on the defined frequency.

**Note:**

The default setting for **Start Time** is **00:00**.

7. (Optional) If you do not want StellarOne to automatically deploy the latest component update to the agent/group, toggle on **Defer Component Update**. StellarOne will manage to deploy only the previous version.



Note:

The configuration of agent component update will somehow impact the component update status displayed on the **Agents** screen and the **Agent Component Status** widget on **Dashboard**. See [Manage Agent Component Status \(on page 55\)](#) for more details.

8. (Optional) You may toggle on **Randomly distribute updates across the designated hour to reduce server load**, which adds a random time offset to the scheduled component update start time for each agent, so they don't all update at exactly the same minute. The hour at which the scheduled update starts is still based on the **Start time** hour selected.

External Device Management

StellarOne provides a series of functions to enhance external device management on the endpoints.

- **Device Control:** When this function is enabled, Stellar Agent (Windows) and Stellar Agent (Windows-Legacy) will block unauthorized storage devices from accessing the managed endpoints, unless the storage devices are added in the Trusted USB Device list.



Note:

Stellar Agent (Windows-Legacy) supports blocking USB storage devices while supports blocking USB devices, CD/DVD drives and floppy disks on the managed endpoints.

- **USB Auto Scan:** When this function is enabled, the managed endpoints will automatically scan the connected USB devices.
- **Block USB AutoRun:** When this function is enabled, the connected USB storage devices are not permitted to automatically launch programs or applications on the managed endpoints.
- **USB Access Tracking:** When this function is enabled, whenever the USB storage devices are connected to or disconnected from the managed endpoints, the agents will send event log.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For functions on how to go to the Policy page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **External Device Management** pane and toggle on the following function(s) as needed.

- **Device Control:** See [Device Control \(on page 155\)](#) for more details on how to configure the **Trusted USB Device** list.
- **USB Auto Scan.**
- **Block USB AutoRun.**
- **USB Access Tracking.**

Device Control

When **Device Control** is enabled, every time the local user connects an unrecognized USB storage device to the protected endpoint, a pop-up notification will be displayed on the Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) agent console for the local user to check and confirm if the USB device access is permitted. In addition, the associated event log will also be generated to notify the StellarOne administrator.

This StellarOne admin can grant one-time access to the unrecognized USB device via the event action available on the blocked USB event. The USB will then be temporarily recognized as a trusted USB device and granted access until disconnected from the endpoint. On top of that, the StellarOne admin can choose to add the USB to the **Trusted USB Device** list via the policy settings, permitting it to access directly and permanently without further check.



Note:

In addition to USB devices, Stellar Agent (Windows-Legacy) also support blocking CD/DVD drives and floppy disks on the managed endpoints with **Device Control** enabled.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For functions on how to go to the Policy page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **External Device Management** pane and toggle on **Device Control**.
4. Click **Trusted USB Device** and a pop-up window appears.
5. Specify at least one of the following information for the trusted USB device. The **Description** field is optional.
 - **Vendor ID**
 - **Product ID**
 - **Serial number**
6. Click **OK** to complete the setting.
7. Check if the USB device is successfully added in the trusted USB device list.
8. (Optional) To edit the USB device information, select the USB device and click the edit icon in the **Actions** column. A pop-up window appears. Edit the USB device information in the related text fields and then click **OK**.

9. (Optional) To remove a USB device from trusted list, choose either way listed below.
 - For removing multiple USB devices at the same time, select the USB devices and click the **Delete** button next to the **+Add** button.
 - For removing only one USB device, click the Delete icon in the **Actions** column.

A pop-up **Notification** window appears. Click **Confirm** to delete the USB device(s).

Get Device Information

To get Device Information, use one of the following methods:

- Open the **Device Manager** on the endpoint.
- For Stellar Agent (Windows-Legacy) agent, use the `SLCmd.exe` command on the endpoint. For more information, go to **MyTXOne** site and look for "**Stellar Agent (Windows-Legacy) Administrator Guide**" under the **Endpoint Protection** filter on the **Documentation** page.
- On StellarOne, go to the **Logs > Agent Events** on StellarOne console to check the event details about removable devices with Agent Event ID 1281/1282 (Stellar Agent (Windows)) or 5000/5001 (Stellar Agent (Windows-Legacy)).

For Stellar Agent (Windows-Legacy) agent, you can view the list of trusted USB devices on an endpoint by exporting the agent settings. To manually configure the trusted USB device list on an endpoint, do one of the following:

- Export the agent's settings, make changes, and then import the modified settings back to the agent via StellarOne
- Import an updated settings file via StellarOne
- Use the `SLCmd.exe` command on the Stellar Agent (Windows-Legacy) agent

Edit/Add/Remove Trusted USB Devices by Importing Configuration File

1. Go to **Agents > All**.
2. Click the **All** group on the **Agents** screen. The **Agents** screen displays a list of agents managed by StellarOne.
3. Select the target agent by clicking the checkbox next to it.
4. Click the **Import/Export** button from the Tool Bar at the top of the **Agents** screen.
5. Click the **Export Agent Configuration** option.
6. Click **Confirm**.
7. A pop-up **Command Deployment** window appears. The **Status** shows if the agent configuration is exported successfully.
8. Click the **Download** link to download the target agent's configuration file.
9. Open the agent configuration file in a text editor and find the `DeviceException` section.

Figure 7. DeviceException section

```
<StorageDeviceBlocking Enable="no" ActionMode="1" AllowNonMassStorageUSBDevice="no">
  <DeviceException>
    <DeviceGroup name="UserDefined"/>
  </DeviceException>
</StorageDeviceBlocking>
```


10. The following figure shows an example where the section contains two entries for the added trusted USB devices.

Figure 8. Devices added in DeviceException section

```
<StorageDeviceBlocking Enable="no" ActionMode="1" AllowNonMassStorageUSBDevice="no">
  <DeviceException>
    <DeviceGroup name="UserDefined">
      <Device vid="781" pid="5151" sn="2444130A5442A4F5"/>
      <Device vid="951" pid="1666" sn="E03F49AEC0DDF351E913003F"/>
    </DeviceGroup>
  </DeviceException>
</StorageDeviceBlocking>
```

11. You can edit, add, or remove the trusted USB devices by modifying, adding, or deleting the entries for the trusted USB devices and save the agent configuration file.
12. Import the updated agent configuration file to the target agents.

User-Defined Suspicious Objects

The **User-Defined Suspicious Object** allows users to manually add the file hashes (SHA-1 or SHA-2) or paths of new IOC (Indicators of Compromise) into the blocked-file list, which prevents all managed endpoints from being infected by the malicious files.



Note:

The Stellar Agent (Windows-Legacy) only supports SHA-1 file hash.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Find the **User-Defined Suspicious Object** at the right side of the screen.
4. Click **Add**. The **Add Item to User-Defined Suspicious Objects** window appears.
5. Select **Hash** or **File Path** as the suspicious file type.
6. Specify the file hash or path in the corresponding text field.
7. (Optional) Specify notes in the **Notes** text field.
8. Click **OK** to complete this task.
9. (Optional) To remove a user-defined suspicious object, select the target hash/file path and click the **Delete** button next to the **+Add** button.
10. A pop-up **Notification** window appears. Click **Confirm** to delete the selected item.

Agent Password

This function allows StellarOne administrators to remotely change the Agent's Administrator or User password required for logging on the Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) local consoles. It does not require the old agent password to create a new one.



Note:



This function is only available for users with privileges of Admins or Operators.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Scroll down and find the **Agent Password** at the right side of the screen.
4. Select either **Agent Self-Managed** or **Policy Central-Managed** for the Change Permission option on either the Administrator Account or the User Account section.
5. If **Policy Central-Managed** is selected, you will be prompted to enter a new password.
6. Input the new password twice and click **Confirm** to finish this policy setting.



Note:

- The password must be 8 to 64 alphanumeric characters. The following characters are not supported: | > " : < \ spaces
- If the group/agent policy has been changed to customized, make sure you reset the agent password for better password management.

Patch

The **Patch** function allows the administrator to deploy a patch file upgrade on all agents under the same group policy. The patching process can be conducted remotely and automatically using policy synchronization. Only one patch file (Agent version) is allowed to be upgraded each time under each group policy.



Important:

A patch is generally used to fix or enhance the current version. If you accidentally patch an older version, the patch deployment should not work and the agent status will keep un-synced with the StellarOne console. Meanwhile, other policy settings can't be deployed, either. After 20 minutes the agents will resynchronize with StellarOne; until then can the policy settings be applied to the agent.

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Scroll down and find the **Patch** at the bottom right corner of the screen.
 4. Click the checkbox next to the version of the patch file for deployment.
-

**Note:**

You can import new patches for the agent on the [Importing/Deleting Agent's Patch \(on page 215\)](#) page.

5. The selected patch file will be deployed on the agents under the same group policy.
-

**Note:**

Since StellarOne can apply global policy to all managed agents or certain group policies to group-owned endpoints for conducting the patching process on multiple devices at the same time, before you select agent version, please be aware that:

- By default, the global policy should be applied to every agent. TXOne Networks suggests that you keep lower agent version in the global policy settings.
 - If you don't want to set any agent version for patch deployment, do not select any of the checkboxes next to the agent version patch files in the **Patch** pane.
-

**Important:**

Stellar Agent (Windows) 1.0 does not support remote patch because it does not have any available remote patch files.

6. By default, StellarOne will automatically deploy the selected patch to the group of agents. However, if you toggle off the **Allow automatic updates**, the agents will only download the latest patch from StellarOne without installing. The local users can choose to run on-demand patch update manually on the agent console.

Trusted Certificates Settings

Similar to hash values, trusted certificates are made by the application vendors or organizations to allow the agent to know which applications are trustworthy. **Trusted Certificates** provides an import function allowing the administrator to add new trusted certificates. The trusted certificates defined by users and the corresponding applications will be bypassed during scanning, will not be blocked by Application Lockdown, and will not trigger alerts related to Ransomware Behavior Monitoring and OBAD Application Behavior.

Importing/Deleting Trusted Certificates

1. Go to **Agents > All**.
2. Navigate to the target agent or group, and then go to its **Policy** page.



Note:

For instructions on how to go to the **Policy** page, see [Go to the Agent View \(on page 105\)](#) for a single agent or [Go to the Group Policy Screen \(on page 176\)](#) for a group of agents.

3. Scroll down and find the **Trusted Certificates** at the right side of the screen.
4. Click **Import** to import the selected trusted certificate file.
5. (Stellar Agent (Windows-Legacy) only) Enable the **Installer** toggle switch to automatically add all files created or modified by the trusted installer to the Approved List.



Note:

By default, the **Installer** toggle is turned off.

6. Click **Import** to add the trusted certificate and the settings will be saved.
7. To remove the trusted certificate(s), choose either way listed below.
 - For removing multiple trusted certificates at the same time, select them and click the **Delete** button next to the **+Add** button.
 - For removing only one trusted certificate, click the Delete icon in the **Actions** column.

A pop-up **Notification** window appears. Click **Confirm** to delete the selected certificate(s).

Baseline

The Baseline page displays a unique fingerprint baseline of each agent-device, which is generated via TXOne cyber-physical system (CPS) detection methods.

Topics in this section include:

- [Baseline for Stellar Agent \(Windows\) \(on page 160\)](#)
- [Baseline for Stellar Agent \(Windows-Legacy\) \(on page 167\)](#)

Baseline for Stellar Agent (Windows)

The Stellar Agent (Windows) **Baseline** page displays the baseline fingerprint at the agent level.



Note:

The baseline data is transmitted at the default or specified policy refresh interval. See [Set Policy Refresh Interval \(on page 87\)](#) for more information.

See the following table for more details about this page.

Table 30. About the Stellar Agent (Windows) Baseline Page

Item	Description
OT Applications	Upon launch, Stellar Agent (Windows) will auto-detect currently-installed OT applications and put them under protection. The recognized OT applications will be shown on the Baseline tab page. See OT Application Safeguard (on page 137) for more information.
OT Certificates	Upon launch and running pre-scan during the agent installation, Stellar Agent (Windows) will auto-detect currently-accepted OT certificates. The recognized OT certificates will be shown on the Baseline tab page.
Approved Script Behaviors	Once you enable the Script Behavior of the Operations Behavior Anomaly Detection , the agent automatically learns and allows the approved scripts to run on the endpoints. See Approved Script Behaviors (on page 161) for more details.
Approved Login Accounts	Once you enable the User Login of the Operations Behavior Anomaly Detection , the agent automatically learns and allows the approved user accounts and related login behaviors to run on the endpoints. See Approved Login Accounts (on page 163) for more details.
Approved Applications	Once you enable the Application Behavior of the Operations Behavior Anomaly Detection , the agent automatically learns and allows the approved applications to run on the endpoints. See Approved Applications (on page 164) for more information.
Approved Network Access	Once you enable the Network Access of the Operations Behavior Anomaly Detection , the agent automatically learns and allows the approved networks to run on the endpoints. See Approved Network Access (on page 166) for more information.
Installed Applications	The applications listed below are detected by the Stellar agent and will be updated automatically every day. Please note that this list may not be updated in real-time, as it depends on when the agent connects to StellarOne. To refresh the list, go to the Policy page and enable Learn Mode under Operations Behavior Anomaly Detection .

See [Operations Behavior Anomaly Detection \(on page 108\)](#) for more details about the **Approved Script Behaviors**, **Approved Login Accounts**, **Approved Applications**, and **Approved Network Access**.

Approved Script Behaviors

If you enable the **Operations Behavior Anomaly Detection > Script Behavior** function, script behaviors found on the Stellar Agent (Windows) agent-device will be added to its baseline and displayed on the **Baseline > Approved Script Behaviors** page.

See the following table for more information about the **Approved Script Behaviors** page.

Table 31. About the Baseline > Approved Script Behaviors Page

Item	Description
Baseline Toggle	Allows you to determine if you want to include specific approved script behaviors in the baseline. If you turn the toggle off, the target script behaviors will be viewed as unexpected changes; alerts or preventative actions will be triggered depending on the selected Operations Behavior Anomaly Detection mode: • In Detect mode: relevant events will be generated. • In Enforce mode: target script behaviors will be blocked.
Monitored Process / Script	Displays the monitored operation process containing certain applications and accompanied parameters. By default, Stellar Agent (Windows) monitored 5 applications as listed below. You can also specify other commonly-abused applications in the Operations Behavior Anomaly Detection > Script Behavior > Policy-based Watchlist. • powershell.exe • wscript.exe • cscript.exe • mshta.exe • psexec.exe See Policy-based Watchlist (on page 117) for more details.
Approved Operation	Displays the approved operations stored in the baseline. The approved operations can be viewed as the full execution process for triggering the monitored process mentioned above. See Operations Behavior Anomaly Detection (on page 108) for more details.
Added From	Displays the sources the approved script behaviors are added from:

Table 31. About the Baseline > Approved Script Behaviors Page (continued)

Item	Description
	• Learn mode: the approved script behaviors have been detected and added to the baseline during Operations Behavior Anomaly Detection Learn mode. • Event action: the approved script behaviors have been added to the baseline by StellarOne administrator manually from the agent events (by clicking the Add to Baseline action button). See Add to Baseline (on page 183) for more details.
Time Added	Displays the time when the approved script behaviors were added to the baseline.

**Note:**

TXOne Networks recommends switching back to **Operations Behavior Anomaly Detection Learn** mode before adding new script behaviors or modifying existing ones.

Approved Login Accounts

If you enable the **Operations Behavior Anomaly Detection > User Login** function, user accounts and related login activities found on the Stellar Agent (Windows) agent-device will be added to its baseline and displayed on the **Baseline > Approved Login Accounts** page.

See the following table for more details about the **Approved Login Accounts** page.

Table 32. About the Baseline > Approved Login Accounts Page

Item	Description
Baseline Toggle	Allows you to determine if you want to include the approved login accounts in the baseline. If you turn it off, the corresponding login accounts will be viewed as not allowed and relevant events will be generated.
Domain	Displays the approved domains for the user to log in from.
Username	Displays the approved usernames stored in the baseline.
Source IP	Displays the approved IP addresses for the user to log in from.

Table 32. About the Baseline > Approved Login Accounts Page (continued)

Item	Description
Login Type	Displays the approved login type stored in the baseline.
Added From	Displays the sources the approved login accounts are added from: • Learn mode: the approved login accounts have been detected and added to the baseline during Operations Behavior Anomaly Detection Learn mode. • Event action: the approved login accounts have been added to the baseline by StellarOne administrator manually from the agent events (by clicking the Add to Baseline action button). See Add to Baseline (on page 183) for more details.
Time Added	Displays the time when the approved login accounts were added to the baseline.

**Note:**

TXOne Networks recommends switching back to **Operations Behavior Anomaly Detection Learn** mode before adding new user accounts or modifying existing ones.

Approved Applications

If you enable the **Operations Behavior Anomaly Detection > Application Behavior** function, applications found on the Stellar Agent (Windows) agent-device will be added to its baseline and displayed on the **Baseline > Approved Applications** page.

See the following table for more details about the **Approved Applications** page.

Table 33. About the Baseline > Approved Applications Page

Item	Description
Baseline Toggle	Allows you to determine if you want to include the approved applications in the baseline. If you turn it off, the running of the corresponding application will be viewed as unexpected changes and relevant events will be generated.
Application	Displays the product name of the approved application stored in the baseline.

Table 33. About the Baseline > Approved Applications Page (continued)

Item	Description
Size	Displays the size of the approved application.
SHA-1	Displays the SHA-1 file hash value of the approved application
SHA-256	Displays the SHA-256 file hash value of the approved application
path	Displays the file path to the approved application
Version	Displays the version of the approved application when it was added to the baseline
Added From	Displays the sources the approved applications are added from: • Learn mode: the approved applications have been detected and added to the baseline during Operations Behavior Anomaly Detection "Learn" mode. • Event action: the approved applications have been added to the baseline by StellarOne administrator manually from the agent events (by clicking the Add to Baseline action button). See Add to Baseline (on page 183) for more details.  Note: ◦ If the approved applications are added during the "Learn" mode, the agent learns not only the applications but also the relevant behaviors; different application behaviors may be detected as anomalies. ◦ If the approved applications are added from the event action "Add to Baseline", the applications will be viewed as "exceptions" and associated behavior changes will be treated as acceptable.
Time Added	Displays the time when the approved applications were added to the baseline.

 **Note:**



TXOne Networks recommends switching back to **Operations Behavior Anomaly Detection Learn** mode before running the application updates.

Approved Network Access

If you enable the **Operations Behavior Anomaly Detection > Network Access** function, network access found on the Stellar Agent (Windows) agent-device will be added to its baseline and displayed on the **Baseline > Approved Network Access** page.

See the following table for more details about the **Approved Network Access** page.

Table 34. About the Baseline > Approved Network Access Page

Item	Description
Baseline Toggle	Allows you to determine if you want to include the approved network access in the baseline. If you turn it off, the connection of the corresponding network will be viewed as unexpected changes and relevant events will be generated.
IP	Displays the remote IP address of the approved network stored in the baseline.
Direction	Displays the direction of the network traffic.
Remote/Local Port	Displays the port number of the remote/local port. For outbound TCP connections or UDP sessions, this field indicates the port of the remote host. For inbound connections and session, this field indicates the local port.
L4 Protocol	Displays the L4 Protocol of the network.
L7 Protocol	Displays the L7 Protocol of the network.
Gateway IP	Displays the gateway IP of the network.
Local IP	Displays the local IP of the network.
MAC Address	Displays the MAC address of the NIC device on the network.
Subnet Prefix Length	Displays the subnet prefix length of the network.
Added From	Displays the sources that the approved networks are added from:

Table 34. About the Baseline > Approved Network Access Page (continued)

Item	Description
	• Learn mode: the approved applications have been detected and added to the baseline during Operations Behavior Anomaly Detection "Learn" mode. • Event action: the approved networks have been added to the baseline by StellarOne administrator manually from the agent events (by clicking the Add to Baseline action button). See Add to Baseline (on page 183) for more details.
Applications	Displays the name and the repository path of the associated application. If there are more than one application, the number of the applications will be displayed. Click the number to display the name and the path of all applications. If the application utilizes the connection cannot be determined, a placeholder text "Unknown Application" will be shown.
Time Added	Displays the time when the approved networks were added to the baseline.

**Note:**

TXOne Networks recommends switching back to **Operations Behavior Anomaly Detection Learn** mode before running the application updates.

Baseline for Stellar Agent (Windows-Legacy)

The Stellar Agent (Windows-Legacy) **Baseline** page displays the baseline fingerprint at the agent level.

**Note:**

The baseline data are transmitted at the default or specified policy refresh interval. See [Set Policy Refresh Interval \(on page 87\)](#) for more information.

See the following table for more details about this page.

Table 35. About the Stellar Agent (Windows-Legacy) Baseline Page

Item	Description
Approved Script Behaviors	Once you enable the Script Behavior of the Operations Behavior Anomaly Detection , the agent automatically learns and allows the approved scripts to run on the endpoints. See Approved Script Behaviors (on page 168) for more details.
Approved Login Accounts	Once you enable the User Login of the Operations Behavior Anomaly Detection , the agent automatically learns and allows the approved user accounts and related login behaviors to run on the endpoints. See Approved Login Accounts (on page 170) for more details.
Approved Applications	Once you enable the Application Behavior of the Operations Behavior Anomaly Detection , the agent automatically learns and allows the approved applications to run on the endpoints. See Approved Applications (on page 171) for more information.
Installed Applications	The applications listed below are detected by the Stellar agent and will be updated automatically every day. Please note that this list may not be updated in real-time, as it depends on when the agent connects to StellarOne. To refresh the list, go to the Policy page and enable Learn Mode under Operations Behavior Anomaly Detection .

See [Operations Behavior Anomaly Detection \(on page 108\)](#) for more details about the **Approved Script Behaviors**, **Approved Login Accounts**, and **Approved Applications**.

Approved Script Behaviors

If you enable the **Operations Behavior Anomaly Detection > Script Behavior** function, script behaviors found on the Stellar Agent (Windows-Legacy) agent-device will be added to its baseline and displayed on the **Baseline > Approved Script Behaviors** page.

See the following table for more information about the **Approved Script Behaviors** page.

Table 36. About the Baseline > Approved Script Behaviors Page

Item	Description
Baseline Toggle	Allows you to determine if you want to include specific approved script behaviors in the baseline. If you turn the toggle off, the target script behaviors will be viewed as unexpected changes; alerts or preventative actions will be triggered depending on the selected Operations Behavior Anomaly Detection mode: • In Detect mode: relevant events will be generated. • In Enforce mode: target script behaviors will be blocked.

Table 36. About the Baseline > Approved Script Behaviors Page (continued)

Item	Description
Monitored Process / Script	Displays the monitored operation process containing certain applications and accompanied parameters. By default, Stellar Agent (Windows-Legacy) monitored 5 applications as listed below. You can also specify other commonly-abused applications in the Operations Behavior Anomaly Detection > Script Behavior > Policy-based Watchlist. • powershell.exe • wscript.exe • cscript.exe • mshta.exe • psexec.exe See Policy-based Watchlist (on page 117) for more details.
Approved Operation	Displays the approved operations stored in the baseline. The approved operations can be viewed as the full execution process for triggering the monitored process and/or script mentioned above. See Operations Behavior Anomaly Detection (on page 108) for more details.
Added From	Displays the sources the approved script behaviors are added from: • Learn mode: the approved script behaviors have been detected and added to the baseline during Operations Behavior Anomaly Detection Learn mode. • Event action: the approved script behaviors have been added to the baseline by StellarOne administrator manually from the agent events (by clicking the Add to Baseline action button). See Add to Baseline (on page 183) for more details.
Time Added	Displays the time when the approved script behaviors were added to the baseline.

**Note:**



TXOne Networks recommends switching back to **Operations Behavior Anomaly Detection Learn** mode before adding new script behaviors or modifying existing ones.

Approved Login Accounts

If you enable the **Operations Behavior Anomaly Detection > User Login** function, user accounts and related login activities found on the Stellar Agent (Windows-Legacy) agent-device will be added to its baseline and displayed on the **Baseline > Approved Login Accounts** page.

See the following table for more details about the **Approved Login Accounts** page.

Table 37. About the Baseline > Approved Login Accounts Page

Item	Description
Baseline Toggle	Allows you to determine if you want to include the approved login accounts in the baseline. If you turn it off, the running of the corresponding login accounts will be viewed as not allowed and relevant events will be generated.
Domain	Displays the approved domains for the user to log in from.
Username	Displays the approved usernames stored in the baseline.
Source IP	Displays the approved IP addresses for the user to log in from.
Login Type	Displays the approved login type stored in the baseline.
Added From	Displays the sources the approved login accounts are added from: • Learn mode: the approved login accounts have been detected and added to the baseline during Operations Behavior Anomaly Detection Learn mode. • Event action: the approved login accounts have been added to the baseline by StellarOne administrator manually from the agent events (by clicking the Add to Baseline action button). See Add to Baseline (on page 183) for more details.
Time Added	Displays the time when the approved login accounts were added to the baseline.



Note:



TXOne Networks recommends switching back to **Operations Behavior Anomaly Detection Learn** mode before adding new user accounts or modifying existing ones.

Approved Applications

If you enable the **Operations Behavior Anomaly Detection > Application Behavior** function, applications found on the Stellar Agent (Windows-Legacy) agent-device will be added to its baseline and displayed on the **Baseline > Approved Applications** page.

See the following table for more details about the **Approved Applications** page.

Table 38. About the Baseline > Approved Applications Page

Item	Description
Baseline Toggle	Allows you to determine if you want to include the approved applications in the baseline. If you turn it off, the running of the corresponding application will be viewed as unexpected changes and relevant events will be generated.
Application	Displays the product name of the approved application stored in the baseline.
Size	Displays the size of the approved application.
SHA-1	Displays the SHA-1 file hash value of the approved application
SHA-256	Displays the SHA-256 file hash value of the approved application
path	Displays the file path to the approved application
Version	Displays the version of the approved application when it was added to the baseline
Added From	Displays the sources the approved applications are added from:

Table 38. About the Baseline > Approved Applications Page (continued)

Item	Description
	• Learn mode: the approved applications have been detected and added to the baseline during Operations Behavior Anomaly Detection "Learn" mode. • Event action: the approved applications have been added to the baseline by StellarOne administrator manually from the agent events (by clicking the Add to Baseline action button). See Add to Baseline (on page 183) for more details.  Note: ◦ If the approved applications are added during the "Learn" mode, the agent learns not only the applications but also the relevant behaviors; different application behaviors may be detected as anomalies. ◦ If the approved applications are added from the event action "Add to Baseline", the applications will be viewed as "exceptions" and associated behavior changes will be treated as acceptable.
Time Added	Displays the time when the approved applications were added to the baseline.


**Note:**

TXOne Networks recommends switching back to **Operations Behavior Anomaly Detection Learn** mode before running the application updates.

Situational Awareness

The Situational Awareness page provides an overview and access to the detailed information to the risks detected against the established baseline.

The page is divided into the following blocks.



• Threat Detection and Response

StellarOne provides the agent's **Impact Risk** level at the top left of the page, and in the same block here list the number of suspicious activities for users to view the event log promptly. See the following sections for more information.

• Operation Behavior Highlights

In the Operation Behavior Highlight block on the top right of the page, StellarOne lists the status of **Baseline Deviation** and the number of detected baseline activities. Clicking the numbers will open respective pop-up windows. See the following sections for more information.

Threat Detection and Response

The agent's **Impact Risk** level is displayed in the **Threat Detection and Response** box, providing users the status of the agent in one glance. Along with the Impact Risk level, the number of the events are listed and categorized by their severity.

Clicking the numbers of the events will display below the filtered events' **Time**, **Event Type**, risk **Level**, and the **Action** button.

Clicking the **Action** button in the **Query Results** pane below will open a pop-up window to display the details of the event. See [Agent Events \(on page 180\)](#) for more information.

Operation Behavior Highlight

StellarOne list the **Baseline Deviation** status and the number of detected baseline activities in the **Operation Behavior Highlight** box.

• Connected IP's in Baseline

Clicking the number of **Connected IP's in Baseline** will open a pop-up window displaying a list of IP's that are in the baseline and have records of established connection to the agent.

• Accessed Ports (Inbound) in Baseline:

Clicking the number of **Accessed Ports (Inbound) in Baseline** will open a pop-up window displaying a list of ports that are in the baseline and have records of established inbound connection.

• Executed Applications in Baseline:

Clicking the number of **Executed Applications in Baseline** will open a pop-up window displaying a list of applications that are in the baseline and have execution records.

• Executed Scripts in Baseline:

Clicking the number of **Executed Scripts in Baseline** will open a pop-up window displaying a list of scripts that are in the baseline and have execution records.

• User Login in Baseline:

Clicking the number of **User Login in Baseline** will open a pop-up window displaying a list of login credential that are in the baseline and have login records.

Vulnerabilities

The Vulnerabilities page provides an overview of vulnerabilities found on the agent, and categorizes them based on critical, high, medium, and low.

The screenshot shows the StellarOne interface for the Vulnerabilities page. The sidebar on the left has filters for Critical (10), High (146), Medium (169), and Low (2548). The main content area shows a table of vulnerabilities. The table has columns: CVE ID, CVSS 4.0, Application/OS, Affected Version, and First Seen. The table is sorted by First Seen date, showing vulnerabilities from 2026-03-20T04:40:01+08:00 to 2026-03-20T04:40:01+08:00.

CVE ID	CVSS 4.0	Application/OS	Affected Version	First Seen
CVE-2024-5274	9.4	Google Chrome	Before 125.0.6422.112	2026-03-20T04:40:01+08:00
CVE-2024-4947	9.4	Google Chrome	Before 125.0.6422.60	2026-03-20T04:40:01+08:00
CVE-2023-6345	9.4	Google Chrome	Before 119.0.6045.199	2026-03-20T04:40:01+08:00
CVE-2024-4671	9.4	Google Chrome	Before 124.0.6367.201	2026-03-20T04:40:01+08:00
CVE-2024-7971	9.4	Google Chrome	Before 128.0.6613.84	2026-03-20T04:40:01+08:00
CVE-2023-2136	9.4	Google Chrome	Before 112.0.5615.137	2026-03-20T04:40:01+08:00
CVE-2017-8543	9.3	Windows 7 Professional Service Pack 1 (build 7601), 64...	-	2026-03-20T04:40:01+08:00
CVE-2019-0708	9.3	Windows 7 Professional Service Pack 1 (build 7601), 64...	-	2026-03-20T04:40:01+08:00
CVE-2015-1635	9.3	Windows 7 Professional Service Pack 1 (build 7601), 64...	-	2026-03-20T04:40:01+08:00
CVE-2017-0148	9.2	Windows 7 Professional Service Pack 1 (build 7601), 64...	-	2026-03-20T04:40:01+08:00

On the left side of the page, users can filter between critical, high, medium, and low level vulnerabilities. By default, **Critical** is selected. To the right of these filter buttons, a table is shown with the following columns:

Column Name	Description
CVE ID	The CVE ID, with a link to the US Government's National Vulnerability Database.
CVSS 4.0	The CVSS 4.0 (Common Vulnerability Scoring System version 4.0) of the vulnerability.
Application/OS	The application or OS that the vulnerability belongs to.
Affected Version	The version of the application or OS that is affected.
First Seen	The date and time when the vulnerability was first seen.

Group Policy Settings

The StellarOne console combines agents management and policy deployment by allowing you to organize agents into various groups, build up multi-level hierarchy among the groups, and deploy different policies to different groups when needed.

Two types of policy management are available for choice:

- Policy **Inherited**: The group policy is inherited from the parent group
- Policy **Customized**: The group policy is customized for specific groups by the StellarOne administrators




Note:

Self-managed: This special policy setting allows local agents to be free from StellarOne's policy management and instead, to be managed directly by the on-site operators. Though it's a policy setting, once enabled, the **Self-managed** status will be shown in the **Policy** column on the **Agents** screen.

Topics in this chapter include:

- [Go to the Group Policy Screen \(on page 176\)](#)
- [Group Policy Settings \(on page 176\)](#)

Go to the Group Policy Screen



1. Click the **Agents** tab in the top navigation bar of the StellarOne web console.
2. Click the **All** group, and then a screen displays the second level of groups/agents managed by StellarOne.
3. Navigate to the target group. Choose one of the ways to go to the group policy configuration page.
 - Click the link (**Inherited**, **Customized**, or **Self-managed**) in the **Policy** column.
 - Click the  Policy icon in the **Actions** column, and then click the **Policy** tab.
4. The **Policy** screen appears.



Note:

You can also click the  Policy icon of the **All** group to check its policy settings.


Group Policy Settings

Unlike the agent policy page, the group policy configuration page allows you to manage policy at the group level. Also, the group policy page displays information at the group level; thus, the links for directing users to the **General Info**, **Baseline**, or **Situational Awareness** at the agent level are not available.

At the group level, if the **Policy Inheritance** is toggled on, the custom exceptions menu appears and allows you to customize specific settings that will take precedence over the inherited policy.

The **Agent Only** labels show the main differences between the agent and group policy configuration pages. See the image below as an example:

Figure 9. An Example Showing the Main Differences between Agent & Group Policy Pages

**Note:**

- See [Settings for the Agent/Group Policy Screen \(on page 86\)](#) for the comparison between the options available in the agent view and those available on the group policy screen.
- See [Agent Policy Settings \(on page 108\)](#) for how to configure group policy settings.
- After making changes to this page, you may press the **Save Changes** or **Discard Changes** buttons to save or discard your changes. If you leave the page without pressing either button, you will be prompted to do so first.

Create Custom Exceptions to the Inherited Policy

You can create custom exceptions to the inherited policy at the group level, which transform the selected settings to customizable and associated changes will take precedence over the inherited policy. Meanwhile, the rest of the settings still remain inherited from the parent group

1. Go to the group policy page and toggle on **Policy Inheritance**.
2. The **Custom Exceptions** icon  appears.
3. Click the  and a pop-up window appears.
4. Select the settings you want to make customizable, and then click **Save**.

**Note:**

Only the enabled features are available for selection in the custom exceptions list.

5. On the **Policy** page, the **Custom Exception** icon  **Custom Exception** appears by the selected items.
6. You can now edit the selected items. The associated changes will take precedence over the inherited group policy.

Global Policy Settings

As groups and agents do not always inherit policies from their parent groups, settings such as Trusted Certificates and User-Defined Suspicious Objects often need to be configured repeatedly for each non-inherited group or agent. With Global Policy, Trusted Certificates and User-Defined Suspicious Objects can be applied automatically to all groups and agents, except Self-Management agents.

The following items can be configured with Global Policy:

1. Trusted Certificates
2. User-Defined Suspicious Objects

← GLOBAL POLICY

Function Type: StellarProtect

Policy

User-Defined Suspicious Objects (0)

Update new threat information to protect against suspicious objects not yet identified on your network.

[+ Add](#)

Hash/File Path	Type	Notes	Actions
No data to display			

Trusted Certificates (0)

The trusted certificates defined by users will be bypassed during scanning and will not be blocked by Application Lockdown.

[Import](#)

Issued To	Issued By	Hash	Actions
No data to display			

[Save Changes](#) [Discard Changes](#)

Chapter 6. Logs

This chapter describes how to access StellarOne-generated logs and the logs related to the agents, as well as includes detailed log information for advanced administrator management. Topics in this chapter include:

- [Agent Events \(on page 180\)](#)
- [Server Events \(on page 186\)](#)
- [System Logs \(on page 189\)](#)
- [Audit Logs \(on page 190\)](#)

Agent Events

The StellarOne collects activities on agents and log them in the **Agent Events**.

1. Mouse over the **Logs** tab in the top navigation bar of the StellarOne web console. A drop-down menu appears.
2. Click the **Agent Events**.
3. The **Agent Events** screen appears.
4. You can search for the most relevant events for troubleshooting or analysis by using the filter tool in the upper-right corner of the screen. See [Agent Events Filtering \(on page 182\)](#) for more details.



Note:

- For Stellar Agent (Windows)'s event IDs and corresponding log information, see [Log Descriptions for Stellar Agent \(Windows\) \(on page 252\)](#).
- For Stellar Agent (Windows-Legacy)'s event IDs and corresponding log information, see [Log Descriptions for Stellar Agent \(Windows-Legacy\) \(on page 282\)](#)

About Agent Events Screen

Figure 10. Agent Events Logs





Table 39. About Agent Events Screen

Item	Description
(1) Export	You can export log list as an .csv file by clicking the Export button. It provides a drop-down menu consisting of:

Table 39. About Agent Events Screen (continued)

Item	Description
	• Export Selected: This button is activated when you select the checkbox(es) next to the logs to export. • Export: This button is always activated for exporting a maximum of 100,000 log entries. • Include Event Details
(2) Filter	Provides the filter tool for finding the most relevant event logs for troubleshooting or analysis. See Agent Events Filtering (on page 182) for more details.
(3) Log display setting	You can specify the time range for viewing the logs generated within the specific period.
(4) Screen display setting	By clicking this button, you can customize the screen display by: • selecting how many logs to display per page • hiding certain contents by unselecting Time, Level, Event, Function Type, or Endpoint in the Customize Table Display window.
(5) Refresh	Provides manual refresh of the screen for the latest log outputs
(6) View Details	In Information or Critical level logs, you can view and print event details such as event information and agent information. In some of the Warning level logs, in addition to viewing and printing event details such as event information and agent information, you can also apply certain action to the detected files or blocked devices, such as Ignore, Delete, Quarantine, Add to Approved List, Grant One-Time Access, or Add to Baseline. See Agent Event Actions (on page 182) for more details.

Table 39. About Agent Events Screen (continued)

Item	Description
	Figure 11. An Example of Available Event Actions in Certain Warning Level Logs  The screenshot shows a window titled 'Event Details' with a close button (X) in the top right. Below the title bar is a timestamp '2023-01-23T18:52:09+08:00'. Under the 'Action' section, there are five buttons: 'Print', 'Ignore', 'Delete', 'Quarantine', and 'Add to Approved List'. The last four buttons are grouped together and highlighted with a red rectangular box. Below this is the 'Event Information' section, which lists 'Time' as '2023-01-23T18:52:09+08:00', 'Level' as 'Warning', and 'Event ID' as '2509'.

Agent Events Filtering

This section describes how to filter the **Agent Events** logs to find the most relevant log messages.

1. Go to **Logs > Agent Events**. Click the filter tool  in the upper-right corner of the screen, and then a drop-down menu appears.
2. Select **Add Filter**, and then the option menu appears.
3. Select the desired search criteria from the menu. The selected criteria will appear on the left side of the screen.
4. Click the criteria and specify the value by typing in the text field or selecting from the option menu.
5. Click **Apply** and then the screen will display the search result.
6. Click the close icon to remove the selected criteria one by one, or click **Clear all** to remove all of the selected criteria.
7. You can save the selected criteria as a filter by clicking the **Save filter** on the right side of the screen.
 - a. The **Save Filter** window appears. Specify the name of the filter in the **Filter Name** text field.
 - b. Click **Save** to complete the setting.
 - c. Click the filter tool  in the upper-right corner of the screen and the **Saved Filter** is available for selection.
 - d. Click the **Saved Filter** and then the target filter. The screen will display the search result.



Note:

You can change the name of the saved filter or delete it by clicking the **edit** or **remove** icon beside it.

Agent Event Actions

The following table shows the actions you can apply to certain warning level events.


Action	Description
Ignore	Performs no action to the detected file.
Delete	Deletes the detected file.
Quarantine	Moves the detected file to a quarantine folder on the agent-device.
Add to Approved List	Adds the detected file to the Approved List. See Stellar Agent (Windows) Application Lockdown (on page 127) or Stellar Agent (Windows-Legacy) Application Lockdown (on page 140) for more details.
Add to Baseline	Adds the detected file to the baseline. See Add to Baseline (on page 183) for more details.
Add to Suspicious Objects Blocklist	Adds the detected file to the blocklist. See Add to Suspicious Objects Blocklist (on page 184) for more details.
Add to Network Access Blocklist	Adds the detected network to the blocklist. See Add to Network Access Blocklist (on page 185) for more details.
Grant One-Time Access	Allow the blocked USB to access the endpoint temporarily until the USB is disconnected. See Grant One-Time Access (on page 185) for more details.
Release and add to Approved List	Ignore the quarantined file and add the file to the Approved List.

Add to Baseline

This section describes how to apply the **Add to Baseline** action when the relevant event occurs and the associated outcomes. By applying this action, you allow the detected anomalies to run on the device without further check.

1. To check agent events, go to **Logs > Agent Events**.
2. Find the **Warning** level events related to the Operations Behavior Anomaly Detection, and then click the **Event Details** icon in the **Action** column.
3. The **Event Details** window appears.
4. Click **Add to Baseline** to apply this action. The unrecognized application detected as shown in the following example will be added to the agent baseline as an approved application.

Figure 12. An example of the event with "Add to Baseline" action



5. To check if the application has been added to the agent baseline, go to the **Baseline** page.
6. Find the search and filter tool, select **Added From** and **Event action** as the criteria and click the search icon.
7. As a result, the table displays a list of the approved applications added from the event action **"Add to Baseline"**.

**Note:**

Since the baseline data are transmitted at the default or specified policy refresh interval, the result of the applied action may not appear in the **Baseline** immediately. You can shorten the policy refresh interval to make the result appear earlier. See [Set Policy Refresh Interval \(on page 87\)](#) for how to configure the settings.

Add to Suspicious Objects Blocklist

This section describes how to apply the **Add to Suspicious Objects Blocklist** action when the relevant event occurs and the associated outcomes. By applying this action, you block the application associated with the detected anomalies to run on the device without further check.

1. To check agent events, go to **Logs > Agent Events**.
2. Find the **Warning** level events related to the Operations Behavior Anomaly Detection – Application Behavior, and then click the **Event Details** icon in the **Action** column.
3. The **Event Details** window appears.
4. Click **Add to Suspicious Objects Blocklist** to apply this action. The application associated with the detected anomalies will be added to the Suspicious Objects Blocklist.
5. A confirmation window appears. Read it carefully and click **Confirm** if you decide to add the application to the Suspicious Objects Blocklist.

**Important:**



Once added, the application will be blocked from running on the endpoint unless removed from the Suspicious Objects Blocklist.

6. To check if the application has been added to the Suspicious Objects Blocklist, navigate to the target agent and then go to its **Policy** page.
7. Go to **Operations Behavior Anomaly Detection > Application Behavior**.
8. Find and click **Suspicious Objects Blocklist**. A pop-up window appears and displays a list of the blocked applications added from the event action "**Add to Suspicious Objects Blocklist**".

Add to Network Access Blocklist

This section describes how to apply the **Add to Network Access Blocklist** action when the relevant event occurs and the associated outcomes. By applying this action, you block the network access associated with the detected anomalies without further check.

1. To check agent events, go to **Logs > Agent Events**.
2. Find the **Warning** level events related to the Operations Behavior Anomaly Detection – Network Traffic, and then click the **Event Details** icon in the **Action** column.
3. The **Event Details** window appears.
4. Click **Add to Network Access Blocklist** to apply this action. The network associated with the detected anomalies will be added to the Network Access Blocklist.



Note: This action is available only when the event was triggered with the Operation Behavior Anomaly Detection set in **Enforce** mode.

5. A confirmation window appears. Read it carefully and click **Confirm** if you decide to add the network to the Network Access Blocklist.



Important:

Once added, the network access will be blocked from making connection to the endpoint unless removed from the Network Access Blocklist.


6. To check if the network has been added to the Network Access Blocklist, navigate to the target agent and then go to its **Policy** page.
7. Go to **Operations Behavior Anomaly Detection > Network Access**.
8. Find and click **Network Access Blocklist**. A pop-up window appears and displays a list of the blocked networks added from the event action "**Add to Network Access Blocklist**".

Grant One-Time Access

This section describes how to apply the **Grant One-Time Access** action when the relevant event occurs and the associated outcomes. By applying this action, you temporarily allow the blocked USB device to access until disconnected from the endpoint.

1. To check agent events, go to **Logs > Agent Events**.
2. Find the **Warning** level events related to blocked USB devices, and then click the **Event Details** icon in the **Action** column.
3. The **Event Details** window appears.
4. Click **Grant One-Time Access** to apply this action. The blocked USB as shown in the following example will be temporarily recognized as a trusted USB device and granted access until disconnected from the endpoint.

Figure 13. An example of the event with "Grant One-Time Access" action



Note:

By clicking **Edit Device Control Policy**, you will be directed to the policy page where you can add the blocked USB device to a policy-based trusted device list. The device added will then have permanent access to the target endpoint or group of endpoints.

Server Events

Activities on StellarOne Servers and configuration deployed on the Agents by StellarOne are logged and shown in the **Server Events** screen.

1. Mouse hover the **Logs** tab in the top navigation bar of the StellarOne web console. Click the **Server Events** option.
2. Click the Stellar Agent (Windows) or Stellar Agent (Windows-Legacy) tab, the configuration events deployed on the Agents by StellarOne appear.
3. Click the **StellarOne** tab, the StellarOne server event logs appear.

About Server Events Screen

Table 40. About Stellar Agent Server Events Screen

Item	Description
Export	Users can export log list as an .csv file by clicking the Export button. It provides a drop-down menu consisting of: • Export Selected: This button is activated when users select the checkbox(es) next to the logs to be exported. • Export All: This button is always activated for users to export all logs.  Note: A maximum of 10,000 logs can be exported.
Filter	This tool allows users to search for the relevant log messages for troubleshooting or analysis. Please refer to Server Events Log Filtering (on page 188) for procedures.
Log display setting	Users can customize the display period for logs.
Screen display setting	By clicking this button, users can customize the screen display by: • selecting how many logs to be displayed on one page • hiding certain contents by unchecking Time, User ID, Event Type, Endpoint/[Groups], or Status in the Customize Table Display window.
Refresh	The button allows users to manually refresh the screen for the latest log outputs.

Table 41. About StellarOne Server Events Screen

Item	Description
Export	Users can export log list as an .csv file by clicking the Export button. It provides a drop-down menu consisting of:

Table 41. About StellarOne Server Events Screen (continued)

Item	Description
	• Export Selected: This button is activated when users select the checkbox(es) next to the logs to be exported. • Export All: This button is always activated for users to export all logs.
Screen display setting	By clicking this button, users can customize the screen display by: • selecting how many logs to be displayed per page • hiding certain contents by unchecking Time, User ID, Event Type, Endpoint/[Groups], or Status in the Customize Table Display window.
Refresh	The button allows users to manually refresh the screen for the latest log outputs.

Server Events Log Filtering

This section describes how to filter the **Server Events** logs to find the most relevant log messages.

1. Go to **Logs > Server Events > Stellar Agent**. Click the **User ID** next to the search bar, and then a drop-down menu appears.
2. There are two types of log filtering based on the drop-down menu. Choose from either one listed below depending on your needs.
 - Select the **User ID** or **Endpoint Name**, and then type the search strings in the search field.
 - Select **Event Type**, and a drop-down menu with options of event types appears. Select one of them for viewing the relevant log records.



Note:

Please refer to [Server Event Log Descriptions for Stellar Agent \(Windows\) \(on page 281\)](#) for more details on various event types.

3. Click the search icon next to the search bar and then the screen will display the search result.
4. To clear the search criteria, close the filtering criteria appears above the **Export** button.



Note:

Please refer to [Server Event Log Descriptions for Stellar Agent \(Windows\) \(on page 281\)](#) and [Server Event Log Descriptions for StellarOne \(on page 343\)](#) in the Appendices for more details about event IDs and corresponding log information..

System Logs

Internal system processes generated by StellarOne Servers are logged and shown in the **System Logs**.

1. Mouse over the **Logs** tab in the top navigation bar of the StellarOne web console.
2. Click the **System Logs** option.
3. The **System Logs** screen appears.

About System Logs Screen

Figure 14. System Logs Screen




Table 42. About System Logs Screen

Item	Description
Export	Users can export log list as an .csv file by clicking the Export button. It provides a drop-down menu consisting of: • Export Selected: This button is activated when users select the checkbox(es) next to the logs to be exported. • Export All: This button is always activated for users to export all logs.
Filter	Users can filter logs by selecting or specifying certain severity level directly in the search bar. The severity levels are listed as below: • Emergency • Alert • Critical • Error

Table 42. About System Logs Screen (continued)

Item	Description
	• Warning • Notice • Information • Debug After users set the search criteria and click the search button, the screen displays the search result. Meanwhile, the filtering criteria appears above the Export button. Close it to clear the search criteria and return to the initial screen.
Log display setting	Users can customize how many logs to be displayed either by: • the number of the latest logs records • the logs generated within a particular period
Screen display setting	By clicking this button, users can customize the screen display by: • selecting how many logs to be displayed per page • hiding certain contents by unchecking Time, Severity, or Message in the Customize Table Display window.
Refresh	The button allows users to manually refresh the screen for the latest log outputs.

Audit Logs

The **Audit Logs** screen displays the user activities such as login, logout, or account creation/deletion.

1. Mouse over the **Logs** tab in the top navigation bar of the StellarOne web console.
2. Click the **Audit Logs** option.
3. The **Audit Logs** screen appears.

About Audit Logs Screen

Figure 15. Audit Logs Screen




Table 43. About Audit Logs Screen

Item	Description
(1) Export	Users can export log list as an .csv file by clicking the Export button. It provides a drop-down menu consisting of: • Export Selected: This button is activated when users select the checkbox(es) next to the logs to be exported. • Export All: This button is always activated for users to export all logs.
(2) Filter	This tool allows users to search for the relevant log messages for troubleshooting or analysis. Please refer to Audit Log Filtering (on page 192) for procedures.
(3) Log display setting	Users can customize how many logs to be displayed either by: • the number of the latest logs records • the logs generated within a particular period
(4) Screen display setting	By clicking this button, users can customize the screen display by: • selecting how many logs to be displayed per page • hiding certain contents by unchecking Time, Severity, User ID, Client IP, or Message in the Customize Table Display window.
(5) Refresh	The button allows users to manually refresh the screen for the latest log outputs.

Audit Log Filtering

This section describes how to filter the **Audit Log** to find the most relevant log messages.

1. Go to **Logs > Audit Log**. Click the **Severity** next to the search bar, and then a drop-down menu appears.
2. There are two types of log filtering based on the drop-down menu. Choose from either one listed below depending on your needs.
 - Select the **User ID** or **Client IP**, and then type the search strings in the search field for viewing logs related to certain user account or IP address.
 - Select the **Severity**, a search box with an arrow pointing downwards appears. Tap on it to see the options listed below. Select one of them for viewing the log records by different levels.
 - Emergency
 - Alert
 - Critical
 - Error
 - Warning
 - Notice
 - Information
 - Debug
3. Click the search icon next to the search bar, and then the screen will display the search result.
4. To clear the search criteria, close the filtering criteria appears above the **Export** button.

Chapter 7. Administration

This chapter introduces the StellarOne web console's administration settings, mainly grouped into four categories: **Account**, **Notification**, **Update**, and **System**.

Topics in this chapter includes:

- **Account**

- [Account Management \(on page 194\)](#)
- [Single Sign-On \(on page 202\)](#)

- **Notification**

- [SMTP Settings and Notification \(on page 207\)](#)
- [Scheduled Report \(on page 208\)](#)
- [Syslog Forwarding \(on page 209\)](#)
- [Import CA Certificates via CLI \(on page 209\)](#)

- **Update**

- [Proxy Settings \(on page 210\)](#)
- [Downloads/Updates \(on page 211\)](#)
- [Importing Firmware \(on page 217\)](#)
- [License \(on page 217\)](#)

- **System**

- [System Time \(on page 234\)](#)
- [Log Purge \(on page 235\)](#)
- [Importing SSL Certificate \(on page 236\)](#)
- [OT Intelligent Trust \(on page 237\)](#)
- [Service Integration \(on page 237\)](#)
- [StellarOne Pool \(on page 238\)](#)

Account

Topics in this section includes

- [Account Management \(on page 194\)](#)
- [Single Sign-On \(on page 202\)](#)

Account Management

Go to **Administration > Account Management** to manage user accounts for accessing the StellarOne web console.



The **Account Management** screen has five tabs:

1. Users: Allows users to view all users belonging to an account.
2. SSO User Groups: Allows users to view and create SSO User Groups.
3. Roles: Allows users to view all Roles.
4. Password Policy: Allows users to view and set the password policy, including minimum password length, password complexity, expiration period and lockout threshold.
5. Locked Users: User accounts shown here have been locked after exceeding the incorrect password attempts limit. If Automatic Unlock is enabled, StellarOne will automatically unlock accounts.

Table 44. About Account Management Screen - Users

Item	Description
+Add User	This button allows you to add account(s) for accessing StellarOne web console. See Add Accounts (on page 199) for instructions.
Delete	This button allows you to delete account(s). See Delete Accounts (on page 200) for instructions.
Actions	The Edit button allows you to edit a single user account. See Edit Accounts (on page 201) for instructions. The three dots More Actions button allows you to: • Generate an API Key: see Generate an API Key (on page 201) for instructions. • Delete a single user account: see Delete Accounts (on page 200) for instructions.

Table 44. About Account Management Screen - Users (continued)

Item	Description
Screen display setting	 By clicking this button, you can customize the screen display by: • selecting how many items to be displayed on one page • hiding certain contents by unchecking items related to the titles in the Customize Table Display window.
Account icon	 Click the account icon at the top-right corner of the screen to change your password or log off.

See [Account Types \(on page 195\)](#) for more information about the **Roles** page.

Account Types

StellarOne user accounts are categorized into three types as listed below.

Table 45. StellarOne Account Types

Account Types	Access Rights	Privileges
Admin	Full control	• Manage StellarOne: The privilege of configuring system settings • Manage Group: The privilege of creating, moving, or deleting groups • Account Management: The privilege of managing StellarOne accounts • Policy Configuration: The privilege of defining policy for Agents such as USB Control and Intelligent Runtime Learning

Table 45. StellarOne Account Types (continued)

Account Types	Access Rights	Privileges
Operator	Asset control	• Manage Group: The privilege of creating, moving, or deleting groups • Policy Configuration: The privilege of defining policy for Agents such as USB Control and Intelligent Runtime Learning
Viewer	Read only	• Read only for the dashboard, agent events logs, agent policy configurations, and StellarOne information.

Server Accounts Overview

TXOne StellarOne features web console accounts with different privileges and limitations. Use these accounts to configure StellarOne and to monitor or manage Stellar Agent (Windows) agents. The following table outlines typical StellarOne tasks and the account privileges required to perform them.

Table 46. StellarOne Account Types

Task	Account Privilege Allowed		
	Admin	Operator	Viewer
Dashboard	√		√
Configure Application Lockdown	√	√	
Configure Maintenance Mode	√	√	
Configure Device Control	√	√	
Add trusted files	√	√	

Table 46. StellarOne Account Types (continued)

Task	Account Privilege Allowed		
	Admin	Operator	Viewer
Add trusted USB devices	√	√	
Scan now	√	√	
Update Approved List	√	√	
Update agent components	√	√	
Deploy agent patch	√	√	
Check connection	√	√	
Deploy policies	√	√	
Policy refresh interval	√	√	
Collect event logs	√	√	
Import / Export (Approved List / agent configuration)	√	√	
Organize (edit description / move / delete)	√	√	
Configure group policy	√	√	

Table 46. StellarOne Account Types (continued)

Task	Account Privilege Allowed		
	Admin	Operator	Viewer
Configure global policy	√	√	
Monitor agent event logs	√	√	√
Monitor server event logs	√	√	
Monitor system logs	√	√	
Monitor audit logs	√	√	
Account management	√		
Single Sign-On	√		
System time settings	√		
Syslog forwarding	√		
Log purge	√		
Scheduled report	√		
Notification settings	√		
SMTP settings	√		
Proxy settings	√		

Table 46. StellarOne Account Types (continued)

Task	Account Privilege Allowed		
	Admin	Operator	Viewer
Downloads / Updates	√		
Firmware update	√		
SSL Certificate	√		
License management	√		
OT Intelligent Trust	√		
Service Integration	√		
StellarOne Pool	√		
Update Pool	√		
Global Policy	√		

Add Accounts

This section describes how to add user accounts for accessing StellarOne web console.

1. Log on to the web console using an account with the **Admin** role.



Note:

- The logon credentials entered here are case-sensitive.
- Only the account with the **Admin** role can manage user accounts.

2. Go to **Administration > Account Management**.
3. Click **Add User** button, and then the **Add User Account** window appears.
4. Specify the **Authentication Source** (**Local** or **SAML Identity Provider**).

- To add a **Local** user, specify the **ID** and **Name**.
- To add an **SAML Identity Provider** user, specify **Email for SAML Account Mapping** and **Name**.



Note:

To allow an SAML Identity Provider user to log in using Single Sign-On (SSO), click the **Single Sign On Configuration** link. Please refer to [Single Sign-On \(on page 202\)](#) for procedures.



Note:

The **ID**, **Name**, and **Email for SAML Account Mapping** entered here are case-sensitive.

5. **Role:** Select among the account roles **Admin**, **Operator** or **Viewer** (Default). Please refer to [Account Types \(on page 195\)](#) for more details on the account privileges.
 - For a **Temporary** user, specify the **Local Password** and re-type it for confirmation.
6. **Group Control:** Select the groups the target account is allowed to access or view.
7. Click **Confirm** to complete the user account creation.

Delete Accounts

This section describes how to delete user accounts that are no longer needed.

1. Log on to the web console using an account with the **Admin** role.



Note:

- The logon credentials entered here are case-sensitive.
- Only users logged on with the **Admin** role can manage user accounts.

2. Go to **Administration > Account Management**.
3. There are two ways of deleting user accounts.
 - To delete only one user account at a time, under the **Actions** column, click the trash-can icon corresponding to the target user account.
 - To delete multiple user accounts at a time, click the checkboxes next to the user accounts you want to delete, and then click the **Delete** button next to the **Add User** button.
4. The **Delete User Account** window appears.
5. Click **Confirm** to delete the user account(s).

Edit Accounts

This section describes how to edit user accounts that have been created.

1. Log on to the web console using an account with the **Admin** role.



Note:

- The logon credentials entered here are case-sensitive.
- Only the account with the **Admin** role can manage user accounts.

2. Go to **Administration > Account Management**.
3. Under the **Actions** column, click the edit icon corresponding to the target user account.
4. The **Edit User Account** window appears.
 - For a **Local** user, the **Role**, **Name**, **Password**, **Group Control**, and **Description** of an account can be edited.
 - For an **SAML Identity Provider** user, the **Role**, **Name**, **Group Control**, and **Description** of an account can be edited.



Note:

To allow an SAML Identity Provider user to log in using Single Sign-On (SSO), click the **Single Sign On Configuration** link. Please refer to [Single Sign-On \(on page 202\)](#) for procedures.

5. Click **Confirm** to complete editing user account(s).

Generate an API Key

Users can generate API keys and query data from agents via the open API. The expiration dates of the API keys can be set for different user accounts to increase account management efficiency.

1. Log on to the web console using an account with the **Admin** role.



Note:

- The logon credentials entered here are case-sensitive.

2. Go to **Administration > Account Management**.
3. Under the **Users** tab, find the user ID you want to modify and go to the kebab menu under **Actions** at the right of the screen.
4. Click on the kebab menu, and then select the **Generate an API Key** option.
5. The **Generate an API Key** window appears. Click the date picker and choose an expiration date on the pop-up calendar. Click **Confirm**.
6. An API key is generated. Click the clipboard for copying the generated API key.



Important:

Make sure to back up the copied API key before proceeding to the next step. The API key will not be displayed again for security reasons.

7. Click **OK**.
8. Check the result under the **API Key Expiry Date** or mouse over above the kebab menu of the user account, and the expiration date of the API key will appear.

Single Sign-On

Users who log on with the SAML Identity Provider (IdP) user account can choose to complete the Single Sign-On (SSO) configuration, which allows to access multiple applications and services using a single set of login credentials.

1. Log on to the web console using an account with the **Admin** role.
-



Note:

The logon credentials entered here are case-sensitive.

2. Go to **Administration > Single Sign-On**.
 3. Click the **Download** button to download the StellarOne metadata XML file.
 4. Import the StellarOne metadata XML file to your IdP.
-



Note:

See [Configuring ADFS as SAML IdP for SSO \(on page 203\)](#) to configure the specific settings required to integrate your IdP with StellarOne SSO.

5. Download the IdP metadata XML file from the following URL on a computer connected with the IdP server:

```
https://<adfs hostname>/federationmetadata/2007-06/  
federationmetadata.xml
```

6. Click the **Upload** button to upload the IdP metadata XML file to StellarOne web console to complete the SAML 2.0 SSO configuration.
-



Important:



The IdP metadata XML file must be re-uploaded if there is a configuration change on the IdP.

7. After the IdP metadata XML file is uploaded, the **Test Connection** button will appear.
8. Click **Test Connection** to test the connectivity between the StellarOne and IdP servers.



Note: If the IdP and StellarOne servers are connected to different networks, the IdP connection test may fail, yet the SAML SSO may still work. Try logging in with SSO and if invalid logon error message appears, see [Resolving the SSO Issue \(on page 204\)](#) to check the email settings in IdP server or the system time synchronization in IdP and StellarOne servers.

Configuring ADFS as SAML IdP for SSO


The following instructions takes Windows ADFS server as an example for how to integrate your SAML IdP with StellarOne SSO.

1. Open Windows **Server Manager** and go to **Tools > AD FS Management**.
2. Right-click on **Relying Party Trusts** and select **Add Relying Party Trusts**.
3. The **Add Relying Party Trust Wizard** appears. Go through the steps and ensure you configure the specific settings as described below:
 - a. **Import StellarOne file:** In **Select Data Source** step, select **Import data about the relying party from a file** and import the StellarOne metadata xml file.
 - b. Proceed with the steps and in the **Finish** step, ensure you select **Open the Edit Claim Rules dialog...** and click **Close**.
 - c. **Add rules:** The **Edit Claim Rules for...** window appears. Click **Add Rule...** and the **Add Transform Claim Rule Wizard** appears.
 - i. In **Choose Rule Type**, select **Send LDAP Attributes as Claims**.
 - ii. In **Configure Claim Rule**, select **Active Directory** from the **Attribute store** menu. In the **LDAP Attribute**, select **User-Principal-Name or E-Mail-Addresses**, and **E-Mail Address** in the **Outgoing Claim Type** field, and then click **Finish**.
 - iii. Click **Add Rule** to add the second rule.
 - iv. In **Choose Rule Type**, select **Transform an Incoming Claim** and proceed. Ensure you select **E-Mail Address**, **Name ID**, and **Email** as the incoming claim type, outgoing claim type, and outgoing name ID format, and then click **Finish**.
4. The window displaying the two rules configured for StellarOne SSO will appear. Proceed with downloading the IdP metadata file. See [Single Sign-On \(on page 202\) Step 5](#) for more details.

Resolving the SSO Issue

1. Open the **Users** folder under the **Active Directory Users and Computers** in IdP server.
2. Right-click on the user account used for SSO, and then go to **Properties > General**.
3. Check the **E-mail** field. Make sure the email input here is consistent with the account email used for accessing StellarOne web console.

Figure 16. Resolving SSO Issue - Email Check



4. Make sure the system time in IdP and StellarOne servers is synchronized. You can choose one of the ways listed below to configure the associated settings.
 - a. Sync time with an NTP server via StellarOne:
 - i. Log on StellarOne and go to **Administration > System Time**.
 - ii. Click the **Synchronize system time with an NTP server** to enable it.
 - iii. Click **Test Synchronization** to check if the sync was successful.




Note:

The default NTP server is pool.ntp.org.

- b. Sync time via VMware Tools:

- i. Ensure the time in the IdP server and the host PC running the StellarOne Virtual Machine (VM) is synchronized.
- ii. Open the VM settings of StellarOne and go to **Options > VMware Tools**.
- iii. Click the checkbox of **Synchronize guest time with host**, and then click **OK**.

Figure 17. Virtual Machine Settings - Time Synchronization



Group Single Sign-On

The following instructions show how to enable SSO (Single Sign-On) for an entire Active Directory group, saving time for organizations with large teams. After you have already completed the [Configuring ADFS as SAML IdP for SSO \(on page 203\)](#) setup, complete the following steps:

1. Open **Server Manager** and go to **Tools > AD FS Management > Relying Party Trusts**.
2. Locate the Relaying Party Trust associated with your StellarOne server.
3. Right-click on the Relaying Party Trust and select **Edit Claim Issuance Policy**.
4. Select the **email** rule and click **Edit Rule**.
5. Create a new LDAP attribute, and select **Token-Groups - Unqualified Names**.
6. In the Outgoing Claim Type column for the row you just created, select **Group**.

Mapping of LDAP attributes to outgoing claim types:

	LDAP Attribute (Select or type to add more)	Outgoing Claim Type (Select or type to add more)
▶	E-Mail-Addresses ▼	E-Mail Address ▼
	Token-Groups - Unqualified Names ▼	Group ▼
*	▼	▼

7. Click **OK** to save and exit the menu.
8. In StellarOne, go to **Administration > Account Management > SSO User Groups**.
9. Click **Add Access Group**.
10. Enter a Group Name of your choice.
11. Enter the AD Group Name, ensuring that it mirrors the group name in your AD Server.
12. Select a Role.

13. Configure Group Control. Any checked groups will be accessible to users in the AD group.

Create SAML SSO Access Group

×

Create a rule to manage users with SAML SSO. Users with the same AD group ID will have the same group access. Before creating the rule, configure SAML SSO in Admin > [Single Sign-On](#).

Group Name*

TestGroup

Description

AD Group Name*

TestGroup

Description (Optional)

+

Role*

Operator

▼

Group Control*

☒ All (2)

Confirm

Cancel

14. Click **Confirm** to save.
15. Verify that the setup was completed successfully by logging into StellarOne using a user account that belongs to the configured AD group.

Setting SAML Audience for SSO



Note: This setting is only required for IDP servers that need to manually configure the SAML audience.

1. Go to **Administration > Single Sign-On**.
2. Click the **Download** button to download the StellarOne metadata XML file.
3. Copy the **entityID** value.

```
<EntityDescriptor xmlns="urn:oasis:names:tc:SAML:2.0:metadata"
validUntil="2025-04-20T11:02:36.154Z" entityID="https://10.8.150.163/rest/admin/saml/spmeta">
  <SPSSODescriptor xmlns="urn:oasis:names:tc:SAML:2.0:metadata"
validUntil="2025-04-20T11:02:36.153513994Z"
protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol" AuthnRequestsSigned="false"
WantAssertionsSigned="true">
    <SingleLogoutService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
Location="https://10.8.150.163/saml/slo" ResponseLocation="https://10.8.150.163/saml/slo">
</SingleLogoutService>
```

4. Change the the **saml:Audience** value on IdP server by pasting the entityID.
5. Log in SAML again.

Notification

Topics in this section includes:

- [SMTP Settings and Notification \(on page 207\)](#)
- [Scheduled Report \(on page 208\)](#)
- [Syslog Forwarding \(on page 209\)](#)
- [Import CA Certificates via CLI \(on page 209\)](#)

SMTP Settings and Notification

The settings allow users to receive notifications of warning or outbreak events by emails.

1. Go to **Administration > SMTP Settings** for specifying the SMTP server setting required for notification sending.
2. Specify the **Server address**, **Port**, and **Sender**.
3. Specify the **Security Mode** by clicking **STARTTLS**, **SMTPS**, or **None**.
4. (Optional) If the SMTP server requires authentication, toggle on **SMTP server requires authentication**. Specify the **User name** and **Password** as the SMTP server authentication credential.
5. Click the **Send Test Email** button to send a test email from StellarOne (This step is essential for *Step 13*).
6. Click **Save** to complete the SMTP setting.
7. Go to **Administration > Notification** for notification criteria and email setting.
8. Under the **Warning Level Agent Events**, click the **Send warning level agent events** toggle to enable it.



Note:

When the toggle is enabled, StellarOne console will send a notification to the specified email when an incident that triggers a **Warning** level events occurs.

9. Under the **Outbreak**, click the **Send outbreak notifications** toggle to enable it.



Note:

When the toggle is enabled, StellarOne console will send a notification to the specified email when more than a specified number of open warning messages have appeared in a specified time period.

10. Define an outbreak by the number of detections and the detection period.
 - Specify the number of occurrences of an event in the field of **Number of warnings in a time period** (1- 20000).
 - Specify the time frame during which the event has occurred in the field of **The time period of those warnings** (1 - 60 minutes).
11. Under **Email Notifications**, specify the email address for receiving the notifications in the **Recipient List** field.
12. Click **Save** to complete the setting.
13. Go to the specified email box to check if you receive the test email sent from StellarOne (see *Step 5*).

Scheduled Report

By configuring the **Scheduled Report**, users can receive a list of all reports that automatically generate on a user-defined schedule. The **Scheduled Report** screen also provides basic information about previously configured schedules and recipients, as well as allows users to enable and disable sending scheduled reports.

1. Go to **Administration > Scheduled Report**.
2. Click **Add**. The following options appear on the Customize Scheduled Report menu.

Settings	Description
Report Name	The name of the scheduled report.
Contents	Contents of the scheduled report, options include: ◦ Executive Summary ◦ Security Monitoring ◦ Vulnerability ◦ Assets
Data Period	Data period for the report contents, options include: ◦ Yesterday ◦ Last 3 days ◦ Last 7 days (Default) ◦ Last 14 days ◦ Last 30 days ◦ Last 90 days ◦ Last 180 days
Frequency	Set the frequency and start time for the scheduled reports on a daily, weekly, or monthly basis.  Note: It is recommended not to select the date 29th, 30th, or 31st for monthly update frequency. This helps prevent the system from bypassing the update in the month that does not contain the date 29th, 30th, or 31st.

Settings	Description
Time	Time that the scheduled report should be sent.
Send scheduled reports	Whether or not the scheduled report should be sent.
Recipient List	The recipients who will receive the scheduled report. Use a semicolon (;) between each address.

3. Click **Save** to save the settings.

Syslog Forwarding

Users can forward the Agent Events, Server Events, System Logs and Audit Log to one or more external Syslog servers for increasing monitoring and management capabilities. TXOne StellarOne console forwards logs in the Common Event Format (CEF). Make sure your Syslog server supports the Common Event Format (CEF).

1. Go to **Administration > Syslog Forwarding**.
2. Click the **+Add** button.
3. On the pop-up **Add Syslog Server Profile** window, specify the **Server Address**, **Protocol**, **Port**, and a **Profile Name** for this server profile.
4. (Optional) To start forwarding the syslog immediately after creating, toggle on the switch of **Start forwarding logs now**.
5. Click **Add**.
6. Go back to the Syslog Forwarding window, click the toggle in the Syslog Forwarding to start forwarding logs to the selected server.



Tip:

To edit or delete a created server profile, click the respective icons in the **Action** column.

See [Stellar Agent \(Windows\)/Stellar Agent \(Windows-Legacy\) Syslog Content - CEF \(on page 354\)](#) or [StellarOne Syslog Content - CEF \(on page 370\)](#) in the Appendices for details about the logs forwarded in the Common Event Format (CEF).



Note:

You can create up to 3 servers for syslog forwarding. However, take into consideration that using multiple forwarding servers may consume more resources, such as CPU, memory, and the internet bandwidth.

Import CA Certificates via CLI

Administrators can import trusted CA certificates to StellarOne via the CLI.



Note: StellarOne only supports CA certificate (X.509) version 3.0.

1. Open the StellarOne CLI. Refer to **Chapter 4 of the Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) Installation Guide** for instructions and details.
 2. Type **trust-ca add '<meta information of CA>'** and press enter.
 3. Paste the certificate's ID, and then press **Enter**.
 4. Follow the instructions on the screen to restart the service.
-



Note:

- a. To list all certificates, use *trust-ca ls* command.
 - b. To show a specific certificate, use *trust-ca show <uuid1>* command.
 - c. To remove a certificate, use *trust-ca rm <certificate ID>* command.
-

Update

Topics in this section includes:

- [Proxy Settings \(on page 210\)](#)
- [Downloads/Updates \(on page 211\)](#)
- [Importing Firmware \(on page 217\)](#)
- [License \(on page 217\)](#)

Proxy Settings

There are three proxy settings: Proxy Settings for StellarOne to internet, Proxy settings for StellarOne to Agent communications, and Proxy Settings for Agent to StellarOne communicates.

1. Go to **Administration > Proxy**.
2. Toggle on the **Proxy Settings...** to enable below settings.
 - **Proxy Settings for StellarOne to internet**
 - **Proxy Settings for StellarOne to Agent communications**
 - **Proxy Settings for Agent to StellarOne communications**
3. To configure proxy settings for updates:

- a. Select the HTTPS or HTTP protocol.

**Note:**

For **Proxy Settings for Agent to StellarOne communications**, only HTTP proxies are supported.

- b. In the **Server Address** field, specify the IPv4 address or FQDN of the proxy server.
- c. Specify the **Port**.
- d. If your proxy server requires authentication, select **Proxy server requires authentication** and enter your credentials.
- e. Click **Save**.
-

**Tip:**

To configure the proxy settings used by StellarOne when sending messages to Stellar Agent:

- **Before installation:** Add the proxy information to the configuration file in the Agent's installer package and save the proxy settings. The settings will then be included in the Agent's installer package after the Agent's installer package is repacked.
 - **After installation:** Use the `opcnd.exe` or `SLCmd.exe` Command Line Interface tool on the local Stellar Agent (Windows) or Stellar Agent (Windows-Legacy) Agent.
-

Downloads/Updates

The **Downloads/Updates** page allows users to execute below tasks:

- Configuring scan component for StellarOne
- Manually Update Scan Component for StellarOne
- Downloading the Agent Installer Package or `Group.ini` file for [Group Mapping \(on page 215\)](#).
- Importing or deleting patch files for the agents
- Update Pool

Configuring Scan Component for StellarOne

1. Go to **Administration > Downloads/Updates > StellarOne**.
2. To start the component update for StellarOne immediately, click the **Update Now** button in the **Scan Component** section.



Note:

- By clicking the **Update Now**, StellarOne will download and update the latest components. All of the pattern and engine versions available are listed under the **Update Now** button.
- You can refer to the **Last Updated:** near the **Update Now** button for the last time the scan component was updated.
- For SDP and VDS patterns updates, using the **Update Now** button will also complete the task.

3. To schedule for the component update, find and click the **Scan Component Update Schedule (StellarOne)**.

- a. The **Scan Component Update Schedule (StellarOne)** window appears.
- b. Toggle on the **Schedule Update**.
- c. Click the radio buttons next to **Frequency** to set the frequency by **Daily**, **Weekly**, or **Monthly**.



Important:

It is recommended NOT to select the date 29th, 30th, or 31st for monthly update frequency. This helps prevent the system from bypassing the update in the month that does not contain the date 29th, 30th, or 31st.

- d. Click the **Start Time** to determine when to start the scheduled scan component update.



Note: For SDP and VDS pattern updates, using the **Scan Component Update Schedule (StellarOne)** button will also complete the task.

4. To specify the download source for StellarOne regarding different network configurations, find and click the **Scan Component Update Source**.

- a. The **Scan Component Update Source** window appears.
- b. In the **Scan Component Update Source (StellarOne)** section:
 - If the StellarOne server can connect to the ActiveUpdate server, select the **ActiveUpdate server**, the component update will be downloaded directly from the ActiveUpdate server.
 - If the StellarOne server can not connect to the ActiveUpdate server or if users host an update server in an internal network, select **Other update source** and specify the URL address in the text field.

5. To specify the download source for agents regarding different network configurations or agent types, find and click the **Scan Component Update Source**.
 - a. The **Scan Component Update Source** window appears.
 - b. In the **Scan Component Update Source (Agents)** section:
 - If the agents can connect to StellarOne server, select **Update from StellarOne** to download the component update directly from the StellarOne server.
 - If the agents can not connect to StellarOne server or if users host an update server in an internal network, select **Other update source** and specify the URL address in the text field.

Manually Update Scan Component for StellarOne

This feature supports users to manually update the Scan Component when in an air-gapped environment or when the scheduled updates are not available. The process can be divided into 2 parts: **Download the patterns from MyTXOne** and **Upload it on StellarOne**.



Note:

For Debian OS, the SDP and VDS updates also utilize this feature. Follow the instructions in this section to perform manual OS component update.

Download patterns from MyTXOne

1. Log in the **MyTXOne** page and then click **Pattern** on the left panel.
2. On the filter on top of the page, select **Endpoint Protection** in the **Product Line** field.



Note:

- The patterns are categorized in four packages: under **AV Pattern** section, there is **Anti-Virus Patterns** (in two file format), and under **Stellar Pattern** section, there are **Grey Detection Pattern**, **Protect OT Vault Pattern**, and **Threat-Detection Pattern**.
- For Debian SDP pattern update, click **Patten** on the left panel. On the filter on top of the page, select **Endpoint Protection** in the **Product Line** field. In the displayed page, find the package in the **SDP Pattern** section.

3. Click **Download** of the package of your selection to download and save it in your drive.

Upload it on StellarOne

1. Go to StellarOne. Click **Administration > Downloads/Updates > StellarOne**.
2. Click the **Manual Update** button and then on Manually Update Scan Component pop-up window, select the package that was downloaded previously.
3. Click **Update**.



Note:

- Upon clicking the **Update** button, StellarOne will start the pattern upload and update process. All users will not be able to update patterns until the process is concluded
- The process will be failed if the downloaded package is not the latest version pattern file or it is the same as the version in StellarOne.

4. The **Scan component (pattern) has been successfully updated** message will appear on the screen after the process is successfully completed.

Downloading Agent Installer Package/Group.ini File

1. Go to **Administration > Downloads/Updates > Agent**.
2. To download the latest Agent Installer Package, select the Agent Edition, your required OS, and click **Download**.

A zipped folder is downloaded. Extract the folder and proceed with the installation for the agents. Please refer to the Stellar Agent (Windows) [Installation Guide](#) for more details.



Note:

Applying or replacing a StellarDiscover add-on license does not trigger a repack of the Agent Installer Package. Installer packages continue to use the StellarICS primary license profile.

On a server with a StellarICS primary license and a StellarDiscover add-on license, the following installer packages are available:

Table 47. Available Agent Installer Packages

Agent Edition	Operating system
Protect	Windows, Linux
Discover	Windows

3. (Optional) If the StellarOne uses proxy to communicate with the agents, click the **Proxy** link or go to **Administration > Proxy** to complete the proxy configuration before downloading the installer package. Please refer to [Proxy Settings \(on page 210\)](#) for detailed procedures.
4. (Optional) To directly register the agent to a specific group via StellarOne console, click the **download a Group.ini** link and add it into the agent's installer package. Please refer to [Group Mapping \(on page 215\)](#) for more details.

Group Mapping

This function allows users to directly register agent to a specific group via the StellarOne web console.

1. Go to **Administration > Downloads/Updates**.
2. Select the **Agent** tab.
3. Click **Download** to download the Installer Package.
4. Click the **download Group.ini** link.
5. The **Select a group** window appears.
6. Select a group for the target agent and click **Download**. Click the **Close** button to close the window.
7. A file named `Group.ini` has been downloaded. Place the `Group.ini` file as the top-level file in the installer package of the target agent.
8. Run the installation on the target agent. Make sure the agent is connected to StellarOne console during the installation process.
9. Users can check the StellarOne console and the on-site target agent to see if the agent is successfully registered.

Importing/Deleting Agent's Patch

1. Go to **Administration > Downloads/Updates > Agent > Import Patch Files**.
2. Select **Stellar Agent**, **Stellar Agent (Windows-Legacy)** or **Stellar Agent (Linux)** to determine the target agent.
3. Click **Import** to import the target patch file.
4. A **Import Patch** window appears. Click the radio button to determine the target agent.
5. Click **Select File** to select the patch file to import.



Important:

Be sure to select the patch file that matches the target agent.



Tip:

Click the **Agents** link to be directed to the **Agents** screen, and then use the **Update** button to deploy the imported patch to the target agents. See [Deploy Agent Patches \(on page 75\)](#) for instructions.

6. To remove existing patch files on StellarOne, select the target files and then the **Delete** button appears next to the **Import** button. Click **Delete** to remove the selected entries.

Update Pool

To effectively utilize the resource of the StellarOne server, you can assign agents as component update replay agents. So instead of connecting to the StellarOne server for component updates, the agents will receive updates from the assigned agents serving as update source. You can manage all the Update Agents in the **Update Pool** and their recipients on the **Update Pool** page under the **Administration** tab on the web console.

Create an Update Pool

Follow the instructions below to create an Update Pool.

1. Go to **Administration** in the top navigation bar of the StellarOne web console. Select **Downloads/Updates**.
2. Click the **Update Pool** tab.
3. Click **+Create Update Pool**.
4. Specify a **Pool Name**. Click **Confirm**.



Note:

- The Pool Name must be unique.
 - A pool name can be up to 128 characters long.
 - To delete an update pool, click the icon in the **Action** column then click **Remove**. After an Update Pool is removed, its **Recipient Groups** will default back to StellarOne as an component update source.
 - You can create up to 100 Update Pools.
-

Manage Update Agents

Follow the instructions below to add and remove update agents for a pool.

1. Go to **Administration** in the top navigation bar of the StellarOne web console. Select **Downloads/Updates**.
2. Click the **Update Pool** tab.
3. Click the pencil icon in the **Update Agents** column of a pool.
4. To add an update agent to the pool, check the box next to it. To remove an update agent out of the pool (revoke update agent), uncheck the box.



Note:

- The agents have to be assigned as an **Update Agent** first to appear in the **Update Agents** list. See [Assign Update Agents \(on page 63\)](#) for more details
 - You can assign up to 10 Update Agents to a pool.
-

5. Click **Assign** to save the changes. The changes will apply after policy sync.

Manage Recipient Groups

Follow the instructions below to add and remove Recipient Group that are receiving the component updates form the Update Agents.

1. Go to **Administration** in the top navigation bar of the StellarOne web console. Select **Downloads/Updates**.
2. Click the **Update Pool** tab.
3. Click the pencil icon in the **Recipient Groups** column of a pool.
4. To add an agent group to the recipients, check the box next to it. To remove an group out of the pool, uncheck the box.
5. Click **Confirm** to save the changes. The changes will apply after policy sync.

Importing Firmware

StellarOne Update:

- Go to **Administration > Firmware**.
- Under StellarOne Update, select **Upload ACF File**.
- Select the new firmware and upload.
- Follow the on-screen instructions.



Note:

Before executing the firmware upgrade, please create a back up of the VM files first.


Operating System Component Update:

- Download Debian OS component patterns from MyTXOne.
- Go to **Administration > Firmware**.
- Under Operating System Component Update, select **Upload ACF File**.
- Select the downloaded Debian OS component pattern and upload.
- Follow the on-screen instructions.



Note:

For Debian OS component update, follow the instructions as the banner shows to restart StellarOne. StellarOne will still work if it is not restarted, however, the component updates will take effects only after it is restarted.



License

Topics in this section includes:

- [About the License Screen \(on page 217\)](#)
- [License Management \(on page 221\)](#)
- [Discover Add-on License \(on page 224\)](#)
- [License Editions \(on page 230\)](#)

About the License Screen

Go to **Administration > License**. The following table lists details about the **License** page.

Figure 18. The License Screen




Table 48. About the License Screen

Item	Description
Renew License Key	This button is for license renewal using the same license key. Refer to Renew License with the same License Key (on page 221) for more details.
New License Key/File	This button is for license activation using new license key or license file. Refer to New License Key/File (on page 223) for more details.  Note: This button can also be used for other purpose such as license renewal using the license file. Refer to Renew License by Importing License File (on page 222) for more details.

Table 48. About the License Screen (continued)

Item	Description
License	Displays current license edition for Stellar product. Refer to License Editions (on page 230) for more details. Applying a StellarDiscover add-on license does not change the license edition shown here. When a StellarDiscover add-on license is applied to a StellarICS primary license, this field continues to display the StellarICS edition.
License Type	• Full: a full version that is officially authorized. • Trial: a trial version with excluded features or limited functions. • Perpetual: provides permanent use and 5-year technical support.
Seats	Specifies current number of agents managed by StellarOne and the total number of agents that can be managed by StellarOne. For example, Seats: 2/10 means: • 2 agents are currently managed • Up to 10 agents can be managed  Note: Overseat is triggered when seat in use exceeds the seat count; the agents that can not be managed by StellarOne due to overseat will be classified as "Inactive Agents" on the Agents screen. See Filter Options for Agents/Groups (on page 64) for more details. When a StellarDiscover add-on license is effective, this field reports StellarICS seat usage only. Discover agents are not counted against the StellarICS seat total; they are reported separately in the Deployed Discover Agents field. When no StellarDiscover add-on license is applied, or when the applied add-on license has reached its hard expiration date, all agents, including Discover agents, are counted against the StellarICS seat total.

Table 48. About the License Screen (continued)

Item	Description
Status	• Activated: The existing license is effective. • Expired: The existing license is out of date.  Note: It is recommended to renew license promptly to protect your devices against cybersecurity threats. Refer to one of the methods listed below for license renewal. ◦ Renew License with the same License Key (on page 221) ◦ Renew License by Importing License File (on page 222)
Expiration	Displays the effective date of existing license.
License Key	The License Key required for activating StellarOne.
Last Updated	Displays the last time the License Key is updated.
Bound License and Expiration	Displays the edition and expiration date of the StellarDiscover add-on license bound to the current StellarICS primary license, for example Stellar Discover, 2026-09-30. This field appears only after a StellarDiscover add-on license has been applied. The date shown is the license expiration date; the add-on license remains effective until its hard expiration date, which is the expiration date plus the grace period. See Discover Add-on License Expiration (on page 229) for more details.
Deployed Discover Agents	Displays the total number of Discover agents registered with this StellarOne server. This field appears only after a StellarDiscover add-on license has been applied.
Learn More	The link directs users to the Online Help web page for more details on license.
Download the Latest License File	The link is used to download the latest license file to renew license for standalone agents.

License Management

Users can renew license or activate new license via the StellarOne web console.

License Renewal

Choose one of the ways to renew license based on your license data:

- [Renew License with the same License Key \(on page 221\)](#)
- [Renew License by Importing License File \(on page 222\)](#)

Renew License with the same License Key

1. Go to **Administration > License**
2. Click the **Renew License Key** button.
3. A message with **The License has been updated successfully** appears. The **Last Updated** shows the latest license renewal date and time.



Note:

See [Resolving Licensing Issues \(on page 244\)](#) if licensing related error messages appear.

Refreshing a Discover add-on license. When a StellarDiscover add-on license is applied, clicking **Renew License Key** refreshes the StellarICS primary license and the StellarDiscover add-on license together in a single operation. After the refresh completes, seat usage and agent activation are recalculated.

Table 49. Outcomes of a Combined License Refresh

Primary license refresh	Add-on license refresh	Overall result
Succeeds	Succeeds	The renewal succeeds. Both licenses are updated.
Succeeds	Fails	The primary license renewal succeeds and the primary license is updated. The StellarDiscover add-on license is not updated.
Fails	Succeeds	The renewal fails. The server license refresh is treated as failed.
Fails	Fails	The renewal fails.



Note:



If the add-on license fails to refresh while the primary license renewal succeeds, the success message on the **License** page refers to the primary license only. The **License** page does not display an **Expiration** date for the StellarDiscover add-on license, so the outcome of the add-on refresh is not shown on screen. If you suspect that the add-on license was not refreshed, check your network and proxy settings, and then click **Renew License Key** again.

Renew License by Importing License File

The license file can be used when StellarOne has no Internet connection.

1. Go to **Administration > License**
 2. Click the **New License Key/File** button.
 3. The **New License** window appears.
 4. Click **License File**.
 5. Select the license file (a .txt file) to import.
-



Note:

If you don't have the license file on hand, refer to [Getting the License File \(on page 222\)](#).

6. Click **Apply**.
 7. A success message appears. The updated license information will be shown on the **License** page.
-



Note:

See [Resolving Licensing Issues \(on page 244\)](#) if licensing related error messages appear.

Getting the License File

If the given license format is License Key, you can use it to download the license file, which can be used to activate a new license or renew the current license when StellarOne has no Internet connection. To get a license file, follow procedures below.

1. Go to **Administration > License**
 2. Click the **New License Key/File** button.
 3. The **New License** window appears.
 4. When you log on StellarOne using your new credentials after the **Login Information Setup** procedure, the **License Activation** window appears.
 5. Click **License File**.
 6. Click **Copy License File Download Link** at the bottom of the **New License** window.
-



Important:

A License Key is required for downloading a License File. An Activation Code cannot be used to download a License File. See [Comparison of License Formats \(on page 24\)](#) for more details.

7. **The Download Link has been copied** toast message appears.
8. Open the copied link in a web browser on a computer with Internet connection.
9. You will be directed to the TXOne **License File Management** screen. Specify the given License Key in the **License Key** field, and then click **Download**.

Figure 19. TXOne License File Management

The screenshot shows a web interface titled 'License File'. It contains two text input fields. The first field is labeled 'Product Serial Number' and contains the text 'a8fc1f7e-7788-11ed-8b70-0050569a90f7'. The second field is labeled 'License Key' and is currently empty; this field is highlighted with a red rectangular border. Below these fields is a button labeled 'Download'.

10. A pop-up window appears showing the license information. Read it carefully and click **Yes** for downloading the license file.

**Tip:**

You can send the license file to StellarOne that has no Internet connection via the internal secured network or a trusted portable device.

New License Key/File

To activate a new license key or license file, follow the procedures below.

1. Go to **Administration > License**.
2. Click **New License Key/File**.
3. The **New License** window appears. Choose one of the ways:
 - Click **License Key** and specify the new license key in the text field below.
 - Click **License File** and select the license file (a .txt file) to import.

**Note:**

If you don't have the license file on hand, refer to [Getting the License File \(on page 222\)](#).

4. Click **Apply**.
 5. A message with **The License is activated successfully** appears.
-



Note:

See [Resolving Licensing Issues \(on page 244\)](#) if licensing related error messages appear.

Discover Add-on License

Topics in this section includes:

- [About the Discover Add-on License \(on page 224\)](#)
- [Applying a Discover Add-on License \(on page 225\)](#)
- [Discover Add-on Seat Allocation \(on page 227\)](#)
- [Discover Add-on License Expiration \(on page 229\)](#)

About the Discover Add-on License

A StellarDiscover add-on license is an additional seat entitlement that you can apply on top of an existing StellarICS primary license. It gives Discover agents their own dedicated seat pool, so that Discover agents do not consume StellarICS seats.

The add-on license affects seat allocation on the StellarOne server only. It does not:

- change the StellarOne server license edition, which remains StellarICS
- change the license profile that StellarOne delivers to agents
- replace or override the StellarICS primary license

All managed agents, including Discover agents, continue to receive the StellarICS primary license profile during policy synchronization. The StellarDiscover add-on license file is never deployed to agents.

Because all agents receive the StellarICS primary license profile, the local console on a Discover agent displays StellarICS as the license, even when the agent is drawing from the Discover add-on seat pool.

Prerequisites

- The StellarOne server must already have an active StellarICS license applied.
 - The StellarDiscover add-on license is supported only under a StellarICS primary license.
-



Important:



Applying a StellarDiscover add-on license to a server whose primary license is StellarKiosk, StellarOEM, or a standalone StellarDiscover license is not supported. The attempt is rejected with the message **The product license is not supported**. See [Resolving Licensing Issues \(on page 244\)](#) for more details.

If the StellarICS primary license is later replaced with a license edition that does not support add-on licenses, such as StellarKiosk or StellarOEM, the StellarDiscover add-on license is removed.

How agents are classified

Seat allocation depends on the agent's operation mode:

- A **Discover agent** is any agent running Discover Edition. When the add-on license is effective, Discover agents draw from the Discover add-on seat pool.
- A **protection agent** is any agent that is not running Discover Edition, such as a Windows, Windows-Legacy, or Linux agent running Protect Edition. Protection agents always draw from the StellarICS seat pool.

An agent's classification is re-evaluated whenever its operation mode changes. See [Discover Add-on Seat Allocation \(on page 227\)](#) for more details.



Note:

Diagnostic detail for support engagements: internally, a Discover agent is an agent whose operation mode is recorded as `sensor`.

Related Topics

- [Applying a Discover Add-on License \(on page 225\)](#)
- [Discover Add-on Seat Allocation \(on page 227\)](#)
- [Discover Add-on License Expiration \(on page 229\)](#)
- [License Editions \(on page 230\)](#)

Applying a Discover Add-on License

Ensure that an active StellarICS license is already applied to the StellarOne server. See [New License Key/File \(on page 223\)](#) for more details.



Note:

The option to bind a StellarDiscover license appears in the **New License** window only when the StellarOne server is currently using a StellarICS license. If the server has no license applied, or is using a StellarDiscover, StellarKiosk, or StellarOEM license, the **New License** window does not display this option.

Apply a StellarDiscover license as an add-on to bind it to the StellarOne server's existing StellarICS primary license. You can supply the add-on license as a License Key or, if StellarOne has no Internet connection, as a License File.

1. Go to **Administration > License**.
2. Click **New License Key/File**.

The **New License** window appears.

3. Select **Bind a Stellar Discover license to this StellarOne**.
4. Choose one of the following:
 - **License Key**: click **License Key**, then specify the StellarDiscover license key in the text field.
 - **License File**: click **License File**, then click **Select** and choose the license file (a .txt file) to import.



Note:

If you don't have the license file on hand, click **Copy License File Download Link** and open the copied link in a web browser on a computer with an Internet connection. See [Getting the License File \(on page 222\)](#) for more details.

5. Click **Apply**.

StellarOne validates that the current primary license is a StellarICS license, that the license you supplied is a StellarDiscover edition license, and that the license is valid and can be parsed. If any of these checks fails, an error message appears. See [Resolving Licensing Issues \(on page 244\)](#) for more details.

6. The message **License key has been applied** appears.

Agent activation is recalculated immediately. Discover agents that were consuming StellarICS seats are reassigned to the Discover add-on seat pool.

The StellarDiscover license is stored as an add-on alongside the StellarICS primary license, but is kept separate from it. On the **License** page:

- The **License** field continues to display the StellarICS edition.
- The **Bound License and Expiration** field displays the StellarDiscover edition and its expiration date.
- The **Deployed Discover Agents** field displays the number of Discover agents registered with the server.

The StellarICS primary license is unchanged.



Note:



Replacing an existing add-on license. If a StellarDiscover add-on license is already applied, entering a new StellarDiscover license replaces the existing one. The StellarICS primary license is not affected, and agent activation is recalculated immediately.



Note:

Applying or replacing a StellarDiscover add-on license does not trigger a repack of the Agent Installer Package. Installer packages continue to use the StellarICS license profile. See [Downloading Agent Installer Package/Group.ini File \(on page 214\)](#) for more details.

Discover add-on expiration date. The expiration date of the StellarDiscover add-on license is aligned with the expiration date of the StellarICS primary license. This is true regardless of the order in which the licenses are applied:

- If you apply the StellarICS license first and then add the StellarDiscover add-on license, the add-on expiration date matches the StellarICS expiration date.
- If you apply the StellarDiscover license first and then apply the StellarICS license, the add-on expiration date still matches the StellarICS expiration date.

Discover Add-on Seat Allocation

How StellarOne allocates seats and activates agents depends on the state of both the StellarICS primary license and the StellarDiscover add-on license.

StellarICS license valid, add-on license effective

- Protection agents use StellarICS seats only. The number of activated protection agents is limited by the StellarICS seat quota.
- Discover agents do not consume StellarICS seats. They use the Discover add-on seat pool, and the number of activated Discover agents is limited by the Discover add-on seat quota.
- Discover agents that exceed the Discover add-on seat count are set to Inactive and are reported as over-deployed. They do not fall back to consuming StellarICS seats.

The following table shows example outcomes.

Table 50. Seat Allocation Examples

StellarICS seats	Discover add-on seats	Protection agents	Discover agents	Result
100	50	80	50	80 protection agents active; 50 Discover agents active

Table 50. Seat Allocation Examples (continued)

StellarICS seats	Discover add-on seats	Protection agents	Discover agents	Result
100	50	100	50	100 protection agents active; 50 Discover agents active
100	50	120	50	100 protection agents active, 20 protection agents inactive; 50 Discover agents active
100	30	80	50	80 protection agents active; 30 Discover agents active, 20 Discover agents inactive

StellarICS license valid, add-on license expired or not applied

All agents, including Discover agents, compete for StellarICS seats under the standard seat calculation. Activation priority follows the existing rule: agents are ordered by registration time, and agents that registered earlier are activated first. When seats are insufficient, agents that registered later are set to Inactive first.

StellarICS primary license expired

All agents become inactive, including both protection agents and Discover agents.



Important:

A valid StellarDiscover add-on license cannot override expiration of the StellarICS primary license. Even if the add-on license is still within its validity period, no agents remain activated once the StellarICS primary license expires. Renew the StellarICS primary license promptly. See [License Renewal \(on page 221\)](#) for more details.

Events that trigger recalculation

StellarOne automatically recalculates agent activation status when any of the following occurs:

- A StellarDiscover add-on license is applied or replaced.
- A StellarDiscover add-on license refresh changes the add-on status.
- A StellarDiscover add-on license reaches its hard expiration date.
- An agent registers with StellarOne or is uninstalled.
- An agent's operation mode changes.

- The StellarICS primary license seat count changes.
- A StellarICS primary license refresh changes the seat count or the expiration date.
- The StellarICS primary license enters the expired state.
- A new or renewed license is applied.

Agent operations that affect seat allocation

Table 51. Agent Operations That Affect Seat Allocation

Operation	Effect
A Discover agent registers with StellarOne while the add-on license is effective	The agent does not consume a StellarICS seat. It is activated according to the Discover add-on seat quota. If the add-on license is not effective, the agent competes for StellarICS seats as normal.
An agent's operation mode changes	Activation is recalculated. An agent converted from Discover Edition to a protection mode is moved into the StellarICS seat pool immediately.
Upgrade from Discover Edition to Protect Edition is issued	The Discover agent is converted into a Protect agent and begins counting against the StellarICS seat quota. If StellarICS seats are insufficient after the conversion, the converted agent becomes Inactive. See Upgrade from Discover Edition to Protect Edition (on page 67) for more details.
Discover agents are transferred to another StellarOne server	The destination server's licensing determines the seat pool used. See Transfer Agents to Another StellarOne (on page 61) for more details.

Discover Add-on License Expiration

A StellarDiscover add-on license passes through three stages.

Table 52. Discover Add-on License Stages

Stage	Description
Active	The current date is on or before the add-on license expiration date. Discover agents use Discover add-on seats.

Table 52. Discover Add-on License Stages (continued)

Stage	Description
In grace period	The add-on license has passed its expiration date but has not yet reached its hard expiration date. The add-on license remains effective. Discover agents continue to use Discover add-on seats and remain exempt from StellarICS seats.
Hard expired	The add-on license has passed its hard expiration date, which is the expiration date plus the grace period. The add-on license is no longer effective. Discover agents return to the StellarICS seat pool and are subject to the StellarICS seat quota.

The expiration date shown in the **Bound License and Expiration** field on the **License** page is the license expiration date, not the hard expiration date. The add-on license remains usable through the grace period.

Behavior after expiration

- StellarOne does not delete StellarDiscover add-on license data when the add-on license expires. The **License** page continues to display the bound license information with an expired status.
- Agent activation is recalculated automatically when the add-on license transitions to hard expired. Discover agents are re-evaluated against the StellarICS seat quota, in order of registration time, and agents that cannot be accommodated are set to Inactive.



Note:

Renewing the StellarICS primary license also refreshes the StellarDiscover add-on license. See [Renew License with the same License Key \(on page 221\)](#) for more details.

License Editions

See below as the four kinds of license editions for the TXOne Stellar 5.0. Stellar Agent supports Windows 7 or later versions; Stellar Agent (Windows-Legacy) supports legacy platforms such as Windows XP/2000.

Table 53. License Editions

Edition	Primary Function	Duration
StellarICS	Stellar Agent (Windows):	Annual

Table 53. License Editions (continued)

Edition	Primary Function	Duration
	• Multi-Method Threat Prevention (Real-Time Scan) • Application Lockdown	
	Stellar Agent (Linux): • Multi-Method Threat Prevention (Real-Time Scan)	
	Stellar Agent (Windows-Legacy) Agent: • Threat Prevention (Real-Time Scan) • Application Lockdown	
StellarKiosk	Stellar Agent: • Multi-Method Threat Prevention (Real-Time Scan)	Annual  Note: StellarKiosk was named StellarMix before the TXOne Stellar version 2.0.
	Stellar Agent (Windows-Legacy): • Threat Prevention (Real-Time Scan) • Application Lockdown	
StellarDiscover  Note: A StellarDiscover license can be applied either as the server's primary license or as an add-on	Stellar Agent (Windows)/Stellar Agent (Windows-Legacy): • Threat Prevention (Scheduled Scan)	3 months

Table 53. License Editions (continued)

Edition	Primary Function	Duration
 license under a Stellar ICS primary license. When applied as an add-on license, it provides a dedicated seat pool for Discover agents and does not change the server license edition. See About the Discover Add-on License (on page 224) for more details.		
StellarOEM	Stellar Agent: • Application Lockdown	Perpetual  Note:

Table 53. License Editions (continued)

Edition	Primary Function	Duration
	Stellar Agent (Windows-Legacy): • Application Lockdown	 • StellarOEM provides permanent use and 5-year technical support for the TXOne Stellar. • This license edition does not support features such as scan and agent component update. • StellarOEM was named Perpetual before the TXOne Stellar version 2.0.

Features of License Editions

StellarICS, StellarKiosk, and StellarOEM license editions provides different features, allowing users in diverse industries to select based on their specific needs.

Table 54. Features of License Editions

Features	StellarICS	StellarKiosk	StellarOEM
Multi-Method Threat Prevention	√	√	-
Operation/Application Lockdown	√	Stellar Agent (Windows-Legacy) only	√
Operations Behavior Anomaly Detection	√	Script Behavior only	Script Behavior only

Table 54. Features of License Editions (continued)

Features	StellarICS	StellarKiosk	StellarOEM
Industrial Application and Certificate Repository	√	√	√
OT Application Safeguard	√	√	√
Intelligent Runtime Learning (Predictive Machine Learning)	√	Stellar Agent (Windows-Legacy) only	√
Trusted USB Device Control	√	√	√
Legacy Systems Compatibility	√	√	√



Note: When using a StellarOEM license, lockdown is enabled by default.

For the features available to Discover Edition agents, see [Table 4: Product Matrix for Discover Edition \(on page 19\)](#).

System

Topics in this section includes:

- [System Time \(on page 234\)](#)
- [Log Purge \(on page 235\)](#)
- [Importing SSL Certificate \(on page 236\)](#)
- [OT Intelligent Trust \(on page 237\)](#)
- [Service Integration \(on page 237\)](#)
- [StellarOne Pool \(on page 238\)](#)

System Time

You can configure the system time settings for the StellarOne web console.

1. Go to **Administration > System Time**.
2. Two options are available for configuring StellarOne system time. In the **Date and Time** section:
 - If you want to set the system time manually, click the Edit icon to specify the date and time, and then click **Apply** to save the setting.
 - If you want to align StellarOne system time with an NTP server, click the **Synchronize system time with an NTP server** toggle to enable it. Click **Test Synchronization** to check if the sync was successful.

**Note:**

The default NTP server is pool.ntp.org.

3. In the **Time Zone** section, click the downward arrow in the blank bar. A drop-down menu with global time zone appears.
4. Select the appropriate time zone for the system, and then click **Save** to complete the settings.

Log Purge

This feature allows users to manage the volume of log files to optimize the disk space usage for StellarOne.

1. Go to **Administration > Log Purge**.
2. Choose one of the ways listed below for log purge settings.
 - **Daily Auto-Purge:**

StellarOne organizes logs into data chunks and deletes old ones daily. When the purge begins, Stellar will first delete specific data chunks by age, then proceed to delete additional data chunks until the remaining entries are close to the goal. Here is how to configure the auto-purge goal.

- a. Click the drop-down list in the column of **Action 1: Delete chunks older than**, and then for each type of event log, select an age of the data chunk to be purged.
 - b. Click the drop-down menu in the column of **Action 2: Keep approx. number of recent logs**, and then for each type of event log, select a number of logs to retain.
 - c. Click **Save** to save the settings. The event logs will be automatically purged once per day.
- **Manual Purge:**

Besides setting up auto-purge, you can also purge the logs manually.

The actual amount of data purged or retained depends on the size of the data chunks. You can manually purge data multiple times if necessary.

- a. Specify the **Purge event type** by selecting a type in the drop-down list: **Agent Events**, **Server Events**, **System Log**, or **Audit Log**.
- b. Click the drop-down list in the column of **Action 1: Delete chunks older than**, and then for each type of event log, select an age of the data chunk to be purged.
- c. Click the drop-down menu in the column of **Action 2: Keep approx. number of recent logs**, and then for each type of event log, select a number of logs to retain.
- d. Click **Purge Now** to start the purge right away.



Note:

- Due to that the logs are organized into chunks instead of a number of entries, the remaining log entries after the auto-purge may not be as exact as what was set.
- If there are audit needs, please back up or export the event log before a purge. It is recommended to set the **approx. number of recent log** entries to keep as **one million**.

Importing SSL Certificate

1. Go to **Administration > SSL Certificate**.
2. Click **Import Certificate**, and then the **Import Certificate** window appears.
 - Click the **Select file...** next to the **Certificate** option to select the target certificate.
 - Click the **Select file...** next to the **Private Key** option to select the target private key.
 - (Optional) Specify the passphrase in the **Passphrase** text field.



Note:

Supported certificate and private key formats include:

- Certificate and private key in PEM format
- Private key in PKCS #1 format with or without encryption
- Private key in PKCS #8 format without encryption

-
3. Click **Import and Restart** to start importing the target certificate.



Note:

Importing the certificate requires restarting the StellarOne console.

OT Intelligent Trust

When enabled, TXOne OT Intelligent Trust shares anonymous threat information with the Smart Protection Network, allowing TXOne to rapidly identify and address new threats. You can disable TXOne OT Intelligent Trust anytime on this console.

1. Go to **Administration > OT Intelligent Trust**.
2. Click the **Learn More** for visiting TXOne's OT threat research website.
3. To enable TXOne OT Intelligent Trust, toggle on the **Enable TXOne OT Intelligent Trust (recommended)**.

Service Integration

The StellarOne web console can be integrated to Trend Micro's Vision One and allows Vision One users to search for StellarOne's detection logs.

Integrate with TXOne Networks SageOne

Users can check for StellarOne data via TXOne Networks SageOne Sensor Management. The data include but not limited to agent even logs or compromised asset analysis. See *SageOne Administrator Guide* for more details about the StellarOne data available on the SageOne console.

1. On StellarOne console, go to **Administration > Service Integration**.
2. Select the **TXOne SageOne** tab. The **TXOne SageOne Settings** screen appears.
3. Specify the SageOne address and API key in the corresponding text fields.



Note:

The API key is required to register StellarOne to SageOne. The API key will expire within 24 hours if not used after generated from the SageOne console. See *SageOne Administrator Guide* for how to get the API key.

4. Click **Test Connection** and a success message should appear.
5. Find **Send Data to SageOne** section, and then toggle on **Send StellarOne data to SageOne**.
6. The **Data Sending Interval** menu appears. Select the frequency in the drop-down menu for sending StellarOne data to SageOne.
7. Click **Save** to complete the settings.



Note:

If StellarOne has connected with SageOne successfully, the **SageOne Onboarding Status** should display **Connected**.

Integrate with Trend Micro Vision One

Users can query for StellarOne malware detection logs via Trend Micro Vision One Search app.



Important:



Be sure to complete the deployment of Trend Micro Vision One Service Gateway and enable **Forward proxy** function first, and then obtain the information for Service Gateway settings required in *Step 2* and *Step 3*. Please contact your support provider for more information.

1. On StellarOne console, go to **Administration > Service Integration**.
 2. Select the **Trend Micro Vision One** tab. The **Trend Micro Vision One Settings** screen appears.
 3. Specify the IP address and API key of Trend Micro Vision One Service Gateway in **Service Gateway Address** and **Service Gateway API Key**.
-



Note:

The IP address and API key should be obtained from the Trend Micro Vision One Service Gateway Virtual Appliance.

4. Specify the Trend Micro Vision One enrollment token in **Product Connector Enrollment Token**.
-



Note:

The enrollment token is required to register StellarOne to Trend Micro Vision One. The enrollment token will expire within 24 hours if not used after generated from the Vision One Product Connector app.

5. Click **Test Connection** and a success message should appear.
 6. Find **Forward Logs to Vision One** section, and then toggle on **Send StellarOne malware detection logs to Vision One**.
 7. The **Log Sending Interval** menu appears. Select the frequency in the drop-down menu for sending StellarOne detection logs to Trend Micro Vision One.
 8. Click **Save** to complete the settings.
-



Note:

If StellarOne has connected with Trend Micro Vision One successfully, the **Vision One Onboarding Status** should display **Connected**.

StellarOne Pool

To expand scalability, you can add peer StellarOne servers to the **StellarOne Pool** to manage agents.

1. Download the **Server Information** of the StellarOne server that is about to be added as a peer.
Go to the target StellarOne and click the **About** red tab.
2. Click **Download StellarOne Server Information** and save the zip file.
3. Go to the original StellarOne and click **Administration > StellarOne Pool**.
4. Click the **+Add StellarOne Server** button.
5. Select the file that was downloaded previously, and specify a server name. Click **Add**.



Tip: To edit or delete a peer StellarOne server, click the respective icon in the **Action** column.

To transfer agents from a StellarOne server to another, see [Transfer Agents to Another StellarOne \(on page 61\)](#) for more details.

Chapter 8. Getting Help and Troubleshooting

Learn about the following topics:

- [Troubleshooting Resources \(on page 242\)](#)
- [Contacting TXOne Networks \(on page 248\)](#)
- [Other Resources \(on page 249\)](#)

Troubleshooting Resources

Before contacting technical support, consider visiting the following TXOne Networks online resources.

Self-Diagnosis

Identify and troubleshoot low disk space issues with StellarOne.

- [Resolving Low Disk Space Issues \(on page 242\)](#)
- [Resolving Licensing Issues \(on page 244\)](#)

Resolving Low Disk Space Issues

To keep you informed of your disk usage, and any potential issues that may arise, StellarOne displays banners or modal windows at certain disk usage thresholds. When encountering such errors, you can check the following table for the features affected and take actions as suggested in the **Workaround** column.

However, the most efficient way to get rid of low disk space error caused by the 2nd HDD is to add more space to the drive or partition. Follow the procedures:

1. Go to **Dashboard** to check **Widgets for Monitoring Disk Usage** section in *StellarOne Administrator Guide* for the current disk usage.
2. Go to **Dashboard** to check the Disk Usage widgets.
3. Check the following table for the features that will become unavailable at certain usage thresholds.
4. Extend the drive or partition which is running out of space.



Note:

- If you take snapshots for the StellarOne virtual machine, ensure the snapshot files be consolidated before extending the partition space.
 - Contact your support provider if you need to fix the low disk space error caused by the 1st HDD.
-

Table 55. Unavailable Features List due to Low Disk Space

Unavailable Features	Menu Path	Description	Usage Threshold	Workaround
Firmware upgrade	Administration > Update > Firmware	Unable to import the StellarOne firmware for upgrade	• 1st HDD disk free space less than 5 GB + the size of customer-specific data, such as 2nd HDD's other partitions, the number of uploaded agent patches and collected agent logs. • 2nd HDD free disk space: ◦ System partition: less than 5 GB ◦ Database partition: less than 30%	Free up the 2nd HDD disk space on System partition by: • Deleting unused patch files • Purging unwanted agent debug logs

Table 55. Unavailable Features List due to Low Disk Space (continued)

Unavailable Features	Menu Path	Description	Usage Threshold	Workaround
Agent patch file import	Administration > Downloads/Updates > Agent StellarOne debug page (for SEG purpose)	Unable to import Agent patch files	• 2nd HDD disk usage on System partition less than 20% • 2nd HDD disk usage on Database partition less than 20%	
Agent debug tool collection		Unable to collect the debug logs for Stellar Agent (Windows) or Stellar Agent (Windows-Legacy)		
Debug log level selection		Unable to select the Info or Verbose log level. Only the Warn (Default) level logs can be collected.		
Server debug tool collection		Unable to collect the debug logs for the StellarOne server		

Resolving Licensing Issues

The following table provides more information about some licensing error messages and possible actions to take when issues occur during license activation or renewal.

Table 56. Licensing Error Messages and Suggested Actions

Error Message	Description	Possible Actions
Unable to convert the license from full to trial version. To continue using the product, please contact your sales representative for renewing the license.	Once upgraded to a full license, the full license cannot be converted to a trial license.	• Ensure you enter the valid full license data. • Contact your sales representative for renewing the full license.
The product license is not supported.	The license you supplied cannot be applied as a StellarDiscover add-on license. This message appears when the license key or license file you supplied is not a StellarDiscover edition license. It also appears if the StellarOne server's primary license is not a StellarICS license, because StellarDiscover add-on licenses are supported only under a StellarICS primary license.	• Verify that the license key or license file you supplied is for the StellarDiscover edition. • Verify on the License page that the current license edition is StellarICS. • Contact your sales representative if you need a StellarICS license or a StellarDiscover add-on license.
Activation Code detected as the currently used license format. This trial license can only be used once. Please contact your sales representative for a trial License Key or upgrading to a full license.	Based on the terms and conditions, the trial Activation Code can only be used once. An example of the Activation Code: TE-24RF-Q9UN9-S9QQN-XXX XX-XXXXX-XXXXX See Comparison of License Formats (on page 24) for more details.	To continue using the product, contact your sales representative for a trial License Key or upgrading to a full license.
License Key detected as the currently used license format. Please contact your sales representative for extending the license.	Based on the terms and conditions, the trial License Key can be extended under certain circumstances.	To continue using the product, contact your sales representative for extending the trial license, upgrading to a full license, or renewing the full license.

Table 56. Licensing Error Messages and Suggested Actions (continued)

Error Message	Description	Possible Actions
	You can also choose to upgrade to a full license for a minimum period of one-year protection coverage. If you're using a full license, consider renewing the license. An example of the License Key: FIJN-HPYB-XXXX-XXXX	
Unable to connect to the license server. Proxy authentication is required.	This message signifies unspecified or invalid proxy authentication causes this issue that StellarOne cannot connect to the license server for license activation or renewal.	Check your proxy settings.
Unable to connect to the license server. The certificate was signed by an unknown authority.	This message signifies a self-signed certificate is used in a scenario that requires a trusted CA-signed certificate.	Import customer trusted certificate via vShell command. See <i>StellarOne Administrator Guide</i> for more details.
StellarOne has no Internet connection. You may try it again or choose to activate the license by importing the license file.	Due to unidentified network issues, StellarOne cannot connect to the license server to complete the license activation.	• Check your network settings and then try to activate or renew license again. • You can also use the License File to activate or renew license in the offline environment. The License Key is required for downloading the License File. See Getting the License File (on page 222) for more information.
StellarOne has no Internet connection. You may try it again or click New License to get and import the updated license file.	Due to unidentified network issues, StellarOne cannot connect to the license server to complete the license renewal.	
Unable to renew license. Make sure your network connection between StellarOne and license server is active or check your proxy settings and then try again.	Due to unidentified network issues, StellarOne cannot connect to the license server. Check your network settings and try again later.	Check your network settings and then try to renew license again.

Table 56. Licensing Error Messages and Suggested Actions (continued)

Error Message	Description	Possible Actions
	The Activation Code cannot be used to renew license offline.	

Collect Debug Log

Before you contact TXOne Networks via the methods introduced in the following sections, you may need to obtain a debug log for the customer support agents to provide a solution. Follow the instructions below to obtain the Debug Log.



Note:

Only the account with the **Admin** role can collect the debug log.

1. Go to your StellarOne web console on a browser, in the address line, change the address after the server address to "**diagnostics**". Press **Enter**.



2. Set the **Debug Log Level** to **Verbose**, and then click **Save** to save the setting.
3. Perform the steps that originally led to the issue so that the debug logs can capture all necessary details.
4. Click the **Collect Debug Log** button.
5. Set the **Debug Log Level** back to **Warn**, and then click **Save** to save the setting.

Using the Support Portal

The TXOne Networks Support Portal is a 24x7 online resource that contains the most up-to-date information about both common and unusual problems.

1. Go to <https://help.txone.com/>.
2. Click the appropriate button to search for solutions.
3. Use the **Search** box to search for available solutions.
4. If no solution is found, click **Live Chat** or **VoIP** service to submit a support case online.

A TXOne Networks support engineer investigates the case and responds in 24 hours or less.



Important:

If the StellarOne virtual machine has been encrypted, ensure that you decrypt it for problem analysis.

Threat Encyclopedia

Most malware today consists of blended threats, which combine two or more technologies, to bypass computer security protocols. TXOne Networks combats this complex malware with products that create a custom defense strategy. The Threat Encyclopedia provides a comprehensive list of names and symptoms for various blended threats, including known malware, spam, malicious URLs, and known vulnerabilities.

Go to <https://www.encyclopedia.txone.com/> to learn more about:

- Malware and malicious mobile code currently active or "in the wild"
- Correlated threat information pages to form a complete web attack story
- Internet threat advisories about targeted attacks and security threats
- Web attack and online trend information
- Weekly malware reports

Contacting TXOne Networks

TXOne Networks representatives are available by phone or chat/VoIP services:

Table 57. TXOne Networks Contact Information

U.S.	+1 (346) 586-7975
Netherlands	+31 402-310-122
Taiwan	+886 (2) 7727-5120
Chat/VoIP services	https://help.txone.com/
Website	https://www.txone.com/contact/

- TXOne Networks product documentation:

<https://my.txone.com/>

Speeding Up the Support Call

To improve problem resolution, have the following information available:

- Steps to reproduce the problem
- Appliance or network information
- Computer brand, model, and any additional connected hardware or devices
- Amount of memory and free hard disk space
- Operating system and service pack version
- Version of the installed agent
- Product serial number and license file, or license key
- Detailed description of the environment where the agent is installed
- Exact text of any error message received

Other Resources

In addition to solutions and support, there are many other helpful resources available online to stay up to date, learn about innovations, and be aware of the latest security trends.

Download Center

From time to time, TXOne Networks may release a patch for a reported known issue or an upgrade that applies to a specific product or service. To find out whether any patches are available, go to:

<https://my.txone.com/>

If a patch has not been applied (patches are dated), open the Readme file to determine whether it is relevant to your environment. The Readme file also contains installation instructions.

Appendix A. Appendices

Topics in this section include:

- [Log Descriptions \(on page 252\)](#)
- [Syslog Content - CEF \(on page 353\)](#)

Log Descriptions

Topics in this section include:

- [Log Descriptions for Stellar Agent \(Windows\) \(on page 252\)](#)
- [Log Descriptions for Stellar Agent \(Windows-Legacy\) \(on page 282\)](#)
- [Server Event Log Descriptions for StellarOne \(on page 343\)](#)
- [Agent Event Log Descriptions for Stellar Agent - Protect Edition \(Linux\) \(on page 346\)](#)

Log Descriptions for Stellar Agent (Windows)

Topics in this section include:

- [Agent Event Log Descriptions for Stellar Agent \(Windows\) \(on page 252\)](#)
- [Server Event Log Descriptions for Stellar Agent \(Windows\) \(on page 281\)](#)

Agent Event Log Descriptions for Stellar Agent (Windows)

This table details the Windows event log descriptions for Stellar Agent (Windows).

Event ID	Level	Category	Event	Details
256	Information	System	Service started	
257	Information	System	Policy applied successfully (Version: %version%)	
258	Information	System	Patch applied File Name: %file_name%	
259	Information	System	Patching in progress	After the earlier-applied patch is completed, the system will automatically try to apply this patch: %deferred_file_name%.

Event ID	Level	Category	Event	Details
513	Information	intelli_av	Application vault update was successful	
514	Information	intelli_av	Real Time Scan enabled	
515	Information	intelli_av	A scheduled scan started	
516	Information	intelli_av	A scheduled scan ended	Folders scanned: %1 Symbolic links: %2 Regular files: %3 Files scanned: %4 Files passed: %5 Threats detected: %6
517	Information	intelli_av	A manually launched scan started	
518	Information	intelli_av	A manually launched scan ended	Folders scanned: %1 Symbolic links: %2 Regular files: %3 Files scanned: %4 Files passed: %5

Event ID	Level	Category	Event	Details
				Threats detected: %6
519	Information	intelli_av	A scheduled scan enabled	Next scan will be on %NextScan%.
520	Information	intelli_av	A scheduled scan disabled	
521	Information	intelli_av	A scan manually launched by local user started	
522	Information	intelli_av	A scan manually launched by local user ended	Folders scanned: %1 Symbolic links: %2 Regular files: %3 Files scanned: %4 Files passed: %5 Threats detected: %6
523	Information	intelli_av	Incoming file detected malicious and quarantined successfully	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Quarantine Path: %PATH%

Event ID	Level	Category	Event	Details
				Reboot Required: %NEED_REBOOT%
524	Information	intelli_av	Local file detected malicious and quarantined successfully	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Quarantine Path: %PATH% Reboot Required: %NEED_REBOOT%
525	Information	intelli_av	Malicious file execution detected. Infected executable file quarantined successfully	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Quarantine Path: %PATH% Reboot Required: %NEED_REBOOT%
526	Information	intelli_av	Ransomware Behavior Monitor enabled	

Event ID	Level	Category	Event	Details
527	Information	intelli_av	Prescan completed successfully	Prescan log: %PATH% Scanned files: %NUM% Infected files: %NUM% Files with resolved threats: %NUM%
768	Information	anomaly_detect	Operations Behavior Anomaly Detection (Script Behavior) enabled	Mode: %Mode% Level: %Level% Learning time: %LearningTime% day(s)
769	Information	anomaly_detect	Script behavior added to baseline	Access User: %USERNAME% ID: %ID% Target Process: %PATH% %ARGUMENT% Parent Process 1: %PATH% %ARGUMENT%

Event ID	Level	Category	Event	Details
				Parent Process 2: %PATH% %ARGUMENT% Parent Process 3: %PATH% %ARGUMENT% Parent Process 4: %PATH% %ARGUMENT%
770	Information	anomaly_detect	Script behavior excluded from baseline.	ID: %ID% Target Process: %PATH% %ARGUMENT% Parent Process 1: %PATH% %ARGUMENT% Parent Process 2: %PATH% %ARGUMENT% Parent Process 3: %PATH% %ARGUMENT% Parent Process 4: %PATH% %ARGUMENT%

Event ID	Level	Category	Event	Details
771	Information	anomaly_detect	Operations Behavior Anomaly Detection (User Login) enabled	Mode: %Mode% Level: %Level% Learning time: %LearningTime% day(s)
772	Information	anomaly_detect	Operations Behavior Anomaly Detection (Application Behavior) enabled	Mode: %Mode% Level: %Level% Learning time: %LearningTime% day(s)
773	Information	anomaly_detect	Login account added to baseline	Domain: %Domain% Account: %Account% Login Type: %LoginType% Source IP: %IP%
774	Information	anomaly_detect	Login account excluded from baseline	Domain: %Domain% Account: %Account% Login Type: %LoginType% Source IP: %IP%

Event ID	Level	Category	Event	Details
775	Information	anomaly_detect	Application added to baseline	Application Path: %Path%
776	Information	anomaly_detect	Application excluded from baseline	Application Path: %Path%
777	Information	anomaly_detect	Operations Behavior Anomaly Detection (Network Behavior) enabled	Mode: %Mode% Level: %Level% Learning Time Setting: %LearningTime% day(s)
778	Information	anomaly_detect	The network traffic was added to the baseline	Remote IP: %IP Destination Port: %PORT%L4 Protocol: %STRING%L7 Protocol: %STRING% Direction: %Direction%
779	Information	anomaly_detect	The network traffic was excluded from the baseline	Remote IP: %IP Destination Port: %PORT%L4 Protocol: %STRING%L7 Protocol: %STRING% Direction: %Direction%

Event ID	Level	Category	Event	Details
784	Information	anomaly_detect	DLL Injection Prevention enabled	
1280	Information	device_control	Device Control enabled	
1281	Information	device_control	USB device added into trusted device list	Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING% Type: permanent or one time
1282	Information	device_control	USB device removed from trusted device list	Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING%
1283	Information	device_control	Trusted USB device connected	Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING% Active User: %STRING%
1284	Information	device_control	Trusted USB device disconnected	Vendor ID: %HEX%

Event ID	Level	Category	Event	Details
				Product ID: %HEX% Serial Number: %STRING% Active User: %STRING%
1285	Information	device_control	Block USB AutoRun enabled	
1286	Information	device_control	USB Access Tracking enabled	
1287	Information	device_control	USB Auto Scan enabled	
1792	Information	lockdown	File access allowed: %PATH%	Access Image Path: %PATH% Access User: %USERNAME% Mode: %MODE% List: %LIST%
1793	Information	lockdown	A new file added to Approved List in Maintenance Mode.	Path: %PATH% Hash: %SHA256_HEXSTR%
1794	Information	lockdown	The hash of an existing file in Approved List was updated in Maintenance Mode	Path: %PATH% Hash: %SHA256_HEXSTR%

Event ID	Level	Category	Event	Details
1795	Information	lockdown	Approved List initialization started	
1796	Information	lockdown	Approved List initialization completed	Count: %COUNT%
1797	Information	lockdown	Application Lockdown enabled	Mode: %MODE%
1798	Information	lockdown	DLL/Driver Lockdown enabled	
1799	Information	lockdown	Script Lockdown enabled	
1800	Information	lockdown	Intelligent Runtime Learning enabled	
2048	Information	update	Component update started	
2049	Information	update	Component update ended	
2050	Information	update	Scheduled component update enabled. Next update will be on %NEXT_UPDATE_LOCAL_TIME_STR% (agent's local system time).	
2051	Information	update	Scheduled component update disabled	
2052	Information	update	Components updated successfully.	Update Source: %UPDATE_URL% [Original Version]

Event ID	Level	Category	Event	Details
				%COMPONENTS_INFO% [Updated Version] %COMPONENTS_INFO%
2053	Information	update	Components duplicated successfully.	Update Source: %UPDATE_URL%
3840	Information	misc	User account enabled	
3841	Information	misc	User account disabled	
3842	Information	misc	User password changed	
4352	Warning	system	Service stopped	
4353	Warning	system	Unable to apply policy (Version: %version%)	
4354	Warning	system	Unable to update file	Source Path: %src_path% Destination Path: %dst_path% Error Code: %err_code%
4355	Warning	system	Unable to apply patch	File Name: %file_name% Error Code: %err_code%

Event ID	Level	Category	Event	Details
4609	Warning	intelli_av	Incoming files scanned, action taken by Antivirus: %PATH%	Incoming files were scanned by antivirus. Action was taken according to settings. File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Action Result: %INTEGER% Quarantine Path: %PATH%
4610	Warning	intelli_av	Incoming files scanned, action taken by Next-Generation Antivirus: %PATH%	Incoming files were scanned by next-generation antivirus. Action was taken according to settings. File Path: %PATH% File Hash: %STRING% Threat Type: %STRING%

Event ID	Level	Category	Event	Details
				Threat Name: %STRING% Action Result: %INTEGER% Quarantine Path: %PATH%
4611	Warning	intelli_av	Local files scanned, action taken by Antivirus: %PATH%	Local files were scanned by antivirus. Action was taken according to settings. File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Action Result: %INTEGER% Quarantine Path: %PATH%
4612	Warning	intelli_av	Local files scanned, action taken by Next-Generation Antivirus: %PATH%	Local files were scanned by next-generation antivirus.

Event ID	Level	Category	Event	Details
				Action was taken according to settings. File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Action Result: %INTEGER% Quarantine Path: %PATH%
4613	Warning	suspicious_objects	Suspicious program execution blocked	Suspicious program execution was blocked. File Path: %PATH% File Hash: %STRING%
4614	Warning	suspicious_objects	Suspicious program currently running	Suspicious program is currently running. Process ID: %PID% File Path: %PATH% File Hash: %STRING%

Event ID	Level	Category	Event	Details
				File Credibility: %STRING%
4615	Warning	intelli_av	Application execution blocked by Antivirus	Application execution was blocked by antivirus. Process Image Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4617	Warning	intelli_av	Application execution blocked by Next-Generation Antivirus	Application execution was blocked by next-generat ion antivirus. Process Image Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4618	Warning	intelli_av	Failed to quarantine incoming file detected malicious	File Path: %PATH% File Hash: %STRING%

Event ID	Level	Category	Event	Details
				Threat Type: %STRING% Threat Name: %STRING%
4619	Warning	intelli_av	Failed to quarantine local file detected malicious	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4620	Warning	intelli_av	Malicious file execution detected. Failed to quarantine the infected executable file	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4623	Warning	intelli_av	Script containing malicious content was blocked	Script host path: %PATH% Script file path: %PATH% Threat type: %STRING% Threat name: %STRING%
4624	Warning	intelli_av	Application execution bypassed by antivirus	Process Image Path: %PATH%

Event ID	Level	Category	Event	Details
				File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4625	Warning	intelli_av	Application execution bypassed by next-generation antivirus	Process Image Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4626	Warning	intelli_av	Ransomware Behavior Monitor disabled	
4627	Warning	intelli_av	Malicious application behavior detected by Ransomware Behavior Monitor	Program Path: %Path% Program Hash: %SHA256%; Program Size: %Size% Certificate: %CertificateSigner% Vendor: %VendorName" Product: %Product%

Event ID	Level	Category	Event	Details
				Rules Violated: %PoliciesAnd Rules% %THROTTLING_INFO_MSG%
4628	Warning	intelli_av	Application file access bypassed by antivirus. Linux only., Application file access was bypassed by antivirus.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4629	Warning	intelli_av	Application file access blocked by antivirus. Linux only., Application file access was blocked by antivirus.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4630	Warning	intelli_av	Script containing malicious content was detected but ignored.	
4631	Warning	intelli_av	Unable to scan compressed files that are password protected or contain password protected files.	
4864	Warning	anomaly_detect	Operations Behavior Anomaly Detection (Script Behavior) disabled	
4865	Warning	anomaly_detect	Script Behavior allowed by Operations Behavior Anomaly Detection: %PATH% %ARGUMENT%	Access User: %USERNAME% Parent Process 1: %PATH% %ARGUMENT%

Event ID	Level	Category	Event	Details
				Parent Process 2: %PATH% %ARGUMENT% Parent Process 3: %PATH% %ARGUMENT% Parent Process 4: %PATH% %ARGUMENT% Mode: %Mode% Level: %LEVEL%
4866	Warning	anomaly_detect	Script Behavior blocked by Operations Behavior Anomaly Detection:%PATH% %ARGUMENT%	Access User: %USERNAME% Parent Process 1: %PATH% %ARGUMENT% Parent Process 2: %PATH% %ARGUMENT% Parent Process 3: %PATH% %ARGUMENT%

Event ID	Level	Category	Event	Details
				Parent Process 4: %PATH% %ARGUMENT% Mode: %Mode% Level: %LEVEL%
4867	warning	anomaly_detect	Operations Behavior Anomaly Detection (User Login) disabled	
4868	warning	anomaly_detect	Operations Behavior Anomaly Detection (Application Behavior) disabled	
4869	warning	anomaly_detect	A user login failure detected by Operations Behavior Anomaly Detection	Domain: %Domain% Account: %Account% Login Type: %LoginType% Source IP: %IP%
4870	warning	anomaly_detect	An abnormal user login detected by Operations Behavior Anomaly Detection	Domain: %Domain% Account: %Account% Login Type: %LoginType% Source IP: %IP%

Event ID	Level	Category	Event	Details
4871	warning	anomaly_detect	Suspicious application behavior detected by Operations Behavior Anomaly Detection	Program Path: %Path% Program Hash: %SHA256% Program Size: %Size% Certificate: %CertificateSigner% Vendor: %VendorName% Product: %Product%
4872	warning	anomaly_detect	An unrecognized application detected by Operations Behavior Anomaly Detection	PID: %PID% Program Path: %Path% Program Hash: %SHA256% Program Size: %Size% Certificate: %CertificateSigner% Vendor: %VendorName% Product: %Product%

Event ID	Level	Category	Event	Details
4873	warning	anomaly_detect	Malicious application behavior detected by Operations Behavior Anomaly Detection	Program Path: %Path% Program Hash: %SHA256% Program Size: %Size% Certificate: %CertificateSigner% Vendor: %VendorName% Product: %Product%
4874	warning	anomaly_detect	Operations Behavior Anomaly Detection (Network Access) disabled	
4875	warning	anomaly_detect	Unable to turn on the Operations Behavior Anomaly Detection (Network Access)	
4876	warning	anomaly_detect	Abnormal outbound network traffic detected by Operations Behavior Anomaly Detection	Program Path: %Path% Program Hash: %SHA256% Remote IP: %IP% Remote Port: %PORT% L4 Protocol: %STRING" L7 Protocol: %STRING%

Event ID	Level	Category	Event	Details
				%THROTTLING_INFO_MSG%
4877	warning	anomaly_detect	Abnormal inbound network traffic detected by Operations Behavior Anomaly Detection	Program Path: %Path% Program Hash: %SHA256% Remote IP: %IP% Local Port: %PORT% L4 Protocol: %STRING" L7 Protocol: %STRING% %THROTTLING_INFO_MSG%
4880	Warning	anomaly_detect	DLL Injection Prevention disabled	
4881	Warning	anomaly_detect	DLL Injection Prevention blocked: %OBJ_PATH%	Threat Image Path: %SUBJ_PATH% Threat User: %USER%
5120	Warning	change_control	Change to an ICS file blocked by OT Application Safeguard.	Blocked Process: %PATH% Target File: %PATH%

Event ID	Level	Category	Event	Details
5376	Warning	device_control	Device Control disabled	
5377	Warning	device_control	USB access blocked: %PATH%	Access Image Path: %PATH% Access User: %USERNAME% Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING%
5378	Warning	device_control	USB autorun.inf file blocked: %PATH%	
5379	Warning	device_control	Untrusted USB device connected	Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING% Active User: %STRING%
5380	Warning	device_control	Untrusted USB device disconnected	Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING%

Event ID	Level	Category	Event	Details
				Active User: %STRING%
5381	Warning	device_control	Block USB AutoRun disabled	
5382	Warning	device_control	USB Access Tracking disabled	
5383	Warning	device_control	USB Auto Scan disabled	
5888	Warning	lockdown	File access allowed: %PATH%	Access Image Path: %PATH% Access User: %USERNAME% Mode: %MODE% Reason: %ALLOWED_REASON% File hash allowed: %SHA256_HASHSTR% %THROTTLING_INFO_MSG%
5889	Warning	lockdown	File access blocked: C:\object_file_path	Access Image Path: %PATH% Access User: %USERNAME% Mode: %MODE%

Event ID	Level	Category	Event	Details
				Reason: %BLOCKED_REASON% File hash blocked: %SHA256_HEXSTR% %THROTTLING_INFO_MSG%
5890	Warning	lockdown	Unable to add to or update Approved List: %PATH%	
5891	Warning	lockdown	Application Lockdown disabled	
5892	Warning	lockdown	DLL/Driver Lockdown disabled	
5893	Warning	lockdown	Script Lockdown disabled	
5894	Warning	lockdown	Intelligent Runtime Learning disabled	
5895	Warning	lockdown	Approved List initialization canceled	
6144	Warning	update	Component update unsuccessful (%AU_ERROR_CODE%)	Update Source: %UPDATE_URL% [Original Version] %COMPONENTS_INFO% [Updated Version] %COMPONENTS_INFO%

Event ID	Level	Category	Event	Details
6145	Warning	update	Failed to duplicate components.	Update Source: %UPDATE_URL%
6400	Warning	network_restriction	Connections blocked by either the Network Access Restrictions or the Network Access Blocklist	Time Period: %TIME_START% ~ %TIME_END% Connections Blocked: %BLOCKED_COUNT% Direction: %DIRECTION% Remote IP: %REMOTE_IP% Destination Port: %DESTINATION_PORT% Program Path: %Path% Program Hash:%SHA256%; Program Size:%Size% Certificate: %CertificateSignature% Vendor: %VendorName" Product: %Product%

Event ID	Level	Category	Event	Details
6401	Warning	network_restriction	Unable to turn on Isolation Mode	
6402	Warning	network_restriction	Unable to activate Network Access Restrictions	
8448	Critical	system	Protection stopped manually via protection stop button or CLI	
8449	Critical	system	Protection resumed	%REASON% could be one of the followings: • Manually via the protection resume button or CLI • Automatically after device reboot
8706	Critical	intelli_av	Real-Time Scan disabled	
9216	Critical	change_control	Maintenance Mode started	
9217	Critical	change_control	Maintenance Mode ended	
10496	Critical	network_restriction	Isolation Mode started	
10497	Critical	network_restriction	Isolation Mode stopped	

Server Event Log Descriptions for Stellar Agent (Windows)

This table lists the server event log descriptions for Stellar Agent.

Event ID	Event
33027	Switch agent (%s) to policy mode
33028	Switch agent (%s) to individual mode
33029	Deploy policy with version: %s
33041	Modify in common use (DLL Injection Prevention, Device Control, OT Application Safeguard, OBAD) setting for [%s] group policy with version: %s
33042	Modify real-time scan settings for [%s] group policywith version: %s
33043	Modify schedule scan settings for [%s] group policywith version: %s
33044	Maintain Device Control list for [%s] group policy with version: %s
33045	Maintain User-Defined Suspicious Object list for [%s] group policy with version: %s
33046	Maintain Operations Behavior Anomaly Detection Watch List for [%s] group policy with version: %s
33047	Maintain Trusted Certification list for [%s] group policy with version: %s
33048	Maintain OT Application Safeguard list for [%s] group policy with version: %s
33049	Modify agent password for [%s] group policy with version: %s
33056	Modify available patch setting for [%s] group policy with version: %s
33057	Maintain an authorized process for [%s] group policy with version: %s
33058	Modify schedule update settings for [%s] group policy with version: %s

Event ID	Event
33059	Modify lockdown config for [%s] group policy with version: %s
33105	Send individual command to agent (%s)
33106	Send protection command <Configure Maintenance Mode> to agents
33107	Send protection command <Scan Now> to agents
33108	Send update command <Update Agent Component> to agents
33109	Send update command <Deploy Agent Patches> to agents
33110	Send protection command <Initialize Lockdown Approved List> to agents
33111	Send update command <Check Connections> to agents
33112	Send update command <Apply Policies> to agents
33115	Send protection command <Enable Isolation Mode> to agents
33116	Send protection command <Disable Isolation Mode> to agents
33121	Apply event action to agent (%AGENT_NAME%)
33122	Apply event action <%ACTION_TYPE%> to agent(s)
33283	Network Connection Added to Baseline
37122	Set activation code with policy version: %s
37123	Active agents
37124	Inactive agents

Log Descriptions for Stellar Agent (Windows-Legacy)

Topics in this section include:

- [Agent Event Log Descriptions for Stellar Agent \(Windows-Legacy\) \(on page 283\)](#)
- [Agent Error Code Descriptions for Stellar Agent \(Windows-Legacy\) \(on page 335\)](#)
- [Server Event Log Descriptions for Stellar Agent \(Windows-Legacy\) \(on page 339\)](#)

Agent Event Log Descriptions for Stellar Agent (Windows-Legacy)

This table details the Windows event log descriptions for Stellar Agent (Windows-Legacy).

Event ID	Level	Category	Event	Details
1000	Information	System	Service started	
1001	Warning	System	Service stopped	
1002	Information	System	Application Lockdown "enforce" mode enabled	
1003	Warning	System	Application Lockdown "detect" mode enabled	
1004	Warning	System	Application Lockdown disabled	
1005	Information	System	Administrator password changed	
1006	Information	System	User password changed	
1007	Information	System	User account enabled	
1008	Information	System	User account disabled	
1009	Information	System	Product activated	

Event ID	Level	Category	Event	Details
1010	Information	System	Product deactivated	
1011	Warning	System	License Expired. Grace period enabled	
1012	Warning	System	License Expired. Grace period ended	
1013	Information	System	Product configuration import started: %path%	
1014	Information	System	Product configuration import completed: %path%	
1015	Information	System	Product configuration exported to: %path%	
1016	Information	System	USB Malware Protection set to Allow	
1017	Information	System	USB Malware Protection set to Block	
1018	Information	System	USB Malware Protection enabled	
1019	Warning	System	USB Malware Protection disabled	

Event ID	Level	Category	Event	Details
1025	Information	System	Memory Randomization enabled	
1026	Warning	System	Memory Randomization disabled	
1027	Information	System	API Hooking Prevention set to Allow	
1028	Information	System	API Hooking Prevention set to Block	
1029	Information	System	API Hooking Prevention enabled	
1030	Warning	System	API Hooking Prevention disabled	
1031	Information	System	DLL Injection Prevention set to Allow	
1032	Information	System	DLL Injection Prevention set to Block	
1033	Information	System	DLL Injection Prevention enabled	
1034	Warning	System	DLL Injection Prevention disabled	

Event ID	Level	Category	Event	Details
1035	Information	System	Pre-defined Trusted Update enabled	
1036	Information	System	Pre-defined Trusted Update disabled	
1037	Information	System	DLL/Driver Lockdown enabled	
1038	Warning	System	DLL/Driver Lockdown disabled	
1039	Information	System	Script Lockdown enabled	
1040	Warning	System	Script Lockdown disabled	
1041	Information	System	Script added	File extension: %extension% Interpreter: %interpreter%
1042	Information	System	Script removed	File extension: %extension% Interpreter: %interpreter%
1044	Information	System	Exception path enabled	
1045	Information	System	Exception path disabled	

Event ID	Level	Category	Event	Details
1047	Information	System	Trusted certificate enabled	
1048	Information	System	Trusted certificate disabled	
1049	Information	System	Write Protection enabled	
1050	Warning	System	Write Protection disabled	
1051	Information	System	Write Protection set to Allow	
1052	Information	System	Write Protection set to Block	
1055	Information	System	Added file to Write Protection List Path: %path%	
1056	Information	System	Removed file from Write Protection List Path: %path%	
1057	Information	System	Added file to Write Protection Rules List Path: %path% Process: %process%	
1058	Information	System	Removed file from Write Protection Rules List Path: %path%	

Event ID	Level	Category	Event	Details
			Process: %process%	
1059	Information	System	Added folder to Write Protection Rules List Path: %path% Scope: %scope%	
1060	Information	System	Removed folder from Write Protection Rules List Path: %path% Scope: %scope%	
1061	Information	System	Added folder to Write Protection Rules List Path: %path% Scope: %scope% Process: %process%	
1062	Information	System	Removed folder from Write Protection Rules List Path: %path% Scope: %scope% Process: %process%	
1063	Information	System	Added registry value to Write Protection Rules List	

Event ID	Level	Category	Event	Details
			Registry Key: %regkey%	
			Registry Value Name: %regvalue%	
1064	Information	System	Removed registry value from Write Protection Rules List Registry Key: %regkey%	
			Registry Value Name: %regvalue%	
1065	Information	System	Added registry value to Write Protection Rules List Registry Key: %regkey%	
			Registry Value Name: %regvalue%	
			Process: %process%	
1066	Information	System	Removed registry value from Write Protection Rules List Registry Key: %regkey%	
			Registry Value Name: %regvalue%	
			Process: %process%	

Event ID	Level	Category	Event	Details
1067	Information	System	Added registry key to Write Protection Rules List Path: %regkey% Scope: %scope%	
1068	Information	System	Removed registry key from Write Protection Rules List Path: %regkey% Scope: %scope%	
1069	Information	System	Added registry key to Write Protection Rules List Path: %regkey% Scope: %scope% Process: %process%	
1070	Information	System	Removed registry key from Write Protection Rules List Path: %regkey% Scope: %scope% Process: %process%	
1071	Information	System	Custom Action set to Ignore	

Event ID	Level	Category	Event	Details
1072	Information	System	Custom Action set to Quarantine	
1073	Information	System	Custom Action set to Ask StellarOne	
1074	Information	System	Quarantined file is restored.	Original Location: %path% Source: %source%
1075	Information	System	Quarantined file is deleted.	Original Location: %path% Source: %source%
1076	Information	System	Integrity Monitoring enabled	
1077	Information	System	Integrity Monitoring disabled	
1079	Information	System	Server certification imported: %path%	
1080	Information	System	Server certification exported: %path%	
1081	Information	System	Managed mode configuration imported: %path%	
1082	Information	System	Managed mode configuration exported: %path%	

Event ID	Level	Category	Event	Details
1083	Information	System	Managed mode enabled	
1084	Information	System	Managed mode disabled	
1085	Information	System	Protection applied to Write Protection Rules List and Approved List while Write Protection was enabled	
1086	Warning	System	Protection applied to Write Protection Rules List while Write Protection was enabled.	
1088	Information	System	Windows Update Support enabled	
1089	Information	System	Windows Update Support disabled	
1094	Information	System	Applied a patch to agent by StellarOne File applied: %file_name%	
1096	Information	System	Trusted hash enabled	
1097	Information	System	Trusted hash disabled	

Event ID	Level	Category	Event	Details
1099	Information	System	Storage device access set to Allow	
1100	Information	System	Storage device access set to Block	
1101	Information	System	Storage device control enabled	
1102	Warning	System	Storage device control disabled	
1103	Information	System	Event Log settings changed	Windows Event Log: %ON off% Level: Warning Log: %ON off% Information Log: %ON off% System Log: %ON off% Exception Path Log: %ON off% Write Protection Log: %ON off% List Log: %ON off% Approved Access Log: DllDriver Log: %ON off% Trusted Updater Log: %ON off% Exception Path Log: %ON off% Trusted Certification Log: %ON off%

Event ID	Level	Category	Event	Details
				Trusted Hash Log: %ON off% Write Protection Log: %ON off% Blocked Access Log: %ON off% USB Malware Protection Log: %ON off% Execution Prevention Log: %ON off% Integrity Monitoring Log File Created Log: %ON off% File Modified Log: %ON off% File Deleted Log: %ON off% File Renamed Log: %ON off% RegValue Modified Log: %ON off% RegValue Deleted Log: %ON off% RegKey Created Log: %ON off% RegKey Deleted Log: %ON off% RegKey Renamed Log: %ON off% Device Control Log: %ON off%

Event ID	Level	Category	Event	Details
				Debug Log: %ON off%
1104	Warning	System	Memory Randomization is not available in this version of Windows.	
1105	Information	System	Blocked File Notification enabled	
1106	Information	System	Blocked File Notification disabled	
1107	Information	System	Administrator password changed remotely	
1108	Information	System	Prescan completed successfully	Prescan log: %PATH% Scanned files: %NUM% Infected files: %NUM% Files with resolved threats: %NUM%
1109	Warning	System	Prescan completed successfully; system restart required	Prescan log: %PATH% Scanned files: %NUM% Infected files: %NUM% Files with resolved threats: %NUM%

Event ID	Level	Category	Event	Details
				Files with resolved threats after restart: %NUM%
1110	Warning	System	Prescan unsuccessful	Prescan log: %PATH% Scanned files: %NUM% Infected files: %NUM% Files with resolved threats: %NUM% Files with resolved threats after restart: %NUM% Files with unresolved threats: %NUM%
1111	Information	System	Fileless Attack Prevention enabled	
1112	Warning	System	Fileless Attack Prevention disabled	
1113	Warning	System	Intelligent Runtime Learning enabled	
1114	Warning	System	Intelligent Runtime Learning disabled	

Event ID	Level	Category	Event	Details
1115	Critical	System	Protection stopped manually via protection stop button or CLI	
1116	Critical	System	Protection resumed	%REASON% could be one of the followings: • Manually via the protection resume button or CLI • Automatically after device reboot
1117	Information	System	USB Access Tracking enabled	
1118	Warning	System	USB Access Tracking disabled	
1119	Information	System	USB Auto Scan enabled	
1120	Warning	System	USB Auto Scan disabled	
1500	Information	List	Trusted Update started.	
1501	Information	List	Trusted Update stopped.	
1502	Information	List	Approved List import started: %path%	

Event ID	Level	Category	Event	Details
1503	Information	List	Approved List import complete: %path%	
1504	Information	List	Approved List exported to: %path%	
1505	Information	List	Added to Approved List: %path%	
1506	Information	List	Added to Trusted Updater List: %path%	
1507	Information	List	Removed from Approved List: %path%	
1508	Information	List	Removed from Trusted Updater List: %path%	
1509	Information	List	Approved List updated: %path%	
1510	Information	List	Trusted Updater List updated: %path%	
1511	Warning	List	Unable to add to or update Approved List: %path%	
1512	Warning	List	Unable to add to or update Trusted Updater List: %path%	

Event ID	Level	Category	Event	Details
1513	Information	System	Added to Exception Path List	Type: %exceptionpathtype% Path: %exceptionpath%
1514	Information	System	Removed from Exception Path List	Type: %exceptionpathtype% Path: %exceptionpath%
1515	Information	System	Added to Trusted Certification List	Label: %label% Hash: %hashvalue% Type: %type% Subject: %subject% Issuer: %issuer%
1516	Information	System	Removed from Trusted Certification List	Label: %label% Hash: %hashvalue% Type: %type% Subject: %subject% Issuer: %issuer%
1517	Information	System	Added to Trusted Hash List.%n	Label : %label% Hash : %hashvalue% Type : %type% Add to Approved List: %yes no%

Event ID	Level	Category	Event	Details
				Path : %path% Note: %note%
1518	Information	System	Removed from Trusted Hash List.%n	Label : %label% Hash : %hashvalue% Type : %type% Add to Approved List: %yes no% Path : %path% Note: %note%
1519	Information	List	Removed from Approved List remotely: %path%	
1520	Warning	List	Unable to create Approved List because an unexpected error occurred during enumeration of the files in %1 %n Error Code: %2 %n	
1521	Information	System	Added Fileless Attack Prevention exception	Label : %label% Target Process: %process_name% Arguments: %arguments% %regex_flag% Parent Process 1 Image Path: %path%

Event ID	Level	Category	Event	Details
				Parent Process 2 Image Path: %path% Parent Process 3 Image Path: %path% Parent Process 4 Image Path: %path%
1522	Information	System	Removed Fileless Attack Prevention exception	Label : %label% Target Process: %process_name% Arguments: %arguments% %regex_flag% Parent Process 1 Image Path: %path% Parent Process 2 Image Path: %path% Parent Process 3 Image Path: %path% Parent Process 4 Image Path: %path%
1523	Information	System	Maintenance Mode started	
1524	Information	System	Leaving Maintenance Mode	
1525	Information	System	Maintenance Mode stopped	

Event ID	Level	Category	Event	Details
1526	Information	List	Added to Approved List in Maintenance Mode Path: %1 Hash: %2	
1527	Information	List	Approved List updated in Maintenance Mode Path: %1 Hash: %2	
1528	Information	List	Maintenance Mode Summary	
1529	Information	List	Approved List initialization started	
1530	Information	List	Approved List initialization completed	
1531	Warning	List	Approved List initialization canceled	
2000	Information	Access Approved	File access allowed: %path%	Access Image Path: %path% Access User: %username% Mode: %mode% List: %list%

Event ID	Level	Category	Event	Details
2001	Warning	Access Approved	File access allowed: %path%	Access Image Path: %path% Access User: %username% Mode: %mode% File Hash allowed: %hash%
2002	Warning	Access Approved	File access allowed: %path% Unable to get the file path while checking the Approved List	Access Image Path: %path% Access User: %username% Mode: %mode%
2003	Warning	Access Approved	File access allowed: %path% Unable to calculate hash while checking the Approved List	Access Image Path: %path% Access User: %username% Mode: %mode%
2004	Warning	Access Approved	File access allowed: %path% Unable to get notifications to monitor process	
2005	Warning	Access Approved	File access allowed: %path% Unable to add process to non exception list	
2006	Information	Access Approved	File access allowed: %path%	Access Image Path: %path% Access User: %username%

Event ID	Level	Category	Event	Details
				Mode: %mode%
2007	Warning	Access Approved	File access allowed: %path% An error occurred while checking the Exception Path List	Access Image Path: %path% Access User: %username% Mode: %mode%
2008	Warning	Access Approved	File access allowed: %path% An error occurred while checking the Trusted Certification List	Access Image Path: %path% Access User: %username% Mode: %mode%
2011	Information	Access Approved	Registry access allowed Registry Key: %regkey% Registry Value Name: %regvalue%	Access Image Path: %path% Access User: %username% Mode: %mode%
2012	Information	Access Approved	Registry access allowed Registry Key: %regkey%	Access Image Path: %path% Access User: %username% Mode: %mode%
2013	Information	Access Approved	Change of File/Folder allowed by Exception List: %path%	Access Image Path: %path% Access User: %username% Mode: %mode%

Event ID	Level	Category	Event	Details
2015	Information	Access Approved	Change of Registry Value allowed by Exception List Registry Key: %regkey% Registry Value Name: %regvalue%	Access Image Path: %path% Access User: %username% Mode: %mode%
2016	Information	Access Approved	Change of Registry Key allowed by Exception List Registry Key: %regkey%	Access Image Path: %path% Access User: %username% Mode: %mode%
2017	Warning	Access Approved	Change of File/Folder allowed: %path%	Access Image Path: %path% Access User: %username% Mode: %mode%
2019	Warning	Access Approved	Change of Registry Value allowed Registry Key: %regkey% Registry Value Name: %regvalue%	Access Image Path: %path% Access User: %username% Mode: %mode%
2020	Warning	Access Approved	Change of Registry Key allowed Registry Key: %regkey%	Access Image Path: %path% Access User: %username% Mode: %mode%

Event ID	Level	Category	Event	Details
2021	Warning	Access Approved	File access allowed: %path% An error occurred while checking the Trusted Hash List	Access Image Path: %path% Access User: %username% Mode: %mode%
2022	Warning	Access Approved	Process allowed by Fileless Attack Prevention: %path% %argument%	Access User: %username% Parent Process 1 Image Path: %path% Parent Process 2 Image Path: %path% Parent Process 3 Image Path: %path% Parent Process 4 Image Path: %path% Mode: Unlocked Reason: %reason%
2500	Warning	Access Blocked	File access blocked	
2503	Warning	Access Blocked	Change of File/Folder blocked: %path%	Access Image Path: %path% Access User: %username% Mode: %mode%
2505	Warning	Access Blocked	Change of Registry Value blocked.	Access Image Path: %path% Access User: %username%

Event ID	Level	Category	Event	Details
			Registry Key: %regkey% Registry Value Name: %regvalue%	Mode: %mode%
2506	Warning	Access Blocked	Change of Registry Key blocked. Registry Key: %regkey%	Access Image Path: %path% Access User: %username% Mode: %mode%
2507	Information	Access Blocked	Action completed successfully: %path%	Action: %action% Source: %source%
2508	Warning	Access Blocked	Unable to take specified action: %path%	Action: %action% Source: %source%
2509	Warning	Access Blocked	File access blocked: %path%	Access Image Path: %path% Access User: %username% Mode: %mode% Reason: Not in Approved List File Hash blocked: %hash%
2510	Warning	Access Blocked	File access blocked: %path%	Access Image Path: %path% Access User: %username% Mode: %mode%

Event ID	Level	Category	Event	Details
				Reason: Hash does not match expected value File Hash blocked: %hash%
2511	Information	Access Blocked	Change of File/Folder blocked: %path%	Access Image Path: %path% Access User: %username% Mode: %mode%
2512	Warning	Access Blocked	Change of Registry Value blocked. Registry Key: %regkey% Registry Value Name: %regvalue%	Access Image Path: %path% Access User: %username%  Note: Enabling the Service Creation Prevention feature triggers Event ID 2512.
2513	Warning	Access Blocked	Process blocked by Fileless Attack Prevention: %path% %argument%	Access User: %username% Parent Process 1 Image Path: %path% Parent Process 2 Image Path: %path% Parent Process 3 Image Path: %path%

Event ID	Level	Category	Event	Details
				Parent Process 4 Image Path: %path% Mode: locked Reason: %reason%
2514	Warning	Access Blocked	File access blocked: %BLOCKED_FILE_PATH%	Access Image Path: %PARENT_PROCESS_PATH% Access User: %USER_NAME% Reason: Blocked file is in a folder that has the case sensitive attribute enabled.
3000	Warning	USB Malware Protection	Device access allowed: %path%	Access Image Path: %path% Access User: %username% Device Type: %type%
3001	Warning	USB Malware Protection	Device access blocked: %path%	Access Image Path: %path% Access User: %username% Device Type: %type%
4002	Warning	Process Protection Event	API Hooking allowed: %path%	Threat Image Path: %path% Threat User: %username%

Event ID	Level	Category	Event	Details
4003	Warning	Process Protection Event	API Hooking blocked: %path%	Threat Image Path: %path% Threat User: %username%
4004	Warning	Process Protection Event	DLL Injection allowed: %path%	Threat Image Path: %path% Threat User: %username%
4005	Warning	Process Protection Event	DLL Injection blocked: %path%	Threat Image Path: %path% Threat User: %username%
4500	Information	Changes in System	File/Folder created: %path%	Access Image Path: %path% Access Process Id: %pid% Access User: %username%
4501	Information	Changes in System	File modified: %path%	Access Image Path: %path% Access Process Id: %pid% Access User: %username%
4502	Information	Changes in System	File/Folder deleted: %path%	Access Image Path: %path% Access Process Id: %pid% Access User: %username%

Event ID	Level	Category	Event	Details
4503	Information	Changes in System	File/Folder renamed: %path% New Path: %path%	Access Image Path: %path% Access Process Id: %pid% Access User: %username%
4504	Information	Changes in System	Registry Value modified. Registry Key: %regkey% Registry Value Name: %regvalue% Registry Value Type: %regvaluetype%	Access Image Path: %path% Access Process Id: %pid% Access User: %username%
4505	Information	Changes in System	Registry Value deleted. Registry Key: %regkey% Registry Value Name: %regvalue%	Access Image Path: %path% Access Process Id: %pid% Access User: %username%
4506	Information	Changes in System	Registry Key created. Registry Key: %regkey%	Access Image Path: %path% Access Process Id: %pid% Access User: %username%
4507	Information	Changes in System	Registry Key deleted. Registry Key: %regkey%	Access Image Path: %path% Access Process Id: %pid%

Event ID	Level	Category	Event	Details
				Access User: %username%
4508	Information	Changes in System	Registry Key renamed. Registry Key: %regkey% New Registry Key: %regkey%	Access Image Path: %path% Access Process Id: %pid% Access User: %username%
5000	Warning	Device Control	Storage device access allowed: %PATH%	Access Image path: %PATH% Access User: %USERNAME% Device Type: %TYPE% %DEVICEINFO%
5001	Warning	Device Control	Storage device access blocked: %PATH%	Access Image path: %PATH% Access User: %USERNAME% Device Type: %TYPE% %DEVICEINFO%
5002	Information	Device Control	Trusted USB device connected	Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING% Active User: %STRING%
5003	Information	Device Control	Trusted USB device disconnected	Vendor ID: %HEX%

Event ID	Level	Category	Event	Details
				Product ID: %HEX% Serial Number: %STRING% Active User: %STRING%
5004	Warning	Device Control	Untrusted USB device connected	Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING% Active User: %STRING%
5005	Warning	Device Control	Untrusted USB device disconnected	Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING% Active User: %STRING%
5006	Information	Device Control	USB device added into trusted device list	Device Type: %STRING% Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING% Type: %STRING%

Event ID	Level	Category	Event	Details
5007	Information	Device Control	USB device removed from trusted device list	Device Type: %STRING% Vendor ID: %HEX% Product ID: %HEX% Serial Number: %STRING%
6000	Information	System	%Result%	Update Source: %SERVER% [Original Version] Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION%

Event ID	Level	Category	Event	Details
				[Updated Version] Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION% The Agent attempted to request updates from the following Update Agents but failed: Host: %IP1% Port: %PORT% Host: %IP2% Port: %PORT%

Event ID	Level	Category	Event	Details
6001	Warning	System	Update unsuccessful	Update failed: %ERROR_MSG% (%ERROR_CODE%) [Details] Update Source: %SERVER% [Original Version] Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION% [Updated Version] Virus Pattern: %VERSION%

Event ID	Level	Category	Event	Details
				Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION% The Agent attempted to request updates from the following Update Agents but failed: Host: %IP1% Port: %PORT% Host: %IP2% Port: %PORT%
6002	Information	System	Malware scan started: %SCAN_TYPE%	Files to scan: %SCAN_FOLDE R_TYPE% Scanned folders: %PATHS%

Event ID	Level	Category	Event	Details
				Excluded paths: %PATHS% Excluded files: %PATHS% Excluded extensions: %PATHS% [Components] Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION%
6003	Information	System	Malware scan completed: %SCAN_TYPE%.	Files to scan: %SCAN_FOLDE R_TYPE%

Event ID	Level	Category	Event	Details
			Number of infected files: %NUM%	Scanned folders: %PATHS% Excluded paths: %PATHS% Excluded files: %PATHS% Excluded extensions: %PATHS% Start date/time: %DATE_TIME% End date/time: %DATE_TIME% Number of scanned files: %NUM% Number of infected files: %NUM% Number of cleaned files: %NUM% Number of files cleaned after reboot: %NUM% [Components] Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION%

Event ID	Level	Category	Event	Details
				Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION%
6004	Warning	System	Malware scan unsuccessful: %SCAN_TYPE% %ERROR%	Files to scan: %SCAN_FOLDE R_TYPE% Scanned folders: %PATHS% Excluded paths: %PATHS% Excluded files: %PATHS% Excluded extensions: %PATHS% Start date/time: %DATE_TIME% End date/time: %DATE_TIME% Number of scanned files: %NUM% Number of infected files: %NUM%

Event ID	Level	Category	Event	Details
				Number of cleaned files: %NUM% Number of files cleaned after reboot: %NUM% [Components] Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION%
6005	Information	System	Malware detected: %ACTION% File path: %PATH%	Reboot required: %NEED_REBOOT% [Scan Result]

Event ID	Level	Category	Event	Details
				Threat type: %TYPE% Threat name: %NAME% [Components] Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION%
6006	Warning	System	Malware detected. Unable to perform scan actions: %PATH%	First action: %1ST_ACTION% Second action: %2ND_ACTION% Threat type: %TYPE%

Event ID	Level	Category	Event	Details
				Threat name: %NAME% [Components] Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION%
6007	Warning	Maintenance Mode	Malware detected in Maintenance Mode (file quarantine successful): %PATH%	Component versions: %VERSION% Virus Pattern: %VERSION% Spyware Pattern: %VERSION%

Event ID	Level	Category	Event	Details
				Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION%
6008	Warning	Maintenance Mode	Malware detected in Maintenance Mode (file quarantine unsuccessful): %PATH%	Component versions: Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION%

Event ID	Level	Category	Event	Details
				Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION% Scanner: %VERSION%
6009	Warning	Maintenance Mode	Malware detected in Maintenance Mode: %PATH%	Component versions: Virus Pattern: %VERSION% Spyware Pattern: %VERSION% Digital Signature Pattern: %VERSION% Program Inspection Pattern: %VERSION% Damage Cleanup Template: %VERSION% Damage Cleanup Engine Configuration: %VERSION% Virus Scan Engine: %VERSION% Damage Cleanup Engine: %VERSION%

Event ID	Level	Category	Event	Details
				Scanner: %VERSION%
6010	Information	System	Components duplicated successfully.	Update Source: %URL%
6011	Warning	System	Failed to duplicate components.	Update Source: %URL%
6012	Warning	System	Unable to scan compressed files that are password protected or contain password protected files.	
8000	Information	System	Real Time Scan is enabled.	
8001	Warning	System	Real Time Scan is disabled.	
8010	Warning	System	Incoming files were scanned by antivirus. Action was taken according to settings.	File Path: %PATH% File Hash: %HASH% Threat Type: %TYPE% Threat Name: %NAME% Action Result: %INTEGER% Quarantine Path: %PATH%
8011	Warning	System	Application execution was blocked by antivirus.	Process Image Path: %PATH% File Hash: %HASH% Threat Type: %TYPE%

Event ID	Level	Category	Event	Details
				Threat Name: %NAME%
8012	Information	System	Incoming file detected malicious and quarantined successfully	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Quarantine Path: %PATH% Reboot Required: %NEED_REBOOT%
8013	Warning	System	Failed to quarantine incoming file detected malicious	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
8014	Information	System	Malicious file execution was detected. The infected executable file was quarantined successfully	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Quarantine Path: %PATH%

Event ID	Level	Category	Event	Details
				Reboot Required: %NEED_REB OOT%
8015	Warning	System	Malicious file execution detected. Failed to quarantine the infected executable file	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
8016	Warning	suspicious_objects	Suspicious program execution blocked	File Path: %PATH% File Hash: %STRING%
8017	Warning	System	Application execution was bypassed by antivirus.	Application execution was bypassed by antivirus. Process Image Path: %PATH% File Hash: %HASH% Threat Type: %TYPE% Threat Name: %NAME%
8018	Warning	System	The malicious application behavior was detected by Ransomware Behavior Monitor	"The malicious application behavior was detected by Ransomware Behavior Monitor.%n [Detail]%n

Event ID	Level	Category	Event	Details
				Program Path: %1%n Program Hash: %2%n Program Size: %3%n Certificate: %4%n Vendor: %5%n Product: %6n Rules Violated: %7%n Description: %9%n %THROTTLING_I NFO_MSG% THROTTLING_IN FO_MSG wording: 10 event(s) throttled within time window 2022-08-19T11:4 2:30 ~ 2022-08-19T11:4 3:07"
8019	Information	System	Ransomware Behavior Monitor enabled	
8020	Warning	System	Ransomware Behavior Monitor disabled	
8500	Information	System	Scheduled component update has been enabled. Next	

Event ID	Level	Category	Event	Details
			update will be on %TIME% (agent's local system time).	
8501	Information	System	Scheduled component update has been disabled.	
8601	Information	anomaly_detect	Operations Behavior Anomaly Detection (User Login) enabled	Mode: %Mode% Level: %Level% Learning time: %LearningTime% day(s)
8602	Information	anomaly_detect	Operations Behavior Anomaly Detection (User Login) disabled	
8603	Information	anomaly_detect	Operations Behavior Anomaly Detection (Application Behavior) enabled	Mode: %Mode% Level: %Level% Learning time: %LearningTime% day(s)
8604	Warning	anomaly_detect	Operations Behavior Anomaly Detection (Application Behavior) disabled	
8605	Information	anomaly_detect	Operations Behavior Anomaly Detection (Script Behavior) enabled	Mode: %Mode% Level: %Level% Learning time: %LearningTime% day(s)

Event ID	Level	Category	Event	Details
8606	Warning	anomaly_detect	Operations Behavior Anomaly Detection (Script Behavior) disabled	
8610	warning	anomaly_detect	An abnormal user login detected by Operations Behavior Anomaly Detection	Domain: %Domain% Account: %Account% Login Type: %LoginType% Source IP: %IP%
8611	warning	anomaly_detect	A user login failure detected by Operations Behavior Anomaly Detection	Domain: %Domain% Account: %Account% Login Type: %LoginType% Source IP: %IP%
8612	warning	anomaly_detect	An unrecognized application detected by Operations Behavior Anomaly Detection	PID: %PID% Program Path: %Path% Program Hash: %SHA256% Program Size: %Size% Certificate: %CertificateSigner% Vendor: %VendorName% Product: %Product%

Event ID	Level	Category	Event	Details
8613	warning	anomaly_detect	Malicious application behavior detected by Operations Behavior Anomaly Detection	Program Path: %Path% Program Hash: %SHA256% Program Size: %Size% Certificate: %CertificateSigner% Vendor: %VendorName% Product: %Product%
8614	warning	anomaly_detect	Suspicious application behavior detected by Operations Behavior Anomaly Detection	Program Path: %Path% Program Hash: %SHA256% Program Size: %Size% Certificate: %CertificateSigner% Vendor: %VendorName% Product: %Product%
8615	warning	anomaly_detect	Script Behavior allowed by Operations Behavior Anomaly Detection: %PATH% %ARGUMENT%	Access User: %USERNAME% Parent Process 1: %PATH% %ARGUMENT% Parent Process 2: %PATH% %ARGUMENT%

Event ID	Level	Category	Event	Details
				Parent Process 3: %PATH% %ARGUMENT% Parent Process 4: %PATH% %ARGUMENT% Mode: %MODE% Level: %LEVEL% %THROTTLING_I NFO_MSG%
8616	warning	anomaly_det ect	Script Behavior blocked by Operations Behavior Anomaly Detection: %PATH% %ARGUMENT%	Access User: %USERNAME% Parent Process 1: %PATH% %ARGUMENT% Parent Process 2: %PATH% %ARGUMENT% Parent Process 3: %PATH% %ARGUMENT% Parent Process 4: %PATH% %ARGUMENT% Mode: %MODE% Level: %LEVEL% %THROTTLING_I NFO_MSG%
8620	Information	anomaly_det ect	Login account added baseline	Domain: %Domain% Account: %Account% Login Type: %LoginType%

Event ID	Level	Category	Event	Details
				Source IP: %IP%
8621	Information	anomaly_detect	Login account excluded from baseline	Domain: %Domain% Account: %Account% Login Type: %LoginType% Source IP: %IP%
8622	Information	anomaly_detect	Application added to baseline	Application Path: %Path%
8623	Information	anomaly_detect	Application excluded from baseline	Application Path: %Path%
8624	Information	anomaly_detect	Script behavior added to baseline	Access User: %USERNAME% ID:%ID% Monitored Process / Script: %PATH% %ARGUMENT% Parent Process 1: %PATH% %ARGUMENT% Parent Process 2: %PATH% %ARGUMENT% Parent Process 3: %PATH% %ARGUMENT% Parent Process 4: %PATH% %ARGUMENT%

Event ID	Level	Category	Event	Details
8625	Information	anomaly_detect	Script behavior excluded from baseline	ID:%ID% Monitored Process / Script: %PATH% %ARGUMENT% Parent Process 1: %PATH% %ARGUMENT% Parent Process 2: %PATH% %ARGUMENT% Parent Process 3: %PATH% %ARGUMENT% Parent Process 4: %PATH% %ARGUMENT%

Agent Error Code Descriptions for Stellar Agent (Windows-Legacy)

This list describes the various error codes used in Stellar Agent (Windows-Legacy) agent.

Code	Description
0x00040200	Operation successful.
0x80040201	Operation unsuccessful.
0x80040202	Operation unsuccessful.
0x00040202	Operation partially successful.
0x00040203	Requested function not installed.
0x80040203	Requested function not supported.
0x80040204	Invalid argument.

Code	Description
0x80040205	Invalid status.
0x80040206	Out of memory.
0x80040207	Busy. Request ignored.
0x00040208	Retry. (Usually the result of a task taking too long)
0x80040208	System Reserved. (Not used)
0x80040209	The file path is too long.
0x0004020a	System Reserved. (Not used)
0x8004020b	System Reserved. (Not used)
0x0004020c	System Reserved. (Not used)
0x0004020d	System Reserved. (Not used)
0x8004020d	System Reserved. (Not used)
0x0004020e	Reboot required.
0x8004020e	Reboot required for unexpected reason.
0x0004020f	Allowed to perform task.
0x8004020f	Permission denied.
0x00040210	System Reserved. (Not used)
0x80040210	Invalid or unexpected service mode.

Code	Description
0x00040211	System Reserved. (Not used)
0x80040211	Requested task not permitted in current status. Check license.
0x00040212	System Reserved. (Not used)
0x00040213	System Reserved. (Not used)
0x80040213	Passwords do not match.
0x00040214	System Reserved. (Not used)
0x80040214	System Reserved. (Not used)
0x00040215	Not found.
0x80040215	"Expected, but not found."
0x80040216	Authentication is locked.
0x80040217	Invalid password length.
0x80040218	Invalid characters in password.
0x00040219	Duplicate password. Administrator and Restricted User passwords cannot match.
0x80040220	System Reserved. (Not used)
0x80040221	System Reserved. (Not used)
0x80040222	System Reserved. (Not used)
0x80040223	File not found (as expected, and not an error).

Code	Description
0x80040224	System Reserved. (Not used)
0x80040225	System Reserved. (Not used)
0x80040240	Library not found.
0x80040241	Invalid library status or unexpected error in library function.
0x80040260	System Reserved. (Not used)
0x80040261	System Reserved. (Not used)
0x80040262	System Reserved. (Not used)
0x80040263	System Reserved. (Not used)
0x80040264	System Reserved. (Not used)
0x00040265	System Reserved. (Not used)
0x80040265	System Reserved. (Not used)
0x80040270	System Reserved. (Not used)
0x80040271	System Reserved. (Not used)
0x80040272	System Reserved. (Not used)
0x80040273	System Reserved. (Not used)
0x80040274	System Reserved. (Not used)
0x80040275	System Reserved. (Not used)

Code	Description
0x80040280	Invalid Activation Code.
0x80040281	Incorrect Activation Code format.

Server Event Log Descriptions for Stellar Agent (Windows-Legacy)

This table lists the server event log descriptions for Stellar Agent (Windows-Legacy).

ID	Server Event	Description
1011	Unable to send reports	Unable to send scheduled reports to %email_address%.
1012	Unable to send notifications	Unable to send notifications to %email_address%.
3001	Purge agent event logs - automatic	Automatic purge of agent event logs.
3002	Purge agent event logs - manual	Manual purge of agent event logs.
3004	Purge server event logs - automatic	Automatic purge of server event logs.
3005	Purge server event logs - manual	Manual purge of server event logs.
4001	Take action on unapproved blocked file	Request sent to endpoint(s): Add blocked file to Approved List. File name: %file_name% File hash: %file_hash% (SHA-1) Request sent to endpoint(s): Delete the blocked file. File name: %file_name% File hash: %file_hash% (SHA-1) Request sent to endpoint(s): Ignore the blocked file.

ID	Server Event	Description
		File name: %file_name% File hash: %file_hash% (SHA-1) Request sent to endpoint(s): Quarantine the file. File name: %file_name% File hash: %file_hash% (SHA-1) Request sent to endpoint(s): Restore the file from quarantine. File name: %file_name% File hash: %file_hash% (SHA-1)
4004	Release the quarantined malicious file	Request sent to endpoint(s): Restore the file from quarantine. File name: %file_name% File hash: %file_hash% (SHA-1)
4005	Delete the quarantined malicious file	Request sent to endpoint(s): Delete the file from quarantine. File name: %file_name% File hash: %file_hash% (SHA-1)
4006	Take action on unapproved fileless attack	Request sent to endpoint(s): Add blocked process chain and command argument. Process chain: %process_name% Command argument: %parameter% Request sent to endpoint(s): Ignore blocked process chain and command argument. Process chain: %process_name% Command argument: %parameter%
4100	Login Account Added to Baseline	A user login account has been added to the baseline. Domain:%domain% Account:%account%

ID	Server Event	Description
		Login type:%logon_type% Source IP:%source_ip%
4101	Application Added to Baseline	An application has been added to the baseline. Application Path: %app_path%
5001	Turn Application Lockdown on	Turned Application Lockdown on for endpoint(s).
5002	Turn Application Lockdown off	Turned Application Lockdown off for endpoint(s).
5011	Add trusted file hashes	Added 1 trusted file hash to endpoint(s). Added %num% trusted file hashes to endpoint(s).
5013	Delete approved files	Removed specified items from the Approved List on endpoint(s) using SLtasks.exe.
5021	Block access from storage devices	Blocked access from storage devices on endpoint(s).
5023	Allow access from storage devices	Allowed access from storage devices on endpoint(s).
5025	Add trusted USB device on selected endpoint(s)	Add trusted USB device on selected endpoint(s)
5601	Export agent settings	Exported (%file_desc%) from %endpoint_name%.
5602	Import agent settings	Imported (%file_desc%) to endpoint(s).
5700	Scan for malware	Scanned endpoint(s) for malware.
5701	Update agent components	Updated agent components on endpoint(s).

ID	Server Event	Description
5800	Change agent administrator password	Changed password on endpoint(s).
5900	Update agent Approved List	Updated Approved List on endpoint(s).
6001	Deploy agent patch	Deploy agent patch to endpoint(s). Patch name: %patch_name%
6101	Agent transferred to new StellarOne server	Agent transferred to new StellarOne server
6201	Turn Maintenance Mode on	Turned Maintenance Mode on for endpoint(s).
6202	Turn Maintenance Mode off	Turned Maintenance Mode off for endpoint(s).
6301	Deploy group policy	Deploy group policy. Version: %version%.
6401	Set Intelligent Runtime Learning	Set Intelligent Runtime Learning. Version: %policy_version%
6402	Set Agent Password	Set Agent Password. Version: %policy_version%
6403	Set Schedule Scan Setting	Set Schedule Scan Setting. Version: %policy_version%
6404	Set User-Defined Suspicious Objects	Set User-Defined Suspicious Objects. Version: %policy_version%

ID	Server Event	Description
6405	Set Agent Patch	Set Agent Patch. Version: %policy_version%

Server Event Log Descriptions for StellarOne

This table lists the server event log descriptions for StellarOne.

ID	Content
33105	The individual command to an agent was sent
33106	The protection command <Configure Maintenance Mode> was sent to agents
33107	The protection command <Scan Now> was sent to agents
33108	The protection command <Update Component> was sent to agents
33109	The protection command <Apply Patch> was sent to agents
33110	The protection command <Initialize Lockdown Approved List> was sent to agents
33111	The update command <Check Connections> was sent to agents
33112	The update command <Apply Policies> was sent to agents
33113	Agent settings exported
33114	The protection command <Transfer Agents> was sent to agents
33115	The protection command <Enable Isolation Mode> was sent to agents
33116	The protection command <Disable Isolation Mode> was sent to agents
33117	Exported (Trusted Programs) from endpoint(s)
33118	Imported (Trusted Programs) to endpoint(s)
33119	Send command <Set Maintenance Mode> to agents
33120	Send command <Collect Event Log> to agents
33121	The Event Action was applied to the agent
33122	The Event Action was applied to the agent(s)
33123	Send command <Export Config> to agents
33124	Send command <Import Config> to agents
33125	Send command <Import Approved List> to agents
33126	Send command <Enable/Disable Smart Trusted Program List> to agents
33127	Send command <Enable Emergency Stop> to agents

ID	Content
33128	Send command <Disable Emergency Stop> to agents
33129	Send command <Upgrade from Discover Edition to Protect Edition> to agents
37123	Agents activated
37124	Agents inactivated
45313	Scan component updated
45314	Scan component update job started
45315	Scan Component Scheduled Update enabled
45316	Scan Component Scheduled Update disabled
45317	Scan Component Update Source for StellarOne modified
45318	Scan Component Update Source for agents modified
45319	Scan component update was successful
45320	Scan component update was successful. Your scan component is the latest version
45321	Scan component update failed with internal error
45322	Scan component update failed due to a network connection failure
45323	The "Policy Inheritance" setting was changed to "Customized"
45324	The "Policy Inheritance" setting was changed to "Inherited"
45325	Scan component update failed
45326	Policy updated
45327	Scan component update failed with invalid license
45328	Global policy updated.
45329	Create group
45330	Rename group
45331	Delete group
45332	Move agents to group
45333	Delete agents
45334	Import exceptions
45335	Change custom exceptions
45361	Scan component import was successful
45362	Scan component import was successful. Your scan component is the latest version
45363	Scan component import failed
45364	System component import was successful

ID	Content
45365	System component import was successful. Your system component is the latest version
45366	System component import failed
45569	Policy sync interval modified
45570	The endpoint(s) Self-management setting was turned on
45571	The endpoint(s) Self-management setting was turned off
45572	Converting Lite agent(s) to Protect agent(s) started
45600	Update pool created
45601	Update agent assigned
45602	Update agent role revoked
45603	Update agent assigned to the update pool
45604	Remove an update agent from the update pool
45605	Update pool renamed
45606	Update pool deleted
45607	Group added to the update pool
45608	Group removed from the update pool
45824	Forwarding logs to Trend Micro Vision One enabled
45825	Forwarding logs to Trend Micro Vision One disabled
45840	Suspicious Objects Synchronization with Trend Micro Vision One enabled
45841	Suspicious Objects Synchronization with Trend Micro Vision One disabled
45842	Suspicious Objects Synchronization with Trend Micro Vision One has completed successfully
45843	Suspicious Objects Synchronization with Trend Micro Vision One failed
46080	Automatic purge of agent events was completed
46081	Automatic purge of agent events failed
46082	Manual purge of agent events succeeded
46083	Manual purge of agent events failed
46084	Automatic purge of server events was completed
46085	Automatic purge of server events failed
46086	Manual purge of server events succeeded
46087	Manual purge of server events failed
46096	The certificate used to communicate with agents has been rotated
46097	The trusted CA used to communicate with the server has been renewed

ID	Content
46112	License changed
46336	Event Rate Limit Reached
46592	Scheduled report rule added
46593	Scheduled report rule modified
46594	Scheduled report rule deleted
46595	Email delivery enabled for scheduled report rule
46596	Email delivery disabled for scheduled report rule
46597	PDF report generated for scheduled report rule

Agent Event Log Descriptions for Stellar Agent - Protect Edition (Linux)

This table details the event log descriptions for Stellar Agent - Protect Edition (Linux).

Event ID	Level	Category	Event	Details
256	Information	system	Service started.	
257	Information	system	Policy applied successfully.	Policy applied successfully. (Version: %version%)
258	Information	system	Patch applied.	File Name: %file_name%
259	Information	system	Patching in progress.	After the earlier-applied patch is completed, the system will automatically try to apply this patch: %deferred_file_name%
514	Information	intelli_av	Real-Time Scan enabled.	
515	Information	intelli_av	A scheduled scan started.	
516	Information	intelli_av	A scheduled scan ended.	Folders scanned: %1

Event ID	Level	Category	Event	Details
				Symbolic links: %2 Regular files: %3 Files scanned: %4 Files passed: %5 Threats detected: %6
517	Information	intelli_av	A manually launched scan started.	
518	Information	intelli_av	A manually launched scan ended.	Folders scanned: %1 Symbolic links: %2 Regular files: %3 Files scanned: %4 Files passed: %5 Threats detected: %6
519	Information	intelli_av	A scheduled scan enabled.	Next scan will be on %NextScan%.
520	Information	intelli_av	A scheduled scan disabled.	A scheduled scan disabled.
521	Information	intelli_av	Manual scan started.	A scan manually launched by local user started.
522	Information	intelli_av	Manual scan ended.	A scan manually launched by local user ended. Folders scanned: %1 Symbolic links: %2 Regular files: %3

Event ID	Level	Category	Event	Details
				Files scanned: %4 Files passed: %5 Threats detected: %6
523	Information	intelli_av	Incoming file detected malicious was quarantined successfully.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Quarantine Path: %PATH% Reboot Required: %NEED_REBOOT%
524	Information	intelli_av	Local file detected malicious was quarantined successfully.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Quarantine Path: %PATH% Reboot Required: %NEED_REBOOT%

Event ID	Level	Category	Event	Details
528	Information	intelli_av	Malicious file access was detected. The infected file was quarantined successfully.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Quarantine Path: %PATH% Reboot Required: %NEED_REBOOT%
2048	Information	update	Component update started.	
2049	Information	update	Component update ended.	
2050	Information	update	Scheduled component update enabled. Next update will be on %NEXT_UPDATE_LOCAL_TIME_STR% (agent's local system time).	
2051	Information	update	Scheduled component update disabled.	
2052	Information	update	Components updated successfully.	Update Source: %UPDATE_URL%
4352	Warning	system	Service stopped.	
4353	Warning	system	Unable to apply policy.	(Version: %version%)

Event ID	Level	Category	Event	Details
4355	Warning	system	Unable to apply patch.	File Name: %file_name% Error Code: %err_code%
4609	Warning	intelli_av	Incoming files were scanned by antivirus. Action was taken according to settings.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Action Result: %STRING% Quarantine Path: %PATH% Last Modifier Path: %LAST_MODIFIER_PATH%
4610	Warning	intelli_av	Incoming files were scanned by next-generation antivirus. Action was taken according to settings.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Action Result: %STRING% Quarantine Path: %PATH% Last Modifier Path: %LAST_MODIFIER_PATH%

Event ID	Level	Category	Event	Details
4611	Warning	intelli_av	Local files were scanned by antivirus. Action was taken according to settings.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Action Result: %STRING%
4612	Warning	intelli_av	Local files were scanned by next-generation antivirus. Action was taken according to settings.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING% Action Result: %STRING% Quarantine Path: %PATH%
4618	Warning	intelli_av	Failed to quarantine the incoming file that was detected malicious.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4619	Warning	intelli_av	Failed to quarantine the local file that was detected malicious.	File Path: %PATH%

Event ID	Level	Category	Event	Details
				File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4628	Warning	intelli_av	Application file access was bypassed by antivirus.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4629	Warning	intelli_av	Application file access was blocked by antivirus.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4631	Warning	intelli_av	Unable to scan compressed files that are password protected or contain password protected files.	File Path: %PATH% File Hash: %STRING%
4632	Warning	intelli_av	Application file access was bypassed by next-generation antivirus.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING%

Event ID	Level	Category	Event	Details
				Threat Name: %STRING%
4633	Warning	intelli_av	Application file access was blocked by next-generation antivirus.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
4634	Warning	intelli_av	Malicious file access was detected. Failed to quarantine the infected file.	File Path: %PATH% File Hash: %STRING% Threat Type: %STRING% Threat Name: %STRING%
6144	Warning	update	Failed to update components. (%AU_ERROR_CODE%)	Update Source: %UPDATE_URL%
8706	Critical	intelli_av	Real-Time Scan disabled.	

Syslog Content - CEF

The following section maps syslog content between StellarOne log output and CEF syslog types.

Topics in this section includes:

- [Stellar Agent \(Windows\)/Stellar Agent \(Windows-Legacy\) Syslog Content - CEF \(on page 354\)](#)
- [StellarOne Server Event Format \(Console Log\) \(on page 369\)](#)
- [StellarOne Syslog Content - CEF \(on page 370\)](#)

Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) Syslog Content - CEF

The following section describes Stellar Agent (Windows)/Stellar Agent (Windows-Legacy) and Stellar Agent (Linux) agent/server events in the Common Event Format.

Topics in this section includes:

- [Stellar Agent Agent Event Format \(on page 354\)](#)
- [Stellar Agent Server Event Format \(on page 359\)](#)
- [Stellar Agent \(Windows-Legacy\) Agent Event Format \(on page 360\)](#)
- [Stellar Agent \(Windows-Legacy\) Server Event Format \(on page 365\)](#)
- [Stellar Agent \(Linux\) Agent Event Format \(on page 366\)](#)

Stellar Agent Agent Event Format

See the following table for Stellar Agent (Windows) agent events in the Common Event Format.

Table 58. Stellar Agent (Windows) Agent Event Format

CEF Field Name	Description	Possible Values
Header		
CEF:Version	CEF format version	CEF:0
Device Vendor	Device Vendor	TXOne Networks
Device Product	Device Product	Stellar Agent (Windows)
Device Version	Device Version	3.2.1234
Device Event Class ID	Event ID	4609, 4870
Name	Event category	Agent Event
Severity	Critical: 7~10 Warning: 4~6 Information: 0~3	{2, 4, 6}

Table 58. Stellar Agent (Windows) Agent Event Format (continued)

CEF Field Name	Description	Possible Values
Extension		
eventTime	Stellar Agent format	Apr 02 2022 13:31:51 GMT+00:00
msg	<string>	
rt	<string>	
category	OPTION: 0 SYSTEM: 1 INTELLI_AV: 2 ANOMALY_DETECT: 3 CHANGE_CONTROL: 4 DEVICE_CONTROL: 5 ADC(DEPRECATED): 6 UPDATE: 8 NETWORK_RESTRICTIONS: 9 MISC: 15	
cat	<int>	
act	<string>	Successful, Failed (-1)
certificate	<string>	
desc	<string>	
destPort	<int>	
direction	<string>	Inbound, Outbound
agentHostName	<string>	
endTime	<string>	
fileName	<string>	
fileSize	<string>	
frameworkName	<string>	

Table 58. Stellar Agent (Windows) Agent Event Format (continued)

CEF Field Name	Description	Possible Values
I4Protocol	<string>	
I7Protocol	<string>	
learningTime	<string>	
legacyAgentSeverity	<int>	
mode	<string>	
serverIP	<string>	
agentEndpoint	<string>	
agentIp	<string>	
agentLocation	<string>	
agentVendor	<string>	
agentModel	<string>	
agentOS	<string>	
alLastUpdateAt	<string>	
agentRt	<string>	
agentGrpGuid	<string>	
agentGrpName	<string>	
blockedCount	<int>	
agentGrpPath	<string>	
s1HostName	<string>	
agentDvc	<string>	
fileCreateTime	<string>	
fileHashBlocked	<string>	
fileModificationTime	<string>	
policyVersion	<string>	
detailMsg	<string>	

Table 58. Stellar Agent (Windows) Agent Event Format (continued)

CEF Field Name	Description	Possible Values
targetProcess	<string>	
fileHash	<string>	
threatType	<string>	
threatName	<string>	
filePath	<string>	
actionResult	<int>	
quarantinePath	<string>	
obadMode	<string>	
obadLevel	<string>	
reason	<string>	
path	<string>	
product	<string>	
programHash	<string>	
programPath	<string>	
programSize	<string>	
originalVersion	<string>	
rebootRequired	<int>	
remoteIP	<string>	
signature	<string>	
startTime	<string>	
threatAttackID	<string>	
trustedType	<string>	
updateSource	<string>	
updateVersion	<string>	

Table 58. Stellar Agent (Windows) Agent Event Format (continued)

CEF Field Name	Description	Possible Values
vendor	<string>	
accessUser	<string>	
processId	<string>	
parentProcess1	<string>	
parentProcess2	<string>	
parentProcess3	<string>	
parentProcess4	<string>	
targetArguments	<string>	
parentArguments1	<string>	
parentArguments2	<string>	
parentArguments3	<string>	
parentArguments4	<string>	
blockedProcess	<string>	
targetFile	<string>	
vid	<int>	
pid	<int>	
sn	<string>	

Table 58. Stellar Agent (Windows) Agent Event Format (continued)

CEF Field Name	Description	Possible Values
accessImagePath	<string>	
srcPath	<string>	
dstPath	<string>	
errCode	<int>	
patchFileName	<string>	
filePath	<string>	
exceptionPathType	<string>	
scanType	<string>	
trustedCertType	<string>	
trustedHashType	<string>	
agentHostName	<string>	
monitoredProcessOrScript	<string>	
parentProcess1	<string>	
parentProcess2	<string>	
parentProcess3	<string>	
parentProcess4	<string>	
processId	<int>	
targetArguments	<string>	

Stellar Agent Server Event Format

See the following table for Stellar Agent (Windows) server events in the Common Event Format.

Table 59. Stellar Agent (Windows) Server Event Format

CEF Field Name	Description	Possible Values
Header		

Table 59. Stellar Agent (Windows) Server Event Format (continued)

CEF Field Name	Description	Possible Values
CEF:Version	CEF format version	CEF:0
Device Vendor	Device Vendor	TXOne Networks
Device Product	Device Product	Stellar Agent
Device Version	Device Version	5.0.1357
Device Event Class ID	Event ID	For example: {33106}
Name	Event category	Server Event
Severity	LOG_INFO: 6	{6}
Extension		
eventTime	Stellar Agent format	Apr 02 2023 13:31:51 GMT+00:00
msg	<string>	
userName	<string>	
userRole	<string>	
clientIp	<string>	
serverIP	<string>	

Stellar Agent (Windows-Legacy) Agent Event Format

See the following table for Stellar Agent (Windows-Legacy) agent events in the Common Event Format.

Table 60. Stellar Agent (Windows-Legacy) Agent Event Format

CEF Key	Description	Possible Values / Example
Header (logVer)	CEF format version	CEF:0
Header (vendor)	Device Vendor	TXOne Networks
Header (pname)	Device Product	Stellar Agent (Windows-Legacy)
Header (pver)	Device Version	3.2.1234
Header (eventid)	Device Event Class ID	2509, 6005
Header (eventName)	Name	Agent Event
Header (severity)	Severity	4
rt	Logged Time	2025-12-09T03:21:26.000Z
msg	Event Id mapped message	File access blocked. File not found in Approved List
dvchost	Computer name	Localhost
agentDvc	IP address	192.168.154.137
rebootRequired	<int>	
registryKey	<string>	
product	<string>	
cat	CEF Category	system:1 intelli_av:2 anomaly_detect: 3 change_control: 4 device control: 5 lockdown: 7

Table 60. Stellar Agent (Windows-Legacy) Agent Event Format (continued)

CEF Key	Description	Possible Values / Example
		update: 8 network_restrictions: 9 misc: 15
agentRt	<string>	
agentOS	<string>	
accessImagePath	<string>	
accessUser	<string>	
fileHashBlocked	<string>	
fileName	<string>	
fileSize	<string>	
frameworkName	MITRE ATT&CK	
learningTime	<string>	
legacyAct	<string>	
obadLevel	<string>	Normal, strict
obadMode	<string>	Learn, detect, enforce
originalVersion	<string>	
programHash	<string>	
programPath	<string>	
programSize	<string>	
quarantinePath	<string>	
result	<string>	Components updated successfully.
reason	<string>	Manually via the protection resume button or CLI.
act	Scan action result (identical to actionResult, customer request)	
action	Scan action (antivirus)	
actionResult	<string>	
scanEndTime	<string>	
scanFolderType	<string>	
scannedFolders	<string>	

Table 60. Stellar Agent (Windows-Legacy) Agent Event Format (continued)

CEF Key	Description	Possible Values / Example
scanStartTime	<string>	
agentEndpoint	<string>	
agentGrpGuid	Agent policy group GUID	
agentGrpName	Agent policy group name.	
agentGrpPath	Agent policy group full path.	
threatName	<string>	
threatType	<string>	
trustedType	<string>	
category	<int>	
certificate	<string>	
deviceType	<string>	
s1HostName	<string>	
legacyAgentSeverity	<int>	
legacyFileCreateTime	<string>	
legacyFileHash	<string>	
legacyFileModificationTime	<string>	
legacyFilePath	<string>	
malwarePath	<string>	
mode	<string>	
policyVersion	<string>	
numCleanedFiles	<int>	
numScannedFiles	<int>	
numFilesCleanedAfterReboot	<int>	
numInfectedFiles	<int>	
signature	<string>	
threatAttackID	<string>	
updateSource	<string>	
updateVersion	<string>	
cs1Label	Detailed Event Message	Detailed Event Message

Table 60. Stellar Agent (Windows-Legacy) Agent Event Format (continued)

CEF Key	Description	Possible Values / Example
cs1	Event ID mapped detailed message	File access blocked: C:\\Documents and Settings\\Administrator\\Local Settings\\Temp\\isD5V0T.tmp\\is-H7K4O.tmp Malware detected: Quarantine. File path: C:\\leicar\\ \\EICAR_TEST_FILE.exe
cs2Label	Client OS	Client OS
cs2	OS description	Microsoft Windows 7 Enterprise Edition Service Pack 1 build 7601, 64-bit
cs3Label	Client Description	Client Description
cs3	Description	-
suser	Login User	PC1688\\Administrator
act	Action Type	ACTION_TYPE_BLOCKED
fileHash	SHA1	2201589AA3ED709B3665E4F F979E10C6AD5137F C
filePath	File path	C:\\Documents and Settings\\Administrator\\Local Settings\\Temp\\is-D5V0T.tmp\\is-H7K4O.tmp
fileCreateTime	File create time	04 02 2022 14:00:21
fileModificationTime	File modified time	04 02 2022 14:00:21

Table 60. Stellar Agent (Windows-Legacy) Agent Event Format (continued)

CEF Key	Description	Possible Values / Example
logGuid	Log GUID	: F43500BB-1F8A-4589-A292-144A9DA343AA#{56B7345A-B6D3-4BBB-A515-4AFFAE04092F}
pid	<string>	
sn	<string>	
vid	<string>	
vendor	<string>	
virusPattern	<string>	
violatedPolicy	<string>	TXPSIRT_ransom_reg_d01 (reg_ransom-d01): Delete internet settings in registry
allLastUpdateAt	<string>	
agentIp	<string>	
ServerIP	Server IP	10.8.145.157
agentHostName	<string>	
monitoredProcessOrScript	<string>	
parentProcess1	<string>	
parentProcess2	<string>	
parentProcess3	<string>	
parentProcess4	<string>	
processId	<int>	
targetArguments	<string>	

Stellar Agent (Windows-Legacy) Server Event Format

See the following table for Stellar Agent (Windows-Legacy) server events in the Common Event Format.

Table 61. Stellar Agent (Windows-Legacy) Server Event Format

CEF Field Name	Description	Possible Values
Header		

Table 61. Stellar Agent (Windows-Legacy) Server Event Format (continued)

CEF Field Name	Description	Possible Values
CEF:Version	CEF format version	CEF:0
Device Vendor	Device Vendor	TXOne Networks
Device Product	Device Product	Stellar Agent (Windows-Legacy)
Device Version	Device Version	5.0.1357
Device Event Class ID	Event ID	For example: {4407}
Name	Event category	Server Event
Severity		{6}
Extension		
rt	<string>	
suser	<string>	
msg	<string>	
serverIP	<string>	

Stellar Agent (Linux) Agent Event Format

See the following table for Stellar Agent (Linux) agent events in the Common Event Format.

Table 62. Stellar Agent (Linux) Agent Event Format

CEF Field Name	Description	Possible Values
HEADER (logVer)	CEF format version	CEF: 0
HEADER (vendor)	Device Vendor	TXOne Networks
HEADER (pname)	Device Product	StellarProtect Linux
HEADER (pver)	Device Version	e.g. 1.0.122
HEADER (eventid)	Device Event Class ID	e.g. 4609

Table 62. Stellar Agent (Linux) Agent Event Format (continued)

CEF Field Name	Description	Possible Values
HEADER (eventName)	Event category	Agent Event
HEADER (severity)	Severity	Critical: 7~10 Warning: 4~6 Information: 0~3
rt	Logged Time	e.g. 1768186754000
msg	Event Id mapped message	e.g. Incoming files were scanned by antivirus. Incoming file detected malicious was quarantined successfully. File access was blocked by antivirus.
cat	CEF Category	system: 1 intelli_av: 2 anomaly_detect: 3 change_control: 4 device_control: 5 lockdown: 7 update: 8 network_restriction: 9 misc: 15
category	<int>	
frameworkName	MITRE ATT&CK	MITRE ATT&CK
threatAttackID	A full ID of a threat or attack as defined in the security framework	e.g. T0865,T0847,T0883,T0864,T0849,T0867
targetProcess	<string>	e.g. /home/txone/eicar.com
threatType	<string>	e.g. Trojan, Virus
threatName	<string>	e.g. Eicar_test_file
threatsDetected	<int>	e.g. 2, 6
policyVersion	Agent policy settings update version number	e.g. 1768197173639949
actionResult	Scan action result	e.g. Successful, Failed(-1)
act	Scan action result (identical to actionResult, customer request)	e.g. Successful, Failed(-1)
quarantinePath	<string>	e.g. /var/opt/txone/backup/quarantine/534e1cbe-08ee-45e1-b0f4-97acf016a8c0
rebootRequired	<int>	e.g. 1
agentHostName	<string>	e.g. centos9build114
agentDvc	<string>	e.g. 10.8.150.141
agentLocation	<string>	
agentVendor	<string>	

Table 62. Stellar Agent (Linux) Agent Event Format (continued)

CEF Field Name	Description	Possible Values
agentModel	<string>	
agentOS	<string>	e.g. CentOS Stream 9
agentGrpPath	<string>	e.g. All
agentGrpName	<string>	e.g. All
agentGrpGuid	<string>	e.g. 2d0defde-a9cf-4c5e-869a-1edbb3070c
agentRt	<string>	e.g. 1768197183000
agentIp	<string>	e.g. 10.8.150.141
agentEndpoint	<string>	e.g. centos9build114
desc	<string>	
s1HostName	<string>	e.g. 10.8.145.138
serverIP	<string>	e.g. 10.8.145.138
fileName	<string>	e.g. eicar.com
filePath	<string>	e.g. /home/txone/eicar.com
fileHash	<string>	e.g. 275a021bbfb6489e54d471899f7db9d1663fc695ec2fe2a2c4538aabf651fd0f
fileSize	<string>	e.g. 68 Bytes
fileModificationTime	<string>	e.g. 1735918157000
lastModifierPath	<string>	
legacyAgentSeverity	<int>	e.g. 6
eventTime	<string>	e.g. 1768208021000
symbolicLinks	<int>	e.g. 48698
updateSource	<string>	e.g. https://10.8.145.138/rest/stellar-au/duplicate/protect
updateVersion	<string>	e.g. Virus Pattern: 20.699.00\n,IntelliTrap Exception Pattern: 2.409.00\n,IntelliTrap Pattern: 0.253.00\n,Spyware/Grayware Pattern: 2.907.00\n,Advanced Threat Scan Engine (64-bit): 21.6.0.1006\n

Table 62. Stellar Agent (Linux) Agent Event Format (continued)

CEF Field Name	Description	Possible Values
originalVersion	<string>	e.g. Virus Pattern: 19.703.00\n,IntelliTrap Exception Pattern: 2.283.00\n,IntelliTrap Pattern: 0.253.00\n,Spyware/Grayware Pattern: 2.779.00\n,Advanced Threat Scan Engine (64-bit): 21.6.0.1006\n
regularFiles	<int>	
filesScanned	<int>	
filesPassed	<int>	
foldersScanned	<int>	
patchFileName	<string>	
deferredFileName	<string>	
AutoApplyPatch AfterCompletedE arlierAppliedPa tch	<string>	
errCode	<int>	

StellarOne Server Event Format (Console Log)

See the following table for StellarOne server events format in the Common Event Format.

Table 63. StellarOne Server Event Format

CEF Field Name	Description	Possible Values
Header		
CEF:Version	CEF format version	CEF:0
Device Vendor	Device Vendor	TXOne Networks
Device Product	Device Product	StellarOne
Device Version	Device Version	3.2.1357
Device Event Class ID	Event ID	46080
Name	Event category	Console Log
Severity		{6}
Extension		

Table 63. StellarOne Server Event Format (continued)

CEF Field Name	Description	Possible Values
eventTime	Stellar Agent format	
msg	<string>	
userName	<string>	system
userRole	<string>	
clientIp	<string>	
status	<string>	0
product	<string>	StellarOne
serverIP	<string>	10.8.150.245

StellarOne Syslog Content - CEF

The following section maps syslog content between StellarOne log output and CEF syslog types.

Topics in this section includes:

- [StellarOne System Event Format \(on page 370\)](#)
- [StellarOne Audit Event Format \(on page 372\)](#)

StellarOne System Event Format

See the following table for StellarOne system events in the Common Event Format.

Table 64. StellarOne System Event Format

CEF Field Name	Description	Value Type	Possible Values
Header			
CEF:Version	CEF format version	<String>	CEF:0
Device Vendor	Vendor name	<String>	TXOne Networks
Device Product	Product name	<String>	StellarOne
Device Version	Product version	<String>	3.0.4115
Signature ID	System Event Logs	<Integer>	0

Table 64. StellarOne System Event Format (continued)

CEF Field Name	Description	Value Type	Possible Values
Event Name	System Event Logs	<String>	SYSTEM_EVENT
Severity	The severity of the system event	<Integer>	• 2: Information • 4: Notice • 6: Warning • 7: Error
Extension			
start	The time when the event log is generated. Format: MM dd yyyy HH:mm:ss GMT+00:00	<DateTime>	Dec 26 2023 15:04:05 GMT+00:00
cat	Device event category	<Integer>	4: System Event Logs
dvchost	(Optional) The hostname of the device generating the event log. It is used to preserve the information of the device generating the event log when it is not the same device sending the syslog.	<String>	stellar1
deviceExternalId	(Optional) The serial number of the device generating the event log	<string>	79070e12-4089-12ee-8435-0050679a1021
eventId	System event ID	<Integer>	8226

Table 64. StellarOne System Event Format (continued)

CEF Field Name	Description	Value Type	Possible Values
			See StellarOne System Event IDs and Messages (on page 372) for the defined system event IDs and the corresponding messages.
msg	The message of the system event	<string>	See StellarOne System Event IDs and Messages (on page 372) for the defined system event IDs and the corresponding messages.
serverIP	StellarOne server IP address	<string>	10.8.145.123

StellarOne System Event IDs and Messages

See the following table for StellarOne system event IDs and messages.

Table 65. StellarOne System Event IDs and Messages

ID	Message	Arguments
6	Sync with NTP server (\$0) failed	\$0: NTP server
8224	NTP server (\$0) synchronized	\$0: NTP server
8226	System time adjusted (\$0 ms)	\$0: delta in ms

StellarOne Audit Event Format

See the following table for StellarOne audit events in the Common Event Format.

Table 66. StellarOne Audit Event Format

CEF Field Name	Description	Value Type	Possible Values
Header			
CEF:Version	CEF format version	<String>	CEF:0
Device Vendor	Vendor name	<String>	TXOne Networks
Device Product	Product name	<String>	StellarOne
Device Version	Product version	<String>	3.0.4115
Signature ID	Audit Event Logs	<Integer>	0
Event Name	Audit Event Logs	<String>	AUDIT_EVENT
Severity	The severity of the audit event	<Integer>	• 2: Information • 4: Notice • 6: Warning • 7: Error
Extension			
start	The time when the event log is generated. Format: MMM dd yyyy HH:mm:ss GMT+00:00	<DateTime>	Dec 26 2023 15:04:05 GMT+00:00
cat	Device event category	<Integer>	5: Audit Event Logs
dvchost	(Optional) The hostname of the device generating the event log. It is	<String>	stellar1

Table 66. StellarOne Audit Event Format (continued)

CEF Field Name	Description	Value Type	Possible Values
	used to preserve the information of the device generating the event log when it is not the same device sending the syslog.		
deviceExternalId	(Optional) The serial number of the device generating the event log	<String>	79070e12-4089-12ee-8435-0050679a1021
eventId	Audit event ID	<String>	8193 See xxx for the defined audit event IDs and the corresponding messages.
suser	The username of the user who triggers the audit event.	<String>	admin
cs1Label	For example, the key for client IP address is labeled as "clientIpAddress"	<String>	clientIpAddress
cs1	The client IP address from which the user logs in and executes commands.	<String>	10.8.144.27
msg	The message of the audit event.	<String>	User (admin) login See xxx for the defined audit event IDs and the corresponding messages.

Table 66. StellarOne Audit Event Format (continued)

CEF Field Name	Description	Value Type	Possible Values
serverIP	StellarOne server IP address	<String>	10.8.151.99

StellarOne Audit Event IDs and Messages

See the following table for StellarOne audit events IDs and messages.

Table 67. StellarOne Audit Event IDs and Messages

ID	Message	Arguments
8193	User (\$0) login	\$0: Account ID
8194	User (\$0) login failed	\$0: Account ID
8195	User (\$0) logout	\$0: Account ID
8196	User (\$0) timeout, force logout	\$0: Account ID
8197	User (\$0) changed password	\$0: Account ID
8208	Reset admin account from vshell	None
8209	User (\$0) created user account (\$1)	\$0: Account ID \$1: User account ID being created
8211	User (\$0) deleted user account (\$1)	\$0: Account ID \$1: User account ID being deleted
8214	User (\$0) changed user account (\$1) password	\$0: Account ID \$1: User account ID being changed

Table 67. StellarOne Audit Event IDs and Messages (continued)

ID	Message	Arguments
8225	User (\$0) changed system time (\$1)	\$0: Account ID \$1: new system time in ISO 8601, e.g., "2023-12-11T18:12:14+08:00"
8226	User (\$0) enabled NTP synchronization (\$1)	\$0: Account ID \$1: NTP server
8227	User (\$0) disabled NTP synchronization	\$0: Account ID
8228	User (\$0) synchronized system time with NTP server (\$1)	\$0: Account ID \$1: NTP server
8229	User (\$0) changed time zone to (\$1)	\$0: Account ID \$1: new time zone ID, e.g., "Asia/Taipei"
8243	User (\$0) changed the syslog setting (\$1)	\$0: Account ID \$1: Setting Name
8273	User (\$0) changed SSL certificate	\$0: Account ID
8289	User (\$0) executed "Purge Now"	\$0: Account ID
8290	User (\$0) changed auto-purge settings	\$0: Account ID
10241	User (\$0) created (\$1)'s API Key expired on (\$2)	\$0: Account ID \$1: Account ID \$2: time in ISO 8601, e.g., "2023-12-15T16:42:16+08:00"

Table 67. StellarOne Audit Event IDs and Messages (continued)

ID	Message	Arguments
10242	User (\$0) deleted (\$1)'s API key	\$0: Account ID \$1: Account ID
10243	User (\$0) created (\$1)'s API Key (No expiration)	\$0: Account ID \$1: Account ID

Index

A

account management.....	195
access rights.....	195
account types.....	195
privileges.....	195
administration.....	193
account.....	194
account management.....	194
CA certificate.....	209
notification.....	206
Single Sign-On.....	202
syslog forwarding.....	209
system.....	234
system time.....	234
update.....	210
Administration	
log purge.....	235
Agent policy settings.....	108
Agent status settings.....	54
Agent view and policy settings.....	105
agents.....	49
agent upgrade.....	67
Discover agents, seat allocation.....	225
export/import settings.....	79
protection.....	67
update.....	75
appendices.....	251
agent syslog content - CEF.....	354
log descriptions.....	252
syslog content - CEF.....	353, 370

D

Dashboard.....	30
Discover add-on license.....	224, 224

G

group policy screen.....	176
Group policy settings.....	175, 176

L

legacy mode	
collect event logs.....	77
export agent settings.....	82
import agent settings.....	80
license.....	217
add-on license.....	224, 226
Discover add-on.....	220, 224
hard expiration.....	229
New License Key/File.....	218
primary license.....	219
Renew License Key.....	218
license editions.....	230
StellarDiscover.....	231

StellarICS.....	230
StellarKiosk.....	231
StellarOEM.....	232
license features.....	233
logs.....	179
agent events.....	180
audit logs.....	190
server events.....	186
system logs.....	189

O

Operation Behavior Highlight.....	173
Operations Behavior Anomaly Detection... migration.....	108
Policy-based approved applications.....	124
Policy-based Approved Login Accounts.....	118
Policy-based approved network access..	117
Policy-based watchlist.....	118
Strict Mode.....	117
	121

P

Policy configuration.....	85
---------------------------	----

S

scheduled report.....	208
seats	
Discover add-on seats.....	227
server accounts.....	196
account privilege allowed.....	196
task.....	196
situational awareness	
StellarProtect (Legacy Mode).....	167
Situational awareness.....	160, 172
StellarProtect.....	160
support	
resolve issues faster.....	248

T

technical support.....	241
contact.....	248
troubleshooting resources.....	242
Threat Detection.....	173

U

update	
apply policies.....	77
check connections.....	76

V

Vulnerabilities.....	174
----------------------	-----