Escanear puertos con nmap

Distribución

Tenemos 2 maquinas, una Debian con DVWA instalado y la IP es 10.0.2.8 y una maquina Kali con IP 10.0.2.6

Escaneo

Realizamos un NMap desde Kali al Debian.

```
┌──(kali㉿kali)-[~]
└─$ nmap 10.0.2.8
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-09 05:27 -0400
Nmap scan report for 10.0.2.8
Host is up (0.00090s latency).
Not shown: 998 closed tcp ports (reset)
PORT    STATE SERVICE
80/tcp  open  http
443/tcp open  https
MAC Address: 08:00:27:D1:65:C7 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 0.76 seconds

┌──(kali㉿kali)-[~]
└─$ nmap -sV 10.0.2.8
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-09 05:28 -0400
Nmap scan report for 10.0.2.8
Host is up (0.00053s latency).
Not shown: 998 closed tcp ports (reset)
PORT    STATE SERVICE  VERSION
80/tcp  open  http     Apache httpd 2.4.66 ((Debian))
443/tcp open  ssl/http Apache httpd 2.4.66 ((Debian))
MAC Address: 08:00:27:D1:65:C7 (Oracle VirtualBox virtual NIC)

Service detection performed. Please report any incorrect results at https://n
map.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 13.55 seconds
```

Vemos que la máquina Debian tiene 2 puertos abiertos, el 80 y el 433 para el servicio web. Y vemos la versión que tiene.

```
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-09 05:31 -0400
Stats: 0:00:37 elapsed; 0 hosts completed (1 up), 1 undergoing Script Scan
NSE Timing: About 97.92% done; ETC: 05:32 (0:00:00 remaining)
Nmap scan report for 10.0.2.8
Host is up (0.00096s latency).
Not shown: 998 closed tcp ports (reset)
PORT    STATE SERVICE  VERSION
80/tcp  open  http     Apache httpd 2.4.66 ((Debian))
|_http-server-header: Apache/2.4.66 (Debian)
|_http-csrf: Couldn't find any CSRF vulnerabilities.
|_http-dombased-xss: Couldn't find any DOM based XSS.
| http-enum:
|   /wordpress/: Blog
|_  /wordpress/wp-login.php: Wordpress login page.
|_http-stored-xss: Couldn't find any stored XSS vulnerabilities.
443/tcp open  ssl/http Apache httpd 2.4.66 ((Debian))
|_http-dombased-xss: Couldn't find any DOM based XSS.
|_http-csrf: Couldn't find any CSRF vulnerabilities.
|_http-stored-xss: Couldn't find any stored XSS vulnerabilities.
|_http-server-header: Apache/2.4.66 (Debian)
| http-enum:
|   /wordpress/: Blog
|_  /wordpress/wp-login.php: Wordpress login page.
MAC Address: 08:00:27:D1:65:C7 (Oracle VirtualBox virtual NIC)

Service detection performed. Please report any incorrect results at https://n
map.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 45.84 seconds
```

Podemos ver un informe con las vulnerabilidades, con esque que hemos conseguido, podemos ver la versión del Apache, nos informa de que no hay vulnerabilidades, que hay un Wordpress instalado y que este tiene una página de acceso wp-login, por donde puede aprovechar para acceder.