Precise calcium-to-spike inference using biophysical generative models

This Figshare repository is in support of "Precise calcium-to-spike inference using biophysical generative models" from Broussard et al. It contains the data exports, MATLAB plotting functions, Python plotting scripts, shared utilities, and rendered table assets used to reproduce the manuscript figures and supplementary figures.

Figure panels are generated by scripts in the matching figure* or supp_figure* directory. MATLAB panels are generally script-style functions named for the figure and panel range. Python panels are installable console entry points defined in setup.py.

Environment and paths

Use MATLAB for .m scripts and a conda or venv Python environment for .py scripts. From the repository root on a Windows machine:

```
python -m venv .venv
.\.venv\Scripts\Activate.ps1

pip install -e .
```

Conda works equivalently after activating the target environment. Python entry points resolve data and output paths back to this project checkout, not to the environment's site-packages directory. If launching from an unusual working directory, set GCAMP_FIGSHARE_ROOT or FIGSHARE_PROJECT_DIR to the repository root.

For MATLAB, run scripts from the repository root or from their figure directory after adding the repository and Utilities to the MATLAB path. Outputs are written to the figure directory or its output subdirectory when saving is enabled.

Main figure contents

- figure1: jGCaMP response properties. Panels cover single-spike responses, response amplitude/kinetic summaries, paired-pulse and multi-spike response behavior, and jGCaMP8f in vivo quiescent-event examples with last-aligned averages and fast decay summaries.
- figure2: stopped-flow and bouton kinetic measurements across GCaMP variants. Scripts plot on/off kinetics, stopped-flow rise times, bouton rise comparisons, Hill-style summaries, 10-pulse responses, decay summaries, and kinetic contribution analyses.
- figure3: biophysical generative model fits and spike-inference examples. MATLAB scripts show stopped-flow and bouton/state fits for GCaMP6f, jGCaMP7f, and jGCaMP8f. The Python script compares biophysical and linear SMC inference on simulated excitatory/inhibitory examples.
- figure4: spike-inference performance on jGCaMP8f data. MATLAB scripts plot example continuous/discrete spike predictions and correlation versus smoothing width for excitatory and inhibitory cells using correlation_tbl_jG8f.mat. The Python script plots matched bias/recall-style distributions.

Supplementary figure contents

- supp_figure1: saturation, elongation, and related controls for jGCaMP8f multi-spike protocols.
- supp_figure2: EGTA/BAPTA clamp comparisons, including data and simulations for OGB and jGCaMP8f.
- supp_figure3: magnesium and ionic-strength effects on steady-state fluorescence and kinetics across sensors.
- supp_figure4: stopped-flow decay traces, biexponential fits, and decay-component summaries.
- supp_figure5: clustered parameter-set summaries used during GCaMP model parameter selection.
- supp_figure6: model fits and model-state plots using the parameter JSON files stored with Table 3.
- supp_figure9: legacy/additional jGCaMP8f correlation analyses. Current Figure 4 analyses use figure4/correlation_tbl_jG8f.mat.
- supp_figure10: example high/low SNR spike predictions and discrete spike timing metrics.
- supp_figure11: STA/SNA bias and uncertainty distributions for matched or unmatched jGCaMP8f detections. Run with run_supp_figure11_A_code.
- supp_figure12: trialwise jGCaMP8f analyses using packaged CSV/NPZ exports. Run with run_supp_figure12_code; the script writes the raincloud panel and combined trace panels only.
- supp_figure13: jGCaMP8f Janelia-parameter comparison. suppfigure13_A_B_code.m uses janelia_model_selection_data_jG8f.mat; run_supp_figure13_C_D_code plots trace and correlation-vs-sigma comparisons.
- supp_figure14: jGCaMP8m analyses. suppfigure14_A_B_C_code.m uses decay_v_spikeNum.mat for quiescent binning; suppfigure14_D_E_code.m uses janelia_model_selection_data_jG8m.mat; run_supp_figure14_F_G_code plots trace and correlation-vs-sigma comparisons.

Table1, Table2, Table3, and Table4 contain CSV, TeX, PDF, and render scripts for manuscript tables. Table1 contains the spike inference precision, recall, F-score, accuracy, bias, and uncertainty summary. Table3 contains the GCaMP kinetic parameter table and the JSON parameter files also used by supp_figure6. The PowerShell table render helpers regenerate TeX from the CSV inputs before compiling PDFs and require pdflatex; Python-backed helpers should be run from an activated environment or passed the appropriate Python executable where supported.

Python entry points

After pip install -e ., available console scripts include:

run_figure3_F_G_code
run_figure4_E_code
run_supp_figure11_A_code
run_supp_figure12_code
run_supp_figure13_C_D_code
run_supp_figure14_F_G_code

The supplementary Python scripts accept --output-dir, --format, and --show where applicable. Temporary Matplotlib/cache directories created by these scripts are cleaned at the end of each run.

Shared data and utilities

Shared_data contains common MATLAB data sources such as stopped-flow traces and the GCaMP database. Utilities contains shared MATLAB helpers, including AccessFitFiles_Janelia.m, GCaMPalias.m, and color utilities. SharedUtilities contains shared Python helpers, including trialwise_plots.py and project path resolution used by installed console scripts.

The model-selection intermediates in supp_figure13 and supp_figure14 intentionally contain only the fit information needed for model selection and plotting. The panel scripts do not require the original raw fit-cache infrastructure from the analysis repository.