

# Exercise: Analysis of a File Containing City Population Data

## Tasks

Perform the following tasks:

**1. Read the file “cities.csv” with SCALA:**

- The file can be read with the command `sc.textFile("cities.csv")`, where `sc` is the Spark context.
- Use the command `sc.textFile("cities.csv").take(1001)` to load the first 1001 lines and inspect the data.

**2. Count the lines of the result:**

- Count the number of lines in the file to verify that the data has been loaded correctly. This can be done using the `.count()` function.

**3. Filter the file to remove the header:**

- Filter the file to remove the headline (the first row), which contains the column names.
- Hint: use the `filter` function and `!line.startsWith("City")` to exclude the header line.

**4. Map the file to split each line into fields:**

- Use a `map` function to split each line into its respective fields (i.e., columns).
- Each field corresponds to the columns “City”, “Country”, and “Population”.
- For this task, you can use `line.split(",")` to separate the fields by commas.

**5. Retrieve the population column:**

- Use a `map` function to retrieve the field corresponding to “Population”.

- Convert the population field, which is a string, to an integer using `.toInt`.
  - The population field is the third column (index 2).
6. **Filter the collection of population values:**
- Filter the population collection to retain only records where the population is greater than 0.
  - The final collection will be called `collectPopulations`.
7. **Use a MapReduce function to compute the total number of cities:**
- Code a MapReduce function to compute the total number of cities in `collectPopulations`.
  - The result will be stored in the variable `countCities`.
8. **Use a reduce function to compute the total sum of city populations:**
- Code a reduce function to compute the total population of all cities.
  - The result will be stored in the variable `totalPopulation`.
9. **Use a reduce function to compute the maximum population of a city:**
- Code a reduce function to compute the maximum population of a city.
  - The result will be stored in the variable `maxPopulation`.
  - What can you conclude from this result?
10. **Compute and print on screen:**
- Compute and display the following results:
    - Total population
    - Number of cities
    - Maximum city population
    - Average city population

## Expected Scala Code

Here's a general idea of how your code could look. Adjust it according to the exact structure of the `cities.csv` file.

```

// Step 1: Read the file
val file = sc.textFile("cities.csv")

// Step 2: Count the number of lines
val lineCount = file.count()
println(s"Number of lines: $lineCount")

// Step 3: Filter to remove the header
val dataWithoutHeader = file.filter(line => !line.startsWith("City"))

// Step 4: Split each line into fields (City, Country, Population)
val columns = dataWithoutHeader.map(line => line.split(","))

// Step 5: Retrieve the Population field (third column) and convert it to an integer
val populations = columns.map(fields => fields(2).toInt)

// Step 6: Filter to keep only populations greater than 0
val collectPopulations = populations.filter(pop => pop > 0)

// Step 7: Compute the total number of cities
val countCities = collectPopulations.count()

// Step 8: Compute the total population
val totalPopulation = collectPopulations.reduce(_ + _)

// Step 9: Compute the maximum population of a city
val maxPopulation = collectPopulations.reduce((a, b) => Math.max(a, b))

// Step 10: Compute the average population
val averagePopulation = totalPopulation / countCities

// Print the results
println(s"""
  | Total number of cities: $countCities
  | Total population: $totalPopulation
  | Maximum city population: $maxPopulation
  | Average city population: $averagePopulation
  """).stripMargin)

```

## Dataset Structure

The dataset (cities.csv) is assumed to have the following columns:

```

City, Country, Population
New York, USA, 8419600

```

```
Los Angeles, USA, 3980400  
Paris, France, 2148000  
...
```

This exercise is a good parallel to the `les-arbres.csv` problem but works with city population data, and it introduces similar MapReduce operations to compute counts, sums, maximums, and averages.