Nom i Cognoms:_____**Una posible solució**_____

1) (3p.) Un dels circuits d'exemple del proteus presenta la següent connexió d'un altaveu als pins de sortida d'un micro.



a) Quina és la finalitat de les resistències R1 i R2?

Posen un '1' feble als pins RA0 i RA1 en l'estat de repòs dels polsadors

b) Quin avantatge té que cada born de l'altaveu estigui connectat a 2 pins del micro?

Duplica el corrent que podem lliurar a l'altaveu. Si cada pin pot donar/xuclar 25mA., amb aquesta configuració podem donar/xuclar a l'altaveu fins a 50mA.

c) Quin avantatge té que un dels borns de l'altaveu estigui connectat a RB2-RB3 en comptes d'estar connectat a massa? (NOTA: per a fer sonar l'altaveu, el senyal als pins RB2-RB3 és el negat del senyal als pins RB0-RB1)

Duplica la tensió que podem donar en bornes de l'altaveu.
Si el càtode de l'altaveu estigués connectat a massa, la diferència de potencial en bornes oscil.laria entre 0 i Vdd. A l'estar connectat a RB2:3, la diferència de potencial oscil.la entre Vdd i –Vdd.

Amb aquests dos trucs, multipliquem per 4 la potència que enviem a l'altaveu.

2) (1p.) Calculeu el fan-out estàtic d'un pin de E/S standar del 18F4550.

Absolute Maximum Ratings(†)

Ambient temperature under bias ..... -40°C to +85°C
Storage temperature ..... -65°C to +150°C
Voltage on any pin with respect to VSS (except VDD and $\overline{MCLR}$) **(Note 3)** ..... -0.3V to (VDD + 0.3V)
Voltage on VDD with respect to VSS ..... -0.3V to +7.5V
Voltage on $\overline{MCLR}$ with respect to VSS **(Note 2)** ..... 0V to +13.25V
Total power dissipation **(Note 1)** 1.0W
Maximum current out of VSS pin ..... 300 mA
Maximum current into VDD pin ..... 250 mA
Input clamp current, IIK (VI < 0 or VI > VDD) ..... ±20 mA
Output clamp current, IOK (VO < 0 or VO > VDD) ..... ±20 mA
Maximum output current sunk by any I/O pin ..... 25 mA
Maximum output current sourced by any I/O pin ..... 25 mA
Maximum current sunk by all ports ..... 200 mA
Maximum current sourced by all ports ..... 200 mA

DC CHARACTERISTICS			Standard Operating Conditions (unless otherwise stated) Operating temperature -40°C ≤ TA ≤ +85°C for industrial			
Param No.	**Symbol**	**Characteristic**	**Min**	**Max**	**Units**	**Conditions**
	VIL	**Input Low Voltage**				
		I/O Ports (except RC4/RC5 in USB mode):				
D030		with TTL Buffer	VSS	0.15 VDD	V	VDD < 4.5V
D030A			—	0.8	V	4.5V ≤ VDD ≤ 5.5V
D031		with Schmitt Trigger Buffer	VSS	0.2 VDD	V	
		RB0 and RB1	VSS	0.3 VDD	V	When in I^2C™ mode
D032		$\overline{MCLR}$	VSS	0.2 VDD	V	
D032A		OSC1 and T1OSI	VSS	0.3 VDD	V	XT, HS, HSPLL modes(1)
D033		OSC1	VSS	0.2 VDD	V	EC mode(1)
	VIH	**Input High Voltage**				
		I/O Ports (except RC4/RC5 in USB mode):				
D040		with TTL Buffer	0.25 VDD + 0.8V	VDD	V	VDD < 4.5V
D040A			2.0	VDD	V	4.5V ≤ VDD ≤ 5.5V
D041		with Schmitt Trigger Buffer	0.8 VDD	VDD	V	
		RB0 and RB1	0.7 VDD	VDD	V	When in I^2C mode
D042		$\overline{MCLR}$	0.8 VDD	VDD	V	
D042A		OSC1 and T1OSI	0.7 VDD	VDD	V	XT, HS, HSPLL modes(1)
D043		OSC1	0.8 VDD	VDD	V	EC mode(1)
	IIL	**Input Leakage Current(2)**				
D060		I/O Ports, except D+ and D-	—	±200	nA	VSS ≤ VPIN ≤ VDD, Pin at high-impedance
D061		$\overline{MCLR}$	—	±1	µA	Vss ≤ VPIN ≤ VDD
D063		OSC1	—	±1	µA	Vss ≤ VPIN ≤ VDD
	IPU	**Weak Pull-up Current**				
D070	IPURB	PORTB Weak Pull-up Current	50	400	µA	VDD = 5V, VPIN = VSS
D071	IPURD	PORTD Weak Pull-up Current	50	400	µA	VDD = 5V, VPIN = VSS

Cada pin pot donar fins a ±25mA. Cada entrada xucla fins a ±200nA.
Fan_Out = 25mA/ 200nA = 125000

Nom i Cognoms:_____**Una posible solució**_____

3) (1.5p.) Com queden els registres de la taula després d'executar el següent codi? Justifica la respota.

```
movlb   1       bsr=1
movf    0,0,0   wreg=1
movwf   1,1     1:1=1
movf    0,0,1   wreg=4
movwf   0,0     0:0=4
movf    1,0,1   wreg=1
movwf   0,1     0:1=1
                (registre:bank)
```

Bank	Address	Valor previ	Valor final
0	0	1	4
0	1	2	2
0	2	3	3
1	0	4	1
1	1	5	1
1	2	6	6

4) (1.5p.) Donat el següent fragment de codi:

```
        ...
        clrf    PORTA,0
        clrf    TRISA,0
        setf    PORTA,0
        movlw   08
        movwf   00,0
loop:   decfsz  00,1,0
        bra     loop
        clrf    PORTA,0
        ...
```

Quant de temps han estat els bits del PORTA a '1' si l'oscil.lador del micro és de 10MHz? Exposa els càlculs.

Es posa a 1 a l'executar:

```
        setf    PORTA,0
        movlw   08          // 1 cicle
        movwf   00,0        // 1 cicle

loop:   decfsz  00,1,0      // 7 vegades 3 cicles: (1 dec
        bra     loop        // + 2 bra)=21 cicles

        decfsz  00,1,0      // 1 vegada 2 cicles: 1 dec +
        bra     loop        // 1 skip del bra = 2 cicles
        clrf    PORTA,0     // 1 cicle i es posa a 0 !
```

Total 26 cicles d'instrucció. Temps de cicle = 4 * Tosc = 4* 100ns = 400ns
Temps total amb el PORTA a '1'= 26*400ns = 10,4 us (microsegons)

5) (1 p.) perquè hi ha instruccions com el *decfsz* que poden trigar un cicle, dos o tres? Posa algun exemple.

(1) Si després de decrementar no es fa *skip*, dura un cicle. Si al decrementar el resultat és 0 i cal fer *skip*, hi ha dues opcions: (2) la segueix una instrucció *single word* (per ex. movlw) que provoca 1 fetch invàlid i per tant necessitem dos cicles en total o (3) la segueix una instrucció *double word* (no de dos cicles d'execució com el bra, sino de dos paraules a memòria com el goto, movff, etc.) que produeix dos fetch invàlids i per tant necessitem tres cicles en total.

TABLE 26-2: PIC18FXXXX INSTRUCTION SET

Mnemonic, Operands		Description	Cycles	16-Bit Instruction Word MSb			LSb	Status Affected	Notes
BYTE-ORIENTED OPERATIONS									
ADDWF	f, d, a	Add WREG and f	1	0010	01da	ffff	ffff	C, DC, Z, OV, N	1, 2
ADDWFC	f, d, a	Add WREG and Carry bit to f	1	0010	00da	ffff	ffff	C, DC, Z, OV, N	1, 2
ANDWF	f, d, a	AND WREG with f	1	0001	01da	ffff	ffff	Z, N	1,2
CLRF	f, a	Clear f	1	0110	101a	ffff	ffff	Z	2
COMF	f, d, a	Complement f	1	0001	11da	ffff	ffff	Z, N	1, 2
CPFSEQ	f, a	Compare f with WREG, Skip =	1 (2 or 3)	0110	001a	ffff	ffff	None	4
CPFSGT	f, a	Compare f with WREG, Skip >	1 (2 or 3)	0110	010a	ffff	ffff	None	4
CPFSLT	f, a	Compare f with WREG, Skip <	1 (2 or 3)	0110	000a	ffff	ffff	None	1, 2
DECF	f, d, a	Decrement f	1	0000	01da	ffff	ffff	C, DC, Z, OV, N	1, 2, 3, 4
DECFSZ	f, d, a	Decrement f, Skip if 0	1 (2 or 3)	0010	11da	ffff	ffff	None	1, 2, 3, 4
DCFSNZ	f, d, a	Decrement f, Skip if Not 0	1 (2 or 3)	0100	11da	ffff	ffff	None	1, 2
INCF	f, d, a	Increment f	1	0010	10da	ffff	ffff	C, DC, Z, OV, N	1, 2, 3, 4
INCFSZ	f, d, a	Increment f, Skip if 0	1 (2 or 3)	0011	11da	ffff	ffff	None	4
INFSNZ	f, d, a	Increment f, Skip if Not 0	1 (2 or 3)	0100	10da	ffff	ffff	None	1, 2
IORWF	f, d, a	Inclusive OR WREG with f	1	0001	00da	ffff	ffff	Z, N	1, 2
MOVF	f, d, a	Move f	1	0101	00da	ffff	ffff	Z, N	1
MOVFF	f_s, f_d	Move f_s (source) to 1st word f_d (destination) 2nd word	2	1100 1111	ffff ffff	ffff ffff	ffff ffff	None	
MOVWF	f, a	Move WREG to f	1	0110	111a	ffff	ffff	None	
MULWF	f, a	Multiply WREG with f	1	0000	001a	ffff	ffff	None	1, 2
NEGF	f, a	Negate f	1	0110	110a	ffff	ffff	C, DC, Z, OV, N	
RLCF	f, d, a	Rotate Left f through Carry	1	0011	01da	ffff	ffff	C, Z, N	1, 2
RLNCF	f, d, a	Rotate Left f (No Carry)	1	0100	01da	ffff	ffff	Z, N	
RRCF	f, d, a	Rotate Right f through Carry	1	0011	00da	ffff	ffff	C, Z, N	
RRNCF	f, d, a	Rotate Right f (No Carry)	1	0100	00da	ffff	ffff	Z, N	
SETF	f, a	Set f	1	0110	100a	ffff	ffff	None	1, 2
SUBFWB	f, d, a	Subtract f from WREG with Borrow	1	0101	01da	ffff	ffff	C, DC, Z, OV, N	
SUBWF	f, d, a	Subtract WREG from f	1	0101	11da	ffff	ffff	C, DC, Z, OV, N	1, 2
SUBWFB	f, d, a	Subtract WREG from f with Borrow	1	0101	10da	ffff	ffff	C, DC, Z, OV, N	
LITERAL OPERATIONS									
ADDLW	k	Add Literal and WREG	1	0000	1111	kkkk	kkkk	C, DC, Z, OV, N	
ANDLW	k	AND Literal with WREG	1	0000	1011	kkkk	kkkk	Z, N	
IORLW	k	Inclusive OR Literal with WREG	1	0000	1001	kkkk	kkkk	Z, N	
LFSR	f, k	Move Literal (12-bit) 2nd word to FSR(f) 1st word	2	1110 1111	1110 0000	00ff kkkk	kkkk kkkk	None	
MOVLB	k	Move Literal to BSR<3:0>	1	0000	0001	0000	kkkk	None	
MOVLW	k	Move Literal to WREG	1	0000	1110	kkkk	kkkk	None	
MULLW	k	Multiply Literal with WREG	1	0000	1101	kkkk	kkkk	None	
RETLW	k	Return with Literal in WREG	2	0000	1100	kkkk	kkkk	None	
SUBLW	k	Subtract WREG from Literal	1	0000	1000	kkkk	kkkk	C, DC, Z, OV, N	
XORLW	k	Exclusive OR Literal with WREG	1	0000	1010	kkkk	kkkk	Z, N	
CONTROL OPERATIONS									
BC	n	Branch if Carry	1 (2)	1110	0010	nnnn	nnnn	None	
BN	n	Branch if Negative	1 (2)	1110	0110	nnnn	nnnn	None	
BNC	n	Branch if Not Carry	1 (2)	1110	0011	nnnn	nnnn	None	
BNN	n	Branch if Not Negative	1 (2)	1110	0111	nnnn	nnnn	None	
BNOV	n	Branch if Not Overflow	1 (2)	1110	0101	nnnn	nnnn	None	
BNZ	n	Branch if Not Zero	1 (2)	1110	0001	nnnn	nnnn	None	
BOV	n	Branch if Overflow	1 (2)	1110	0100	nnnn	nnnn	None	
BRA	n	Branch Unconditionally	2	1101	0nnn	nnnn	nnnn	None	
BZ	n	Branch if Zero	1 (2)	1110	0000	nnnn	nnnn	None	
CALL	n, s	Call Subroutine 1st word 2nd word	2	1110 1111	110s kkkk	kkkk kkkk	kkkk kkkk	None	
CLRWDT	—	Clear Watchdog Timer	1	0000	0000	0000	0100	$\overline{TO}$, $\overline{PD}$	
DAW	—	Decimal Adjust WREG	1	0000	0000	0000	0111	C	
GOTO	n	Go to Address 1st word 2nd word	2	1110 1111	1111 kkkk	kkkk kkkk	kkkk kkkk	None	
NOP	—	No Operation	1	0000	0000	0000	0000	None	
NOP	—	No Operation	1	1111	xxxx	xxxx	xxxx	None	4
POP	—	Pop Top of Return Stack (TOS)	1	0000	0000	0000	0110	None	
PUSH	—	Push Top of Return Stack (TOS)	1	0000	0000	0000	0101	None	
RCALL	n	Relative Call	2	1101	1nnn	nnnn	nnnn	None	
RESET		Software Device Reset	1	0000	0000	1111	1111	All	
RETFIE	s	Return from Interrupt Enable	2	0000	0000	0001	000s	GIE/GIEH, PEIE/GIEL	
RETLW	k	Return with Literal in WREG	2	0000	1100	kkkk	kkkk	None	
RETURN	s	Return from Subroutine	2	0000	0000	0001	001s	None	
SLEEP	—	Go into Standby mode	1	0000	0000	0000	0011	$\overline{TO}$, $\overline{PD}$	

d = 0 for result destination to be WREG register
d = 1 for result destination to be file register (f)
a = 0 to force Access Bank
a = 1 for BSR to select bank
f = 8-bit file register address