



🏠 / Design Patterns

# Creational patterns

In software engineering, creational design patterns are design patterns that deal with object creation mechanisms, trying to create objects in a manner suitable to the situation. The basic form of object creation could result in design problems or added complexity to the design. Creational design patterns solve this problem by somehow controlling this object creation.

- **Abstract Factory**

Creates an instance of several families of classes

- **Builder**

Separates object construction from its representation

- **Factory Method**

Creates an instance of several derived classes

- **Object Pool**


Avoid expensive acquisition and release of resources by recycling objects that are no longer in use

- **Prototype**

A fully initialized instance to be copied or cloned

- **Singleton**

A class of which only a single instance can exist



## Rules of thumb

1. Sometimes creational patterns are competitors: there are cases when either **Prototype** or **Abstract Factory** could be used profitably. At other times they are complementary: **Abstract Factory** might store a set of **Prototypes** from which to clone and return product objects, **Builder** can use one of the other patterns to implement which components get built. **Abstract Factory**,

**Builder**, and **Prototype** can use **Singleton** in their implementation.

2. **Abstract Factory**, **Builder**, and **Prototype** define a factory object that's responsible for knowing and creating the class of product objects, and make it a parameter of the system. **Abstract Factory** has the factory object producing objects of several classes. **Builder** has the factory object building a complex product incrementally using a correspondingly complex protocol. **Prototype** has the factory object (aka prototype) building a product by copying a prototype object.
3. **Abstract Factory** classes are often implemented with **Factory Methods**, but they can also be implemented using **Prototype**.
4. **Abstract Factory** can be used as an alternative to **Facade** to hide platform-specific classes.
5. **Builder** focuses on constructing a complex object step by step. **Abstract Factory** emphasizes a family of product objects (either simple or complex). **Builder** returns the product as a final step, but as far as the **Abstract Factory** is concerned, the product gets returned immediately.
6. **Builder** is to creation as **Strategy** is to algorithm.
7. **Builder** often builds a **Composite**.
8. **Factory Methods** are usually called within **Template methods**.
9. **Factory Method**: creation through inheritance. **Prototype**: creation through delegation.
10. Often, designs start out using **Factory Method** (less complicated, more customizable, subclasses proliferate) and evolve toward **Abstract Factory**, **Prototype**, or **Builder** (more flexible, more complex) as the designer discovers where more flexibility is needed.
11. **Prototype** doesn't require subclassing, but it does require an Initialize operation. **Factory Method** requires subclassing, but doesn't require Initialize.
12. Designs that make heavy use of the **Composite** and **Decorator** patterns often can benefit from **Prototype** as well.


## Read next

This article is taken from our book **Design Patterns Explained Simply**.

All of the design patterns are compiled there. The book is written in clear, simple language that makes it easy to read and understand (just like this article).

We distribute it in PDF & EPUB formats so you can get it onto your iPad, Kindle, or other portable device immediately after your purchase.

♥ Learn more



## Code examples

READ NEXT

Abstract Factory



## RETURN

Design Patterns  
AntiPatterns  
Refactoring  
UML

My account  
Forum  
Contact us  
About us

© 2007-2018 SourceMaking.com  
All rights reserved.

Privacy policy