

1 Random Variables and Expectation

Plucky has an n -sided die that will generate numbers in $\{1, 2, \dots, n\}$ uniformly at random. She is bored and she has decided to start and keep rolling her die until she has seen all the numbers in $\{1, 2, \dots, n\}$ at least once.

We want to calculate how many die rolls it takes in expectation for Plucky to stop.

For each $i \in \{1, 2, \dots, n\}$, we define a random variable X_i : its value is equal to the number of additional die rolls we need to see the i -th unique value after having already seen $i - 1$ unique values.

What is the type of probability distribution that the random variable X_i follows?

- ☐ Binomial
- ☐ Bernoulli
- ☐ Poisson
- ☒ Geometric

Correct

Assume Plucky has started rolling her die and she has seen $i - 1$ unique values so far. What is the probability of seeing a new number that she has not seen before in her next die roll?

- ☐ $\frac{1}{n}$
- ☐ $\frac{i}{n}$
- ☒ $\frac{n-i+1}{n}$
- ☐ $\frac{1}{i-1}$

Correct

What is $\mathbb{E}[X_i]$?

- ☐ n
- ☐ $\frac{n}{i}$
- ☒ $\frac{n}{n-i+1}$
- ☐ $i - 1$

Correct

What is the expected total number of die rolls, until Plucky sees all the n values at least once?

- ☐ $\Theta(n)$
- ☒ $\Theta(n \log n)$
- ☐ $\Theta(n^2)$
- ☐ $\Omega(n^2 \log n)$

Correct

2 Randomized Algorithms

Can we use the random pivot selection idea in QuickSort for the selection problem?

Assume we modify the k -select algorithm that we saw in previous lectures; instead of picking the pivot cleverly, we just pick a uniformly random element as the pivot each time. We call the resulting algorithm QuickSelect.

What is the worst case runtime of QuickSelect?

- ☐ $\Theta(n)$
- ☐ $\Theta(n \log n)$
- ☒ $\Theta(n^2)$
- ☐ $\Omega(n^2 \log n)$

Correct

What is the probability that our random pivot partitions the array into two parts, each of size at most $\frac{3n}{4}$?

- ☐ $\frac{3}{4} \pm O(1/n)$
- ☒ $\frac{1}{2} \pm O(1/n)$
- ☐ $\frac{1}{3} \pm O(1/n)$
- ☐ $\frac{1}{4} \pm O(1/n)$

Correct

Assume we group QuickSelect's recursive calls into multiple phases. Phase i is when the size of the array is in the interval

$$\left((3/4)^{(i+1)}n, (3/4)^i n \right].$$

Note that we start at phase 0 with an array of size n .

For each phase we define a random variable X_i , whose value is the number of recursive calls in that phase. Using the answers to previous questions, calculate an upper bound for $\mathbb{E}[X_i]$. Which of the following is the (asymptotically) smallest upper bound on $\mathbb{E}[X_i]$?

- ☐ $3 + O(1/n)$
- ☒ $2 + O(1/n)$
- ☐ n
- ☐ $O(\log n)$

Correct

What is the expected (average case) runtime of QuickSelect?

- ☒ $\Theta(n)$
- ☐ $\Theta(n \log n)$
- ☐ $\Theta(n^2)$
- ☐ $\Omega(n^2 \log n)$

Correct