docker stack deploy

Estimated reading time: 4 minutes

Description

Deploy a new stack or update an existing stack

API 1.25+ (https://docs.docker.com/engine/api/v1.25/) The client and daemon API must both be at least 1.25 (https://docs.docker.com/engine/api/v1.25/) to use this command. Use the docker version command on the client to check your client and daemon API versions.

Usage

docker stack deploy [OPTIONS] STACK

Options

| Name, shorthand | Default | Description |
|--------------------|---------|---|
| bundle-file | | experimental (daemon) (https://docs.docker.com/engine/reference/commandline/dockerd/#daemon-configuration-file) Swarm Path to a Distributed Application Bundle file |
| compose-file , -c | | API 1.25+ (https://docs.docker.com/engine/api/v1.25/) Path to a Compose file, or "-" to read from stdin |
| namespace | | Kubernetes Kubernetes namespace to use |
| prune | | API 1.27+ (https://docs.docker.com/engine/api/v1.27/) Swarm Prune services that are no longer referenced |
| resolve-image | always | API 1.30+ (https://docs.docker.com/engine/api/v1.30/) Swarm Query the registry to resolve image digest and supported platforms ("always" "changed" "never") |
| with-registry-auth | | Swarm Send registry authentication details to Swarm agents |
| kubeconfig | | Kubernetes Kubernetes config file |
| orchestrator | | Orchestrator to use (swarm kubernetes all) |

Parent command

| Command | Description |
|---|----------------------|
| docker stack (https://docs.docker.com/engine/reference/commandline/stack) | Manage Docker stacks |

Related commands

| Command | Description |
|--|--|
| docker stack deploy (https://docs.docker.com/engine/reference/commandline/stack_deploy/) | Deploy a new stack or update an existing stack |
| docker stack ls (https://docs.docker.com/engine/reference/commandline/stack_ls/) | List stacks |
| docker stack ps (https://docs.docker.com/engine/reference/commandline/stack_ps/) | List the tasks in the stack |
| docker stack rm (https://docs.docker.com/engine/reference/commandline/stack_rm/) | Remove one or more stacks |
| docker stack services (https://docs.docker.com/engine/reference/commandline/stack_services/) | List the services in the stack |

Extended description

Create and update a stack from a compose or a dab file on the swarm. This command has to be run targeting a manager node.

Examples

Compose file

The $\ \mbox{deploy}$ command supports compose file version $\ \mbox{3.0}$ and above.

```
$ docker stack deploy --compose-file docker-compose.yml vossibility

Ignoring unsupported options: links

Creating network vossibility_vossibility
Creating network vossibility_default
Creating service vossibility_nsqd
Creating service vossibility_logstash
Creating service vossibility_elasticsearch
Creating service vossibility_kibana
Creating service vossibility_ghollector
Creating service vossibility_lookupd
```

The Compose file can also be provided as standard input with --compose-file - :

```
$ cat docker-compose.yml | docker stack deploy --compose-file - vossibility
Ignoring unsupported options: links

Creating network vossibility_vossibility
Creating network vossibility_default
Creating service vossibility_nsqd
Creating service vossibility_logstash
Creating service vossibility_elasticsearch
Creating service vossibility_kibana
Creating service vossibility_ghollector
Creating service vossibility_lookupd
```

If your configuration is split between multiple Compose files, e.g. a base configuration and environment-specific overrides, you can provide multiple --compose-file flags.

```
$ docker stack deploy --compose-file docker-compose.yml -c docker-compose.prod.yml vossibility
Ignoring unsupported options: links

Creating network vossibility_vossibility
Creating network vossibility_default
Creating service vossibility_nsqd
Creating service vossibility_logstash
Creating service vossibility_elasticsearch
Creating service vossibility_kibana
Creating service vossibility_ghollector
Creating service vossibility_lookupd
```

You can verify that the services were correctly created:

\$ docker service ls

| ID | NAME | MODE | REPLICAS | IMAGE | | |
|---|-----------------------------------|------------|----------|-------------------------|--|--|
| 29bv0vn1m903 | vossibility_lookupd | replicated | 1/1 | nsqio/nsq@sha256:eeba05 | | |
| 599f31eba418e96e71e0984c3dc96963ceb66924dd37a47bf7ce18a662 | | | | | | |
| 4awt47624qwh | vossibility_nsqd | replicated | 1/1 | nsqio/nsq@sha256:eeba05 | | |
| 599f31eba418e96e71e0984c3dc96963ceb66924dd37a47bf7ce18a662 | | | | | | |
| 4tjx9biia6fs | vossibility_elasticsearch | replicated | 1/1 | elasticsearch@sha256:12 | | |
| ac7c6af55d001f71800b83ba91a04f716e58d82e748fa6e5a7359eed2301aa | | | | | | |
| 7563uuzr9eys | vossibility_kibana | replicated | 1/1 | kibana@sha256:6995a2d25 | | |
| 709a62694a937b8a529ff36da92ebee74bafd7bf00e6caf6db2eb03 | | | | | | |
| 9gc5m4met4he | vossibility_logstash | replicated | 1/1 | logstash@sha256:2dc8bdd | | |
| d1bb4a5a34e8ebaf73749f6413c101b2edef6617f2f7713926d2141fe | | | | | | |
| axqh55ipl40h | vossibility_vossibility-collector | replicated | 1/1 | icecrime/vossibility-co | | |
| llector@sha256:f03f2977203ba6253988c18d04061c5ec7aab46bca9dfd89a9a1fa4500989fba | | | | | | |

DAB file

```
$ docker stack deploy --bundle-file vossibility-stack.dab vossibility
Loading bundle from vossibility-stack.dab
Creating service vossibility_elasticsearch
Creating service vossibility_kibana
Creating service vossibility_logstash
Creating service vossibility_lookupd
Creating service vossibility_nsqd
Creating service vossibility_vossibility-collector
```

You can verify that the services were correctly created:

\$ docker service 1s

| ID | NAME | MODE | REPLICAS | IMAGE | |
|---|-----------------------------------|------------|----------|-------------------------|--|
| 29bv0vn1m903 | vossibility_lookupd | replicated | 1/1 | nsqio/nsq@sha256:eeba05 | |
| 599f31eba418e96e71e0984c3dc96963ceb66924dd37a47bf7ce18a662 | | | | | |
| 4awt47624qwh | vossibility_nsqd | replicated | 1/1 | nsqio/nsq@sha256:eeba05 | |
| 599f31eba418e96e71e0984c3dc96963ceb66924dd37a47bf7ce18a662 | | | | | |
| 4tjx9biia6fs | vossibility_elasticsearch | replicated | 1/1 | elasticsearch@sha256:12 | |
| ac7c6af55d001f71800b83ba91a04f716e58d82e748fa6e5a7359eed2301aa | | | | | |
| 7563uuzr9eys | vossibility_kibana | replicated | 1/1 | kibana@sha256:6995a2d25 | |
| 709a62694a937b8a529ff36da92ebee74bafd7bf00e6caf6db2eb03 | | | | | |
| 9gc5m4met4he | vossibility_logstash | replicated | 1/1 | logstash@sha256:2dc8bdd | |
| d1bb4a5a34e8ebaf73749f6413c101b2edef6617f2f7713926d2141fe | | | | | |
| axqh55ipl40h | vossibility_vossibility-collector | replicated | 1/1 | icecrime/vossibility-co | |
| llector@sha256:f03f2977203ba6253988c18d04061c5ec7aab46bca9dfd89a9a1fa4500989fba | | | | | |