ARCHITECTURE SPECIFICATION & BUSINESS BRIEF

Tier-Aware Brief Workflow

System: n8n Enterprise Orchestration | **Category:** Dynamic Account Intelligence | **Status:** Production Specification

1. Executive Summary

The **Tier-Aware Brief Workflow** is an enterprise automation pipeline engineered to dynamically adapt business intelligence generation based on client segmentation tiers (e.g., Enterprise, Mid-Market, Startup). By embedding deterministic account lookup and conditional routing prior to LLM processing and output formatting, the system guarantees that high-value customer interactions receive comprehensive, multi-dimensional briefs while lower-priority tiers follow streamlined, token-optimized summaries.

2. Business Problem & Strategic Value

> **Core Challenge:** Uniform briefing logic treats all client inquiries equally. This results in wasted LLM token expenditure and unnecessary API overhead for routine accounts, while high-stakes Enterprise accounts risk receiving insufficient context or delayed support.

- **Token & Infrastructure Cost Optimization:** Restricts deep context assembly and expensive model calls strictly to high-tier accounts where ROI justifies the execution cost.
- **White-Glove VIP Operations:** Empowers Account Managers and Support Engineers with tailored, high-density intelligence before engaging with top-tier clients.
- **SLA & Priority Escalation:** Automated routing guarantees high-value requests immediately surface in dedicated priority channels (e.g., Slack).

3. End-to-End Execution Architecture

Execution Stage	n8n Node / Component	Functional Responsibility
1. Ingestion	`Execute Workflow Trigger / Test Request`	Initiates the briefing pipeline upon receiving an inbound trigger or manual customer inquiry.
2. Account Lookup	`Search Records` (Airtable / CRM)	Queries the central account database to retrieve client metadata, contract status, and account tier classification.
3. Context Transfer	`Carry Account Context`	Binds account parameters, system prompts, and request payloads into a unified state payload.
4. Tier Routing	`Route by Tier` (Switch Node)	Evaluates `$json.tier` and deterministically branches into tier-specific processing logic.
5. Branch Stubs	`Enterprise`, `Mid-Market`, `Startup`, `Fallback`	Executes customized brief generation stubs tailored to the specific depth and requirement of each tier.

Execution Stage	n8n Node / Component	Functional Responsibility
6. Aggregation & Delivery	`Combine Branches` & `Format for Slack`	Consolidates output streams back into a single payload and dispatches the styled brief to designated Slack channels.

4. Key Architectural & Operational Takeaways

- **Deterministic Branching:** Relies on explicit rule-based routing nodes (`Route by Tier`) rather than prompt-based LLM self-direction, ensuring 100% predictable execution paths.
- **Fail-Safe Fallback Handling:** Unclassified or newly ingested accounts pass through a dedicated `Fallback Brief Stub` to ensure zero silent workflow failures.
- **Modular Extensibility:** Additional output destinations (e.g., CRM activity logs, email summaries) can be plugged directly into the post-combination stage without altering upstream tier logic.