MTZstore

1 client ... 3

1.1 node_modules ... 3

1.2 public ... 3

1.3 src ... 3

1.3.1 assets ... 3
1.3.2 components ... 3
1.3.2.1 AccountSidebar ... 3
1.3.2.1.1 index.jsx ... 3
1.3.2.2 AdsBannerSlider ... 6
1.3.2.3 AdsBannerSliderV2 ... 7
1.3.2.3.1 index.jsx ... 7
1.3.2.4 Badge ... 8
1.3.2.4.1 index.jsx ... 8
1.3.2.5 BannerBox ... 8
1.3.2.5.1 index.jsx ... 8
1.3.2.6 bannerBoxV2 ... 9
1.3.2.6.1 index.jsx ... 9
1.3.2.6.2 style.css ... 9
1.3.2.7 BlogItem ... 10
1.3.2.8 CartPanel ... 10
1.3.2.8.1 index.jsx ... 10
1.3.2.9 CategoryCollapse ... 12
1.3.2.9.1 index.jsx ... 12
1.3.2.10 Footer ... 14
1.3.2.10.1 index.jsx ... 14
1.3.2.11 Header ... 20
1.3.2.11.1 Navigation ... 20
1.3.2.11.1.1 CategoryPanel.jsx ... 20
1.3.2.11.1.2 index.jsx ... 21
1.3.2.11.1.3 MobileNav.jsx ... 23
1.3.2.11.1.4 style.css ... 25
1.3.2.11.2 index.jsx ... 25
1.3.2.12 HomeCatSlider ... 30
1.3.2.12.1 index.jsx ... 30
1.3.2.13 HomeSlider ... 31
1.3.2.13.1 index.jsx ... 31
1.3.2.14 HomeSliderV2 ... 32
1.3.2.14.1 index.jsx ... 32
1.3.2.15 LoadingSkeleton ... 34
1.3.2.15.1 bannerLoading.jsx ... 34
1.3.2.16 OtpBox ... 34
1.3.2.16.1 index.jsx ... 34
1.3.2.17 ProductDetails ... 35
1.3.2.17.1 index.jsx ... 35
1.3.2.18 ProductItem ... 39
1.3.2.18.1 index.jsx ... 39
1.3.2.18.2 style.css ... 45
1.3.2.19 ProductItemListView ... 45
1.3.2.19.1 index.jsx ... 45
1.3.2.19.2 style.css ... 51
1.3.2.20 ProductLoading ... 51
1.3.2.20.1 index.jsx ... 51
1.3.2.20.2 productLoadingGrid.jsx ... 53
1.3.2.21 ProductsSlider ... 57
1.3.2.21.1 index.jsx ... 57
1.3.2.22 ProductZoom ... 58
1.3.2.22.1 index.jsx ... 58
1.3.2.23 QtyBox ... 60
1.3.2.24 index.jsx ... 60
1.3.2.25 Search ... 62
1.3.2.25.1 index.jsx ... 62
1.3.2.25.2 style.css ... 63
1.3.2.26 Sidebar ... 63
1.3.2.26.1 index.jsx ... 63
1.3.2.26.2 style.css ... 71
1.3.3 Pages ... 71
1.3.3.1 Cart ... 71

1.3.3.1.1 cartItems.jsx ... 71
1.3.3.1.2 index.jsx ... 76
1.3.3.2 Checkout ... 78
1.3.3.2.1 index.jsx ... 78
1.3.3.3 ForgotPassword ... 85
1.3.3.3.1 index.jsx ... 85
1.3.3.4 Home ... 87
1.3.3.4.1 index – Copy.jsx ... 87
1.3.3.4.2 index.jsx ... 92
1.3.3.5 Login ... 98
1.3.3.5.1 index.jsx ... 98
1.3.3.6 MyAccount ... 102
1.3.3.6.1 addAddress.jsx ... 102
1.3.3.6.2 address.jsx ... 107
1.3.3.6.3 addressBox.jsx ... 109
1.3.3.6.4 index.jsx ... 110
1.3.3.7 MyList ... 116
1.3.3.7.1 index.jsx ... 116
1.3.3.7.2 myListItems.jsx ... 116
1.3.3.8 Orders ... 118
1.3.3.8.1 falied.jsx ... 118
1.3.3.8.2 index.jsx ... 118
1.3.3.8.3 success.jsx ... 123
1.3.3.9 ProductDetails ... 123
1.3.3.9.1 index.jsx ... 123
1.3.3.9.2 reviews.jsx ... 126
1.3.3.10 ProductListing ... 129
1.3.3.10.1 index.jsx ... 129
1.3.3.11 Register ... 132
1.3.3.12 index.jsx ... 132
1.3.3.13 Search ... 136
1.3.3.13.1 index.jsx ... 136
1.3.3.14 Verify ... 139
1.3.3.14.1 index.jsx ... 139
1.3.4 utils ... 140
1.3.4.1 api.js ... 140
1.3.4.2 formatPrice.js ... 142
1.3.4.3 storage.js ... 142
1.3.5 App.css ... 143
1.3.6 App.jsx ... 143
1.3.7 firebase.jsx ... 152
1.3.8 index.css ... 156
1.3.9 main.jsx ... 159
1.3.10 responsive.css ... 159

1.4 .env ... 160

1.5 .gitignore ... 161

1.6 eslint.config.js ... 161

1.7 index.html ... 162

1.8 package-lock.json ... 162

1.9 package.json ... 162

1.10 postcss.config.js ... 163

1.11 tailwind.config.js ... 163

1.12 vite.config.js ... 163

1 client

1.1 node_modules

1.2 public

1.3 src

1.3.1 assets

1.3.2 components

1.3.2.1 AccountSidebar

1.3.2.1.1 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import { Button } from "@mui/material";
import { FaCloudUploadAlt } from "react-icons/fa";
import { FaRegUser } from "react-icons/fa";
import { IoBagCheckOutline } from "react-icons/io5";
import { IoMdHeartEmpty } from "react-icons/io";
import { IoIosLogOut } from "react-icons/io";
import { NavLink } from "react-router";
import { MyContext } from "../../App";
import CircularProgress from '@mui/material/CircularProgress';
import { fetchDataFromApi, uploadImage } from "../../utils/api";
import { LuMapPin } from "react-icons/lu";



const AccountSidebar = () => {

  const [previews, setPreviews] = useState([]);
  const [uploading, setUploading] = useState(false);

  const context = useContext(MyContext);

  useEffect(() => {
    const userAvtar = [];
    if (context?.userData?.avatar !== "" && context?.userData?.avatar !== undefined) {
      userAvtar.push(context?.userData?.avatar);
      setPreviews(userAvtar)
    }

  }, [context?.userData])

  let selectedImages = [];

  const formdata = new FormData();

  const onChangeFile = async (e, apiEndPoint) => {
    try {
      setPreviews([]);
      const files = e.target.files;
      setUploading(true);


      for (var i = 0; i < files.length; i++) {
        if (files[i] && (files[i].type === "image/jpeg" || files[i].type === "image/jpg" ||
          files[i].type === "image/png" ||
          files[i].type === "image/webp")
        ) {

          const file = files[i];

          selectedImages.push(file);
          formdata.append(`avatar`, file);


        } else {
          context.alertBox("error", "Please select a valid JPG , PNG or webp image file.");
```

```
          setUploading(false);
          return false;
        }
      }

      uploadImage("/api/user/user-avatar", formdata).then((res) => {
        setUploading(false);
        let avatar = [];
        avatar.push(res?.data?.avtar);
        setPreviews(avatar);
        context.alertBox("success", "Profile picture updated successfully!");
        fetchDataFromApi(`/api/user/user-details`).then((res) => {
          context?.setUserData(res.data);
        })

      })

    } catch (error) {
      console.log(error);
    }
  }


  const logout = () => {

    fetchDataFromApi(`/api/user/logout?token=${localStorage.getItem('accessToken')}`, {
withCredentials: true }).then((res) => {
      if (res?.error === false) {
        context.setIsLogin(false);
        localStorage.removeItem("accessToken");
        localStorage.removeItem("refreshToken");
        context.setUserData(null);
        context?.setCartData([]);
        context?.setMyListData([]);
        history("/");
      }


    })

  }
  return (
    <div className="card bg-white shadow-md rounded-md sticky top-[160px]">
      <div className="w-full p-5 flex items-center justify-center flex-col">
        <div className="w-[110px] h-[110px] rounded-full overflow-hidden mb-4 relative group flex
items-center justify-center bg-gray-200">

          {
            uploading === true ? <CircularProgress color="inherit" /> :
              <>
                {
                  previews?.length !== 0 ? previews?.map((img, index) => {
                    return (
                      <img
                        src={img}
                        key={index}
                        className="w-full h-full object-cover"
                      />
                    )
                  })
                    :
                    <img
                      src={"/user.jpg"}
                      className="w-full h-full object-cover"
                    />

                }
              </>
```

```
          }


          <div className="overlay w-[100%] h-[100%] absolute top-0 left-0 z-50 bg-[rgba(0,0,0,0.7)]
flex items-center justify-center cursor-pointer opacity-0 transition-all group-hover:opacity-100">
            <FaCloudUploadAlt className="text-[#fff] text-[25px]" />
            <input
              type="file"
              className="absolute top-0 left-0 w-full h-full opacity-0"
              accept='image/*'
              onChange={(e) =>
                onChangeFile(e, "/api/user/user-avatar")
              }
              name="avatar"
            />
          </div>
        </div>

        <h3>{context?.userData?.name}</h3>
        <h6 className="text-[13px] font-[500]">{context?.userData?.email}</h6>
      </div>

      <ul className="list-none pb-5 bg-[#f1f1f1] myAccountTabs">
        <li className="w-full">
          <NavLink
            to="/my-account"
            className={({ isActive }) => (isActive ? "isActive" : "")}
          >
            <Button className="w-full !text-left !py-2 !px-5 !justify-start !capitalize !text-
[rgba(0,0,0,0.8)] !rounded-none flex items-center gap-2">
              <FaRegUser className="text-[15px]" /> Mi Cuenta
            </Button>
          </NavLink>
        </li>

        <li className="w-full">
          <NavLink
            to="/address"
            className={({ isActive }) => (isActive ? "isActive" : "")}
          >
            <Button className="w-full !text-left !py-2 !px-5 !justify-start !capitalize !text-
[rgba(0,0,0,0.8)] !rounded-none flex items-center gap-2">
              <LuMapPin className="text-[18px]" /> Dirección
            </Button>
          </NavLink>
        </li>

        <li className="w-full">
          <NavLink
            to="/my-list"
            className={({ isActive }) => (isActive ? "isActive" : "")}
          >
            <Button className="w-full !py-2 !text-left !px-5 !justify-start !capitalize !text-
[rgba(0,0,0,0.8)] !rounded-none flex items-center gap-2">
              <IoMdHeartEmpty className="text-[17px]" /> Lista de deseos
            </Button>
          </NavLink>
        </li>

        <li className="w-full">
          <NavLink
            to="/my-orders"
            className={({ isActive }) => (isActive ? "isActive" : "")}
          >
            <Button className="w-full !py-2 !text-left !px-5 !justify-start !capitalize !text-
[rgba(0,0,0,0.8)] !rounded-none flex items-center gap-2">
              <IoBagCheckOutline className="text-[17px]" /> Mis Pedidos
            </Button>
          </NavLink>
```

```
        </li>

        <li className="w-full">
          <Button className="w-full !py-2  !text-left !px-5 !justify-start !capitalize !text-
[rgba(0,0,0,0.8)] !rounded-none flex items-center gap-2" onClick={logout}>
            <IoIosLogOut className="text-[18px]" /> Cerrar sesión
          </Button>
        </li>
      </ul>
    </div>
  );
};


export default AccountSidebar;
```

1.3.2.2 AdsBannerSlider

```
import React, { useContext } from "react";
import { Swiper, SwiperSlide } from "swiper/react";
import "swiper/css";
import "swiper/css/navigation";
import 'swiper/css/free-mode';

import { Navigation, FreeMode } from "swiper/modules";
import BannerBox from "../BannerBox";
import { MyContext } from "../../App";

const AdsBannerSlider = (props) => {

  const context = useContext(MyContext);

  return (
    <div className="py-5 w-full">
      <Swiper
        slidesPerView={props.items}
        spaceBetween={10}
        navigation={context?.windowWidth < 992 ? false : true}
        modules={[Navigation, FreeMode]}
        freeMode={true}
        breakpoints={{
          300: {
            slidesPerView: 1,
            spaceBetween: 5,
          },
          450: {
            slidesPerView: 2,
            spaceBetween: 5,
          },
          750: {
            slidesPerView: 3,
            spaceBetween: 5,
          },
          1100: {
            slidesPerView: 4,
            spaceBetween: 5,
          },
        }}
        className="smlBtn"
      >
        {
          props?.data?.map((item, index) => {
            return (
              <SwiperSlide key={index}>
                <BannerBox img={item?.images[0]} item={item}/>
              </SwiperSlide>
            )
          })
```

```
        }

      </Swiper>
    </div>
  );
};

export default AdsBannerSlider;
```

1.3.2.3 AdsBannerSliderV2

1.3.2.3.1 index.jsx

```
import React, { useContext } from "react";
import { Swiper, SwiperSlide } from "swiper/react";
import "swiper/css";
import "swiper/css/navigation";
import 'swiper/css/free-mode';

import { Navigation, FreeMode } from "swiper/modules";
import BannerBox from "../BannerBox";
import BannerBoxV2 from "../bannerBoxV2";
import { MyContext } from "../../App";

const AdsBannerSlider = (props) => {

  const context = useContext(MyContext);

  return (
    <div className="py-2 lg:py-5 w-full resBannersSlider">
      <Swiper
        slidesPerView={props.items}
        spaceBetween={10}
        navigation={context?.windowWidth < 992 ? false : true}
        modules={[Navigation, FreeMode]}
        freeMode={true}
        breakpoints={{
          300: {
            slidesPerView: 1,
            spaceBetween: 5,
          },
          450: {
            slidesPerView: 2,
            spaceBetween: 5,
          },
          750: {
            slidesPerView: 3,
            spaceBetween: 5,
          },
          1100: {
            slidesPerView: 4,
            spaceBetween: 5,
          },
        }}
        className="smlBtn"
      >

        {
          props?.data?.map((item, index) => {
            return (
              <SwiperSlide key={index}>
                <BannerBoxV2 info={item?.alignInfo} item={item} image={item?.images[0]} link={"/"}
/>
              </SwiperSlide>
            )
          })

        }
```

```
      </Swiper>
    </div>
  );
};

export default AdsBannerSlider;
```

1.3.2.4 Badge

1.3.2.4.1 index.jsx

```
import React from "react";
import { IoMdCheckmark } from "react-icons/io";


const Badge = (props) => {
  return (
    <span
      className={`inline-flex items-center justify-center gap-1 py-1 px-4 rounded-full text-[11px]
capitalize ${props.status === "pending" && "bg-primary text-white"
        } ${props.status === "confirm" && "bg-green-500 text-white"} ${props.status === "delivered"
&& "bg-green-700 text-white"}`}
    >
      {
        props.status === "delivered"  &&
        <>
          <IoMdCheckmark size={13} />
        </>

      }
      {props.status}

    </span>
  );
};

export default Badge;
```

1.3.2.5 BannerBox

1.3.2.5.1 index.jsx

```
import React from "react";
import { Link } from "react-router-dom";

const BannerBox = (props) => {
  return (
    <div className="box bannerBox overflow-hidden rounded-lg group">
    {console.log(props?.item)}
      {
        props?.item?.subCatId !== undefined && props?.item?.subCatId !== null &&
props?.item?.subCatId !== ""  ?
          <Link to={`/products?subCatId=${props?.item?.subCatId}`} className="text-[16px] font-
[600] link">
            <img src={props.img} className="w-full transition-all group-hover:scale-105 group-
hover:rotate-1" alt="banner" />
          </Link>
          :

          <Link to={`/products?catId=${props?.item?.catId}`} className="text-[16px] font-[600]
link">

            <img src={props.img} className="w-full transition-all group-hover:scale-105 group-
hover:rotate-1" alt="banner" />
          </Link>

      }
```

```
    </div>
  );
};

export default BannerBox;
```

1.3.2.6 bannerBoxV2

1.3.2.6.1 index.jsx

```
import React from "react";
import "../bannerBoxV2/style.css";
import { Link } from "react-router-dom";
import { formatPrice } from "../../utils/formatPrice"; // ✅ mostrar siempre en BOB

const BannerBoxV2 = (props) => {
  // ✅ Tomar BOB si viene del back, si no cae a price
  const unitBob = Number(props?.item?.priceBob ?? props?.item?.price ?? 0);

  return (
    <div className="bannerBoxV2 box w-full overflow-hidden rounded-md group relative">
      <img
        src={props.image}
        className="w-full transition-all duration-150 group-hover:scale-105"
      />

      <div
        className={`info absolute p-5 top-0 ${props.info === "left" ? "left-0" : "right-0"
          } w-[70%] h-[100%] z-50 flex items-center justify-center flex-col gap-2
         ${props.info === "left" ? "" : "pl-16"}`}
      >
        <h2 className="text-[14px] md:text-[18px] font-[600]">
          {props?.item?.bannerTitle}
        </h2>

        {/* ✅ Precio siempre en BOB */}
        <span className="text-[20px] text-primary font-[600] w-full">
          {formatPrice(unitBob, "BOB")}
        </span>

        <div className="w-full">
          {props?.item?.subCatId !== undefined && props?.item?.subCatId !== null ? (
            <Link
              to={`/products?subCatId=${props?.item?.subCatId}`}
              className="text-[16px] font-[600] link"
            >
              COMPRA AHORA
            </Link>
          ) : (
            <Link
              to={`/products?catId=${props?.item?.catId}`}
              className="text-[16px] font-[600] link"
            >
              CAOMPRA AHORA
            </Link>
          )}
        </div>
      </div>
    </div>
  );
};

export default BannerBoxV2;
```

1.3.2.6.2 style.css

```
.bannerBoxV2{height: 210px;}
.bannerBoxV2 a{text-decoration: underline !important;}
```

1.3.2.7 BlogItem

```
import React from "react";
import { IoMdTime } from "react-icons/io";
import { Link } from "react-router-dom";
import { IoIosArrowForward } from "react-icons/io";
import { fetchDataFromApi, deleteData } from '../../utils/api';
import { LazyLoadImage } from "react-lazy-load-image-component";
import "react-lazy-load-image-component/src/effects/blur.css";


const BlogItem = (props) => {
  return (
    <div className="blogItem group">
      <div className="imgWrapper w-full overflow-hidden rounded-md cursor-pointer relative">
        <LazyLoadImage
          alt={"image"}
          effect="blur"
          className="w-full transition-all group-hover:scale-105  group-hover:rotate-1"
          src={props?.item?.images[0]}
        />


        <span className="flex items-center justify-center text-white absolute bottom-[15px] right-
[15px] z-50 bg-primary rounded-md p-1 text-[11px] font-[500] gap-1">
          <IoMdTime className="text-[16px]" /> {props?.item?.createdAt?.split("T")[0]}
        </span>
      </div>

      <div className="info py-4">
        <h2 className="text-[15px] font-[600] text-black mb-1  lg:mb-3">
          <Link to="/" className="link">{props?.item?.title}</Link>
        </h2>

        <div className="mb-3 text-[14px] lg:text-[16px]" dangerouslySetInnerHTML={{ __html:
props?.item?.description?.substr(0, 100) + '...' }} />



        <Link className="link font-[500] text-[14px] flex items-center gap-1">Leer más
<IoIosArrowForward /></Link>

      </div>
    </div>
  );
};

export default BlogItem;
```

1.3.2.8 CartPanel

1.3.2.8.1 index.jsx

```
import React, { useContext } from "react";
import { Link } from "react-router-dom";
import { MdOutlineDeleteOutline } from "react-icons/md";
import Button from "@mui/material/Button";
import { MyContext } from "../../App";
import { deleteData } from "../../utils/api";
// ✅ Mostrar siempre en BOB
import { formatPrice } from "../../utils/formatPrice";

const CartPanel = (props) => {
  const context = useContext(MyContext);

  const removeItem = (id) => {
```

```
    deleteData(`/api/cart/delete-cart-item/${id}`).then((res) => {
      context.alertBox("success", "Item Removed ");
      context?.getCartItems();
    });
  };

  // ✅ Subtotales/Total en BOB
  const totalBob = (context.cartData?.length
    ? context.cartData
      .map((it) => (Number(it.price) || 0) * (Number(it.quantity) || 0))
      .reduce((sum, v) => sum + v, 0)
    : 0
  );

  return (
    <>
      <div className="scroll w-full max-h-[60vh] overflow-y-scroll overflow-x-hidden py-3 px-4">
        {props?.data?.map((item, index) => {
          const priceBob = Number(item?.price) || 0;

          return (
            <div
              key={item?._id || index}
              className="cartItem w-full flex items-center gap-4 border-b border-[rgba(0,0,0,0.1)]
pb-4"
            >
              <div
                className="img w-[25%] overflow-hidden h-[80px] rounded-md"
                onClick={context.toggleCartPanel(false)}
              >
                <Link to={`/product/${item?.productId}`} className="block group">
                  <img src={item?.image} className="w-full group-hover:scale-105" />
                </Link>
              </div>

              <div className="info w-[75%] pr-5 relative pt-3">
                <h4
                  className="text-[12px] sm:text-[14px] font-[500]"
                  onClick={context.toggleCartPanel(false)}
                >
                  <Link to={`/product/${item?.productId}`} className="link transition-all">
                    {item?.productTitle?.substr(0, 20) + "..."}
                  </Link>
                </h4>

                <p className="flex items-center gap-5 mt-2 mb-2">
                  <span className="text-[13px] sm:text-[14px]">
                    Qty : <span>{item?.quantity}</span>
                  </span>

                  {/* ✅ Precio unitario en BOB */}
                  <span className="text-primary font-bold">
                    {formatPrice(priceBob, "BOB")}
                  </span>
                </p>

                <MdOutlineDeleteOutline
                  className="absolute top-[10px] right-[10px] cursor-pointer text-[20px] link
transition-all"
                  onClick={() => removeItem(item?._id)}
                />
              </div>
            </div>
          );
        })}
      </div>

      <br />
```

```
      <div className="bottomSec absolute bottom-[10px] left-[10px] w-full overflow-hidden pr-5">
        <div className="bottomInfo py-3 px-4 w-full border-t border-[rgba(0,0,0,0.1)] flex items-
center justify-between flex-col">
          <div className="flex items-center justify-between w-full">
            <span className="text-[14px] font-[600]">
              {context?.cartData?.length} Ítem
              {context?.cartData?.length === 1 ? "" : "s"}
            </span>

            {/* ✅ Subtotal en BOB */}
            <span className="text-primary font-bold">
              {formatPrice(totalBob, "BOB")}
            </span>
          </div>
        </div>

        <div className="bottomInfo py-3 px-4 w-full border-t border-[rgba(0,0,0,0.1)] flex items-
center justify-between flex-col">
          <div className="flex items-center justify-between w-full">
            <span className="text-[14px] font-[600]">Total (impuestos excl.)</span>

            {/* ✅ Total en BOB */}
            <span className="text-primary font-bold">
              {formatPrice(totalBob, "BOB")}
            </span>
          </div>

          <br />

          <div className="flex items-center justify-between w-full gap-5">
            <Link to="/cart" className=" w-[50%] d-block" onClick={context.toggleCartPanel(false)}>
              <Button className="btn-org btn-lg w-full">Ver Carrito</Button>
            </Link>
            <Link
              to="/checkout"
              className=" w-[50%] d-block"
              onClick={context.toggleCartPanel(false)}
            >
              <Button className="btn-org btn-border btn-lg w-full">Pagar Ahora</Button>
            </Link>
          </div>
        </div>
      </div>
    </>
  );
};

export default CartPanel;
```

1.3.2.9 CategoryCollapse

1.3.2.9.1 index.jsx

```
import React, { useState } from "react";
import { Link } from "react-router-dom";
import Button from "@mui/material/Button";
import { FiMinusSquare } from "react-icons/fi";
import { FaRegSquarePlus } from "react-icons/fa6";

export const CategoryCollapse = (props) => {
  const [submenuIndex, setSubmenuIndex] = useState(null);
  const [innerSubmenuIndex, setInnerSubmenuIndex] = useState(null);



  const openSubmenu = (index) => {
    if (submenuIndex === index) {
      setSubmenuIndex(null);
    } else {
```

```
      setSubmenuIndex(index);
    }
  };

  const openInnerSubmenu = (index) => {
    if (innerSubmenuIndex === index) {
      setInnerSubmenuIndex(null);
    } else {
      setInnerSubmenuIndex(index);
    }
  };


  return (
    <>
      <div className="scroll">
        <ul className="w-full">
          {
            props?.data?.length !== 0 && props?.data?.map((cat, index) => {
              return (
                <li className="list-none flex items-center relative flex-col" key={index}>

                  <Link to={`/products?catId=${cat?._id}`} className="w-full">
                    <Button className="w-full !text-left !justify-start !px-3 !text-
[rgba(0,0,0,0.8)]">
                      {cat?.name}
                    </Button>
                  </Link>

                  <div className="absolute w-[30px] h-[30px] flex items-center justify-center top-
[10px] right-[15px]  cursor-pointer" onClick={() => openSubmenu(index)}>

                    {submenuIndex === index ? (
                      <FiMinusSquare
                      />
                    ) : (
                      <FaRegSquarePlus
                      />
                    )}
                  </div>
                  {submenuIndex === index && (
                    <ul className="submenu w-full pl-3">
                      {
                        cat?.children?.length !== 0 && cat?.children?.map((subCat, index_) => {
                          return (
                            <li className="list-none relative" key={index_}>
                              <Link to={`/products?subCatId=${subCat?._id}`} className="w-full">
                                <Button className="w-full !text-left !justify-start !px-3 !text-
[rgba(0,0,0,0.8)]">

                                  {subCat?.name}
                                </Button>
                              </Link>

                              <div className="absolute w-[30px] h-[30px] flex items-center justify-
center top-[10px] right-[15px]  cursor-pointer" onClick={() => openInnerSubmenu(index_)}>
                                {innerSubmenuIndex === index_ ? (
                                  <FiMinusSquare
                                  />
                                ) : (
                                  <FaRegSquarePlus
                                  />
                                )}
                              </div>

                              {innerSubmenuIndex === index_ && (
                                <ul className="inner_submenu w-full pl-3">
                                  {
                                    subCat?.children?.length !== 0 &&
subCat?.children?.map((thirdLavelCat, index__) => {
```

```
                                        return (
                                          <li className="list-none relative mb-1" key={index__}>
                                            <Link
                                              to={`/products?thirdLavelCatId=${thirdLavelCat?._id}`}
                                              className="link w-full !text-left !justify-start !px-3
transition text-[14px]"
                                            >
                                              {thirdLavelCat?.name}
                                            </Link>
                                          </li>
                                        )
                                      })
                                    }



                                  </ul>
                                )}
                              </li>
                            )
                          })
                        }

                      </ul>
                    )}
                  </li>
                )
              })
            }

          </ul>
        </div>
      </>
    );
};
```

1.3.2.10 Footer

1.3.2.10.1 index.jsx

```
import React, { useContext } from "react";
import { LiaShippingFastSolid } from "react-icons/lia";
import { PiKeyReturnLight } from "react-icons/pi";
import { BsWallet2 } from "react-icons/bs";
import { LiaGiftSolid } from "react-icons/lia";
import { BiSupport } from "react-icons/bi";
import { Link } from "react-router-dom";
import { IoChatboxOutline } from "react-icons/io5";

import FormControlLabel from "@mui/material/FormControlLabel";
import Checkbox from "@mui/material/Checkbox";
import { FaFacebookF } from "react-icons/fa";
import { AiOutlineYoutube } from "react-icons/ai";
import { FaPinterestP } from "react-icons/fa";
import { FaInstagram } from "react-icons/fa";

import Drawer from "@mui/material/Drawer";
import CartPanel from "../CartPanel";
import { MyContext } from "../../App";

import Button from "@mui/material/Button";
import Dialog from "@mui/material/Dialog";
import DialogContent from "@mui/material/DialogContent";
import { ProductZoom } from "../ProductZoom";
import { IoCloseSharp } from "react-icons/io5";
import { ProductDetailsComponent } from "../ProductDetails";
import AddAddress from "../../Pages/MyAccount/addAddress";

// ✅ Mostrar BOB siempre
```

```
import { formatPrice } from "../../utils/formatPrice";

const FREE_SHIPPING_THRESHOLD_BOB = 100; // Ajusta el umbral si lo necesitas

const Footer = () => {
  const context = useContext(MyContext);

  return (
    <>
      <footer className="py-6 bg-[#fafafa]">
        <div className="container">
          <div className="flex items-center justify-center gap-2 py-3 lg:py-8 pb-0 lg:pb-8 px-0
lg:px-5 scrollableBox footerBoxWrap">
            <div className="col flex items-center justify-center flex-col group w-[15%]">
              <LiaShippingFastSolid className="text-[40px] transition-all duration-300 group-
hover:text-primary group-hover:-translate-y-1" />
              <h3 className="text-[16px] font-[600] mt-3">Envío gratuito</h3>
              {/* Antes: "$100" → ahora BOB */}
              <p className="text-[12px] font-[500]">
                Para todos los pedidos superiores a: {formatPrice(FREE_SHIPPING_THRESHOLD_BOB,
"BOB")}
              </p>
            </div>

            <div className="col flex items-center justify-center flex-col group w-[15%]">
              <PiKeyReturnLight className="text-[40px] transition-all duration-300 group-
hover:text-primary group-hover:-translate-y-1" />
              <h3 className="text-[16px] font-[600] mt-3">Devolución 30D</h3>
              <p className="text-[12px] font-[500]">Para un producto de intercambio</p>
            </div>

            <div className="col flex items-center justify-center flex-col group w-[15%]">
              <BsWallet2 className="text-[40px] transition-all duration-300 group-hover:text-
primary group-hover:-translate-y-1" />
              <h3 className="text-[16px] font-[600] mt-3">Pago Seguro</h3>
              <p className="text-[12px] font-[500]">Tarjetas de pago aceptadas</p>
            </div>

            <div className="col flex items-center justify-center flex-col group w-[15%]">
              <LiaGiftSolid className="text-[40px] transition-all duration-300 group-hover:text-
primary group-hover:-translate-y-1" />
              <h3 className="text-[16px] font-[600] mt-3">Regalos especiales</h3>
              <p className="text-[12px] font-[500]">Para el primer pedido</p>
            </div>

            <div className="col flex items-center justify-center flex-col group w-[15%]">
              <BiSupport className="text-[40px] transition-all duration-300 group-hover:text-
primary group-hover:-translate-y-1" />
              <h3 className="text-[16px] font-[600] mt-3">Soporte 24/7</h3>
              <p className="text-[12px] font-[500]">Póngase en contacto con nosotros en cualquier
momento</p>
            </div>
          </div>
          <br />

          <hr />

          <div className="footer flex px-3 lg:px-0 flex-col lg:flex-row py-8">
            <div className="part1 w-full lg:w-[25%] border-r border-[rgba(0,0,0,0.1)]">
              <h2 className="text-[18px] font-[600] mb-4">Contáctanos</h2>
              <p className="text-[13px] font-[400] pb-4">
                MTZstore – La mejor tienda de la región
                <br />
                6 de Octubre entre San Felipe y Aldana
              </p>

              <Link
                className="link text-[13px]"
                to="mailto:someone@example.com"
```

```
          >
            mtzstore.bo@gmail.com
          </Link>

          <span className="text-[22px] font-[600] block w-full mt-3 mb-5 text-primary">
            (+591) 71854443
          </span>

          <div className="flex items-center gap-2">
            <IoChatboxOutline className="text-[40px] text-primary" />
            <span className="text-[16px] font-[600]">
              Chat en línea
              <br />
              Obtenga ayuda de expertos
            </span>
          </div>
        </div>

        <div className="part2  w-full lg:w-[40%] flex pl-0 lg:pl-8 mt-5 lg:mt-0">
          <div className="part2_col1 w-[50%]">
            <h2 className="text-[18px] font-[600] mb-4">Productos</h2>

            <ul className="list">
              <li className="list-none text-[14px] w-full mb-2">
                <Link to="/" className="link">
                  Precios bajos
                </Link>
              </li>
              <li className="list-none text-[14px] w-full mb-2">
                <Link to="/" className="link">
                  Nuevos productos
                </Link>
              </li>
              <li className="list-none text-[14px] w-full mb-2">
                <Link to="/" className="link">
                  Las mejores novedades
                </Link>
              </li>
              <li className="list-none text-[14px] w-full mb-2">
                <Link to="/" className="link">
                  Contáctanos
                </Link>
              </li>
              <li className="list-none text-[14px] w-full mb-2">
                <Link to="/" className="link">
                  Ubicación
                </Link>
              </li>
              <li className="list-none text-[14px] w-full mb-2">
                <Link to="/" className="link">
                  Tiendas
                </Link>
              </li>
            </ul>
          </div>

          <div className="part2_col2 w-[50%]">
            <h2 className="text-[18px] font-[600] mb-4">Nuestra empresa</h2>

            <ul className="list">
              <li className="list-none text-[14px] w-full mb-2">
                <Link to="/" className="link">
                  Reparto
                </Link>
              </li>
              <li className="list-none text-[14px] w-full mb-2">
                <Link to="/" className="link">
                  Aviso Legal
                </Link>
```

```
                  </li>
                  <li className="list-none text-[14px] w-full mb-2">
                    <Link to="/" className="link">
                      Terminos y condiciones de uso
                    </Link>
                  </li>
                  <li className="list-none text-[14px] w-full mb-2">
                    <Link to="/" className="link">
                      Sobre nosotros
                    </Link>
                  </li>
                  <li className="list-none text-[14px] w-full mb-2">
                    <Link to="/" className="link">
                      Pago seguro
                    </Link>
                  </li>
                  <li className="list-none text-[14px] w-full mb-2">
                    <Link to="/" className="link">
                      Iniciar Sesión
                    </Link>
                  </li>
                </ul>
              </div>
            </div>

            <div className="part2  w-full lg:w-[35%] flex pl-0 lg:pl-8 flex-col pr-8 mt-5 lg:mt-0">
              <h2 className="text-[18px] font-600] mb-2 lg:mb-4">
                Suscribirse al boletín
              </h2>
              <p className="text-[13px]">
                Suscríbase a nuestro último boletín para recibir noticias sobre descuentos
especiales.
              </p>

              <form className="mt-5">
                <input
                  type="text"
                  className="w-full h-[45px] border outline-none pl-4 pr-4 rounded-sm mb-4
focus:border-[rgba(0,0,0,0.3)]"
                  placeholder="Tu dirección de correo electrónico"
                />

                <Button className="btn-org">SUSCRÍBETE</Button>

                <FormControlLabel
                  className="mt-3 lg:mt-0 block w-full"
                  control={<Checkbox />}
                  label=" Acepto los términos y condiciones y la política de privacidad"
                />
              </form>
            </div>
          </div>
        </div>
      </footer>

      <div className="bottomStrip border-t border-[rgba(0,0,0,0.1)] pt-3 pb-[100px] lg:pb-3 bg-
white">
        <div className="container flex items-center justify-between flex-col lg:flex-row gap-4
lg:gap-0">
          <ul className="flex items-center gap-2">
            <li className="list-none">
              <Link
                to="/"
                target="_blank"
                className="w-[35px] h-[35px] rounded-full border border-[rgba(0,0,0,0.1)] flex
items-center justify-center group hover:bg-primary transition-all"
              >
                <FaFacebookF className="text-[17px] group-hover:text-white" />
              </Link>
```

```
            </li>

            <li className="list-none">
              <Link
                to="/"
                target="_blank"
                className="w-[35px] h-[35px] rounded-full border border-[rgba(0,0,0,0.1)] flex
items-center justify-center group hover:bg-primary transition-all"
              >
                <AiOutlineYoutube className="text-[21px] group-hover:text-white" />
              </Link>
            </li>

            <li className="list-none">
              <Link
                to="/"
                target="_blank"
                className="w-[35px] h-[35px] rounded-full border border-[rgba(0,0,0,0.1)] flex
items-center justify-center group hover:bg-primary transition-all"
              >
                <FaPinterestP className="text-[17px] group-hover:text-white" />
              </Link>
            </li>

            <li className="list-none">
              <Link
                to="/"
                target="_blank"
                className="w-[35px] h-[35px] rounded-full border border-[rgba(0,0,0,0.1)] flex
items-center justify-center group hover:bg-primary transition-all"
              >
                <FaInstagram className="text-[17px] group-hover:text-white" />
              </Link>
            </li>
          </ul>

          <p className="text-[13px] text-center mb-0">
            © 2025 - Comercio Electrónico Oruro-Bolivia
          </p>

          <div className="flex items-center gap-1">
            <img src="/carte_bleue.png" alt="image" />
            <img src="/visa.png" alt="image" />
            <img src="/master_card.png" alt="image" />
            <img src="/american_express.png" alt="image" />
            <img src="/paypal.png" alt="image" />
          </div>
        </div>
      </div>

      {/* Cart Panel */}
      <Drawer
        open={context.openCartPanel}
        onClose={context.toggleCartPanel(false)}
        anchor={"right"}
        className="cartPanel"
      >
        <div className="flex items-center justify-between py-3 px-4 gap-3 border-b border-
[rgba(0,0,0,0.1)] overflow-hidden">
          <h4> Carrito de compra
 ({context?.cartData?.length})</h4>
          <IoCloseSharp className="text-[20px] cursor-pointer"
onClick={context.toggleCartPanel(false)} />
        </div>

        {context?.cartData?.length !== 0 ? (
          <CartPanel data={context?.cartData} />
        ) : (
          <>
```

```
            <div className="flex items-center justify-center flex-col pt-[100px] gap-5">
              <img src="/empty-cart.png" className="w-[150px]" />
              <h4> Su carrito está vacío actualmente</h4>
              <Button className="btn-org btn-sm" onClick={context.toggleCartPanel(false)}>
                Continue comprando
              </Button>
            </div>
          </>
        )}
      </Drawer>

      {/* Address Panel */}
      <Drawer
        open={context.openAddressPanel}
        onClose={context.toggleAddressPanel(false)}
        anchor={"right"}
        className="addressPanel"
      >
        <div className="flex items-center justify-between py-3 px-4 gap-3 border-b border-
[rgba(0,0,0,0.1)] overflow-hidden">
          <h4>{context?.addressMode === "add" ? "Add" : "Edit"} Dirección de entrega </h4>
          <IoCloseSharp className="text-[20px] cursor-pointer"
onClick={context.toggleAddressPanel(false)} />
        </div>

        <div className="w-full max-h-[100vh] overflow-auto">
          <AddAddress />
        </div>
      </Drawer>

      <Dialog
        open={context?.openProductDetailsModal.open}
        fullWidth={context?.fullWidth}
        maxWidth={context?.maxWidth}
        onClose={context?.handleCloseProductDetailsModal}
        aria-labelledby="alert-dialog-title"
        aria-describedby="alert-dialog-description"
        className="productDetailsModal"
      >
        <DialogContent>
          <div className="flex items-center w-full productDetailsModalContainer relative">
            <Button
              className="!w-[40px] !h-[40px] !min-w-[40px] !rounded-full !text-[#000] !absolute
top-[15px] right-[15px] !bg-[#f1f1f1]"
              onClick={context?.handleCloseProductDetailsModal}
            >
              <IoCloseSharp className="text-[20px]" />
            </Button>
            {context?.openProductDetailsModal?.item?.length !== 0 && (
              <>
                <div className="col1 w-[40%] px-3 py-8">
                  <ProductZoom images={context?.openProductDetailsModal?.item?.images} />
                </div>

                <div className="col2 w-[60%] py-8 px-8 pr-16 productContent ">
                  <ProductDetailsComponent item={context?.openProductDetailsModal?.item} />
                </div>
              </>
            )}
          </div>
        </DialogContent>
      </Dialog>
    </>
  );
};

export default Footer;
```

1.3.2.11 Header

1.3.2.11.1 Navigation

1.3.2.11.1.1CategoryPanel.jsx

```
import React, { useContext, useState } from "react";
import Box from "@mui/material/Box";
import Drawer from "@mui/material/Drawer";
import { IoCloseSharp } from "react-icons/io5";
import { CategoryCollapse } from "../../CategoryCollapse";
import { Button } from "@mui/material";
import { MyContext } from "../../../App";
import { Link } from "react-router-dom";
import { fetchDataFromApi } from "../../../utils/api";

const CategoryPanel = (props) => {

  const context = useContext(MyContext);

  const toggleDrawer = (newOpen) => () => {
    props.setIsOpenCatPanel(newOpen);
    props.propsSetIsOpenCatPanel(newOpen)
  };


  const DrawerList = (
    <Box sx={{ width: 250 }} role="presentation" className="categoryPanel">

      <div className="p-3">
        <img src={localStorage.getItem('logo')} className="w-[170px]" />
      </div>

      <h3 className="p-3 text-[16px] font-[500] flex items-center justify-between">
        Shop By Categories{" "}
        <IoCloseSharp
          onClick={toggleDrawer(false)}
          className="cursor-pointer text-[20px]"
        />
      </h3>

      {
        props?.data?.length !== 0 && <CategoryCollapse data={props?.data} />
      }

      {
        context?.windowWidth < 992 && context?.isLogin === false &&
        <Link to="/login" className="p-3 block" onClick={() => {
          props.setIsOpenCatPanel(false);
          props.propsSetIsOpenCatPanel(false)
        }}>
          <Button className="btn-org w-full">Iniciar Sesión</Button>
        </Link>
      }


      {
        context?.windowWidth < 992 && context?.isLogin === true &&
        <div className="p-3 block" onClick={() => {
          props.setIsOpenCatPanel(false);
          props.propsSetIsOpenCatPanel(false)
          fetchDataFromApi(`/api/user/logout?token=${localStorage.getItem('accessToken')}`, {
withCredentials: true }).then((res) => {
            if (res?.error === false) {
              context.setIsLogin(false);
              localStorage.removeItem("accessToken");
              localStorage.removeItem("refreshToken");
              context.setUserData(null);
              context?.setCartData([]);
              context?.setMyListData([]);
              history("/");
```

```
            }


          })
        }}>
          <Button className="btn-org w-full">Cerrar Sesión</Button>
        </div>
      }


    </Box>
  );

  return (
    <>
      <Drawer open={props.isOpenCatPanel} onClose={toggleDrawer(false)}>
        {DrawerList}
      </Drawer>
    </>
  );
};

export default CategoryPanel;
```

1.3.2.11.1.2index.jsx

```
import Button from "@mui/material/Button";
import React, { useContext, useEffect, useState } from "react";
import { RiMenu2Fill } from "react-icons/ri";
import { LiaAngleDownSolid } from "react-icons/lia";
import { Link } from "react-router-dom";
import { GoRocket } from "react-icons/go";
import CategoryPanel from "./CategoryPanel";

import "../Navigation/style.css";
import { fetchDataFromApi } from "../../../utils/api";
import { MyContext } from "../../../App";
import MobileNav from "./MobileNav";

const Navigation = (props) => {
  const [isOpenCatPanel, setIsOpenCatPanel] = useState(false);
  const [catData, setCatData] = useState([]);

  const context = useContext(MyContext);

  useEffect(() => {
    setCatData(context?.catData);
  }, [context?.catData]);

  useEffect(() => {
    setIsOpenCatPanel(props.isOpenCatPanel);
  }, [props.isOpenCatPanel])

  const openCategoryPanel = () => {
    setIsOpenCatPanel(true);
  };

  return (
    <>
      <nav className="navigation">
        <div className="container flex items-center justify-start lg:justify-end gap-8">
          {
            context?.windowWidth > 992 &&
            <div className="col_1 w-[20%]">
              <Button
                className="!text-black gap-2 w-full"
                onClick={openCategoryPanel}
              >
                <RiMenu2Fill className="text-[18px]" />
```

```
                Todas las categorías
                <LiaAngleDownSolid className="text-[13px] ml-auto font-bold" />
              </Button>
            </div>
          }


          <div className="col_2 w-full lg:w-[60%]">
            <ul className="flex items-center gap-3 nav">
              <li className="list-none">
                <Link to="/" className="link transition text-[14px] font-[500]">
                  <Button className="link transition !font-[500] !text-[rgba(0,0,0,0.8)]
hover:!text-[#ff5252] !py-4">
                    Inicio
                  </Button>
                </Link>
              </li>

              {
                catData?.length !== 0 && catData?.map((cat, index) => {
                  return (
                    <li className="list-none relative" key={index}>
                      <Link to={`/products?catId=${cat?._id}`} className="link transition text-
[14px] font-[500]">
                        <Button className="link transition !font-[500] !text-[rgba(0,0,0,0.8)]
hover:!text-[#ff5252] !py-4">
                          {cat?.name}
                        </Button>
                      </Link>

                      {
                        cat?.children?.length !== 0 &&
                        <div className="submenu absolute top-[120%] left-[0%] min-w-[150px] bg-
white shadow-md opacity-0 transition-all">
                          <ul>
                            {
                              cat?.children?.map((subCat, index_) => {
                                return (
                                  <li className="list-none w-full relative" key={index_}>
                                    <Link to={`/products?subCatId=${subCat?._id}`} className="w-
full">
                                      <Button className="!text-[rgba(0,0,0,0.8)]  w-full !text-left
!justify-start !rounded-none">
                                        {subCat?.name}
                                      </Button>

                                      {
                                        subCat?.children?.length !== 0 &&
                                        <div className="submenu absolute top-[0%] left-[100%] min-
w-[150px] bg-white shadow-md opacity-0 transition-all">
                                          <ul>
                                            {
                                              subCat?.children?.map((thirdLavelCat, index__) => {
                                                return (
                                                  <li className="list-none w-full" key={index__}>
                                                    <Link
to={`/products?thirdLavelCatId=${thirdLavelCat?._id}`} className="w-full">
                                                      <Button className="!text-[rgba(0,0,0,0.8)]
w-full !text-left !justify-start !rounded-none">
                                                        {thirdLavelCat?.name}
                                                      </Button>
                                                    </Link>
                                                  </li>)
                                              })
                                            }



                                          </ul>
```

```
                                        </div>
                                      }


                                    </Link>
                                  </li>
                                )
                              })
                            }




                          </ul>
                        </div>
                      }

                    </li>
                  )
                })
              }


            </ul>
          </div>

          <div className="col_3 w-[20%] hidden lg:block">
            <p className="text-[14px] font-[500] flex items-center gap-3 mb-0 mt-0">
              <GoRocket className="text-[18px]" />
              Envío gratis a nivel local
            </p>
          </div>
        </div>
      </nav>

      {/* category panel component */}
      {
        catData?.length !== 0 &&
        <CategoryPanel
          isOpenCatPanel={isOpenCatPanel}
          setIsOpenCatPanel={setIsOpenCatPanel}
          propsSetIsOpenCatPanel={props.setIsOpenCatPanel}
          data={catData}
        />
      }


      {
        context?.windowWidth < 992 && <MobileNav />
      }



    </>
  );
};

export default Navigation;
```

1.3.2.11.1.3MobileNav.jsx

```
import { Button } from '@mui/material'
import React, { useContext, useEffect } from 'react';
import { IoHomeOutline } from "react-icons/io5";
import { IoSearch } from "react-icons/io5";
import { LuHeart } from "react-icons/lu";
import { BsBagCheck } from "react-icons/bs";
import { FiUser } from "react-icons/fi";
```

```
import { NavLink } from "react-router";
import { MdOutlineFilterAlt } from "react-icons/md";
import { MyContext } from '../../../App';
import { useLocation } from "react-router-dom";

const MobileNav = () => {

    const context = useContext(MyContext)

    const location = useLocation();

    useEffect(() => {

        if (location.pathname === "/products" || location.pathname === "/search") {
            context?.setisFilterBtnShow(true)
            // Perform your action here
        } else {
            context?.setisFilterBtnShow(false)
        }
    }, [location]);

    const openFilters = () => {
        context?.setOpenFilter(true);
        context?.setOpenSearchPanel(false)
    }


    return (
        <div className='mobileNav bg-white p-1 px-3 w-full flex items-center justify-between fixed
bottom-0 left-0 gap-0 z-[51]'>
            <NavLink
                to="/"
                className={({ isActive }) => (isActive ? "isActive" : "")}
                onClick={() => context?.setOpenSearchPanel(false)}
            >
                <Button className="flex-col !w-[40px] !min-w-[40px] !capitalize !text-gray-700">
                    <IoHomeOutline size={18} />
                    <span className="text-[12px]">Inicio</span>
                </Button>
            </NavLink>



            {
                context?.isFilterBtnShow === true &&
                <Button className="flex-col !w-[40px] !h-[40px] !min-w-[40px] !capitalize !text-
gray-700 !bg-primary !rounded-full" onClick={openFilters}>
                    <MdOutlineFilterAlt size={18} className='text-white' />
                </Button>
            }

            <Button className="flex-col !w-[40px] !min-w-[40px] !capitalize !text-gray-700"
                onClick={() => context?.setOpenSearchPanel(true)}>
                <IoSearch size={18} />
                <span className='text-[12px]'>Buscar</span>
            </Button>




            <NavLink
                to="/my-list"
                className={({ isActive }) => (isActive ? "isActive" : "")}
                onClick={() => context?.setOpenSearchPanel(false)}
            >
                <Button className="flex-col !w-[40px] !min-w-[40px] !capitalize !text-gray-700">
                    <LuHeart size={18} />
                    <span className="text-[12px]">Lista de deseos</span>
                </Button>
```

```
            </NavLink>

            <NavLink
                to="/my-orders"
                className={({ isActive }) => (isActive ? "isActive" : "")}
                onClick={() => context?.setOpenSearchPanel(false)}
            >
                <Button className="flex-col !w-[40px] !min-w-[40px] !capitalize !text-gray-700">
                    <BsBagCheck size={18} />
                    <span className="text-[12px]">Pedidos</span>
                </Button>
            </NavLink>

            <NavLink
                to="/my-account"
                className={({ isActive }) => (isActive ? "isActive" : "")}
                onClick={() => context?.setOpenSearchPanel(false)}
            >
                <Button className="flex-col !w-[40px] !min-w-[40px] !capitalize !text-gray-700">
                    <FiUser size={18} />
                    <span className="text-[12px]">Mi cuenta</span>
                </Button>
            </NavLink>

        </div>
    )
}

export default MobileNav
```

1.3.2.11.1.4 style.css

```
.categoryPanel button{text-transform: capitalize !important;}

.nav li .submenu{visibility: hidden; z-index: 1000;}
.nav li .submenu button{font-weight: 400 !important;}
.nav li:hover .submenu{opacity: 1 !important; visibility: inherit; top: 100%;}
.nav li .submenu li:hover button{color: #ff5252 !important;}

.nav li .submenu li .submenu{top: 0px !important; left: 120% !important; opacity: 0 !important;}
.nav li .submenu li:hover .submenu{left: 100% !important; opacity: 1 !important;}

.nav li .submenu li .submenu button{color: rgba(0,0,0,0.80) !important;}
.nav li .submenu li .submenu button:hover{color: #ff5252 !important;}
```

1.3.2.11.2 index.jsx

```
import React, { useContext, useState } from "react";
import { Link, useLocation, useNavigate } from "react-router-dom";
import Search from "../Search";
import Badge from "@mui/material/Badge";
import { styled } from "@mui/material/styles";
import IconButton from "@mui/material/IconButton";
import { MdOutlineShoppingCart } from "react-icons/md";
import { IoGitCompareOutline } from "react-icons/io5";
import { FaRegHeart } from "react-icons/fa6";
import Tooltip from "@mui/material/Tooltip";
import Navigation from "./Navigation";
import { MyContext } from "../../App";
import { Button } from "@mui/material";
import { FaRegUser } from "react-icons/fa";

import Menu from "@mui/material/Menu";
import MenuItem from "@mui/material/MenuItem";
import { IoBagCheckOutline } from "react-icons/io5";
import { IoMdHeartEmpty } from "react-icons/io";
import { IoIosLogOut } from "react-icons/io";
import { fetchDataFromApi } from "../../utils/api";
```

```
import { LuMapPin } from "react-icons/lu";
import { useEffect } from "react";
import { HiOutlineMenu } from "react-icons/hi";


const StyledBadge = styled(Badge)(({ theme }) => ({
  "& .MuiBadge-badge": {
    right: -3,
    top: 13,
    border: `2px solid ${theme.palette.background.paper}`,
    padding: "0 4px",
  },
}));

const Header = () => {
  const [anchorEl, setAnchorEl] = useState(null);
  const open = Boolean(anchorEl);

  const [isOpenCatPanel, setIsOpenCatPanel] = useState(false);

  const context = useContext(MyContext);

  const history = useNavigate();

  const handleClick = (event) => {
    setAnchorEl(event.currentTarget);
  };
  const handleClose = () => {
    setAnchorEl(null);
  };


  const location = useLocation();

  useEffect(() => {

    fetchDataFromApi("/api/logo").then((res) => {
      localStorage.setItem('logo', res?.logo[0]?.logo)
    })


    setTimeout(() => {
      const token = localStorage.getItem('accessToken');

      if (token !== undefined && token !== null && token !== "") {
        const url = window.location.href
        history(location.pathname)
      } else {
        history("/login")
      }
    }, [1000])

  }, [context?.isLogin]);

  const logout = () => {
    setAnchorEl(null);

    fetchDataFromApi(`/api/user/logout?token=${localStorage.getItem('accessToken')}`, {
withCredentials: true }).then((res) => {
      if (res?.error === false) {
        context.setIsLogin(false);
        localStorage.removeItem("accessToken");
        localStorage.removeItem("refreshToken");
        context.setUserData(null);
        context?.setCartData([]);
        context?.setMyListData([]);
        history("/");
      }
```

```
    })

  }

  return (
    <>
      <header className="bg-white fixed lg:sticky left-0 w-full top-0 lg:-top-[47px] z-[101]">
        <div className="top-strip hidden lg:block py-2 border-t-[1px] border-gray-250  border-b-
[1px]">
          <div className="container">
            <div className="flex items-center justify-between">
              <div className="col1 w-[50%] hidden lg:block">
                <p className="text-[12px] font-[500] mt-0 mb-0">
                  Obtenga hasta un 50 % de descuento en productos de remate, solo por tiempo
limitado
                </p>
              </div>

              <div className="col2 flex items-center justify-between w-full lg:w-[50%] lg:justify-
end">
                <ul className="flex items-center gap-3 w-full justify-between lg:w-[200px]">
                  <li className="list-none">
                    <Link
                      to="/help-center"
                      className="text-[11px] lg:text-[13px] link font-[500] transition"
                    >
                      Ayuda{" "}
                    </Link>
                  </li>
                  <li className="list-none">
                    <Link
                      to="/order-tracking"
                      className="text-[11px] lg:text-[13px] link font-[500] transition"
                    >
                      Seguimiento
                    </Link>
                  </li>
                </ul>
              </div>
            </div>
          </div>
        </div>

        <div className="header py-2 lg:py-4 border-b-[1px] border-gray-250">
          <div className="container flex items-center justify-between">
            {
              context?.windowWidth < 992 &&
              <Button className="!w-[35px] !min-w-[35px] !h-[35px] !rounded-full !text-gray-800"
onClick={() => setIsOpenCatPanel(true)}><HiOutlineMenu size={22} /></Button>
            }

            <div className="col1 w-[40%] lg:w-[25%]">
              <Link to={"/"}>
                <img src={localStorage.getItem('logo')} className="max-w-[140px] lg:max-w-[200px]"
/>
              </Link>
            </div>

            <div className={`col2 fixed top-0 left-0 w-full h-full lg:w-[40%] lg:static p-2 lg:p-0
bg-white z-50 ${context?.windowWidth > 992 && '!block'} ${context?.openSearchPanel === true ?
'block' : 'hidden'}`}>
              <Search />
            </div>

            <div className="col3 w-[10%] lg:w-[30%] flex items-center pl-7">
              <ul className="flex items-center justify-end gap-0 lg:gap-3 w-full">
                {context.isLogin === false && context?.windowWidth > 992 ? (
                  <li className="list-none">
                    <Link
```

```
                    to="/login"
                    className="link transition text-[15px] font-[500]"
                  >
                    Iniciar sesión
                  </Link>{" "}
                  |  
                  <Link
                    to="/register"
                    className="link  transition text-[15px]  font-[500]"
                  >
                    Crear cuenta
                  </Link>
                </li>
              ) : (
                <>
                  {
                    context?.windowWidth > 992 &&
                    <li>
                      <Button
                        className="!text-[#000] myAccountWrap flex items-center gap-3 cursor-
pointer"
                        onClick={handleClick}
                      >
                        <div className="!w-[40px] !h-[40px] !min-w-[40px] !rounded-full !bg-gray-
200 flex items-center justify-center">
                          <FaRegUser className="text-[17px] text-[rgba(0,0,0,0.7)]" />
                        </div>

                        {context?.windowWidth > 992 && (
                          <div className="info flex flex-col">
                            <h4 className="leading-3 text-[14px] text-[rgba(0,0,0,0.6)] font-
[500] mb-0 capitalize text-left justify-start">
                              {context?.userData?.name}
                            </h4>
                            <span className="text-[13px] text-[rgba(0,0,0,0.6)]  font-[400]
capitalize text-left justify-start">
                              {context?.userData?.email}
                            </span>
                          </div>
                        )}
                      </Button>


                      <Menu
                        anchorEl={anchorEl}
                        id="account-menu"
                        open={open}
                        onClose={handleClose}
                        onClick={handleClose}
                        slotProps={{
                          paper: {
                            elevation: 0,
                            sx: {
                              overflow: "visible",
                              filter: "drop-shadow(0px 2px 8px rgba(0,0,0,0.32))",
                              mt: 1.5,
                              "& .MuiAvatar-root": {
                                width: 32,
                                height: 32,
                                ml: -0.5,
                                mr: 1,
                              },
                              "&::before": {
                                content: '""',
                                display: "block",
                                position: "absolute",
                                top: 0,
                                right: 14,
                                width: 10,
```

```
                    height: 10,
                    bgcolor: "background.paper",
                    transform: "translateY(-50%) rotate(45deg)",
                    zIndex: 0,
                  },
                },
              },
            }}
            transformOrigin={{ horizontal: "right", vertical: "top" }}
            anchorOrigin={{ horizontal: "right", vertical: "bottom" }}
          >
            <Link to="/my-account" className="w-full block">
              <MenuItem
                onClick={handleClose}
                className="flex gap-2 ! !py-2"
              >
                <FaRegUser className="text-[18px]" />{" "}
                <span className="text-[14px]">Mi cuenta</span>
              </MenuItem>
            </Link>
            <Link to="/address" className="w-full block">
              <MenuItem
                onClick={handleClose}
                className="flex gap-2 ! !py-2"
              >
                <LuMapPin className="text-[18px]" />{" "}
                <span className="text-[14px]">Dirección</span>
              </MenuItem>
            </Link>
            <Link to="/my-orders" className="w-full block">
              <MenuItem
                onClick={handleClose}
                className="flex gap-2 ! !py-2"
              >
                <IoBagCheckOutline className="text-[18px]" />{" "}
                <span className="text-[14px]">Pedidos</span>
              </MenuItem>
            </Link>
            <Link to="/my-list" className="w-full block">
              <MenuItem
                onClick={handleClose}
                className="flex gap-2 ! !py-2"
              >
                <IoMdHeartEmpty className="text-[18px]" />{" "}
                <span className="text-[14px]">Lista de deseos</span>
              </MenuItem>
            </Link>

            <MenuItem
              onClick={logout}
              className="flex gap-2 ! !py-2"
            >
              <IoIosLogOut className="text-[18px]" />{" "}
              <span className="text-[14px]">Cerrar Sesión</span>
            </MenuItem>
          </Menu>
        </li>
      }

    </>
  )}


  {
    context?.windowWidth > 992 &&
    <li>
      <Tooltip title="Wishlist">
        <Link to="/my-list">
          <IconButton aria-label="cart">
```

```
                          <StyledBadge badgeContent={context?.myListData?.length !== 0 ?
context?.myListData?.length : 0} color="secondary">
                            <FaRegHeart />
                          </StyledBadge>
                        </IconButton>
                      </Link>
                    </Tooltip>
                  </li>

                }


                <li>
                  <Tooltip title="Cart">
                    <IconButton
                      aria-label="cart"
                      onClick={() => context.setOpenCartPanel(true)}
                    >

                      <StyledBadge badgeContent={context?.cartData?.length !== 0 ?
context?.cartData?.length : 0} color="secondary">
                        <MdOutlineShoppingCart />
                      </StyledBadge>
                    </IconButton>
                  </Tooltip>
                </li>
              </ul>
            </div>
          </div>
        </div>

        <Navigation isOpenCatPanel={isOpenCatPanel} setIsOpenCatPanel={setIsOpenCatPanel} />
      </header>


      <div className="afterHeader mt-[115px] lg:mt-0"></div>

    </>
  );
};

export default Header;
```

1.3.2.12 HomeCatSlider

1.3.2.12.1 index.jsx

```
import React, { useContext } from "react";
import { Swiper, SwiperSlide } from "swiper/react";
import "swiper/css";
import "swiper/css/navigation";
import "swiper/css/free-mode";

import { Navigation, FreeMode } from "swiper/modules";
import { Link } from "react-router-dom";
import { MyContext } from "../../App";

const HomeCatSlider = (props) => {
  const context = useContext(MyContext);

  return (
    <div className="homeCatSlider pt-0 lg:pt-4 py-4 lg:py-8">
      <div className="container">
        <Swiper
          slidesPerView={8}
          spaceBetween={10}
          navigation={context?.windowWidth < 992 ? false : true}
          modules={[Navigation, FreeMode]}
          freeMode={true}
```

```
          breakpoints={{
            300: {
              slidesPerView: 4,
              spaceBetween: 5,
            },
            550: {
              slidesPerView: 5,
              spaceBetween: 5,
            },
            900: {
              slidesPerView: 5,
              spaceBetween: 5,
            },
            1100: {
              slidesPerView: 8,
              spaceBetween: 5,
            },
          }}
          className="mySwiper"
        >
          {(props?.data || []).map((cat, index) => {
            const key =
              cat?._id ||
              cat?.id ||
              cat?.slug ||
              `${cat?.name || "cat"}-${index}`;

            return (
              <SwiperSlide key={key}>
                <Link to="/">
                  <div className="item py-4 lg:py-7 px-3 bg-white rounded-sm text-center flex
items-center justify-center flex-col">
                    <img
                      src={cat?.images?.[0]}
                      className="w-[40px] lg:w-[60px] transition-all"
                      alt={cat?.name || "category"}
                      loading="lazy"
                    />
                    <h3 className="text-[12px] lg:text-[15px] font-[500] mt-3">
                      {cat?.name}
                    </h3>
                  </div>
                </Link>
              </SwiperSlide>
            );
          })}
        </Swiper>
      </div>
    </div>
  );
};

export default HomeCatSlider;
```

1.3.2.13 HomeSlider

1.3.2.13.1 index.jsx

```
import React, { useContext } from "react";
import { Swiper, SwiperSlide } from "swiper/react";
import "swiper/css";
import "swiper/css/navigation";

import { Navigation, Autoplay } from "swiper/modules";
import { MyContext } from "../../App";

const HomeSlider = (props) => {
  const context = useContext(MyContext);
```

```
  // Normaliza y revierte solo si hay data
  const slides = Array.isArray(props?.data) ? props.data.slice().reverse() : [];
  const slidesCount = slides.length;

  // ✅ Solo activa loop/autoplay si hay al menos 2 slides
  const canLoop = slidesCount > 1;
  const autoplay = canLoop
    ? { delay: 2500, disableOnInteraction: false }
    : false;

  return (
    <div className="homeSlider pb-3 pt-3 lg:pb-5 lg:pt-5 relative z-[99]">
      <div className="container">
        <Swiper
          loop={canLoop}
          spaceBetween={10}
          navigation={context?.windowWidth < 992 ? false : true}
          modules={[Navigation, Autoplay]}
          autoplay={autoplay}
          className="sliderHome"
        >
          {slidesCount > 0 &&
            slides.map((item, index) => (
              <SwiperSlide key={index}>
                <div className="item rounded-[10px] overflow-hidden">
                  <img
                    src={item?.images?.[0]}
                    alt="Banner slide"
                    className="w-full"
                    loading="lazy"
                  />
                </div>
              </SwiperSlide>
            ))}
        </Swiper>
      </div>
    </div>
  );
};

export default HomeSlider;
```

1.3.2.14 HomeSliderV2

1.3.2.14.1 index.jsx

```
import React, { useContext } from "react";
import { Swiper, SwiperSlide } from "swiper/react";
// Import Swiper styles
import "swiper/css";
import "swiper/css/effect-fade";
import "swiper/css/navigation";
import "swiper/css/pagination";

// import required modules
import { EffectFade, Navigation, Pagination, Autoplay } from "swiper/modules";
import Button from "@mui/material/Button";
import { Link } from "react-router-dom";
import { MyContext } from "../../App";
import { formatPrice } from "../../utils/formatPrice"; // 👈 NUEVO

const HomeBannerV2 = (props) => {
  const context = useContext(MyContext);

  // normalizamos y filtramos solo items válidos
  const slides = Array.isArray(props?.data)
    ? props.data.filter(
      (item) => item?.isDisplayOnHomeBanner === true && item?.bannerimages?.length > 0
    )
```

```
    : [];

  const slidesCount = slides.length;

  // ✅ loop y autoplay solo si hay más de 1 slide
  const canLoop = slidesCount > 1;
  const autoplay = canLoop
    ? { delay: 2500, disableOnInteraction: false }
    : false;

  return (
    <Swiper
      loop={canLoop}
      slidesPerView={1}
      spaceBetween={30}
      effect="fade"
      navigation={context?.windowWidth < 992 ? false : true}
      pagination={{ clickable: true }}
      autoplay={autoplay}
      modules={[EffectFade, Navigation, Pagination, Autoplay]}
      className="homeSliderV2"
    >
      {slides.map((item, index) => (
        <SwiperSlide key={index}>
          <div className="item w-full rounded-md overflow-hidden relative">
            <img src={item?.bannerimages[0]} className="w-full" loading="lazy" />

            <div className="info absolute top-0 -right-[100%] opacity-0 w-[50%] h-[100%] z-50 p-8
flex items-center flex-col justify-center transition-all duration-700">
              <h4 className="text-[12px] lg:text-[18px] font-[500] w-full text-left mb-3 relative -
right-[100%] opacity-0 hidden lg:block">
                {item?.bannerTitleName}
              </h4>

              {context?.windowWidth < 992 && (
                <h2 className="text-[15px] lg:text-[30px] font-[700] w-full relative -right-[100%]
opacity-0">
                  {item?.name?.length > 30 ? item?.name.substr(0, 30) + "..." : item?.name}
                </h2>
              )}

              {context?.windowWidth > 992 && (
                <h2 className="text-[16px] sm:text-[20px] md:text-[25px] lg:text-[30px] font-[700]
w-full relative -right-[100%] opacity-0">
                  {item?.name?.length > 70 ? item?.name.substr(0, 70) + "..." : item?.name}
                </h2>
              )}

              <h3 className="flex items-center gap-0 lg:gap-3 text-[12px] lg:text-[18px] font-[500]
w-full text-left mt-3 mb-0 lg:mb-3 relative -right-[100%] opacity-0 flex-col lg:flex-row">
                <span className="w-full lg:w-max hidden lg:block">A partir de sólo</span>{" "}
                <span className="text-primary text-[16px] lg:text-[30px] font-[700] block lg:inline
w-full lg:w-max">
                  {formatPrice(Number(item?.priceBob ?? item?.price ?? 0), "BOB")}
                </span>
              </h3>

              <div className="w-full relative -right-[100%] opacity-0 btn_">
                <Link to={`/product/${item?._id}`}>
                  <Button className="btn btn-org">COMPRAR AHORA</Button>
                </Link>
              </div>
            </div>
          </div>
        </SwiperSlide>
      ))}
    </Swiper>
  );
};
```

```
export default HomeBannerV2;
```

1.3.2.15 LoadingSkeleton

1.3.2.15.1 bannerLoading.jsx

```
import React from 'react'

const BannerLoading = () => {
    return (
        <div className="homeSlider pb-2 pt-3 lg:pb-5 lg:pt-5 top-0 left-0 z-50 w-full">
            <div className="container">
                <div className="flex items-center gap-2 animate-pulse relative w-full">
                    <img src="/homeBannerPlaceholder.jpg" className='opacity-0' />
                    <div className="flex items-center mb-3 justify-center w-full h-full bg-gray-300
rounded-lg  dark:bg-gray-700 absolute top-0 left-0 z-50">
                        <svg className="w-10 h-10 lg:w-20 lg:h-20 text-gray-400 dark:text-gray-600"
aria-hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                            <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-2V2a2 2
0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0 0 1-
.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                        </svg>
                    </div>
                </div>
            </div>
        </div>
    )
}


export default BannerLoading;
```

1.3.2.16 OtpBox

1.3.2.16.1 index.jsx

```
import React, { useState } from "react";

const OtpBox = ({ length, onChange }) => {
  const [otp, setOtp] = useState(new Array(length).fill(""));

  const handleChange = (element, index) => {
    const value = element.value;
    if (isNaN(value)) return; // Only numbers allowed

    // Update OTP value
    const newOtp = [...otp];
    newOtp[index] = value;
    setOtp(newOtp);
    onChange(newOtp.join(""));

    // Focus on next input
    if (value && index < length - 1) {
      document.getElementById(`otp-input-${index + 1}`).focus();
    }
  };

  const handleKeyDown = (event, index) => {
    if (event.key === "Backspace" && !otp[index] && index > 0) {
      document.getElementById(`otp-input-${index - 1}`).focus();
    }
  };

  return (
    <div style={{ display: "flex", gap: "5px", justifyContent:'center' }} className="otpBox">
      {otp.map((data, index) => (
        <input
```

```
          key={index}
          id={`otp-input-${index}`}
          type="text"
          maxLength="1"
          value={otp[index]}
          onChange={(e) => handleChange(e.target, index)}
          onKeyDown={(e) => handleKeyDown(e, index)}
          className="w-[35px] h-[35px] sm:w-[45px] sm:h-[45px] text-center text-[17px]"
        />
      ))}
    </div>
  );
};

export default OtpBox;
```

1.3.2.17 ProductDetails

1.3.2.17.1 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import Button from "@mui/material/Button";
import { QtyBox } from "../QtyBox";
import Rating from "@mui/material/Rating";
import { MdOutlineShoppingCart } from "react-icons/md";
import { FaRegHeart } from "react-icons/fa";
import { IoGitCompareOutline } from "react-icons/io5";
import { MyContext } from "../../App";
import CircularProgress from '@mui/material/CircularProgress';
import { postData } from "../../utils/api";
import { FaCheckDouble } from "react-icons/fa";
import { IoMdHeart } from "react-icons/io";

// 👇 formateador para mostrar BOB
import { formatPrice } from "../../utils/formatPrice";

export const ProductDetailsComponent = (props) => {
  const [productActionIndex, setProductActionIndex] = useState(null);
  const [quantity, setQuantity] = useState(1);
  const [selectedTabName, setSelectedTabName] = useState(null);
  const [isLoading, setIsLoading] = useState(false);
  const [tabError, setTabError] = useState(false);
  const [isAdded, setIsAdded] = useState(false);
  const [isAddedInMyList, setIsAddedInMyList] = useState(false);

  const context = useContext(MyContext);

  // 👇 Precio principal SIEMPRE en BOB (fallback si aún no llega del backend)
  const priceBob =
    props?.item?.priceBob != null ? props.item.priceBob : props?.item?.price;
  const oldPriceBob =
    props?.item?.oldPriceBob != null
      ? props.item.oldPriceBob
      : props?.item?.oldPrice;

  const handleSelecteQty = (qty) => {
    setQuantity(qty);
  };

  const handleClickActiveTab = (index, name) => {
    setProductActionIndex(index);
    setSelectedTabName(name);
    setTabError(false);
  };

  // 👇 Ajuste leve: observa cambios reales del carrito
  useEffect(() => {
    const item = context?.cartData?.filter((cartItem) =>
```

```
    cartItem.productId.includes(props?.item?._id)
  );
  setIsAdded(item?.length > 0);
}, [context?.cartData, props?.item?._id]);

useEffect(() => {
  const myListItem = context?.myListData?.filter((item) =>
    item.productId.includes(props?.item?._id)
  );
  setIsAddedInMyList(myListItem?.length > 0);
}, [context?.myListData, props?.item?._id]);

const addToCart = (product, userId, quantity) => {
  if (userId === undefined) {
    context?.alertBox("error", "No has iniciado sesión, por favor inicia sesión primero");
    return false;
  }

  const productItem = {
    _id: product?._id,
    productTitle: product?.name,
    image: product?.images?.[0],
    rating: product?.rating,
    // 👇 guardar precio en BOB en todo el flujo
    price: priceBob,
    oldPrice: oldPriceBob,
    discount: product?.discount,
    quantity: quantity,
    subTotal: parseInt((priceBob || 0) * quantity),
    productId: product?._id,
    countInStock: product?.countInStock,
    brand: product?.brand,
    size: props?.item?.size?.length !== 0 ? selectedTabName : "",
    weight: props?.item?.productWeight?.length !== 0 ? selectedTabName : "",
    ram: props?.item?.productRam?.length !== 0 ? selectedTabName : "",
  };

  const requiereTab =
    (props?.item?.size?.length ?? 0) !== 0 ||
    (props?.item?.productWeight?.length ?? 0) !== 0 ||
    (props?.item?.productRam?.length ?? 0) !== 0;

  if (requiereTab && !selectedTabName) {
    setTabError(true);
    return;
  }

  setIsLoading(true);
  postData("/api/cart/add", productItem).then((res) => {
    if (res?.error === false) {
      context?.alertBox("success", res?.message);
      context?.getCartItems();
      setTimeout(() => {
        setIsLoading(false);
        setIsAdded(true);
      }, 500);
    } else {
      context?.alertBox("error", res?.message);
      setTimeout(() => {
        setIsLoading(false);
      }, 500);
    }
  });
};

const handleAddToMyList = (item) => {
  if (context?.userData === null) {
    context?.alertBox("error", "No has iniciado sesión, por favor inicia sesión primero");
    return false;
```

```
    } else {
      const obj = {
        productId: item?._id,
        userId: context?.userData?._id,
        productTitle: item?.name,
        image: item?.images?.[0],
        rating: item?.rating,
        // 👇 referencia en BOB
        price: priceBob,
        oldPrice: oldPriceBob,
        brand: item?.brand,
        discount: item?.discount,
      };

      postData("/api/myList/add", obj).then((res) => {
        if (res?.error === false) {
          context?.alertBox("success", res?.message);
          setIsAddedInMyList(true);
          context?.getMyListData();
        } else {
          context?.alertBox("error", res?.message);
        }
      });
    }
  };

  return (
    <>
      <h1 className="text-[18px] sm:text-[22px] font-[600] mb-2">
        {props?.item?.name}
      </h1>

      <div className="flex items-start sm:items-center lg:items-center flex-col sm:flex-row
md:flex-row lg:flex-row gap-3 justify-start">
        <span className="text-gray-400 text-[13px]">
          Marca:{" "}
          <span className="font-[500] text-black opacity-75">
            {props?.item?.brand}
          </span>
        </span>

        <Rating
          name="size-small"
          value={props?.item?.rating}
          size="small"
          readOnly
        />
        <span
          className="text-[13px] cursor-pointer"
          onClick={props.gotoReviews}
        >
          Reseñas ({props.reviewsCount})
        </span>
      </div>

      <div className="flex flex-col sm:flex-row md:flex-row lg:flex-row items-start sm:items-center
gap-4 mt-4">
        <div className="flex items-center gap-4">
          <span className="oldPrice line-through text-gray-500 text-[20px] font-[500]">
            {oldPriceBob ? formatPrice(oldPriceBob, "BOB") : ""}
          </span>
          <span className="price text-primary text-[20px] font-[600]">
            {formatPrice(priceBob, "BOB")}
          </span>
        </div>

        <div className="flex items-center gap-4">
          <span className="text-[14px]">
            Disponible en stock:{" "}
```

```
            <span className="text-green-600 text-[14px] font-bold">
              {props?.item?.countInStock} ítems
            </span>
          </span>
        </div>
      </div>

      <p className="mt-3 pr-10 mb-5">{props?.item?.description}</p>

      {/* Opciones (RAM / SIZE / WEIGHT) */}
      {props?.item?.productRam?.length !== 0 && (
        <div className="flex items-center gap-3">
          <span className="text-[16px]">RAM:</span>
          <div className="flex items-center gap-1 actions">
            {props?.item?.productRam?.map((item, index) => {
              return (
                <Button
                  key={index}
                  className={`${productActionIndex === index ? "!bg-primary !text-white" : ""}
${tabError === true && !selectedTabName ? "error" : ""
                    }`}
                  onClick={() => handleClickActiveTab(index, item)}
                >
                  {item}
                </Button>
              );
            })}
          </div>
        </div>
      )}

      {props?.item?.size?.length !== 0 && (
        <div className="flex items-center gap-3">
          <span className="text-[16px]">TALLA:</span>
          <div className="flex items-center gap-1 actions">
            {props?.item?.size?.map((item, index) => {
              return (
                <Button
                  key={index}
                  className={`${productActionIndex === index ? "!bg-primary !text-white" : ""}
${tabError === true && !selectedTabName ? "error" : ""
                    }`}
                  onClick={() => handleClickActiveTab(index, item)}
                >
                  {item}
                </Button>
              );
            })}
          </div>
        </div>
      )}

      {props?.item?.productWeight?.length !== 0 && (
        <div className="flex items-center gap-3">
          <span className="text-[16px]">PESO:</span>
          <div className="flex items-center gap-1 actions">
            {props?.item?.productWeight?.map((item, index) => {
              return (
                <Button
                  key={index}
                  className={`${productActionIndex === index ? "!bg-primary !text-white" : ""}
${tabError === true && !selectedTabName ? "error" : ""
                    }`}
                  onClick={() => handleClickActiveTab(index, item)}
                >
                  {item}
                </Button>
              );
            })}
```

```
          </div>
        </div>
      )}

      <p className="text-[14px] mt-5 mb-2 text-[#000]">
        Envío gratis (Tiempo de entrega estimado 2-3 días)
      </p>

      <div className="flex items-center gap-4 py-4">
        <div className="qtyBoxWrapper w-[70px]">
          <QtyBox handleSelecteQty={handleSelecteQty} />
        </div>

        <Button
          className="btn-org flex gap-2 !min-w-[150px]"
          onClick={() => addToCart(props?.item, context?.userData?._id, quantity)}
        >
          {isLoading === true ? (
            <CircularProgress />
          ) : (
            <>
              {isAdded === true ? (
                <>
                  <FaCheckDouble /> Agregado
                </>
              ) : (
                <>
                  <MdOutlineShoppingCart className="text-[22px]" /> Agregar al carrito
                </>
              )}
            </>
          )}
        </Button>
      </div>

      <div className="flex items-center gap-4 mt-4">
        <span
          className="flex items-center gap-2 text-[14px] sm:text-[15px] link cursor-pointer font-
[500]"
          onClick={() => handleAddToMyList(props?.item)}
        >
          {isAddedInMyList === true ? (
            <IoMdHeart className="text-[18px] !text-primary group-hover:text-white hover:!text-
white" />
          ) : (
            <FaRegHeart className="text-[18px] !text-black group-hover:text-white hover:!text-
white" />
          )}
          Agregar a la lista de deseos
        </span>

        <span className="flex items-center gap-2 text-[14px] sm:text-[15px] link cursor-pointer
font-[500]">
          <IoGitCompareOutline className="text-[18px]" /> Agregar para comparar
        </span>
      </div>
    </>
  );
};
```

1.3.2.18 ProductItem

1.3.2.18.1 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import "../ProductItem/style.css";
import { Link } from "react-router-dom";
import Rating from "@mui/material/Rating";
```

```
import Button from "@mui/material/Button";
import { FaRegHeart } from "react-icons/fa";
import { IoGitCompareOutline } from "react-icons/io5";
import { MdZoomOutMap } from "react-icons/md";
import { MyContext } from "../../App";
import { MdOutlineShoppingCart } from "react-icons/md";
import { FaMinus } from "react-icons/fa6";
import { FaPlus } from "react-icons/fa6";
import { deleteData, editData, postData } from "../../utils/api";
import CircularProgress from '@mui/material/CircularProgress';
import { MdClose } from "react-icons/md";
import { IoMdHeart } from "react-icons/io";

// 👇 nuevo: formateador de precio BOB
import { formatPrice } from "../../utils/formatPrice";

const ProductItem = (props) => {
  const [quantity, setQuantity] = useState(1);
  const [isAdded, setIsAdded] = useState(false);
  const [isAddedInMyList, setIsAddedInMyList] = useState(false);
  const [cartItem, setCartItem] = useState([]);

  const [activeTab, setActiveTab] = useState(null);
  const [isShowTabs, setIsShowTabs] = useState(false);
  const [selectedTabName, setSelectedTabName] = useState(null);
  const [isLoading, setIsLoading] = useState(false);

  const context = useContext(MyContext);

  // 👇 precio principal SIEMPRE en BOB (fallback a .price si aún no llega .priceBob)
  const priceBob =
    props?.item?.priceBob != null ? props.item.priceBob : props?.item?.price;

  const oldPriceBob =
    props?.item?.oldPriceBob != null
      ? props.item.oldPriceBob
      : props?.item?.oldPrice;

  const addToCart = (product, userId, quantity) => {
    const productItem = {
      _id: product?._id,
      name: product?.name,
      image: product?.images?.[0],
      rating: product?.rating,
      // 👇 guardamos precio en BOB para todo el flujo del carrito
      price: priceBob,
      oldPrice: oldPriceBob,
      discount: product?.discount,
      quantity: quantity,
      subTotal: parseInt((priceBob || 0) * quantity),
      productId: product?._id,
      countInStock: product?.countInStock,
      brand: product?.brand,
      size: props?.item?.size?.length !== 0 ? selectedTabName : "",
      weight: props?.item?.productWeight?.length !== 0 ? selectedTabName : "",
      ram: props?.item?.productRam?.length !== 0 ? selectedTabName : "",
    };

    setIsLoading(true);

    if (
      props?.item?.size?.length !== 0 ||
      props?.item?.productRam?.length !== 0 ||
      props?.item?.productWeight?.length !== 0
    ) {
      setIsShowTabs(true);
    } else {
      setIsAdded(true);
      setIsShowTabs(false);
```

```
    setTimeout(() => {
      setIsLoading(false);
    }, 500);
    context?.addToCart(productItem, userId, quantity);
  }

  if (activeTab !== null) {
    context?.addToCart(productItem, userId, quantity);
    setIsAdded(true);
    setIsShowTabs(false);
    setTimeout(() => {
      setIsLoading(false);
    }, 500);
  }
};

const handleClickActiveTab = (index, name) => {
  setActiveTab(index);
  setSelectedTabName(name);
};

useEffect(() => {
  const item = context?.cartData?.filter((cartItem) =>
    cartItem.productId.includes(props?.item?._id)
  );

  const myListItem = context?.myListData?.filter((item) =>
    item.productId.includes(props?.item?._id)
  );

  if (item?.length !== 0) {
    setCartItem(item);
    setIsAdded(true);
    setQuantity(item[0]?.quantity);
  } else {
    setQuantity(1);
  }

  if (myListItem?.length !== 0) {
    setIsAddedInMyList(true);
  } else {
    setIsAddedInMyList(false);
  }
}, [context?.cartData]);

const minusQty = () => {
  if (quantity !== 1 && quantity > 1) {
    setQuantity(quantity - 1);
  } else {
    setQuantity(1);
  }

  if (quantity === 1) {
    deleteData(`/api/cart/delete-cart-item/${cartItem[0]?._id}`).then(
      (res) => {
        setIsAdded(false);
        context.alertBox("success", "Item Removed ");
        context?.getCartItems();
        setIsShowTabs(false);
        setActiveTab(null);
      }
    );
  } else {
    const obj = {
      _id: cartItem[0]?._id,
      qty: quantity - 1,
      // 👇 subTotal en BOB
      subTotal: (priceBob || 0) * (quantity - 1),
    };
```

```
      editData(`/api/cart/update-qty`, obj).then((res) => {
        context.alertBox("success", res?.data?.message);
        context?.getCartItems();
      });
    }
  };

  const addQty = () => {
    setQuantity(quantity + 1);

    const obj = {
      _id: cartItem[0]?._id,
      qty: quantity + 1,
      // 👇 subTotal en BOB
      subTotal: (priceBob || 0) * (quantity + 1),
    };

    editData(`/api/cart/update-qty`, obj).then((res) => {
      context.alertBox("success", res?.data?.message);
      context?.getCartItems();
    });
  };

  const handleAddToMyList = (item) => {
    if (context?.userData === null) {
      context?.alertBox("error", "you are not login please login first");
      return false;
    } else {
      const obj = {
        productId: item?._id,
        userId: context?.userData?._id,
        productTitle: item?.name,
        image: item?.images?.[0],
        rating: item?.rating,
        // 👇 guardamos referencia de precio en BOB
        price: priceBob,
        oldPrice: oldPriceBob,
        brand: item?.brand,
        discount: item?.discount,
      };

      postData("/api/myList/add", obj).then((res) => {
        if (res?.error === false) {
          context?.alertBox("success", res?.message);
          setIsAddedInMyList(true);
          context?.getMyListData();
        } else {
          context?.alertBox("error", res?.message);
        }
      });
    }
  };

  return (
    <div className="productItem shadow-lg rounded-md overflow-hidden border-1 border-
[rgba(0,0,0,0.1)]">
      <div className="group imgWrapper w-[100%]  overflow-hidden  rounded-md rounded-bl-none
rounded-br-none relative">
        <Link to={props?.item?.images?.[1]}>
          <div className="img h-[200px] overflow-hidden">
            <img src={props?.item?.images?.[0]} className="w-full" />
            {props?.item?.images?.length > 1 && (
              <img
                src={props?.item?.images?.[1]}
                className="w-full transition-all duration-700 absolute top-0 left-0 opacity-0
group-hover:opacity-100 group-hover:scale-105"
              />
            )}
```

```
          </div>
        </Link>

        {isShowTabs === true && (
          <div
            className="flex items-center justify-center absolute top-0 left-0 w-full h-full
      bg-[rgba(0,0,0,0.7)] z-[60] p-3 gap-2"
          >
            <Button
              className="!absolute top-[10px] right-[10px] !min-w-[30px] !min-h-[30px] !w-[30px]
!h-[30px] !rounded-full !bg-[rgba(255,255,255,1)] text-black"
              onClick={() => setIsShowTabs(false)}
            >
              <MdClose className=" text-black z-[90] text-[25px]" />
            </Button>

            {props?.item?.size?.length !== 0 &&
              props?.item?.size?.map((item, index) => {
                return (
                  <span
                    key={index}
                    className={`flex items-center justify-center p-1 px-2 bg-
[rgba(255,555,255,0.8)] max-w-[35px] h-[25px]
          rounded-sm cursor-pointer hover:bg-white
          ${activeTab === index && '!bg-primary text-white'}`}
                    onClick={() => handleClickActiveTab(index, item)}
                  >
                    {item}
                  </span>
                );
              })}

            {props?.item?.productRam?.length !== 0 &&
              props?.item?.productRam?.map((item, index) => {
                return (
                  <span
                    key={index}
                    className={`flex items-center justify-center p-1 px-2 bg-
[rgba(255,555,255,0.8)] max-w-[45px] h-[25px]
          rounded-sm cursor-pointer hover:bg-white
          ${activeTab === index && '!bg-primary text-white'}`}
                    onClick={() => handleClickActiveTab(index, item)}
                  >
                    {item}
                  </span>
                );
              })}

            {props?.item?.productWeight?.length !== 0 &&
              props?.item?.productWeight?.map((item, index) => {
                return (
                  <span
                    key={index}
                    className={`flex items-center justify-center p-1 px-2 bg-
[rgba(255,555,255,0.8)] max-w-[35px] h-[25px]
          rounded-sm cursor-pointer hover:bg-white
          ${activeTab === index && '!bg-primary text-white'}`}
                    onClick={() => handleClickActiveTab(index, item)}
                  >
                    {item}
                  </span>
                );
              })}
          </div>
        )}

        <span className="discount flex items-center absolute top-[10px] left-[10px] z-50 bg-primary
text-white rounded-lg p-1 text-[12px] font-[500]">
          {props?.item?.discount}%
```

```
        </span>

        <div className="actions absolute top-[-20px] right-[5px] z-50 flex items-center gap-2 flex-
col w-[50px] transition-all duration-300 group-hover:top-[15px] opacity-0 group-hover:opacity-100">
          <Button
            className="!w-[35px] !h-[35px] !min-w-[35px] !rounded-full !bg-white  text-black
hover:!bg-primary hover:text-white group"
            onClick={() =>
              context.handleOpenProductDetailsModal(true, props?.item)
            }
          >
            <MdZoomOutMap className="text-[18px] !text-black group-hover:text-white hover:!text-
white" />
          </Button>

          <Button className="!w-[35px] !h-[35px] !min-w-[35px] !rounded-full !bg-white  text-black
hover:!bg-primary hover:text-white group">
            <IoGitCompareOutline className="text-[18px] !text-black group-hover:text-white
hover:!text-white" />
          </Button>

          <Button
            className={`!w-[35px] !h-[35px] !min-w-[35px] !rounded-full !bg-white  text-black
hover:!bg-primary hover:text-white group`}
            onClick={() => handleAddToMyList(props?.item)}
          >
            {isAddedInMyList === true ? (
              <IoMdHeart className="text-[18px] !text-primary group-hover:text-white hover:!text-
white" />
            ) : (
              <FaRegHeart className="text-[18px] !text-black group-hover:text-white hover:!text-
white" />
            )}
          </Button>
        </div>
      </div>

      <div className="info p-3 py-5 relative pb-[50px] h-[190px]">
        <h6 className="text-[13px] !font-[400]">
          <span className="link transition-all">{props?.item?.brand}</span>
        </h6>
        <h3 className="text-[12px] lg:text-[13px] title mt-1 font-[500] mb-1 text-[#000]">
          <Link to={`/product/${props?.item?._id}`} className="link transition-all">
            {props?.item?.name?.substr(0, 25) + "..."}
          </Link>
        </h3>

        <Rating
          name="size-small"
          defaultValue={props?.item?.rating}
          size="small"
          readOnly
        />

        <div className="flex items-center gap-4 justify-between">
          <span className="oldPrice line-through text-gray-500 text-[12px] lg:text-[14px] font-
[500]">
            {oldPriceBob ? formatPrice(oldPriceBob, "BOB") : ""}
          </span>
          <span className="price text-primary text-[12px] lg:text-[14px]  font-[600]">
            {formatPrice(priceBob, "BOB")}
          </span>
        </div>

        <div className="!absolute bottom-[15px] left-0 pl-3 pr-3 w-full">
          {isAdded === false ? (
            <Button
              className="btn-org addToCartBtn btn-border flex w-full btn-sm gap-2 "
              size="small"
```

```
              onClick={() =>
                addToCart(props?.item, context?.userData?._id, quantity)
              }
            >
              <MdOutlineShoppingCart className="text-[18px]" /> Agregar al carrito
            </Button>
          ) : (
            <>
              {isLoading === true ? (
                <Button className="addtocart btn-org btn-border flex w-full btn-sm gap-2 "
size="small">
                  <CircularProgress />
                </Button>
              ) : (
                <div className="flex items-center justify-between overflow-hidden rounded-full
border border-[rgba(0,0,0,0.1)]">
                  <Button
                    className="!min-w-[35px] !w-[35px] !h-[30px] !bg-[#f1f1f1]  !rounded-none"
                    onClick={minusQty}
                  >
                    <FaMinus className="text-[rgba(0,0,0,0.7)]" />
                  </Button>
                  <span>{quantity}</span>
                  <Button
                    className="!min-w-[35px] !w-[35px] !h-[30px] !bg-gray-800 !rounded-none"
                    onClick={addQty}
                  >
                    <FaPlus className="text-white" />
                  </Button>
                </div>
              )}
            </>
          )}
        </div>
      </div>
    </div>
  );
};

export default ProductItem;
```

1.3.2.18.2 style.css

```
.productItem .title{line-height: 18px;}
.productItem .actions button:hover svg{color: #fff !important;}
.productItem .actions button svg{pointer-events:none !important;}
```

1.3.2.19 ProductItemListView

1.3.2.19.1 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import "../ProductItem/style.css";
import { Link } from "react-router-dom";
import Rating from "@mui/material/Rating";
import Button from "@mui/material/Button";
import { FaRegHeart } from "react-icons/fa";
import { IoGitCompareOutline } from "react-icons/io5";
import { MdZoomOutMap } from "react-icons/md";
import { MyContext } from "../../App";
import { MdOutlineShoppingCart } from "react-icons/md";
import { FaMinus } from "react-icons/fa6";
import { FaPlus } from "react-icons/fa6";
import { deleteData, editData, postData } from "../../utils/api";
import CircularProgress from '@mui/material/CircularProgress';
import { MdClose } from "react-icons/md";
```

```
import { IoMdHeart } from "react-icons/io";

// 👇 formateador para BOB
import { formatPrice } from "../../utils/formatPrice";

const ProductItem = (props) => {

  const [quantity, setQuantity] = useState(1);
  const [isAdded, setIsAdded] = useState(false);
  const [isAddedInMyList, setIsAddedInMyList] = useState(false);
  const [cartItem, setCartItem] = useState([]);

  const [activeTab, setActiveTab] = useState(null);
  const [isShowTabs, setIsShowTabs] = useState(false);
  const [selectedTabName, setSelectedTabName] = useState(null);
  const [isLoading, setIsLoading] = useState(false);

  const context = useContext(MyContext);

  // 👇 precio principal y oldPrice SIEMPRE en BOB (fallback a .price/.oldPrice)
  const priceBob = props?.item?.priceBob != null ? props.item.priceBob : props?.item?.price;
  const oldPriceBob = props?.item?.oldPriceBob != null ? props.item.oldPriceBob :
props?.item?.oldPrice;

  const addToCart = (product, userId, quantity) => {

    const productItem = {
      _id: product?._id,
      name: product?.name,
      image: product?.images[0],
      rating: product?.rating,
      // 👇 guardamos precio en BOB para todo el flujo
      price: priceBob,
      oldPrice: oldPriceBob,
      discount: product?.discount,
      quantity: quantity,
      subTotal: parseInt((priceBob || 0) * quantity),
      productId: product?._id,
      countInStock: product?.countInStock,
      brand: product?.brand,
      size: props?.item?.size?.length !== 0 ? selectedTabName : '',
      weight: props?.item?.productWeight?.length !== 0 ? selectedTabName : '',
      ram: props?.item?.productRam?.length !== 0 ? selectedTabName : ''
    }

    setIsLoading(true);

    if (props?.item?.size?.length !== 0 || props?.item?.productRam?.length !== 0 ||
props?.item?.productWeight?.length !== 0) {
      setIsShowTabs(true)
    } else {
      setIsAdded(true);
      setIsShowTabs(false);
      setTimeout(() => {
        setIsLoading(false);
      }, 500);
      context?.addToCart(productItem, userId, quantity);
    }

    if (activeTab !== null) {
      context?.addToCart(productItem, userId, quantity);
      setIsAdded(true);
      setIsShowTabs(false)
      setTimeout(() => {
        setIsLoading(false);
      }, 500);
    }
  }
```

```
const handleClickActiveTab = (index, name) => {
  setActiveTab(index)
  setSelectedTabName(name)
}

useEffect(() => {
  const item = context?.cartData?.filter((cartItem) =>
    cartItem.productId.includes(props?.item?._id)
  )

  const myListItem = context?.myListData?.filter((item) =>
    item.productId.includes(props?.item?._id)
  )

  if (item?.length !== 0) {
    setCartItem(item)
    setIsAdded(true);
    setQuantity(item[0]?.quantity)
  } else {
    setQuantity(1)
  }

  if (myListItem?.length !== 0) {
    setIsAddedInMyList(true);
  } else {
    setIsAddedInMyList(false)
  }

}, [context?.cartData]);

const minusQty = () => {
  if (quantity !== 1 && quantity > 1) {
    setQuantity(quantity - 1)
  } else {
    setQuantity(1)
  }

  if (quantity === 1) {
    deleteData(`/api/cart/delete-cart-item/${cartItem[0]?._id}`).then((res) => {
      setIsAdded(false);
      context.alertBox("success", "Item Removed ");
      context?.getCartItems();
      setIsShowTabs(false);
      setActiveTab(null);
    })
  } else {
    const obj = {
      _id: cartItem[0]?._id,
      qty: quantity - 1,
      // 👇 subTotal en BOB
      subTotal: (priceBob || 0) * (quantity - 1)
    }

    editData(`/api/cart/update-qty`, obj).then((res) => {
      context.alertBox("success", res?.data?.message);
      context?.getCartItems();
    })
  }
}

const addQty = () => {
  setQuantity(quantity + 1);

  const obj = {
    _id: cartItem[0]?._id,
    qty: quantity + 1,
    // 👇 subTotal en BOB
    subTotal: (priceBob || 0) * (quantity + 1)
  }
```

```
    editData(`/api/cart/update-qty`, obj).then((res) => {
      context.alertBox("success", res?.data?.message);
      context?.getCartItems();
    })
  }

  const handleAddToMyList = (item) => {
    if (context?.userData === null) {
      context?.alertBox("error", "you are not login please login first");
      return false
    }
    else {
      const obj = {
        productId: item?._id,
        userId: context?.userData?._id,
        productTitle: item?.name,
        image: item?.images[0],
        rating: item?.rating,
        // 👇 referencia de precio en BOB
        price: priceBob,
        oldPrice: oldPriceBob,
        brand: item?.brand,
        discount: item?.discount
      }

      postData("/api/myList/add", obj).then((res) => {
        if (res?.error === false) {
          context?.alertBox("success", res?.message);
          setIsAddedInMyList(true);
          context?.getMyListData();
        } else {
          context?.alertBox("error", res?.message);
        }
      })
    }
  }

  return (
    <div className="productItem p-4 shadow-md bg-[#f1f1f1] rounded-md overflow-hidden border-1
border-[rgba(0,0,0,0.1)] flex items-center flex-col lg:flex-row">
      <div className="group imgWrapper w-full lg:w-[25%]  overflow-hidden  rounded-md relative">
        <Link to={`/product/${props?.item?._id}`}>
          <div className="img  overflow-hidden">
            <img
              src={props?.item?.images[0]}
              className="w-full"
            />

            {
              props?.item?.images?.length > 1 &&
              <img
                src={`${API_URL}/download/${props?.item?.images[1]}`}
                className="w-full transition-all duration-700 absolute top-0 left-0 opacity-0
group-hover:opacity-100 group-hover:scale-105"
              />
            }

          </div>
        </Link>

        {
          isShowTabs === true &&
          <div className="flex items-center justify-center absolute top-0 left-0 w-full h-full
      bg-[rgba(0,0,0,0.7)] z-[60] p-3 gap-2">

            <Button className="!absolute top-[10px] right-[10px] !min-w-[30px] !min-h-[30px] !w-
[30px] !h-[30px] !rounded-full !bg-[rgba(255,255,255,1)] text-black"
              onClick={() => setIsShowTabs(false)}
```

```
            > <MdClose className=" text-black z-[90] text-[25px]" /></Button>

            {
              props?.item?.size?.length !== 0 && props?.item?.size?.map((item, index) => {
                return (
                  <span key={index} className={`flex items-center justify-center p-1 px-2 bg-
[rgba(255,555,255,0.8)] max-w-[35px] h-[25px]
          rounded-sm cursor-pointer hover:bg-white
          ${activeTab === index && '!bg-primary text-white'}`}
                    onClick={() => handleClickActiveTab(index, item)}
                  >{item}
                  </span>)
              })
            }

            {
              props?.item?.productRam?.length !== 0 && props?.item?.productRam?.map((item, index)
=> {
                return (
                  <span key={index} className={`flex items-center justify-center p-1 px-2 bg-
[rgba(255,555,255,0.8)] max-w-[45px] h-[25px]
          rounded-sm cursor-pointer hover:bg-white
          ${activeTab === index && '!bg-primary text-white'}`}
                    onClick={() => handleClickActiveTab(index, item)}
                  >{item}
                  </span>)
              })
            }

            {
              props?.item?.productWeight?.length !== 0 && props?.item?.productWeight?.map((item,
index) => {
                return (
                  <span key={index} className={`flex items-center justify-center p-1 px-2 bg-
[rgba(255,555,255,0.8)] max-w-[35px] h-[25px]
          rounded-sm cursor-pointer hover:bg-white
          ${activeTab === index && '!bg-primary text-white'}`}
                    onClick={() => handleClickActiveTab(index, item)}
                  >{item}
                  </span>)
              })
            }

          </div>
        }

        <span className="discount flex items-center absolute top-[10px] left-[10px] z-50 bg-primary
text-white rounded-lg p-1 text-[12px] font-[500]">
          {props?.item?.discount}%
        </span>

        <div className="actions absolute top-[-20px] right-[5px] z-50 flex items-center gap-2 flex-
col w-[50px] transition-all duration-300 group-hover:top-[15px] opacity-0 group-hover:opacity-100">

          <Button className="!w-[35px] !h-[35px] !min-w-[35px] !rounded-full !bg-white  text-black
hover:!bg-primary hover:text-white group" onClick={() =>
context.handleOpenProductDetailsModal(true, props?.item)}>
            <MdZoomOutMap className="text-[18px] !text-black group-hover:text-white hover:!text-
white" />
          </Button>

          <Button className="!w-[35px] !h-[35px] !min-w-[35px] !rounded-full !bg-white  text-black
hover:!bg-primary hover:text-white group">
            <IoGitCompareOutline className="text-[18px] !text-black group-hover:text-white
hover:!text-white" />
          </Button>

          <Button className={`!w-[35px] !h-[35px] !min-w-[35px] !rounded-full !bg-white  text-black
hover:!bg-primary hover:text-white group`}
```

```
            onClick={() => handleAddToMyList(props?.item)}
          >
            {
              isAddedInMyList === true ? <IoMdHeart className="text-[18px] !text-primary group-
hover:text-white hover:!text-white" /> :
                <FaRegHeart className="text-[18px] !text-black group-hover:text-white hover:!text-
white" />

            }

          </Button>
        </div>
      </div>

      <div className="info p-3 py-5 pb-0 px-3 lg:px-8  w-full lg:w-[75%]">
        <h6 className="text-[15px] !font-[400]">
          <Link to="/" className="link transition-all">
            {props?.item?.brand}
          </Link>
        </h6>
        <h3 className="text-[18px] title mt-3 font-[500] mb-1 text-[#000]" style={{ lineHeight:
'25px' }}>
          <Link to={`/product/${props?.item?._id}`} className="link transition-all">
            {props?.item?.name}
          </Link>
        </h3>

        <p className="text-[14px] mb-3">
          {props?.item?.description}
        </p>

        <Rating name="size-small" value={props?.item?.rating} size="small" readOnly />

        <div className="flex items-center gap-4">
          <span className="oldPrice line-through text-gray-500 text-[15px] font-[500]">
            {oldPriceBob ? formatPrice(oldPriceBob, "BOB") : ""}
          </span>
          <span className="price text-primary text-[15px]  font-[600]">
            {formatPrice(priceBob, "BOB")}
          </span>
        </div>

        <div className="mt-3 w-[180px]">
          {
            isAdded === false ?

              <Button className="btn-org btn-border btn-sm  !w-[195px] !h-[35px]"
                onClick={() => addToCart(props?.item, context?.userData?._id, quantity)}>
                <MdOutlineShoppingCart className="text-[18px]" /> Agregar al carrito
              </Button>

              :

              <>
                {
                  isLoading === true ?
                    <Button className="addtocart btn-org btn-border flex w-full btn-sm gap-2 "
size="small">
                      <CircularProgress />
                    </Button>

                    :


                    <div className="flex items-center justify-between overflow-hidden rounded-full
border border-[rgba(0,0,0,0.1)]">
                      <Button className="!min-w-[35px] !w-[35px] !h-[30px] !bg-[#f1f1f1]  !rounded-
none" onClick={minusQty}><FaMinus className="text-[rgba(0,0,0,0.7)]" /></Button>
                      <span>{quantity}</span>
```

```
                        <Button className="!min-w-[35px] !w-[35px] !h-[30px] !bg-primary !rounded-
none"
                          onClick={addQty}>
                          <FaPlus className="text-white" /></Button>
                      </div>

                  }
                </>

            }
          </div>
        </div>
      </div>
    );
};

export default ProductItem;
```

1.3.2.19.2 style.css

```
.productItem .title{line-height: 18px;}
.productItem .actions button:hover svg{color: #fff !important;}
.productItem .actions button svg{pointer-events:none !important;}
```

1.3.2.20 ProductLoading

1.3.2.20.1 index.jsx

```
import React from 'react'

const ProductLoading = () => {
    return (
        <div className="flex items-center gap-2 animate-pulse py-5 scrollableBox">
            <div className="col w-[16%] h-[250px]">
                <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-300
rounded-lg  dark:bg-gray-700">
                    <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-hidden="true"
xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                        <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-2V2a2 2 0 0
0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0 0 1-.895-
1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1 1.618.1l2.541
4a1 1 0 0 1 .028 1.011Z" />
                    </svg>
                </div>

                <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-4"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-2.5"></div>

                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
            </div>

            <div className="col w-[16%] h-[250px]">
                <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-300
rounded-lg  dark:bg-gray-700">
                    <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-hidden="true"
xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                        <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-2V2a2 2 0 0
0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0 0 1-.895-
1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1 1.618.1l2.541
4a1 1 0 0 1 .028 1.011Z" />
                    </svg>
                </div>

                <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-4"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-2.5"></div>

                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-2"></div>
```

```
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
            </div>


            <div className="col w-[16%] h-[250px]">
                <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-300
rounded-lg  dark:bg-gray-700">
                    <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-hidden="true"
xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                        <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-2V2a2 2 0 0
0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0 0 1-.895-
1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1 1.618.1l2.541
4a1 1 0 0 1 .028 1.011Z" />
                    </svg>
                </div>

                <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-4"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-2.5"></div>

                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
            </div>


            <div className="col w-[16%] h-[250px]">
                <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-300
rounded-lg  dark:bg-gray-700">
                    <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-hidden="true"
xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                        <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-2V2a2 2 0 0
0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0 0 1-.895-
1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1 1.618.1l2.541
4a1 1 0 0 1 .028 1.011Z" />
                    </svg>
                </div>

                <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-4"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-2.5"></div>

                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
            </div>


            <div className="col w-[16%] h-[250px]">
                <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-300
rounded-lg  dark:bg-gray-700">
                    <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-hidden="true"
xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                        <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-2V2a2 2 0 0
0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0 0 1-.895-
1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1 1.618.1l2.541
4a1 1 0 0 1 .028 1.011Z" />
                    </svg>
                </div>

                <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-4"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-2.5"></div>

                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
            </div>


            <div className="col w-[16%] h-[250px]">
```

```
                <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-300
rounded-lg  dark:bg-gray-700">
                    <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-hidden="true"
xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                        <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-2V2a2 2 0 0
0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0 0 1-.895-
1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1 1.618.1l2.541
4a1 1 0 0 1 .028 1.011Z" />
                    </svg>
                </div>

                <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-4"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-2.5"></div>

                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-2"></div>
                <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
            </div>

        </div>
    )
}


export default ProductLoading;
```

1.3.2.20.2 productLoadingGrid.jsx

```
import React from 'react'

const ProductLoadingGrid = (props) => {
    return (
        <>

            {
                props?.view === "grid" &&
                <>
                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>


                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>


                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
```

```
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>


                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>


                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>
```

```
                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>


                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>


                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
```

```
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>


                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>


                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>


                    <div className="col  animate-pulse">
                        <div className="flex items-center mb-3 justify-center w-full h-60 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>
```

```
                        <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
4"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                        <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                    </div>

                </>
            }


            {
                props?.view === "list" &&
                <>
                    <div className="col  animate-pulse flex items-center gap-4">
                        <div className="flex items-center mb-3 justify-center w-[20%] h-52 bg-gray-
300 rounded-lg  dark:bg-gray-700">
                            <svg className="w-10 h-10 text-gray-200 dark:text-gray-600" aria-
hidden="true" xmlns="http://www.w3.org/2000/svg" fill="currentColor" viewBox="0 0 20 18">
                                <path d="M18 0H2a2 2 0 0 0-2 2v14a2 2 0 0 0 2 2h16a2 2 0 0 0 2-
2V2a2 2 0 0 0-2-2Zm-5.5 4a1.5 1.5 0 1 1 0 3 1.5 1.5 0 0 1 0-3Zm4.376 10.481A1 1 0 0 1 16 15H4a1 1 0
0 1-.895-1.447l3.5-7A1 1 0 0 1 7.468 6a.965.965 0 0 1 .9.5l2.775 4.757 1.546-1.887a1 1 0 0 1
1.618.1l2.541 4a1 1 0 0 1 .028 1.011Z" />
                            </svg>
                        </div>

                        <div className='w-[80%]'>
                            <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48
mb-4"></div>
                            <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 mb-
2.5"></div>

                            <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-48 mb-
2"></div>
                            <div className="h-2.5 bg-gray-200 rounded-full dark:bg-gray-700 w-48
mb-4"></div>
                            <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 w-36 mb-
2"></div>
                            <div className="h-2 bg-gray-200 rounded-full dark:bg-gray-700 "></div>
                            <div className="h-2 bg-gray-200 rounded-full mt-2 dark:bg-gray-700 mb-
2.5"></div>
                        </div>
                    </div>


                </>
            }
        </>

    )
}


export default ProductLoadingGrid;
```

1.3.2.21 ProductsSlider

1.3.2.21.1 index.jsx

```
import React, { useContext } from "react";
import { Swiper, SwiperSlide } from "swiper/react";
import "swiper/css";
import "swiper/css/navigation";
import 'swiper/css/free-mode';
```

```
import { Navigation, FreeMode } from "swiper/modules";
import ProductItem from "../ProductItem";
import { MyContext } from "../../App";

const ProductsSlider = (props) => {

  const context = useContext(MyContext);

  return (
    <div className="productsSlider pt-1 lg:pt-3 pb-0">
      <Swiper
        slidesPerView={props.items}
        spaceBetween={10}
        slidesPerGroup={4}
        navigation={context?.windowWidth<992 ? false : true}
        modules={[Navigation, FreeMode]}
        freeMode={true}
        breakpoints={{
          250: {
            slidesPerView: 1,
            spaceBetween: 10,
          },
          330: {
            slidesPerView: 2,
            spaceBetween: 10,
          },
          500: {
            slidesPerView: 3,
            spaceBetween: 10,
          },
          1100: {
            slidesPerView: 6,
            spaceBetween: 10,
          },
        }}
        className="mySwiper"
      >
        {
          props?.data?.map((item, index) => {
            return (
              <SwiperSlide key={index}>
                <ProductItem item={item} />
              </SwiperSlide>
            )
          })
        }


      </Swiper>
    </div>
  );
};

export default ProductsSlider;
```

1.3.2.22 ProductZoom

1.3.2.22.1 index.jsx

```
import React, { useContext, useRef, useState } from "react";
import InnerImageZoom from "react-inner-image-zoom";
import "react-inner-image-zoom/lib/InnerImageZoom/styles.css";
import { Swiper, SwiperSlide } from "swiper/react";
import "swiper/css";
import "swiper/css/navigation";
import { Navigation } from "swiper/modules";
import { MyContext } from "../../App";
```

```
export const ProductZoom = (props) => {

  const [slideIndex, setSlideIndex] = useState(0);
  const zoomSliderBig = useRef();
  const zoomSliderSml = useRef();

  const context = useContext(MyContext);

  const goto = (index) => {
    setSlideIndex(index);
    zoomSliderSml.current.swiper.slideTo(index);
    zoomSliderBig.current.swiper.slideTo(index);
  }

  return (
    <>
      <div className="flex flex-col lg:flex-row gap-3">
        <div className="slider w-full lg:w-[15%] order-2 lg:order-1">
          <Swiper
            ref={zoomSliderSml}
            direction={context?.windowWidth < 992 ? "horizontal" : "vertical"}
            slidesPerView={5}
            spaceBetween={10}
            navigation={context?.windowWidth < 992 ? false : true}
            modules={[Navigation]}
            className={`zoomProductSliderThumbs h-auto lg:h-[500px] overflow-hidden
${props?.images?.length > 5 && 'space'}`}
          >
            {
              props?.images?.map((item, index) => {
                return (
                  <SwiperSlide key={index}>
                    <div className={`item rounded-md overflow-hidden cursor-pointer group h-[100%]
${slideIndex === index ? 'opacity-1' : 'opacity-30'}`} onClick={() => goto(index)}>
                      <img
                        src={item}
                      />
                    </div>
                  </SwiperSlide>
                )
              })
            }

          </Swiper>
        </div>

        <div className="zoomContainer w-full lg:w-[85%] h-auto lg:h-[500px] overflow-hidden
rounded-md  order-1 lg:order-2">
          <Swiper
            ref={zoomSliderBig}
            slidesPerView={1}
            spaceBetween={0}
            navigation={false}
          >
            {
              props?.images?.map((item, index) => {
                return (
                  <SwiperSlide key={index}>
                    <InnerImageZoom
                      zoomType="hover"
                      zoomScale={1}
                      src={item}
                    />
                  </SwiperSlide>
                )
              })
            }
```

```
          </Swiper>
        </div>
      </div>
    </>
  );
};
```

1.3.2.23 QtyBox

1.3.2.24 index.jsx

```
// src/components/QtyBox/index.jsx
import React, { useEffect, useState } from "react";
import Button from "@mui/material/Button";
import { FaAngleUp, FaAngleDown } from "react-icons/fa6";

/**
 * Props (todas opcionales, se mantienen compatibilidades):
 * - value:     número inicial/controlado (default 1)
 * - min:       mínimo permitido (default 1)
 * - max:       máximo permitido (default 99)
 * - step:      paso de incremento/decremento (default 1)
 * - className: clases extra para el contenedor
 * - handleSelecteQty: callback legacy (n -> void)
 * - onChange:  callback moderna (n -> void) (alias del anterior)
 */
function QtyBox({
  value = 1,
  min = 1,
  max = 99,
  step = 1,
  className = "",
  handleSelecteQty,
  onChange,
}) {
  // estado interno (soporta modo semi-controlado)
  const [qtyVal, setQtyVal] = useState(sanitize(value, { min, max }));

  // sincroniza cuando cambia "value" desde el padre
  useEffect(() => {
    setQtyVal(sanitize(value, { min, max }));
  }, [value, min, max]);

  const emit = (n) => {
    handleSelecteQty?.(n);
    onChange?.(n);
  };

  const update = (n) => {
    const v = sanitize(n, { min, max });
    setQtyVal(v);
    emit(v);
  };

  const plusQty = () => update(qtyVal + step);
  const minusQty = () => update(qtyVal - step);

  const onInputChange = (e) => {
    const raw = e.target.value;
    // permite vacío temporal para que el usuario pueda escribir
    if (raw === "") {
      setQtyVal("");
      return;
    }
    // solo números
```

```
    const parsed = Number(raw);
    if (Number.isFinite(parsed)) {
      setQtyVal(parsed);
    }
  };

  const onInputBlur = () => {
    // al perder foco, clamp seguro
    update(qtyVal === "" ? min : qtyVal);
  };

  // evita scroll accidental que cambie el valor
  const onWheel = (e) => e.currentTarget.blur();

  return (
    <div className={`qtyBox flex items-center relative ${className}`}>
      <input
        type="number"
        className="w-full h-[40px] p-2 pl-5 text-[15px] focus:outline-none border border-
[rgba(0,0,0,0.2)] rounded-md"
        value={qtyVal}
        min={min}
        max={max}
        step={step}
        onChange={onInputChange}
        onBlur={onInputBlur}
        onWheel={onWheel}
        inputMode="numeric"
        pattern="[0-9]*"
        aria-label="Cantidad"
      />

      <div className="flex items-center flex-col justify-between h-[40px] absolute top-0 right-0 z-
50">
        <Button
          type="button"
          className="!min-w-[25px] !w-[25px] !h-[20px] !text-[#000] !rounded-none hover:!bg-
[#f1f1f1]"
          onClick={plusQty}
          disabled={Number(qtyVal) >= max}
          aria-label="Incrementar cantidad"
        >
          <FaAngleUp className="text-[12px] opacity-55" />
        </Button>
        <Button
          type="button"
          className="!min-w-[25px] !w-[25px] !h-[20px] !text-[#000] !rounded-none hover:!bg-
[#f1f1f1]"
          onClick={minusQty}
          disabled={Number(qtyVal) <= min}
          aria-label="Disminuir cantidad"
        >
          <FaAngleDown className="text-[12px] opacity-55" />
        </Button>
      </div>
    </div>
  );
}

/* ---------- helpers ---------- */
function clamp(n, min, max) {
  return Math.min(max, Math.max(min, n));
}
function sanitize(n, { min, max }) {
  const num = Number(n);
  if (!Number.isFinite(num)) return min;
  return clamp(num, min, max);
}
```

```
/* Export default + named para no romper imports existentes */
export { QtyBox };
export default QtyBox;
```

1.3.2.25 Search

1.3.2.25.1 index.jsx

```
import React, { useContext, useState } from "react";
import "../Search/style.css";
import Button from "@mui/material/Button";
import { IoSearch } from "react-icons/io5";
import { MyContext } from "../../App";
import { useNavigate } from "react-router-dom";
import { postData } from "../../utils/api";
import CircularProgress from '@mui/material/CircularProgress';

const Search = () => {

  const [searchQuery, setSearchQuery] = useState("");
  const [isLoading, setIsLoading] = useState(false);

  const context = useContext(MyContext);

  const history = useNavigate();

  const onChangeInput = (e) => {
    setSearchQuery(e.target.value);
  }


  const search = () => {

    setIsLoading(true)

    const obj = {
      page: 1,
      limit: 3,
      query: searchQuery
    }

    if (searchQuery !== "") {
      postData(`/api/product/search/get`, obj).then((res) => {
        context?.setSearchData(res);
        setTimeout(() => {
          setIsLoading(false);
          context?.setOpenSearchPanel(false)
          history("/search")
        }, 1000);
      })
    }

  }

  return (
    <div className="searchBox w-[100%] h-[50px] bg-[#e5e5e5] rounded-[5px] relative p-2">
      <input
        type="text"
        placeholder="Search for products..."
        className="w-full h-[35px] focus:outline-none bg-inherit p-2 text-[15px]"
        value={searchQuery}
        onChange={onChangeInput}
      />
      <Button className="!absolute top-[8px] right-[5px] z-50 !w-[37px] !min-w-[37px] h-[37px]
!rounded-full !text-black" onClick={search}>
        {
```

```
          isLoading === true ? <CircularProgress /> : <IoSearch className="text-[#4e4e4e] text-
[22px]" />
        }


      </Button>
    </div>
  );
};

export default Search;
```

1.3.2.25.2 style.css

```
.searchBox input::placeholder{color: #1f1f1f !important;}
```

1.3.2.26 Sidebar

1.3.2.26.1 index.jsx

```
// admin/src/components/Sidebar/index.jsx
import React, { useContext, useMemo, useState } from "react";
import { Link, useNavigate, NavLink } from "react-router-dom";
import { Button } from "@mui/material";
import { Collapse } from "react-collapse";

import { RxDashboard } from "react-icons/rx";
import { FaRegImage, FaAngleDown } from "react-icons/fa6";
import { TbCategory, TbBuildingStore, TbCreditCard } from "react-icons/tb"; // ⬅️ agregado
TbCreditCard
import { RiProductHuntLine } from "react-icons/ri";
import { FiUsers } from "react-icons/fi";
import { IoBagCheckOutline } from "react-icons/io5";
import { IoMdLogOut } from "react-icons/io";
import { SiBloglovin } from "react-icons/si";
import { IoLogoBuffer } from "react-icons/io";

import { MyContext } from "../../App";
import { fetchDataFromApi } from "../../utils/api";
import { usePermission } from "../../hooks/usePermission"; // ⬅️

// helper permisos (suave: si no hay permisos cargados, muestra todo)
const can = (ctx, ...need) => {
  const perms =
    ctx?.permissions || ctx?.userData?.permissions || ctx?.userData?.perms;
  if (!Array.isArray(perms) || perms.length === 0) return true;
  return need.some((p) => perms.includes(p));
};

const Sidebar = () => {
  const [submenuIndex, setSubmenuIndex] = useState(null);
  const context = useContext(MyContext);
  const navigate = useNavigate();

  const isOpenSubMenu = (index) =>
    setSubmenuIndex((prev) => (prev === index ? null : index));

  const closeOnMobile = () => {
    if (context?.windowWidth < 992) context?.setisSidebarOpen(false);
    setSubmenuIndex(null);
  };

  const logout = async () => {
    closeOnMobile();
    try {
      await fetchDataFromApi("/api/user/logout");
    } catch (_) {
      // aunque falle en red, limpiamos sesión local
    } finally {
```

```
      context.setIsLogin(false);
      localStorage.removeItem("accessToken");
      localStorage.removeItem("refreshToken");
      localStorage.removeItem("X-Store-Id");
      navigate("/login", { replace: true });
    }
  };

  // ancho seguro (Tailwind no soporta w-[${var}%] dinámico)
  const sidebarWidth = useMemo(
    () =>
      context.isSidebarOpen
        ? (context?.windowWidth ?? 1200) < 992
          ? "320px"
          : "20%"
        : "0px",
    [context.isSidebarOpen, context?.windowWidth]
  );

  // ⬇️ permisos con hook
  const { any: canSeeStores } = usePermission(["store:read"]);
  const { any: canSePayments } = usePermission(["payment:read"]); // ⬅️ NUEVO

  return (
    <>
      <div
        className="sidebar fixed top-0 left-0 z-[52] bg-white h-full border-r border-
[rgba(0,0,0,0.1)] py-2 px-4 overflow-hidden transition-all"
        style={{ width: sidebarWidth }}
      >
        {/* Logo */}
        <div
          className="py-2 w-full cursor-pointer"
          onClick={() => {
            closeOnMobile();
            navigate("/");
          }}
        >
          <img
            src={localStorage.getItem("logo")}
            className="w-[170px] md:min-w-[200px]"
            alt="Logo"
          />
        </div>

        {/* Menú */}
        <ul className="mt-4 overflow-y-auto max-h-[80vh] pr-1">
          {/* Dashboard */}
          <li>
            <Link
              to="/"
              onClick={closeOnMobile}
              className="block"
            >
              <Button className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]">
                <RxDashboard className="text-[18px]" />
                <span>Panel de control</span>
              </Button>
            </Link>
          </li>

          {/* Banners (Home Slider) */}
          {can(context, "homeSlider:read", "banner:read") && (
            <li>
              <Button
                className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]"
                onClick={() => isOpenSubMenu(1)}
```

```
            >
              <FaRegImage className="text-[18px]" />
              <span>Baner de slide</span>
              <span className="ml-auto w-[30px] h-[30px] flex items-center justify-center">
                <FaAngleDown
                  className={`transition-all ${submenuIndex === 1 ? "rotate-180" : ""
                    }`}
                />
              </span>
            </Button>

            <Collapse isOpened={submenuIndex === 1}>
              <ul className="w-full">
                {can(context, "homeSlider:read") && (
                  <li className="w-full">
                    <Link to="/homeSlider/list" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-
full !text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Lista de baner de inicio
                      </Button>
                    </Link>
                  </li>
                )}
                {can(context, "homeSlider:create") && (
                  <li className="w-full">
                    <Button
                      className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3"
                      onClick={() => {
                        context.setIsOpenFullScreenPanel({
                          open: true,
                          model: "Add Home Slide",
                        });
                        closeOnMobile();
                      }}
                    >
                      <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                      Agregar baner de inicio
                    </Button>
                  </li>
                )}
              </ul>
            </Collapse>
          </li>
        )}

        {/* Categorías */}
        {can(context, "category:read") && (
          <li>
            <Button
              className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]"
              onClick={() => isOpenSubMenu(3)}
            >
              <TbCategory className="text-[18px]" />
              <span>Categoría</span>
              <span className="ml-auto w-[30px] h-[30px] flex items-center justify-center">
                <FaAngleDown
                  className={`transition-all ${submenuIndex === 3 ? "rotate-180" : ""
                    }`}
                />
              </span>
            </Button>

            <Collapse isOpened={submenuIndex === 3}>
              <ul className="w-full">
```

```
                  <li className="w-full">
                    <Link to="/category/list" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Lista de categoría
                      </Button>
                    </Link>
                  </li>

                  {can(context, "category:create") && (
                    <li className="w-full">
                      <Button
                        className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3"
                        onClick={() => {
                          context.setIsOpenFullScreenPanel({
                            open: true,
                            model: "Add New Category",
                          });
                          closeOnMobile();
                        }}
                      >
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Agregar categoría
                      </Button>
                    </li>
                  )}

                  <li className="w-full">
                    <Link to="/subCategory/list" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Lista de subcategoría
                      </Button>
                    </Link>
                  </li>

                  {can(context, "category:create") && (
                    <li className="w-full">
                      <Button
                        className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3"
                        onClick={() => {
                          context.setIsOpenFullScreenPanel({
                            open: true,
                            model: "Add New Sub Category",
                          });
                          closeOnMobile();
                        }}
                      >
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Agregar subcategoría
                      </Button>
                    </li>
                  )}
                </ul>
              </Collapse>
            </li>
          )}

          {/* Productos */}
          {can(context, "product:read") && (
            <li>
```

```
              <Button
                className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]"
                onClick={() => isOpenSubMenu(4)}
              >
                <RiProductHuntLine className="text-[18px]" />
                <span>Productos</span>
                <span className="ml-auto w-[30px] h-[30px] flex items-center justify-center">
                  <FaAngleDown
                    className={`transition-all ${submenuIndex === 4 ? "rotate-180" : ""
                      }`}
                  />
                </span>
              </Button>

              <Collapse isOpened={submenuIndex === 4}>
                <ul className="w-full">
                  <li className="w-full">
                    <Link to="/products" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Lista de productos
                      </Button>
                    </Link>
                  </li>

                  {can(context, "product:create") && (
                    <li className="w-full">
                      <Button
                        className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3"
                        onClick={() => {
                          context.setIsOpenFullScreenPanel({
                            open: true,
                            model: "Add Product",
                          });
                          closeOnMobile();
                        }}
                      >
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Actualizar producto
                      </Button>
                    </li>
                  )}

                  <li className="w-full">
                    <Link to="/product/addRams" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Agregar producto RAMS
                      </Button>
                    </Link>
                  </li>

                  <li className="w-full">
                    <Link to="/product/addWeight" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Agregar peso de WEIGHT
                      </Button>
                    </Link>
                  </li>
```

```
                  <li className="w-full">
                    <Link to="/product/addSize" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Agregar producto SIZE
                      </Button>
                    </Link>
                  </li>
                </ul>
              </Collapse>
            </li>
          )}

          {/* Usuarios */}
          {can(context, "user:read") && (
            <li>
              <Link to="/users" onClick={closeOnMobile}>
                <Button className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]">
                  <FiUsers className="text-[18px]" />
                  <span>Usuarios</span>
                </Button>
              </Link>
            </li>
          )}

          {/* Tiendas (nuevo con usePermission.any) */}
          {canSeeStores && (
            <li>
              <NavLink to="/stores" onClick={closeOnMobile}>
                <Button className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]">
                  <TbBuildingStore className="text-[18px]" />
                  <span>Tiendas</span>
                </Button>
              </NavLink>
            </li>
          )}

          {/* Pagos (NUEVO) */}
          {canSeePayments && (
            <li>
              <NavLink to="/payments" onClick={closeOnMobile}>
                <Button className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]">
                  <TbCreditCard className="text-[18px]" />
                  <span>Pagos</span>
                </Button>
              </NavLink>
            </li>
          )}

          {/* Pedidos */}
          {can(context, "order:read") && (
            <li>
              <Link to="/orders" onClick={closeOnMobile}>
                <Button className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]">
                  <IoBagCheckOutline className="text-[20px]" />
                  <span>Pedidos</span>
                </Button>
              </Link>
            </li>
          )}

          {/* Banners v1/v2 */}
```

```
          {can(context, "banner:read") && (
            <li>
              <Button
                className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]"
                onClick={() => isOpenSubMenu(5)}
              >
                <RiProductHuntLine className="text-[18px]" />
                <span>Baners</span>
                <span className="ml-auto w-[30px] h-[30px] flex items-center justify-center">
                  <FaAngleDown
                    className={`transition-all ${submenuIndex === 5 ? "rotate-180" : ""
                      }`}
                  />
                </span>
              </Button>

              <Collapse isOpened={submenuIndex === 5}>
                <ul className="w-full">
                  <li className="w-full">
                    <Link to="/bannerV1/List" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Lista baner de inicio
                      </Button>
                    </Link>
                  </li>
                  {can(context, "banner:create") && (
                    <li className="w-full">
                      <Button
                        className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3"
                        onClick={() => {
                          context.setIsOpenFullScreenPanel({
                            open: true,
                            model: "Add Home Banner List 1",
                          });
                          closeOnMobile();
                        }}
                      >
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Agregar banner de inicio
                      </Button>
                    </li>
                  )}

                  <li className="w-full">
                    <Link to="/bannerlist2/List" onClick={closeOnMobile}>
                      <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                        <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                        Lista baner de inicio 2
                      </Button>
                    </Link>
                  </li>

                  {can(context, "banner:create") && (
                    <li className="w-full">
                      <Button
                        className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3"
                        onClick={() => {
                          context.setIsOpenFullScreenPanel({
                            open: true,
                            model: "Add Home Banner List2",
```

```
                        });
                        closeOnMobile();
                      }}
                    >
                      <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                      Agregar banner de inicio 2
                    </Button>
                  </li>
                )}
              </ul>
            </Collapse>
          </li>
        )}

        {/* Blogs */}
        {can(context, "blog:read") && (
          <li>
            <Button
              className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]"
              onClick={() => isOpenSubMenu(6)}
            >
              <SiBloglovin className="text-[18px]" />
              <span>Blogs</span>
              <span className="ml-auto w-[30px] h-[30px] flex items-center justify-center">
                <FaAngleDown
                  className={`transition-all ${submenuIndex === 6 ? "rotate-180" : ""
                    }`}
                />
              </span>
            </Button>

            <Collapse isOpened={submenuIndex === 6}>
              <ul className="w-full">
                <li className="w-full">
                  <Link to="/blog/List" onClick={closeOnMobile}>
                    <Button className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3">
                      <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                      Lista de blog
                    </Button>
                  </Link>
                </li>

                {can(context, "blog:create") && (
                  <li className="w-full">
                    <Button
                      className="!text-[rgba(0,0,0,0.7)] !capitalize !justify-start !w-full
!text-[13px] !font-[500] !pl-9 flex gap-3"
                      onClick={() => {
                        context.setIsOpenFullScreenPanel({
                          open: true,
                          model: "Add Blog",
                        });
                        closeOnMobile();
                      }}
                    >
                      <span className="block w-[5px] h-[5px] rounded-full bg-[rgba(0,0,0,0.2)]"
/>
                      Agregar blog
                    </Button>
                  </li>
                )}
              </ul>
            </Collapse>
          </li>
        )}
```

```
          {/* Logo */}
          {can(context, "logo:update", "logo:read") && (
            <li>
              <Link to="/logo/manage" onClick={closeOnMobile}>
                <Button className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]">
                  <IoLogoBuffer className="text-[18px]" />
                  <span>Administrar Logo</span>
                </Button>
              </Link>
            </li>
          )}

          {/* Logout */}
          <li>
            <Button
              className="w-full !capitalize !justify-start flex gap-3 text-[14px] !text-
[rgba(0,0,0,0.8)] !font-[500] items-center !py-2 hover:!bg-[#f1f1f1]"
              onClick={logout}
            >
              <IoMdLogOut className="text-[20px]" />
              <span>Cerrar sesión</span>
            </Button>
          </li>
        </ul>
      </div>

      {/* Overlay móvil clicable */}
      {context?.windowWidth < 920 && context?.isSidebarOpen === true && (
        <div
          className="sidebarOverlay fixed top-0 left-0 bg-[rgba(0,0,0,0.5)] w-full h-full z-[51]"
          onClick={closeOnMobile}
        />
      )}
    </>
  );
};

export default Sidebar;
```

1.3.2.26.2 style.css

```
.sidebar .scroll{max-height: 200px; overflow-y: scroll; overflow-x: hidden;}
.sidebar .scroll::-webkit-scrollbar{width: 5px !important; height: 5px !important;}
.sidebar .scroll::-webkit-scrollbar-thumb{background: #ccc !important;}

.range-slider{height: 3px !important;}
.range-slider .range-slider__thumb{width: 14px !important; height: 14px !important;}
.range-slider .range-slider__thumb,.range-slider .range-slider__range{background: #ff5252
!important;}
```

1.3.3 Pages

1.3.3.1 Cart

1.3.3.1.1 cartItems.jsx

```
import React, { useContext, useEffect, useState } from "react";
import { Link } from "react-router-dom";
import Menu from "@mui/material/Menu";
import MenuItem from "@mui/material/MenuItem";
import { GoTriangleDown } from "react-icons/go";
import Rating from "@mui/material/Rating";
import { IoCloseSharp } from "react-icons/io5";
import { deleteData, editData, fetchDataFromApi } from "../../utils/api";
import { MyContext } from "../../App";
import { formatPrice } from "../../utils/formatPrice";
```

```
const CartItems = (props) => {
  const [sizeanchorEl, setSizeAnchorEl] = useState(null);
  const [selectedSize, setCartItems] = useState(props.selected);
  const openSize = Boolean(sizeanchorEl);

  const [qtyanchorEl, setQtyAnchorEl] = useState(null);
  const [selectedQty, setSelectedQty] = useState(props.qty);
  const openQty = Boolean(qtyanchorEl);

  const numbers = Array.from({ length: 20 }, () => Math.floor(Math.random() * 10) + 1); // (no
usado, lo dejo para no romper nada)

  const context = useContext(MyContext);

  // Precio principal SIEMPRE en BOB (fallback si aún no llega del backend)
  const priceBob = props?.item?.priceBob != null ? props.item.priceBob : props?.item?.price;
  const oldPriceBob = props?.item?.oldPriceBob != null ? props.item.oldPriceBob :
props?.item?.oldPrice;

  const handleClickSize = (event) => {
    setSizeAnchorEl(event.currentTarget);
  };
  const handleCloseSize = (value) => {
    setSizeAnchorEl(null);
    if (value !== null) {
      setCartItems(value);
    }
  };

  const handleClickQty = (event) => {
    setQtyAnchorEl(event.currentTarget);
  };
  const handleCloseQty = (value) => {
    setQtyAnchorEl(null);
    if (value !== null) {
      setSelectedQty(value);

      const cartObj = {
        _id: props?.item?._id,
        qty: value,
        // subTotal SIEMPRE en BOB
        subTotal: (priceBob || 0) * value,
      };

      editData("/api/cart/update-qty", cartObj).then((res) => {
        if (res?.data?.error === false) {
          context.alertBox("success", res?.data?.message);
          context?.getCartItems();
        }
      });
    }
  };

  const updateCart = (selectedVal, qty, field) => {
    handleCloseSize(selectedVal);

    const cartObj = {
      _id: props?.item?._id,
      qty: qty,
      // subTotal SIEMPRE en BOB
      subTotal: (priceBob || 0) * qty,
      size: props?.item?.size !== "" ? selectedVal : "",
      weight: props?.item?.weight !== "" ? selectedVal : "",
      ram: props?.item?.ram !== "" ? selectedVal : "",
    };

    //if product size available
    if (field === "size") {
      fetchDataFromApi(`/api/product/${props?.item?.productId}`).then((res) => {
```

```
        const product = res?.product;
        const item = product?.size?.filter((size) => size?.includes(selectedVal));
        if (item?.length !== 0) {
          editData("/api/cart/update-qty", cartObj).then((res) => {
            if (res?.data?.error === false) {
              context.alertBox("success", res?.data?.message);
              context?.getCartItems();
            }
          });
        } else {
          context.alertBox("error", `Product not available with the size of ${selectedVal}`);
        }
      });
    }

    //if product weight available
    if (field === "weight") {
      fetchDataFromApi(`/api/product/${props?.item?.productId}`).then((res) => {
        const product = res?.product;
        const item = product?.productWeight?.filter((weight) => weight?.includes(selectedVal));
        if (item?.length !== 0) {
          editData("/api/cart/update-qty", cartObj).then((res) => {
            if (res?.data?.error === false) {
              context.alertBox("success", res?.data?.message);
              context?.getCartItems();
            }
          });
        } else {
          context.alertBox("error", `Product not available with the weight of ${selectedVal}`);
        }
      });
    }

    //if product ram available
    if (field === "ram") {
      fetchDataFromApi(`/api/product/${props?.item?.productId}`).then((res) => {
        const product = res?.product;
        const item = product?.productRam?.filter((ram) => ram?.includes(selectedVal));
        if (item?.length !== 0) {
          editData("/api/cart/update-qty", cartObj).then((res) => {
            if (res?.data?.error === false) {
              context.alertBox("success", res?.data?.message);
              context?.getCartItems();
            }
          });
        } else {
          context.alertBox("error", `Product not available with the ram of ${selectedVal}`);
        }
      });
    }
  };

  const removeItem = (id) => {
    deleteData(`/api/cart/delete-cart-item/${id}`).then((res) => {
      context.alertBox("success", "Product removed from cart");
      context?.getCartItems();
    });
  };

  return (
    <div className="cartItem w-full p-3 flex items-center gap-4 pb-5 border-b border-
[rgba(0,0,0,0.1)]">
      <div className="img w-[30%] sm:w-[20%] lg:w-[15%] rounded-md overflow-hidden">
        <Link to={`/product/${props?.item?.productId}`} className="group">
          <img src={props?.item?.image} className="w-full group-hover:scale-105 transition-all" />
        </Link>
      </div>

      <div className="info  w-[70%]  sm:w-[80%]  lg:w-[85%] relative">
```

```
      <IoCloseSharp
        className="cursor-pointer absolute top-[0px] right-[0px] text-[22px] link transition-all"
        onClick={() => removeItem(props?.item?._id)}
      />
      <span className="text-[13px]">{props?.item?.brand}</span>
      <h3 className="text-[13px] sm:text-[15px] w-[80%]">
        <Link to={`/product/${props?.item?.productId}`} className="link">
          {props?.item?.productTitle?.substr(0, context?.windowWidth < 992 ? 30 : 120) + "..."}
        </Link>
      </h3>

      <Rating name="size-small" value={props?.item?.rating} size="small" readOnly />

      <div className="flex items-center gap-4 mt-2">
        {props?.item?.size !== "" && (
          <>
            {props?.productSizeData?.length !== 0 && (
              <div className="relative">
                <span
                  className="flex items-center justify-center bg-[#f1f1f1] text-[11px]
font-[600] py-1 px-2 rounded-md cursor-pointer"
                  onClick={handleClickSize}
                >
                  Size: {selectedSize} <GoTriangleDown />
                </span>

                <Menu
                  id="size-menu"
                  anchorEl={sizeanchorEl}
                  open={openSize}
                  onClose={() => handleCloseSize(null)}
                  MenuListProps={{
                    "aria-labelledby": "basic-button",
                  }}
                >
                  {props?.productSizeData?.map((item, index) => {
                    return (
                      <MenuItem
                        key={index}
                        className={`${item?.name === selectedSize && "selected"}`}
                        onClick={() => updateCart(item?.name, props?.item?.quantity, "size")}
                      >
                        {item?.name}
                      </MenuItem>
                    );
                  })}
                </Menu>
              </div>
            )}
          </>
        )}

        {props?.item?.ram !== "" && (
          <>
            {props?.productRamsData?.length !== 0 && (
              <div className="relative">
                <span
                  className="flex items-center justify-center bg-[#f1f1f1] text-[11px]
font-[600] py-1 px-2 rounded-md cursor-pointer"
                  onClick={handleClickSize}
                >
                  RAM: {selectedSize} <GoTriangleDown />
                </span>

                <Menu
                  id="size-menu"
                  anchorEl={sizeanchorEl}
                  open={openSize}
                  onClose={() => handleCloseSize(null)}
```

```
                MenuListProps={{
                  "aria-labelledby": "basic-button",
                }}
              >
                {props?.productRamsData?.map((item, index) => {
                  return (
                    <MenuItem
                      key={index}
                      className={`${item?.name === selectedSize && "selected"}`}
                      onClick={() => updateCart(item?.name, props?.item?.quantity, "ram")}
                    >
                      {item?.name}
                    </MenuItem>
                  );
                })}
              </Menu>
            </div>
          )}
        </>
      )}

      {props?.item?.weight !== "" && (
        <>
          {props?.productWeightData?.length !== 0 && (
            <div className="relative">
              <span
                className="flex items-center justify-center bg-[#f1f1f1] text-[11px]
font-[600] py-1 px-2 rounded-md cursor-pointer"
                onClick={handleClickSize}
              >
                Peso: {selectedSize} <GoTriangleDown />
              </span>

              <Menu
                id="size-menu"
                anchorEl={sizeanchorEl}
                open={openSize}
                onClose={() => handleCloseSize(null)}
                MenuListProps={{
                  "aria-labelledby": "basic-button",
                }}
              >
                {props?.productWeightData?.map((item, index) => {
                  return (
                    <MenuItem
                      key={index}
                      className={`${item?.name === selectedSize && "selected"}`}
                      onClick={() => updateCart(item?.name, props?.item?.quantity, "weight")}
                    >
                      {item?.name}
                    </MenuItem>
                  );
                })}
              </Menu>
            </div>
          )}
        </>
      )}

      <div className="relative">
        <span
          className="flex items-center justify-center bg-[#f1f1f1] text-[11px]
font-[600] py-1 px-2 rounded-md cursor-pointer"
          onClick={handleClickQty}
        >
          Qty: {selectedQty} <GoTriangleDown />
        </span>

        <Menu
```

```
              id="size-menu"
              anchorEl={qtyanchorEl}
              open={openQty}
              onClose={() => handleCloseQty(null)}
              MenuListProps={{
                "aria-labelledby": "basic-button",
              }}
            >
              {Array.from({ length: 15 }).map((_, index) => (
                <MenuItem key={index} onClick={() => handleCloseQty(index + 1)}>
                  {index + 1}
                </MenuItem>
              ))}
            </Menu>
          </div>
        </div>

        <div className="flex items-center gap-4 mt-2">
          <span className="price text-[14px]  font-[600]">
            {formatPrice(priceBob, "BOB")}
          </span>

          <span className="oldPrice line-through text-gray-500 text-[14px] font-[500]">
            {oldPriceBob ? formatPrice(oldPriceBob, "BOB") : ""}
          </span>

          <span className="price text-primary text-[14px]  font-[600]">
            {props?.item?.discount}% OFF
          </span>
        </div>
      </div>
    </div>
  );
};

export default CartItems;
```

1.3.3.1.2 index.jsx

```
import React, { useContext, useEffect, useState } from "react";

import Button from "@mui/material/Button";
import { BsFillBagCheckFill } from "react-icons/bs";
import CartItems from "./cartItems";
import { MyContext } from "../../App";
import { fetchDataFromApi } from "../../utils/api";
import { Link } from "react-router-dom";
import { formatPrice } from "../../utils/formatPrice";

const CartPage = () => {

  const [productSizeData, setProductSizeData] = useState([]);
  const [productRamsData, setProductRamsData] = useState([]);
  const [productWeightData, setProductWeightData] = useState([]);
  const context = useContext(MyContext);

  useEffect(() => {
    window.scrollTo(0, 0);

    fetchDataFromApi("/api/product/productSize/get").then((res) => {
      if (res?.error === false) {
        setProductSizeData(res?.data);
      }
    });

    fetchDataFromApi("/api/product/productRAMS/get").then((res) => {
      if (res?.error === false) {
```

```
      setProductRamsData(res?.data);
    }
  });

  fetchDataFromApi("/api/product/productWeight/get").then((res) => {
    if (res?.error === false) {
      setProductWeightData(res?.data);
    }
  });
}, []);

const selectedSize = (item) => {
  if (item?.size !== "") return item?.size;
  if (item?.weight !== "") return item?.weight;
  if (item?.ram !== "") return item?.ram;
};

// 👇 Subtotal SIEMPRE en BOB (los items del carrito ya guardan price en BOB)
const subtotalBOB = (context.cartData?.length
  ? context.cartData.reduce((total, item) => {
    const price = Number(item?.price) || 0;     // BOB
    const qty = Number(item?.quantity) || 0;
    return total + price * qty;
  }, 0)
  : 0
);

const totalBOB = subtotalBOB; // envío Free por ahora

return (
  <section className="section py-4 lg:py-8 pb-10">
    <div className="container w-[80%] max-w-[80%] flex gap-5 flex-col lg:flex-row">
      <div className="leftPart w-full lg:w-[70%]">
        <div className="shadow-md rounded-md bg-white">
          <div className="py-5 px-3 border-b border-[rgba(0,0,0,0.1)]">
            <h2>Tu carrito</h2>
            <p className="mt-0 mb-0">
              Tienes{" "}
              <span className="font-bold text-primary">
                {context?.cartData?.length}
              </span>{" "}
              productos en tu carrito
            </p>
          </div>

          {context?.cartData?.length !== 0 ? (
            context?.cartData?.map((item, index) => {
              return (
                <CartItems
                  selected={() => selectedSize(item)}
                  qty={item?.quantity}
                  item={item}
                  key={index}
                  productSizeData={productSizeData}
                  productRamsData={productRamsData}
                  productWeightData={productWeightData}
                />
              );
            })
          ) : (
            <>
              <div className="flex items-center justify-center flex-col py-10 gap-5">
                <img src="/empty-cart.png" className="w-[150px]" />
                <h4>Su carrito está vacío actualmente</h4>
                <Link to="/"><Button className="btn-org">Continuar comprando</Button></Link>
              </div>
            </>
          )}
        </div>
```

```
        </div>

        <div className="rightPart w-full lg:w-[30%]">
          <div className="shadow-md rounded-md bg-white p-5 sticky top-[155px] z-[90]">
            <h3 className="pb-3">Por pagar</h3>
            <hr />

            <p className="flex items-center justify-between">
              <span className="text-[14px] font-[500]">Sub total</span>
              <span className="text-primary font-bold">
                {formatPrice(subtotalBOB, "BOB")}
              </span>
            </p>

            <p className="flex items-center justify-between">
              <span className="text-[14px] font-[500]">Envío</span>
              <span className="font-bold">Free</span>
            </p>

            <p className="flex items-center justify-between">
              <span className="text-[14px] font-[500]">Destino</span>
              <span className="font-bold">
                <span className="font-bold">
                  {context?.userData?.address_details?.[0]?.country}
                </span>
              </span>
            </p>

            <p className="flex items-center justify-between">
              <span className="text-[14px] font-[500]">Total</span>
              <span className="text-primary font-bold">
                {formatPrice(totalBOB, "BOB")}
              </span>
            </p>

            <br />

            <Link to="/checkout">
              <Button className="btn-org btn-lg w-full flex gap-2">
                <BsFillBagCheckFill className="text-[20px]" /> Pagar
              </Button>
            </Link>
          </div>
        </div>
      </div>
    </section>
  );
};

export default CartPage;
```

1.3.3.2 Checkout

1.3.3.2.1 index.jsx

```
import React, { useContext, useEffect, useRef, useState } from "react";
import { Button } from "@mui/material";
import { BsFillBagCheckFill } from "react-icons/bs";
import { MyContext } from '../../App';
import { FaPlus } from "react-icons/fa6";
import Radio from '@mui/material/Radio';
import { deleteData } from "../../utils/api";
import axios from 'axios';
import { useNavigate } from "react-router-dom";
import CircularProgress from '@mui/material/CircularProgress';
import { formatPrice } from "../../utils/formatPrice";

const VITE_APP_PAYPAL_CLIENT_ID = import.meta.env.VITE_APP_PAYPAL_CLIENT_ID;
```

```
const VITE_API_URL = import.meta.env.VITE_API_URL;

const Checkout = () => {
  const [userData, setUserData] = useState(null);
  const [isChecked, setIsChecked] = useState(0);
  const [selectedAddress, setSelectedAddress] = useState("");
  const [totalAmountBOB, setTotalAmountBOB] = useState(0);
  const [isLoading, setIsloading] = useState(false);
  const context = useContext(MyContext);
  const history = useNavigate();

  // guardamos referencia del botón para poder cerrarlo entre renders
  const paypalButtonsRef = useRef(null);

  useEffect(() => {
    window.scrollTo(0, 0);
    setUserData(context?.userData);
    setSelectedAddress(context?.userData?.address_details?.[0]?._id);
  }, [context?.userData]);

  // Total en BOB
  useEffect(() => {
    const subtotal = (context.cartData?.length
      ? context.cartData.reduce((total, item) => {
        const price = Number(item?.price) || 0; // BOB
        const qty = Number(item?.quantity) || 0;
        return total + price * qty;
      }, 0)
      : 0
    );
    setTotalAmountBOB(subtotal);
  }, [context.cartData]);

  // PayPal SDK + Buttons (con protección contra inicializaciones duplicadas)
  useEffect(() => {
    if (!VITE_APP_PAYPAL_CLIENT_ID) return;

    let isMounted = true;
    const scriptId = "paypal-sdk";
    const containerId = "paypal-button-container";

    const renderButtons = () => {
      if (!isMounted || !window.paypal) return;

      const container = document.getElementById(containerId);
      if (!container) return;

      // limpiar contenedor y cerrar instancia previa
      container.innerHTML = "";
      try { paypalButtonsRef.current?.close(); } catch { }

      paypalButtonsRef.current = window.paypal.Buttons({
        createOrder: async () => {
          const headers = {
            'Authorization': `Bearer ${localStorage.getItem('accessToken')}`,
            'Content-Type': 'application/json',
          };

          // 👉 Enviamos total en BOB; el backend convierte a USD con la tasa snapshot
          const payload = {
            userId: context?.userData?._id,
            totalBob: Number(totalAmountBOB || 0),
            currency: "BOB",
            deliveryAddressId: selectedAddress,
          };

          const response = await axios.post(
            `${VITE_API_URL}/api/order/create-order-paypal`,
            payload,
```

```
            { headers }
          );

          return response?.data?.id;
        },
        onApprove: async (data) => {
          await onApprovePayment(data);
        },
        onError: (err) => {
          console.error("PayPal Checkout onError:", err);
          history("/order/failed");
        },
      });

      paypalButtonsRef.current.render(`#${containerId}`);
    };

    const ensureSdkLoaded = () => {
      if (window.paypal) {
        renderButtons();
        return;
      }

      let script = document.getElementById(scriptId);
      if (script) {
        // ya existe: espera a que cargue si aún no disparó
        script.addEventListener("load", renderButtons, { once: true });
        return;
      }

      // Inyectar una sola vez el SDK con currency=USD
      script = document.createElement("script");
      script.id = scriptId;
      script.src = `https://www.paypal.com/sdk/js?client-
id=${VITE_APP_PAYPAL_CLIENT_ID}&currency=USD&components=buttons&disable-funding=card`;
      script.async = true;
      script.onload = renderButtons;
      document.body.appendChild(script);
    };

    // Render solo si hay dirección y hay items
    if (selectedAddress && (context?.cartData?.length || 0) > 0) {
      ensureSdkLoaded();
    }

    return () => {
      isMounted = false;
      try { paypalButtonsRef.current?.close(); } catch { }
    };
    // Re-render solo cuando cambia lo mínimo necesario:
  }, [selectedAddress, context?.cartData?.length, totalAmountBOB]);

  const onApprovePayment = async (data) => {
    const user = context?.userData;

    const info = {
      userId: user?._id,
      products: context?.cartData,
      payment_status: "COMPLETE",
      delivery_address: selectedAddress,
      totalBob: Number(totalAmountBOB || 0),
      date: new Date().toLocaleString("en-US", {
        month: "short",
        day: "2-digit",
        year: "numeric",
      }),
    };

    const headers = {
```

```
    'Authorization': `Bearer ${localStorage.getItem('accessToken')}`,
    'Content-Type': 'application/json',
  };

  try {
    const res = await axios.post(
      `${VITE_API_URL}/api/order/capture-order-paypal`,
      { ...info, paymentId: data.orderID },
      { headers }
    );

    context.alertBox("success", res?.data?.message);
    history("/order/success");
    await deleteData(`/api/cart/emptyCart/${context?.userData?._id}`);
    context?.getCartItems();

    if (res?.data?.success) {
      context.alertBox("success", "Order completed and saved to database!");
    }
  } catch (err) {
    console.error(err);
    history("/order/failed");
  }
};

// Placeholder Cryptomus
const handleCryptomusSoon = () => {
  context?.alertBox("info", "Cryptomus: próximamente");
};

const editAddress = (id) => {
  context?.setOpenAddressPanel(true);
  context?.setAddressMode("edit");
  context?.setAddressId(id);
};

const handleChange = (e, index) => {
  if (e.target.checked) {
    setIsChecked(index);
    setSelectedAddress(e.target.value);
  }
};

const cashOnDelivery = () => {
  const user = context?.userData;
  setIsloading(true);

  if (userData?.address_details?.length !== 0) {
    const payLoad = {
      userId: user?._id,
      products: context?.cartData,
      paymentId: '',
      payment_status: "CASH ON DELIVERY",
      delivery_address: selectedAddress,
      totalAmt: Number(totalAmountBOB || 0), // BOB
      date: new Date().toLocaleString("en-US", {
        month: "short",
        day: "2-digit",
        year: "numeric",
      }),
    };

    axios.post(`${VITE_API_URL}/api/order/create`, payLoad, {
      headers: {
        'Authorization': `Bearer ${localStorage.getItem('accessToken')}`,
        'Content-Type': 'application/json',
      },
    })
      .then(async (res) => {
```

```
          context.alertBox("success", res?.data?.message);
          if (res?.data?.error === false) {
            await deleteData(`/api/cart/emptyCart/${user?._id}`);
            context?.getCartItems();
          } else {
            context.alertBox("error", res?.data?.message);
          }
          setIsloading(false);
          history("/order/success");
        })
        .catch(() => {
          context.alertBox("error", "Something went wrong");
          setIsloading(false);
        });
    } else {
      context.alertBox("error", "Please add address");
      setIsloading(false);
    }
  };

  return (
    <section className="py-3 lg:py-10 px-3">
      <div className="w-full lg:w-[70%] m-auto flex flex-col md:flex-row gap-5">
        <div className="leftCol w-full md:w-[60%]">
          <div className="card bg-white shadow-md p-5 rounded-md w-full">
            <div className="flex items-center justify-between">
              <h2>Seleccionar dirección de entrega</h2>
              {userData?.address_details?.length !== 0 && (
                <Button
                  variant="outlined"
                  onClick={() => {
                    context?.setOpenAddressPanel(true);
                    context?.setAddressMode("add");
                  }}
                  className="btn"
                >
                  <FaPlus />
                  AGREGAR {context?.windowWidth < 767 ? "" : "NUEVA DIRECCIÓN"}
                </Button>
              )}
            </div>

            <br />

            <div className="flex flex-col gap-4">
              {userData?.address_details?.length !== 0 ? (
                userData?.address_details?.map((address, index) => {
                  return (
                    <label
                      className={`flex gap-3 p-4 border border-[rgba(0,0,0,0.1)] rounded-md
relative ${isChecked === index && "bg-[#fff2f2]"}`}
                      key={address?._id || index}
                    >
                      <div>
                        <Radio
                          size="small"
                          onChange={(e) => handleChange(e, index)}
                          checked={isChecked === index}
                          value={address?._id}
                        />
                      </div>
                      <div className="info">
                        <span className="inline-block text-[13px] font-[500] p-1 bg-[#f1f1f1]
rounded-md">
                          {address?.addressType}
                        </span>
                        <h3>{userData?.name}</h3>
                        <p className="mt-0 mb-0">
```

```
                        {address?.address_line1 + " " + address?.city + " " + address?.country +
" " + address?.state + " " + address?.landmark + " " + "+ " + address?.mobile}
                      </p>
                      <p className="mb-0 font-[500]">
                        {userData?.mobile !== null ? "+" + userData?.mobile : "+" +
address?.mobile}
                      </p>
                    </div>

                    <Button
                      variant="text"
                      className="!absolute top-[15px] right-[15px]"
                      size="small"
                      onClick={() => editAddress(address?._id)}
                    >
                      EDITAR
                    </Button>
                  </label>
                );
                })
              ) : (
                <>
                  <div className="flex items-center mt-5 justify-between flex-col p-5">
                    <img src="/map.png" width="100" />
                    <h2 className="text-center">¡No se encontraron direcciones en su cuenta!</h2>
                    <p className="mt-0">Añade una dirección de entrega</p>
                    <Button
                      className="btn-org"
                      onClick={() => {
                        context?.setOpenAddressPanel(true);
                        context?.setAddressMode("add");
                      }}
                    >
                      AGREGAR DIRECCIÓN
                    </Button>
                  </div>
                </>
              )}
            </div>
          </div>
        </div>

        <div className="rightCol w-full  md:w-[40%]">
          <div className="card shadow-md bg-white p-5 rounded-md">
            <h2 className="mb-4">Tu Pedido</h2>

            <div className="flex items-center justify-between py-3 border-t border-b border-
[rgba(0,0,0,0.1)]">
              <span className="text-[14px] font-[600]">Productos</span>
              <span className="text-[14px] font-[600]">Sub total</span>
            </div>

            <div className="mb-5 scroll max-h-[250px] overflow-y-scroll overflow-x-hidden pr-2">
              {context?.cartData?.length !== 0 &&
                context?.cartData?.map((item, index) => {
                  const lineTotalBOB =
                    (Number(item?.quantity) || 0) * (Number(item?.price) || 0);
                  return (
                    <div className="flex items-center justify-between py-2" key={item?._id ||
index}>
                      <div className="part1 flex items-center gap-3">
                        <div className="img w-[50px] h-[50px] object-cover overflow-hidden rounded-
md group cursor-pointer">
                          <img
                            src={item?.image}
                            className="w-full transition-all group-hover:scale-105"
                          />
                        </div>
```

```
                      <div className="info">
                        <h4 className="text-[14px]" title={item?.productTitle}>
                          {item?.productTitle?.substr(0, 20) + "..."}{" "}
                        </h4>
                        <span className="text-[13px]">Qty : {item?.quantity}</span>
                      </div>
                    </div>

                    <span className="text-[14px] font-[500]">
                      {formatPrice(lineTotalBOB, "BOB")}
                    </span>
                  </div>
                );
              })}
            </div>

            <div className="flex items-center justify-between py-2">
              <span className="text-[14px] font-[600]">Total</span>
              <span className="text-[16px] font-[700] text-primary">
                {formatPrice(totalAmountBOB, "BOB")}
              </span>
            </div>

            <div className="flex items-center flex-col gap-3 mb-2 mt-3">
              {/* Botón placeholder para futura integración de Cryptomus */}
              <Button
                type="button"
                className="btn-dark btn-lg w-full flex gap-2 items-center"
                onClick={() => {
                  context?.alertBox("info", "Cryptomus: próximamente");
                }}
              >
                Pagar con Cryptomus (próximamente)
              </Button>

              {/* PayPal */}
              <div
                id="paypal-button-container"
                className={`${userData?.address_details?.length === 0 ? 'pointer-events-none' : ''}
w-full`}
              ></div>

              {/* Cash on Delivery */}
              <Button
                type="button"
                className="btn-dark btn-lg w-full flex gap-2 items-center"
                onClick={cashOnDelivery}
              >
                {isLoading === true ? (
                  <CircularProgress />
                ) : (
                  <>
                    <BsFillBagCheckFill className="text-[20px]" />
                    Pago contra entrega
                  </>
                )}
              </Button>
            </div>
          </div>
        </div>
      </div>
    </section>
  );
};

export default Checkout;
```

1.3.3.3 ForgotPassword

1.3.3.3.1 index.jsx

```
import React, { useContext, useState } from "react";
import TextField from "@mui/material/TextField";
import Button from "@mui/material/Button";
import { IoMdEye } from "react-icons/io";
import { IoMdEyeOff } from "react-icons/io";
import { Link, useNavigate, useParams } from "react-router-dom";
import { MyContext } from "../../App";
import CircularProgress from '@mui/material/CircularProgress';
import { postData } from "../../utils/api";

const ForgotPassword = () => {
  const [isPasswordShow, setIsPasswordShow] = useState(false);
  const [isPasswordShow2, setIsPasswordShow2] = useState(false);
  const [isLoading, setIsLoading] = useState(false);

  const [formFields, setFormsFields] = useState({
    email: localStorage.getItem("userEmail"),
    newPassword: '',
    confirmPassword: ''
  });

  const context = useContext(MyContext);
  const history = useNavigate();



  const onChangeInput = (e) => {
    const { name, value } = e.target;
    setFormsFields(() => {
      return {
        ...formFields,
        [name]: value
      }
    })
  }


  const valideValue = Object.values(formFields).every(el => el)

  const handleSubmit = (e) => {
    e.preventDefault();

    setIsLoading(true);

    if (formFields.newPassword === "") {
      context.alertBox("error", "Please enter new password");
      setIsLoading(false);
      return false
    }


    if (formFields.confirmPassword === "") {
      context.alertBox("error", "Please enter confirm password");
      setIsLoading(false);
      return false
    }

    if (formFields.confirmPassword !== formFields.newPassword) {
      context.alertBox("error", "Password and confirm password not match");
      setIsLoading(false);
      return false
    }


    postData(`/api/user/forgot-password/change-password`, formFields).then((res) => {
```

```
      console.log(res)
      if (res?.error === false) {
        localStorage.removeItem("userEmail")
        localStorage.removeItem("actionType")
        context.alertBox("success", res?.message);
        setIsLoading(false);
        history("/login")
      }
      else {
        context.alertBox("error", res?.message);
      }
    })


  }


  return (
    <section className="section py-5 lg:py-10">
      <div className="container">
        <div className="card shadow-md w-full sm:w-[400px] m-auto rounded-md bg-white p-5 px-10">
          <h3 className="text-center text-[18px] text-black">
            Olvidó su contrseña ?
          </h3>

          <form className="w-full mt-5" onSubmit={handleSubmit}>
            <div className="form-group w-full mb-5 relative">
              <TextField
                type={isPasswordShow === false ? "password" : "text"}
                id="password"
                label="New Password"
                variant="outlined"
                className="w-full"
                name="newPassword"
                value={formFields.newPassword}
                disabled={isLoading === true ? true : false}
                onChange={onChangeInput}
              />

              <Button
                className="!absolute top-[10px] right-[10px] z-50 !w-[35px] !h-[35px] !min-w-[35px]
!rounded-full !text-black"
                onClick={() => {
                  setIsPasswordShow(!isPasswordShow);
                }}
              >
                {isPasswordShow === false ? (
                  <IoMdEye className="text-[20px] opacity-75" />
                ) : (
                  <IoMdEyeOff className="text-[20px] opacity-75" />
                )}
              </Button>


            </div>

            <div className="form-group w-full mb-5 relative">
              <TextField
                type={isPasswordShow2 === false ? "password" : "text"}
                id="confirm_password"
                label="Confirm Password"
                variant="outlined"
                className="w-full"
                name="confirmPassword"
                value={formFields.confirmPassword}
                disabled={isLoading === true ? true : false}
                onChange={onChangeInput}
              />
              <Button
```

```
                className="!absolute top-[10px] right-[10px] z-50 !w-[35px] !h-[35px] !min-w-[35px]
!rounded-full !text-black"
                onClick={() => {
                  setIsPasswordShow2(!isPasswordShow2);
                }}
              >
                {isPasswordShow2 === false ? (
                  <IoMdEye className="text-[20px] opacity-75" />
                ) : (
                  <IoMdEyeOff className="text-[20px] opacity-75" />
                )}
              </Button>
            </div>


            <div className="flex items-center w-full mt-3 mb-3">
              <Button type="submit" disabled={!valideValue} className="btn-org btn-lg w-full flex
gap-3">
                {
                  isLoading === true ? <CircularProgress color="inherit" />
                    :
                    'Change Password'
                }

              </Button>
            </div>

          </form>
        </div>
      </div>
    </section>
  );
};

export default ForgotPassword;
```

1.3.3.4 Home

1.3.3.4.1 index – Copy.jsx

```
import React, { useContext, useEffect, useState } from "react";
import HomeSlider from "../../components/HomeSlider";
import HomeCatSlider from "../../components/HomeCatSlider";
import { LiaShippingFastSolid } from "react-icons/lia";
import AdsBannerSlider from "../../components/AdsBannerSlider";
import AdsBannerSliderV2 from "../../components/AdsBannerSliderV2";

import Tabs from "@mui/material/Tabs";
import Tab from "@mui/material/Tab";
import ProductsSlider from "../../components/ProductsSlider";

import { Swiper, SwiperSlide } from "swiper/react";
import "swiper/css";
import "swiper/css/navigation";

import { Navigation } from "swiper/modules";
import BlogItem from "../../components/BlogItem";
import HomeBannerV2 from "../../components/HomeSliderV2";
import BannerBoxV2 from "../../components/bannerBoxV2";
import { fetchDataFromApi } from "../../utils/api";
import { MyContext } from "../../App";
import ProductLoading from "../../components/ProductLoading";

const Home = () => {
  const [value, setValue] = useState(0);
  const [homeSlidesData, setHomeSlidesData] = useState([]);
  const [popularProductsData, setPopularProductsData] = useState([]);
  const [productsData, setAllProductsData] = useState([]);
  const [featuredProducts, setFeaturedProducts] = useState([]);
  const [bannerV1Data, setBannerV1Data] = useState([]);
```

```
  const [bannerList2Data, setBannerList2Data] = useState([]);
  const [blogData, setBlogData] = useState([]);
  const [randomCatProducts, setRandomCatProducts] = useState([]);


  const context = useContext(MyContext);


  useEffect(() => {

    window.scrollTo(0, 0);

    fetchDataFromApi("/api/homeSlides").then((res) => {
      setHomeSlidesData(res?.data)
    })
    fetchDataFromApi("/api/product/getAllProducts").then((res) => {
      setAllProductsData(res?.products)
    })

    fetchDataFromApi("/api/product/getAllFeaturedProducts").then((res) => {
      setFeaturedProducts(res?.products)
    })

    fetchDataFromApi("/api/bannerV1").then((res) => {
      setBannerV1Data(res?.data);
    });

    fetchDataFromApi("/api/bannerList2").then((res) => {
      setBannerList2Data(res?.data);
    });

    fetchDataFromApi("/api/blog").then((res) => {
      setBlogData(res?.blogs);
    });
  }, [])



  useEffect(() => {
    if (context?.catData?.length !== 0) {

      fetchDataFromApi(`/api/product/getAllProductsByCatId/${context?.catData[0]?._id}`).then((res)
=> {
        if (res?.error === false) {
          setPopularProductsData(res?.products)
        }

      })
    }

    const numbers = new Set();
    while (numbers.size < context?.catData?.length - 1) {

      const number = Math.floor(1 + Math.random() * 9);

      // Add the number to the set (automatically ensures uniqueness)
      numbers.add(number);
    }


    getRendomProducts(Array.from(numbers), context?.catData)

  }, [context?.catData])



  const getRendomProducts = (arr, catArr) => {

    const filterData = [];
```

```
  for (let i = 0; i < arr.length; i++) {
    let catId = catArr[arr[i]]?._id;

    fetchDataFromApi(`/api/product/getAllProductsByCatId/${catId}`).then((res) => {
      filterData.push({
        catName: catArr[arr[i]]?.name,
        data: res?.products
      })

      setRandomCatProducts(filterData)
    })

  }



}

const handleChange = (event, newValue) => {
  setValue(newValue);
};

const filterByCatId = (id) => {
  setPopularProductsData([])
  fetchDataFromApi(`/api/product/getAllProductsByCatId/${id}`).then((res) => {
    if (res?.error === false) {
      setPopularProductsData(res?.products)
    }

  })
}



return (
  <>

    {
      homeSlidesData?.lengtn !== 0 && <HomeSlider data={homeSlidesData} />
    }


    {
      context?.catData?.length !== 0 && <HomeCatSlider data={context?.catData} />
    }



    <section className="bg-white py-8">
      <div className="container">
        <div className="flex items-center justify-between">
          <div className="leftSec">
            <h2 className="text-[20px] font-[600]">Productos Populares</h2>
            <p className="text-[14px] font-[400] mt-0 mb-0">
              No te pierdas las ofertas vigentes hasta finales de septiembre
            </p>
          </div>

          <div className="rightSec w-[60%]">
            <Tabs
              value={value}
              onChange={handleChange}
              variant="scrollable"
              scrollButtons="auto"
              aria-label="scrollable auto tabs example"
            >
              {
                context?.catData?.length !== 0 && context?.catData?.map((cat, index) => {
```

```
                    return (
                      <Tab label={cat?.name} key={index} onClick={() => filterByCatId(cat?._id)} />
                    )
                  })
                }


              </Tabs>
            </div>
          </div>


          <div className="min-h-[60vh]">
            {
              popularProductsData?.length === 0 && <ProductLoading />
            }
            {
              popularProductsData?.length !== 0 && <ProductsSlider items={6}
data={popularProductsData} />
            }
          </div>

        </div>
      </section>



      <section className="py-6 pt-0 bg-white">
        <div className="container flex  gap-5">
          <div className="part1 w-[70%]">

            {
              productsData?.length !== 0 && <HomeBannerV2 data={productsData} />
            }


          </div>

          <div className="part2 w-[30%] flex items-center gap-5 justify-between flex-col">
            <BannerBoxV2 info={bannerV1Data[bannerV1Data?.length - 1]?.alignInfo}
image={bannerV1Data[bannerV1Data?.length - 1]?.images[0]} item={bannerV1Data[bannerV1Data?.length -
1]} />

            <BannerBoxV2 info={bannerV1Data[bannerV1Data?.length - 2]?.alignInfo}
image={bannerV1Data[bannerV1Data?.length - 2]?.images[0]} item={bannerV1Data[bannerV1Data?.length -
2]} />
          </div>

        </div>
      </section>





      <section className="py-4 pt-8 pb-0 bg-white">
        <div className="container">
          <div className="freeShipping  w-[80%] m-auto py-4 p-4 border-2 border-[#ff5252] flex
items-center justify-between rounded-md mb-7">
            <div className="col1 flex items-center gap-4">
              <LiaShippingFastSolid className="text-[50px]" />
              <span className="text-[20px] font-[600] uppercase">
                Envío gratis{" "}
              </span>
            </div>

            <div className="col2">
              <p className="mb-0 mt-0 font-[500]">
```

```
            Envío gratis ahora en tu primer pedido y más de Bs200
          </p>
        </div>

        <p className="font-bold text-[25px]">- Solo Bs200*</p>
      </div>

      {
        bannerV1Data?.length !== 0 && <AdsBannerSliderV2 items={4} data={bannerV1Data} />
      }


    </div>
  </section>

  <section className="py-5 pt-0 bg-white">
    <div className="container">
      <h2 className="text-[20px] font-[600]">Últimos productos</h2>

      {
        productsData?.length === 0 && <ProductLoading />
      }

      {
        productsData?.length !== 0 && <ProductsSlider items={6} data={productsData} />
      }



    </div>
  </section>
  <section className="py-5 pt-0 bg-white">
    <div className="container">
      <h2 className="text-[20px] font-[600]">Productos destacados</h2>

      {
        featuredProducts?.length === 0 && <ProductLoading />
      }


      {
        featuredProducts?.length !== 0 && <ProductsSlider items={6} data={featuredProducts} />
      }

      {
        bannerList2Data?.length !== 0 && <AdsBannerSlider items={4} data={bannerList2Data} />
      }



    </div>
  </section>




  {
    randomCatProducts?.length !== 0 && randomCatProducts?.map((productRow, index) => {
      if (productRow?.catName !== undefined && productRow?.data?.length !== 0)
        return (
          <section className="py-5 pt-0 bg-white" key={index}>
            <div className="container">
              <h2 className="text-[20px] font-[600]">{productRow?.catName}</h2>

              {
                productRow?.data?.length === 0 && <ProductLoading />
              }

              {
```

```
                    productRow?.data?.length !== 0 && <ProductsSlider items={6}
data={productRow?.data} />
                  }



                </div>
              </section>)
        })

      }


      {
        blogData?.length !== 0 &&
        <section className="py-5 pb-8 pt-0 bg-white blogSection">
          <div className="container">
            <h2 className="text-[20px] font-[600] mb-4">Para el Blog</h2>
            <Swiper
              slidesPerView={4}
              spaceBetween={30}
              navigation={true}
              modules={[Navigation]}
              className="blogSlider"
            >
              {
                blogData?.map((item, index) => {
                  return (
                    <SwiperSlide key={index}>
                      <BlogItem item={item} />
                    </SwiperSlide>
                  )
                })
              }



            </Swiper>
          </div>
        </section>
      }



    </>
  );
};

export default Home;
```

1.3.3.4.2 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import HomeSlider from "../../components/HomeSlider";
import HomeCatSlider from "../../components/HomeCatSlider";
import { LiaShippingFastSolid } from "react-icons/lia";
import AdsBannerSlider from "../../components/AdsBannerSlider";
import AdsBannerSliderV2 from "../../components/AdsBannerSliderV2";

import Tabs from "@mui/material/Tabs";
import Tab from "@mui/material/Tab";
import ProductsSlider from "../../components/ProductsSlider";

import { Swiper, SwiperSlide } from "swiper/react";
import "swiper/css";
import "swiper/css/navigation";
import 'swiper/css/free-mode';

import { Navigation, FreeMode } from "swiper/modules";
```

```
import BlogItem from "../../components/BlogItem";
import HomeBannerV2 from "../../components/HomeSliderV2";
import BannerBoxV2 from "../../components/bannerBoxV2";
import { fetchDataFromApi } from "../../utils/api";
import { MyContext } from "../../App";
import ProductLoading from "../../components/ProductLoading";
import BannerLoading from "../../components/LoadingSkeleton/bannerLoading";
import { Button } from "@mui/material";
import { MdArrowRightAlt } from "react-icons/md";
import { Link } from "react-router-dom";

const Home = () => {
  const [value, setValue] = useState(0);
  const [homeSlidesData, setHomeSlidesData] = useState([]);
  const [popularProductsData, setPopularProductsData] = useState([]);
  const [productsData, setAllProductsData] = useState([]);
  const [productsBanners, setProductsBanners] = useState([]);
  const [featuredProducts, setFeaturedProducts] = useState([]);
  const [bannerV1Data, setBannerV1Data] = useState([]);
  const [bannerList2Data, setBannerList2Data] = useState([]);
  const [blogData, setBlogData] = useState([]);
  const [randomCatProducts, setRandomCatProducts] = useState([]);


  const context = useContext(MyContext);


  useEffect(() => {

    window.scrollTo(0, 0);

    fetchDataFromApi("/api/homeSlides").then((res) => {
      setHomeSlidesData(res?.data)
    })
    fetchDataFromApi("/api/product/getAllProducts?page=1&limit=12").then((res) => {
      setAllProductsData(res?.products)
    })

    fetchDataFromApi("/api/product/getAllProducts").then((res) => {
      setProductsBanners(res?.products)
    })


    fetchDataFromApi("/api/product/getAllFeaturedProducts").then((res) => {
      setFeaturedProducts(res?.products)
    })

    fetchDataFromApi("/api/bannerV1").then((res) => {
      setBannerV1Data(res?.data);
    });

    fetchDataFromApi("/api/bannerList2").then((res) => {
      setBannerList2Data(res?.data);
    });

    fetchDataFromApi("/api/blog").then((res) => {
      setBlogData(res?.blogs);
    });
  }, [])



  useEffect(() => {
    if (context?.catData?.length !== 0) {

      fetchDataFromApi(`/api/product/getAllProductsByCatId/${context?.catData[0]?._id}`).then((res)
=> {
        if (res?.error === false) {
          setPopularProductsData(res?.products)
```

```
      }

    })
  }

  const numbers = new Set();
  while (numbers.size < context?.catData?.length - 1) {

    const number = Math.floor(1 + Math.random() * 8);

    // Add the number to the set (automatically ensures uniqueness)
    numbers.add(number);
  }


  getRendomProducts(Array.from(numbers), context?.catData)

}, [context?.catData])



const getRendomProducts = (arr, catArr) => {

  const filterData = [];

  for (let i = 0; i < arr.length; i++) {
    let catId = catArr[arr[i]]?._id;

    fetchDataFromApi(`/api/product/getAllProductsByCatId/${catId}`).then((res) => {
      filterData.push({
        catName: catArr[arr[i]]?.name,
        data: res?.products
      })

      setRandomCatProducts(filterData)
    })

  }



}

const handleChange = (event, newValue) => {
  setValue(newValue);
};

const filterByCatId = (id) => {
  setPopularProductsData([])
  fetchDataFromApi(`/api/product/getAllProductsByCatId/${id}`).then((res) => {
    if (res?.error === false) {
      setPopularProductsData(res?.products)
    }

  })
}



return (
  <>

    {
      homeSlidesData?.length === 0 && <BannerLoading />
    }

    {
      homeSlidesData?.lengtn !== 0 && <HomeSlider data={homeSlidesData} />
    }
```

```
      {
        context?.catData?.length !== 0 && <HomeCatSlider data={context?.catData} />
      }





      <section className="bg-white py-3 lg:py-8">
        <div className="container">
          <div className="flex items-center justify-between flex-col lg:flex-row">
            <div className="leftSec w-full lg:w-[40%]">
              <h2 className="text-[14px] sm:text-[14px] md:text-[16px] lg:text-[20px] font-
[600]">Productos populares</h2>
              <p className="text-[12px] sm:text-[14px] md:text-[13px] lg:text-[14px] font-[400] mt-
0 mb-0">
                No te pierdas las ofertas vigentes hasta finales de marzo.
              </p>
            </div>

            <div className="rightSec w-full lg:w-[60%]">
              <Tabs
                value={value}
                onChange={handleChange}
                variant="scrollable"
                scrollButtons="auto"
                aria-label="scrollable auto tabs example"
              >
                {
                  context?.catData?.length !== 0 && context?.catData?.map((cat, index) => {
                    return (
                      <Tab label={cat?.name} key={index} onClick={() => filterByCatId(cat?._id)} />
                    )
                  })
                }


              </Tabs>
            </div>
          </div>


          <div className="min-h-max lg:min-h-[60vh]">
            {
              popularProductsData?.length === 0 && <ProductLoading />
            }
            {
              popularProductsData?.length !== 0 && <ProductsSlider items={6}
data={popularProductsData} />
            }
          </div>

        </div>
      </section>



      <section className="py-6 pt-0 bg-white">
        <div className="container flex flex-col lg:flex-row gap-5">
          <div className="part1 w-full lg:w-[70%]">

            {
              productsBanners?.length > 0 && <HomeBannerV2 data={productsBanners} />
            }


          </div>
```

```
          <div className="part2 scrollableBox w-full lg:w-[30%] flex items-center gap-5 justify-
between flex-row lg:flex-col">
            <BannerBoxV2 info={bannerV1Data[bannerV1Data?.length - 1]?.alignInfo}
image={bannerV1Data[bannerV1Data?.length - 1]?.images[0]} item={bannerV1Data[bannerV1Data?.length -
1]} />

            <BannerBoxV2 info={bannerV1Data[bannerV1Data?.length - 2]?.alignInfo}
image={bannerV1Data[bannerV1Data?.length - 2]?.images[0]} item={bannerV1Data[bannerV1Data?.length -
2]} />
          </div>

        </div>
      </section>





      <section className="py-0 lg:py-4 pt-0 lg:pt-8 pb-0 bg-white">
        <div className="container">
          <div className="freeShipping w-full md:w-[80%] m-auto py-4 p-4  border-2 border-[#ff5252]
flex items-center justify-center lg:justify-between flex-col lg:flex-row rounded-md mb-7">
            <div className="col1 flex items-center gap-4">
              <LiaShippingFastSolid className="text-[30px] lg:text-[50px]" />
              <span className="text-[16px] lg:text-[20px] font-[600] uppercase">
                Envío gratis{" "}
              </span>
            </div>

            <div className="col2">
              <p className="mb-0 mt-0 font-[500] text-center">
                Entrega gratuita ahora en tu primer pedido y en compras superiores a Bs200
              </p>
            </div>

            <p className="font-bold text-[20px] lg:text-[25px]">- Solo Bs200*</p>
          </div>

          {
            bannerV1Data?.length !== 0 && <AdsBannerSliderV2 items={4} data={bannerV1Data} />
          }


        </div>
      </section>

      <section className="py-3 lg:py-2 pt-0 bg-white">
        <div className="container">
          <div className="flex items-center justify-between">
            <h2 className="text-[20px] font-[600]">Últimos productos</h2>
            <Link to="/products">
              <Button className="!bg-gray-100 hover:!bg-gray-200 !text-gray-800 !capitalize !px-3
!border !border-[rgba(0,0,0,0.4)]" size="small" >Ver todo <MdArrowRightAlt size={25} /></Button>
            </Link>
          </div>

          {
            productsData?.length === 0 && <ProductLoading />
          }

          {
            productsData?.length !== 0 && <ProductsSlider items={6} data={productsData} />
          }



        </div>
      </section>
      <section className="py-2 lg:py-0 pt-0 bg-white">
```

```
        <div className="container">
          <h2 className="text-[20px] font-[600]">Productos destacados</h2>

          {
            featuredProducts?.length === 0 && <ProductLoading />
          }


          {
            featuredProducts?.length !== 0 && <ProductsSlider items={6} data={featuredProducts} />
          }

          {
            bannerList2Data?.length !== 0 && <AdsBannerSlider items={4} data={bannerList2Data} />
          }



        </div>
      </section>



      {
        randomCatProducts?.length !== 0 && randomCatProducts?.map((productRow, index) => {
          if (productRow?.catName !== undefined && productRow?.data?.length !== 0)
            return (
              <section className="py-5 pt-0 bg-white" key={index}>
                <div className="container">
                  <div className="flex items-center justify-between">
                    <h2 className="text-[20px] font-[600]">{productRow?.catName}</h2>
                    {
                      productRow?.data?.length > 6 &&
                      <Link to={`products?catId=${productRow?.data[0]?.catId}`}>
                        <Button className="!bg-gray-100 hover:!bg-gray-200 !text-gray-800
!capitalize !px-3 !border !border-[rgba(0,0,0,0.4)]" size="small" >Ver todo <MdArrowRightAlt
size={25} /></Button>
                      </Link>
                    }

                  </div>




                  {
                    productRow?.data?.length === 0 && <ProductLoading />
                  }

                  {
                    productRow?.data?.length !== 0 && <ProductsSlider items={6}
data={productRow?.data} />
                  }



                </div>
              </section>)
        })

      }


      {
        blogData?.length !== 0 &&
        <section className="py-5 pb-8 pt-0 bg-white blogSection">
          <div className="container">
            <h2 className="text-[20px] font-[600] mb-4">Del blog</h2>
            <Swiper
              slidesPerView={4}
```

```
              spaceBetween={30}
              navigation={context?.windowWidth < 992 ? false : true}
              modules={[Navigation, FreeMode]}
              freeMode={true}
              breakpoints={{
                250: {
                  slidesPerView: 1,
                  spaceBetween: 10,
                },
                330: {
                  slidesPerView: 1,
                  spaceBetween: 10,
                },
                500: {
                  slidesPerView: 2,
                  spaceBetween: 20,
                },
                700: {
                  slidesPerView: 3,
                  spaceBetween: 20,
                },
                1100: {
                  slidesPerView: 4,
                  spaceBetween: 30,
                },
              }}
              className="blogSlider"
            >
              {
                blogData?.slice()?.reverse()?.map((item, index) => {
                  return (
                    <SwiperSlide key={index}>
                      <BlogItem item={item} />
                    </SwiperSlide>
                  )
                })
              }



            </Swiper>
          </div>
        </section>
      }



    </>
  );
};

export default Home;
```

1.3.3.5 Login

1.3.3.5.1 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import TextField from "@mui/material/TextField";
import Button from "@mui/material/Button";
import { IoMdEye } from "react-icons/io";
import { IoMdEyeOff } from "react-icons/io";
import { Link, useNavigate, useParams } from "react-router-dom";
import { FcGoogle } from "react-icons/fc";
import { MyContext } from "../../App";
import CircularProgress from '@mui/material/CircularProgress';
import { postData } from "../../utils/api";

import { getAuth, signInWithPopup, GoogleAuthProvider } from "firebase/auth";
import { firebaseApp } from "../../firebase";
const auth = getAuth(firebaseApp);
```

```
const googleProvider = new GoogleAuthProvider();

const Login = () => {
  const [isLoading, setIsLoading] = useState(false);
  const [isPasswordShow, setIsPasswordShow] = useState(false);
  const [formFields, setFormsFields] = useState({
    email: '',
    password: ''
  });

  const context = useContext(MyContext);
  const history = useNavigate();


  useEffect(() => {
    window.scrollTo(0, 0)
    const token = localStorage.getItem('accessToken');

    if (token !== undefined && token !== null && token !== "") {
      history("/")
    }

  }, []);

  const forgotPassword = () => {

    if (formFields.email === "") {
      context.alertBox("error", "Por favor ingresa tu correo electrónico");
      return false;
    }
    else {
      context.alertBox("success", `Se envió el código OTP a ${formFields.email}`);
      localStorage.setItem("userEmail", formFields.email);
      localStorage.setItem("actionType", 'forgot-password');

      postData("/api/user/forgot-password", {
        email: formFields.email,
      }).then((res) => {
        if (res?.error === false) {
          context.alertBox("success", res?.message);
          history("/verify")
        } else {
          context.alertBox("error", res?.message);
        }
      })


    }

  }

  const onChangeInput = (e) => {
    const { name, value } = e.target;
    setFormsFields(() => {
      return {
        ...formFields,
        [name]: value
      }
    })
  }


  const valideValue = Object.values(formFields).every(el => el)

  const handleSubmit = (e) => {
    e.preventDefault();

    setIsLoading(true);
```

```
  if (formFields.email === "") {
    context.alertBox("error", "Por favor ingresa tu correo electrónico");
    return false
  }


  if (formFields.password === "") {
    context.alertBox("error", "Por favor ingresa tu contraseña");
    return false
  }


  postData("/api/user/login", formFields, { withCredentials: true }).then((res) => {
    console.log(res)

    if (res?.error !== true) {
      setIsLoading(false);
      context.alertBox("success", res?.message);
      setFormsFields({
        email: "",
        password: ""
      })

      localStorage.setItem("accessToken", res?.data?.accesstoken);
      localStorage.setItem("refreshToken", res?.data?.refreshToken);

      context.setIsLogin(true);

      history("/")
    } else {
      context.alertBox("error", res?.message);
      setIsLoading(false);
    }

  })


}



const authWithGoogle = () => {

  signInWithPopup(auth, googleProvider)
    .then((result) => {
      // This gives you a Google Access Token. You can use it to access the Google API.
      const credential = GoogleAuthProvider.credentialFromResult(result);
      const token = credential.accessToken;
      // The signed-in user info.
      const user = result.user;

      const fields = {
        name: user.providerData[0].displayName,
        email: user.providerData[0].email,
        password: null,
        avatar: user.providerData[0].photoURL,
        mobile: user.providerData[0].phoneNumber,
        role: "USER"
      };


      postData("/api/user/authWithGoogle", fields).then((res) => {

        if (res?.error !== true) {
          setIsLoading(false);
          context.alertBox("success", res?.message);
          localStorage.setItem("userEmail", fields.email)
          localStorage.setItem("accessToken", res?.data?.accesstoken);
          localStorage.setItem("refreshToken", res?.data?.refreshToken);
```

```
          context.setIsLogin(true);

          history("/")
        } else {
          context.alertBox("error", res?.message);
          setIsLoading(false);
        }

      })

      console.log(user)
      // IdP data available using getAdditionalUserInfo(result)
      // ...
    }).catch((error) => {
      // Handle Errors here.
      const errorCode = error.code;
      const errorMessage = error.message;
      // The email of the user's account used.
      const email = error.customData.email;
      // The AuthCredential type that was used.
      const credential = GoogleAuthProvider.credentialFromError(error);
      // ...
    });


  }


  return (
    <section className="section py-5 sm:py-10">
      <div className="container">
        <div className="card shadow-md w-full sm:w-[400px] m-auto rounded-md bg-white p-5 px-10">
          <h3 className="text-center text-[18px] text-black">
            Inicia sesión en tu cuenta
          </h3>

          <form className="w-full mt-5" onSubmit={handleSubmit}>
            <div className="form-group w-full mb-5">
              <TextField
                type="emai"
                id="email"
                name="email"
                value={formFields.email}
                disabled={isLoading === true ? true : false}
                label="Correo electrónico"
                variant="outlined"
                className="w-full"
                onChange={onChangeInput}
              />
            </div>

            <div className="form-group w-full mb-5 relative">
              <TextField
                type={isPasswordShow === false ? 'password' : 'text'}
                id="password"
                label="Contraseña"
                variant="outlined"
                className="w-full"
                name="password"
                value={formFields.password}
                disabled={isLoading === true ? true : false}
                onChange={onChangeInput}
              />
              <Button className="!absolute top-[10px] right-[10px] z-50 !w-[35px] !h-[35px] !min-w-
[35px] !rounded-full !text-black" onClick={() => {
                setIsPasswordShow(!isPasswordShow)
              }}>
                {
```

```
                  isPasswordShow === false ? <IoMdEye className="text-[20px] opacity-75" /> :
                    <IoMdEyeOff className="text-[20px] opacity-75" />
                }
              </Button>
            </div>


            <a className="link cursor-pointer text-[14px] font-[600]"
onClick={forgotPassword}>¿Olvidaste tu contraseña?</a>

            <div className="flex items-center w-full mt-3 mb-3">
              <Button type="submit" disabled={!valideValue} className="btn-org btn-lg w-full flex
gap-3">
                {
                  isLoading === true ? <CircularProgress color="inherit" />
                    :
                    'Iniciar sesión'
                }

              </Button>
            </div>

            <p className="text-center">¿No tienes cuenta? <Link className="link text-[14px] font-
[600] text-primary" to="/register"> Regístrate</Link></p>


            <p className="text-center font-[500]">O continúa con tu cuenta social</p>

            <Button className="flex gap-3 w-full !bg-[#f1f1f1] btn-lg !text-black"
              onClick={authWithGoogle}>
              <FcGoogle className="text-[20px]" /> Iniciar sesión con Google</Button>

          </form>
        </div>
      </div>
    </section>
  );
};

export default Login;
```

1.3.3.6 MyAccount

1.3.3.6.1 addAddress.jsx

```
import React, { useState, useEffect } from 'react'
import Radio from '@mui/material/Radio';
import RadioGroup from '@mui/material/RadioGroup';
import FormControlLabel from '@mui/material/FormControlLabel';
import FormControl from '@mui/material/FormControl';
import FormLabel from '@mui/material/FormLabel';
import { useContext } from 'react';
import { MyContext } from '../../App';
import TextField from '@mui/material/TextField';

import { PhoneInput } from 'react-international-phone';
import 'react-international-phone/style.css';
import 'react-international-phone/style.css';
import { Button } from '@mui/material';
import { deleteData, editData, fetchDataFromApi, postData } from '../../utils/api';
import CircularProgress from '@mui/material/CircularProgress';

const AddAddress = () => {

    const [phone, setPhone] = useState('');
    const [addressType, setAddressType] = useState("");

    const [formFields, setFormsFields] = useState({
        address_line1: '',
```

```
        city: '',
        state: '',
        pincode: '',
        country: '',
        mobile: '',
        userId: '',
        addressType: '',
        landmark: ''
    });

    const [isLoading, setIsLoading] = useState(false);

    const context = useContext(MyContext);

    useEffect(() => {
        if (context?.userData?._id !== undefined) {


            setFormsFields((prevState) => ({
                ...prevState,
                userId: context?.userData?._id
            }))

        }

    }, [context?.userData]);


    const onChangeInput = (e) => {
        const { name, value } = e.target;
        setFormsFields(() => {
            return {
                ...formFields,
                [name]: value
            }
        })

    }



    const handleChangeAddressType = (event) => {
        setAddressType(event.target.value)
        setFormsFields(() => ({
            ...formFields,
            addressType: event.target.value
        }))
    }



    useEffect(() => {

        if (context?.addressMode === "edit") {
            fetchAddress(context?.addressId)
        }

    }, [context?.addressMode]);


    const handleSubmit = (e) => {
        e.preventDefault();
        if (formFields.address_line1 === "") {
            context.alertBox("error", "Por favor ingresa la Dirección (línea 1)");
            return false
        }


        if (formFields.city === "") {
            context.alertBox("error", "Por favor ingresa tu ciudad");
```

```
        return false
    }


    if (formFields.state === "") {
        context.alertBox("error", "Por favor ingresa tu departamento");
        return false
    }


    if (formFields.pincode === "") {
        context.alertBox("error", "Por favor ingresa tu código postal");
        return false
    }


    if (formFields.country === "") {
        context.alertBox("error", "Por favor ingresa tu país");
        return false
    }


    if (phone === "" || phone?.length < 5) {
        context.alertBox("error", "Por favor ingresa tu número de celular de 10 dígitos");
        return false
    }

    if (formFields.landmark === "") {
        context.alertBox("error", "Por favor ingresa un punto de referencia");
        return false
    }

    if (formFields.addressType === "") {
        context.alertBox("error", "Por favor selecciona el tipo de dirección");
        return false
    }



    if (context?.addressMode === "add") {
        setIsLoading(true);
        postData(`/api/address/add`, formFields, { withCredentials: true }).then((res) => {
            console.log(res)
            if (res?.error !== true) {

                context.alertBox("success", res?.message);
                setTimeout(() => {
                    context.setOpenAddressPanel(false)
                    setIsLoading(false);
                }, 500)


                context.getUserDetails();

                setFormsFields({
                    address_line1: '',
                    city: '',
                    state: '',
                    pincode: '',
                    country: '',
                    mobile: '',
                    userId: '',
                    addressType: '',
                    landmark: ''
                })

                setAddressType("");
                setPhone("");
```

```
                } else {
                    context.alertBox("error", res?.message);
                    setIsLoading(false);
                }

            })
        }



        if (context?.addressMode === "edit") {
            setIsLoading(true);
            editData(`/api/address/${context?.addressId}`, formFields, { withCredentials: true
}).then((res) => {

                fetchDataFromApi(`/api/address/get?userId=${context?.userData?._id}`).then((res) =>
{
                    setTimeout(() => {
                        setIsLoading(false);
                        context.setOpenAddressPanel(false);
                    }, 500)
                    context?.getUserDetails(res.data);

                    setFormsFields({
                        address_line1: '',
                        city: '',
                        state: '',
                        pincode: '',
                        country: '',
                        mobile: '',
                        userId: '',
                        addressType: '',
                        landmark: ''
                    })

                    setAddressType("");
                    setPhone("");
                })
            })
        }


    }



    const fetchAddress = (id) => {

        fetchDataFromApi(`/api/address/${id}`).then((res) => {

            setFormsFields({
                address_line1: res?.address?.address_line1,
                city: res?.address?.city,
                state: res?.address?.state,
                pincode: res?.address?.pincode,
                country: res?.address?.country,
                mobile: res?.address?.mobile,
                userId: res?.address?.userId,
                addressType: res?.address?.addressType,
                landmark: res?.address?.landmark
            })

            const ph = `"${res?.address?.mobile}"`
            setPhone(ph)
            setAddressType(res?.address?.addressType)

        })

    }
```

```
return (
    <form className="p-8 py-3 pb-8 px-4" onSubmit={handleSubmit}>
        <div className="col w-[100%] mb-4">
            <TextField
                className="w-full"
                label="Dirección (línea 1)"
                variant="outlined"
                size="small"
                name="address_line1"
                onChange={onChangeInput} value={formFields.address_line1}
            />
        </div>


        <div className="col w-[100%] mb-4">
            <TextField
                className="w-full"
                label="Ciudad"
                variant="outlined"
                size="small"
                name="city" onChange={onChangeInput} value={formFields.city}
            />
        </div>

        <div className="col w-[100%] mb-4">
            <TextField
                className="w-full"
                label="Departamento"
                variant="outlined"
                size="small"
                name="state" onChange={onChangeInput} value={formFields.state}
            />
        </div>

        <div className="col w-[100%] mb-4">
            <TextField
                className="w-full"
                label="Código postal"
                variant="outlined"
                size="small"
                name="pincode" onChange={onChangeInput} value={formFields.pincode}
            />
        </div>

        <div className="col w-[100%] mb-4">
            <TextField
                className="w-full"
                label="País"
                variant="outlined"
                size="small"
                name="country" onChange={onChangeInput} value={formFields.country}
            />
        </div>


        <div className="col w-[100%] mb-4">
            <PhoneInput
                defaultCountry="bo"
                value={phone}
                onChange={(phone) => {
                    setPhone(phone);
                    setFormsFields((prevState) => ({
                        ...prevState,
                        mobile: phone
                    }))
                }}
            />
        </div>
```

```
            <div className="col w-[100%] mb-4">
                <TextField
                    className="w-full"
                    label="Punto de referencia"
                    variant="outlined"
                    size="small"
                    name="landmark" onChange={onChangeInput} value={formFields.landmark}
                />
            </div>


            <div className="flex gap-5 pb-5 flex-col">
                <FormControl>
                    <FormLabel id="demo-row-radio-buttons-group-label">Tipo de
dirección</FormLabel>
                    <RadioGroup
                        row
                        aria-labelledby="demo-row-radio-buttons-group-label"
                        name="row-radio-buttons-group"
                        className="flex items-center gap-5"
                        value={addressType}
                        onChange={handleChangeAddressType}
                    >
                        <FormControlLabel value="Home" control={<Radio />} label="Casa" />
                        <FormControlLabel value="Office" control={<Radio />} label="Oficina" />

                    </RadioGroup>
                </FormControl>
            </div>


            <div className='flex items-center gap-5'>
                <Button type="submit" className="btn-org btn-lg w-full flex gap-2 items-center">
                    {
                        isLoading === true ?
                            <CircularProgress color="inherit" />
                            :

                            'Guardar'

                    }
                </Button>

            </div>
        </form>
    )
}

export default AddAddress
```

1.3.3.6.2 address.jsx

```
import React from 'react'
import AccountSidebar from '../../components/AccountSidebar';
import { useContext } from 'react';
import { MyContext } from '../../App';

import { useState } from 'react';

import { useEffect } from 'react';
import { deleteData, fetchDataFromApi } from '../../utils/api';
import AddressBox from './addressBox';


const label = { inputProps: { 'aria-label': 'Radio demo' } };
```

```
const Address = () => {

    const [address, setAddress] = useState([]);

    const context = useContext(MyContext);

    useEffect(() => {
        if (context?.userData?._id !== "" && context?.userData?._id !== undefined) {

            setAddress(context?.userData?.address_details);

        }

    }, [context?.userData])


    const removeAddress = (id) => {
        deleteData(`/api/address/${id}`).then((res) => {
            fetchDataFromApi(`/api/address/get?userId=${context?.userData?._id}`).then((res) => {
                setAddress(res.data);
                context?.getUserDetails();

            })
        })
    }



    return (
        <>
            <section className="py-5 lg:py-10 w-full">
                <div className="container flex flex-col md:flex-row gap-5">
                    <div className="col1 w-full  md:w-[30%] lg:w-[20%]">
                        <AccountSidebar />
                    </div>

                    <div className="col2 w-full md:w-[70%] lg:w-[50%]">
                        <div className="card bg-white p-5 shadow-md rounded-md mb-5">
                            <div className="flex items-center pb-3">
                                <h2 className="pb-0">Dirección</h2>
                            </div>
                            <hr />


                            <div className='flex items-center justify-center p-5 rounded-md border
border-dashed border-[rgba(0,0,0,0.2)] bg-[#f1faff] hover:bg-[#e7f3f9] cursor-pointer'
                                onClick={() => {
                                    context?.setOpenAddressPanel(true);
                                    context?.setAddressMode("add");
                                }}
                            >
                                <span className='text-[14px] font-[500]'>Añadir dirección</span>
                            </div>


                            <div className="flex gap-2 flex-col mt-4">

                                {
                                    address?.length > 0 && address?.map((address, index) => {
                                        return (
                                            <AddressBox address={address} key={index}
removeAddress={removeAddress} />
                                        )
                                    })
                                }

                            </div>
```

```
                        </div>



                    </div>
                </div>
            </section>

        </>
    )
}


export default Address;
```

1.3.3.6.3 addressBox.jsx

```
import React, { useContext, useState } from 'react'
import IconButton from '@mui/material/IconButton';
import Menu from '@mui/material/Menu';
import MenuItem from '@mui/material/MenuItem';
import { HiOutlineDotsVertical } from "react-icons/hi";
import { MyContext } from '../../App';

const ITEM_HEIGHT = 48;

const AddressBox = (props) => {
    const [anchorEl, setAnchorEl] = useState(null);
    const open = Boolean(anchorEl);

    const context = useContext(MyContext);

    const handleClick = (event) => {
        setAnchorEl(event.currentTarget);
    };
    const handleClose = () => {
        setAnchorEl(null);
    };

    const removeAddress=(id)=>{
        setAnchorEl(null);
        props.removeAddress(id)
    }

    const editAddress=(id)=>{
        setAnchorEl(null);
        context?.setOpenAddressPanel(true);
        context?.setAddressMode("edit");
        context?.setAddressId(id);
    }

    return (
        <div className='group relative border border-dashed border-[rgba(0,0,0,0.2)] addressBox w-
full  bg-[#fafafa] p-4 rounded-md cursor-pointer'>

            <span className="inline-block p-1 bg-[#e7e7e7] text-[12px] rounded-
sm">{props?.address?.addressType}</span>

            <h4 className="pt-2 flex items-center gap-4 text-[14px]">
                <span>{context?.userData?.name} </span>
                <span>+{props?.address?.mobile}</span>
            </h4>

            <span className="pt-0 text-[13px] block w-100">
                {
                    props?.address?.address_line1 + " " +
                    props?.address?.city + " " +
```

```
                    props?.address?.country + " " +
                    props?.address?.state + " " +
                    props?.address?.pincode
                }
            </span>



            <div className="absolute top-[20px] right-[20px]">
                <IconButton
                    aria-label="more"
                    id="long-button"
                    aria-controls={open ? 'long-menu' : undefined}
                    aria-expanded={open ? 'true' : undefined}
                    aria-haspopup="true"
                    onClick={handleClick}
                >
                    <HiOutlineDotsVertical />
                </IconButton>


                <Menu
                    id="long-menu"
                    MenuListProps={{
                        'aria-labelledby': 'long-button',
                    }}
                    anchorEl={anchorEl}
                    open={open}
                    onClose={handleClose}
                    slotProps={{
                        paper: {
                            style: {
                                maxHeight: ITEM_HEIGHT * 4.5,
                                width: '20ch',
                            },
                        },
                    }}
                >
                    <MenuItem onClick={()=>editAddress(props?.address?._id)}>
                        Edit
                    </MenuItem>
                    <MenuItem onClick={()=>removeAddress(props?.address?._id)}>
                        Delete
                    </MenuItem>
                </Menu>


            </div>


        </div>
    )
}

export default AddressBox
```

1.3.3.6.4 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import { Button } from "@mui/material";
import TextField from "@mui/material/TextField";
import AccountSidebar from "../../components/AccountSidebar";
import { MyContext } from "../../App";
import { useNavigate } from "react-router-dom";
import { editData, postData } from "../../utils/api";
import CircularProgress from '@mui/material/CircularProgress';
import { Collapse } from "react-collapse";
import { PhoneInput } from 'react-international-phone';
import 'react-international-phone/style.css';
```

```
const MyAccount = () => {

  const [isLoading, setIsLoading] = useState(false);
  const [isLoading2, setIsLoading2] = useState(false);
  const [userId, setUserId] = useState("");
  const [isChangePasswordFormShow, setisChangePasswordFormShow] = useState(false);
  const [phone, setPhone] = useState('');

  const [formFields, setFormsFields] = useState({
    name: '',
    email: '',
    mobile: ''
  });

  const [changePassword, setChangePassword] = useState({
    email: '',
    oldPassword: '',
    newPassword: '',
    confirmPassword: ''
  });

  const context = useContext(MyContext);
  const history = useNavigate();

  useEffect(() => {
    const token = localStorage.getItem("accessToken");

    if (token === null) {
      history("/");
    }


  }, [context?.isLogin])


  useEffect(() => {
    if (context?.userData?._id !== "" && context?.userData?._id !== undefined) {
      setUserId(context?.userData?._id);
      setTimeout(() => {
        setFormsFields({
          name: context?.userData?.name,
          email: context?.userData?.email,
          mobile: context?.userData?.mobile
        })
      }, 200);
      setPhone(
        typeof context?.userData?.mobile === "string" && context?.userData?.mobile.trim() !== ""
          ? context.userData.mobile
          : ""
      );


      setChangePassword({
        email: context?.userData?.email
      })
    }

  }, [context?.userData])



  const onChangeInput = (e) => {
    const { name, value } = e.target;
    setFormsFields(() => {
      return {
        ...formFields,
        [name]: value
      }
```

```
  })

  setChangePassword(() => {
    return {
      ...formFields,
      [name]: value
    }
  })


}


const valideValue = Object.values(formFields).every(el => el)

const handleSubmit = (e) => {
  e.preventDefault();

  setIsLoading(true);

  if (formFields.name === "") {
    context.alertBox("error", "Please enter full name");
    return false
  }


  if (formFields.email === "") {
    context.alertBox("error", "Please enter email id");
    return false
  }


  if (formFields.mobile === "") {
    context.alertBox("error", "Please enter mobile number");
    return false
  }


  editData(`/api/user/${userId}`, formFields, { withCredentials: true }).then((res) => {
    console.log(res)
    if (res?.error !== true) {
      setIsLoading(false);
      context.alertBox("success", res?.data?.message);

    } else {
      context.alertBox("error", res?.data?.message);
      setIsLoading(false);
    }

  })


}

const valideValue2 = Object.values(formFields).every(el => el)



const handleSubmitChangePassword = (e) => {
  e.preventDefault();

  setIsLoading2(true);

  if (changePassword.oldPassword === "") {
    context.alertBox("error", "Please enter old password");
    return false
  }


  if (changePassword.newPassword === "") {
```

```
      context.alertBox("error", "Please enter new password");
      return false
    }


    if (changePassword.confirmPassword === "") {
      context.alertBox("error", "Please enter confirm password");
      return false
    }

    if (changePassword.confirmPassword !== changePassword.newPassword) {
      context.alertBox("error", "password and confirm password not match");
      return false
    }


    postData(`/api/user/reset-password`, changePassword, { withCredentials: true }).then((res) => {

      if (res?.error !== true) {
        setIsLoading2(false);
        context.alertBox("success", res?.message);
      } else {
        context.alertBox("error", res?.message);
        setIsLoading2(false);
      }

    })


  }

  return (
    <section className="py-3 lg:py-10 w-full">
      <div className="container flex flex-col lg:flex-row gap-5">
        <div className="w-full lg:w-[20%]">

          <AccountSidebar />
        </div>

        <div className="col2 w-full lg:w-[50%]">
          <div className="card bg-white p-5 shadow-md rounded-md mb-5">
            <div className="flex items-center pb-3">
              <h2 className="pb-0">Mi perfil</h2>
              <Button class="!ml-auto" onClick={() =>
setisChangePasswordFormShow(!isChangePasswordFormShow)}>Cambiar contraseña</Button>
            </div>
            <hr />

            <form class="mt-8" onSubmit={handleSubmit}>
              <div class="grid grid-cols-1 sm:grid-cols-2 gap-5 ">
                <div class="col">
                  <TextField
                    label="Full Name"
                    variant="outlined"
                    size="small"
                    class="w-full"
                    name="name"
                    value={formFields.name || ""}
                    disabled={isLoading === true ? true : false}
                    onChange={onChangeInput}
                  />
                </div>

                <div class="col">
                  <TextField
                    type="email"
                    label="Email"
                    variant="outlined"
                    size="small"
```

```
            className="w-full"
            name="email"
            value={formFields.email || ""}
            disabled={true}
            onChange={onChangeInput}
          />
        </div>



        <div className="col">
          <PhoneInput
            defaultCountry="bo"
            value={phone}
            disabled={isLoading === true ? true : false}
            onChange={(phone) => {
              setPhone(phone);
              setFormsFields({
                mobile: phone
              })
            }}
          />

        </div>

      </div>


      <br />

      <div className="flex items-center gap-4">
        <Button type="submit" disabled={!valideValue} className="btn-org btn-sm w-[150px]">
          {
            isLoading === true ? <CircularProgress color="inherit" />
              :
              'Update Profile'
          }
        </Button>

      </div>
    </form>
  </div>




  <Collapse isOpened={isChangePasswordFormShow}>
    <div className="card bg-white p-5 shadow-md rounded-md">
      <div className="flex items-center pb-3">
        <h2 className="pb-0">Cambiar contraseña</h2>
      </div>
      <hr />


      <form className="mt-8" onSubmit={handleSubmitChangePassword}>
        <div className="grid grid-cols-1 sm:grid-cols-2 gap-5">

          {
            context?.userData?.signUpWithGoogle === false &&
            <div className="col">
              <TextField
                label="Old Password"
                variant="outlined"
                size="small"
                className="w-full"
                name="oldPassword"
                value={changePassword.oldPassword || ""}
                disabled={isLoading2 === true ? true : false}
```

```
                onChange={onChangeInput}
              />
            </div>
          }



          <div className="col">
            <TextField
              type="text"
              label="New Password"
              variant="outlined"
              size="small"
              className="w-full"
              name="newPassword"
              value={changePassword.newPassword || ""}
              onChange={onChangeInput}
            />
          </div>

          <div className="col">
            <TextField
              label="Confirm Password"
              variant="outlined"
              size="small"
              className="w-full"
              name="confirmPassword"
              value={changePassword.confirmPassword || ""}
              onChange={onChangeInput}
            />
          </div>


        </div>


        <br />

        <div className="flex items-center gap-4">
          <Button type="submit" className="btn-org btn-sm w-[200px]">
            {
              isLoading2 === true ? <CircularProgress color="inherit" />
                :
                'Change Password'
            }
          </Button>

        </div>
      </form>



    </div>
  </Collapse>



  </div>
 </div>
</section>
);
};

export default MyAccount;
```

1.3.3.7 MyList

1.3.3.7.1 index.jsx

```
import React, { useContext, useEffect } from "react";
import MyListItems from "./myListItems";
import AccountSidebar from "../../components/AccountSidebar";
import { MyContext } from "../../App";
import Button from "@mui/material/Button";
import { Link } from "react-router-dom";

const MyList = () => {
  const context = useContext(MyContext);
  const items = Array.isArray(context?.myListData) ? context.myListData : [];

  useEffect(() => {
    window.scrollTo(0, 0);
    // ⭐ fuerza cargar en BOB
    context?.getMyListData?.("BOB");
  }, []);

  return (
    <section className="py-4 lg:py-6 pb-20 w-full">
      <div className="container flex flex-col md:flex-row gap-5">
        <div className="col1 w-full md:w-[20%] hidden lg:block">
          <AccountSidebar />
        </div>

        <div className="col2 w-full lg:w-[70%]">
          <div className="shadow-md rounded-md bg-white">
            <div className="py-5 px-3 border-b border-[rgba(0,0,0,0.1)]">
              <h2>Mi Lista</h2>
              <p className="mt-0 mb-0">
                Tienes{" "}
                <span className="font-bold text-primary">{items.length}</span>{" "}
                productos en Mi Lista
              </p>
            </div>

            {items.length > 0 ? (
              items.map((item, index) => (
                <MyListItems
                  key={item?._id || item?.productId || index}
                  item={item}
                />
              ))
            ) : (
              <div className="flex items-center justify-center flex-col py-10 px-3 gap-5">
                <img src="/mylistempty.png" className="w-[100px]" alt="Mi lista vacía" />
                <h3>Mi lista está actualmente vacía</h3>
                <Link to="/">
                  <Button className="btn-org btn-sm">Continuar comprando</Button>
                </Link>
              </div>
            )}
          </div>
        </div>
      </div>
    </section>
  );
};

export default MyList;
```

1.3.3.7.2 myListItems.jsx

```
import React, { useContext } from "react";
import PropTypes from "prop-types";
import { Link } from "react-router-dom";
```

```
import Rating from "@mui/material/Rating";
import { IoCloseSharp } from "react-icons/io5";
import { MyContext } from "../../App";
import { deleteData } from "../../utils/api";
import { formatPrice } from "../../utils/formatPrice";

const MyListItems = ({ item }) => {
  const context = useContext(MyContext);

  const removeItem = async (id) => {
    await deleteData(`/api/myList/${id}`);
    context?.alertBox("success", "Product remove from My List");
    // ⭐ vuelve a cargar en BOB para mantener la vista coherente
    context?.getMyListData?.("BOB");
  };

  // Moneda/precios (prioriza lo que manda el API para visualización)
  const currency = String(item?.displayCurrency ?? item?.currency ?? "BOB").toUpperCase();
  const price = item?.displayPrice ?? item?.price ?? 0;
  const oldPrice = item?.displayOldPrice ?? item?.oldPrice ?? 0;
  const ratingVal = Number.isFinite(Number(item?.rating)) ? Number(item?.rating) : 0;

  const title = item?.productTitle || "";
  const shortTitle = title.length > 80 ? title.slice(0, 80) + "..." : title;

  return (
    <div className="cartItem w-full p-3 flex items-center gap-4 pb-5 border-b border-
[rgba(0,0,0,0.1)]">
      <div className="img w-[30%] sm:w-[15%] h-[150px] rounded-md overflow-hidden">
        <Link to={`/product/${item?.productId}`} className="group">
          <img
            src={item?.image}
            alt={title}
            className="w-full h-full object-cover group-hover:scale-105 transition-all"
          />
        </Link>
      </div>

      <div className="info w-full md:w-[85%] relative">
        <IoCloseSharp
          className="cursor-pointer absolute top-[0px] right-[0px] text-[22px] link transition-all"
          onClick={() => removeItem(item?._id)}
          aria-label="Eliminar de Mi Lista"
        />

        <span className="text-[13px]">{item?.brand}</span>

        <h3 className="text-[13px] sm:text-[15px]">
          <Link to={`/product/${item?.productId}`} className="link">
            {shortTitle}
          </Link>
        </h3>

        <Rating name="read-only" value={ratingVal} size="small" readOnly />

        <div className="flex items-center gap-4 mt-2 mb-2">
          <span className="price text-[14px] font-[600]">
            {formatPrice(price, currency)}
          </span>

          {Number(oldPrice) > 0 && (
            <span className="oldPrice line-through text-gray-500 text-[14px] font-[500]">
              {formatPrice(oldPrice, currency)}
            </span>
          )}

          {Number(item?.discount) > 0 && (
            <span className="price text-primary text-[14px] font-[600]">
              {Number(item.discount)}% OFF
```

```
            </span>
          )}
        </div>
      </div>
    </div>
  );
};

MyListItems.propTypes = {
  item: PropTypes.shape({
    _id: PropTypes.string.isRequired,
    productId: PropTypes.string.isRequired,
    productTitle: PropTypes.string,
    image: PropTypes.string,
    brand: PropTypes.string,
    rating: PropTypes.oneOfType([PropTypes.number, PropTypes.string]),
    discount: PropTypes.oneOfType([PropTypes.number, PropTypes.string]),
    // precios base
    price: PropTypes.oneOfType([PropTypes.number, PropTypes.string]),
    oldPrice: PropTypes.oneOfType([PropTypes.number, PropTypes.string]),
    currency: PropTypes.string,
    // precios calculados opcionales
    displayPrice: PropTypes.oneOfType([PropTypes.number, PropTypes.string]),
    displayOldPrice: PropTypes.oneOfType([PropTypes.number, PropTypes.string]),
    displayCurrency: PropTypes.string,
  }).isRequired,
};

export default MyListItems;
```

1.3.3.8 Orders

1.3.3.8.1 falied.jsx

```
import React from 'react';
import Button from "@mui/material/Button";
import { Link } from "react-router-dom";

export const OrderFailed = () => {
    return (
        <section className='w-full p-10 py-8 lg:py-20 flex items-center justify-center flex-col
gap-2'>
            <img src="/delete.png" className="w-[70px] sm:w-[120px]" />
            <h3 className='mb-0 text-[20px] sm:text-[25px]'>Tu pedido no se completó</h3>
            <p className='mt-0 text-center'>Tu pedido falló por alguna razón</p>
            <Link to="/">
                <Button className="btn-org btn-border">Volver al inicio</Button>
            </Link>
        </section>
    )
}
```

1.3.3.8.2 index.jsx

```
import React, { useEffect, useState } from "react";
import AccountSidebar from "../../components/AccountSidebar";
import { Button } from "@mui/material";
import { FaAngleDown } from "react-icons/fa6";
import Badge from "../../components/Badge";
import { FaAngleUp } from "react-icons/fa6";
import { fetchDataFromApi } from "../../utils/api";
import Pagination from "@mui/material/Pagination";
import { formatPrice } from "../../utils/formatPrice"; // 👈 NUEVO

const Orders = () => {
  const [isOpenOrderdProduct, setIsOpenOrderdProduct] = useState(null);
  const [orders, setOrders] = useState([]);

  const [page, setPage] = useState(1);
```

```
const isShowOrderdProduct = (index) => {
  if (isOpenOrderdProduct === index) {
    setIsOpenOrderdProduct(null);
  } else {
    setIsOpenOrderdProduct(index);
  }
};

useEffect(() => {
  fetchDataFromApi(`/api/order/order-list/orders?page=${page}&limit=5`).then((res) => {
    if (res?.error === false) {
      setOrders(res);
    }
  });
}, [page]);

// --- Totales por pedido: BOB principal (~USD si hay tasa) ---
const pickOrderTotals = (order) => {
  const R = Number(order?.fx?.rate); // R = BOB por 1 USDT
  const hasR = Number.isFinite(R) && R > 0;

  const totalBob = Number(order?.totalBob);
  const totalUsd = Number(order?.totalUsd);
  const legacyBob = Number(order?.totalAmt); // compat historial, asumido BOB

  if (Number.isFinite(totalBob) && totalBob > 0) {
    return {
      mainValue: totalBob, mainCur: "BOB",
      altValue: Number.isFinite(totalUsd) ? totalUsd : (hasR ? totalBob / R : null),
      altCur: "USD",
      rate: hasR ? R : null
    };
  }
  if (Number.isFinite(totalUsd) && totalUsd > 0) {
    return {
      mainValue: totalUsd, mainCur: "USD",
      altValue: Number.isFinite(totalBob) ? totalBob : (hasR ? totalUsd * R : null),
      altCur: "BOB",
      rate: hasR ? R : null
    };
  }
  if (Number.isFinite(legacyBob) && legacyBob > 0) {
    return {
      mainValue: legacyBob, mainCur: "BOB",
      altValue: hasR ? legacyBob / R : null,
      altCur: "USD",
      rate: hasR ? R : null
    };
  }
  return { mainValue: 0, mainCur: "BOB", altValue: null, altCur: "USD", rate: null };
};

// --- Por línea: unitario y subtotal (BOB principal, (~USD) alterno) ---
const pickLineAmounts = (item, orderRate) => {
  const R = Number(item?.fx?.rate ?? orderRate);
  const hasR = Number.isFinite(R) && R > 0;

  const unitBob = Number(item?.unitPriceBob);
  const unitUsd = Number(item?.unitPriceUsd);
  const legacyUnitBob = Number(item?.price); // compat viejo

  // BOB como principal
  const mainUnit = Number.isFinite(unitBob)
    ? unitBob
    : Number.isFinite(legacyUnitBob)
      ? legacyUnitBob
      : Number.isFinite(unitUsd) && hasR
        ? unitUsd * R
        : 0;
```

```
    const altUnit = Number.isFinite(unitUsd) ? unitUsd : (hasR ? mainUnit / R : null);

    const qty = Number(item?.quantity) || 0;
    const mainSub = mainUnit * qty;
    const altSub = altUnit != null ? altUnit * qty : null;

    return { mainUnit, altUnit, mainSub, altSub, mainCur: "BOB", altCur: "USD" };
  };

  return (
    <section className="py-5 lg:py-10 w-full">
      <div className="container flex flex-col lg:flex-row gap-5">
        <div className="col1 w-[20%] hidden lg:block">
          <AccountSidebar />
        </div>

        <div className="col2 w-full lg:w-[80%]">
          <div className="shadow-md rounded-md bg-white">
            <div className="py-5 px-5 border-b border-[rgba(0,0,0,0.1)]">
              <h2>Mis pedidos</h2>
              <p className="mt-0 mb-0">
                Hay <span className="font-bold text-primary">{orders?.data?.length}</span>{" "}
                pedidos
              </p>

              <div className="relative overflow-x-auto mt-5 bg-white">
                <table className="w-full text-sm text-left rtl:text-right text-gray-700">
                  <thead className="text-xs text-gray-700 uppercase bg-gray-100">
                    <tr>
                      <th scope="col" className="px-6 py-3"> </th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">ID de pedido</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">ID de pago</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">Nombre</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">Número de
teléfono</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">Dirección</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">Código postal</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">Importe total</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">Correo
electrónico</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">ID de usuario</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">Estado del
pedido</th>
                      <th scope="col" className="px-6 py-3 whitespace-nowrap">Fecha</th>
                    </tr>
                  </thead>

                  <tbody>
                    {orders?.data?.length !== 0 && orders?.data?.map((order, index) => {
                      const t = pickOrderTotals(order);
                      return (
                        <React.Fragment key={order?._id || index}>
                          <tr className="bg-white border-b border-gray-200">
                            <td className="px-6 py-4 font-[500]">
                              <Button
                                className="!w-[35px] !h-[35px] !min-w-[35px] !rounded-full !bg-
[#f1f1f1]"
                                onClick={() => isShowOrderdProduct(index)}
                              >
                                {isOpenOrderdProduct === index
                                  ? <FaAngleUp className="text-[16px] text-[rgba(0,0,0,0.7)]" />
                                  : <FaAngleDown className="text-[16px] text-[rgba(0,0,0,0.7)]" />}
                              </Button>
                            </td>

                            <td className="px-6 py-4 font-[500]"><span className="text-
primary">{order?._id}</span></td>
                            <td className="px-6 py-4 font-[500]">
```

```
                                <span className="text-primary whitespace-nowrap text-[13px]">
                                  {order?.paymentId ? order?.paymentId : "PAGO CONTRA ENTREGA"}
                                </span>
                              </td>
                              <td className="px-6 py-4 font-[500] whitespace-
nowrap">{order?.userId?.name}</td>
                              <td className="px-6 py-4 font-
[500]">{order?.delivery_address?.mobile}</td>

                              <td className="px-6 py-4 font-[500]">
                                <span className="inline-block text-[13px] font-[500] p-1 bg-[#f1f1f1]
rounded-md">
                                  {order?.delivery_address?.addressType}
                                </span>
                                <span className="block w-[400px]">
                                  {(order?.delivery_address?.address_line1 || "") + " " +
                                    (order?.delivery_address?.city || "") + " " +
                                    (order?.delivery_address?.landmark || "") + " " +
                                    (order?.delivery_address?.state || "") + " " +
                                    (order?.delivery_address?.country || "")}
                                </span>
                              </td>

                              <td className="px-6 py-4 font-
[500]">{order?.delivery_address?.pincode}</td>

                              {/* Total (BOB principal, ~USD alterno) */}
                              <td className="px-6 py-4 font-[500] whitespace-nowrap">
                                <div className="flex flex-col">
                                  <span className="font-[600]">{formatPrice(t.mainValue,
t.mainCur)}</span>
                                  {t.altValue != null && (
                                    <span className="text-[12px] text-gray-600">
                                      (~ {formatPrice(t.altValue, t.altCur)})
                                    </span>
                                  )}
                                </div>
                              </td>

                              <td className="px-6 py-4 font-[500]">{order?.userId?.email}</td>
                              <td className="px-6 py-4 font-[500]"><span className="text-
primary">{order?.userId?._id}</span></td>
                              <td className="px-6 py-4 font-[500]"><Badge
status={order?.order_status} /></td>
                              <td className="px-6 py-4 font-[500] whitespace-
nowrap">{order?.createdAt?.split("T")[0]}</td>
                            </tr>

                            {isOpenOrderdProduct === index && (
                              <tr>
                                <td className="pl-20" colSpan="12">
                                  <div className="relative overflow-x-auto bg-white">
                                    <table className="w-full text-sm text-left rtl:text-right text-
gray-700">
                                      <thead className="text-xs text-gray-700 uppercase bg-gray-100">
                                        <tr>
                                          <th className="px-6 py-3 whitespace-nowrap">ID del
producto</th>
                                          <th className="px-6 py-3 whitespace-nowrap">Título del
producto</th>
                                          <th className="px-6 py-3 whitespace-nowrap">Imagen</th>
                                          <th className="px-6 py-3 whitespace-nowrap">Cantidad</th>
                                          <th className="px-6 py-3 whitespace-nowrap">Precio</th>
                                          <th className="px-6 py-3 whitespace-nowrap">Subtotal</th>
                                        </tr>
                                      </thead>
                                      <tbody>
                                        {order?.products?.map((item, i) => {
                                          const L = pickLineAmounts(item, t.rate);
```

```
                                        return (
                                          <tr className="bg-white border-b border-gray-200"
key={item?._id || i}>
                                            <td className="px-6 py-4 font-[500]">
                                              <span className="text-gray-600">{item?._id}</span>
                                            </td>
                                            <td className="px-6 py-4 font-[500]">
                                              <div className="w-[200px]">{item?.productTitle}</div>
                                            </td>
                                            <td className="px-6 py-4 font-[500]">
                                              <img src={item?.image} className="w-[40px] h-[40px]
object-cover rounded-md" alt={item?.productTitle || "Producto"} />
                                            </td>
                                            <td className="px-6 py-4 font-[500] whitespace-
nowrap">{item?.quantity}</td>

                                            {/* Precio unitario (BOB / ~USD) */}
                                            <td className="px-6 py-4 font-[500] whitespace-nowrap">
                                              <div className="flex flex-col">
                                                <span className="font-
[600]">{formatPrice(L.mainUnit, L.mainCur)}</span>
                                                {L.altUnit != null && (
                                                  <span className="text-[12px] text-gray-600">
                                                    (~ {formatPrice(L.altUnit, L.altCur)})
                                                  </span>
                                                )}
                                              </div>
                                            </td>

                                            {/* Subtotal (BOB / ~USD) */}
                                            <td className="px-6 py-4 font-[500] whitespace-nowrap">
                                              <div className="flex flex-col">
                                                <span className="font-
[600]">{formatPrice(L.mainSub, L.mainCur)}</span>
                                                {L.altSub != null && (
                                                  <span className="text-[12px] text-gray-600">
                                                    (~ {formatPrice(L.altSub, L.altCur)})
                                                  </span>
                                                )}
                                              </div>
                                            </td>
                                          </tr>
                                        );
                                      })}

                                      <tr>
                                        <td className="bg-gray-100" colSpan="12"></td>
                                      </tr>
                                    </tbody>
                                  </table>
                                </div>
                              </td>
                            </tr>
                          )}
                        </React.Fragment>
                      );
                    })}
                  </tbody>
                </table>
              </div>


              {orders?.totalPages > 1 && (
                <div className="flex items-center justify-center mt-10">
                  <Pagination
                    showFirstButton
                    showLastButton
                    count={orders?.totalPages}
                    page={page}
```

```
                    onChange={(e, value) => setPage(value)}
                  />
                </div>
              )}
            </div>
          </div>
        </div>
      </div>
    </section>
  );
};

export default Orders;
```

1.3.3.8.3 success.jsx

```
import React, { useContext } from 'react';
import Button from "@mui/material/Button";
import { Link } from "react-router-dom";
import { MyContext } from '../../App';

export const OrderSuccess = () => {
    const context = useContext(MyContext);
    return (
        <section className='w-full p-10 py-8 lg:py-20 flex items-center justify-center flex-col
gap-2'>
            <img src="/checked.png" className="w-[80px] sm:w-[120px]" />
            <h3 className='mb-0 text-[20px] sm:text-[25px]'>Tu pedido ha sido realizado</h3>
            <p className='mt-0 mb-0'>Gracias por tu pago.</p>
            <p className='mt-0 text-center'>La factura del pedido fue enviada a tu correo
<b>{context?.userData?.email}</b></p>
            <Link to="/">
                <Button className="btn-org btn-border">Volver al inicio</Button>
            </Link>
        </section>
    )
}
```

1.3.3.9 ProductDetails

1.3.3.9.1 index.jsx

```
import React, { useEffect, useRef, useState } from "react";
import Breadcrumbs from "@mui/material/Breadcrumbs";
import { Link, useParams } from "react-router-dom";
import { ProductZoom } from "../../components/ProductZoom";
import ProductsSlider from '../../components/ProductsSlider';
import { ProductDetailsComponent } from "../../components/ProductDetails";

import { fetchDataFromApi } from "../../utils/api";
import CircularProgress from '@mui/material/CircularProgress';
import { Reviews } from "./reviews";

export const ProductDetails = () => {

  const [activeTab, setActiveTab] = useState(0);
  const [productData, setProductData] = useState();
  const [isLoading, setIsLoading] = useState(false);
  const [reviewsCount, setReviewsCount] = useState(0);
  const [relatedProductData, setRelatedProductData] = useState([]);

  const { id } = useParams();

  const reviewSec = useRef();

  useEffect(() => {
    fetchDataFromApi(`/api/user/getReviews?productId=${id}`).then((res) => {
      if (res?.error === false) {
```

```
        setReviewsCount(res.reviews.length)
      }
    })

  }, [reviewsCount])

  useEffect(() => {
    setIsLoading(true);
    fetchDataFromApi(`/api/product/${id}`).then((res) => {
      if (res?.error === false) {
        setProductData(res?.product);


fetchDataFromApi(`/api/product/getAllProductsBySubCatId/${res?.product?.subCatId}`).then((res) => {
          if (res?.error === false) {
            const filteredData = res?.products?.filter((item) => item._id !== id);
            setRelatedProductData(filteredData)
          }
        })

        setTimeout(() => {
          setIsLoading(false);
        }, 700);
      }
    })


    window.scrollTo(0, 0)
  }, [id])


  const gotoReviews = () => {
    window.scrollTo({
      top: reviewSec?.current.offsetTop - 170,
      behavior: 'smooth',
    })

    setActiveTab(1)

  }

  return (
    <>
      <div className="py-5 hidden">
        <div className="container">
          <Breadcrumbs aria-label="breadcrumb">
            <Link
              underline="hover"
              color="inherit"
              to="/"
              className="link transition !text-[14px]"
            >
              Inicio
            </Link>
            <Link
              underline="hover"
              color="inherit"
              to="/"
              className="link transition !text-[14px]"
            >
              Moda
            </Link>

            <Link
              underline="hover"
              color="inherit"
              className="link transition !text-[14px]"
            >
              Chaqueta bomber de satén recortada
```

```
            </Link>
          </Breadcrumbs>
        </div>
      </div>



      <section className="bg-white py-5">
        {
          isLoading === true ?
            <div className="flex items-center justify-center min-h-[300px]">
              <CircularProgress />
            </div>


            :


            <>
              <div className="container flex gap-8 flex-col lg:flex-row items-start lg:items-
center">
                <div className="productZoomContainer w-full lg:w-[40%]">
                  <ProductZoom images={productData?.images} />
                </div>

                <div className="productContent w-full lg:w-[60%] pr-2 pl-2 lg:pr-10 lg:pl-10">
                  <ProductDetailsComponent item={productData} reviewsCount={reviewsCount}
gotoReviews={gotoReviews} />
                </div>
              </div>

              <div className="container pt-10">
                <div className="flex items-center gap-8 mb-5">
                  <span
                    className={`link text-[17px] cursor-pointer font-[500] ${activeTab === 0 &&
"text-primary"
                      }`}
                    onClick={() => setActiveTab(0)}
                  >
                    Descripción
                  </span>


                  <span
                    className={`link text-[17px] cursor-pointer font-[500] ${activeTab === 1 &&
"text-primary"
                      }`}
                    onClick={() => setActiveTab(1)}
                    ref={reviewSec}
                  >
                    Reseñas ({reviewsCount})
                  </span>
                </div>

                {activeTab === 0 && (
                  <div className="shadow-md w-full py-5 px-8 rounded-md text-[14px]">
                    {
                      productData?.description
                    }
                  </div>
                )}


                {activeTab === 1 && (
                  <div className="shadow-none lg:shadow-md w-full sm:w-[80%] py-0  lg:py-5 px-0
lg:px-8 rounded-md">
                    {
                      productData?.length !== 0 && <Reviews productId={productData?._id}
setReviewsCount={setReviewsCount} />
```

```
                    }

                  </div>
                )}
              </div>

              {
                relatedProductData?.length !== 0 &&
                <div className="container pt-8">
                  <h2 className="text-[20px] font-[600] pb-0">Productos relacionados</h2>
                  <ProductsSlider items={6} data={relatedProductData} />
                </div>
              }


            </>

        }




      </section>
    </>
  );
};
```

1.3.3.9.2 reviews.jsx

```
import React, { useContext, useEffect, useState } from 'react'
import Rating from "@mui/material/Rating";
import Button from "@mui/material/Button";
import TextField from "@mui/material/TextField";
import { MyContext } from '../../App';
import { fetchDataFromApi, postData } from '../../utils/api';
import CircularProgress from '@mui/material/CircularProgress';
export const Reviews = (props) => {

    const [reviews, setReviews] = useState({
        image: '',
        userName: '',
        review: '',
        rating: 1,
        userId: '',
        productId: ''
    });

    const [loading, setLoading] = useState(false);

    const [reviewsData, setReviewsData] = useState([])

    const context = useContext(MyContext);

    useEffect(() => {
        setReviews(() => ({
            ...reviews,
            image: context?.userData?.avatar,
            userName: context?.userData?.name,
            userId: context?.userData?._id,
            productId: props?.productId
        }))

        getReviews();
    }, [context?.userData, props]);


    const onChangeInput = (e) => {
        setReviews(() => ({
            ...reviews,
```

```
            review: e.target.value
        }))
    }


    const addReview = (e) => {
        e.preventDefault();

        if (reviews?.review !== "") {
            setLoading(true);
            postData("/api/user/addReview", reviews).then((res) => {
                if (res?.error === false) {
                    context.alertBox("success", res?.message);
                    setReviews(() => ({
                        ...reviews,
                        review: '',
                        rating: 1
                    }))

                    setLoading(false);
                    getReviews();

                } else {
                    context.alertBox("error", res?.message);
                }
            })
        }
        else {
            context.alertBox("error", "Por favor añade una reseña");
        }


    }



    const getReviews = () => {
        fetchDataFromApi(`/api/user/getReviews?productId=${props?.productId}`).then((res) => {
            if (res?.error === false) {
                setReviewsData(res.reviews)
                props.setReviewsCount(res.reviews.length)
            }
        })
    }

    return (
        <div className="w-full productReviewsContainer">
            <h2 className="text-[16px] lg:text-[18px]">Preguntas y respuestas de clientes</h2>

            {
                reviewsData?.length !== 0 &&
                <div className="reviewScroll w-full max-h-[300px] overflow-y-scroll overflow-x-
hidden mt-5 pr-5">
                    {
                        reviewsData?.map((review, index) => {
                            return (
                                <div key={index} className="review pt-5 pb-5 border-b border-
[rgba(0,0,0,0.1)] w-full flex items-center justify-between">
                                    <div className="info w-[80%] flex items-center gap-3">
                                        <div className="img w-[60px] h-[60px] overflow-hidden
rounded-full">

                                            {
                                                review?.image !== "" && review?.image !== null ?
                                                    <img
                                                        src={review?.image}
                                                        className="w-full"
                                                    />
```

```
                                                    :
                                                    <img
                                                        src={"/user.jpg"}
                                                        className="w-full"
                                                    />
                                                }

                                            </div>

                                            <div className="w-[80%]">
                                                <h4 className="text-[16px]">{review?.userName}</h4>
                                                <h5 className="text-[13px] mb-
0">{review?.createdAt?.split("T")[0]}</h5>
                                                <p className="mt-0 mb-0 text-[13px]">
                                                    {review?.review}
                                                </p>
                                            </div>
                                        </div>

                                        <div class="">
                                            <Rating name="size-small" size="small"
value={review?.rating} readOnly />
                                        </div>
                                    </div>)
                                })
                            }
                        </div>
                    }


                    <br />

                    <div className="reviewForm bg-[#fafafa] p-4 rounded-md">
                        <h2 className="text-[18px]">Agregar una reseña</h2>

                        <form className="w-full mt-5" onSubmit={addReview}>
                            <TextField
                                id="outlined-multiline-flexible"
                                label="Escribe una reseña..."
                                className="w-full"
                                onChange={onChangeInput}
                                name="review"
                                multiline
                                rows={5}
                                value={reviews.review}
                            />

                            <br />
                            <br />
                            <Rating name="size-small" value={reviews.rating} onChange={(event, newValue) =>
{
                                setReviews(() => ({
                                    ...reviews,
                                    rating: newValue
                                }))
                            }} />

                            <div className="flex items-center mt-5">


                                <Button type="submit" className="btn-org flex gap-2">

                                    {
                                        loading === true && <CircularProgress size={15} />
                                    }
                                    Enviar reseña</Button>
                            </div>
                        </form>
                    </div>
```

```
        </div>
    )
}
```

1.3.3.10 ProductListing

1.3.3.10.1 index.jsx

```
import React, { useContext, useEffect, useState } from 'react'
import { Sidebar } from "../../components/Sidebar";
import Breadcrumbs from "@mui/material/Breadcrumbs";
import ProductItem from "../../components/ProductItem";
import ProductItemListView from "../../components/ProductItemListView";
import Button from "@mui/material/Button";
import { IoGridSharp } from "react-icons/io5";
import { LuMenu } from "react-icons/lu";
import Menu from "@mui/material/Menu";
import MenuItem from "@mui/material/MenuItem";
import Pagination from "@mui/material/Pagination";
import ProductLoadingGrid from "../../components/ProductLoading/productLoadingGrid";
import { postData } from "../../utils/api";
import { MyContext } from "../../App";

const ProductListing = () => {
  const [itemView, setItemView] = useState("grid");
  const [anchorEl, setAnchorEl] = React.useState(null);

  const [productsData, setProductsData] = useState([]);
  const [isLoading, setIsLoading] = useState(false);

  const [page, setPage] = useState(1);
  const [totalPages, setTotalPages] = useState(1);

  const [selectedSortVal, setSelectedSortVal] = useState("Nombre, A a Z");

  const context = useContext(MyContext);

  useEffect(() => {
    window.scrollTo(0, 0);
  }, []);

  const open = Boolean(anchorEl);
  const handleClick = (event) => {
    setAnchorEl(event.currentTarget);
  };
  const handleClose = () => {
    setAnchorEl(null);
  };

  // 🟢 Mapear "price" → "priceBob" para ordenar por BOB
  const SORT_KEY_MAP = {
    price: "priceBob",
    name: "name",
  };

  const handleSortBy = (name, order, products, value) => {
    setSelectedSortVal(value);
    const sortKey = SORT_KEY_MAP[name] || name;

    postData(`/api/product/sortBy`, {
      products: products,
      sortBy: sortKey, // <- usar priceBob cuando pidan "price"
      order: order,
    }).then((res) => {
      setProductsData(res);
      setAnchorEl(null);
    });
  };
```

```
  return (
    <section className=" pb-0">
      <div className="bg-white p-2">
        <div className="container flex gap-3">
          {/* 🖌 Mini fix de clase: 'w-fulllg:h-full' → 'w-full lg:h-full' */}
          <div
            className={`sidebarWrapper fixed -bottom-[100%] left-0 w-full lg:h-full lg:static lg:w-
[20%] bg-white z-[102] lg:z-[100] p-3 lg:p-0 transition-all lg:opacity-100 opacity-0
${context?.openFilter === true ? "open" : ""
              }`}
          >
            <Sidebar
              productsData={productsData}
              setProductsData={setProductsData}
              isLoading={isLoading}
              setIsLoading={setIsLoading}
              page={page}
              setTotalPages={setTotalPages}
            />
          </div>

          {context?.windowWidth < 992 && (
            <div
              className={`filter_overlay w-full h-full bg-[rgba(0,0,0,0.5)] fixed top-0 left-0 z-
[101]  ${context?.openFilter === true ? "block" : "hidden"
                }`}
              onClick={() => context?.setOpenFilter(false)}
            ></div>
          )}

          <div className="rightContent w-full lg:w-[80%] py-3">
            <div className="bg-[#f1f1f1] p-2 w-full mb-4 rounded-md flex items-center justify-
between sticky top-[135px] z-[99]">
              <div className="col1 flex items-center itemViewActions">
                <Button
                  className={`!w-[35px] !h-[35px] !min-w-[35px] !rounded-full
                    !text-[#000] ${itemView === "list" && "active !bg-[#dfdfdf]"}`}
                  onClick={() => setItemView("list")}
                >
                  <LuMenu className="text-[rgba(0,0,0,0.7)] text-[16px]" />
                </Button>
                <Button
                  className={`!w-[35px] !h-[35px] !min-w-[35px] !rounded-full
                    !text-[#000] ${itemView === "grid" && "active !bg-[#dfdfdf]"}`}
                  onClick={() => setItemView("grid")}
                >
                  <IoGridSharp className="text-[rgba(0,0,0,0.7)] text-[14px]" />
                </Button>

                <span className="text-[14px] hidden sm:block md:block lg:block font-[500] pl-3
text-[rgba(0,0,0,0.7)]">
                  Hay {productsData?.products?.length || 0} productos.
                </span>
              </div>

              <div className="col2 ml-auto flex items-center justify-end gap-3 pr-4">
                <span className="text-[14px] font-[500] pl-3 text-[rgba(0,0,0,0.7)]">
                  Ordenar por
                </span>

                <Button
                  id="basic-button"
                  aria-controls={open ? "basic-menu" : undefined}
                  aria-haspopup="true"
                  aria-expanded={open ? "true" : undefined}
                  onClick={handleClick}
                  className="!bg-white !text-[12px] !text-[#000] !capitalize !border-2
                  !border-[#000]"
```

```
          >
            {selectedSortVal}
          </Button>

          <Menu
            id="basic-menu"
            anchorEl={anchorEl}
            open={open}
            onClose={handleClose}
            MenuListProps={{
              "aria-labelledby": "basic-button",
            }}
          >
            <MenuItem
              onClick={() =>
                handleSortBy("name", "asc", productsData, "Nombre, A a Z")
              }
              className="!text-[13px] !text-[#000] !capitalize"
            >
              Nombre, A a Z
            </MenuItem>

            <MenuItem
              onClick={() =>
                handleSortBy("name", "desc", productsData, "Nombre, Z a A")
              }
              className="!text-[13px] !text-[#000] !capitalize"
            >
              Nombre, Z a A
            </MenuItem>

            <MenuItem
              onClick={() =>
                handleSortBy("price", "asc", productsData, "Precio, de menor a mayor")
              }
              className="!text-[13px] !text-[#000] !capitalize"
            >
              Precio, de menor a mayor
            </MenuItem>

            <MenuItem
              onClick={() =>
                handleSortBy("price", "desc", productsData, "Precio, de mayor a menor")
              }
              className="!text-[13px] !text-[#000] !capitalize"
            >
              Precio, de mayor a menor
            </MenuItem>
          </Menu>
        </div>
      </div>

      <div
        className={`grid ${itemView === "grid"
            ? "grid-cols-2 sm:grid-cols-3 md:grid-cols-4 lg:grid-cols-5"
            : "grid-cols-1 sm:grid-cols-2 md:grid-cols-3 lg:grid-cols-1"
          } gap-4`}
      >
        {itemView === "grid" ? (
          <>
            {isLoading === true ? (
              <ProductLoadingGrid view={itemView} />
            ) : (
              productsData?.products?.length !== 0 &&
              productsData?.products?.map((item, index) => {
                return <ProductItem key={index} item={item} />;
              })
            )}
          </>
```

```
            ) : (
              <>
                {isLoading === true ? (
                  <ProductLoadingGrid view={itemView} />
                ) : (
                  productsData?.products?.length !== 0 &&
                  productsData?.products?.map((item, index) => {
                    return <ProductItemListView key={index} item={item} />;
                  })
                )}
              </>
            )}
          </div>

          {totalPages > 1 && (
            <div className="flex items-center justify-center mt-10">
              <Pagination
                showFirstButton
                showLastButton
                count={totalPages}
                page={page}
                onChange={(e, value) => setPage(value)}
              />
            </div>
          )}
        </div>
      </div>
    </div>
  </section>
);
};

export default ProductListing;
```

1.3.3.11 Register

1.3.3.12 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import TextField from "@mui/material/TextField";
import Button from "@mui/material/Button";
import { IoMdEye } from "react-icons/io";
import { IoMdEyeOff } from "react-icons/io";
import { Link } from "react-router-dom";
import { FcGoogle } from "react-icons/fc";
import { MyContext } from "../../App";
import { postData } from "../../utils/api";
import CircularProgress from '@mui/material/CircularProgress';
import { useNavigate } from "react-router-dom";

import { getAuth, signInWithPopup, GoogleAuthProvider } from "firebase/auth";
import { firebaseApp } from "../../firebase";
const auth = getAuth(firebaseApp);
const googleProvider = new GoogleAuthProvider();

const Register = () => {

  const [isLoading, setIsLoading] = useState(false);
  const [isPasswordShow, setIsPasswordShow] = useState(false);
  const [formFields, setFormFields] = useState({
    name: "",
    email: "",
    password: ""
  })

  const context = useContext(MyContext);
  const history = useNavigate();
```

```
  useEffect(()=>{
    window.scrollTo(0,0)
  },[])


const onChangeInput = (e) => {
  const { name, value } = e.target;
  setFormFields(() => {
    return {
      ...formFields,
      [name]: value
    }
  })
}

const valideValue = Object.values(formFields).every(el => el)

const handleSubmit = (e) => {
  e.preventDefault();

  setIsLoading(true);

  if (formFields.name === "") {
    context.alertBox("error", "Por favor ingresa tu nombre completo");
    return false
  }

  if (formFields.email === "") {
    context.alertBox("error", "Por favor ingresa tu correo electrónico");
    return false
  }


  if (formFields.password === "") {
    context.alertBox("error", "Por favor ingresa tu contraseña");
    return false
  }


  postData("/api/user/register", formFields).then((res) => {

    if (res?.error !== true) {
      setIsLoading(false);
      context.alertBox("success", res?.message);
      localStorage.setItem("userEmail", formFields.email)
      setFormFields({
        name: "",
        email: "",
        password: ""
      })

      history("/verify")
    } else {
      context.alertBox("error", res?.message);
      setIsLoading(false);
    }

  })


}



const authWithGoogle = () => {

  signInWithPopup(auth, googleProvider)
    .then((result) => {
      // This gives you a Google Access Token. You can use it to access the Google API.
```

```
      const credential = GoogleAuthProvider.credentialFromResult(result);
      const token = credential.accessToken;
      // The signed-in user info.
      const user = result.user;

      const fields = {
        name: user.providerData[0].displayName,
        email: user.providerData[0].email,
        password: null,
        avatar: user.providerData[0].photoURL,
        mobile: user.providerData[0].phoneNumber,
        role: "USER"
      };


      postData("/api/user/authWithGoogle", fields).then((res) => {

        if (res?.error !== true) {
          setIsLoading(false);
          context.alertBox("success", res?.message);
          localStorage.setItem("userEmail", fields.email)
          localStorage.setItem("accessToken", res?.data?.accesstoken);
          localStorage.setItem("refreshToken", res?.data?.refreshToken);

          context.setIsLogin(true);

          history("/")
        } else {
          context.alertBox("error", res?.message);
          setIsLoading(false);
        }

      })

      console.log(user)
      // IdP data available using getAdditionalUserInfo(result)
      // ...
    }).catch((error) => {
      // Handle Errors here.
      const errorCode = error.code;
      const errorMessage = error.message;
      // The email of the user's account used.
      const email = error.customData.email;
      // The AuthCredential type that was used.
      const credential = GoogleAuthProvider.credentialFromError(error);
      // ...
    });


}

return (
  <section className="section py-5 sm:py-10">
    <div className="container">
      <div className="card shadow-md w-full sm:w-[400px] m-auto rounded-md bg-white p-5 px-10">
        <h3 className="text-center text-[18px] text-black">
          Regístrate con una cuenta nueva
        </h3>

        <form className="w-full mt-5" onSubmit={handleSubmit}>
          <div className="form-group w-full mb-5">
            <TextField
              type="text"
              id="name"
              name="name"
              value={formFields.name}
              disabled={isLoading === true ? true : false}
              label="Nombre completo"
              variant="outlined"
```

```
                className="w-full"
                onChange={onChangeInput}
              />
            </div>


            <div className="form-group w-full mb-5">
              <TextField
                type="emai"
                id="email"
                name="email"
                label="Correo electrónico"
                value={formFields.email}
                disabled={isLoading === true ? true : false}
                variant="outlined"
                className="w-full"
                onChange={onChangeInput}
              />
            </div>

            <div className="form-group w-full mb-5 relative">
              <TextField
                type={isPasswordShow === false ? 'password' : 'text'}
                id="password"
                name="password"
                label="Contraseña"
                variant="outlined"
                className="w-full"
                value={formFields.password}
                disabled={isLoading === true ? true : false}
                onChange={onChangeInput}
              />
              <Button className="!absolute top-[10px] right-[10px] z-50 !w-[35px] !h-[35px] !min-w-
[35px] !rounded-full !text-black" onClick={() => {
                setIsPasswordShow(!isPasswordShow)
              }}>
                {
                  isPasswordShow === false ? <IoMdEye className="text-[20px] opacity-75" /> :
                    <IoMdEyeOff className="text-[20px] opacity-75" />
                }
              </Button>
            </div>

            <div className="flex items-center w-full mt-3 mb-3">
              <Button type="submit" disabled={!valideValue} className="btn-org btn-lg w-full flex
gap-3">
                {
                  isLoading === true ? <CircularProgress color="inherit" />
                    :
                    'Registrarse'
                }

              </Button>
            </div>

            <p className="text-center">¿Ya tienes una cuenta? <Link className="link text-[14px]
font-[600] text-primary" to="/login"> Iniciar sesión</Link></p>


            <p className="text-center font-[500]">O continúa con tu cuenta social</p>

            <Button className="flex gap-3 w-full !bg-[#f1f1f1] btn-lg !text-black"
              onClick={authWithGoogle}>
              <FcGoogle className="text-[20px]" /> Regístrate con Google</Button>

          </form>
        </div>
      </div>
    </section>
```

```
  );
};

export default Register;
```

1.3.3.13 Search

1.3.3.13.1 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import { Sidebar } from "../../components/Sidebar";
import Breadcrumbs from "@mui/material/Breadcrumbs";
import ProductItem from "../../components/ProductItem";
import ProductItemListView from "../../components/ProductItemListView";
import Button from "@mui/material/Button";
import { IoGridSharp } from "react-icons/io5";
import { LuMenu } from "react-icons/lu";
import Menu from "@mui/material/Menu";
import MenuItem from "@mui/material/MenuItem";
import Pagination from "@mui/material/Pagination";
import ProductLoadingGrid from "../../components/ProductLoading/productLoadingGrid";
import { postData } from "../../utils/api";
import { MyContext } from "../../App";

const SearchPage = () => {
  const [itemView, setItemView] = useState("grid");
  const [anchorEl, setAnchorEl] = React.useState(null);

  const [productsData, setProductsData] = useState([]);
  const [isLoading, setIsLoading] = useState(false);

  const [page, setPage] = useState(1);
  const [totalPages, setTotalPages] = useState(1);

  const [selectedSortVal, setSelectedSortVal] = useState("Nombre, A a Z");

  const context = useContext(MyContext);

  useEffect(() => {
    window.scrollTo(0, 0);
  }, [])


  const open = Boolean(anchorEl);
  const handleClick = (event) => {
    setAnchorEl(event.currentTarget);
  };
  const handleClose = () => {
    setAnchorEl(null);
  };



  const handleSortBy = (name, order, products, value) => {
    setSelectedSortVal(value);
    postData(`/api/product/sortBy`, {
      products: products,
      sortBy: name,
      order: order
    }).then((res) => {
      setProductsData(res);
      setAnchorEl(null);
    })
  }

  return (
    <section className=" pb-0">

      <div className="bg-white p-2">
```

```
        <div className="container flex gap-3">
          <div className={`sidebarWrapper fixed -bottom-[100%] left-0 w-fulllg:h-full lg:static
lg:w-[20%] bg-white z-[102] lg:z-[100] p-3 lg:p-0  transition-all lg:opacity-100 opacity-0
${context?.openFilter === true ? 'open' : ''}`}>
            <Sidebar
              productsData={productsData}
              setProductsData={setProductsData}
              isLoading={isLoading}
              setIsLoading={setIsLoading}
              page={page}
              setTotalPages={setTotalPages}
            />
          </div>

          {
            context?.windowWidth < 992 &&
            <div className={`filter_overlay w-full h-full bg-[rgba(0,0,0,0.5)] fixed top-0 left-0
z-[101]  ${context?.openFilter === true ? 'block' : 'hidden'}`}
              onClick={()=>context?.setOpenFilter(false)}
            ></div>
          }


          <div className="rightContent w-full lg:w-[80%] py-3">
            <div className="bg-[#f1f1f1] p-2 w-full mb-4 rounded-md flex items-center justify-
between sticky top-[135px] z-[99]">
              <div className="col1 flex items-center itemViewActions">
                <Button
                  className={`!w-[35px] !h-[35px] !min-w-[35px] !rounded-full
                    !text-[#000] ${itemView === "list" && "active !bg-[#dfdfdf]"}`}
                  onClick={() => setItemView("list")}
                >
                  <LuMenu className="text-[rgba(0,0,0,0.7)] text-[16px]" />
                </Button>
                <Button
                  className={`!w-[35px] !h-[35px] !min-w-[35px] !rounded-full
                    !text-[#000] ${itemView === "grid" && "active !bg-[#dfdfdf]"}`}
                  onClick={() => setItemView("grid")}
                >
                  <IoGridSharp className="text-[rgba(0,0,0,0.7)] text-[14px]" />
                </Button>

                <span className="text-[14px] hidden sm:block md:block lg:block font-[500] pl-3
text-[rgba(0,0,0,0.7)]">
                  Hay {productsData?.products?.length !== 0 ? productsData?.products?.length : 0}
productos.
                </span>
              </div>

              <div className="col2 ml-auto flex items-center justify-end gap-3 pr-4">
                <span className="text-[14px] font-[500] pl-3 text-[rgba(0,0,0,0.7)]">
                  Ordenar por
                </span>

                <Button
                  id="basic-button"
                  aria-controls={open ? "basic-menu" : undefined}
                  aria-haspopup="true"
                  aria-expanded={open ? "true" : undefined}
                  onClick={handleClick}
                  className="!bg-white !text-[12px] !text-[#000] !capitalize !border-2
                  !border-[#000]"
                >
                  {selectedSortVal}
                </Button>

                <Menu
                  id="basic-menu"
                  anchorEl={anchorEl}
```

```
                  open={open}
                  onClose={handleClose}
                  MenuListProps={{
                    "aria-labelledby": "basic-button",
                  }}
                >
                  <MenuItem
                    onClick={() => handleSortBy('name', 'asc', productsData, 'Nombre, A a Z')}
                    className="!text-[13px] !text-[#000] !capitalize"
                  >
                    Nombre, A a Z
                  </MenuItem>


                  <MenuItem
                    onClick={() => handleSortBy('name', 'desc', productsData, 'Nombre, Z a A')}
                    className="!text-[13px] !text-[#000] !capitalize"
                  >
                    Nombre, Z a A
                  </MenuItem>


                  <MenuItem
                    onClick={() => handleSortBy('price', 'asc', productsData, 'Precio, de menor a
mayor')}
                    className="!text-[13px] !text-[#000] !capitalize"
                  >
                    Precio, de menor a mayor
                  </MenuItem>


                  <MenuItem
                    onClick={() => handleSortBy('price', 'desc', productsData, ' Precio, de mayor a
menor')}
                    className="!text-[13px] !text-[#000] !capitalize"
                  >
                    Precio, de mayor a menor
                  </MenuItem>

                </Menu>
              </div>
            </div>

            <div
              className={`grid ${itemView === "grid"
                ? "grid-cols-2 sm:grid-cols-3 md:grid-cols-4 lg:grid-cols-5"
                : "grid-cols-1 sm:grid-cols-2 md:grid-cols-3 lg:grid-cols-1"
                } gap-4`}
            >
              {itemView === "grid" ? (
                <>

                  {
                    isLoading === true ? <ProductLoadingGrid view={itemView} />
                      :

                      productsData?.products?.length !== 0 && productsData?.products?.map((item,
index) => {
                        return (
                          <ProductItem key={index} item={item} />
                        )
                      })

                  }


                </>
              ) : (
                <>
```

```
                  {
                    isLoading === true ? <ProductLoadingGrid view={itemView} />
                      :

                      productsData?.products?.length !== 0 && productsData?.products?.map((item,
index) => {
                        return (
                          <ProductItemListView key={index} item={item} />
                        )
                      })

                  }

                </>
              )}
            </div>

            {
              totalPages > 1 &&
              <div className="flex items-center justify-center mt-10">
                <Pagination
                  showFirstButton showLastButton
                  count={totalPages}
                  page={page}
                  onChange={(e, value) => setPage(value)}
                />
              </div>
            }


          </div>
        </div>
      </div>
    </section>
  );
};

export default SearchPage;
```

1.3.3.14 Verify

1.3.3.14.1 index.jsx

```
import React, { useContext, useEffect, useState } from "react";
import OtpBox from "../../components/OtpBox";
import Button from "@mui/material/Button";
import { postData } from "../../utils/api";
import { useNavigate } from "react-router-dom";
import { MyContext } from "../../App";

const Verify = () => {
  const [otp, setOtp] = useState("");
  const handleOtpChange = (value) => {
    setOtp(value);
  };

  const history = useNavigate();
  const context = useContext(MyContext)

  const verityOTP = (e) => {
    e.preventDefault();

    const actionType = localStorage.getItem("actionType");

    if (actionType !== "forgot-password") {

      postData("/api/user/verifyEmail", {
        email: localStorage.getItem("userEmail"),
        otp: otp
```

```
      }).then((res) => {
        if (res?.error === false) {
          context.alertBox("success", res?.message);
          localStorage.removeItem("userEmail")
          history("/login")
        } else {
          context.alertBox("error", res?.message);
        }
      })
    }

    else {
      postData("/api/user/verify-forgot-password-otp", {
        email: localStorage.getItem("userEmail"),
        otp: otp
      }).then((res) => {
        if (res?.error === false) {
          context.alertBox("success", res?.message);
          history("/forgot-password")
        } else {
          context.alertBox("error", res?.message);
        }
      })
    }

  }

  return (
    <section className="section py-5 lg:py-10">
      <div className="container">
        <div className="card shadow-md w-full sm:w-[400px] m-auto rounded-md bg-white p-5 px-10">
          <div className="text-center flex items-center justify-center">
            <img src="/verify3.png" width="80" />
          </div>
          <h3 className="text-center text-[18px] text-black mt-4 mb-1">
            Verificar OTP
          </h3>

          <p className="text-center mt-0 mb-4">
            OTP enviado a{" "}
            <span className="text-primary font-bold">{localStorage.getItem("userEmail")}</span>
          </p>

          <form onSubmit={verityOTP}>
            <OtpBox length={6} onChange={handleOtpChange} />

            <div className="flex items-center justify-center mt-5 px-3">
              <Button type="submit" className="w-full btn-org btn-lg">Verificar OTP</Button>
            </div>
          </form>
        </div>
      </div>
    </section>
  );
};

export default Verify;
```

1.3.4 utils

1.3.4.1 api.js

```
// src/utils/api.js
import axios from "axios";
const apiUrl = import.meta.env.VITE_API_URL;

// Reutilizar headers de auth sin cambiar tu patrón actual
const authHeaders = () => ({
```

```
    Authorization: `Bearer ${localStorage.getItem('accessToken')}`,
});

// --- POST (mantengo fetch como lo tienes)
export const postData = async (url, formData) => {
    try {
        const response = await fetch(apiUrl + url, {
            method: 'POST',
            headers: {
                ...authHeaders(),
                'Content-Type': 'application/json',
            },
            body: JSON.stringify(formData),
        });

        const json = await response.json();
        return json; // conservamos tu contrato actual
    } catch (error) {
        console.error('Error:', error);
        return { error: true, message: String(error) };
    }
};

// --- GET (axios) sin cambios de contrato
export const fetchDataFromApi = async (url) => {
    try {
        const params = {
            headers: {
                ...authHeaders(),
                'Content-Type': 'application/json',
            },
        };
        const { data } = await axios.get(apiUrl + url, params);
        return data;
    } catch (error) {
        console.log(error);
        return error; // conservamos tu retorno actual
    }
};

// --- PUT multipart (no forzar Content-Type para que ponga el boundary)
export const uploadImage = async (url, updatedData) => {
    const params = {
        headers: {
            ...authHeaders(),
            // ¡No seteamos 'Content-Type': el navegador lo define con boundary!
        },
    };
    let response;
    await axios.put(apiUrl + url, updatedData, params).then((res) => {
        response = res;
    });
    return response;
};

// --- PUT JSON (igual que tenías)
export const editData = async (url, updatedData) => {
    const params = {
        headers: {
            ...authHeaders(),
            'Content-Type': 'application/json',
        },
    };
    let response;
    await axios.put(apiUrl + url, updatedData, params).then((res) => {
        response = res;
    });
    return response;
};
```

```
// --- DELETE (corrige: axios devuelve .data, no { res })
export const deleteData = async (url) => {
    const params = {
        headers: {
            ...authHeaders(),
            'Content-Type': 'application/json',
        },
    };
    const { data } = await axios.delete(apiUrl + url, params);
    return data; // <- fix
};

// --- Helpers ligeros (opcional, no rompe nada)
// FX: R = BOB por 1 USDT
export const getFxLatest = () => fetchDataFromApi('/fx/latest');

// Productos (por si lo quieres usar en listados/detalle)
export const getProducts = (query = '') => fetchDataFromApi(`/products${query}`);
export const getProductById = (id) => fetchDataFromApi(`/products/${id}`);
```

1.3.4.2 formatPrice.js

```
// src/utils/formatPrice.js
export function formatPrice(amount, currency) {
  if (amount === null || amount === undefined || amount === "") return "—";

  const num = Number(amount);
  if (isNaN(num)) return amount;

  switch (currency?.toUpperCase()) {
    case "USD":
      return `$${num.toFixed(2)}`;
    case "BOB":
      return `${num.toFixed(2)} Bs`;
    default:
      return `${num.toFixed(2)} ${currency || ""}`;
  }
}
```

1.3.4.3 storage.js

```
// src/utils/storage.js

// Guardar valor en localStorage
export function saveLocal(key, value) {
  try {
    localStorage.setItem(key, JSON.stringify(value));
  } catch (err) {
    console.error("Error saving to localStorage:", err);
  }
}

// Cargar valor desde localStorage
export function loadLocal(key, fallback = null) {
  try {
    const raw = localStorage.getItem(key);
    return raw ? JSON.parse(raw) : fallback;
  } catch (err) {
    console.error("Error loading from localStorage:", err);
    return fallback;
  }
}

// Eliminar valor de localStorage
```

```
export function removeLocal(key) {
  try {
    localStorage.removeItem(key);
  } catch (err) {
    console.error("Error removing from localStorage:", err);
  }
}
```

1.3.5 App.css

1.3.6 App.jsx

```
// admin/src/App.jsx
import "./App.css";
import "./responsive.css";
import React from "react";
import { createBrowserRouter, RouterProvider, Navigate } from "react-router-dom";

import AppLayout from "./layout/AppLayout";
import ProtectedRoute from "./routes/ProtectedRoute";
import RoleRedirect from "./routes/RoleRedirect";
import RequireAdmin from "./routes/RequireAdmin";
import RequireTenant from "./components/Guards/RequireTenant";

// ✅ Contexto (default)
import MyContext from "./context/AppContext.js";

// -------- Páginas base --------
import Dashboard from "./Pages/Dashboard";
import Login from "./Pages/Login";
import SignUp from "./Pages/SignUp";
import Products from "./Pages/Products";
import HomeSliderBanners from "./Pages/HomeSliderBanners";
import CategoryList from "./Pages/Categegory";
import SubCategoryList from "./Pages/Categegory/subCatList";
import Users from "./Pages/Users";
import Orders from "./Pages/Orders";
import ForgotPassword from "./Pages/ForgotPassword";
import VerifyAccount from "./Pages/VerifyAccount";
import ChangePassword from "./Pages/ChangePassword";
import Profile from "./Pages/Profile";
import ProductDetails from "./Pages/Products/productDetails";

// ------- Formularios que eran “full screen” pero ahora son rutas limpias -------
import AddProduct from "./Pages/Products/addProduct";
import AddRAMS from "./Pages/Products/addRAMS.JSX";
import AddWeight from "./Pages/Products/addWeight";
import AddSize from "./Pages/Products/addSize";
import AddAddress from "./Pages/Address/addAddress";
import AddHomeSlide from "./Pages/HomeSliderBanners/addHomeSlide";
import EditHomeSlide from "./Pages/HomeSliderBanners/editHomeSlide";
import AddCategory from "./Pages/Categegory/addCategory";
import EditCategory from "./Pages/Categegory/editCategory";
import AddSubCategory from "./Pages/Categegory/addSubCategory";

// Banners
import { AddBannerV1 } from "./Pages/Banners/addBannerV1";
import { EditBannerV1 } from "./Pages/Banners/editBannerV1";
import { BannerList2_AddBanner } from "./Pages/Banners/bannerList2_AddBanner";
import { BannerList2_Edit_Banner } from "./Pages/Banners/bannerList2_Edit_Banner";

import AddBlog from "./Pages/Blog/addBlog";
import EditBlog from "./Pages/Blog/editBlog";

import BannerV1List from "./Pages/Banners/bannerV1List";
import { BannerList2 } from "./Pages/Banners/bannerList2";
import { BlogList } from "./Pages/Blog";
import ManageLogo from "./Pages/ManageLogo";
```

```
import StoresPage from "./Pages/Stores";
import PaymentsPage from "./Pages/Payments";
import ApplicationsBridgePage from "./Pages/Applications/index.jsx";
import RequestSellerCard from "./Pages/Stores/RequestSellerCard";

// Delivery (listas/detalles)
import DeliveryList from "./Pages/Delivery/DeliveryList";
import DeliveryDetail from "./Pages/Delivery/DeliveryDetail";
import MyDeliveries from "./Pages/Delivery/MyDeliveries";

// ✅ Admin de postulaciones
import SellerApplicationsAdminList from "./Pages/Stores/AdminList";
import DeliveryApplicationsAdmin from "./Pages/Delivery/AdminList";
import MyStore from "./Pages/Stores/MyStore";
// Reports
import ReportsPage from "./Pages/Reports/ReportsPage";
import ReportsPrint from "./Pages/Reports/ReportsPrint";

// Fase 8 (marketing/soporte)
import PromotionsList from "./Pages/Promotions/List";
import PromotionCreate from "./Pages/Promotions/Create";
import PromotionEdit from "./Pages/Promotions/Edit";
import TicketsList from "./Pages/Support/TicketsList";
import TicketDetail from "./Pages/Support/TicketDetail";

// Fase 9 (auditoría/seguridad)
import AuditLogsPage from "./Pages/Audit/AuditLogsPage";
import PermissionsPanelPage from "./Pages/Security/PermissionsPanelPage";

import toast, { Toaster } from "react-hot-toast";
import LoadingBar from "react-top-loading-bar";
import { api } from "./utils/api";
import { hydrateMeAndNormalizeScope } from "./utils/session";
import SelectStorePage from "./Pages/Stores/SelectStorePage";

// ⬇️ NUEVO: inicializar socket + helpers de listeners
import { getSocket, on } from "./utils/socket";

// Lazy: Inventario / ApplyDelivery
const InventoryPage = React.lazy(async () => {
  try {
    const mod = await import("./Pages/Inventory");
    return { default: mod.default || mod };
  } catch {
    return {
      default: () => (
        <div className="p-6">
          <h2 className="text-lg font-semibold mb-2">Inventario</h2>
          <p className="text-sm text-gray-600">
            Crea <code>admin/src/Pages/Inventory/index.jsx</code> para cargar esta página.
          </p>
        </div>
      ),
    };
  }
});

const ApplyDelivery = React.lazy(async () => {
  try {
    const mod = await import("./Pages/Delivery/ApplyDelivery.jsx");
    return { default: mod.default || mod };
  } catch {
    return {
      default: () => (
        <div className="p-6">
          <h2 className="text-lg font-semibold mb-2">Postulación a Delivery</h2>
          <p className="text-sm text-gray-600">
```

```
            Crea <code>admin/src/Pages/Delivery/ApplyDelivery.jsx</code> para personalizar esta
vista.
          </p>
        </div>
      ),
    };
  }
});

const Forbidden = () => <div className="p-6">403 • No autorizado</div>;

const SuperDashboard = () => <Dashboard scope="super" />;
const StoreDashboard = () => <Dashboard scope="store" />;
const InventoryDashboard = () => <Dashboard scope="inventory" />;
const FinanceDashboard = () => <Dashboard scope="finance" />;
const DeliveryDashboard = () => <Dashboard scope="delivery" />;
const SupportDashboard = () => <Dashboard scope="support" />;

/** ====== LEGACY modal → rutas embebidas ====== */
const LEGACY_MODEL_TO_PATH = (model, { id } = {}) => {
  switch ((model || "").toLowerCase()) {
    case "add product":
    case "agregar producto":
      return "/products/new";
    case "edit product":
    case "editar producto":
      return "/products";
    case "add ram":
    case "agregar ram":
    case "ram":
      return "/product/addRams";
    case "add weight":
    case "agregar weight":
    case "peso":
      return "/product/addWeight";
    case "add size":
    case "agregar size":
    case "talla":
      return "/product/addSize";
    case "agregar slide principal":
    case "add home slide":
      return "/marketing/slider/new";
    case "editar slide principal":
    case "edit homeslide":
      return "/marketing/slider";
    case "add category":
    case "agregar categoría":
      return "/catalog/categories/new";
    case "edit category":
    case "editar categoría":
      return "/catalog/categories";
    case "add sub category":
    case "add new sub category":
    case "agregar subcategoría":
      return "/catalog/subcategories/new";
    case "add address":
    case "agregar dirección":
      return "/address/new";
    case "add bannerv1":
    case "agregar bannerv1":
      return "/marketing/banners/v1/new";
    case "edit bannerv1":
    case "editar bannerv1":
      return "/marketing/banners/v1";
    case "add bannerlist2":
    case "agregar bannerlist2":
      return "/marketing/banners/v2/new";
    case "edit bannerlist2":
    case "editar bannerlist2":
```

```
      return "/marketing/banners/v2";
    case "add blog":
    case "agregar blog":
      return "/blog/new";
    case "edit blog":
    case "editar blog":
      return "/blog";
    case "manage logo":
    case "logo":
    case "edit logo":
      return "/logo/manage";
    default:
      return null;
  }
};

function App() {
  // ---- Layout/UI ----
  const [isSidebarOpen, setisSidebarOpen] = React.useState(true);
  const [windowWidth, setWindowWidth] = React.useState(window.innerWidth);
  const [sidebarWidth, setSidebarWidth] = React.useState(18);
  const [progress, setProgress] = React.useState(0);

  // ⚠️ Compat interno (estado legacy visual)
  const [_legacyFullScreenPanel, _setLegacyFullScreenPanel] = React.useState({ open: false, id: ""
});

  // ---- Auth / User ----
  const [isLogin, setIsLogin] = React.useState(false);
  const [userData, setUserData] = React.useState(null);
  const [isSuper, setIsSuper] = React.useState(false);
  const [authReady, setAuthReady] = React.useState(false);
  const [booted, setBooted] = React.useState(false);

  // ---- Data base (categorías) ----
  const [catData, setCatData] = React.useState([]);
  const [address, setAddress] = React.useState([]);

  // ---- Tenant helpers ----
  const [activeStoreId, setActiveStoreId] = React.useState(
    localStorage.getItem("X-Store-Id") || null
  );
  const getTenantHeaders = () =>
    activeStoreId ? { "X-Store-Id": String(activeStoreId) } : {};
  const setTenant = (storeId) => {
    if (storeId) {
      localStorage.setItem("X-Store-Id", String(storeId));
      setActiveStoreId(String(storeId));
      // 🔔 notifica a la app (misma pestaña)
      try {
        window.dispatchEvent(new CustomEvent("mtz:tenant-changed", { detail: { id: String(storeId)
} }));
      } catch { }
    } else {
      localStorage.removeItem("X-Store-Id");
      setActiveStoreId(null);
      try {
        window.dispatchEvent(new CustomEvent("mtz:tenant-changed", { detail: { id: null } }));
      } catch { }
    }
  };

  // Sincroniza X-Store-Id entre pestañas
  React.useEffect(() => {
    const onStorage = (e) => {
      if (e.key === "X-Store-Id") {
        setActiveStoreId(e.newValue ? String(e.newValue) : null);
      }
    };
```

```
  window.addEventListener("storage", onStorage);
  return () => window.removeEventListener("storage", onStorage);
}, []);

// 🔔 Sincroniza X-Store-Id en la misma pestaña (evento custom)
React.useEffect(() => {
  const onTenantChanged = (e) => {
    const next = e?.detail?.id ?? localStorage.getItem("X-Store-Id") ?? null;
    setActiveStoreId(next ? String(next) : null);
  };
  window.addEventListener("mtz:tenant-changed", onTenantChanged);
  return () => window.removeEventListener("mtz:tenant-changed", onTenantChanged);
}, []);

// Layout responsive
React.useEffect(() => {
  if (windowWidth < 992) {
    setisSidebarOpen(false);
    setSidebarWidth(100);
  } else {
    setSidebarWidth(18);
  }
}, [windowWidth]);

React.useEffect(() => {
  const handleResize = () => setWindowWidth(window.innerWidth);
  window.addEventListener("resize", handleResize);
  return () => window.removeEventListener("resize", handleResize);
}, []);

// ⬇️ NUEVO: en cuanto haya token, inicializa socket una sola vez
React.useEffect(() => {
  try {
    const t = localStorage.getItem("accessToken");
    if (t) getSocket(); // getSocket es singleton
  } catch { /* noop */ }
}, []); // solo al montar

// 🔔 NUEVO: escucha estado de la solicitud de vendedor para redirigir al aprobarse
React.useEffect(() => {
  const token = localStorage.getItem("accessToken");
  if (!token) return;

  // asegura conexión
  getSocket();

  // on() devuelve cleanup → evita duplicados con HMR
  const offSellerStatus = on("seller-app:status", (payload) => {
    try {
      if (payload?.status === "APPROVED" && payload?.storeId) {
        setTenant(String(payload.storeId));
        // feedback opcional
        try { toast.success("🎉 Tu tienda fue aprobada"); } catch { }
        // navega al área de tienda
        // si prefieres dashboard de tienda: router.navigate("/dashboard/store");
        router.navigate("/my-store");
      }
    } catch { /* noop */ }
  });

  return () => {
    offSellerStatus?.();
  };
}, [ /* router creado abajo es estable via useMemo, setTenant es estable */]);

// BOOT: hidrata /me y normaliza scope
React.useEffect(() => {
  setAuthReady(false); // ⬅️ asegura que Sidebar espere al /me
  (async () => {
```

```
    try {
      const token = localStorage.getItem("accessToken");
      if (!token) {
        setIsLogin(false);
        setUserData(null);
        setIsSuper(false);
        setAuthReady(true);
        return;
      }
      const { me, isSuper: isSuperHydrated } = await hydrateMeAndNormalizeScope();
      const roles = Array.isArray(me?.roles) ? me.roles.map(String) : [];
      const computedIsSuper = Boolean(
        isSuperHydrated || me?.isSuper || roles.includes("SUPER_ADMIN")
      );

      setUserData(me || null);
      setIsSuper(computedIsSuper);
      setIsLogin(Boolean(me));
    } catch {
      setIsLogin(false);
      setUserData(null);
      setIsSuper(false);
    } finally {
      setBooted(true);
      setAuthReady(true);
    }
  })();
}, []);

// Cargar catálogo base
React.useEffect(() => {
  getCat();
}, [activeStoreId]); // eslint-disable-line

const getCat = async () => {
  try {
    const res = await api.get("/api/category", { headers: { ...getTenantHeaders() } });
    const data = res?.data?.data || res?.data || [];
    setCatData(Array.isArray(data) ? data : []);
  } catch {
    setCatData([]);
  }
};

const alertBox = (type, msg) => {
  if (type === "success") toast.success(msg);
  if (type === "error") toast.error(msg);
};

// ---------------- RUTAS ----------------
const routes = [
  { path: "/", element: <Navigate to="/dashboard" replace /> },
  { path: "/admin", element: <Navigate to="/dashboard" replace /> },

  // Públicas
  { path: "/login", element: <Login /> },
  { path: "/sign-up", element: <SignUp /> },
  { path: "/forgot-password", element: <ForgotPassword /> },
  { path: "/verify-account", element: <VerifyAccount /> },
  { path: "/change-password", element: <ChangePassword /> },
  { path: "/403", element: <Forbidden /> },

  // 🔁 Aliases legacy → rutas limpias
  { path: "/admin/sell", element: <Navigate to="/sell" replace /> },
  { path: "/admin/apply-delivery", element: <Navigate to="/apply-delivery" replace /> },
  { path: "/admin/applications", element: <Navigate to="/applications" replace /> },

  // ✅ Redirección pedida: arriba de las rutas protegidas
  { path: "/admin/my-store", element: <Navigate to="/my-store" replace /> },
```

```
// Protegidas
{
  element: <ProtectedRoute />,
  children: [
    // ---- SIN TENANT (select store) ----
    { path: "/admin/select-store", element: <SelectStorePage /> },
    { path: "/select-store", element: <SelectStorePage /> },

    // ==== Onboarding SIN tenant pero con Layout (NO envolver en RequireTenant) ====
    {
      element: <AppLayout />, // ← mantiene header/sidebar y contención
      children: [
        { path: "applications", element: <ApplicationsBridgePage embedded /> },
        { path: "sell", element: <RequestSellerCard /> },
        {
          path: "apply-delivery",
          element: (
            <React.Suspense fallback={<div className="p-6">Cargando formulario…</div>}>
              <ApplyDelivery />
            </React.Suspense>
          ),
        },
      ],
    },

    // ==== Bloque que SÍ requiere tenant (todo lo demás) ====
    {
      path: "/*",
      element: (
        <RequireTenant>
          <AppLayout />
        </RequireTenant>
      ),
      children: [
        { path: "dashboard", element: <RoleRedirect /> },
        { path: "dashboard/super", element: <SuperDashboard /> },
        { path: "dashboard/store", element: <StoreDashboard /> },
        { path: "dashboard/inventory", element: <InventoryDashboard /> },
        { path: "dashboard/finance", element: <FinanceDashboard /> },
        { path: "dashboard/delivery", element: <DeliveryDashboard /> },
        { path: "dashboard/support", element: <SupportDashboard /> },

        // ✅ Ruta real dentro de RequireTenant
        { path: "my-store", element: <MyStore /> },

        // Listas/módulos
        { path: "products", element: <Products /> },
        { path: "homeSlider/list", element: <HomeSliderBanners /> },
        { path: "category/list", element: <CategoryList /> },
        { path: "subCategory/list", element: <SubCategoryList /> },
        { path: "orders", element: <Orders /> },
        { path: "profile", element: <Profile /> },
        { path: "payments", element: <PaymentsPage /> },
        { path: "product/:id", element: <ProductDetails /> },
        { path: "bannerV1/list", element: <BannerV1List /> },
        { path: "bannerlist2/List", element: <BannerList2 /> },
        { path: "blog/List", element: <BlogList /> },
        { path: "logo/manage", element: <ManageLogo /> },

        // Formularios (antes modales)
        { path: "products/new", element: <AddProduct /> },
        { path: "product/addRams", element: <AddRAMS /> },
        { path: "product/addWeight", element: <AddWeight /> },
        { path: "product/addSize", element: <AddSize /> },
        { path: "address/new", element: <AddAddress /> },
        { path: "marketing/slider/new", element: <AddHomeSlide /> },
        { path: "marketing/slider", element: <EditHomeSlide /> },
        { path: "catalog/categories/new", element: <AddCategory /> },
```

```
          { path: "catalog/categories", element: <EditCategory /> },
          { path: "catalog/subcategories/new", element: <AddSubCategory /> },
          { path: "marketing/banners/v1/new", element: <AddBannerV1 /> },
          { path: "marketing/banners/v1", element: <EditBannerV1 /> },
          { path: "marketing/banners/v2/new", element: <BannerList2_AddBanner /> },
          { path: "marketing/banners/v2", element: <BannerList2_Edit_Banner /> },
          { path: "blog/new", element: <AddBlog /> },
          { path: "blog", element: <EditBlog /> },

          // Lazy
          {
            path: "inventory",
            element: (
              <React.Suspense fallback={<div className="p-6">Cargando inventario…</div>}>
                <InventoryPage />
              </React.Suspense>
            ),
          },

          // Delivery
          { path: "delivery", element: <DeliveryList /> },
          { path: "delivery/:id", element: <DeliveryDetail /> },
          { path: "my-deliveries", element: <MyDeliveries /> },

          // Reports
          { path: "reports", element: <ReportsPage /> },
          { path: "reports/print", element: <ReportsPrint /> },

          // Solo Admin
          {
            element: <RequireAdmin />,
            children: [
              { path: "stores", element: <StoresPage /> },
              { path: "admin/stores", element: <StoresPage /> },
              { path: "users", element: <Users /> },
              { path: "audit", element: <AuditLogsPage /> },
              { path: "security/permissions", element: <PermissionsPanelPage /> },
              { path: "delivery-applications/admin", element: <DeliveryApplicationsAdmin /> },
              { path: "seller-applications/admin", element: <SellerApplicationsAdminList /> },
            ],
          },
        ],
      },
    ],
  },

  { path: "*", element: <Navigate to="/dashboard" replace /> },
];

// === Router (única instancia) ===
const router = React.useMemo(
  () => createBrowserRouter(routes),
  [isSidebarOpen, windowWidth, isLogin, activeStoreId]
);

// Helpers de navegación que usan la instancia del router
const openPanel = React.useCallback((path) => {
  try { router.navigate(path); } catch { }
}, [router]);

const closePanel = React.useCallback(() => {
  try { router.navigate(-1); } catch { }
}, [router]);

if (!booted) {
  return (
    <div className="min-h-screen flex flex-col items-center justify-center text-center p-6">
      <LoadingBar color="#1565c0" progress={progress || 30} height={3} />
      <div className="animate-pulse mt-4">
```

```
        <h1 className="text-xl font-semibold">Inicializando…</h1>
      </div>
    </div>
  );
}

const values = {
  // UI/Layout
  isSidebarOpen,
  setisSidebarOpen,
  windowWidth,
  sidebarWidth,
  setSidebarWidth,

  // Auth
  isLogin,
  setIsLogin,
  userData,
  setUserData,
  isSuper,
  setIsSuper,
  authReady,
  setAuthReady,
  booted,
  user: userData,
  setUser: setUserData,

  // Compat + helpers
  isOpenFullScreenPanel: _legacyFullScreenPanel,
  setIsOpenFullScreenPanel: (next) => {
    try {
      if (!next || next.open === false) {
        closePanel();
        _setLegacyFullScreenPanel({ open: false, id: "" });
        return;
      }
      if (next.open && next.model) {
        const path = LEGACY_MODEL_TO_PATH(next.model, { id: next.id });
        if (path) {
          openPanel(path);
          _setLegacyFullScreenPanel({ open: true, id: next.id || "" });
          return;
        }
      }
      _setLegacyFullScreenPanel(next);
    } catch {
      _setLegacyFullScreenPanel(next);
    }
  },
  openPanel,
  closePanel,

  // Utils
  alertBox,
  progress,
  setProgress,
  catData,
  setCatData,
  address,
  setAddress,
  getCat,

  // Tenant
  viewer: { activeStoreId },
  setTenant,
};

return (
  <MyContext.Provider value={values}>
```

```
      <React.Suspense fallback={<div className="p-6">Cargando…</div>}>
        <RouterProvider router={router} />
      </React.Suspense>
      <LoadingBar
        color="#1565c0"
        progress={progress}
        onLoaderFinished={() => setProgress(0)}
        className="topLoadingBar"
        height={3}
      />
      <Toaster />
    </MyContext.Provider>
  );
}

export default App;
```

1.3.7 firebase.jsx

```
import React, { useEffect, useState } from "react";
import { BrowserRouter, Route, Routes } from "react-router-dom";
import "./App.css";
import "./responsive.css";
import Header from "./components/Header";
import Footer from "./components/Footer";
import Home from "./Pages/Home";
import ProductListing from "./Pages/ProductListing";
import { ProductDetails } from "./Pages/ProductDetails";
import { createContext } from "react";

import Login from "./Pages/Login";
import Register from "./Pages/Register";
import CartPage from "./Pages/Cart";
import Verify from "./Pages/Verify";
import ForgotPassword from "./Pages/ForgotPassword";
import Checkout from "./Pages/Checkout";
import MyAccount from "./Pages/MyAccount";
import MyList from "./Pages/MyList";
import Orders from "./Pages/Orders";

import toast, { Toaster } from 'react-hot-toast';
import { fetchDataFromApi, postData } from "./utils/api";
import Address from "./Pages/MyAccount/address";
import { OrderSuccess } from "./Pages/Orders/success";
import { OrderFailed } from "./Pages/Orders/failed";
import SearchPage from "./Pages/Search";


const MyContext = createContext();

function App() {
  const [openProductDetailsModal, setOpenProductDetailsModal] = useState({
    open: false,
    item: {}
  });
  const [isLogin, setIsLogin] = useState(false);
  const [userData, setUserData] = useState(null);
  const [catData, setCatData] = useState([]);
  const [cartData, setCartData] = useState([]);
  const [myListData, setMyListData] = useState([]);

  const [openCartPanel, setOpenCartPanel] = useState(false);
  const [openAddressPanel, setOpenAddressPanel] = useState(false);

  const [addressMode, setAddressMode] = useState("add");
  const [addressId, setAddressId] = useState("");
  const [searchData, setSearchData] = useState([]);
  const [windowWidth, setWindowWidth] = useState(window.innerWidth);
```

```
const [openFilter, setOpenFilter] = useState(false);
const [isFilterBtnShow, setisFilterBtnShow] = useState(false);

const [openSearchPanel, setOpenSearchPanel] = useState(false);

const handleOpenProductDetailsModal = (status, item) => {
  setOpenProductDetailsModal({
    open: status,
    item: item
  });
}

const handleCloseProductDetailsModal = () => {
  setOpenProductDetailsModal({
    open: false,
    item: {}
  });
};

const toggleCartPanel = (newOpen) => () => {
  setOpenCartPanel(newOpen);
};

const toggleAddressPanel = (newOpen) => () => {
  if (newOpen == false) {
    setAddressMode("add");
  }

  setOpenAddressPanel(newOpen);
};




useEffect(() => {
  localStorage.removeItem("userEmail")
  const token = localStorage.getItem('accessToken');

  if (token !== undefined && token !== null && token !== "") {
    setIsLogin(true);

    getCartItems();
    getMyListData();
    getUserDetails();

  } else {
    setIsLogin(false);
  }


}, [isLogin])


const getUserDetails = () => {
  fetchDataFromApi(`/api/user/user-details`).then((res) => {
    setUserData(res.data);
    if (res?.response?.data?.error === true) {
      if (res?.response?.data?.message === "You have not login") {
        localStorage.removeItem("accessToken");
        localStorage.removeItem("refreshToken");
        alertBox("error", "Your session is closed please login again");


        //window.location.href = "/login"

        setIsLogin(false);
      }
    }
```

```
  })
}



useEffect(() => {
  fetchDataFromApi("/api/category").then((res) => {
    if (res?.error === false) {
      setCatData(res?.data);
    }
  })

  const handleResize = () => {
    setWindowWidth(window.innerWidth);
  };

  window.addEventListener("resize", handleResize);

  return () => {
    window.removeEventListener("resize", handleResize);
  };

}, []);

const alertBox = (type, msg) => {
  if (type === "success") {
    toast.success(msg)
  }
  if (type === "error") {
    toast.error(msg)
  }
}



const addToCart = (product, userId, quantity) => {

  if (userId === undefined) {
    alertBox("error", "you are not login please login first");
    return false;
  }

  const data = {
    productTitle: product?.name,
    image: product?.image,
    rating: product?.rating,
    price: product?.price,
    oldPrice: product?.oldPrice,
    discount: product?.discount,
    quantity: quantity,
    subTotal: parseInt(product?.price * quantity),
    productId: product?._id,
    countInStock: product?.countInStock,
    brand: product?.brand,
    size: product?.size,
    weight: product?.weight,
    ram: product?.ram
  }


  postData("/api/cart/add", data).then((res) => {
    if (res?.error === false) {
      alertBox("success", res?.message);

      getCartItems();


    } else {
      alertBox("error", res?.message);
```

```
    }

  })


}



const getCartItems = () => {
  fetchDataFromApi(`/api/cart/get`).then((res) => {
    if (res?.error === false) {
      setCartData(res?.data);
    }
  })
}



const getMyListData = () => {
  fetchDataFromApi("/api/myList").then((res) => {
    if (res?.error === false) {
      setMyListData(res?.data)
    }
  })
}

const values = {
  openProductDetailsModal,
  setOpenProductDetailsModal,
  handleOpenProductDetailsModal,
  handleCloseProductDetailsModal,
  setOpenCartPanel,
  toggleCartPanel,
  openCartPanel,
  setOpenAddressPanel,
  toggleAddressPanel,
  openAddressPanel,
  isLogin,
  setIsLogin,
  alertBox,
  setUserData,
  userData,
  setCatData,
  catData,
  addToCart,
  cartData,
  setCartData,
  getCartItems,
  myListData,
  setMyListData,
  getMyListData,
  getUserDetails,
  setAddressMode,
  addressMode,
  addressId,
  setAddressId,
  setSearchData,
  searchData,
  windowWidth,
  setOpenFilter,
  openFilter,
  setisFilterBtnShow,
  isFilterBtnShow,
  setOpenSearchPanel,
  openSearchPanel
};

return (
```

```
    <>
      <BrowserRouter>
        <MyContext.Provider value={values}>
          <Header />
          <Routes>
            <Route path="/" element={<Home />} />
            <Route path="/products" element={<ProductListing />} />
            <Route path="/product/:id" element={<ProductDetails />} />
            <Route path="/login" element={<Login />} />
            <Route path="/register" element={<Register />} />
            <Route path="/cart" element={<CartPage />} />
            <Route path="/verify" element={<Verify />} />
            <Route path="/forgot-password" element={<ForgotPassword />} />
            <Route path="/checkout" element={<Checkout />} />
            <Route path="/my-account" element={<MyAccount />} />
            <Route path="/my-list" element={<MyList />} />
            <Route path="/my-orders" element={<Orders />} />
            <Route path="/order/success" element={<OrderSuccess />} />
            <Route path="/order/failed" element={<OrderFailed />} />
            <Route path="/address" element={<Address />} />
            <Route path="/search" element={<SearchPage />} />
          </Routes>
          <Footer />
        </MyContext.Provider>
      </BrowserRouter>

      <Toaster />
    </>
  );

}

export default App;

export { MyContext };
```

1.3.8 index.css

```
@tailwind base;
@tailwind components;
@tailwind utilities;

*{margin: 0px; padding: 0px; box-sizing: border-box;}


body{
  font-family: "Montserrat", sans-serif;
  font-optical-sizing: auto;
  background: #f5f0f0;
  color: #3e3e3e;
  overflow-x: hidden;
}

p{font-size: 14px; line-height: 25px; margin-bottom: 10px; margin-top: 10px;}

h1, h2, h3, h4, h5, h6{font-weight: 600;}


::-webkit-scrollbar{width: 8px !important; height: 8px !important;}
::-webkit-scrollbar-thumb{background: #ff5252;}
::-webkit-scrollbar-track{background: #fff;}

.overflow-x-auto::-webkit-scrollbar-thumb{background: #ccc;}

.container{width: 95%; margin: auto;}

.btn-org{background: #ff5252 !important; color: #fff !important; font-weight: 500; font-size: 16px;
padding: 7px 20px !important; border:1px solid transparent !important; }
```

```
.btn-org:hover{background: #171717 !important;}

.btn-org.btn-border{background: none !important; color: #ff5252 !important; border:1px solid
#ff5252 !important; font-weight: 500; font-size: 16px; padding: 7px 20px !important;}
.btn-org.btn-border:hover{background: #171717 !important; color: #fff !important;  border:1px solid
#171717 !important;}

.btn-dark{background: #363636 !important; color: #fff !important;  border:1px solid #171717
!important;}
.btn-dark:hover{background: #171717 !important; }


.btn-lg{ font-size: 18px; padding: 10px 20px !important;}
.btn-sm{ font-size: 12px !important; padding: 5px 20px !important;}

.link:hover,.Mui-checked{color: #ff5252 !important;}

.MuiBadge-badge{background-color: #ff5252 !important;}

nav ul button{text-transform: capitalize !important;}

nav ul button:hover{background: none !important;}

.scroll::-webkit-scrollbar{width: 5px !important;}
.scroll::-webkit-scrollbar-thumb{background: #ccc !important;}

.sliderHome{overflow: inherit !important;}

.swiper-button-prev,.swiper-button-next{display: flex; align-items: center; justify-content:
center; background: #fff; border-radius: 100%; width: 45px; height: 45px; min-width: 45px;
  box-shadow: 0 1px 3px #0000001f, 0 1px 2px #0000003d !important; transition:all 0.2s;}

.swiper-button-prev:after,.swiper-button-next:after{font-size: 22px !important; color: #000;}


.smlBtn .swiper-button-prev,.smlBtn .swiper-button-next{width: 30px !important; height: 30px
!important; min-width: 30px !important; top: 55% !important;}
.smlBtn  .swiper-button-prev:after,.smlBtn  .swiper-button-next:after{font-size: 18px !important;
color: #000;}


.homeCatSlider{overflow: inherit !important;}
.homeCatSlider .swiper-button-prev,.homeCatSlider .swiper-button-next{width: 30px; height: 30px;
min-width: 30px;}
.homeCatSlider .swiper-button-prev:after,.homeCatSlider .swiper-button-next:after{font-size: 16px
!important;}

.homeCatSlider .swiper-button-prev{left: -10px !important;}
.homeCatSlider .swiper-button-next{right: -10px !important;}

.homeCatSlider .item{border: 1px solid rgba(0,0,0,0.1);}

.swiper-button-prev:hover,.swiper-button-next:hover{background: #ff5252 !important;}
.swiper-button-prev:hover::after,.swiper-button-next:hover::after{color: #fff !important;}

.homeCatSlider .item:hover img{transform:scale(1.1);}


.MuiTabs-indicator{background-color: #ff5252 !important;}
.MuiTab-textColorPrimary.Mui-selected{color:#ff5252 !important;}

.productsSlider .swiper-wrapper{padding: 15px 8px; margin-left: -15px; margin-right: -15px;}


footer form input::placeholder{font-size: 14px;}

.css-imrjgg-MuiButtonBase-root-MuiCheckbox-root.Mui-checked, .css-imrjgg-MuiButtonBase-root-
MuiCheckbox-root.MuiCheckbox-indeterminate{color:#ff5252 !important;}
```

```
.MuiFormControlLabel-label{font-size: 13px !important; color: rgba(0,0,0,0.8);}

.swiper-pagination-bullet-active{background: #ff5252 !important;}


.homeSliderV2 .swiper-slide-active .info{right: 0px !important; opacity: 1;}
.homeSliderV2 .swiper-slide-active .info h4{right: 0px !important; opacity: 1;}
.homeSliderV2 .swiper-slide-active .info h3{right: 0px !important; opacity: 1;}
.homeSliderV2 .swiper-slide-active .info h2{right: 0px !important; opacity: 1;}
.homeSliderV2 .swiper-slide-active .info .btn_{right: 0px !important; opacity: 1;}

.homeSliderV2 .info h4{transition-duration: 1.2s;}
.homeSliderV2 .info h2{transition-duration: 1.5s;}
.homeSliderV2 .info h3{transition-duration: 1.8s;}
.homeSliderV2 .info .btn_{transition-duration: 2.1s;}

.MuiCheckbox-root{padding:6px !important;}

.ReactCollapse--collapse {
  transition: height 400ms;
}

.itemViewActions button.active svg{color:#ff5252 !important; opacity: 1;}
.Mui-selected.MuiPaginationItem-page{background: #ff5252 !important; color:#fff !important;}

.shadow-md,.shadow-lg{box-shadow: 0 1px 3px rgba(0, 0, 0, 0.12), 0 1px 2px rgba(0, 0, 0, 0.24)
!important;}

.zoomProductSliderThumbs.space .swiper-wrapper{padding-top: 38px !important;}
.zoomProductSliderThumbs .swiper-button-next{bottom: 0px !important; right: inherit !important;
top: inherit !important; width: 100% !important; height: 30px !important; border-radius: 0px
!important;}

.zoomProductSliderThumbs .swiper-button-next:after{transform: rotate(90deg);}

.zoomProductSliderThumbs .swiper-button-prev{top: 20px !important; left:0 !important;  width: 100%
!important; height: 30px !important; border-radius: 0px !important;}

.zoomProductSliderThumbs .swiper-button-prev:after{transform: rotate(90deg);}


.productContent .actions button{min-width: 40px !important; height: 30px !important; border: 1px
solid rgba(0,0,0,0.1) !important; color: rgba(0,0,0,0.7);}
.productContent .actions button.error{ border: 1px solid #ff5252 !important;}

input[type=number]::-webkit-inner-spin-button,
input[type=number]::-webkit-outer-spin-button {
    -webkit-appearance: none;
    -moz-appearance: none;
    appearance: none;
}


.reviewScroll::-webkit-scrollbar{width: 5px !important;}
.reviewScroll::-webkit-scrollbar-thumb{background: #ccc !important;}


.productDetailsModal .MuiDialogContent-root{padding:0px !important;}

.productsSlider .swiper,.blogSection .swiper{overflow: inherit !important;}

.cartPanel .MuiPaper-root{width: 400px; overflow: hidden;}
.addressPanel .MuiPaper-root{width: 500px; overflow: hidden;}


#size-menu .MuiButtonBase-root{font-size: 12px !important;}

.otpBox input{border: 1px solid rgba(0,0,0,0.3) !important; outline: none !important;
  border-radius: 4px;}
```

```
  .otpBox input:focus{border: 1px solid rgba(0,0,0,0.7) !important;}

  .otpPage .container{height:90vh; display: flex;}

  #account-menu .MuiPaper-root{width: 200px !important;}

  .myAccountTabs li a{position: relative; display: block;}
  .myAccountTabs li a:before{content: ''; width: 3px; height: 50%; position: absolute; top: 50%;
left: 0px; background: #ff5252; transition: all 0.3s ease-in-out; opacity: 0;}

  .myAccountTabs li a.active::before{height: 100%; opacity: 1; top: 0px;}
  .myAccountTabs li a.active button svg{color: #ff5252 !important; opacity: 1 !important;}

  button .MuiCircularProgress-root{width:25px !important; height:25px !important;}
  button.btn-org .MuiCircularProgress-root{color: #fff !important;}
  .addtocart .MuiCircularProgress-root{width:20px !important; height:20px !important;}

  .react-international-phone-input{width: 100% !important;}
.react-international-phone-country-selector-button{width: 55px !important;}
.react-international-phone-input-container{border: 1px solid rgba(0,0,0,0.1) !important;}

.MuiDialog-paper{width: 700px !important; max-width: 700px !important;}

.productDetailsModal  .MuiDialog-paper{width: 1200px !important; max-width: 1200px !important;}

header{box-shadow: 0px 1px 5px #0000001a;}

.lazy-load-image-background img{transition: all 0.1s ease-in-out !important ;}

.MuiFormControlLabel-root{margin-right: 0px !important;}

.MuiCircularProgress-root{@apply !text-primary}

.MuiButtonBase-root.MuiMenuItem-root.MuiMenuItem-gutters.selected{@apply !text-primary}

.react-international-phone-country-selector-dropdown{z-index: 100 !important;}

#paypal-button-container{width: 100% !important;}


table td{padding: 8px 17px !important; font-size: 13px !important;}

.searchBox .MuiCircularProgress-root{width: 20px !important; height: 20px !important;}
```

1.3.9 main.jsx

```
import { StrictMode } from 'react'
import { createRoot } from 'react-dom/client'
import './index.css'
import App from './App.jsx'

createRoot(document.getElementById('root')).render(
  <StrictMode>
    <App />
  </StrictMode>,
)
```

1.3.10 responsive.css

```
@media only screen and (min-width:320px) and (max-width:992px){
    html,body{overflow-x: hidden;}


    .btn-sm{padding: 3px 10px !important; font-size: 11px !important;}
    .btn-lg{padding: 5px 10px !important; font-size: 14px !important;}
    .btn{padding: 5px 10px !important; font-size: 12px !important;}
```

```
    .btn svg{font-size: 15px !important;}

    .mobileNav a.active button{@apply !text-primary}
    .navigation ul{white-space: nowrap; overflow-x: scroll; overflow-y: hidden; display: block
!important; text-align: center;}
    .navigation ul::-webkit-scrollbar{display: none !important;}
    .navigation ul li{display: inline-block !important; vertical-align: top !important;}

    .container{width: 95% !important; max-width: 95% !important;}

    .scrollableBox{white-space: nowrap; overflow-x: scroll; overflow-y: hidden; display: block
!important;}
    .scrollableBox::-webkit-scrollbar{display: none !important;}
    .scrollableBox .box{display: inline-block !important; vertical-align: top !important; margin-
right: 12px !important; width: 300px !important;}
    .scrollableBox .box .info *{white-space: break-spaces !important;}

    .scrollableBox .col{display: inline-block !important; vertical-align: top !important; margin-
right: 12px !important; width: 200px !important;}
    .productsSlider .swiper, .blogSection .swiper{overflow: hidden !important;}

    .resBannersSlider{white-space: nowrap; overflow-x: scroll; overflow-y: hidden; display: block
!important;}

    .productsSlider .swiper-wrapper{padding: 7px !important;}
    .resBannersSlider .swiper-slide{display: inline-block !important; vertical-align: top
!important; margin-right: 12px !important; width: 300px !important;}
    .resBannersSlider .swiper-slide *{white-space: break-spaces !important;}

    .footerBoxWrap{padding-left:20px !important ;}
    .footerBoxWrap .col{width: 180px !important;}

    .sidebarWrapper.open{bottom: 0px !important; opacity: 1 !important;}

}

@media only screen and (min-width:320px) and (max-width:767px){
    .MuiTabs-flexContainer button{font-size: 13px !important;}
    .productItem  .addToCartBtn{padding: 7px 13px !important;}

    .part2_col1 li a,.part2_col2 li a{font-size: 13px !important;}

    .sidebar{max-height: 100vh !important; overflow-y: scroll !important; overflow-x: hidden
!important;}
    .sidebar::-webkit-scrollbar{display: none !important;}

    .zoomProductSliderThumbs.space .swiper-wrapper{padding-top: 0px !important;}


}



@media only screen and (min-width:320px) and (max-width:575px){
    .cartPanel .MuiPaper-root,.addressPanel .MuiPaper-root{width: 300px !important;}
}

@media only screen and (min-width:575px) and (max-width:767px){
    .cartPanel .MuiPaper-root,.addressPanel .MuiPaper-root{width: 400px !important;}
}
```

1.4 .env

```
VITE_API_URL=http://localhost:8000

# firebase config keys
VITE_FIREBASE_APP_API_KEY=AIzaSyAGd5Ps4o5q_CyMDuVCw6BUGOxLeANLD-U
VITE_FIREBASE_APP_AUTH_DOMAIN=mtzecommerse.firebaseapp.com
```

```
VITE_FIREBASE_APP_PROJECT_ID=mtzecommerse
VITE_FIREBASE_APP_STORAGE_BUCKET=mtzecommerse.appspot.com
VITE_FIREBASE_APP_MESSAGING_SENDER_ID=6591829041
VITE_FIREBASE_APP_APP_ID=1:6591829041:web:1a23c424207ad6b7113110
VITE_FIREBASE_APP_MEASUREMENT_ID=G-8CYJNX3LZR

VITE_APP_RAZORPAY_KEY_ID=rzp_test_lh06WJjtmN7Evj
VITE_APP_RAZORPAY_KEY_SECRET=cQ1LJqRbvB92QhrWUFO4h2X7


# paypal test key
VITE_APP_PAYPAL_CLIENT_ID=AUnF0fGF7T26mBemePiPUf7xWyYt5-JDt1K-qU6gxBvuRD_4uaKVFs2FzMH0M1N-BU--5rUG-
wlyYXoU

# # paypal live key
# VITE_APP_PAYPAL_CLIENT_ID=AWYIq-kMQvlZT5uwRrf9fRdnOh3fK8kq_vAozAwbdvnkvR-yA1CbmjMZhjGYxxFmnZur-
rLBGVsaUG4e
```

1.5 .gitignore

```
# See https://help.github.com/articles/ignoring-files/ for more about ignoring files.

# dependencies
/node_modules
/.pnp
.pnp.js

# testing
/coverage

# production
/build

# misc
.DS_Store
.env.local
.env.development.local
.env.test.local
.env.production.local

npm-debug.log*
yarn-debug.log*
yarn-error.log*
```

1.6 eslint.config.js

```
import js from '@eslint/js'
import globals from 'globals'
import react from 'eslint-plugin-react'
import reactHooks from 'eslint-plugin-react-hooks'
import reactRefresh from 'eslint-plugin-react-refresh'

export default [
  { ignores: ['dist'] },
  {
    files: ['**/*.{js,jsx}'],
    languageOptions: {
      ecmaVersion: 2020,
      globals: globals.browser,
      parserOptions: {
        ecmaVersion: 'latest',
        ecmaFeatures: { jsx: true },
        sourceType: 'module',
      },
    },
```

```
    settings: { react: { version: '18.3' } },
    plugins: {
      react,
      'react-hooks': reactHooks,
      'react-refresh': reactRefresh,
    },
    rules: {
      ...js.configs.recommended.rules,
      ...react.configs.recommended.rules,
      ...react.configs['jsx-runtime'].rules,
      ...reactHooks.configs.recommended.rules,
      'react/jsx-no-target-blank': 'off',
      'react-refresh/only-export-components': [
        'warn',
        { allowConstantExport: true },
      ],
    },
  },
]
```

1.7 index.html

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <link rel="icon" type="image/svg+xml" href="/vite.svg" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <link rel="preconnect" href="https://fonts.googleapis.com">
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
<link
href="https://fonts.googleapis.com/css2?family=Montserrat:ital,wght@0,100..900;1,100..900&family=Ra
leway:ital,wght@0,100..900;1,100..900&family=Roboto:ital,wght@0,100;0,300;0,400;0,500;0,700;0,900;1
,100;1,300;1,400;1,500;1,700;1,900&display=swap" rel="stylesheet">

    <title>Mern Stack Ecommerce</title>
  </head>
  <body>
    <div id="root"></div>
    <script type="module" src="/src/main.jsx"></script>
    <script src="https://checkout.razorpay.com/v1/checkout.js"></script>
  </body>
</html>
```

1.8 package-lock.json

1.9 package.json

```
{
  "name": "my-project",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "set \"GENERATE_SOURCEMAP=false\" && vite build",
    "lint": "eslint .",
    "preview": "vite preview"
  },
  "dependencies": {
    "@emotion/react": "^11.13.5",
    "@emotion/styled": "^11.13.5",
    "@mui/material": "^6.1.8",
    "@mui/styled-engine-sc": "^6.1.8",
    "@stripe/stripe-js": "^5.6.0",
    "axios": "^1.11.0",
    "firebase": "^11.10.0",
```

```
    "react": "^18.3.1",
    "react-collapse": "^5.1.1",
    "react-dom": "^18.3.1",
    "react-hot-toast": "^2.4.1",
    "react-icons": "^5.3.0",
    "react-inner-image-zoom": "^3.0.2",
    "react-international-phone": "^4.4.0",
    "react-lazy-load-image-component": "^1.6.3",
    "react-range-slider-input": "^3.0.7",
    "react-router-dom": "^7.0.1",
    "styled-components": "^6.1.13",
    "swiper": "^11.1.15"
  },
  "devDependencies": {
    "@eslint/js": "^9.13.0",
    "@types/react": "^18.3.12",
    "@types/react-dom": "^18.3.1",
    "@vitejs/plugin-react": "^4.3.3",
    "autoprefixer": "^10.4.20",
    "eslint": "^9.13.0",
    "eslint-plugin-react": "^7.37.2",
    "eslint-plugin-react-hooks": "^5.0.0",
    "eslint-plugin-react-refresh": "^0.4.14",
    "globals": "^15.11.0",
    "postcss": "^8.4.49",
    "tailwindcss": "^3.4.15",
    "vite": "^5.4.10"
  }
}
```

1.10 postcss.config.js

```
export default {
  plugins: {
    tailwindcss: {},
    autoprefixer: {},
  },
}
```

1.11 tailwind.config.js

```
/** @type {import('tailwindcss').Config} */
export default {
  content: [
    "./index.html",
    "./src/**/*.{js,ts,jsx,tsx}",
  ],
  theme: {
    extend: {
      colors:{
        primary:'#ff5252',
      },
      backgroundColor:{
        primary:'#ff5252',
      }
    },
  },
  plugins: [],
}
```

1.12 vite.config.js

```
import { defineConfig } from 'vite'
import react from '@vitejs/plugin-react'
```

```
// https://vite.dev/config/
export default defineConfig({
  plugins: [react()],
})
```