

60-ITEM MULTIPLE CHOICE EXAMINATION

Subject: SH1804 — Manipulating CSS, DOM, & Event Handling Using jQuery

Instructions: Read each question carefully and select the best answer from the given choices.

1. Which jQuery method is used to add one or more classes to the selected elements?

- A) setClass()
- B) addClass()
- C) appendClass()
- D) toggleClass()

2. How are multiple class names separated when using the addClass() method?

- A) With commas
- B) With semicolons
- C) With whitespace
- D) With plus signs

3. What happens when toggleClass() is executed on an element that already has the specified class?

- A) The class is added again.
- B) The class is removed.
- C) An error is thrown.
- D) Nothing changes.

4. Which jQuery method can be used to both get and set CSS property values?

- A) css()
- B) style()
- C) attr()
- D) html()

5. When setting multiple CSS properties with css(), which syntax format is used?

- A) XML syntax
- B) JSON syntax
- C) YAML syntax
- D) HTML attribute syntax

6. Property-value pairs in the css() method are enclosed in which type of brackets?

- A) Square brackets []
- B) Angle brackets <>
- C) Parentheses ()
- D) Curly braces {}

7. Which method returns the width of an element excluding padding, borders, and margins?

- A) innerWidth()
- B) outerWidth()
- C) width()
- D) css("width")

8. The innerWidth() method includes which of the following element dimensions?

- A) Content width only
- B) Content width and padding ONLY
- C) Content width, padding, and border
- D) Content width, padding, border, and margin

9. Which dimension method calculates size including both padding and borders?

- A) height()
- B) innerHeight()
- C) outerHeight()
- D) marginHeight()

10. Numerical dimension values in jQuery are converted and treated as equivalent measurements in what unit?

- A) Inches
- B) Percentages
- C) Em units
- D) Pixels

11. DOM traversal in jQuery is designed to simplify processes compared to native JavaScript by requiring:

- A) More code
- B) Less code
- C) Complex loops
- D) Raw XML parsing

12. Which jQuery traversal method returns the direct parent element of the selected element?

- A) parents()
- B) parent()
- C) children()
- D) ancestor()

13. What does the parents() method return?

- A) Only the top-most root element
- B) The direct parent element
- C) All ancestor elements of the selected element
- D) All child elements of the parent

14. Which method returns all direct children of the selected element?

- A) children()
- B) siblings()
- C) descendants()
- D) find()

15. To select all sibling elements of a target element, which method is used?

- A) next()
- B) prev()
- C) siblings()
- D) eq()

16. What is returned by the next() method?

- A) The next child element
- B) The next sibling element
- C) All ancestor elements
- D) The direct parent element

17. Which method retrieves previous sibling elements in the DOM hierarchy?

- A) prev() / prevAll()
- B) parent()
- C) children()
- D) back()

18. The eq() method selects an element based on its:

- A) ID name
- B) Class name
- C) Specific index number
- D) Tag name

19. What is the index number of the first element in a set selected by eq()?

- A) -1
- B) 0
- C) 1
- D) 2

20. Which method is used to completely remove elements from the DOM?

- A) empty()
- B) remove()
- C) detachClass()
- D) hide()

21. What does the empty() method remove from a selected element?

- A) The selected element itself
- B) Only the attributes of the element
- C) Any child elements of the selected element
- D) The element's CSS classes

22. When empty() is used on a parent element, what happens to the parent element itself?

- A) It is completely deleted.
- B) It is retained, but its children are removed.
- C) It is converted into a span tag.
- D) It gets hidden using display: none.

23. Which event fires when an element is clicked twice in rapid succession?

- A) click()
- B) dblclick()
- C) mouseenter()
- D) hover()

24. Which event handler occurs when the mouse pointer moves over (enters) an element's area?

- A) mouseleave()
- B) mouseout()
- C) mouseenter()
- D) focus()

25. What event is triggered when the mouse pointer leaves a selected element?

- A) mouseenter()
- B) mouseleave()
- C) blur()
- D) change()

26. Which keyboard event triggers at the moment a key is pressed down?

- A) keyup()
- B) keypress()
- C) keydown()
- D) input()

27. Which event handler function is triggered when a key is released?

- A) keydown()
- B) keyup()
- C) blur()
- D) change()

28. What event handler is used to run code when a form is submitted?

- A) submit()
- B) send()
- C) post()
- D) change()

29. The change() event occurs when:

- A) An element loses focus
- B) The value of an element has been changed
- C) The mouse pointer moves
- D) The window is resized

30. Which event handler is executed when an element receives focus?

- A) blur()
- B) focus()
- C) ready()
- D) active()

31. The blur() event handler occurs when an element:

- A) Gets focus
- B) Loses focus
- C) Is hidden
- D) Is clicked

32. Which event handler is executed as soon as the DOM hierarchy has been fully loaded?

- A) load()
- B) ready()
- C) resize()
- D) scroll()

33. Which event fires when the user resizes the browser window?

- A) scroll()
- B) resize()
- C) change()
- D) scale()

34. What method offers an alternative technique to attach event handlers to selected elements?

- A) bind()
- B) attach()
- C) on()
- D) listen()

35. When using the on() method, what is passed as the first argument?

- A) The event handling function
- B) The actual event listening method (e.g., "click")
- C) The CSS selector
- D) The target DOM element

36. Which method is used to detach or remove an event handler attached with on()?

- A) off()
- B) unbind()
- C) detach()
- D) remove()

37. Event handling functions receive an object that contains event-related properties and methods. What is this object called?

- A) DOM Object
- B) Action Object
- C) Event Object
- D) Response Object

38. Which properties of the Event Object return the mouse X & Y coordinates at the time of the event?

- A) clientX and clientY
- B) pageX and pageY
- C) screenX and screenY
- D) posX and posY

39. The type property of an Event Object returns:

- A) The HTML tag name
- B) The data type of the target element
- C) The name/type of the event (e.g., "click")
- D) The class name of the element

40. In keyboard events, which property returns the key or button that was pressed?

- A) key
- B) code
- C) which
- D) keyCode

41. Which property returns any custom data passed in when the event was bound?

- A) target
- B) data
- C) value
- D) info

42. The target property of an Event Object returns:

- A) The DOM element that initiated the event
- B) The parent element of the active element
- C) The event listener function
- D) The return value of the function

43. Which method prevents default actions (such as a link following a URL)?

- A) stopPropagation()
- B) cancelBubble()
- C) preventDefault()
- D) stop()

44. What does stopPropagation() do?

- A) Stops the script execution completely
- B) Prevents event bubbling to ancestor elements
- C) Prevents forms from submitting
- D) Pauses CSS animations

45. Which jQuery method allows executing event handling functions manually without physical user interaction?

- A) fire()
- B) trigger()
- C) dispatch()
- D) emit()

46. What is a limitation of the trigger() method?

- A) It cannot handle custom events.
- B) It cannot mimic native browser events like clicking anchor tags.
- C) It works only on form elements.
- D) It requires an internet connection.

47. Which method is used to hide selected elements?

- A) show()
- B) hide()
- C) toggle()
- D) remove()

48. Which method alternates between revealing and hiding elements?

- A) slide()
- B) fade()
- C) toggle()
- D) switch()

49. What does the fadeIn() method do?

- A) Makes an element completely invisible instantly
- B) Gradually fades an element until it is visible
- C) Fades an element up to a fixed 50% opacity
- D) Slides the element down

50. Which fading method accepts floating-point values between 0 and 1 to set custom opacity?

- A) fadeIn()
- B) fadeOut()
- C) fadeToggle()
- D) fadeTo()

51. In fadeTo(), what floating-point value represents an opacity level of 60%?

- A) 60
- B) 6.0
- C) 0.6
- D) 0.06

52. Speed arguments in fading and sliding methods take numerical values measured in:

- A) Seconds
- B) Milliseconds
- C) Frames per second
- D) Minutes

53. Which sliding method creates an upward effect to hide an element?

- A) slideDown()
- B) slideUp()
- C) slideToggle()
- D) slideOut()

54. What effect is produced by slideDown()?

- A) Downward sliding effect to show an element
- B) Downward sliding effect to hide an element
- C) Fading out effect
- D) Horizontal expansion

55. Which method allows custom animation to set values or values relative to current values?

- A) animate()
- B) css()
- C) transform()
- D) transition()

56. How are multiple CSS properties separated inside the animate() method's first parameter?

- A) Semicolons
- B) Colons
- C) Commas
- D) Spaces

57. Relative values in animate() can be specified using which operators?

- A) ++ or --
- B) += or -=
- C) == or !=
- D) *= or /=

58. According to the rules of animate(), CSS property names with multiple words must be written in:

- A) kebab-case
- B) SNAKE_CASE
- C) camelCase
- D) PascalCase

59. When using animate(), how should the CSS property margin-right be formatted?

- A) margin-right
- B) margin_right
- C) marginRight
- D) MarginRight

60. How does jQuery handle sequential calls to the animate() method on the same element?

- A) It executes them all simultaneously.
- B) It cancels earlier animations.
- C) It creates an internal queue and executes them sequentially.
- D) It throws a syntax error.

Answer Key

Q#	Ans	Q#	Ans	Q#	Ans	Q#	Ans
1	B	16	B	31	B	46	B
2	C	17	A	32	B	47	B
3	B	18	C	33	B	48	C
4	A	19	B	34	C	49	B
5	B	20	B	35	B	50	D
6	D	21	C	36	A	51	C
7	C	22	B	37	C	52	B
8	B	23	B	38	B	53	B
9	C	24	C	39	C	54	A
10	D	25	B	40	C	55	A
11	B	26	C	41	B	56	C
12	B	27	B	42	A	57	B
13	C	28	A	43	C	58	C
14	A	29	B	44	B	59	C
15	C	30	B	45	B	60	C