

# Contents

|                                                                      |           |
|----------------------------------------------------------------------|-----------|
| <b>1. Overview</b>                                                   | <b>3</b>  |
| <b>2. Tech Stack &amp; Architecture</b>                              | <b>4</b>  |
| 2.1 Core Dependencies . . . . .                                      | 4         |
| 2.2 Deployment Topology . . . . .                                    | 4         |
| 2.3 Authentication Architecture . . . . .                            | 4         |
| 2.4 Row-Level Security Pattern . . . . .                             | 5         |
| 2.5 Database Functions (RPC) . . . . .                               | 5         |
| <b>3. Database Schema</b>                                            | <b>7</b>  |
| 3.1 Core Content Tables . . . . .                                    | 7         |
| 3.2 Therapist Tables . . . . .                                       | 7         |
| 3.3 Submission / Inquiry Tables . . . . .                            | 7         |
| 3.4 Admin / Auth / Messaging Tables . . . . .                        | 8         |
| 3.5 Enumerated Types . . . . .                                       | 9         |
| <b>4. Email System</b>                                               | <b>10</b> |
| 4.1 Email Templates (lib/email/templates.ts) . . . . .               | 10        |
| <b>5. Public Website — Pages &amp; Features</b>                      | <b>11</b> |
| 5.1 Home — / . . . . .                                               | 11        |
| 5.2 About — /about . . . . .                                         | 11        |
| 5.3 Our Therapists — /therapists and /therapists/[slug] . . . . .    | 11        |
| 5.4 Find Your Therapist — /find-your-therapist . . . . .             | 11        |
| 5.5 Intake — /intake . . . . .                                       | 11        |
| 5.6 Support Groups — /support-groups . . . . .                       | 12        |
| 5.7 Contact — /contact . . . . .                                     | 12        |
| 5.8 FAQ — /faq . . . . .                                             | 12        |
| 5.9 Legal Pages — /[slug] . . . . .                                  | 12        |
| 5.10 Accounts, Auth & Messaging . . . . .                            | 12        |
| 5.11 Blog — /blog (disabled) . . . . .                               | 13        |
| 5.12 API Routes Summary . . . . .                                    | 13        |
| <b>6. Admin CRM Dashboard</b>                                        | <b>14</b> |
| 6.1 Navigation . . . . .                                             | 14        |
| 6.2 Overview — /admin . . . . .                                      | 14        |
| 6.3 Session Bookings — /admin/sessions . . . . .                     | 14        |
| 6.4 Find Your Therapist — /admin/match-requests . . . . .            | 14        |
| 6.5 Booking Requests — /admin/bookings . . . . .                     | 14        |
| 6.6 Volunteer Applications — /admin/volunteer-applications . . . . . | 15        |
| 6.7 Inquiries & Group Registrations . . . . .                        | 15        |
| 6.8 Messages — /admin/messages . . . . .                             | 15        |
| 6.9 Therapists — /admin/therapists . . . . .                         | 15        |
| 6.10 Users — /admin/users . . . . .                                  | 15        |
| 6.11 Notification Bell . . . . .                                     | 15        |
| 6.12 Scheduling Overview Calendar . . . . .                          | 15        |
| <b>7. Content Management System</b>                                  | <b>16</b> |
| 7.1 Content Manager Tabs (/admin/content) . . . . .                  | 16        |
| <b>8. Design System</b>                                              | <b>17</b> |
| 8.1 Color Tokens . . . . .                                           | 17        |
| 8.2 Typography Scale (observed conventions) . . . . .                | 17        |

|                                                        |           |
|--------------------------------------------------------|-----------|
| 8.3 Reusable UI Components (components/ui/)            | 17        |
| 8.4 Motion System (components/motion/)                 | 18        |
| 8.5 Signature Visual Treatments                        | 18        |
| <b>9. Environment Variables &amp; Deployment Notes</b> | <b>20</b> |
| 9.1 Environment Variables                              | 20        |
| 9.2 Open Items for Handoff                             | 20        |

---

title: "GESA Platform — Technical Specification"  
 subtitle: "Global Emotional Support Alliance — Website & CRM"  
 author: "Prepared for Roy — VentVest"  
 date: "August 29, 2026"  
 toc: true  
 toc-depth: 3  
 numbersections: true  
 geometry: margin=1in  
 colorlinks: true  
 linkcolor: NavyBlue  
 urlcolor: NavyBlue  
 toccolor: black  
 fontsize: 10.5pt

---

# 1. Overview

GESA (Global Emotional Support Alliance) is a nonprofit platform connecting people in need of emotional support with a global network of verified volunteer therapists, at no cost to the client. The platform consists of a public marketing/intake site, a set of client-facing tools (accounts, chat, session booking), and an internal CRM/admin dashboard for staff to manage therapists, submissions, scheduling, and site content.

**Stack at a glance:** Next.js 14 (App Router, TypeScript) on Vercel, Supabase (Postgres, Auth, Storage, Realtime) as the backend, Resend for transactional email, and an optional Anthropic-powered AI matching engine with a rule-based fallback.

**Repository conventions:** all work is tracked as sequential numbered “Phases” in EXECUTION\_PLAN.md, each ending with a review gate before the next begins. The codebase favors editing existing files over deleting them — deprecated components/fields are commented as unused rather than removed, so nothing is destroyed without explicit confirmation.

## 2. Tech Stack & Architecture

### 2.1 Core Dependencies

| Category            | Library                         | Version                                              |
|---------------------|---------------------------------|------------------------------------------------------|
| Framework           | Next.js                         | 14.2.3 (App Router, TypeScript)                      |
| UI                  | React / React DOM               | ^18                                                  |
| Backend / DB / Auth | @supabase/supabase-js           | ^2.42.0                                              |
| Backend / DB / Auth | @supabase/ssr                   | ^0.12.4                                              |
| Styling             | Tailwind CSS                    | ^3.4.1                                               |
| Animation           | Framer Motion                   | ^11.18.2                                             |
| Icons               | lucide-react                    | ^0.370.0                                             |
| Email               | Resend                          | ^3.2.0                                               |
| Validation          | Zod                             | ^3.23.8                                              |
| AI matching         | @anthropic-ai/sdk               | ^0.32.1 (falls back to a rule-based scorer if unset) |
| Language            | TypeScript                      | ^5                                                   |
| Unit testing        | Jest ^29.7, Testing Library ^16 |                                                      |
| E2E testing         | Playwright                      | ^1.48.0                                              |
| Runtime             | Node.js                         | >= 20                                                |

**NPM scripts:** dev, build, start, lint, typecheck (tsc --noEmit), test (Jest), test:e2e (Playwright), db:types (regenerates lib/database.types.ts from the live Supabase schema).

### 2.2 Deployment Topology

Deployed on **Vercel**, source-controlled on **GitHub**. Three environments map to three Git branches and (intended) three Supabase projects:

| Branch      | Environment   | Supabase Project                                             |
|-------------|---------------|--------------------------------------------------------------|
| main        | Production    | iddeoavrlnvwwfopsacy                                         |
| uat         | UAT           | <i>(not yet created — temporarily points at Dev, see §9)</i> |
| other / PRs | Preview (Dev) | gesa-dev (ggjvpfivyqartvanvhzq)                              |

No `vercel.json` is committed — all configuration lives in Vercel’s dashboard-level environment variables (per environment) rather than in code.

### 2.3 Authentication Architecture

| Client         | File                   | Role                                                                                                                                                            |
|----------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Browser client | lib/supabase/client.ts | <code>createBrowserClient()</code> from <code>@supabase/ssr</code> ; used in every Client Component; fully subject to RLS as the signed-in (or anonymous) user. |

| Client                     | File                                                       | Role                                                                                                                                                           |
|----------------------------|------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Server client              | lib/supabase/server.ts                                     | createServerClient(), session read/written via Next's cookies() API; still runs under the anon key and RLS — never bypasses row-level security.                |
| Admin client               | lib/supabase/admin.ts                                      | Service-role client for privileged server-side work; not yet exercised in production flows (SUPABASE_SERVICE_ROLE_KEY intentionally left unset until needed).  |
| Session-refresh middleware | lib/supabase/middleware.ts (invoked by root middleware.ts) | Standard @supabase/ssr pattern — refreshes the session cookie via supabase.auth.getUser() on every request so Server Components always see current auth state. |

**Auth pages:** /login, /signup, /forgot-password, /reset-password (see §6 for details). A handle\_new\_user() Postgres trigger provisions a profiles row automatically on signup, and a welcome email is sent via sendEmailSafely.

**Roles (AppRole):** admin, reviewer, therapist, client, finance — drives both RLS policies (via a Postgres auth\_role() function) and the requireAdmin() server guard protecting every /admin/\*\* route.

## 2.4 Row-Level Security Pattern

Every public-submission table (inquiries, booking\_requests, match\_requests, session\_bookings, group\_registrations, therapist\_applications, and supporting reference tables like clinic\_locations) follows one consistent policy shape:

1. **Public insert** — the anon role may INSERT, so unauthenticated visitors can submit forms directly from the browser with no service-role key involved.
2. **No public read** — anon/authenticated cannot SELECT these rows, protecting submitter PII (explicitly called out for group\_registrations: insert-only, never publicly readable).
3. **Admin (+ reviewer) read** — \*\_admin\_read policies, resolved through auth\_role(), grant read access to role = 'admin' and, on some tables, role = 'reviewer'.
4. **Admin-only update** — status/lifecycle changes are restricted to role = 'admin' specifically, deliberately *not* bundled with reviewer even on tables whose read policy is bundled.
5. **Narrower therapist-read policies** exist on match\_requests/booking\_requests so a linked therapist account can see only their own matched/booked requests.

The application-level requireAdmin() guard on /admin/\*\* is explicitly defense-in-depth on top of this — every admin query still executes under the signed-in user's own session and is independently enforced by the database policies above, not by trusting the guard alone.

## 2.5 Database Functions (RPC)

| Function                                              | Purpose                                                                                                                                                                                                          |
|-------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>auth_role()</code>                              | Returns the caller's AppRole; kept executable by anon/authenticated since RLS policies call it directly.                                                                                                         |
| <code>get_or_create_my_client()</code>                | Idempotently returns the caller's clients row id.                                                                                                                                                                |
| <code>get_or_create_thread(p_therapist_id)</code>     | Idempotently returns a chat_threads id for a client/therapist pair.                                                                                                                                              |
| <code>get_booked_slots(p_therapist_id, p_date)</code> | SECURITY DEFINER — lets an anonymous visitor see which time slots are already taken without exposing other clients' booking details; the underlying session_bookings table itself stays fully access-restricted. |
| <code>handle_new_user()</code>                        | auth.users insert trigger that provisions the matching profiles row; execute permission revoked from all client roles (trigger-only).                                                                            |

## 3. Database Schema

Source of truth: `lib/database.types.ts` (generated from the live Supabase schema via `npm run db:types`). Postgres schema `public`.

### 3.1 Core Content Tables

| Table                         | Columns                                                                                                                                                                                                                                                                                   |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>blog_posts</code>       | <code>id</code> , <code>slug</code> , <code>title</code> , <code>subtitle</code> , <code>body</code> , <code>author</code> , <code>category</code> , <code>status</code> , <code>published_at</code> , <code>created_at</code><br><i>(feature built but currently disabled site-wide)</i> |
| <code>faqs</code>             | <code>id</code> , <code>question</code> , <code>answer</code> , <code>sort</code>                                                                                                                                                                                                         |
| <code>testimonials</code>     | <code>id</code> , <code>author</code> , <code>quote</code> , <code>role</code> , <code>sort</code>                                                                                                                                                                                        |
| <code>legal_pages</code>      | <code>id</code> , <code>slug</code> , <code>title</code> , <code>body</code> , <code>updated_at</code>                                                                                                                                                                                    |
| <code>crisis_resources</code> | <code>id</code> , <code>region</code> , <code>hotline</code> , <code>hours</code> , <code>language</code> , <code>notes</code> , <code>created_at</code>                                                                                                                                  |
| <code>support_groups</code>   | <code>id</code> , <code>title</code> , <code>description</code> , <code>facilitator_name</code> , <code>schedule</code> , <code>format</code> , <code>location</code> , <code>capacity</code> , <code>register_url</code> , <code>created_at</code>                                       |
| <code>site_content</code>     | <code>id</code> , <code>key</code> (unique), <code>value</code> (jsonb), <code>updated_at</code><br>— generic CMS store, see §8                                                                                                                                                           |

### 3.2 Therapist Tables

| Table                               | Columns                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>therapists</code>             | <code>id</code> , <code>slug</code> , <code>full_name</code> , <code>bio</code> , <code>short_summary</code> , <code>credentials</code> , <code>contact_email</code> , <code>contact_phone</code> , <code>gender</code> , <code>languages[]</code> , <code>specialties[]</code> , <code>tracks[]</code> , <code>session_lengths[]</code> , <code>time_zone</code> , <code>years_experience</code> , <code>photo_url</code> , <code>profile_id</code> (FK → <code>profiles</code> ), <code>is_active</code> , <code>is_verified</code> , <code>verified_at</code> , <code>verified_by</code> , <code>created_at</code> , <code>updated_at</code> |
| <code>therapist_weekly_hours</code> | <code>id</code> , <code>therapist_id</code> (FK), <code>day_of_week</code> (0=Sun..6=Sat), <code>start_time</code> , <code>end_time</code> , <code>created_at</code> — recurring local-time availability                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>therapist_applications</code> | <code>id</code> , <code>full_name</code> , <code>email</code> , <code>phone</code> , <code>credentials_proof</code> , <code>specialties[]</code> , <code>languages[]</code> , <code>meeting_duration</code> (preset or free text), <code>bio</code> , <code>status</code> , <code>notes</code> , <code>reviewed_at</code> , <code>reviewed_by</code> (FK → <code>profiles</code> ), <code>created_at</code>                                                                                                                                                                                                                                     |
| <code>clinic_locations</code>       | <code>id</code> , <code>name</code> , <code>address</code> , <code>is_active</code> , <code>created_at</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

### 3.3 Submission / Inquiry Tables

| Table               | Columns                                                                                                                                                                                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| inquiries           | id, name, email, phone, type, message, created_at — general contact form                                                                                                                                                                                                     |
| booking_requests    | id, name, email, entry_route, matched_therapist_id (FK), status, created_at — simple 4-entry-route intake                                                                                                                                                                    |
| match_requests      | id, name, email, phone, gender_preference, session_format, symptoms[], treatment_type, clinic_location_id (FK), preferred_date, preferred_time, matched_therapist_ids[], selected_therapist_id (FK), ai_reasoning (jsonb), status, created_at — “Find Your Therapist” wizard |
| session_bookings    | id, therapist_id (FK), client_name, client_email, client_phone, client_city, client_birth_year, agreed_terms_at, agreed_privacy_at, session_date, session_time, contact_channel, path, status, created_at — real conflict-free reserved slot                                 |
| group_registrations | id, group_id, name, email, phone, created_at                                                                                                                                                                                                                                 |

**Double-booking protection:** session\_bookings has a **database-level UNIQUE(therapist\_id, session\_date, session\_time) constraint** — the one true hard guarantee against two people booking the same therapist at the same time. match\_requests’ preferred date/time has no such constraint (it is a *preference*, not a reservation) — see §7.3’s conflict-detection UI for how the admin CRM surfaces potential collisions there instead.

### 3.4 Admin / Auth / Messaging Tables

| Table             | Columns                                                                                                                                                                               |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| profiles          | id (= auth.users.id), full_name, email, phone, country, preferred_language, role, created_at, updated_at                                                                              |
| clients           | id, profile_id (FK), full_name, email, phone, country, track, is_minor, guardian_consent_at, is_soldier_or_crisis, free_sessions_total, free_sessions_used, no_show_count, created_at |
| chat_threads      | id, client_id (FK), therapist_id (FK), created_at                                                                                                                                     |
| chat_messages     | id, thread_id (FK), sender_id, body, read_at, created_at — Realtime-enabled                                                                                                           |
| translation_cache | id, source_hash, source_text, target_lang, translated_text, created_at                                                                                                                |



### **3.5 Enumerated Types**

AppRole, DocumentStatus, DocumentType, GenderType, SessionDuration, TrackType, Gender-Preference, SessionFormat, ContactChannel, BookingStatus, MeetingDurationChoice.

## 4. Email System

**File:** `lib/email/resend.ts` — the `sendEmailSafely()` helper is the single choke point for every outbound email:

- If `RESEND_API_KEY` is unset, the Resend client is never constructed; `sendEmailSafely` logs a warning and returns `{ skipped: true }` immediately.
- Any error (Resend API error or thrown exception) is caught and logged, never re-thrown.
- **Design intent:** the underlying database write (signup, booking, inquiry, registration, application) always happens first and is never rolled back or blocked by an email failure. Email is best-effort by design.
- `FROM_EMAIL` defaults to `GESA <no-reply@gesa.org>` if `RESEND_FROM_EMAIL` is unset.

### 4.1 Email Templates (`lib/email/templates.ts`)

| Template pair                                                                                                               | Trigger                                                                                  |
|-----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| welcomeEmail                                                                                                                | New account signup                                                                       |
| contactReceivedEmail /<br>contactNotificationEmail                                                                          | Contact form — sender confirmation +<br>team notification                                |
| volunteerApplicationReceivedEmail /<br>volunteerApplicationNotificationEmail                                                | Volunteer therapist application — applicant<br>confirmation + detailed team notification |
| bookingConfirmationEmail /<br>bookingTeamNotificationEmail /<br>therapistNewMatchEmail                                      | Simple 4-entry-route booking request                                                     |
| matchConfirmationEmail /<br>matchTeamNotificationEmail                                                                      | “Find Your Therapist” wizard<br>preferred-time request                                   |
| sessionBookingConfirmationEmail /<br>sessionBookingTeamNotificationEmail /<br>sessionBookingTherapistNotificationE-<br>mail | Real conflict-free session booking                                                       |
| groupRegistrationEmail                                                                                                      | Support-group registration                                                               |

All templates share a common inline-styled `shell()` layout matching the site’s sage/clay/cream palette. The team-facing notification address defaults to `hello@gesa.org`, overridable via `GESA_CONTACT_INBOX`.

## 5. Public Website — Pages & Features

### 5.1 Home — /

Landing page introducing GESA and its four entry “paths” (crisis, veterans/reservists/families, general support, and previously “helpers” — see design notes below). Built from components/home/Paths.tsx (the gold hero band + three flip-animated path cards), Stats (impact numbers), and DonateBand.

- Path cards link into /intake?path=... — no data is submitted from the Home page itself.
- Fully Content-Manager editable via site\_content key page\_home.
- Opts into the site’s “footer reveal” scroll effect (§9.4).
- Several experiments remain in the codebase, unused but not deleted, per the project’s standing “don’t remove without confirming” rule: a Testimonials section (relocated to Support Groups), a NewsTicker marquee, and an unused purposeTicker CMS field.

### 5.2 About — /about

Mission/story page: hero, “Our Mission” statement, a “How GESA Works” card grid, founder bios (with optional uploaded photos, falling back to initials avatars), a volunteer-recruitment CTA band, and a legal/nonprofit-status blurb. Fully CMS-editable across two site\_content keys (page\_about\_hero, page\_about\_sections). The “Join us as a caregiver” CTA opens the volunteer application modal (writes to therapist\_applications) unless an admin has manually repointed the link elsewhere.

### 5.3 Our Therapists — /therapists and /therapists/[slug]

Public directory of active therapists with a client-side filter sidebar (search, specialty, language, meeting duration, gender) over a pre-fetched list — filtering never re-queries the database. Each therapist’s public profile page (/therapists/[slug]) shows their photo/verified badge, credentials, specialties, languages, session lengths, and bio, with a “Book a free session” link into /intake and a “Message” button that starts an authenticated chat thread. Banner and directory-label copy are CMS-editable; individual therapist profiles are not (they’re live data, not marketing copy).

### 5.4 Find Your Therapist — /find-your-therapist

The guided, no-account-required AI-matching flow: a 4-step wizard (symptom assessment → treatment/gender preferences → format & location → ranked AI matches with stated reasoning). Selecting a match opens a booking modal collecting contact details and a *preferred* date/time, which is submitted to /api/match-booking and stored in match\_requests — explicitly a preference, not a guaranteed slot (see §7.3 for how staff review potential conflicts).

### 5.5 Intake — /intake

The fast “reach out now” path from Home’s cards (?path=crisis|veteran|general|helpers). Runs the same AI matcher server-side, seeded by the selected path, and returns up to three real matches immediately — no multi-step questionnaire. Choosing a therapist opens the platform’s **real, conflict-free scheduling flow**:

1. Contact channel choice (email / WhatsApp / Zoom)
2. A date picker (today through +14 days) that live-fetches genuinely open slots from /api/therapist-availability, which subtracts already-booked times from the therapist’s recurring weekly hours

3. Slot selection, contact details, and two required consent checkboxes (Terms & Conditions, Privacy Policy)
4. Submission to `/api/intake-booking`, which re-validates age/consent server-side, re-checks slot availability, and inserts into `session_bookings` — protected by the database’s unique constraint, so a same-instant double-submission from two visitors returns a friendly “just taken” response (HTTP 409) rather than a silent double-booking.

The crisis path additionally surfaces hotline resources from `crisis_resources` and a disclaimer linking to [findahelpline.com](https://findahelpline.com).

## 5.6 Support Groups — `/support-groups`

A card grid of peer support groups (from `support_groups`); clicking a card opens a sliding detail drawer with a “Register” action that inserts into `group_registrations` and sends a confirmation email. Also renders the relocated “Stories of Healing” testimonials section. Fully CMS-editable (banner + directory/registration labels).

## 5.7 Contact — `/contact`

A general inquiry form (name, email, subject dropdown, message) that inserts into inquiries and best-effort sends a confirmation + team-notification email pair.

## 5.8 FAQ — `/faq`

An accordion of question/answer pairs sourced from the `faqs` table (managed through a dedicated Content Manager tab, not the generic `site_content` mechanism).

## 5.9 Legal Pages — `/[slug]`

A single catch-all route rendering any row in the `legal_pages` table by slug (privacy-policy, cookies-policy, legal-notice, accessibility-statement, terms-and-conditions), returning a 404 for unknown slugs. Managed through its own Content Manager tab, independent of `site_content`.

## 5.10 Accounts, Auth & Messaging

| Route                         | Purpose                                                                                                                                                                                                      |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>/signup</code>          | Client account creation ( <code>supabase.auth.signUp</code> ); therapists apply via the volunteer application modal instead, linked inline. Sends a welcome email.                                           |
| <code>/login</code>           | Sign-in; links to <code>/forgot-password</code> and <code>/signup</code> .                                                                                                                                   |
| <code>/forgot-password</code> | Requests a password-reset email via <code>supabase.auth.resetPasswordForEmail</code> ; always shows the same confirmation regardless of whether the address exists (prevents account enumeration by design). |

| Route                           | Purpose                                                                                                                                                                                                          |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| /reset-password                 | Landing page for the emailed recovery link; sets a new password via <code>supabase.auth.updateUser</code> , using the short-lived recovery session Supabase's browser client detects automatically from the URL. |
| /account                        | Authenticated profile management — name, phone, country, preferred language (email is read-only); admins see a shortcut into the CRM.                                                                            |
| /messages, /messages/[threadId] | Authenticated inbox and 1:1 real-time chat with a therapist, backed by Supabase Realtime on <code>chat_messages</code> .                                                                                         |

### 5.11 Blog — /blog (disabled)

Fully built but intentionally disabled: both `/blog` and `/blog/[slug]` immediately redirect to Home, since there is no published content yet. The Content Manager still has a `page_blog` editor tab ready for when it's re-enabled.

### 5.12 API Routes Summary

| Route                                 | Purpose                                                                                          |
|---------------------------------------|--------------------------------------------------------------------------------------------------|
| POST /api/booking                     | Legacy simple booking-request path from Home's four entry routes → <code>booking_requests</code> |
| POST /api/match-booking               | Backs the Find Your Therapist wizard → <code>match_requests</code>                               |
| POST /api/intake-booking              | The real conflict-free scheduling endpoint → <code>session_bookings</code>                       |
| POST /api/match                       | Generic AI therapist-matching endpoint                                                           |
| GET /api/therapist-availability       | Computes a therapist's genuinely open slots for a given date                                     |
| POST /api/translate                   | Batch text translation (capped at 200 texts/request), backing a site-wide language switcher      |
| POST /api/email/welcome               | Signup welcome email                                                                             |
| POST /api/email/contact               | Contact-form confirmation + notification pair                                                    |
| POST /api/email/group-registration    | Support-group registration confirmation                                                          |
| POST /api/email/volunteer-application | Volunteer application confirmation + team notification                                           |

## 6. Admin CRM Dashboard

Every `/admin/**` route is wrapped by `requireAdmin()` (`app/admin/layout.tsx`), which redirects signed-out visitors to `/login` and any signed-in non-admin role (including reviewer) back to the public site. This is explicitly documented as defense-in-depth on top of the database’s own RLS policies (§2.4), not a substitute for them.

### 6.1 Navigation

The admin sidebar (`AdminNav`) lists 11 sections in order: **Overview, Session bookings, Find Your Therapist, Booking requests, Volunteer Applications, Inquiries, Group registrations, Messages, Therapists, Users, and Content Manager.**

### 6.2 Overview — `/admin`

The CRM’s executive dashboard:

- An **email-configuration warning banner** that checks server-side whether `RE-SEND_API_KEY/GESA_CONTACT_INBOX` are actually set, surfacing a visible alert if notification emails are silently being skipped.
- **Four KPI tiles** (Session bookings, Find Your Therapist, Booking requests, Volunteer applicants), each showing a “new” sub-count and linking to its detail page.
- A hand-rolled **6-month trend chart** (no charting library) bucketing every submission type by month.
- A scrollable **activity feed** of the latest 40 items across all six submission types, with New/Seen state and relative timestamps.
- A **requests comparison bar chart** and a **community panel** (total users, new this week, role breakdown).
- An embedded **Scheduling Overview calendar** (§6.9).

### 6.3 Session Bookings — `/admin/sessions`

Read/status-manage view of confirmed, conflict-free reservations from the Intake flow. Statuses: confirmed, cancelled.

### 6.4 Find Your Therapist — `/admin/match-requests`

Review queue for AI-matched *preferred-time* requests. Statuses: new, contacted, scheduled, closed.

**Conflict detection:** for any request with a selected therapist and a preferred date/time, the page flags (a) an exact collision with an already-confirmed `session_bookings` row (“This therapist is already booked at this time,” shown in red), or (b) another pending `match_requests` row wanting the identical slot (“Also requested by N others for this same slot,” shown in amber). This is a visual warning surfaced to staff at decision time — since a “preferred time” was never meant to be a second hard-booking system, it does not auto-block confirmation.

### 6.5 Booking Requests — `/admin/bookings`

Review queue for the legacy 4-entry-route booking requests. Same status set as Find Your Therapist (new/contacted/scheduled/closed).

## 6.6 Volunteer Applications — /admin/volunteer-applications

Review queue for prospective volunteer therapists. Statuses: new, reviewing, approved, rejected. Explicitly **does not** auto-create a live therapists row on approval — an admin must separately add an approved applicant to the public directory.

## 6.7 Inquiries & Group Registrations

/admin/inquiries and /admin/registrations are simple read-only tables (contact-form submissions and support-group signups respectively) — neither table has a status field in the schema.

## 6.8 Messages — /admin/messages

A **monitoring-only** view of every client↔therapist chat thread, explicitly labeled as such in-product (“for evaluation and monitoring only — conversations remain private between the client and therapist”). No admin write actions exist anywhere in this feature.

## 6.9 Therapists — /admin/therapists

Manage the public therapist directory. The list view supports per-row and bulk selection with an “Activate selected / Deactivate selected” action bar (a single batched database update), plus a per-therapist edit page for profile/bio/photo/language management. Deactivating a therapist hides them from the public directory without deleting their record.

## 6.10 Users — /admin/users

Grants or revokes platform access by changing a user’s role (admin, reviewer, therapist, client, finance). Includes a self-protection guard: an admin cannot demote their own account from this screen.

## 6.11 Notification Bell

A shared header component, role-gated:

- **Admins** see the latest activity across all six submission tables (match requests, booking requests, inquiries, session bookings, volunteer applications, group registrations), polling every 60 seconds, with a detail modal per item.
- **Therapists** see only their own upcoming matched/booked sessions, enforced by the same RLS therapist-read policies described in §2.4.
- Read/unread state is tracked client-side via `localStorage`, not a database column (chosen because each source table’s status enum differs and a single unified “unread” concept doesn’t map cleanly onto them).

## 6.12 Scheduling Overview Calendar

A Google-Calendar-style month view embedded in the Overview page, merging every date-bearing submission type into one place with a color-coded legend (Sessions, Find Your Therapist, Booking requests, Inquiries, Group registrations, Volunteer applicants). Clicking a day opens a full day-view modal. Note: the double-booking **conflict warnings** live specifically on the Find Your Therapist page (§6.4), not on this calendar — the calendar itself is a display surface, not a conflict-detection tool.

## 7. Content Management System

All editable marketing copy lives in one generic table, `site_content` (key unique, value jsonb). Pages read their content through a shared `getPageContent()` helper with a fallback contract: if a key's row is missing or a specific field is absent from its JSON, a hardcoded fallback constant is used instead — so the live site can never render blank, and new editable fields can ship in code before an admin has ever touched the Content Manager UI for them. Writes always use `upsert(..., { onConflict: "key" })` rather than `update`, since a given key's row may not exist yet.

### 7.1 Content Manager Tabs (/admin/content)

| Tab            | site_content key(s)                                     | Notes                                                       |
|----------------|---------------------------------------------------------|-------------------------------------------------------------|
| Header         | site_header                                             | Nav/logo copy                                               |
| Home           | page_home                                               | Hero band + path-card copy                                  |
| About          | page_about_hero,<br>page_about_sections                 | Hero + mission/how-it-works/founders/volunteer CTA          |
| Our Therapists | page_therapists, component_therapists_directory         | Banner + filter/directory labels                            |
| Support Groups | page_support_groups, component_support_groups_directory | Banner + registration-flow labels                           |
| Blog           | page_blog                                               | Copy ready for when the disabled Blog feature is re-enabled |
| FAQ            | page_faq (banner) + the faqs table (questions)          | Two separate mechanisms on one tab                          |
| Contact        | page_contact                                            | Banner                                                      |
| Footer         | page_footer                                             | All footer copy/links                                       |
| Legal Pages    | legal_pages table directly                              | Not part of the site_content system                         |

Image fields (e.g. founder photos) upload directly to Supabase Storage and store the resulting URL as a plain string inside the relevant JSON value.



## 8. Design System

### 8.1 Color Tokens

Defined as CSS custom properties in `app/globals.css`:

| Token                     | Hex               | Role                                              |
|---------------------------|-------------------|---------------------------------------------------|
| --background              | #eef1f6           | Page background — pale powder ivory               |
| --foreground              | #2b3140           | Primary text — deep slate                         |
| --card                    | #e3e8ef           | Card/surface background                           |
| --primary / --primary-600 | #2b3140 / #1d212b | Primary action color + hover state                |
| --secondary / --muted     | #b7c3d6           | Pills, ghost buttons, section bands               |
| --accent                  | #9ba283           | Sage/olive — icons, hover borders                 |
| --accent-soft             | #eaf0e4           | Pale sage wash for badges/pills                   |
| --sage-soft               | #e3ead9           | Richer sage wash for full section bands           |
| --clay / --clay-soft      | #bfa046 / #f5eeda | Muted gold — eyebrow labels, thin borders, badges |
| --amber / --amber-soft    | #8c6f1f / #ede2c0 | Higher-contrast gold accent                       |
| --espresso                | #1d212b           | Footer / strong-contrast surfaces                 |
| --border                  | #c7d0de           | Default border color                              |
| --destructive             | #bb5138           | Error/status color                                |
| --radius                  | 22px              | Global corner radius                              |

**Fonts:** Cormorant Garamond (serif, headings) and Nunito Sans (sans, body) — loaded via a Google Fonts `@import`, mapped to `--font-serif`/`--font-sans` and exposed as Tailwind's `font-serif`/`font-sans`.

### 8.2 Typography Scale (observed conventions)

| Use                            | Size                                                                                               |
|--------------------------------|----------------------------------------------------------------------------------------------------|
| Home hero headline             | <code>clamp(38px, 5vw, 60px)</code>                                                                |
| Secondary-page hero (PageHero) | <code>clamp(32px, 4.5vw, 44px)</code>                                                              |
| Section headings               | 30-34px                                                                                            |
| Sub-section headings           | 22px                                                                                               |
| Admin dashboard headings       | 26px (page title), smaller/plainer elsewhere — a deliberately denser CRM UI vs. the marketing site |

### 8.3 Reusable UI Components (components/ui/)

| Component       | Purpose                                                                                                                                 |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Button          | Polymorphic button/link with four variants — primary (solid), outline, ghost, clay (gold-ringed secondary CTA, never a solid gold fill) |
| Card            | Generic bordered surface with hover lift and accent-tinted border                                                                       |
| PageHero        | Shared banner used by most secondary pages; optional gold variant                                                                       |
| GoldWatermarks  | Very-low-opacity decorative line-art icons for gold-background sections                                                                 |
| HighlightedText | Renders a heading with one substring in an accent color, from a single CMS field                                                        |
| Badge           | Small pill label (sage or clay tone)                                                                                                    |
| Modal           | The site's one reusable dialog (booking, intake, registration flows)                                                                    |
| TagPicker       | Curated-chip + free-text multi-select control (used by the volunteer application form)                                                  |

## 8.4 Motion System (components/motion/)

All timing/easing/distance values come from one shared `config.ts` (durations 0.2–0.9s, a calm no-overshoot easing curve, and small 28–72px entrance offsets) so every animated element in the site moves consistently.

| Primitive                     | Purpose                                                                                            |
|-------------------------------|----------------------------------------------------------------------------------------------------|
| Reveal                        | Fade/slide-in on scroll into view (fade, fade-up, fade-scale, horizontal, horizontal-right, image) |
| StaggerGroup / StaggerItem    | Staggered entrance for card grids and lists                                                        |
| ParallaxLayer / ParallaxMedia | Subtle background/image drift as a section scrolls through view                                    |
| ScrollText                    | Scroll-linked drift reserved for a handful of “hero statement” headlines                           |
| SmoothScroll                  | A spring-smoothed scroll-progress value via React Context — never hijacks real browser scrolling   |
| NewsTicker                    | A genuine infinite marquee (currently unused on the live site, retained in code)                   |

**Reduced motion:** every primitive checks `prefers-reduced-motion` and falls back to instant/opacity-only transitions; the same guard is duplicated at the CSS layer (`.gold-banner`, `.gold-card-hover`, `.reveal-page__*`) as defense-in-depth.

## 8.5 Signature Visual Treatments

- **.gold-banner** — the warm gold gradient background (built from `--clay/--amber`) with a slow animated diagonal sheen, used for Home's hero band, About's hero, and gold-variant PageHero banners.

- **.gold-card-hover** — a one-shot gold light-sweep + glow on hover/focus, used on Home’s three path cards.
- **Footer-reveal effect** — a pure-CSS scroll trick where each opted-in page’s own content acts as an opaque “cover” over a fixed donate-band + footer layer beneath it, uncovered only once the visitor scrolls to the true bottom of the page. Used on Home, About, Our Therapists, and Support Groups; falls back to normal static layout under 760px viewport width or reduced motion.

## 9. Environment Variables & Deployment Notes

### 9.1 Environment Variables

| Variable                      | Exposure    | Purpose                                                                             |
|-------------------------------|-------------|-------------------------------------------------------------------------------------|
| NEXT_PUBLIC_SUPABASE_URL      | Public      | Supabase project URL for the active environment                                     |
| NEXT_PUBLIC_SUPABASE_ANON_KEY | Public      | Anon/publishable key                                                                |
| SUPABASE_SERVICE_ROLE_KEY     | Server-only | Reserved for privileged server-side operations; not yet used in any live flow       |
| RESEND_API_KEY                | Server-only | Blank = every notification email silently no-ops                                    |
| RESEND_FROM_EMAIL             | Server-only | Verified sending address, e.g. GESA <no-reply@gesa.org>                             |
| GESA_CONTACT_INBOX            | Server-only | Destination inbox for contact-form/team notifications                               |
| ANTHROPIC_API_KEY             | Server-only | Powers the AI matching engine; blank = rule-based fallback scorer                   |
| GOOGLE_TRANSLATE_API_KEY      | Server-only | Powers the language switcher; blank = preference is saved but no translation occurs |
| NEXT_PUBLIC_SITE_URL          | Public      | Canonical site URL, used e.g. as the password-reset email's redirect base           |
| NEXT_PUBLIC_APP_ENV           | Public      | development / production flag                                                       |

### 9.2 Open Items for Handoff

- **Production schema lag:** at the time of writing, Production's Supabase project has not yet received the testimonials, legal\_pages, site\_content, and group\_registrations migrations that Dev already has — these must be applied to Production before its next real deploy.
- **UAT environment:** no dedicated Supabase project exists yet for UAT (blocked on the organization's 2-project free-tier cap); the uat branch is temporarily pointed at the Dev project's credentials as a stand-in.
- **Supabase Auth redirect allow-list:** the forgot-password flow's /reset-password redirect must be added to the Supabase project's own Authentication → URL Configuration allow-list (in the Supabase dashboard, not in this codebase) for both the Dev and Production projects, or recovery emails will fail to redirect correctly even though the email itself sends.
- **Service-role key:** currently unset in all environments; only needed if a future feature requires bypassing RLS server-side (none currently do).

---

*This document reflects the codebase as of the phase history recorded in EXECUTION\_PLAN.md at the time of writing. For the authoritative, most current state of any specific feature, defer to the live code and that file's latest entries.*