



GESA Platform

Technical Specification & System Documentation

Prepared by VentVest for Roy

August 2026

Document Control: v1.7 — Confidential — Prepared for internal handoff

Document Control — Version History

Version	Date	Author	Reviewer / Approver	Description
1.0	2026-08-29	R. Rapada	J. Buena	Initial technical specification: tech stack, architecture, database schema, email system, public site pages, admin CRM, content management, design system, and environment/deployment notes.
1.1	2026-08-29	R. Rapada	J. Buena	Rebranded as a professional handoff document — VentVest logo added to the cover page and to a running header on every page, document-control line added to the title page.
1.2	2026-08-29	R. Rapada	J. Buena	Added Functional Requirements, Client Workflow, and Therapist Workflow sections.
1.3	2026-08-30	R. Rapada	J. Buena	Added QA & Testing Reference section — form validation rules, button/CTA inventory, navigation reference, error/empty states, and suggested test scenarios.
1.4	2026-08-30	R. Rapada	J. Buena	Corrected duplicate section numbering throughout; renamed the table of contents to "Tables of Version".
1.5	2026-08-30	R. Rapada	J. Buena	Added this Document Control — Version History page.
1.6	2026-08-30	R. Rapada	J. Buena	Restyled the version-history table with corporate header/row formatting for a cleaner, more professional presentation.
1.7	2026-08-30	R. Rapada	J. Buena	Moved this page to start on page 2 (title page now stands alone); set Author/Reviewer to R. Rapada / J. Buena; switched document font to Arial.

Tables of Version

1 Overview	5
2 Tech Stack & Architecture	6
2.1 Core Dependencies	6
2.2 Deployment Topology	6
2.3 Authentication Architecture	6
2.4 Row-Level Security Pattern	7
2.5 Database Functions (RPC)	7
3 Database Schema	9
3.1 Core Content Tables	9
3.2 Therapist Tables	9
3.3 Submission / Inquiry Tables	9
3.4 Admin / Auth / Messaging Tables	10
3.5 Enumerated Types	10
4 Email System	11
4.1 Email Templates (lib/email/templates.ts)	11
5 Public Website — Pages & Features	12
5.1 Home — /	12
5.2 About — /about	12
5.3 Our Therapists — /therapists and /therapists/[slug]	12
5.4 Find Your Therapist — /find-your-therapist	12
5.5 Intake — /intake	12
5.6 Support Groups — /support-groups	13
5.7 Contact — /contact	13
5.8 FAQ — /faq	13
5.9 Legal Pages — /[slug]	13
5.10 Accounts, Auth & Messaging	13
5.11 Blog — /blog (disabled)	14
5.12 API Routes Summary	14
6 Admin CRM Dashboard	15
6.1 Navigation	15
6.2 Overview — /admin	15
6.3 Session Bookings — /admin/sessions	15
6.4 Find Your Therapist — /admin/match-requests	15
6.5 Booking Requests — /admin/bookings	15
6.6 Volunteer Applications — /admin/volunteer-applications	15
6.7 Inquiries & Group Registrations	16
6.8 Messages — /admin/messages	16
6.9 Therapists — /admin/therapists	16
6.10 Users — /admin/users	16
6.11 Notification Bell	16
6.12 Scheduling Overview Calendar	16
7 Content Management System	17
7.1 Content Manager Tabs (/admin/content)	17
8 Design System	18
8.1 Color Tokens	18
8.2 Typography Scale (observed conventions)	18

8.3	Reusable UI Components (components/ui/)	18
8.4	Motion System (components/motion/)	19
8.5	Signature Visual Treatments	19
9	Environment Variables & Deployment Notes	21
9.1	Environment Variables	21
9.2	Open Items for Handoff	21
10	Functional Requirements	22
10.1	Public Intake & Matching	22
10.2	Public Content & Directory	22
10.3	Accounts, Authentication & Messaging	23
10.4	Volunteer / Therapist Applications	23
10.5	Admin CRM	23
10.6	Email Notifications	23
11	Client Workflow	24
11.1	Entry Points	24
11.2	Choosing and Requesting a Therapist	24
11.3	Conflict-Free Booking Flow	24
11.4	Optional Account and Ongoing Messaging	25
11.5	Key Records Touched	25
12	Therapist Workflow	26
12.1	Application	26
12.2	Admin Review	26
12.3	Manual Promotion to a Listed Therapist	26
12.4	Availability	26
12.5	Appearing Publicly and Receiving Requests	26
12.6	Optional Chat Access	27
12.7	Key Records Touched	27
13	QA & Testing Reference	28
13.1	Form Field Reference & Validation Rules	28
13.2	Button / CTA Inventory	29
13.3	Navigation Reference	30
13.4	Error, Empty & Loading States	30
13.5	Responsive & Accessibility Test Notes	31
13.6	Suggested Functional Test Scenarios	31

1 Overview

GESA (Global Emotional Support Alliance) is a nonprofit platform connecting people in need of emotional support with a global network of verified volunteer therapists, at no cost to the client. The platform consists of a public marketing/intake site, a set of client-facing tools (accounts, chat, session booking), and an internal CRM/admin dashboard for staff to manage therapists, submissions, scheduling, and site content.

Stack at a glance: Next.js 14 (App Router, TypeScript) on Vercel, Supabase (Postgres, Auth, Storage, Realtime) as the backend, Resend for transactional email, and an optional Anthropic-powered AI matching engine with a rule-based fallback.

Repository conventions: all work is tracked as sequential numbered “Phases” in `EXECUTION_PLAN.md`, each ending with a review gate before the next begins. The codebase favors editing existing files over deleting them — deprecated components/fields are commented as unused rather than removed, so nothing is destroyed without explicit confirmation.

2 Tech Stack & Architecture

2.1 Core Dependencies

Category	Library	Version
Framework	Next.js	14.2.3 (App Router, TypeScript)
UI	React / React DOM	^18
Backend / DB / Auth	@supabase/supabase-js	^2.42.0
Backend / DB / Auth	@supabase/ssr	^0.12.4
Styling	Tailwind CSS	^3.4.1
Animation	Framer Motion	^11.18.2
Icons	lucide-react	^0.370.0
Email	Resend	^3.2.0
Validation	Zod	^3.23.8
AI matching	@anthropic-ai/sdk	^0.32.1 (falls back to a rule-based scorer if unset)
Language	TypeScript	^5
Unit testing	Jest ^29.7, Testing Library ^16	
E2E testing	Playwright	^1.48.0
Runtime	Node.js	>= 20

NPM scripts: dev, build, start, lint, typecheck (tsc --noEmit), test (Jest), test:e2e (Playwright), db:types (regenerates lib/database.types.ts from the live Supabase schema).

2.2 Deployment Topology

Deployed on **Vercel**, source-controlled on **GitHub**. Three environments map to three Git branches and (intended) three Supabase projects:

Branch	Environment	Supabase Project
main	Production	iddeoavrlnvwwfopsacy
uat	UAT	(not yet created — temporarily points at Dev, see §9)
other / PRs	Preview (Dev)	gesa-dev (ggjvpfivyqartvanvhzq)

No `vercel.json` is committed — all configuration lives in Vercel's dashboard-level environment variables (per environment) rather than in code.

2.3 Authentication Architecture

Client	File	Role
Browser client	lib/supabase/client.ts	<code>createBrowserClient()</code> from <code>@supabase/ssr</code> ; used in every Client Component; fully subject to RLS as the signed-in (or anonymous) user.

Client	File	Role
Server client	lib/supabase/server.ts	createServerClient(), session read/written via Next's cookies() API; still runs under the anon key and RLS — never bypasses row-level security.
Admin client	lib/supabase/admin.ts	Service-role client for privileged server-side work; not yet exercised in production flows (SUPABASE_SERVICE_ROLE_KEY intentionally left unset until needed).
Session-refresh middleware	lib/supabase/middleware.ts (invoked by root middleware.ts)	Standard @supabase/ssr pattern — refreshes the session cookie via supabase.auth.getUser() on every request so Server Components always see current auth state.

Auth pages: /login, /signup, /forgot-password, /reset-password (see §6 for details). A `handle_new_user()` Postgres trigger provisions a `profiles` row automatically on signup, and a welcome email is sent via `sendEmailSafely`.

Roles (AppRole): `admin`, `reviewer`, `therapist`, `client`, `finance` — drives both RLS policies (via a Postgres `auth_role()` function) and the `requireAdmin()` server guard protecting every `/admin/**` route.

2.4 Row-Level Security Pattern

Every public-submission table (`inquiries`, `booking_requests`, `match_requests`, `session_bookings`, `group_registrations`, `therapist_applications`, and supporting reference tables like `clinic_locations`) follows one consistent policy shape:

1. **Public insert** — the `anon` role may `INSERT`, so unauthenticated visitors can submit forms directly from the browser with no service-role key involved.
2. **No public read** — `anon/authenticated` cannot `SELECT` these rows, protecting submitter PII (explicitly called out for `group_registrations`: insert-only, never publicly readable).
3. **Admin (+ reviewer) read** — `*_admin_read` policies, resolved through `auth_role()`, grant read access to `role = 'admin'` and, on some tables, `role = 'reviewer'`.
4. **Admin-only update** — status/lifecycle changes are restricted to `role = 'admin'` specifically, deliberately *not* bundled with `reviewer` even on tables whose read policy is bundled.
5. **Narrower therapist-read policies** exist on `match_requests/booking_requests` so a linked therapist account can see only their own matched/booked requests.

The application-level `requireAdmin()` guard on `/admin/**` is explicitly defense-in-depth on top of this — every admin query still executes under the signed-in user's own session and is independently enforced by the database policies above, not by trusting the guard alone.

2.5 Database Functions (RPC)

Function	Purpose
<code>auth_role()</code>	Returns the caller's <code>AppRole</code> ; kept executable by <code>anon/authenticated</code> since RLS policies call it directly.
<code>get_or_create_my_client()</code>	Idempotently returns the caller's <code>clients</code> row id.
<code>get_or_create_thread(p_therapist_id)</code>	Idempotently returns a <code>chat_threads</code> id for a client/therapist pair.
<code>get_booked_slots(p_therapist_id, p_date)</code>	SECURITY DEFINER — lets an anonymous visitor see which time slots are already taken without exposing other clients' booking details; the underlying <code>session_bookings</code> table itself stays fully access-restricted.
<code>handle_new_user()</code>	<code>auth.users</code> insert trigger that provisions the matching <code>profiles</code> row; execute permission revoked from all client roles (trigger-only).

3 Database Schema

Source of truth: `lib/database.types.ts` (generated from the live Supabase schema via `npm run db:types`). Postgres schema `public`.

3.1 Core Content Tables

Table	Columns
<code>blog_posts</code>	<code>id</code> , <code>slug</code> , <code>title</code> , <code>subtitle</code> , <code>body</code> , <code>author</code> , <code>category</code> , <code>status</code> , <code>published_at</code> , <code>created_at</code> (<i>feature built but currently disabled site-wide</i>)
<code>faqs</code>	<code>id</code> , <code>question</code> , <code>answer</code> , <code>sort</code>
<code>testimonials</code>	<code>id</code> , <code>author</code> , <code>quote</code> , <code>role</code> , <code>sort</code>
<code>legal_pages</code>	<code>id</code> , <code>slug</code> , <code>title</code> , <code>body</code> , <code>updated_at</code>
<code>crisis_resources</code>	<code>id</code> , <code>region</code> , <code>hotline</code> , <code>hours</code> , <code>language</code> , <code>notes</code> , <code>created_at</code>
<code>support_groups</code>	<code>id</code> , <code>title</code> , <code>description</code> , <code>facilitator_name</code> , <code>schedule</code> , <code>format</code> , <code>location</code> , <code>capacity</code> , <code>register_url</code> , <code>created_at</code>
<code>site_content</code>	<code>id</code> , <code>key</code> (unique), <code>value</code> (jsonb), <code>updated_at</code> — generic CMS store, see §8

3.2 Therapist Tables

Table	Columns
<code>therapists</code>	<code>id</code> , <code>slug</code> , <code>full_name</code> , <code>bio</code> , <code>short_summary</code> , <code>credentials</code> , <code>contact_email</code> , <code>contact_phone</code> , <code>gender</code> , <code>languages[]</code> , <code>specialties[]</code> , <code>tracks[]</code> , <code>session_lengths[]</code> , <code>time_zone</code> , <code>years_experience</code> , <code>photo_url</code> , <code>profile_id</code> (FK → <code>profiles</code>), <code>is_active</code> , <code>is_verified</code> , <code>verified_at</code> , <code>verified_by</code> , <code>created_at</code> , <code>updated_at</code>
<code>therapist_weekly_hours</code>	<code>id</code> , <code>therapist_id</code> (FK), <code>day_of_week</code> (0=Sun..6=Sat), <code>start_time</code> , <code>end_time</code> , <code>created_at</code> — recurring local-time availability
<code>therapist_applications</code>	<code>id</code> , <code>full_name</code> , <code>email</code> , <code>phone</code> , <code>credentials_proof</code> , <code>specialties[]</code> , <code>languages[]</code> , <code>meeting_duration</code> (preset or free text), <code>bio</code> , <code>status</code> , <code>notes</code> , <code>reviewed_at</code> , <code>reviewed_by</code> (FK → <code>profiles</code>), <code>created_at</code>
<code>clinic_locations</code>	<code>id</code> , <code>name</code> , <code>address</code> , <code>is_active</code> , <code>created_at</code>

3.3 Submission / Inquiry Tables

Table	Columns
<code>inquiries</code>	<code>id</code> , <code>name</code> , <code>email</code> , <code>phone</code> , <code>type</code> , <code>message</code> , <code>created_at</code> — general contact form

Table	Columns
booking_requests	id, name, email, entry_route, matched_therapist_id (FK), status, created_at — simple 4-entry-route intake
match_requests	id, name, email, phone, gender_preference, session_format, symptoms[], treatment_type, clinic_location_id (FK), preferred_date, preferred_time, matched_therapist_ids[], selected_therapist_id (FK), ai_reasoning (jsonb), status, created_at — “Find Your Therapist” wizard
session_bookings	id, therapist_id (FK), client_name, client_email, client_phone, client_city, client_birth_year, agreed_terms_at, agreed_privacy_at, session_date, session_time, contact_channel, path, status, created_at — real conflict-free reserved slot
group_registrations	id, group_id, name, email, phone, created_at

Double-booking protection: `session_bookings` has a **database-level** `UNIQUE(therapist_id, session_date, session_time)` **constraint** — the one true hard guarantee against two people booking the same therapist at the same time. `match_requests`’ preferred date/time has no such constraint (it is a *preference*, not a reservation) — see §7.3’s conflict-detection UI for how the admin CRM surfaces potential collisions there instead.

3.4 Admin / Auth / Messaging Tables

Table	Columns
profiles	id (= auth.users.id), full_name, email, phone, country, preferred_language, role, created_at, updated_at
clients	id, profile_id (FK), full_name, email, phone, country, track, is_minor, guardian_consent_at, is_soldier_or_crisis, free_sessions_total, free_sessions_used, no_show_count, created_at
chat_threads	id, client_id (FK), therapist_id (FK), created_at
chat_messages	id, thread_id (FK), sender_id, body, read_at, created_at — Realtime-enabled
translation_cache	id, source_hash, source_text, target_lang, translated_text, created_at

3.5 Enumerated Types

AppRole, DocumentStatus, DocumentType, GenderType, SessionDuration, TrackType, GenderPreference, SessionFormat, ContactChannel, BookingStatus, MeetingDurationChoice.

4 Email System

File: `lib/email/resend.ts` — the `sendEmailSafely()` helper is the single choke point for every outbound email:

- If `RESEND_API_KEY` is unset, the Resend client is never constructed; `sendEmailSafely` logs a warning and returns `{ skipped: true }` immediately.
- Any error (Resend API error or thrown exception) is caught and logged, never re-thrown.
- **Design intent:** the underlying database write (signup, booking, inquiry, registration, application) always happens first and is never rolled back or blocked by an email failure. Email is best-effort by design.
- `FROM_EMAIL` defaults to GESA `<no-reply@gesa.org>` if `RESEND_FROM_EMAIL` is unset.

4.1 Email Templates (`lib/email/templates.ts`)

Template pair	Trigger
<code>welcomeEmail</code>	New account signup
<code>contactReceivedEmail /</code> <code>contactNotificationEmail</code>	Contact form — sender confirmation + team notification
<code>volunteerApplicationReceivedEmail /</code> <code>volunteerApplicationNotificationEmail</code>	Volunteer therapist application — applicant confirmation + detailed team notification
<code>bookingConfirmationEmail /</code> <code>bookingTeamNotificationEmail /</code>	Simple 4-entry-route booking request
<code>therapistNewMatchEmail</code> <code>matchConfirmationEmail /</code> <code>matchTeamNotificationEmail</code>	“Find Your Therapist” wizard preferred-time request
<code>sessionBookingConfirmationEmail /</code> <code>sessionBookingTeamNotificationEmail /</code> <code>sessionBookingTherapistNotificationEmail</code>	Real conflict-free session booking
<code>groupRegistrationEmail</code>	Support-group registration

All templates share a common inline-styled `shell()` layout matching the site’s sage/clay/cream palette. The team-facing notification address defaults to `hello@gesa.org`, overridable via `GESA_CONTACT_INBOX`.

5 Public Website — Pages & Features

5.1 Home — /

Landing page introducing GESA and its four entry “paths” (crisis, veterans/reservists/families, general support, and previously “helpers” — see design notes below). Built from `components/home/Paths.tsx` (the gold hero band + three flip-animated path cards), `Stats` (impact numbers), and `DonateBand`.

- Path cards link into `/intake?path=...` — no data is submitted from the Home page itself.
- Fully Content-Manager editable via `site_content` key `page_home`.
- Opts into the site’s “footer reveal” scroll effect (§9.4).
- Several experiments remain in the codebase, unused but not deleted, per the project’s standing “don’t remove without confirming” rule: a Testimonials section (relocated to Support Groups), a `NewsTicker` marquee, and an unused `purposeTicker` CMS field.

5.2 About — /about

Mission/story page: hero, “Our Mission” statement, a “How GESA Works” card grid, founder bios (with optional uploaded photos, falling back to initials avatars), a volunteer-recruitment CTA band, and a legal/nonprofit-status blurb. Fully CMS-editable across two `site_content` keys (`page_about_hero`, `page_about_sections`). The “Join us as a caregiver” CTA opens the volunteer application modal (writes to `therapist_applications`) unless an admin has manually reointed the link elsewhere.

5.3 Our Therapists — /therapists and /therapists/[slug]

Public directory of active therapists with a client-side filter sidebar (search, specialty, language, meeting duration, gender) over a pre-fetched list — filtering never re-queries the database. Each therapist’s public profile page (`/therapists/[slug]`) shows their photo/verified badge, credentials, specialties, languages, session lengths, and bio, with a “Book a free session” link into `/intake` and a “Message” button that starts an authenticated chat thread. Banner and directory-label copy are CMS-editable; individual therapist profiles are not (they’re live data, not marketing copy).

5.4 Find Your Therapist — /find-your-therapist

The guided, no-account-required AI-matching flow: a 4-step wizard (symptom assessment → treatment/gender preferences → format & location → ranked AI matches with stated reasoning). Selecting a match opens a booking modal collecting contact details and a *preferred* date/time, which is submitted to `/api/match-booking` and stored in `match_requests` — explicitly a preference, not a guaranteed slot (see §7.3 for how staff review potential conflicts).

5.5 Intake — /intake

The fast “reach out now” path from Home’s cards (`?path=crisis|veteran|general|helpers`). Runs the same AI matcher server-side, seeded by the selected path, and returns up to three real matches immediately — no multi-step questionnaire. Choosing a therapist opens the platform’s **real, conflict-free scheduling flow**:

1. Contact channel choice (email / WhatsApp / Zoom)
2. A date picker (today through +14 days) that live-fetches genuinely open slots from `/api/therapist-availability`, which subtracts already-booked times from the therapist’s recurring weekly hours
3. Slot selection, contact details, and two required consent checkboxes (Terms & Conditions, Privacy Policy)
4. Submission to `/api/intake-booking`, which re-validates age/consent server-side, re-checks slot availability, and inserts into `session_bookings` — protected by the database’s unique constraint, so a

same-instant double-submission from two visitors returns a friendly “just taken” response (HTTP 409) rather than a silent double-booking.

The crisis path additionally surfaces hotline resources from `crisis_resources` and a disclaimer linking to `findahelpline.com`.

5.6 Support Groups — /support-groups

A card grid of peer support groups (from `support_groups`); clicking a card opens a sliding detail drawer with a “Register” action that inserts into `group_registrations` and sends a confirmation email. Also renders the relocated “Stories of Healing” testimonials section. Fully CMS-editable (banner + directory/registration labels).

5.7 Contact — /contact

A general inquiry form (name, email, subject dropdown, message) that inserts into `inquiries` and best-effort sends a confirmation + team-notification email pair.

5.8 FAQ — /faq

An accordion of question/answer pairs sourced from the `faqs` table (managed through a dedicated Content Manager tab, not the generic `site_content` mechanism).

5.9 Legal Pages — /[slug]

A single catch-all route rendering any row in the `legal_pages` table by slug (`privacy-policy`, `cookies-policy`, `legal-notice`, `accessibility-statement`, `terms-and-conditions`), returning a 404 for unknown slugs. Managed through its own Content Manager tab, independent of `site_content`.

5.10 Accounts, Auth & Messaging

Route	Purpose
/signup	Client account creation (<code>supabase.auth.signUp</code>); therapists apply via the volunteer application modal instead, linked inline. Sends a welcome email.
/login	Sign-in; links to <code>/forgot-password</code> and <code>/signup</code> .
/forgot-password	Requests a password-reset email via <code>supabase.auth.resetPasswordForEmail</code> ; always shows the same confirmation regardless of whether the address exists (prevents account enumeration by design).
/reset-password	Landing page for the emailed recovery link; sets a new password via <code>supabase.auth.updateUser</code> , using the short-lived recovery session. Supabase’s browser client detects automatically from the URL.
/account	Authenticated profile management — name, phone, country, preferred language (email is read-only); admins see a shortcut into the CRM.

Route	Purpose
/messages, /messages/[threadId]	Authenticated inbox and 1:1 real-time chat with a therapist, backed by Supabase Realtime on chat_messages.

5.11 Blog — /blog (disabled)

Fully built but intentionally disabled: both /blog and /blog/[slug] immediately redirect to Home, since there is no published content yet. The Content Manager still has a page_blog editor tab ready for when it's re-enabled.

5.12 API Routes Summary

Route	Purpose
POST /api/booking	Legacy simple booking-request path from Home's four entry routes → booking_requests
POST /api/match-booking	Backs the Find Your Therapist wizard → match_requests
POST /api/intake-booking	The real conflict-free scheduling endpoint → session_bookings
POST /api/match	Generic AI therapist-matching endpoint
GET /api/therapist-availability	Computes a therapist's genuinely open slots for a given date
POST /api/translate	Batch text translation (capped at 200 texts/request), backing a site-wide language switcher
POST /api/email/welcome	Signup welcome email
POST /api/email/contact	Contact-form confirmation + notification pair
POST /api/email/group-registration	Support-group registration confirmation
POST /api/email/volunteer-application	Volunteer application confirmation + team notification

6 Admin CRM Dashboard

Every `/admin/**` route is wrapped by `requireAdmin()` (`app/admin/layout.tsx`), which redirects signed-out visitors to `/login` and any signed-in non-admin role (including `reviewer`) back to the public site. This is explicitly documented as defense-in-depth on top of the database's own RLS policies (§2.4), not a substitute for them.

6.1 Navigation

The admin sidebar (`AdminNav`) lists 11 sections in order: **Overview**, **Session bookings**, **Find Your Therapist**, **Booking requests**, **Volunteer Applications**, **Inquiries**, **Group registrations**, **Messages**, **Therapists**, **Users**, and **Content Manager**.

6.2 Overview — `/admin`

The CRM's executive dashboard:

- An **email-configuration warning banner** that checks server-side whether `RESEND_API_KEY/GESA_CONTACT_INBOX` are actually set, surfacing a visible alert if notification emails are silently being skipped.
- **Four KPI tiles** (Session bookings, Find Your Therapist, Booking requests, Volunteer applicants), each showing a “new” sub-count and linking to its detail page.
- A hand-rolled **6-month trend chart** (no charting library) bucketing every submission type by month.
- A scrollable **activity feed** of the latest 40 items across all six submission types, with New/Seen state and relative timestamps.
- A **requests comparison bar chart** and a **community panel** (total users, new this week, role breakdown).
- An embedded **Scheduling Overview calendar** (§6.9).

6.3 Session Bookings — `/admin/sessions`

Read/status-manage view of confirmed, conflict-free reservations from the Intake flow. Statuses: `confirmed`, `cancelled`.

6.4 Find Your Therapist — `/admin/match-requests`

Review queue for AI-matched *preferred-time* requests. Statuses: `new`, `contacted`, `scheduled`, `closed`.

Conflict detection: for any request with a selected therapist and a preferred date/time, the page flags (a) an exact collision with an already-confirmed `session_bookings` row (“This therapist is already booked at this time,” shown in red), or (b) another pending `match_requests` row wanting the identical slot (“Also requested by N others for this same slot,” shown in amber). This is a visual warning surfaced to staff at decision time — since a “preferred time” was never meant to be a second hard-booking system, it does not auto-block confirmation.

6.5 Booking Requests — `/admin/bookings`

Review queue for the legacy 4-entry-route booking requests. Same status set as Find Your Therapist (`new/contacted/scheduled/closed`).

6.6 Volunteer Applications — `/admin/volunteer-applications`

Review queue for prospective volunteer therapists. Statuses: `new`, `reviewing`, `approved`, `rejected`. Explicitly **does not** auto-create a live `therapists` row on approval — an admin must separately add an approved applicant to the public directory.

6.7 Inquiries & Group Registrations

`/admin/inquiries` and `/admin/registrations` are simple read-only tables (contact-form submissions and support-group signups respectively) — neither table has a status field in the schema.

6.8 Messages — `/admin/messages`

A **monitoring-only** view of every client ↔ therapist chat thread, explicitly labeled as such in-product (“for evaluation and monitoring only — conversations remain private between the client and therapist”). No admin write actions exist anywhere in this feature.

6.9 Therapists — `/admin/therapists`

Manage the public therapist directory. The list view supports per-row and bulk selection with an “Activate selected / Deactivate selected” action bar (a single batched database update), plus a per-therapist edit page for profile/bio/photo/language management. Deactivating a therapist hides them from the public directory without deleting their record.

6.10 Users — `/admin/users`

Grants or revokes platform access by changing a user's role (admin, reviewer, therapist, client, finance). Includes a self-protection guard: an admin cannot demote their own account from this screen.

6.11 Notification Bell

A shared header component, role-gated:

- **Admins** see the latest activity across all six submission tables (match requests, booking requests, inquiries, session bookings, volunteer applications, group registrations), polling every 60 seconds, with a detail modal per item.
- **Therapists** see only their own upcoming matched/booked sessions, enforced by the same RLS therapist-read policies described in §2.4.
- Read/unread state is tracked client-side via `localStorage`, not a database column (chosen because each source table's status enum differs and a single unified “unread” concept doesn't map cleanly onto them).

6.12 Scheduling Overview Calendar

A Google-Calendar-style month view embedded in the Overview page, merging every date-bearing submission type into one place with a color-coded legend (Sessions, Find Your Therapist, Booking requests, Inquiries, Group registrations, Volunteer applicants). Clicking a day opens a full day-view modal. Note: the double-booking **conflict warnings** live specifically on the Find Your Therapist page (§6.4), not on this calendar — the calendar itself is a display surface, not a conflict-detection tool.

7 Content Management System

All editable marketing copy lives in one generic table, `site_content` (key unique, value jsonb). Pages read their content through a shared `getPageContent()` helper with a fallback contract: if a key's row is missing or a specific field is absent from its JSON, a hardcoded fallback constant is used instead — so the live site can never render blank, and new editable fields can ship in code before an admin has ever touched the Content Manager UI for them. Writes always use `upsert(..., { onConflict: "key" })` rather than `update`, since a given key's row may not exist yet.

7.1 Content Manager Tabs (/admin/content)

Tab	site_content key(s)	Notes
Header	site_header	Nav/logo copy
Home	page_home	Hero band + path-card copy
About	page_about_hero, page_about_sections	Hero + mission/how-it-works/founders/volunteer CTA
Our Therapists	page_therapists, component_therapists_directory	Banner + filter/directory labels
Support Groups	page_support_groups, component_support_groups_directory	Banner + registration-flow labels
Blog	page_blog	Copy ready for when the disabled Blog feature is re-enabled
FAQ	page_faq (banner) + the faqs table (questions)	Two separate mechanisms on one tab
Contact	page_contact	Banner
Footer	page_footer	All footer copy/links
Legal Pages	legal_pages table directly	Not part of the site_content system

Image fields (e.g. founder photos) upload directly to Supabase Storage and store the resulting URL as a plain string inside the relevant JSON value.

8 Design System

8.1 Color Tokens

Defined as CSS custom properties in `app/globals.css`:

Token	Hex	Role
<code>--background</code>	<code>#eef1f6</code>	Page background — pale powder ivory
<code>--foreground</code>	<code>#2b3140</code>	Primary text — deep slate
<code>--card</code>	<code>#e3e8ef</code>	Card/surface background
<code>--primary / --primary-600</code>	<code>#2b3140 / #1d212b</code>	Primary action color + hover state
<code>--secondary / --muted</code>	<code>#b7c3d6</code>	Pills, ghost buttons, section bands
<code>--accent</code>	<code>#9ba283</code>	Sage/olive — icons, hover borders
<code>--accent-soft</code>	<code>#eaf0e4</code>	Pale sage wash for badges/pills
<code>--sage-soft</code>	<code>#e3ead9</code>	Richer sage wash for full section bands
<code>--clay / --clay-soft</code>	<code>#bfa046 / #f5eeda</code>	Muted gold — eyebrow labels, thin borders, badges
<code>--amber / --amber-soft</code>	<code>#8c6f1f / #ede2c0</code>	Higher-contrast gold accent
<code>--espresso</code>	<code>#1d212b</code>	Footer / strong-contrast surfaces
<code>--border</code>	<code>#c7d0de</code>	Default border color
<code>--destructive</code>	<code>#bb5138</code>	Error/status color
<code>--radius</code>	<code>22px</code>	Global corner radius

Fonts: Cormorant Garamond (serif, headings) and Nunito Sans (sans, body) — loaded via a Google Fonts `@import`, mapped to `--font-serif/--font-sans` and exposed as Tailwind's `font-serif/font-sans`.

8.2 Typography Scale (observed conventions)

Use	Size
Home hero headline	<code>clamp(38px, 5vw, 60px)</code>
Secondary-page hero (PageHero)	<code>clamp(32px, 4.5vw, 44px)</code>
Section headings	30–34px
Sub-section headings	22px
Admin dashboard headings	26px (page title), smaller/plainer elsewhere — a deliberately denser CRM UI vs. the marketing site

8.3 Reusable UI Components (`components/ui/`)

Component	Purpose
Button	Polymorphic button/link with four variants — primary (solid), outline, ghost, clay (gold-ringed secondary CTA, never a solid gold fill)
Card	Generic bordered surface with hover lift and accent-tinted border
PageHero	Shared banner used by most secondary pages; optional gold variant
GoldWatermarks	Very-low-opacity decorative line-art icons for gold-background sections
HighlightedText	Renders a heading with one substring in an accent color, from a single CMS field
Badge	Small pill label (sage or clay tone)
Modal	The site's one reusable dialog (booking, intake, registration flows)
TagPicker	Curated-chip + free-text multi-select control (used by the volunteer application form)

8.4 Motion System (components/motion/)

All timing/easing/distance values come from one shared `config.ts` (durations 0.2–0.9s, a calm no-overshoot easing curve, and small 28–72px entrance offsets) so every animated element in the site moves consistently.

Primitive	Purpose
Reveal	Fade/slide-in on scroll into view (fade, fade-up, fade-scale, horizontal, horizontal-right, image)
StaggerGroup / StaggerItem	Staggered entrance for card grids and lists
ParallaxLayer / ParallaxMedia	Subtle background/image drift as a section scrolls through view
ScrollText	Scroll-linked drift reserved for a handful of “hero statement” headlines
SmoothScroll	A spring-smoothed scroll-progress value via React Context — never hijacks real browser scrolling
NewsTicker	A genuine infinite marquee (currently unused on the live site, retained in code)

Reduced motion: every primitive checks `prefers-reduced-motion` and falls back to instant/opacity-only transitions; the same guard is duplicated at the CSS layer (`.gold-banner`, `.gold-card-hover`, `.reveal-page_*`) as defense-in-depth.

8.5 Signature Visual Treatments

- `.gold-banner` — the warm gold gradient background (built from `--clay`/`--amber`) with a slow animated diagonal sheen, used for Home's hero band, About's hero, and gold-variant `PageHero` banners.
- `.gold-card-hover` — a one-shot gold light-sweep + glow on hover/focus, used on Home's three path cards.
- Footer-reveal effect** — a pure-CSS scroll trick where each opted-in page's own content acts as an opaque “cover” over a fixed donate-band + footer layer beneath it, uncovered only once the visitor

scrolls to the true bottom of the page. Used on Home, About, Our Therapists, and Support Groups; falls back to normal static layout under 760px viewport width or reduced motion.

9 Environment Variables & Deployment Notes

9.1 Environment Variables

Variable	Exposure	Purpose
NEXT_PUBLIC_SUPABASE_URL	Public	Supabase project URL for the active environment
NEXT_PUBLIC_SUPABASE_ANON_KEY	Public	Anon/publishable key
SUPABASE_SERVICE_ROLE_KEY	Server-only	Reserved for privileged server-side operations; not yet used in any live flow
RESEND_API_KEY	Server-only	Blank = every notification email silently no-ops
RESEND_FROM_EMAIL	Server-only	Verified sending address, e.g. GESA <no-reply@gesa.org>
GESA_CONTACT_INBOX	Server-only	Destination inbox for contact-form/team notifications
ANTHROPIC_API_KEY	Server-only	Powers the AI matching engine; blank = rule-based fallback scorer
GOOGLE_TRANSLATE_API_KEY	Server-only	Powers the language switcher; blank = preference is saved but no translation occurs
NEXT_PUBLIC_SITE_URL	Public	Canonical site URL, used e.g. as the password-reset email's redirect base
NEXT_PUBLIC_APP_ENV	Public	development / production flag

9.2 Open Items for Handoff

- **Production schema lag:** at the time of writing, Production's Supabase project has not yet received the `testimonials`, `legal_pages`, `site_content`, and `group_registrations` migrations that Dev already has — these must be applied to Production before its next real deploy.
- **UAT environment:** no dedicated Supabase project exists yet for UAT (blocked on the organization's 2-project free-tier cap); the `uat` branch is temporarily pointed at the Dev project's credentials as a stand-in.
- **Supabase Auth redirect allow-list:** the forgot-password flow's `/reset-password` redirect must be added to the Supabase project's own Authentication → URL Configuration allow-list (in the Supabase dashboard, not in this codebase) for both the Dev and Production projects, or recovery emails will fail to redirect correctly even though the email itself sends.
- **Service-role key:** currently unset in all environments; only needed if a future feature requires bypassing RLS server-side (none currently do).

10 Functional Requirements

The following requirements are derived directly from the current codebase (routes, API handlers, and table schemas) and describe what the system does today, not aspirational scope.

10.1 Public Intake & Matching

- **FR-1** — The system shall offer a 4-step “Find Your Therapist” wizard (Assessment → Preferences → Format & Location → Matches), usable without an account. (`app/find-your-therapist/page.tsx`, `components/match/MatchWizard.tsx`)
- **FR-2** — The system shall offer a quick-entry path (`/intake?path=crisis|veteran|general|helpers`) that returns AI-matched therapists without a multi-step form. (`app/intake/page.tsx`)
- **FR-3** — The system shall rank up to 3 candidate therapists using an AI matching engine (Anthropic Claude, model `claude-haiku-4-5-20251001`) against symptoms, treatment type, and gender preference, with a deterministic rule-based scorer as fallback if the API key is unset or the call fails. (`lib/ai/matchTherapists.ts`)
- **FR-4** — Gender preference shall act as a hard filter on the candidate pool; if no therapist matches, the system shall fall back to the unfiltered pool and explicitly flag `genderPreferenceHonored: false` so the UI can disclose this to the client.
- **FR-5** — The system shall expose a stateless matching endpoint, `POST /api/match`, for the wizard's client-side “Matches” step.
- **FR-6** — The system shall record a preferred-time match/booking request (not a guaranteed slot) via `POST /api/match-booking`, writing to `match_requests` and emailing the client, the GESA team inbox, and the matched therapist if a contact email is on file.
- **FR-7** — The system shall record legacy simple booking requests via `POST /api/booking`, writing to `booking_requests`, with the same three-way email fan-out.
- **FR-8** — The system shall support conflict-free scheduling: `GET /api/therapist-availability` computes open slots from weekly therapist hours minus already-booked times, and `POST /api/intake-booking` performs the actual reservation into `session_bookings`, guarded by a unique (`therapist_id`, `session_date`, `session_time`) database constraint that returns HTTP 409 on a double-booking attempt.
- **FR-9** — The booking flow shall enforce legal consent server-side: an age check (must be 18 or older, computed from birth year) and two required consent checkboxes (terms & conditions, privacy policy), persisted as timestamps rather than booleans.
- **FR-10** — The system shall let a client choose a contact channel per booking — email, WhatsApp, or Zoom — and shall require a phone number when WhatsApp is selected.

10.2 Public Content & Directory

- **FR-11** — The system shall present a public directory of active, verified therapists and individual therapist profile pages, incrementally regenerated every 60 seconds.
- **FR-12** — The system shall present a blog, an FAQ, a support-groups directory, an about page, and legal pages (privacy policy, terms), all driven from editable content tables rather than hard-coded copy.
- **FR-13** — The system shall accept general contact-form submissions, writing to an `inquiries` table (name, email, phone, type, message).
- **FR-14** — The system shall accept support-group registrations, writing to `group_registrations` (group, name, email, phone).
- **FR-15** — The system shall support live UI translation via a translation API with a caching table keyed by content hash and target language, plus a static Hebrew dictionary as a bundled fallback.
- **FR-16** — The system shall surface region-specific crisis hotline resources on the crisis intake path and via a persistent, always-visible crisis button.
- **FR-17** — The system shall manage all editable public-site copy (home hero, about sections, footer, header navigation, FAQ, legal pages, support-groups directory, therapists directory) through a CMS-

style key/value content table, edited from an admin content manager.

10.3 Accounts, Authentication & Messaging

- **FR-18** — The system shall support email/password signup for clients only; the signup screen explicitly redirects prospective therapists to the volunteer application flow instead of self-registration.
- **FR-19** — The system shall support login, forgot-password request, and password reset, with the deliberate anti-enumeration behavior of always showing a “check your email” confirmation regardless of whether the address has an account.
- **FR-20** — The system shall send a welcome email on signup, sent best-effort and never blocking account creation if delivery fails.
- **FR-21** — The system shall let signed-in users view and edit their own profile, with a shortcut into the admin CRM shown only to users with the admin role.
- **FR-22** — The system shall support real-time one-to-one chat between a client and a therapist, using a database-driven real-time subscription so new messages appear without a page reload; threads are created on demand from a therapist’s profile page.
- **FR-23** — The system shall enforce role-based access control with distinct roles (admin, reviewer, therapist, client, finance); all admin-only pages shall be restricted specifically to the admin role, enforced at both the application layer and the database row-level-security layer.

10.4 Volunteer / Therapist Applications

- **FR-24** — The system shall accept a structured volunteer-therapist application (name, email, optional phone, credentials/proof of license, one or more specialties, one or more languages, session-length preference, bio), inserted directly into an applications table and confirmed by email.
- **FR-25** — Approving a volunteer application shall be a tracking label only; the system shall not automatically create a public therapist listing from an approved application — promoting an applicant to a listed therapist is a separate, manual administrative action.

10.5 Admin CRM

- **FR-26** — The system shall provide an admin dashboard with KPI tiles (session bookings, match requests, booking requests, volunteer applicants), a rolling activity trend chart, a combined user-activity feed, and a scheduling-overview calendar that merges every date-bearing record type into one view.
- **FR-27** — The system shall provide dedicated management screens, each with inline status controls, for booking requests, match requests, session bookings (including double-booking conflict detection), volunteer applications, inquiries, group registrations, user role assignment, the therapist directory (bulk activate/deactivate, per-record edit), chat oversight, and site content.
- **FR-28** — The system shall let an admin edit a therapist’s public profile (photo upload, bio, credentials, contact details, specialties, languages) and toggle whether that therapist is publicly active.
- **FR-29** — The system shall detect and visibly warn administrators, in the dashboard itself, when transactional email is not actually configured (missing API key or missing destination inbox), rather than failing silently.

10.6 Email Notifications

- **FR-30** — On an AI-matched request, the system shall email the client, the GESA team inbox, and the matched therapist (if a contact address is on file).
- **FR-31** — On a conflict-free session booking, the system shall email the client, the GESA team inbox, and the therapist.
- **FR-32** — On a legacy booking request, contact-form submission, group registration, volunteer application, and account signup, the system shall send the corresponding confirmation and/or notification email via a dedicated email endpoint for that event type.

11 Client Workflow

This section describes the end-to-end journey of a client (a person seeking support) through the platform. No account is required to complete an intake, a match, or a real booking — those steps write plain contact-detail records keyed by email, not by an authenticated user id. Account creation is a separate, optional track that unlocks profile management and ongoing chat with a therapist.

11.1 Entry Points

A client reaches the matching experience by one of three routes:

1. **Homepage paths** — the home page presents a small set of “paths” (crisis, veteran/reservist/family, seeking help, helping the helpers) that lead into the quick-entry intake flow, alongside general calls to action into the guided wizard or the public therapist directory.
2. **Quick-entry intake** (`/intake?path=...`) — the chosen path is mapped to a matching hint and fed directly into the AI matching engine with no form to fill in. The crisis path additionally surfaces regional crisis hotline resources above the matches.
3. **Guided wizard** (`/find-your-therapist`) — a four-step form: symptoms/assessment, treatment type and gender preference, session format (online, phone call, or in person — with a clinic location picker for in-person), and finally a “Matches” step that calls the matching endpoint and displays up to three therapist cards, with a disclosure banner if the requested gender preference could not be honored.

A client may also start from the public therapist directory, browse individual profiles, and either begin a booking directly or (if signed in) message a therapist to start a real-time chat thread.

11.2 Choosing and Requesting a Therapist

From either the quick-entry flow or the wizard, the client selects a matched therapist and is shown a brief, plain-language explanation of why that therapist was suggested. From here there are two distinct request types in the system:

- **Preferred-time request** (from the guided wizard’s “Book a Session” action) — collects name, email, phone, and a preferred date/time. This is a request, not a confirmed slot; it is written to the match-requests table and reviewed/actioned by admin staff.
- **Conflict-free session booking** (from the quick-entry intake flow’s “Choose this therapist” action) — a true reservation against the therapist’s real weekly availability, described next.

11.3 Conflict-Free Booking Flow

1. The client chooses a contact channel: email, WhatsApp, or Zoom (a phone number is required if WhatsApp is chosen).
2. The client picks a date up to two weeks out; the system computes and displays only genuinely open 60-minute slots, calculated from the therapist’s weekly hours minus any slot already reserved by another client.
3. The client selects a time slot and completes the booking form: name, email, phone, city, birth year, and two required consent checkboxes (terms & conditions, privacy policy).
4. On submission, the server independently re-validates age (18+) and consent, re-checks the slot is still free, and only then creates the reservation.
5. If another client has claimed the same slot in the interim, the system rejects the booking with a clear conflict message and refreshes the available times — it does not silently double-book.
6. On success, the client, the GESA team, and the therapist each receive a confirmation/notification email; for WhatsApp bookings, the client’s confirmation screen also includes a direct message link to the therapist.

11.4 Optional Account and Ongoing Messaging

A client may separately create an account (email/password), which sends a welcome email and requires confirming the address before first sign-in. A signed-in client can view and edit their profile, and can message a therapist directly from that therapist's profile page — this opens or resumes a real-time chat thread that updates live without a page reload. Chat is available whether or not the client has ever completed a formal booking, and all threads remain visible to admin staff for oversight.

11.5 Key Records Touched

Step	Table	Notes
Legacy simple booking request	booking_requests	Older "reach out now" path
Wizard preferred-time request	match_requests	Includes matched and selected therapist ids
Conflict-free reservation	session_bookings	Unique constraint prevents double-booking; status is confirmed OR cancelled
Contact form	inquiries	Name, email, phone, type, message
Support-group signup	group_registrations	Group id, name, email, phone
Account & messaging	profiles, chat_threads, chat_messages	Only touched if the client signs in

12 Therapist Workflow

Therapists do not have a self-service portal. There is no therapist login flow distinct from the generic client sign-in, no therapist-facing dashboard for editing their own bio, photo, specialties, or availability, and no in-app queue for accepting or declining requests. Every public-facing therapist record is created and maintained by GESA admin staff through the admin CRM; this is a deliberate characteristic of the current system, not a gap awaiting discovery; the code notes directly that most listed therapists have no linked account, and that their listed contact email is the only reliable way to reach them.

12.1 Application

A prospective volunteer therapist submits a structured application through a “Become a volunteer therapist” call to action found across the public site. The application collects full name, email, optional phone, credentials/proof of license (free text), one or more specialties (from a curated list, with a free-text option), one or more languages (same pattern), a preferred session length (60/45/30 minutes or a custom duration), and a short bio. The application is written directly to an applications table and the applicant receives a “thank you, our team reviews every application by hand” confirmation, together with a best-effort confirmation email.

12.2 Admin Review

Admin staff review submitted applications from a dedicated screen showing applied date, contact details, specialties, languages, session-length preference, proof of license, and bio. Each application carries a status the admin can move through new, reviewing, approved, or rejected, along with a reviewed-at timestamp. Setting an application to approved is explicitly a tracking label for the admin’s own workflow; it does not, by itself, create a public therapist listing.

12.3 Manual Promotion to a Listed Therapist

To actually list someone publicly, an admin performs a separate, manual step: creating or editing a record in the therapist directory with the applicant’s full name, URL slug, bio, short summary, credentials, contact email and phone, an uploaded photo, specialties, languages, gender, offered session lengths, time zone, years of experience, and an active/verified flag (with verification timestamp and reviewer recorded for audit purposes).

12.4 Availability

A therapist’s bookable weekly hours are likewise admin-managed records (day of week, start time, end time) rather than something the therapist sets themselves. These records are what the client-facing conflict-free booking flow reads from to compute genuinely open slots; there is no evidence in the current system of a therapist-facing screen for editing this schedule directly.

12.5 Appearing Publicly and Receiving Requests

Once marked active, a therapist appears in the public directory, on their own profile page, and becomes eligible for the AI matching pool used by both intake flows. When a client matches with or books that therapist, the therapist is notified by email only, to the contact address on their listed profile — there is no in-app inbox or accept/decline queue for the therapist. Any resulting coordination happens by email, WhatsApp, or Zoom outside the admin CRM, or is tracked and moderated by admin staff from the match-requests and sessions management screens.

12.6 Optional Chat Access

If, and only if, an admin has linked a therapist's directory record to a real account, that person can sign in through the same generic login used by clients and see and reply to chat threads from their clients. This is the one point at which a therapist could have day-to-day self-service access to the system, but it is opt-in and admin-provisioned rather than a dedicated therapist portal or onboarding flow, and all chat threads remain visible to admin staff for oversight.

12.7 Key Records Touched

Step	Table	Notes
Application	therapist_applications	Status: new, reviewing, approved, rejected
Public listing	therapists	Entirely admin-authored; <code>is_active</code> / <code>is_verified</code> flags
Availability	therapist_weekly_hours	Admin-authored; drives real booking slots
Optional chat	chat_threads, chat_messages	Only if the therapist record is linked to an account

13 QA & Testing Reference

This section exists to make the document usable as a direct handoff to a QA/testing team. It goes beyond architecture and requirements to record the exact, verifiable detail a tester needs: field-level form validation, verbatim button labels, navigation targets, error/empty/loading states, and a starting set of test scenarios. All labels and rules below are taken directly from the current code, not paraphrased from memory — where the visible copy is editable through the CMS, the fallback text shown is what renders until an admin changes it.

13.1 Form Field Reference & Validation Rules

Contact form (/contact) — Name (required, text), Email (required, valid email), Subject (optional dropdown: General inquiry / Donation / Volunteer as a therapist / I need support), Message (required, 5-row textarea). Submit label “Send message” → “Sending...”. Success: form replaced by “Thank you — your message has been received. We’ll be in touch soon.” Error: “Something went wrong sending your message. Please try again.”

Login (/login) — Email (required), Password (required, no client-side minimum). Submit “Sign in” → “Signing in...”. Error shows the raw Supabase message verbatim (e.g. “Invalid login credentials”).

Signup (/signup) — Full name (required), Email (required), Password (required, minimum 8 characters). Submit “Create account” → “Creating account...”. Success replaces the card with “Check your email” / a confirmation-link message. Error shows the raw Supabase message.

Forgot password (/forgot-password) — Email (required). Submit “Send reset link” → “Sending...”. Success always shows “Check your email” regardless of whether the address has an account (intentional, not a bug to report).

Reset password (/reset-password) — New password and Confirm new password (both required, minimum 8 characters). Client-side check: mismatched values produce “Passwords don’t match.” before any network call. Submit “Update password” → “Updating...”. Success: “Password updated” with a “Go to sign in” button.

Volunteer application modal — Full name (required), Email (required), Phone (optional, placeholder “+1 555 123 4567”), Proof of license (required, free text), Specialties (curated chips + free text, at least one required, enforced in script rather than by the browser), Languages (same pattern, at least one required), Meeting duration (60 / 45 / 30 minutes or “Specify time” with a follow-up free-text field), Bio (required). Validation runs in this order and stops at the first failure: specialty required → language required → duration required → custom-duration text required. Submit “Submit application” → “Submitting...”. Success: “Thank you, {name}” confirmation naming the email that will be contacted. Approving this application in the admin CRM does not by itself create a public therapist listing — that is a separate manual step (see §12.3).

Find Your Therapist wizard — Step 1 (Assessment): symptom chips, none required, explicit “Prefer not to say? You can skip this” helper text, “Continue” always enabled. Step 2 (Preferences): treatment type dropdown and gender-preference button grid, both optional, “Back”/“Continue” always enabled. Step 3 (Format & Location): format selection required to proceed — “See my matches” is disabled until a format is chosen; choosing in-person reveals a clinic dropdown only if active clinic locations exist, otherwise explanatory text that staff will arrange a location. Step 4 (Matches): no fields; states covered in §13.4.

Wizard booking modal — Name (required), Email (required), Phone (optional), preferred date and time (both optional date/time pickers, explicitly labeled as a request rather than a confirmed slot). Submit “Confirm request” → “Sending...”. Success: “You’re all set” confirmation, with a WhatsApp deep-link button if the session format was “call” and the therapist has a phone number on file.

Intake booking modal (conflict-free scheduling) — Contact channel (Email / WhatsApp / Zoom, default Email), Date (required, restricted to today through 14 days out), Time (required, chosen from a live-fetched slot grid), Name (required), Email (required), Phone (required only if WhatsApp is selected, otherwise optional), City (optional), Year of birth (required, restricted to a 100-year window ending at the current year),

Terms checkbox (required, links to the terms page), Privacy checkbox (required, links to the privacy page). Validation order: time selected → WhatsApp requires the therapist to have a phone on file → birth year must be a valid number in range → birth year must indicate 18 or older → both consent checkboxes must be checked. Submit “Book a Support Meeting” → “Booking...”, disabled until a time is chosen and both checkboxes are ticked. A same-slot race condition returns HTTP 409 and the message “That time was just booked — please pick another slot,” after which slots are refetched automatically.

Support group registration — Name (required), Email (required), Phone (optional). Submit label is CMS-editable, falling back to “Confirm registration” → “Registering...”. Success heading is CMS-editable, falling back to “You’re registered.”

Account form (/account) — Email is read-only. Full name, Phone, Country, and Preferred language (dropdown) are all optional. Single “Save changes” button → “Saving...”; success shows inline “Saved.”, failure shows “Couldn’t save — try again.”

Admin — Therapist edit form — Photo upload (“Upload new photo” → “Uploading...”), Full name, Short summary, Bio, Credentials, Contact email, Specialties and Spoken languages (both comma-separated free text) — none marked required at the field level. “Save changes” → “Saving...” with the same inline “Saved.” / “Couldn’t save — try again.” pattern. A separate “Deactivate therapist” / “Reactivate therapist” toggle (label flips based on current state) hides or restores the therapist’s public listing without deleting the record.

Admin status and role controls — all follow the same optimistic-update pattern: the dropdown value changes immediately, and on a write failure it reverts with “Couldn’t save — try again.” An admin cannot change their own role away from admin from the Users screen; attempting to shows “You can’t remove your own admin access here.”

13.2 Button / CTA Inventory

Location	Label	Action
Header	Home / About / Our Therapists / Support Groups	Navigate to /, /about, /therapists, /support-groups
Header	Donate	Navigate to /contact?subject=Donation (CMS-editable target)
Home path cards (×3)	“Reach out now”	Navigate to /intake?path=crisis, ?path=veteran, ?path=general
Donate band	“Donate to GESA”	Navigate to /contact?subject=Donation
Therapist directory card	“Book a Session”	Opens the conflict-free booking modal
Therapist directory card	“Message” (→ “Opening...”)	Signed out: redirects to /login?next=/therapists. Signed in: creates/opens a chat thread and navigates to it
Therapists directory sidebar	“Join us as a therapist”	Opens the volunteer application modal
Footer	“Find a Therapist” / “Join a Group” / “Donate” / “Volunteer” / “Emergency Contact”	/find-your-therapist, /support-groups, /contact?subject=Donation, opens volunteer modal, tel:988

Location	Label	Action
Footer “Help us grow” form	“Sent” (verbatim label in code — flagged below)	Inserts an inquiry of type “Help us grow”
Crisis button (fixed, bottom-right)	“In crisis? Get help”	Opens a modal listing 988 Suicide & Crisis Lifeline, Crisis Text Line, 988 Lifeline Chat, and a worldwide helpline finder
Support groups drawer	“Register” (CMS-editable)	Opens the registration modal

Copy defect to verify with product before QA logs it as a bug: the footer “Help us grow” form’s submit button is literally labeled **“Sent”** in the current code (`components/footer/HelpUsGrowForm.tsx`), where “Send” would be the expected imperative label. Confirm with Roy/product whether this is intentional before treating it as a defect.

13.3 Navigation Reference

Header: Home (/), About (/about), Our Therapists (/therapists), Support Groups (/support-groups), Donate CTA (default `/contact?subject=Donation`) — all labels and the Donate target are CMS-editable.

Footer — Explore column: About, Our Therapists, Support Groups, Blog (disabled — rendered as a non-clickable element with a “Soon” badge, not a real link), FAQ, Contact. **Footer — Support column:** Find a Therapist, Join a Group, Donate, Volunteer (opens a modal, not a link), Emergency Contact (tel:988). **Footer — Legal column:** Privacy Policy, Cookies Policy, Legal Notice, Accessibility Statement, Terms & Conditions.

Admin sidebar (11 items, exact order): Overview (/admin), Session bookings (/admin/sessions), Find Your Therapist (/admin/match-requests), Booking requests (/admin/bookings), Volunteer Applications (/admin/volunteer-applications), Inquiries (/admin/inquiries), Group registrations (/admin/registrations), Messages (/admin/messages), Therapists (/admin/therapists), Users (/admin/users), Content Manager (/admin/content). The Overview link only highlights on an exact path match; every other item highlights on a prefix match, so editing a specific therapist still highlights “Therapists.”

13.4 Error, Empty & Loading States

- **Find Your Therapist — Matches step:** loading shows three pulsing placeholder bars; a fetch failure shows “Something went wrong finding your matches. Please try again, or contact us directly.”; zero matches shows “We couldn’t find a match right now. Please contact our team and we’ll help you find the right therapist directly.”
- **Intake booking modal — availability:** loading shows “Checking availability...”; a day with no open slots shows “No open times this day — try another date.”; a losing race on a slot returns the “just booked” message described in §13.1 and auto-refreshes the slot list.
- **Therapist directory search/filter:** zero results shows a CMS-editable message (fallback: “No therapists match your search right now. Try clearing a filter, or contact us and we’ll help you find the right person.”). The result-count text is announced to screen readers on every filter change.
- **Support groups:** zero open groups shows a CMS-editable message (fallback: “No support groups are open for registration right now — check back soon.”).
- **Chat window:** an empty thread shows “No messages yet — say hello to start the conversation.” New messages arrive over a live subscription with no page reload; the send button is disabled while a message is in flight or the draft is empty/whitespace-only.
- **Admin dropdowns and bulk actions:** any failed write reverts the control to its prior value and shows “Couldn’t save — try again.” (single-row) or “Couldn’t update those therapists — try again.” (bulk).

- **General convention:** every pending-state button label across the app uses a genuine ellipsis character (“...”), not three periods — worth a spot-check for visual consistency, since a stray “...” would be a small but noticeable regression.

13.5 Responsive & Accessibility Test Notes

- The “footer reveal” scroll effect (Home, About, Our Therapists, Support Groups only) is explicitly disabled below a 760px viewport width, falling back to normal static layout — test just above and below that breakpoint on each of the four pages.
- `prefers-reduced-motion`: reduce should be verified to disable: smooth scrolling, the gold-banner sheen animation, the gold-card hover sweep, the news-ticker marquee, the footer-reveal effect (falls back to static layout, same as the sub-760px case), and the booking/volunteer/registration modal’s open animation (should fade only, with no slide or scale).
- Keyboard-only navigation: the three home-page path cards use a flip animation driven by hover, but are also wired to trigger on keyboard focus — tab to each card’s CTA and confirm the back face (with the real “Reach out now” link) becomes visible and reachable, not just clickable by mouse. Every modal in the app (volunteer application, support-group registration, wizard booking, intake booking) should close on the Escape key.
- Screen-reader spot checks: modal close buttons, the volunteer form’s tag-remove chips, the footer’s social icons, and the admin therapist table’s select-all/per-row checkboxes all carry explicit `aria-labels` worth confirming are read correctly. The disabled “Blog” footer link is marked non-interactive for assistive technology rather than behaving like a dead link — confirm it is not announced as a clickable link.

13.6 Suggested Functional Test Scenarios

The items below are a starting acceptance-test checklist derived directly from the behaviors documented above and in §10–12; they are not exhaustive; and should be expanded by the testing team into full test cases with expected results.

- Complete a conflict-free booking end to end (Intake path) and confirm a client, team, and therapist email are all sent (or, in an environment without `RESEND_API_KEY` configured, confirm the booking still succeeds and the admin dashboard shows its email-configuration warning).
- Attempt to book the same therapist/date/time slot from two browser sessions in quick succession and confirm the second attempt receives the 409 “just booked” response rather than creating a duplicate reservation.
- Attempt an intake booking with a birth year indicating under 18 and confirm the client-side block; then, if feasible, attempt to bypass client-side validation (e.g. by calling `POST /api/intake-booking` directly) and confirm the server independently rejects it.
- Submit the Find Your Therapist wizard with a gender preference that no active therapist satisfies, and confirm the disclosure banner appears and the returned matches are the closest fit rather than an empty result.
- Submit a volunteer application with zero specialties or zero languages selected and confirm the specific corresponding validation message appears, in the documented order, before any network call is made.
- Approve a volunteer application in the admin CRM and confirm no therapist row is created automatically; then manually promote that applicant via `/admin/therapists` and confirm they appear in the public directory only after `is_active` is set.
- As a non-admin role (reviewer, therapist, client, finance), attempt to load any `/admin/**` route directly by URL and confirm redirection to the public site; as a signed-out visitor, confirm redirection to `/login`.
- As an admin, attempt to change your own role away from admin on `/admin/users` and confirm the self-protection guard blocks it.
- Trigger the forgot-password flow with both a registered and an unregistered email address and confirm the response text is identical in both cases.

- Deactivate a therapist from `/admin/therapists` and confirm they immediately disappear from the public directory and from the AI matching pool, without their historical bookings or messages being affected.
- Register for a support group and confirm the confirmation email arrives and the group's registration count/behavior updates as expected on next admin view.
- Resize each of the four “footer reveal” pages across the 760px breakpoint and confirm the layout switches correctly in both directions without visual glitches.
- With OS-level reduced-motion enabled, revisit the animation-dependent surfaces listed in §13.5 and confirm each one degrades to its static/opacity-only fallback.

This document reflects the codebase as of the phase history recorded in `EXECUTION_PLAN.md` at the time of writing. For the authoritative, most current state of any specific feature, defer to the live code and that file's latest entries.