

Files

Link	Description	Versions
achievements	The achievements of a specific user.	1.0 {default} 1.1 (2010-11-24) 1.2 (2021-08-03)
arenadetails	Information about specific arenas, supporter statistics and the largest arenas in Hattrick.	1.3 {default} 1.4 1.5 (2013-06-11) 1.6 (2013-06-11) 1.7 (2023-02-08)
alliances	Alliance / Federation search	1.1 {default} 1.2 1.3 (2011-05-30) 1.4 (2013-03-04)
alliancedetails	Alliance / Federation information	1.2 {default} 1.3 1.4 1.5 (2013-03-04)
avatars	Avatars for all players of user's team	1.0 {default} 1.1 (2013-01-08)
bookmarks	User bookmarks	1.0 {default}
challenges	Challenges	1.2 (2010-11-08) {default} 1.3 (2011-02-17) 1.4 (2013-05-02) 1.5 (2015-03-02) 1.6 (2016-10-27)
club	Information about specialists and youth	1.1 {default} 1.2 (2010-11-08) 1.3 (2013-05-02) 1.4 (2014-04-09) 1.5 (2015-09-22)
cupmatches	Information about cup matches	1.2 {default} 1.3 (2011-02-01) 1.4 (2011-06-03)
currentbids	Shows the current transfer activity for a team.	1.0 (2014-02-10) {default}
economy	Economy	1.1 {default} 1.2 (2011-04-13) 1.3 (2013-05-02) 1.4 (2022-03-09)
fans	Fanclub information	1.0 {default} 1.1 (2011-04-13) 1.2 (2013-05-02) 1.3 (2018-06-01)
hofplayers	Hall of Fame Players	1.0 (2011-04-13) {default} 1.1 (2014-07-23) 1.2 (2020-06-02)
ladderdetails	Information about teams in the ladder and positions in it	1.0 (2013-11-20) {default}
ladderlist	Information about ladder that the user is currently playing in.	1.0 (2013-11-08) {default}
leaguedetails	Information about a League Level Unit (series)	1.2 {default} 1.3 (2012-02-12) 1.4 (2012-02-15) 1.5 (2017-01-05) 1.6 (2022-03-03)
leaguefixtures	Fixtures for a League Level Unit (series)	1.2 {default}
leaguelevels	Shows league level units (series) information for a specific league.	1.0 (2024-08-26) {default}
live	Get (live) match ticker	1.3 {default} 1.4 1.5 1.6 (2011-09-26) 1.7 (2011-11-14) 1.8 (2012-09-01) 1.9 (2016-08-02) 2.0 (2020-09-01) 2.1 (2021-08-25) 2.3 (2022-03-03) 2.3 (2022-05-04)

managercompendium	The manager compendium of the logged in user.	1.0 (2013-12-10) {default} 1.1 (2016-05-17) 1.2 (2018-03-01) 1.3 (2019-12-03) 1.4 (2022-03-04) 1.5 (2023-01-18) 1.6 (2026-02-11) 1.7 (2026-02-26)
matches	The most recent and upcoming matches for a particular team (Senior or Youth).	2.3 {default} 2.4 2.5 2.6 2.7 (2013-11-20) 2.8 (2015-02-09) 2.9 (2022-03-03)
matchesarchive	Matches Archive	1.1 {default} 1.2 (2013-11-21) 1.3 (2015-02-09) 1.4 (2018-04-03) 1.5 (2022-03-03)
matchdetails	Detailed match information	1.5 {default} 1.6 1.7 1.8 1.9 (2010-11-08) 2.0 (2011-01-11) 2.1 (2012-02-01) 2.2 (2012-02-15) 2.3 (2012-03-06) 2.4 (2013-03-04) 2.5 (2013-05-02) 2.6 (2014-10-20) 2.7 (2015-02-09) 2.8 (2016-08-02) 2.9 (2016-08-15) 3.0 (2017-12-14) 3.1 (2022-03-03)
matchlineup	Match lineup for finished matches	1.2 {default} 1.3 1.5 (2011-09-12) 1.6 (2011-09-20) 1.7 (2012-02-13) 1.8 (2012-03-06) 1.9 (2015-10-01) 2.0 (2016-08-02) 2.1 (2022-03-03)
matchorders	Match orders for upcoming matches	1.3 {default} 1.4 1.5 1.6 (2010-11-08) 1.7 (2011-06-22) 1.8 (2011-08-30) 1.9 (2011-12-15) 2.0 (2012-03-06) 2.1 (2012-03-15) 2.2 (2013-05-02) 2.3 (2013-11-29) 2.4 (2015-09-22) 3.0 (2017-05-18) 3.1 (2022-03-03)
nationalteams	National teams	1.2 1.3 {default} 1.4 (2011-02-12) 1.5 (2013-03-04) 1.6 (2021-01-18)
nationalteamdetails	National Team information	1.2 1.3 {default} 1.4 (2010-11-08) 1.5 (2011-01-13) 1.6 (2011-04-13)

		1.7 (2011-06-16)
		1.8 (2013-03-04)
		1.9 (2016-06-28)
nationalteammatches	National team matches	1.2 {default}
		1.3 (2013-03-04)
		1.4 (2022-03-03)
nationalplayers	National team players	1.2 {default}
		1.3 (2013-03-04)
		1.4 (2021-04-09)
		1.5 (2022-03-04)
players	Players	1.4 {default}
		1.5
		1.6
		1.7
		1.8 (2011-02-03)
		1.9 (2011-02-25)
		2.0 (2011-05-12)
		2.1 (2011-10-13)
		2.2 (2011-10-21)
		2.3 (2013-03-04)
		2.4 (2019-11-04)
		2.5 (2021-01-19)
		2.6 (2023-09-07)
		2.7 (2025-02-25)
		2.8 (2026-02-11)
playerdetails	Detailed information for a player	1.2 {default}
		1.3
		1.4
		1.5
		1.6 (2010-12-16)
		1.7 (2011-02-03)
		1.8 (2011-02-25)
		1.9 (2011-05-12)
		2.0 (2011-10-13)
		2.1 (2011-10-21)
		2.2 (2011-12-05)
		2.3 (2012-04-12)
		2.4 (2013-03-04)
		2.5 (2013-12-12)
		2.6 (2014-02-05)
		2.7 (2016-05-17)
		2.8 (2019-11-04)
		2.9 (2022-03-04)
		3.0 (2023-09-07)
		3.1 (2025-02-25)
		3.2 (2026-02-09)
playerevents	Player events	1.1 {default}
		1.2
		1.3 (2013-03-04)
regiondetails	Detailed information about a region	1.2 {default}
search	Search	1.2 {default}
staffavatars	Avatars for all staff members.	1.0 (2014-04-03) {default}
		1.1 (2023-09-07)
stafflist	A list of all staff members	1.0 (2014-04-03) {default}
		1.1 (2015-04-07)
		1.2 (2023-09-07)
supporters	Information about teams supported and teams supporting.	1.0 (2013-12-16) {default}
teamdetails	Team information	1.9 {default}
		2.0
		2.1
		2.2
		2.3
		2.4 (2010-11-08)
		2.5 (2011-02-03)
		2.6 (2011-04-13)
		2.7 (2013-03-04)
		2.8 (2013-05-02)
		2.9 (2013-05-20)
		3.0 (2013-09-03)

		3.1 (2013-12-16)
		3.2 (2014-07-21)
		3.3 (2015-08-04)
		3.4 (2016-12-19)
		3.5 (2020-07-02)
		3.6 (2022-03-03)
		3.7 (2024-09-16)
		3.8 (2026-02-10)
		3.9 (2026-02-26)
tournamentdetails	Information about a tournament. This is only available for the current season.	1.0 (2013-10-17) {default}
tournamentfixtures	Information about matches for a tournament. This is only available for the current season. For non-restarted tournaments this is available for 2 seasons after the tournament finished.	1.0 (2013-10-17) {default}
		1.1 (2025-09-17)
tournamentleaguetales	League tables for a tournament. This is only available for the current season. For non-restarted tournaments this is available for 2 seasons after the tournament finished.	1.0 (2013-10-17) {default}
		1.1 (2021-06-01)
tournamentlist	Information about tournaments that the user is currently playing in.	1.0 (2013-10-17) {default}
training	Training	1.3 {default}
		1.4
		1.5
		1.6 (2010-11-08)
		1.7 (2011-01-17)
		1.8 (2011-02-03)
		1.9 (2011-02-12)
		2.0 (2013-03-04)
		2.1 (2013-05-02)
		2.2 (2013-11-21)
trainingevents	Get training events for a player.	1.1 {default}
		1.2
		1.3 (2013-03-04)
transfersearch	Search the transfer market. This file is NOT meant to be fetched by bots to automatically scan the transfer market, but instead upon manual user request.	1.0 (2013-12-12) {default}
		1.1 (2022-03-03)
transfersteam	Get the transfer history of a team	1.2 (2011-04-13) {default}
transfersplayer	Get all transfers of a player	1.1 {default}
translations	Translations for the denominations in the game. This file is NOT meant to be fetched on each user session, but instead every certain period of time, like once a week, and store the values in the app.	1.0 (2013-11-27) {default}
		1.1 (2014-08-18)
		1.2 (2022-03-04)
worldcup	World cup groups and matches	1.1 {default}
worlddetails	General Information about all countries in HT World	1.2 {default}
		1.3 (2011-02-12) {default}
		1.4 (2011-10-07)
		1.5 (2013-09-03)
		1.6 (2014-07-21)
		1.7 (2015-08-03)
		1.8 (2016-12-13)
		1.9 (2022-03-03)
		2.0 (2026-02-09)
worldlanguages	Available languages	1.2 {default}
youthavatars	Avatars for all players of user's youthteam	1.0 {default}
		1.1 (2013-05-02)
		1.2 (2021-01-19)
youthleaguedetails	The youth league information.	1.0 (2013-12-02) {default}
		1.1 (2026-02-26)
youthleaguefixtures	Fixtures for a Youthe League (series).	1.0 (2013-12-02) {default}
youthplayerdetails	Detailed information for a youth player	1.0 (2011-11-15) {default}
		1.1 (2014-01-23)
		1.2 (2022-03-03)
		1.3 (2026-02-10)
youthplayerlist	Youth Players.	1.0 (2011-11-15) {default}
		1.1 (2014-01-23)
		1.2 (2022-03-03)
		1.3 (2026-02-11)
youthteamdetails	Youth team information.	1.0 {default}
		1.1 (2015-04-15)
		1.2 (2022-03-03)
		1.3 (2026-02-10)
		1.4 (2026-02-26)

Output

The output container 'HattrickData' always contains the following elements:

Element	Description
FileName	The name of the file that your request was sent to.
Version	The delivered version of the XML output.
UserID	The logged on User's UserID (not to be confused with TeamID). If not logged on, it defaults to 0.
FetchDate	Date and time when the XML file was fetched. Format is DateTime

Data types

For a list of all data types look [here](#).

Error

Any error casued by a internal error is caught. If such an error occurs you'll always get an XML result back but not the file you requested.

ErrorCodes

Code	Description
-1	No information
0	Not logged in
1	Access Denied
2	File Not Specified
3	File not supported
4	POST not supported
5	Must use POST for this action
6	Only for Supporters
7	Not supported version
10	Invalid parameter
50	Unknown TeamID
51	Unknown MatchID
52	Unknown ActionType
53	MatchID not subscribed to
54	Unknown YouthTeamID
55	Unknown YouthPlayerID
56	Unknown PlayerID
57	Unknown LeagueID
58	Unknown LeagueLevelUnitID
59	This request is only allowed for teams owned by the requesting user himself, and the requested team is not owned by this user
60	Unknown TournamentId
61	Unknown LadderId
62	The youth player is now a senior player. The senior player ID is available in the SeniorPlayerID element for the error.
63	Missing required parameters.
64	The player has become a coach.
70	Challenge failed
71	Bid failed
80	Banned from international friendly
81	Banned from transfers
90	Hattrick is down for maintenance, please try again later
91	Hattrick youth academy is down for maintenance, please try again later
92	Hattrick transfer market is down for maintenance, please try again later
93	HTOIntegrated platform is down for maintenance, please try again later
99	Other undefined error
Anything else	Internal .NET error. Please specify this errorcode whenever you report a problem.

Good to know

- For testing purpose you can set supporter to Off (X=-1), Silver (X=0), Gold (X=1), Platinum (X=2) or Diamond (X=3) for a single call by appending overridesSupporter=X to the url. (This does not work for file 'teamdetails')

Live

Get (live) match ticker

Changelog [\(show\)](#)

Input

The following input parameters exist:

Simple

Detailed

Only available inputs in this file version are shown.

required

file = live

optional

version = 2.3

optional

actionType = view {default}

Indicates what type of action the page should perform.

view {default}

Show the latest event(s) for all tracked matches. If matchID is supplied, that match will be shown with all events since the start of the game ('expanded' view).

optional

matchID : unsigned Integer

The globally unique matchID.

optional

sourceSystem : sourceSystem {Default:hattrick}

Specifies which source system the match belongs to, this replace the old isYouth param

optional

includeStartingLineup : Boolean {Default:false}

Should <StartingLineup> and <Substitutions> be included in the response?

optional

useLiveEventsAndTexts : Boolean {Default:false}

Should the events and texts be as on the live page on the site?

viewNew

Show those matches where new events have occurred since last request of the page. You'll need to send the which was your last event according to LastShownIndexes

optional

includeStartingLineup : Boolean {Default:false}

Should <Substitutions> be included in the response?
(Note that <StartingLineup> is never provided for viewNew)

optional

useLiveEventsAndTexts : Boolean {Default:false}

Should the events and texts be as on the live page on the site?

optional

lastShownIndexes : String

JSON formatted array of last shown indexes for each match.

See reference: [#LastShownIndexes](#).

viewAll

Show all the events for all matches.

optional

includeStartingLineup : Boolean {Default:false}

Should <StartingLineup> and <Substitutions> be included in the response?

optional

useLiveEventsAndTexts : Boolean {Default:false}

Should the events and texts be as on the live page on the site?

clearAll

Remove all tracked matches from the tracking session.

https://stage.hattrick.org/Community/CHPP/NewDocs/File.aspx?name=live

1/5

addMatch

Add a new match to be tracked.

required matchID : unsigned Integer

The globally unique matchID.

optional sourceSystem : sourceSystem {Default:hattrick}

Specifies which source system the match belongs to, this replace the old isYouth param

optional includeStartingLineup : Boolean {Default:false}

Should <StartingLineup> and <Substitutions> be included in the response?

optional useLiveEventsAndTexts : Boolean {Default:false}

Should the events and texts be as on the live page on the site?

deleteMatch

Remove a particular match from the session.

required matchID : unsigned Integer

The globally unique matchID.

optional sourceSystem : sourceSystem {Default:hattrick}

Specifies which source system the match belongs to, this replace the old isYouth param

Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple	Detailed	XML	Example
--------	----------	-----	---------

All containers and elements for the selected file version and action type are shown.

- HattrickData

Hattrick Data Container for actionType=view

- MatchList

Container for all the matches.

- Match

The container for a match. An attribute called Index signifies the number of the match in the list.

MatchID : unsigned Integer

The globally unique identifier of the match.

MatchType : MatchTypeID

Integer defining the type of match.

SourceSystem : sourceSystem

Specifies which source system the match belongs to, this replace the old isYouth param

MatchDate : DateTime

The start date (kick-off) of the match.

- HomeTeam

The Home (formal, not taking arena location into account) team of the match.

HomeTeamID : Integer

The teamID of the Home team in the match. (Negative for street teams)

HomeTeamName : String

The team name of the Home team in the match.

HomeTeamShortName : String

The short team name of the Home team in the match.

- StartingLineup

List of players in the hometeam who started the game

- Player

Container for a particular player that is part of the starting lineup.

PlayerID : unsigned Integer

Globally unique ID of the player.

RoleID : MatchRoleID

An integer indicating which formal 'slot' (Role) the player has filled in the match.

PlayerName : String

The full name of the player.

Behaviour : MatchBehaviourID

An integer indicating the individual order or repositioning that the player has played with. Not provided for Captain and Set Pieces taker.

- AwayTeam

The Away (formal, not taking arena location into account) team of the match.

AwayTeamID : Integer

The teamID of the Away team in the match. (Negative for street teams)

AwayTeamName : String

The team name of the Away team in the match.

AwayTeamShortName : String

The short team name of the Away team in the match.

- StartingLineup

List of players in the awayteam who started the game

- Player

Container for a particular player that is part of the starting lineup.

PlayerID : unsigned Integer

Globally unique ID of the player.

RoleID : MatchRoleID

An integer indicating which formal 'slot' (Role) the player has filled in the match.

PlayerName : String

The full name of the player.

Behaviour : MatchBehaviourID

An integer indicating the individual order or repositioning that the player has played with. Not provided for Captain and Set Pieces taker.

- Substitutions

Container for the substitutions in the game.

- Substitution

Container for a particular substitution. An attribute named Index gives a counter.

TeamID : unsigned Integer

The globally unique TeamID for which the orders were sent.

SubjectPlayerID : unsigned Integer

If a/ substitution: The player leaving. If b/ behaviour change: The player changing his behaviour. Or c/ position swap: the first player that will change his position.

ObjectPlayerID : unsigned Integer

The player entering (or once more the player changing behaviour). Or if position swap, the player to swap with.

OrderType : matchOrderTypeID

The type of the order.

NewPositionId : MatchRoleID

An integer representing the new position for the (entering or staying) player.

NewPositionBehaviour : MatchBehaviourID

An integer representing the new behaviour for the (entering or staying) player.

MatchMinute : unsigned Integer

An integer indicating in which minute the order was executed.

MatchPart : matchPart

Which part of the match the order was executed.

- EventList

Container for all the events.

- Event

Attribute: 'Index' : unsigned Integer

Indicates the order of the event relative to the other events sent in the same batch for this match.

Container for the data for a certain event.

See information [MatchEventTypes](#)

Minute : unsigned Integer

The match minute when the event happened.

MatchPart : matchPart

Which part of the match the event happened.

EventKey : String

A unique key defining what type of event it was.

EventText : String

String describing the event as it would appear in the match report.

SubjectTeamID : unsigned Integer

Integer that, for goals and chances, is indicating the attacking team. For other event, this field usually indicates the team that is doing something. It may indicate other things for other events - exactly what is not documented here and the SubjectTeamID information, while free to use for CHPPs is 'unsupported' and used 'at your own risk'.

SubjectPlayerID : unsigned Integer

Integer that, for goals and chances, is indicating the scorer or the player failing to score. For other events, this field usually indicates the primarily active player. It may indicate other things for other events and like SubjectTeamID is 'unsupported' and used 'at your own risk'.

ObjectPlayerID : unsigned Integer

Integer that, for regular goals and chances, is indicating the defending team's goal keeper. For special event chances/goals, the ObjectPlayer is often the assisting player of the attacking team, but can be any other player that is involved in the event. For other events, this field is used very freely and can indicate any kind of relevant integer data. Like SubjectPlayerID and SubjectTeamID, it is 'unsupported' and used at 'your own risk'.

HomeGoals : unsigned Integer

The current number of goals in the match for the home team.

AwayGoals : unsigned Integer

The current number of goals in the match for the away team.

LastShownEventIndex : unsigned Integer

The last shown event. Use this as LastShownIndexes for actionType=viewNew.

NextEventMinute : unsigned Integer

The minute that the next matchevent will happen, this allows you to only ask for new events when needed. Only available while the match is ongoing. It should only be used by the application, **it should NOT be shown to the users.**

NextEventMatchPart : matchPart

The matchPart in which the next matchevent will happen, this allows you to only ask for new events when needed. Only available while the match is ongoing. It should only be used by the application, **it should NOT be shown to the users.**

The following input parameters exist:

Output

Here you can see the output, based on the values of the input parameters and selected action type.

<https://stage.hattrick.org/Community/CHPP/NewDocs/File.aspx?name=managercompendium>

Container for the currency selected by the user.

CurrencyName : String
The name of the currency.

CurrencyRate : Decimal
Decimal value specifying the relative currency rate to SEK (swedish krona).

- Teams

Container for the list of Teams.

- Team

Container for the data about a particular Team.

TeamId : unsigned Integer
The globally unique TeamID.

TeamName : String
The full team name

GenderID : GenderID
The gender of the team.

Added in this Version
LeagueSystemID : LeagueSystemID
The system type of the league for the team.

- Arena

Container for the arena.

Arenald : unsigned Integer
The globally unique Arenald.

ArenaName : String
The arena name.

- League

Container for the league.

LeagueId : unsigned Integer
The globally unique LeagueID

LeagueName : String
The League name.

Season : unsigned Integer
The Current Season.

- Country

Container for the country.

CountryId : unsigned Integer
The globally unique CountryId

CountryName : String
The Country name.

- LeagueLevelUnit

Container for the LeagueLevelUnit ('series').

LeagueLevelUnitId : unsigned Integer
The globally unique LeagueLevelUnitID.

LeagueLevelUnitName : String
The name of the LeagueLevelUnit

- Region

Container for the region.

RegionId : unsigned Integer

The globally unique RegionID.

RegionName : String

The Region name

- YouthTeam

Container for the youthTeam. Will be empty if the team has no Youth academy.

YouthTeamId : unsigned Integer

If the Team has a Youth academy the ID is represented here.

YouthTeamName : String

If the Team has a Youth academy the team name is represented here.

- YouthLeague

Container for the league of the youthTeam. Will be empty if the youthTeam is currently not playing in a league.

YouthLeagueId : unsigned Integer

The globally unique YouthLeagueID.

YouthLeagueName : String

The name of the youth league.

- NationalTeamCoach

Container for national teams the manager is a coach of. Empty if user is not a national team coach.

- NationalTeam

Container for national team.

NationalTeamId : unsigned Integer

The globally unique NationalTeamID.

NationalTeamName : String

The name of the national team.

- NationalTeamAssistant

Container for national teams the manager is an assistant coach of. Empty if user is not a national team assistant coach.

- NationalTeam

Container for national team.

NationalTeamId : unsigned Integer

The globally unique NationalTeamID.

NationalTeamName : String

The name of the national team.

- Avatar

Container for the elements to build the avatar.

BackgroundImage : URI

The URL to the card background-image. This will show a silhouette for non-supporter teams.

- Layer

Attribute: 'x' : unsigned Integer

x-coordinate of image layer

Attribute: 'y' : unsigned Integer

y-coordinate of image layer

The container for each avatar bodypart item. Two attribute named X and Y indicates where the item should be positioned. There are several of this container for each player. This container will not be provided for non-supporter team.

Image : URI

The URL to the bodypart item.

Match Details

Detailed match information

Changelog [\(show\)](#)

Input

The following input parameters exist:

Simple	Detailed
--------	----------

Inputs for all different file versions are shown and marked.

required file = matchdetails

optional version = 3.1 ▾

optional matchEvents = false {default} ▾
Whether match events shall be shown or not

false {default}
Show no match events.

true
Show match events.

required matchID : unsigned Integer
Which match to show details for.

Available in Version(s): 1.5, 1.6, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2

~~**optional** isYouth : Boolean~~ {Default:false}
Is request for youth or not.

required sourceSystem : sourceSystem
Specifies which source system the match belongs to, this replace the old isYouth param

Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple	Detailed	XML	Example
--------	----------	-----	---------

All containers and elements for the selected action type are shown. Containers/Elements for other file version are shown and marked.

- HattrickData
Hattrick Data Container for matchEvents=false

Available in Version(s): 1.5, 1.6, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2

~~isYouth : Boolean~~
Is file request for youth or not.

SourceSystem : sourceSystem
Which sourceSystem the request was made for.

Available in Version(s): 1.5, 1.6, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2, 2.3

~~UserIsSupporter : Boolean~~
Indicated if the fetching user has a supporter subscription or not.

UserSupporterTier : supporterTier
Indicates which Supporter package the fetching user has, or empty if not a Supporter.

Available in Version(s): 1.5, 1.6

~~UserHasClubhouse~~ : **Boolean**

~~Indicated if the fetching user has a Clubhouse or not.~~

- Match

A match.

MatchID : **unsigned Integer**

The globally unique identifier of the match.

MatchType : **MatchTypeID**

Integer defining the type of match.

MatchContextId : **unsigned Integer**

This will be either LeagueLevelUnitId (for League), CupId (Cup, Hatrick Masters, World Cup and U-20 World Cup), LadderId, TournamentId, or 0 for friendly, qualification, single matches and preparation matches.

MatchRuleId : **MatchRuleID**

This will contain the rules that's in place for the ladder or tournament in question. It's provided for all matchtypes and defaults to 0 = No rules

CupLevel : **unsigned Integer**

1 = National/Divisional cup, 2 = Challenger cup, 3 = Consolation cup. 0 if MatchType is not 3.

CupLevelIndex : **unsigned Integer**

In Challenger cups: 1 = Emerald (start week 2), 2 = Ruby (start week 3), 3 = Sapphire (start week 4). Always 1 for National/Divisional (main cups) and Consolation cups. 0 if MatchType is not 3.

MatchDate : **DateTime**

The start date and time (kick-off) of the match.

FinishedDate : **DateTime***

The date and time when the match was finished. Not supplied until it is finished.

AddedMinutes : **Integer**

How many minutes of added time the match had. Not supplied until it is finished.

- HomeTeam

The Home (formal, not taking arena location into account) team of the match.

HomeTeamID : **Integer**

The teamID of the Home team in the match. (Negative for street teams.)

HomeTeamName : **String**

The team name of the Home team in the match.

Available in Version(s): 1.5, 1.6, 1.7, 1.8

~~Dress~~ : **String**

~~7 character string representing the dress of the team: First characters is a letter indicating type pf dress. Next two numbers indicate the shirt colour, next two indicate pants colour and final two numbers indicate socks colour.~~

DressURI : **URI**

URI to an image representing the dress of the team. FOR SENIORS ONLY

Formation : **String**

Character string (x-x-x) representing the formation the team started with.

HomeGoals : **unsigned Integer**

The current number of goals in the match for the home team.

TacticType : **MatchTacticType**

Integer value representing the the team tactic type specified for the match.

TacticSkill : **SkillLevel**

Integer value representing the tactic skill of the team.

RatingMidfield	:	MatchRating	Integer value representing the midfield rating of the team.
RatingRightDef	:	MatchRating	Integer value representing the right defence rating of the team.
RatingMidDef	:	MatchRating	Integer value representing the middle defence rating of the team.
RatingLeftDef	:	MatchRating	Integer value representing the left defence rating of the team.
RatingRightAtt	:	MatchRating	Integer value representing the right attack rating of the team.
RatingMidAtt	:	MatchRating	Integer value representing the middle attack rating of the team.
RatingLeftAtt	:	MatchRating	Integer value representing the left attack rating of the team.
TeamAttitude	:	MatchTeamAttitude	Integer value representing the the team attitude specified for the match. Only shown to the owner of the team - otherwise omitted.
RatingIndirectSetPiecesDef	:	MatchRating	Integer value representing the defensive indirect set pieces rating of the team.
RatingIndirectSetPiecesAtt	:	MatchRating	Integer value representing the attacking indirect set pieces rating of the team.
Added in this Version			
NrOfChancesLeft	:	unsigned Integer	Number of chances the team had on the left side.
Added in this Version			
NrOfChancesCenter	:	unsigned Integer	Number of chances the team had in the middle.
Added in this Version			
NrOfChancesRight	:	unsigned Integer	Number of chances the team had on the right side.
Added in this Version			
NrOfChancesSpecialEvents	:	unsigned Integer	Number of special event chances.
Added in this Version			
NrOfChancesOther	:	unsigned Integer	Number of chances of other types that doesn't fit into any of the above categories.

- AwayTeam			
The Away (formal, not taking arena location into account) team of the match.			
AwayTeamID	:	Integer	The teamID of the Away team in the match. (Negative for street teams.)
AwayTeamName	:	String	The team name of the Away team in the match.
<i>Available in Version(s): 1.5, 1.6, 1.7, 1.8</i>			
Dress	:	String	7-character string representing the dress of the team: First characters is a letter indicating type pf dress. Next two numbers indicate the shirt colour, next two indicate pants colour and final two numbers indicate socks colour.
DressURI	:	URI	

URI to an image representing the dress of the team. FOR SENIORS ONLY

Formation : String

Character string (x-x-x) representing the formation the team started with.

AwayGoals : unsigned Integer

The current number of goals in the match for the away team.

TacticType : MatchTacticType

Integer value representing the the team tactic type specified for the match.

TacticSkill : SkillLevel

Integer value representing the tactic skill of the team.

RatingMidfield : MatchRating

Integer value representing the midfield rating of the team.

RatingRightDef : MatchRating

Integer value representing the right defence rating of the team.

RatingMidDef : MatchRating

Integer value representing the middle defence rating of the team.

RatingLeftDef : MatchRating

Integer value representing the left defence rating of the team.

RatingRightAtt : MatchRating

Integer value representing the right attack rating of the team.

RatingMidAtt : MatchRating

Integer value representing the middle attack rating of the team.

RatingLeftAtt : MatchRating

Integer value representing the left attack rating of the team.

TeamAttitude : MatchTeamAttitude

Integer value representing the the team attitude specified for the match. Only shown to the owner of the team - otherwise omitted.

RatingIndirectSetPiecesDef : MatchRating

Integer value representing the defensive indirect set pieces rating of the team.

RatingIndirectSetPiecesAtt : MatchRating

Integer value representing the attacking indirect set pieces rating of the team.

Added in this Version**NrOfChancesLeft : unsigned Integer**

Number of chances the team had on the left side.

Added in this Version**NrOfChancesCenter : unsigned Integer**

Number of chances the team had in the middle.

Added in this Version**NrOfChancesRight : unsigned Integer**

Number of chances the team had on the right side.

Added in this Version**NrOfChancesSpecialEvents : unsigned Integer**

Number of special event chances.

Added in this Version**NrOfChancesOther : unsigned Integer**

Number of chances of other types that doesn't fit into any of the above categories.

- Arena

Container for the data about the arena where the match was played.

ArenaID : unsigned Integer

The globally unique arenaID.

ArenaName : String

The name of the arena.

WeatherID : WeatherID

Integer defining the weather during the match.

SoldTotal : unsigned Integer

The total number of sold tickets (number of spectators).

Removed in this Version

Available in Version(s): 1.5, 1.6, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0

~~SoldTerraces : unsigned Integer~~~~The number of sold tickets for the terraces section. Only provided to the owner of the home team.~~**Removed in this Version**

Available in Version(s): 1.5, 1.6, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0

~~SoldBasic : unsigned Integer~~~~The number of sold tickets for the basic seating section. Only provided to the owner of the home team.~~**Removed in this Version**

Available in Version(s): 1.5, 1.6, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0

~~SoldRoof : unsigned Integer~~~~The number of sold tickets for the seating under roof section. Only provided to the owner of the home team.~~**Removed in this Version**

Available in Version(s): 1.5, 1.6, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0

~~SoldVIP : unsigned Integer~~~~The number of sold tickets for the VIP section. Only provided to the owner of the home team.~~**Added in this Version****SoldTerraces : unsigned Integer**

The number of sold tickets for the terraces section.

Added in this Version**SoldBasic : unsigned Integer**

The number of sold tickets for the basic seating section.

Added in this Version**SoldRoof : unsigned Integer**

The number of sold tickets for the seating under roof section.

Added in this Version**SoldVIP : unsigned Integer**

The number of sold tickets for the VIP section.

- MatchOfficials

Container for data about the match officials, only shown for matches with SourceSystem=Hattrick.

- Referee

Container for the referee.

Refereeld : unsigned Integer

The globally unique PlayerID for the referee.

RefereeName : String

The name of the referee.

RefereeCountryId : **unsigned Integer**

The countryID of the country the referee is from.

RefereeCountryName : **String**

The name of the country the referee is from.

RefereeTeamId : **unsigned Integer**

The teamId of the team that the referee is a Hall of Fame member of.

RefereeTeamname : **String**

The name of the team that the referee is a Hall of Fame member of.

- RefereeAssistant1

Container for the first assistant referee.

Refereeld : **unsigned Integer**

The globally unique PlayerID for the referee.

RefereeName : **String**

The name of the referee.

RefereeCountryId : **unsigned Integer**

The countryID of the country the referee is from.

RefereeCountryName : **String**

The name of the country the referee is from.

RefereeTeamId : **unsigned Integer**

The teamId of the team that the referee is a Hall of Fame member of.

RefereeTeamname : **String**

The name of the team that the referee is a Hall of Fame member of.

- RefereeAssistant2

Container for the second assistant referee.

Refereeld : **unsigned Integer**

The globally unique PlayerID for the referee.

RefereeName : **String**

The name of the referee.

RefereeCountryId : **unsigned Integer**

The countryID of the country the referee is from.

RefereeCountryName : **String**

The name of the country the referee is from.

RefereeTeamId : **unsigned Integer**

The teamId of the team that the referee is a Hall of Fame member of.

RefereeTeamname : **String**

The name of the team that the referee is a Hall of Fame member of.

- Scorers

Container for the data about the scorers.

Available in Version(s): 1.5

- Goal

Container for a certain goal.

Available in Version(s): 1.5

ScorerPlayerID : **unsigned Integer**

The globally unique PlayerID for the scorer.

Available in Version(s): 1.5

ScorerPlayerName : **String**

The name of the scorer.

Available in Version(s): 1.5

ScorerTeamID : Integer

The teamID of the team that scored.

Available in Version(s): 1.5

ScorerHomeGoals : unsigned Integer

The number of goals for the home team after the goal.

Available in Version(s): 1.5

ScorerAwayGoals : unsigned Integer

The number of goals for the away team after the goal.

Available in Version(s): 1.5

ScorerMinute : unsigned Integer

The minute that the goal was scored in.

MatchPart : matchPart

Which part of the match the goal was scored in.

- Goal

Attribute: 'Index' : unsigned Integer

The relative number of the goal in the list.

Container for a certain goal.

ScorerPlayerID : unsigned Integer

The globally unique PlayerID for the scorer.

ScorerPlayerName : String

The name of the scorer.

ScorerTeamID : Integer

The teamID of the team that scored.

ScorerHomeGoals : unsigned Integer

The number of goals for the home team after the goal.

ScorerAwayGoals : unsigned Integer

The number of goals for the away team after the goal.

ScorerMinute : unsigned Integer

The minute that the goal was scored in.

MatchPart : matchPart

Which part of the match the goal was scored in.

- Bookings

Container for the data about the warned or sent off players.

Available in Version(s): 1.5

- Booking

Container for a certain yellow/red card.

Available in Version(s): 1.5

BookingPlayerID : unsigned Integer

The globally unique PlayerID for the booked player.

Available in Version(s): 1.5

BookingPlayerName : String

The name of the booked player.

Available in Version(s): 1.5

BookingTeamID : Integer

The teamID of the team that suffered the booking.

Available in Version(s): 1.5

BookingType : unsigned Integer

Specifies whether it was a warning (BookingType=1) or red card (BookingType=2).

Available in Version(s): 1.5

BookingMinute : unsigned Integer

The minute that the booking happened.

MatchPart : matchPart

Which part of the match the booking happened.

- Booking

Attribute: 'Index' : unsigned Integer

The relative number of the booking in the list.
Container for a certain yellow/red card.

BookingPlayerID : unsigned Integer

The globally unique PlayerID for the booked player.

BookingPlayerName : String

The name of the booked player.

BookingTeamID : Integer

The teamID of the team that suffered the booking.

BookingType : unsigned Integer

Specifies whether it was a warning (BookingType=1) or red card (BookingType=2).

BookingMinute : unsigned Integer

The minute that the booking happened.

MatchPart : matchPart

Which part of the match the booking happened.

- Injuries

Container for the data about injured players.

- Injury

Attribute: 'Index' : unsigned Integer

The relative number of the booking in the list.
Container for a certain injury.

InjuryPlayerID : unsigned Integer

The globally unique PlayerID for the injured player.

InjuryPlayerName : String

The name of the injured player.

InjuryTeamID : Integer

The teamID of the team that suffered the injury.

InjuryType : unsigned Integer

Specifies whether it was a bruise (InjuryType=1) or an injury (InjuryType=2).

InjuryMinute : unsigned Integer

The minute that the injury happened.

MatchPart : matchPart

Which part of the match the booking happened.

PossessionFirstHalfHome : unsigned Integer

Home team's ball possession in % for first half.

PossessionFirstHalfAway : unsigned Integer
Away team's ball possession in % for first half.

PossessionSecondHalfHome : unsigned Integer
Home team's ball possession in % for second half.

PossessionSecondHalfAway : unsigned Integer
Away team's ball possession in % for second half.

Matches

The most recent and upcoming matches for a particular team (Senior or Youth).

[Changelog](#) [\(show\)](#)

Input

The following input parameters exist:

Simple

Detailed

Inputs for all different file versions are shown and marked.

required

 file = matches

optional

 version =

2.9

optional

 teamID :

unsigned Integer

 {Default:Your senior or youth teamID}
What team to show the matches for: Either teamID or youthTeamID depending on isYouth.

optional

 isYouth :

Boolean

 {Default:false}
Is request for youth or not.

optional

 LastMatchDate :

DateTime

 {Default:Datetime.Now + 28 days}
Last date to show matches to. If more than 50 matches are affected, only the 50 first will be returned.

Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple

Detailed

XML

Example

All containers and elements for the selected action type are shown. Containers/Elements for other file version are shown and marked.

- HattrickData

Hattrick Data Container

- Team

The team that the list applies to.

TeamID : unsigned Integer

The team's TeamID.

TeamName : String

The full name of the team.

ShortTeamName : String

The short team name. Only available when isYouth is false.

- League

Container for the data about the league ('Sverige', 'England' and so on) the team is part of.

LeagueID : unsigned Integer

The globally unique LeagueID.

LeagueName : String

The league name.

- LeagueLevelUnit

Data about the team's LeagueLevelUnit ('series'). If the team is playing a qualification match the tag will be empty. Only available when isYouth is false.

LeagueLevelUnitID : unsigned Integer

The globally unique LeagueLevelUnitID.

LeagueLevelUnitName : String

The name of the LeagueLevelUnit.

LeagueLevel : unsigned Integer

Integer value stating the relative level of the LeagueLevelUnit, with 1 indicating the league's top series.

- MatchList

Container for the matches.

- Match

A match.

MatchID : unsigned Integer

The globally unique identifier of the match.

- HomeTeam

The Home (formal, not taking arena location into account) team of the match.

HomeTeamID : Integer

The teamID of the Home team in the match. (Negative for street teams)

HomeTeamName : String

The team name of the Home team in the match.

HomeTeamShortName : String

The short team name of the Home team in the match.

- AwayTeam

The Away (formal, not taking arena location into account) team of the match.

AwayTeamID : Integer

The teamID of the Away team in the match. (Negative for street teams)

AwayTeamName : String

The team name of the Away team in the match.

AwayTeamShortName : String

The short team name of the Away team in the match.

MatchDate : DateTime

The start date and time (kick-off) of the match.

SourceSystem : sourceSystem

SourceSystem tells from which system the match is ex: hatrick, youth, htointegrated

MatchType : MatchTypeID

Integer defining the type of match.

MatchContextId : unsigned Integer

This will be either LeagueLevelUnitId (for League), CupId (Cup, Hatrick Masters, World Cup and U-20 World Cup), LadderId, TournamentId, or 0 for friendly, qualification, single matches and preparation matches.

CupLevel : unsigned Integer

1 = National/Divisional cup, 2 = Challenger cup, 3 = Consolation cup. 0 if MatchType is not 3.

CupLevelIndex : unsigned Integer

In Challenger cups: 1 = Emerald (start week 2), 2 = Ruby (start week 3), 3 = Sapphire (start week 4). Always 1 for National/Divisional (main cups) and Consolation cups. 0 if MatchType is not 3.

HomeGoals : unsigned Integer

The current number of goals in the match for the home team.

AwayGoals : unsigned Integer

The current number of goals in the match for the away team.

Status : MatchStatus

Specifying whether the match is FINISHED, ONGOING or UPCOMING.

OrdersGiven : Boolean*

A boolean value only supplied for upcoming matches (haven't started yet) of your own team that signifies whether you have given orders or not. If the request is for another team than your own (even if it is for your opponent), this data is not sent.

Match Lineup

Match lineup for finished matches

Changelog [\(show\)](#)

Input

The following input parameters exist:

Simple

Detailed

Inputs for all different file versions are shown and marked.

required

 file = matchlineup

optional

 version =

2.1

required

 matchID :

unsigned Integer

 {Default:last match}
Specifies which particular match data is requested for.

required

 teamID :

unsigned Integer

 {Default:Logged on user's team}
Specifies which of the two participating teams data should be shown for.

Available in Version(s): 1.2, 1.3, 1.5, 1.6, 1.7

~~optional~~

 isYouth :

Boolean

 {Default:false}
Is request for youth or not.

optional

 sourceSystem :

sourceSystem

 {Default:Hattrick}
Specifies which source system the match belongs to, this replace the old isYouth param

Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple

Detailed

XML

Example

All containers and elements for the selected action type are shown. Containers/Elements for other file version are shown and marked.

- HatrickData

Hattrick Data Container for matchEvents=true

MatchID : unsigned Integer

The globally unique identifier of the match.

Removed in this Version

Available in Version(s): 1.2, 1.3, 1.5, 1.6, 1.7, 1.8, 1.9, 2.0

~~isYouth : Boolean~~

Is file request for youth or not.

Added in this Version

SourceSystem : sourceSystem

Specifies which source system the match belongs to, this replace the old isYouth param

- HomeTeam

The Home (formal, not taking arena location into account) team of the match.

HomeTeamID : Integer

The teamID of the Home team in the match. (Negative for street teams)

HomeTeamName : String

https://stage.hattrick.org/Community/CHPP/NewDocs/File.aspx?name=matchlineup

1/4

The team name of the Home team in the match.

- AwayTeam

The Away (formal, not taking arena location into account) team of the match.

AwayTeamID : Integer

The teamID of the Away team in the match. (Negative for street teams)

AwayTeamName : String

The team name of the Away team in the match.

MatchType : MatchTypeID

Integer defining the type of match.

MatchContextId : unsigned Integer

This will be either LeagueLevelUnitId (for League), CupId (Cup, Hatrick Masters, World Cup and U-20 World Cup), LadderId, TournamentId, or 0 for friendly, qualification, single matches and preparation matches.

- Arena

Container for the data about the arena where the match was played.

ArenaID : unsigned Integer

The globally unique arenaID.

ArenaName : String

The name of the arena.

- Team

Container for the data for the requested team.

TeamID : unsigned Integer

The globally unique teamID.

TeamName : String

The team's full name.

ExperienceLevel : SkillLevel

The aggregated experience level of the team.

StyleOfPlay : coachModifier

The style of play used in the match. Value will always be 0 for youth matches.

- StartingLineup

List of players in the hometeam who started the game

- Player

Container for a particular player that is part of the starting lineup.

PlayerID : unsigned Integer

Globally unique ID of the player.

RoleID : MatchRoleID

An integer indicating which formal 'slot' (Role) the player has filled in the match.

Available in Version(s): 1.6

PlayerName : String

The full name of the player.

FirstName : String

The first name of the player.

LastName : String

The last name of the player.

NickName : String

The nick name of the player.

Behaviour : MatchBehaviourID

An integer indicating the individual order or repositioning that the player has played with. Not provided for Captain and Set Pieces taker.

- Substitutions

Container for the substitutions in the game.

- Substitution

Container for a particular substitution.

TeamID : unsigned Integer

The globally unique TeamID for which the orders were sent.

SubjectPlayerID : unsigned Integer

If a/ substitution: The player leaving. If b/ behaviour change: The player changing his behaviour. Or c/ position swap: the first player that will change his position.

ObjectPlayerID : unsigned Integer

The player entering (or once more the player changing behaviour). Or if position swap, the player to swap with.

OrderType : matchOrderTypeID

The type of the order.

NewPositionId : MatchRoleID

An integer representing the new position for the (entering or staying) player.

NewPositionBehaviour : MatchBehaviourID

An integer representing the new behaviour for the (entering or staying) player.

MatchMinute : unsigned Integer

An integer indicating in which minute the order was executed.

MatchPart : matchPart

Which part of the match the order was executed.

- Lineup

Container for the lineup of the requested team.

- Player

Container for a particular player that is part of the lineup.

PlayerID : unsigned Integer

The globally unique playerID.

Available in Version(s): 1.2, 1.3

~~RoleID : MatchRoleOldID~~

~~An integer indicating which formal 'slot' (Role) the player has filled in the match, before the repositionings take effect. So, there can only be one (or zero) player with a particular RoleID (contrary to how PositionCode works). All games are 442-based.~~

RoleID : MatchRoleID

An integer indicating which formal 'slot' (Role) the player has filled in the match, before the repositionings take effect. So, there can only be one (or zero) player with a particular RoleID (contrary to how PositionCode works). Old games still have an 442-based RoleID!

RoleID : MatchRoleID

An integer indicating which formal 'slot' (Role) the player has filled in the match. All games are 553 based.

Available in Version(s): 1.2, 1.3, 1.5, 1.6

PlayerName : String

The full name of the player.

FirstName : String

The first name of the player.

LastName : String

The last name of the player.

NickName : String

The nick name of the player.

RatingStars : Float

The number of stars the player is rated for.

RatingStarsEndOfMatch : Float

The number of stars the player is rated for at the end of the game. This element is not provided for youth.

Available in Version(s): 1.2, 1.3

PositionCode : MatchPositionID

An integer indicating the position the player played at, after repositioning (behaviour) has been taken into account. So, there can be several players with PositionCode 10 (Forward 1). Players who are not on the field do not get a PositionCode. Strictly speaking, PositionCode could be calculated using RoleID and Behaviour and is formally redundant, but it is provided anyway.

Available in Version(s): 1.2, 1.3

PositionCode : MatchPositionID

An integer indicating the position the player played at, after repositioning (behaviour) has been taken into account. So, there can be several players with PositionCode 10 (Forward 1). Players who are not on the field do not get a PositionCode. Strictly speaking, PositionCode could be calculated using RoleID and Behaviour and is formally redundant, but it is provided anyway. In 553 based lineups this is just RoleID repeated.

Behaviour : MatchBehaviourID

An integer indicating the individual order or repositioning that the player has played with.

Team Details

Team information

Changelog [\(show\)](#)

Input

The following input parameters exist:

Simple

Detailed

Inputs for all different file versions are shown and marked.

required

 file = teamdetails

optional

 version =

3.9

required 1

 teamID :

unsigned Integer

 {Default:Your senior teamID}
What team/user to show the data for. teamID and userID generates the same result, except that ownerless teams can only be accessed if submitting a teamID and that users without a team can only be accessed if userID is submitted.

required 1

 userID :

unsigned Integer

 {Default:Your userID, if teamID is also not set}
What team/user to show the data for. teamID and userID generates the same result, except that ownerless teams can only be accessed if submitting a teamID and that users without a team can only be accessed if userID is submitted. If neither userID or teamID is supplied, userID defaults to the logged on user's userID.

optional

 includeDomesticFlags :

Boolean

 {Default:false}
Whether or not the teams own country should be included in the flag collections (provided games against domestic opponents have been played). If not specified then domestic flags won't be included.

optional

 includeFlags :

Boolean

 {Default:false}
Whether or not the flag collection should be provided. If not specified then flags won't be included.

optional

 includeSupporters :

Boolean

 {Default:false}
Whether or not the supported teams and the teams supporters should be included. If not specified they won't be included.

required_1: teamID or userID is required!

Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple

Detailed

XML

Example

All containers and elements for the selected action type are shown. Containers/Elements for other file version are shown and marked.

- HattrickData

Hattrick Data Container

- User

Container for the data about the user ('owner').

UserID : unsigned Integer

The globally unique UserID for the owner of the team. Teams without an owner have UserID = 0.

- Language

https://stage.hattrick.org/Community/CHPP/NewDocs/File.aspx?name=teamdetails

1/18

Container for the data about the language the user has chosen as his/her default language.

LanguageID : unsigned Integer

The globally unique LanguageID.

LanguageName : String

The language name

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6

HasSupporter : Boolean

Boolean value indicating whether the user is currently a Hattrick Supporter.

Available in Version(s): 2.7, 2.8, 2.9, 3.0, 3.1

SupporterTier : supporterTier

The current level of Hattrick Supporter that the user has (NOT including Diamond!). Empty if not a Supporter.

SupporterTier : supporterTier

The current level of Hattrick Supporter that the user has (including Diamond). Empty if not a Supporter.

Loginname : String

The 'username' or 'nickname' used in Forums and around the site. Not supplied if the team is ownerless.

Name : String

The user's personal name or the value 'HIDDEN' to indicate that the user has chosen to hide it. Not supplied if the team is ownerless.

ICQ : unsigned Integer

The user's ICQ number (if any). Not supplied if the team is ownerless.

SignupDate : DateTime

The date and time when the user signed up for Hattrick. Not supplied if the team is ownerless.

ActivationDate : DateTime

The date and time when the user gained control of this team. Not supplied if the team is ownerless.

LastLoginDate : DateTime

The date and time when the user last logged on. Not supplied if the team is ownerless.

Available in Version(s): 3.3, 3.4

HasManagerLicense : Boolean

Whether or not the user has received the manager license

HasManagerLicense : Boolean

Whether or not the user has received the manager license

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0, 3.1, 3.2, 3.3, 3.4

- **NationalTeamCoach**

Container for the national teams. An attribute named Count specifies how many national teams this user coaches. If 0, the child node does not exist.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0, 3.1, 3.2, 3.3, 3.4

- **NationalTeam**

Container for a national team:

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0, 3.1, 3.2, 3.3, 3.4

NationalTeamID : unsigned Integer

The globally unique identifier of the national team.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3.0, 3.1, 3.2, 3.3, 3.4

NationalTeamName : String

The name of the national team.

- NationalTeams

Container for the national teams.

- NationalTeam

Container for a national team.

- NationalTeamStaffType** : **NationalTeamStaffType**
The staff type id from the position the user has in the national team
- NationalTeamID** : **unsigned Integer**
The globally unique identifier of the national team.
- NationalTeamName** : **String**
The name of the national team.

- Teams

Container for the team(s) that are owned by the specified user.

- Team

Container for the data about the team (not supplied for user without team).

- TeamID** : **unsigned Integer**
The globally unique TeamID.
- TeamName** : **String**
The full team name.
- ShortTeamName** : **String**
The short team name.
- IsPrimaryClub** : **Boolean**
True/false indicating if this team is the user's primary team.
- FoundedDate** : **DateTime**
Date when club was founded.
- IsDeactivated** : **Boolean**
Whether or not the team is deactivated and not part of the league system
- GenderID** : **GenderID**
The gender of the team.

Added in this Version

LeagueSystemID : **LeagueSystemID**
The system type of the league for this team.

- Arena

Container for the data about the team's home ground.

- ArenaID** : **unsigned Integer**
The globally unique ArenaID.
- ArenaName** : **String**
The arena name.

- League

Container for the data about the league ('Sverige', 'England' and so on) the team is part of.

- LeagueID** : **unsigned Integer**
The globally unique LeagueID.
- LeagueName** : **String**

The League name.

- Country

Container for the data about the country ('Sverige', 'England' and so on) the team is part of.

CountryID : unsigned Integer

The globally unique CountryID.

CountryName : String

The Country name.

- Region

Container for the data about the region the team is located in.

RegionID : unsigned Integer

The globally unique RegionID.

RegionName : String

The Region name.

- Trainer

The player that is trainer ('coach') for the team. (Not to be confused with the 'owner'/'user').

PlayerID : unsigned Integer

The globally unique PlayerID of the player that has the job as trainer of the team.

HomePage : URI

The home page URL that the team has specified.

- Cup

Data about the team's cup status. If the team is playing a match the container is empty.

StillInCup : Boolean

Boolean value stating if the team is still in the cup.

CupID : unsigned Integer

The globally unique CupID of the cup that the team is still in. Only provided if team is still in cup.

CupName : String

The name of the cup that the team is still in. Only provided if team is still in cup.

CupLeagueLevel : unsigned Integer

LeagueLevel for the cup. 0 = National (LeagueLevel 1-6), 7-9 = Divisional. Only provided if team is still in cup.

CupLevel : unsigned Integer

Level of the cup. 1 = National/Divisional, 2 = Challenger, 3 = Consolation. Only provided if team is still in cup.

CupLevelIndex : unsigned Integer

Index of the cup. Always 1 for National and Consolation cups, for Challenger cup: 1 = Emerald, 2 = Ruby, 3 = Sapphire. Only provided if team is still in cup.

MatchRound : unsigned Integer

Next round (or current if matches are ongoing). (Note that this is different from WorldDetails!). Only provided if team is still in cup.

MatchRoundsLeft : unsigned Integer

How many rounds are left of this cup. Only provided if team is still in cup.

- PowerRating

Data about the team's Power Rating

GlobalRanking : unsigned Integer

The Power Rating team ranking in Global.

LeagueRanking : unsigned Integer

The Power Rating team ranking in the same league.

RegionRanking : unsigned Integer

The Power Rating team ranking in the same region.

PowerRating : unsigned Integer

The Power Rating value of the team.

FriendlyTeamID : unsigned Integer

The team's status about if a friendly is booked. The value is the opponents globally unique teamID if the team has booked a friendly, 0 if not. If the team is playing a match the tag will be empty.

- LeagueLevelUnit

Data about the team's LeagueLevelUnit ('series'). If the league is playing qualification matches the tag will be empty.

LeagueLevelUnitID : unsigned Integer

The globally unique LeagueLevelUnitID.

LeagueLevelUnitName : String

The name of the LeagueLevelUnit.

LeagueLevel : unsigned Integer

Integer value stating the relative level of the LeagueLevelUnit, with 1 indicating the league's top series.

NumberOfVictories : unsigned Integer

If the team is in a winning streak of at least 2 matches, this integer indicates how many victories in a row it currently has. If the team is playing a match the tag will be empty.

NumberOfUndefeated : unsigned Integer

If the team is in a streak of at least 2 matches as undefeated, this integer indicates how many matches in a row it is undefeated. If the team is playing a match the tag will be empty.

- Fanclub

Container for the data about the team's fanclub.

FanclubID : unsigned Integer

The globally unique FanclubID.

FanclubName : String

The name of the fanclub.

FanclubSize : unsigned Integer

The amount of members in the fanclub.

Available in Version(s): 2.8, 2.9

~~**LogoURL** : URI~~

~~This container and its elements is only shown if the user has supporter
The logo URL that the team has specified. Only supplied if the user has Hattrick
Supporter.~~

LogoURL : URI

The logo URL that the team has specified.

- Guestbook

This container and its elements is only shown if the user has supporter Container for the data about the team's guestbook.

NumberOfGuestbookItems : unsigned Integer

The number of postings in the team's guestbook.

- PressAnnouncement

This container and its elements is only shown if the user has supporter Container for the data about the team's most recent PressAnnouncement.

Subject : String

The subject text specified for the PressAnnouncement.

Body : String

The body of the PressAnnouncement.

SendDate : DateTime

The time and date when the PressAnnouncement was submitted.

- TeamColors

This container and its elements is only shown if the user has supporter Container for the team's club theme colors. Empty if no theme has been set for the club.

BackgroundColor : String

The defined background color from the club theme.

Color : String

The matching text color to the defined background color.

DressURI : URI

URI to an image representing the dress of the team.

DressAlternateURI : URI

Same as DressURI, except that it shows the alternate dress.

- BotStatus

Container with data indicating if a team is a 'bot'. If yes the team has default and random lineup and players.

IsBot : Boolean

Specifies whether a team is currently a bot or not.

BotSince : DateTime

The date when the team was made a bot, only available if team is a bot.

TeamRank : unsigned Integer

If the team has an owner, last is the League Rank, a number based on LeagueLevel, position etc, only counting teams with an owner. If the team is playing a match the tag will be empty.

YouthTeamID : unsigned Integer

If the Team has a Youth academy the ID is represented here. If not it will be 0.

YouthTeamName : String*

If the Team has a Youth academy the team name is represented here. If not it will be an empty string.

NumberOfVisits : unsigned Integer

The number of visits the team had in the latest day with at least one visit.

- Flags

Acquired team flags.

- HomeFlags

Acquired team home flags.

- Flag

Container for flags.

LeagueID : unsigned Integer

The Leagueid for the league a flag belongs to.

LeagueName : String

The LeagueName for the league a flag belongs to.

CountryCode : String

The CountryCode for the league a flag belongs to.

- AwayFlags

Acquired team away flags.

- Flag

Container for flags.

LeagueID : unsigned Integer

The Leagueid for the league a flag belongs to.

LeagueName : String

The LeagueName for the league a flag belongs to.

CountryCode : String

The CountryCode for the league a flag belongs to.

- TrophyList

Container for the team's trophies. It will be empty if no trophies are won.

- Trophy

Container for the trophy. There may be several of this element.

TrophyTypeld : trophyID

Typeld for the trophy

TrophySeason : unsigned Integer

The season the trophy was won.

LeagueLevel : unsigned Integer

The level the league the user won. For tournament trophies, this act as a "type".

LeagueLevelUnitId : String

The LeagueLevelUnitId of the leaguelevelunit that the user won. For tournaments this is the id of the tournament.

LeagueLevelUnitName : String

The name of the leaguelevelunit that the user won. For tournaments this is the name of the tournament.

GainedDate : DateTime

The date when the user gained the trophy.

ImageUrl : URI

The url to the trophy image.

CupLeagueLevel : unsigned Integer

The league level of the cup. 0 for the main cups, division 1-6. Empty when not a cup trophy (16).

CupLevel : CupLevel

The level of the cup. Empty when not a cup trophy (16).

CupLevelIndex : CupLevelIndex

Which type of challenger cup. Always 1 for national and consolation cups. Empty when not a cup trophy (16).

- SupportedTeams

Attribute: 'TotalItems' : unsigned Integer

Shows how many teams the user supports in total.

Attribute: 'MaxItems' : unsigned Integer

Shows how many teams that can maximum be outputted in this list.

Container for the the supported teams. It will be empty if the user have no supporters and not present if the user are not a supporter. Only available, when includeSupporters=true.

- SupportedTeam

Container for a supported team. Not supplied if the user dont have no supporters.

UserId : unsigned Integer

The globally unique UserID for the owner of the supported team.

LoginName : String

The 'username' or 'nickname' used in Forums and around the site.

TeamId : unsigned Integer

The globally unique TeamID for the supported team.

TeamName : String

The teamname of the supported team.

LeagueID : unsigned Integer

The globally unique LeagueID for the supported team.

LeagueName : String

The League name.

LeagueLevelUnitID : unsigned Integer

The globally unique LeagueLevelUnitID for the supported team.

LeagueLevelUnitName : String

The name of the LeagueLevelUnit.

- LastMatch

Container for the last match of the supported team.

LastMatchId : unsigned Integer

The globally unique matchID.

LastMatchDate : DateTime

The matchdate of the last match.

LastMatchHomeTeamId : unsigned Integer

The globally unique TeamID for the home team.

LastMatchHomeTeamName : String

The team name of the home team in the match.

LastMatchHomeGoals : unsigned Integer

The number of goals scored in the match by the hometeam.

LastMatchAwayTeamId : unsigned Integer

The globally unique TeamID for the away team.

LastMatchAwayTeamName : String

The team name of the away team in the match.

LastMatchAwayGoals : unsigned Integer

The number of goals scored in the match by the awayteam.

- NextMatch

Container for the last match of the supported team.

NextMatchId : unsigned Integer

The globally unique matchID.

NextMatchDate : DateTime

The matchdate of the next match.

NextMatchHomeTeamId : unsigned Integer

The globally unique TeamID for the home team.

NextMatchHomeTeamName : String

The team name of the home team in the match.

NextMatchAwayTeamId : unsigned Integer

The globally unique TeamID for the away team.

NextMatchAwayTeamName : String

The team name of the away team in the match.

- PressAnnouncement

Container for the data about the user's most recent PressAnnouncement.

PressAnnouncementSendDate : DateTime

The time and date when the PressAnnouncement was submitted.

PressAnnouncementSubject : String

The subject text specified for the PressAnnouncement.

PressAnnouncementBody : String

The body of the PressAnnouncement.

- MySupporters*Attribute: 'TotalItems' : unsigned Integer**Shows how many teams supports the team in total.**Attribute: 'MaxItems' : unsigned Integer**Shows how many teams that can maximum be outputted in this list.*

Container for the the supported teams. It will be empty if the user have no supporters and not present if the user are not a supporter. Only available, when includeSupporters=true.

- SupporterTeam

Container for a supported team. Not supplied if the user dont have no supporters.

UserId : unsigned Integer

The globally unique UserID for the owner of the supporter team.

LoginName : String

The 'username' or 'nickname' used in Forums and around the site.

TeamId : unsigned Integer

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- Team

Container for the data about the team (not supplied for user without team):

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

TeamID : unsigned Integer

The globally unique TeamID.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

TeamName : String

The full team name.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

ShortTeamName : String

The short team name.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- Arena

Container for the data about the team's home-ground:

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

ArenaID : unsigned Integer

The globally unique ArenaID.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

ArenaName : String

The arena name.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- League

Container for the data about the league ('Sverige', 'England' and so on) the team is part of:

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

LeagueID : unsigned Integer

The globally unique LeagueID.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

LeagueName : String

The League name.

https://stage.hattrick.org/Community/CHPP/NewDocs/File.aspx?name=teamdetails

10/18

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- Region

Container for the data about the region the team is located in.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

RegionID : unsigned Integer

The globally unique RegionID.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

RegionName : String

The Region name.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- Trainer

The player that is trainer ('coach') for the team. (Not to be confused with the 'owner'/'user').

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

PlayerID : unsigned Integer

The globally unique PlayerID of the player that has the job as trainer of the team.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

HomePage : URI

The home page URL that the team has specified.

Available in Version(s): 1.9

Clubhouse : URI

Exists only if the team has a Clubhouse and if so holds the name of that clubhouse. The URL of the clubhouse will then be <http://club.hattrick.org/ClubhouseName/> where ClubhouseName is a placeholder for the value in tag Clubhouse.

Available in Version(s): 1.9

- Cup

Data about the team's cup status. If the team is playing a match, an attribute named Available is set to false and the container is empty, otherwise to true.

Available in Version(s): 1.9

StillInCup : Boolean

Boolean value stating if the team is still in the cup.

Available in Version(s): 1.9

CupID : unsigned Integer

The globally unique CupID of the cup that the team is still in. Only provided if team is still in cup.

Available in Version(s): 1.9

CupName : String

The name of the cup that the team is still in. Only provided if team is still in cup.

Available in Version(s): 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- Cup

Data about the team's cup status. If the team is playing a match the container is empty.

Available in Version(s): 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

StillInCup : Boolean

Boolean value stating if the team is still in the cup.

Available in Version(s): 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

CupID : unsigned Integer

The globally unique CupID of the cup that the team is still in. Only provided if team is still in cup.

Available in Version(s): 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

CupName : String

The name of the cup that the team is still in. Only provided if team is still in cup.

CupLeagueLevel : unsigned Integer

LeagueLevel for the cup. 0 = National (LeagueLevel 1-6), 7-9 = Divisional. Only provided if team is still in cup.

CupLevel : unsigned Integer

Level of the cup. 1 = National/Divisional, 2 = Challenger, 3 = Consolation. Only provided if team is still in cup.

CupLevelIndex : unsigned Integer

Index of the cup. Always 1 for National and Consolation cups, for Challenger cup: 1 = Emerald, 2 = Ruby, 3 = Sapphire. Only provided if team is still in cup.

MatchRound : unsigned Integer

Next round (or current if matches are ongoing). (Note that this is different from WorldDetails!). Only provided if team is still in cup.

MatchRoundsLeft : unsigned Integer

How many rounds are left of this cup. Only provided if team is still in cup.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

FriendlyTeamID : unsigned Integer

The team's status about if a friendly is booked. The value is the opponents globally unique teamID if the team has booked a friendly, 0 if not. If the team is playing a match the tag will be empty.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- LeagueLevelUnit

Data about the team's LeagueLevelUnit ('series'). If the league is playing qualification matches the tag will be empty.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

LeagueLevelUnitID : unsigned Integer

The globally unique LeagueLevelUnitID.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

LeagueLevelUnitName : String

The name of the LeagueLevelUnit.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

LeagueLevel : unsigned Integer

Integer value stating the relative level of the LeagueLevelUnit, with 1 indicating the league's top series.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

NumberOfVictories : unsigned Integer

If the team is in a winning streak of at least 2 matches, this integer indicates how many victories in a row it currently has. If the team is playing a match the tag will be empty.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

NumberOfUndeclared : unsigned Integer

If the team is in a streak of at least 2 matches as undeclared, this integer indicates how many matches in a row it is undeclared. If the team is playing a match the tag will be empty.

Available in Version(s): 2.5, 2.6, 2.7

- Fanclub

Container for the data about the team's fanclub.

Available in Version(s): 2.5, 2.6, 2.7

FanclubID : unsigned Integer

The globally unique FanclubID.

Available in Version(s): 2.5, 2.6, 2.7

FanclubName : String

The name of the fanclub.

Available in Version(s): 2.5, 2.6, 2.7

FanclubSize : unsigned Integer

The amount of members in the fancub.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

LogoURL : **URI**

This container and its elements is only shown if the user has supporter
The logo URL that the team has specified. Only supplied if the user has Hattrick
Supporter.

LogoURL : **URI**

The logo URL that the team has specified.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4

- Fancub

This container and its elements is only shown if the user has supporter
Container for the data about the team's fancub.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4

FancubID : **unsigned Integer**

The globally unique FancubID.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4

FancubName : **String**

The name of the fancub.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- Guestbook

This container and its elements is only shown if the user has supporter
Container for the data about the team's guestbook.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

NumberOfGuestbookItems : **unsigned Integer**

The number of postings in the team's guestbook.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- PressAnnouncement

This container and its elements is only shown if the user has supporter
Container for the data about the team's most recent PressAnnouncement.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

Subject : **String**

The subject text specified for the PressAnnouncement.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

Body : **String**

The body of the PressAnnouncement.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

SendDate : **DateTime**

The time and date when the PressAnnouncement was submitted.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3

Dress : **String**

7-character string representing the dress of the team: First character is a letter
indicating type of dress. Next two numbers indicate the shirt colour, next two indicate
pants colour and final two numbers indicate socks colour.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3

DressAlternate : **String**

Same as dress, except that it shows the alternate dress.

Available in Version(s): 2.4, 2.5, 2.6, 2.7

DressURI : **URI**

URI to an image representing the dress of the team.

Available in Version(s): 2.4, 2.5, 2.6, 2.7

DressAlternateURI : **URI**

Same as DressURI, except that it shows the alternate dress.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- BotStatus

Container with data indicating if a team is a 'bot'. If yes the team has default and random lineup and players.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

IsBot : **Boolean**

Specifies whether a team is currently a bot or not.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

BotSince : **DateTime**

The date when the team was made a bot, only available if team is a bot.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

TeamRank : **unsigned Integer**

If the team has an owner, last is the League Rank, a number based on LeagueLevel, position etc, only counting teams with an owner. If the team is playing a match the tag will be empty.

Available in Version(s): 1.9, 2.0, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

YouthTeamID : **unsigned Integer**

If the Team has a Youth academy the ID is represented here. If not it will be 0.

Available in Version(s): 2.4, 2.5, 2.6, 2.7

YouthTeamName : **String***

If the Team has a Youth academy the team name is represented here. If not it will be an empty string.

Available in Version(s): 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- Flags

Acquired team flags:

Available in Version(s): 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- HomeFlags

Acquired team home flags:

Available in Version(s): 2.2

CountryCode : **String**

The CountryCode for the league a flag belongs to.

Available in Version(s): 2.3, 2.4, 2.5, 2.6, 2.7

- Flag

Container for flags:

Available in Version(s): 2.3, 2.4, 2.5, 2.6, 2.7

LeagueID : **unsigned Integer**

The LeagueId for the league a flag belongs to.

Available in Version(s): 2.3, 2.4, 2.5, 2.6, 2.7

LeagueName : **String**

The LeagueName for the league a flag belongs to.

Available in Version(s): 2.3, 2.4, 2.5, 2.6, 2.7

CountryCode : **String**

The CountryCode for the league a flag belongs to.

Available in Version(s): 2.2, 2.3, 2.4, 2.5, 2.6, 2.7

- AwayFlags

Acquired team away flags:

Available in Version(s): 2.2

CountryCode : **String**

The CountryCode for the league a flag belongs to.

Available in Version(s): 2.3, 2.4, 2.5, 2.6, 2.7

- Flag

Container for flags:

Available in Version(s): 2.3, 2.4, 2.5, 2.6, 2.7

LeagueId : **unsigned Integer**

The LeagueId for the league a flag belongs to.

Available in Version(s): 2.3, 2.4, 2.5, 2.6, 2.7

LeagueName : **String**

The LeagueName for the league a flag belongs to.

Available in Version(s): 2.3, 2.4, 2.5, 2.6, 2.7

CountryCode : **String**

The CountryCode for the league a flag belongs to.

Available in Version(s): 2.6, 2.7

- TrophyList

Container for the team's trophies. It will be empty if no trophies are won.

Available in Version(s): 2.6, 2.7

- Trophy

Container for the trophy. There may be several of this element.

Available in Version(s): 2.6, 2.7

TrophyTypeId : **trophyID**

TypeId for the trophy

Available in Version(s): 2.6, 2.7

TrophySeason : **unsigned Integer**

The season the trophy was won.

Available in Version(s): 2.6, 2.7

LeagueLevel : **unsigned Integer**

The level the league the user won. For tournament trophies, this act as a "type".

LeagueLevelUnitId : **String**

The LeagueLevelUnitId of the leaguelevelunit that the user won. For tournaments this is the id of the tournament.

Available in Version(s): 2.6, 2.7

LeagueLevelUnitName : **String**

The name of the leaguelevelunit that the user won. For tournaments this is the name of the tournament.

Available in Version(s): 2.6, 2.7

GainedDate : **DateTime**

The date when the user gained the trophy.

Available in Version(s): 2.6, 2.7

ImageUrl : **URI**

The url to the trophy image.

Available in Version(s): 2.6, 2.7

- SupportedTeams

Attribute: 'TotalItems' : **unsigned Integer**

—Shows how many teams the user supports in total.

Attribute: 'MaxItems' : **unsigned Integer**

—Shows how many teams that can maximum be outputted in this list.

Container for the the supportd teams. It will be empty if the user have no supporters and not present if the user are not a supporter. Only available, when includeSupporters=true.

Available in Version(s): 2.6, 2.7

- SupportedTeam

Container for a supported team. Not supplied if the user dont have no supporters.

Available in Version(s): 2.6, 2.7
UserId : **unsigned Integer**
The globally unique UserID for the owner of the supported team.

Available in Version(s): 2.6, 2.7
LoginName : **String**
The 'username' or 'nickname' used in Forums and around the site.

Available in Version(s): 2.6, 2.7
TeamId : **unsigned Integer**
The globally unique TeamID for the supported team.

Available in Version(s): 2.6, 2.7
TeamName : **String**
The teamname of the supported team.

Available in Version(s): 2.6, 2.7
LeagueID : **unsigned Integer**
The globally unique LeagueID for the supported team.

Available in Version(s): 2.6, 2.7
LeagueName : **String**
The League name.

Available in Version(s): 2.6, 2.7
LeagueLevelUnitID : **unsigned Integer**
The globally unique LeagueLevelUnitID for the supported team.

Available in Version(s): 2.6, 2.7
LeagueLevelUnitName : **String**
The name of the LeagueLevelUnit.

Available in Version(s): 2.6, 2.7
- LastMatch
Container for the last match of the supported team.

Available in Version(s): 2.6, 2.7
LastMatchId : **unsigned Integer**
The globally unique matchID.

Available in Version(s): 2.6, 2.7
LastMatchDate : **DateTime**
The matchdate of the last match.

Available in Version(s): 2.6, 2.7
LastMatchHomeTeamId : **unsigned Integer**
The globally unique TeamID for the home team.

Available in Version(s): 2.6, 2.7
LastMatchHomeTeamName : **String**
The team name of the home team in the match.

Available in Version(s): 2.6, 2.7
LastMatchHomeGoals : **unsigned Integer**
The number of goals scored in the match by the hometeam.

Available in Version(s): 2.6, 2.7
LastMatchAwayTeamId : **unsigned Integer**
The globally unique TeamID for the away team.

Available in Version(s): 2.6, 2.7
LastMatchAwayTeamName : **String**
The team name of the away team in the match.

Available in Version(s): 2.6, 2.7
LastMatchAwayGoals : **unsigned Integer**

The number of goals scored in the match by the awayteam.

Available in Version(s): 2.6, 2.7

- NextMatch

Container for the last match of the supported team.

Available in Version(s): 2.6, 2.7

NextMatchId : unsigned Integer

The globally unique matchID.

Available in Version(s): 2.6, 2.7

NextMatchDate : DateTime

The matchdate of the next match.

Available in Version(s): 2.6, 2.7

NextMatchHomeTeamId : unsigned Integer

The globally unique TeamID for the home team.

Available in Version(s): 2.6, 2.7

NextMatchHomeTeamName : String

The team name of the home team in the match.

Available in Version(s): 2.6, 2.7

NextMatchAwayTeamId : unsigned Integer

The globally unique TeamID for the away team.

Available in Version(s): 2.6, 2.7

NextMatchAwayTeamName : String

The team name of the away team in the match.

Available in Version(s): 2.6, 2.7

- PressAnnouncement

Container for the data about the user's most recent PressAnnouncement.

Available in Version(s): 2.6, 2.7

PressAnnouncementSendDate : DateTime

The time and date when the PressAnnouncement was submitted.

Available in Version(s): 2.6, 2.7

PressAnnouncementSubject : String

The subject text specified for the PressAnnouncement.

Available in Version(s): 2.6, 2.7

PressAnnouncementBody : String

The body of the PressAnnouncement.

Available in Version(s): 2.6, 2.7

- MySupporters

Attribute: 'TotalItems' : unsigned Integer

—Shows how many teams supports the team in total.

Attribute: 'MaxItems' : unsigned Integer

—Shows how many teams that can maximum be outputted in this list.

Container for the the supported teams. It will be empty if the user have no supporters and not present if the user are not a supporter. Only available, when includeSupporters=true.

Available in Version(s): 2.6, 2.7

- SupporterTeam

Container for a supported team. Not supplied if the user dont have no supporters.

Available in Version(s): 2.6, 2.7

UserId : unsigned Integer

The globally unique UserID for the owner of the supporter team.

Available in Version(s): 2.6, 2.7

LoginName : **String**

The 'username' or 'nickname' used in Forums and around the site.

Available in Version(s): 2.6, 2.7

TeamId : **unsigned Integer**

The globally unique TeamID for the supporter team.

Available in Version(s): 2.6, 2.7

TeamName : **String**

The teamname of the supporter team.

Available in Version(s): 2.6, 2.7

LeagueID : **unsigned Integer**

The globally unique LeagueID for the supporter team.

Available in Version(s): 2.6, 2.7

LeagueName : **String**

The League name.

Available in Version(s): 2.6, 2.7

LeagueLevelUnitID : **unsigned Integer**

The globally unique LeagueLevelUnitID for the supported team.

Available in Version(s): 2.6, 2.7

LeagueLevelUnitName : **String**

The name of the LeagueLevelUnit.