

Get (live) match ticker

Input

The following input parameters exist:

Simple	Detailed
Only available inputs in this file version are shown.	
required file = live	
optional version = 2.3 ▼	
optional actionType = view {default} ▼	
Indicates what type of action the page should perform.	
view {default} Show the latest event(s) for all tracked matches. If matchID is supplied, that match will be shown with all events since the start of the game ('expanded' view).	
optional matchID : <u>unsigned Integer</u> The globally unique matchID.	
optional sourceSystem : <u>sourceSystem</u> {Default:hattrick} Specifies which source system the match belongs to, this replace the old isYouth param	
optional includeStartingLineup : <u>Boolean</u> {Default:false} Should <StartingLineup> and <Substitutions> be included in the response?	
optional useLiveEventsAndTexts : <u>Boolean</u> {Default:false} Should the events and texts be as on the live page on the site?	
viewNew Show those matches where new events have occurred since last request of the page. You'll need to send the which was your last event according to LastShownIndexes	
optional includeStartingLineup : <u>Boolean</u> {Default:false} Should <Substitutions> be included in the response? <i>(Note that <StartingLineup> is never provided for viewNew)</i>	
optional useLiveEventsAndTexts : <u>Boolean</u> {Default:false} Should the events and texts be as on the live page on the site?	
optional lastShownIndexes : <u>String</u> JSON formatted array of last shown indexes for each match. See reference: <u>#LastShownIndexes</u> .	
viewAll Show all the events for all matches.	
optional includeStartingLineup : <u>Boolean</u> {Default:false} Should <StartingLineup> and <Substitutions> be included in the response?	
optional useLiveEventsAndTexts : <u>Boolean</u> {Default:false} Should the events and texts be as on the live page on the site?	
clearAll Remove all tracked matches from the tracking session.	

addMatch

Add a new match to be tracked.

required matchID : unsigned Integer

The globally unique matchID.

optional sourceSystem : sourceSystem {Default:hattrick}

Specifies which source system the match belongs to, this replace the old isYouth param

optional includeStartingLineup : Boolean {Default:false}

Should <StartingLineup> and <Substitutions> be included in the response?

optional useLiveEventsAndTexts : Boolean {Default:false}

Should the events and texts be as on the live page on the site?

deleteMatch

Remove a particular match from the session.

required matchID : unsigned Integer

The globally unique matchID.

optional sourceSystem : sourceSystem {Default:hattrick}

Specifies which source system the match belongs to, this replace the old isYouth param

Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple Detailed XML Example

All containers and elements for the selected file version and action type are shown.

- HattrickData

Hattrick Data Container for actionType=view

- MatchList

Container for all the matches.

- Match

The container for a match. An attribute called Index signifies the number of the match in the list.

MatchID : unsigned Integer

The globally unique identifier of the match.

MatchType : MatchTypeID

Integer defining the type of match.

SourceSystem : sourceSystem

Specifies which source system the match belongs to, this replace the old isYouth param

MatchDate : DateTime

The start date (kick-off) of the match.

- HomeTeam

The Home (formal, not taking arena location into account) team of the match.

HomeTeamID : Integer

The teamID of the Home team in the match. (Negative for street teams)

HomeTeamName : String

The team name of the Home team in the match.

HomeTeamShortName : String

The short team name of the Home team in the match.

- StartingLineup

List of players in the hometeam who started the game

- Player

Container for a particular player that is part of the starting lineup.

PlayerID : unsigned Integer

Globally unique ID of the player.

RoleID : MatchRoleID

An integer indicating which formal 'slot' (Role) the player has filled in the match.

PlayerName : String

The full name of the player.

Behaviour : MatchBehaviourID

An integer indicating the individual order or repositioning that the player has played with. Not provided for Captain and Set Pieces taker.

- AwayTeam

The Away (formal, not taking arena location into account) team of the match.

AwayTeamID : Integer

The teamID of the Away team in the match. (Negative for street teams)

AwayTeamName : String

The team name of the Away team in the match.

AwayTeamShortName : String

The short team name of the Away team in the match.

- StartingLineup

List of players in the awayteam who started the game

- Player

Container for a particular player that is part of the starting lineup.

PlayerID : unsigned Integer

Globally unique ID of the player.

RoleID : MatchRoleID

An integer indicating which formal 'slot' (Role) the player has filled in the match.

PlayerName : String

The full name of the player.

Behaviour : MatchBehaviourID

An integer indicating the individual order or repositioning that the player has played with. Not provided for Captain and Set Pieces taker.

- Substitutions

Container for the substitutions in the game.

- Substitution

Container for a particular substitution. An attribute named Index gives a counter.

TeamID : unsigned Integer

The globally unique TeamID for which the orders were sent.

SubjectPlayerID : unsigned Integer

If a/ substitution: The player leaving. If b/ behaviour change: The player changing his behaviour. Or c/ position swap: the first player that will change his position.

ObjectPlayerID : unsigned Integer

The player entering (or once more the player changing behaviour). Or if position swap, the player to swap with.

OrderType : matchOrderTypeID

The type of the order.

NewPositionId : MatchRoleID

An integer representing the new position for the (entering or staying) player.

NewPositionBehaviour : MatchBehaviourID

An integer representing the new behaviour for the (entering or staying) player.

MatchMinute : unsigned Integer

An integer indicating in which minute the order was executed.

MatchPart : matchPart

Which part of the match the order was executed.

- EventList

Container for all the events.

- Event

Attribute: 'Index' : unsigned Integer

Indicates the order of the event relative to the other events sent in the same batch for this match.

Container for the data for a certain event.

See information [MatchEventTypes](#)

Minute : unsigned Integer

The match minute when the event happened.

MatchPart : matchPart

Which part of the match the event happened.

EventKey : String

A unique key defining what type of event it was.

EventText : String

String describing the event as it would appear in the match report.

SubjectTeamID : unsigned Integer

Integer that, for goals and chances, is indicating the attacking team. For other event, this field usually indicates the team that is doing something. It may indicate other things for other events - exactly what is not documented here and the SubjectTeamID information, while free to use for CHPPs is 'unsupported' and used 'at your own risk'.

SubjectPlayerID : unsigned Integer

Integer that, for goals and chances, is indicating the scorer or the player failing to score. For other events, this field usually indicates the primarily active player. It may indicate other things for other events and like SubjectTeamID is 'unsupported' and used 'at your own risk'.

ObjectPlayerID : unsigned Integer

Integer that, for regular goals and chances, is indicating the defending team's goal keeper. For special event chances/goals, the ObjectPlayer is often the assisting player of the attacking team, but can be any other player that is involved in the event. For other events, this field is used very freely and can indicate any kind of relevant integer data. Like SubjectPlayerID and SubjectTeamID, it is 'unsupported' and used at 'your own risk'.

HomeGoals : unsigned Integer

The current number of goals in the match for the home team.

AwayGoals : unsigned Integer

The current number of goals in the match for the away team.

LastShownEventIndex : unsigned Integer

The last shown event. Use this as LastShownIndexes for actionType=viewNew.

NextEventMinute : unsigned Integer

The minute that the next matchevent will happen, this allows you to only ask for new events when needed. Only available while the match is ongoing. It should only be used by the application, **it should NOT be shown to the users.**

NextEventMatchPart : matchPart

The matchPart in which the next matchevent will happen, this allows you to only ask for new events when needed. Only available while the match is ongoing. It should only be used by the application, **it should NOT be shown to the users.**