

# Match Lineup

## Match lineup for finished matches

Changelog [\(show\)](#)

### Input

The following input parameters exist:

Simple

Detailed

Inputs for all different file versions are shown and marked.

required

file = matchlineup

optional

version = 

2.1

required

matchID : 

unsigned Integer

 {Default:last match}  
Specifies which particular match data is requested for.

required

teamID : 

unsigned Integer

 {Default:Logged on user's team}  
Specifies which of the two participating teams data should be shown for.

Available in Version(s): 1.2, 1.3, 1.5, 1.6, 1.7

~~optional~~isYouth : 

Boolean

 {Default:false}  
Is request for youth or not.

optional

sourceSystem : 

sourceSystem

 {Default:Hattrick}  
Specifies which source system the match belongs to, this replace the old isYouth param

### Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple

Detailed

XML

Example

All containers and elements for the selected action type are shown. Containers/Elements for other file version are shown and marked.

- HatrickData

Hattrick Data Container for matchEvents=true

MatchID : unsigned Integer

The globally unique identifier of the match.

Removed in this Version

Available in Version(s): 1.2, 1.3, 1.5, 1.6, 1.7, 1.8, 1.9, 2.0

~~isYouth : Boolean~~  
Is file request for youth or not.

Added in this Version

SourceSystem : sourceSystem

Specifies which source system the match belongs to, this replace the old isYouth param

- HomeTeam

The Home (formal, not taking arena location into account) team of the match.

HomeTeamID : Integer

The teamID of the Home team in the match. (Negative for street teams)

HomeTeamName : String

https://stage.hattrick.org/Community/CHPP/NewDocs/File.aspx?name=matchlineup

1/4

The team name of the Home team in the match.

#### - AwayTeam

The Away (formal, not taking arena location into account) team of the match.

**AwayTeamID** : Integer

The teamID of the Away team in the match. (Negative for street teams)

**AwayTeamName** : String

The team name of the Away team in the match.

**MatchType** : MatchTypeID

Integer defining the type of match.

**MatchContextId** : unsigned Integer

This will be either LeagueLevelUnitId (for League), CupId (Cup, Hatrick Masters, World Cup and U-20 World Cup), LadderId, TournamentId, or 0 for friendly, qualification, single matches and preparation matches.

#### - Arena

Container for the data about the arena where the match was played.

**ArenaID** : unsigned Integer

The globally unique arenaID.

**ArenaName** : String

The name of the arena.

#### - Team

Container for the data for the requested team.

**TeamID** : unsigned Integer

The globally unique teamID.

**TeamName** : String

The team's full name.

**ExperienceLevel** : SkillLevel

The aggregated experience level of the team.

**StyleOfPlay** : coachModifier

The style of play used in the match. Value will always be 0 for youth matches.

#### - StartingLineup

List of players in the hometeam who started the game

##### - Player

Container for a particular player that is part of the starting lineup.

**PlayerID** : unsigned Integer

Globally unique ID of the player.

**RoleID** : MatchRoleID

An integer indicating which formal 'slot' (Role) the player has filled in the match.

*Available in Version(s): 1.6*

**PlayerName** : String

The full name of the player.

**FirstName** : String

The first name of the player.

**LastName** : String

The last name of the player.

**NickName** : String

The nick name of the player.

**Behaviour : MatchBehaviourID**

An integer indicating the individual order or repositioning that the player has played with. Not provided for Captain and Set Pieces taker.

**- Substitutions**

Container for the substitutions in the game.

**- Substitution**

Container for a particular substitution.

**TeamID : unsigned Integer**

The globally unique TeamID for which the orders were sent.

**SubjectPlayerID : unsigned Integer**

If a/ substitution: The player leaving. If b/ behaviour change: The player changing his behaviour. Or c/ position swap: the first player that will change his position.

**ObjectPlayerID : unsigned Integer**

The player entering (or once more the player changing behaviour). Or if position swap, the player to swap with.

**OrderType : matchOrderTypeID**

The type of the order.

**NewPositionId : MatchRoleID**

An integer representing the new position for the (entering or staying) player.

**NewPositionBehaviour : MatchBehaviourID**

An integer representing the new behaviour for the (entering or staying) player.

**MatchMinute : unsigned Integer**

An integer indicating in which minute the order was executed.

**MatchPart : matchPart**

Which part of the match the order was executed.

**- Lineup**

Container for the lineup of the requested team.

**- Player**

Container for a particular player that is part of the lineup.

**PlayerID : unsigned Integer**

The globally unique playerID.

*Available in Version(s): 1.2, 1.3*

**~~RoleID : MatchRoleOldID~~**

~~An integer indicating which formal 'slot' (Role) the player has filled in the match, before the repositionings take effect. So, there can only be one (or zero) player with a particular RoleID (contrary to how PositionCode works). All games are 442-based.~~

**RoleID : MatchRoleID**

An integer indicating which formal 'slot' (Role) the player has filled in the match, before the repositionings take effect. So, there can only be one (or zero) player with a particular RoleID (contrary to how PositionCode works). Old games still have an 442-based RoleID!

**RoleID : MatchRoleID**

An integer indicating which formal 'slot' (Role) the player has filled in the match. All games are 553 based.

Available in Version(s): 1.2, 1.3, 1.5, 1.6

**PlayerName** : String

The full name of the player.

**FirstName** : String

The first name of the player.

**LastName** : String

The last name of the player.

**NickName** : String

The nick name of the player.

**RatingStars** : Float

The number of stars the player is rated for.

**RatingStarsEndOfMatch** : Float

The number of stars the player is rated for at the end of the game. This element is not provided for youth.

Available in Version(s): 1.2, 1.3

**PositionCode** : MatchPositionID

An integer indicating the position the player played at, after repositioning (behaviour) has been taken into account. So, there can be several players with PositionCode 10 (Forward 1). Players who are not on the field do not get a PositionCode. Strictly speaking, PositionCode could be calculated using RoleID and Behaviour and is formally redundant, but it is provided anyway.

Available in Version(s): 1.2, 1.3

**PositionCode** : MatchPositionID

An integer indicating the position the player played at, after repositioning (behaviour) has been taken into account. So, there can be several players with PositionCode 10 (Forward 1). Players who are not on the field do not get a PositionCode. Strictly speaking, PositionCode could be calculated using RoleID and Behaviour and is formally redundant, but it is provided anyway. In 553-based lineups this is just RoleID repeated.

**Behaviour** : MatchBehaviourID

An integer indicating the individual order or repositioning that the player has played with.