

Multi-Channel Extraction Coordinates & 4-Tier Fallback Matrix

Agent-Reach Bridge architecture ensuring zero-result
resilience across 17+ internet data channels

A detailed technical specification of LeadReach's 4-tier fallback architecture for multi-channel data extraction. Covers 17 channels, cascade logic, trigger conditions, zero-result guarantee implementation, proxy rotation infrastructure, and production resilience metrics demonstrating 99.2% pipeline success rate.

TIER 1 Primary 85-95% success	TIER 2 Secondary 70-85% success	TIER 3 Tertiary 60-80% success	TIER 4 LLM Knowledge 40-60% accuracy
--	--	---	---

Section 1: Executive Summary

LeadReach's Agent-Reach Bridge provides multi-channel data extraction across 17+ internet channels with a 4-tier fallback architecture ensuring zero-result resilience. The system is designed for production-grade reliability: when a primary data source fails (rate limit, downtime, blocking), the pipeline automatically cascades through fallback tiers. The pipeline NEVER returns zero results, always falling back to LLM-generated knowledge when all extraction channels are unavailable.

Section 2: Channel Inventory & Status

Web	Jina Reader (r.jina.ai)	z-ai SDK	mcporter	LLM Knowledge	Zero	Active
Exa Search	DuckDuckGo via Jina	z-ai SDK web_search	mcporter Exa	Jina Search API	Zero	Active
LinkedIn	mcporter linkedin-scraper	Jina Reader direct	Exa semantic search	LLM Knowledge	Zero	Active
Twitter/X	Exa Semantic Search	Jina Reader	LLM Knowledge	—	Zero	Active
YouTube	yt-dlp	Jina Reader	LLM Knowledge	—	Zero	Active
GitHub	gh CLI	Exa Search	Jina Reader	LLM Knowledge	Zero (public)	Active
Reddit	Public JSON API	Jina Reader	LLM Knowledge	—	Zero	Limited
RSS	Feedparser	Jina Reader	LLM Knowledge	—	Zero	Active
Bilibili	yt-dlp + Platform API	Rotating API keys (3)	LLM Knowledge	—	3 keys w/ rotation	Active
Weibo	Weibo API	Jina Reader	LLM Knowledge	—	Zero	Active
V2EX	V2EX API	Jina Reader	LLM Knowledge	—	Zero	Active
Xueqiu	Xueqiu API	Auto session cookies	LLM Knowledge	—	Zero	Active
WeChat Articles	Exa Search	Camoufox	LLM Knowledge	—	Partial	Limited
XiaoHongShu	xhs-cli	Cookie export	LLM Knowledge	—	Cookie required	Disabled
Douyin	douyin-mcp-server	mcporter	LLM Knowledge	—	mcporter setup	Disabled
Xiaoyuzhou	Groq Whisper + ffmpeg	LLM Knowledge	—	—	API key required	Disabled

Active: 11 channels | Limited: 3 channels | Disabled: 3 channels | Total: 17 channels

Section 3: 4-Tier Fallback Architecture Detail

Tier 1 — Primary Extraction

Real-time web extraction using purpose-built backends. Highest data quality and freshness. Typical latency: 2–8 seconds. Success rate: 85–95%.

Tier 2 — Secondary Extraction

Alternative extraction methods using different technical approaches. Good data quality, moderate freshness. Typical latency: 4–12 seconds. Success rate: 70–85%.

Tier 3 — Tertiary Extraction

Semantic search or API-based approaches. Lower granularity but reliable coverage. Typical latency: 3–10 seconds. Success rate: 60–80%.

Tier 4 — LLM Knowledge Generation

When all extraction channels fail, the LLM generates synthetic prospect profiles based on its training data. Lowest accuracy but ensures zero-result resilience. Typical latency: 5–15 seconds. Success rate: 40–60% accuracy.

Section 4: Fallback Trigger Conditions

Condition	Detection Method	Response	Cooldown
HTTP 429 (Rate Limited)	Response status code	Skip to next tier	60 seconds
HTTP 403 (Blocked)	Response status code	Skip to next tier	300 seconds
Timeout (>15s)	Request timer	Skip to next tier	None
Empty Response	Content length check	Skip to next tier	None
Parse Failure	Schema validation	Retry once, then skip	None
Malformed Data	Field validation	LLM repair attempt	None
Service Unreachable	Connection error	Skip to next tier	120 seconds

Section 5: Zero-Result Guarantee Implementation

The pipeline implements a strict zero-result guarantee through the following mechanism:

- Agent receives search request from Orchestrator
- Primary backend (Tier 1) is attempted with 15-second timeout
- If Tier 1 fails, Tier 2 is attempted with 15-second timeout
- If Tier 2 fails, Tier 3 is attempted with 15-second timeout

- 5. If Tier 3 fails, Tier 4 (LLM Knowledge) generates synthetic results
- 6. Results from any tier are validated against minimum schema requirements
- 7. If validation fails, the next tier is attempted automatically
- 8. The pipeline ALWAYS returns at least one result

This guarantee is critical for customer trust: no user ever sees “no results found.”

Section 6: Channel Health Monitoring

The AgentReachChannel model monitors real-time health of each channel:

- Status: Active, Degraded, Down, Disabled
- Last Checked timestamp
- Response time tracking
- Error rate tracking
- Automatic status updates based on consecutive failures

Section 7: Proxy Rotation Infrastructure

For channels that may block automated requests:

- Optional proxy rotation via proxy-rotator.ts
- Rotating User-Agent strings
- Request throttling with jitter (1.5s minimum + 500ms random)
- Camoufox integration for browser-fingerprint-resistant extraction

Section 8: Resilience Metrics (Production)

Metric	Value	Target
Overall Pipeline Success Rate	99.2%	>99%
Average Fallback Rate	14.3%	<20%
Tier 1 Success Rate	85.7%	>80%
Tier 4 Invocation Rate	0.8%	<5%
Average Extraction Latency	4.2s	<8s
Max Extraction Latency	45s	<60s
Zero-Result Rate	0%	0%

End of Document — Multi-Channel Extraction Coordinates & 4-Tier Fallback Matrix