

Indwe — Get Lucky Golf Club Leads API

Integration guide · v1 · May 2026

Hi Wilhelm — this is the lead feed for the Indwe sponsorship. One read-only HTTPS endpoint, one Bearer token, every lead captured across the Get Lucky Golf Club website and on-course QR-code forms returned as normalised JSON.

Endpoint

```
GET https://www.getluckygolf.co.za/api/indwe/leads
Authorization: Bearer <YOUR_API_KEY>
```

That's it. No pagination, no signing, no webhooks to register. Poll on whatever interval suits you (we suggest every 15 minutes).

Authentication

A single Bearer token shared out-of-band. Treat it like a password — server-side only, never put it in a browser or mobile app.

```
Authorization: Bearer 5d7e4e11700461f924a3959299f7e281a04d1590bae43c802120912a2b2caa29
```

Your real key will be sent separately.

Query parameters (all optional)

Param	Example	Effect
since	2026-05-01T00:00:00Z	Only return leads with a Timestamp $\geq$ this ISO 8601 value.
type	voucher	Filter to one type. Values: voucher, course-entry, free-entry, partner, corporate.

Recommended pattern: store the generatedAt you receive, pass it back as since on the next poll.

Response shape

```
{
  "count": 2,
  "generatedAt": "2026-05-04T17:32:11.482Z",
  "leads": [
    {
      "id": "GL-VCH-7H3K9",
      "type": "voucher",
      "timestamp": "2026-05-04T16:12:03Z",
      "name": "Jane Smith",
      "email": "jane@example.com",
      "mobile": "+27821234567",
      "course": "Royal Cape",
      "event": "",
      "status": "paid",
      "source": "online",
      "raw": { "...original sheet row...": "" }
    },
    {
      "id": "free-entry-2026-05-04T15:55:01Z-john@example.com",
      "type": "free-entry",
      "timestamp": "2026-05-04T15:55:01Z",
      "name": "John Doe",
      "email": "john@example.com",
      "mobile": "+27839876543",
      "course": "Erinvale",
      "event": "Indwe Corporate Day",
      "status": "lead",
      "source": "qr-on-course",
      "raw": { "...": "" }
    }
  ]
}
```

Field reference

Field	Type	Notes
id	string	Stable identifier (PayFast reference where applicable). Use for dedup.
type	enum	voucher (online purchase) · course-entry (paid QR entry on course) · free-entry (sponsored free entry) · partner (course partner enquiry) · corporate (corporate golf-day enquiry).
timestamp	ISO 8601	When the lead was captured.
name	string	Best available name (full name / buyer / recipient).
email	string	Best available email.
mobile	string	E.164-formatted where possible.
course	string	Golf course associated with the lead.
event	string	Event name or golf-day date, if any.

Field	Type	Notes
status	enum	paid · lead · pending. Only paid records are returned for voucher and course-entry.
source	string	Where the lead came from (online, qr-on-course, etc.).
raw	object	Original row from our system, for any field not in the normalised shape.

Error responses

Status	Meaning
401	Missing or wrong Bearer token.
503	Endpoint not yet enabled (key not configured).
500	Upstream read failure. Retry with backoff.

All error bodies look like { "error": "..."}.

Quick test (curl)

```
curl -s https://www.getluckygolf.co.za/api/indwe/leads \
  -H "Authorization: Bearer YOUR_KEY" | jq
```

Filter to today's paid voucher buyers only:

```
curl -s "https://www.getluckygolf.co.za/api/indwe/leads?type=voucher&since=2026-05-04T00:00:00Z" \
  -H "Authorization: Bearer YOUR_KEY" | jq
```

Recommended polling pattern

```
// Pseudocode – runs every 15 minutes
let lastSync = loadFromDb() || "2026-01-01T00:00:00Z";

const res = await fetch(
  `https://www.getluckygolf.co.za/api/indwe/leads?since=${encodeURIComponent(lastSync)}`,
  { headers: { Authorization: `Bearer ${process.env.GETLUCKY_API_KEY}` } }
);
const { leads, generatedAt } = await res.json();

for (const lead of leads) {
  await upsertById(lead.id, lead); // dedup on lead.id
}

saveToDb(generatedAt); // becomes next `since`
```

Contact

Anything off, ping me directly — Johannes, johannes@getluckygolfclub.com.