











# FluidNC Settings



☒ Flash Settings    ☐ Config Items

Label	Value
Settings that are saved immediately	
Click "Set" after changing a value to set it	
Start/Message	<div>Grbl \V [FluidNC \B (\R)Set</div>
Firmware/Build	<div>Set</div>
SD/FallbackCS	<div>-1Set</div>
Report/Status	<div>1Set</div>
Config/Filename	<div>maslow.yamlSet</div>
Message/Level	<div>Debug▼Set</div>
Notification/Type	<div>NONE▼Set</div>
Notification/T1	<div>Set</div>
Notification/T2	<div>Set</div>
Notification/TS	<div>Set</div>
Telnet/Enable	<div>ON▼Set</div>
Telnet/Port	<div>23Set</div>

Label	Value
HTTP/BlockDuringMotion	ON  Set
HTTP/Enable	ON  Set
HTTP/Port	80 Set
WiFi/Mode	STA>AP  Set
Sta/SSID	<input type="text"/>  Set
Sta/Password	<input type="password"/>  Set
Sta/MinSecurity	WPA2-PSK  Set
WiFi/FastScan	OFF  Set
Sta/IPMode	DHCP  Set
Sta/IP	0.0.0.0 Set
Sta/Gateway	0.0.0.0 Set
Sta/Netmask	0.0.0.0 Set
AP/Country	01  Set
AP/SSID	maslow Set
AP/Password	<input type="password"/>  Set
AP/IP	192.168.0.1 Set
AP/Channel	1 Set

Label	Value
Hostname	<div><div>maslow</div><div>Set</div></div>