



Score: 74%

No. of questions: 10

Correct answer: 8

Incorrect answer: 2

Show incorrect attempt only ☐**Question 1**

1 Mark

In a decision tree, by comparing the impurity across all possible splits in all possible predictors, the next split is chosen. How can we measure the impurity?

A ROC

B Entropy, Gini-Index



C MAPE

Correct Answer: B. Entropy, Gini-Index

ROC and MAPE are evaluation metrics and not the criterion to decide splits. Entropy and Gini-Index are used to decide the right split.

Question 2

2 Marks

While creating a decision tree, can we reuse a feature to split a node?

Prev
VideoNext
VideoA (machine-learning/screen/6209)
Yes

(machine-learning/screen/6210)



No

Module Test



H

Correct Answer: A. Yes

Decision tree recursively uses all the features at each node.

Question 3

3 marks

What is the maximum number of terminal nodes in a decision tree if our training dataset has N samples?

A N

B $N/2$ C $2*N$ D $\log(N)$ **Correct Answer:** A. N

We can have a separate leaf node for each observation as well. Hence the maximum number of terminal nodes, in this case, will be N.

Question 4

1 Mark

Which of the following is/are the disadvantage(s) of decision tree algorithm?

A Decision tree is not easy to interpret



Prev

Video
(machine-

B

Decision tree is not a very stable algorithm

Next

Video
(machine-

learning/screen/6209)

learning/screen/6210)



Decision tree will overfit the data easily if it perfectly memorized it

Module Test



H

D Both B and C



Correct Answer: D. Both B and C

Decision tree is easy to interpret. All other are the disadvantages of decision tree.

Question 5

2 Marks

Which of the following parameter(s) can help to prevent overfitting?

A Max depth

B Minimum samples for node split

C Minimum samples for leaf node

D Splitting criterion

E Option A, B, and C



Correct Answer: E. Option A, B, and C

Splitting criterion does not help in preventing overfitting, it just makes sure that we get pure nodes. Tuning other hyperparameters like max_depth, minimum samples for node split, minimum samples for leaf node will help to prevent overfitting.

Question 6

3 marks

Below are a few options of parameters of a decision tree. In which of the following cases higher is better?

(machine-learning/screen/6209)

(machine-learning/screen/6210)

A Number of samples used for split



Module Test



H

B Depth of tree

C Samples for leaf

D Can't say



Correct Answer: D. Can't say

For all three options A, B and C, it is not necessary that if you increase the value of parameter the performance will increase. For example, if we have a very high value of depth of tree, the resulting tree may overfit the data, and would not generalize well. On the other hand, if we have a very low value, the tree may underfit the data. So, we can't say for sure that "higher is better".

Question 7

1 Mark

Let's say you are asked to work on a problem to predict the future sales of a product in a store and decided to use a decision tree model. Which algorithm should be used for splitting?

A Gini

B Chi-square

C Reduction in variance



D Information gain

Correct Answer: C. Reduction in variance

Since the target variable is continuous, it is a regression problem and hence reduction in variance will be used for splitting.



Prev

Video

(machine-

learning/screen/6209)

Next

Video

(machine-

learning/screen/6210)

Question 8


2 Marks

Why do we prefer information gain over accuracy when splitting?



H

A Decision tree is prone to overfit and accuracy doesn't help to generalize

B Information gain is more stable as compared to accuracy 

C Information gain chooses more impactful features closer to root

D All of the above

Correct Answer: D. All of the above

All of the given options are correct.

Question 9

3 marks

Decision trees are not affected by multicollinearity in features.

A True 

B False

Correct Answer: A. True

True, decision trees are not affected by multicollinearity in features. For example, if there are two 90% correlated features, decision tree would consider only one of them for splitting.

Question 10

1 Mark

How can we avoid overfitting in a decision tree?

Next
Video



(machine-learning/screen/6209)

(machine-learning/screen/6210)

A By stopping the tree growth.



Module Test



H

B By increasing the growth of the tree.

Correct Answer: A. By stopping the tree growth.

Increasing the growth of tree increases the chances of overfitting and hence if we stop the growth, it can help us to avoid overfitting.



Prev
Video
(machine-
learning/screen/6209)

Next
Video



(machine-
learning/screen/6210)