Data Warehouse Naming Conventions

This document outlines the naming conventions used for schemas, tables, views, columns and other objects in the Data Warehouse project.

Table of Content

1. General Principles *(# general-principles*)
2. Table Naming Conventions *(# table-naming-conventions*)
   -Bronze Rules *(# bronze-rules)*
   -Silver Rules *(# silver-rules)*
   -Gold Rules *(# gold-rules)*
3. Column Naming Conventions (*# column-naming-conventions*)
   -Surrogate Keys *(# surrogate-keys)*
   -Technical Keys *(# technical-keys)*
4. Stored Procedures (*# stored-procedures-naming-conventions*)

General Principles:

- Naming Conventions: Use snake-case, with lowercase letters and underscores ('_') to separate words

- Avoid Reserved Word: Do not use SQL reserved words as object names e.g 'table' instead of customers Details.

Table Naming Conventions

Bronze Rules

All names must start with the source system name, and table names must match their original names without renaming

- ***<sourcesystem>_<entity>***
- ***<sourcesystem>:*** name of the source system (e.g crm, erp)
- ***<entity>:*** Exact table name from the source system
- Example: crm_customer_inf: Customer information from the CRM system

Silver Rules

All names must start with the source system name, and table names must match their original names without renaming

- ***<sourcesystem>_<entity>***
- ***<sourcesystem>:*** name of the source system (e.g crm, erp)
- ***<entity>:*** Exact table name from the source system
- Example: crm_customer_inf: Customer information from the CRM system

Gold Rules

All names must use meaningful, business-alignednames for tables, starting with the category prefix

- ***<category>_<entity>***
- ***<category>:*** Describe the role of the tale, such as ***'dim'*** (dimension) or 'fact' (fact table)
- ***<entity>:*** Descriptive name of the table, aligned with the business domain e.g (customers, products, orders).
- Examples:
    - Dim_customers
    - Fact_orders. Fact table containing sails transactions

Glossary of Category Patterns

Pattern	Meaning	Example(s)
dim_	Dimension table	dim_customers, dim_products
fact_	Fact table	Fact_orders,
agg_	Aggregated table	Agg_customers

Column Naming Convention

Surrogate Keys

All primary keys in the dimension tables must use the prefix '_key'

- ***'<table_name_key>'***
- ***'<table_name>':*** Refers to the name of the table or entity the key belongs to
- '***key':*** A suffix indicating that the column is a surrogate key

Technical Columns

Technical columns must start with the prefix ***'dwh_',*** followed by a descriptive name indicating the column's purpose.

- ***'dwh_<column_name>'***
- ***'dwh_<column_name>':*** Prefix exclusively for system-generated metadata
- ***'<column_name>':*** Descriptive name indicating the column's purpose

- Example: ***'dwh_load_date'*** System-generated column used to store the date when the record was loaded

Stored Procedures

All the stored procedures used for loading data must follow the naming pattern:

- ***'load_<layer>'***
- ***'<layer>':*** Represents the layer being loaded, such as ***'bronze', 'silver',*** or ***'gold'***
- Example:

  'load_bronze': Stored procedure for loading data into the bronze layer

  'load_silver': Stored procedure for loading data into silver layer