

20145271 Geum Kang Hyeon

## Digit Classifying Using MNIST Datasets

Let  $x = (x_1, x_2, \dots, x_m)$  be a vector representing an image in the dataset.

The prediction function  $f_w(x)$  is defined by the linear combination of data  $(1, x)$  and the model parameter  $w$ :  $f_d(x; w) = w_0 * 1 + w_1 * x_1 + w_2 * x_2 + \dots + w_m * x_m$  where  $w = (w_0, w_1, \dots, w_m)$

The prediction function  $f_w(x)$  should have the following values:  $f_d(x; w) = +1$  if label(x) is  $d$ ,  $f_d(x; w) = -1$  if label(x) is not  $d$

The optimal model parameter  $w$  is obtained by minimizing the following objective function:

$$\sum_i (f_w(x^i) - y^i)^2$$

and the label of input  $x$  is given by :  $\operatorname{argmax}_d f_d(x; w)$

### 1. Declare required variables

References to Assignment 03 code

In [54]:

```
import matplotlib.pyplot as plt
import numpy as np

train_file_data = "mnist_train.csv"
test_file_data = "mnist_test.csv"

handle_file = open(train_file_data, "r")
data = handle_file.readlines()
handle_file.close()

handle_file = open(test_file_data, "r")
data_Test = handle_file.readlines()
handle_file.close()

size_row = 28
size_col = 28

num_image = len(data)
num_image_Test = len(data_Test)

count = 0
count_Test = 0

list_image = np.empty((num_image, size_row * size_col), dtype=float)
list_label = np.empty(num_image, dtype=int)

list_image_Test = np.empty((num_image_Test, size_row * size_col), dtype=float)
list_label_Test = np.empty(num_image_Test, dtype=int)
```

## 2. Read Data

In [55]:

```
# Read Train Data
for line in data:
    line_data = line.split(',')
    label     = line_data[0]
    im_vector  = np.asfarray(line_data[1:])

    list_label[count] = label
    list_image[count] = im_vector
    count += 1

# Read Test Data
for line in data_Test:
    line_data = line.split(',')
    label     = line_data[0]
    im_vector  = np.asfarray(line_data[1:])

    list_label_Test[count_Test] = label
    list_image_Test[count_Test] = im_vector
    count_Test += 1
```

## 3. Align Data A and b in formula $Ax = b$ for each digit

In [56]:

```
A = np.zeros((count, size_row*size_col), dtype=float)
b = np.zeros((10, count), dtype=float)
b_Test = np.zeros((10, count), dtype=float)

A = list_image
for idx in range(0, 10):
    for i in range(count):
        if list_label[i] == idx:
            b[idx][i] = 1
        else:
            b[idx][i] = -1

    for i in range(count_Test):
        if list_label_Test[i] == idx:
            b_Test[idx][i] = 1
        else:
            b_Test[idx][i] = -1
```

## 4. Calculate x for each digit

$$x = (A^T A)^{-1} A^T b$$

$$x = A^+ b$$

In [60]:

```
transpose_A = np.transpose(A)

# Calculate Pseudo Inverse
step1 = np.matmul(transpose_A, A)
step2 = np.linalg.pinv(step1)
step3 = np.matmul(step2, transpose_A)

#  $x = (\text{Pseudo Inverse of } A) * b$ 
result = np.zeros((10, len(step3)), dtype=float)

for i in range(0, 10):
    result[i] = np.matmul(step3, b[i])
```

## 5. Compute TP, FP, TN, FN using Train Dataset

TP, TN are Answer, FP, FN are Wrong Answer

Put the actual data in the expression  $Ax = b$  and compare it with the answer in the train dataset

In [58]:

```
TP, TN, FP, FN = (0, 0, 0, 0)

for i in range(count):
    value = np.zeros(10, dtype=float)
    for idx in range(0, 10):
        value[idx] = np.matmul(list_image[i], result[idx])
    idx = np.argmax(value)
    if value[idx] >= 0 and b[idx][i] == 1:
        TP += 1
    elif value[idx] < 0 and b[idx][i] == -1:
        TN += 1
    elif value[idx] >= 0 and b[idx][i] == -1:
        FP += 1
    elif value[idx] < 0 and b[idx][i] == 1:
        FN += 1
```

## 6. Compute TP, FP, TN, FN using Test Dataset

x uses x obtained through the train dataset

Model from train dataset can be verified

In [59]:

```

TP_Test, TN_Test, FP_Test, FN_Test = (0, 0, 0, 0)

for i in range(count_Test):
    value = np.zeros(10, dtype=float)
    for idx in range(0,10):
        value[idx] = np.matmul(list_image_Test[i], result[idx])
    idx = np.argmax(value)
    if value[idx] >= 0 and b_Test[idx][i] == 1:
        TP_Test += 1
    elif value[idx] < 0 and b_Test[idx][i] == -1:
        TN_Test += 1
    elif value[idx] >= 0 and b_Test[idx][i] == -1:
        FP_Test += 1
    elif value[idx] < 0 and b_Test[idx][i] == 1:
        FN_Test += 1

```

## 7. Result

In [53]:

```

print('[Train Data Set]')
print('Total Data Count : ' + str(count) + '\n')
print('TRUE POSITIVE : ' + str(TP) + ' (' + str("%0.1f" % (TP / count * 100)) + '%)')
print('TRUE NEGATIVE : ' + str(TN) + ' (' + str("%0.1f" % (TN / count * 100)) + '%)')
print('FALSE POSITIVE : ' + str(FP) + ' (' + str("%0.1f" % (FP / count * 100)) + '%)')
print('FALSE NEGATIVE : ' + str(FN) + ' (' + str("%0.1f" % (FN / count * 100)) + '%)')

print('\n\n[Test Data Set]')
print('Total Data Count : ' + str(count_Test) + '\n')
print('TRUE POSITIVE : ' + str(TP_Test) + ' (' + str("%0.1f" % (TP_Test / count_Test * 100)) + '%)')
print('TRUE NEGATIVE : ' + str(TN_Test) + ' (' + str("%0.1f" % (TN_Test / count_Test * 100)) + '%)')
print('FALSE POSITIVE : ' + str(FP_Test) + ' (' + str("%0.1f" % (FP_Test / count_Test * 100)) + '%)')
print('FALSE NEGATIVE : ' + str(FN_Test) + ' (' + str("%0.1f" % (FN_Test / count_Test * 100)) + '%)')

```

[Train Data Set]  
Total Data Count : 60000

TRUE POSITIVE : 42506 (70.8%)  
TRUE NEGATIVE : 5421 (9.0%)  
FALSE POSITIVE : 3463 (5.8%)  
FALSE NEGATIVE : 8610 (14.3%)

[Test Data Set]  
Total Data Count : 10000

TRUE POSITIVE : 7013 (70.1%)  
TRUE NEGATIVE : 902 (9.0%)  
FALSE POSITIVE : 564 (5.6%)  
FALSE NEGATIVE : 1521 (15.2%)

Train Data	True	False
Positive	42506 (70.8%)	3463 (5.8%)
Negative	5421 (9.0%)	8610 (14.3%)

  

Test Data	True	False
Positive	7013 (70.1%)	564 (5.6%)
Negative	902 (9.0%)	1521 (15.2%)