

L01.02

Coding Cost model Document Distance

50.004 Introduction to Algorithm

Gemma Roig

(slides adapted from Dr. Simon LUI)

ISTD, SUTD

About the coding requirement of the course

coding requirement of this course

- we will be **reading and understanding** code / pseudo code
- You need to do some coding in exercise / homework / problem set
- You need to read/write code in exam
 - E.g. read a code, tell me if it is $O(n)$ or $O(n \log n)$

coding requirement of this course

What is pseudo code

```
if a is divisible by 3  
    print “OH YEAH”
```


What is code

```
if (a%3 == 0)  
    print “OH YEAH”;
```

How to **read** code and find its
 $T(n)$

How to read code

Print("GREAT");



$$T(n) = 1$$

i.e. the number of steps
required to complete this
program is 1

This code is $\Theta(1)$

How to read code

```
Print("GREAT");  
Print("GREAT");  
Print("GREAT");  
Print("GREAT");
```



$$T(n) = 4$$

i.e. the number of steps
required to complete this
program is 4

This code is $\Theta(1)$

How to read code

```
For (i=0;i<5;i++)  
    Print("GREAT");
```



$$T(n) = 5$$

i.e. the number of steps
required to complete this
program is 5

This code is $\Theta(1)$

How to read code

```
For (i=0;i<n;i++)  
    Print("GREAT");
```



$$T(n) = n$$

i.e. the number of steps
required to complete this
program is n

This code is $\Theta(n)$

How to read code

```
For (int i=0;i<n;i++)  
  For (int j=0;j<n;j++)  
    Print("GREAT");
```


$$T(n) = n^2$$

i.e. the number of steps
required to complete this
program is n^2

This code is
 $\Theta(n^2)$

How to read code

```
For (i=0;i<n;i++)  
    For (j=0;j<n;j++)  
        Print("GREAT");  
For (k=0;k<n;k++)  
    print("GREAT");
```



$$T(n) = n^2 + n$$

i.e. the number of steps
required to complete this
program is $n^2 + n$

This code is
 $\Theta(n^2)$

How to read code

```
For (i=0;i<n;i++)  
    For (j=0;j<n;j++)  
        Print("GREAT");  
For (k=0;k<n;k++)  
    print("GREAT");  
print("GREAT");  
print("GREAT");  
print("GREAT");
```


$$T(n) = n^2 + n + 3$$

i.e. the number of steps required to complete this program is $n^2 + n$

This code is
 $\Theta(n^2)$

The cost model of code

Python cost model

$L = [a_1, a_2, \dots, a_n]$ L is a list

Commands	complexity (time)	
$L[i]=x$	$\Theta(1)$	
$L.append(x)$	$\Theta(1)$	Add x to L
$L_1.extend(L_2)$	$\Theta(L_2)$	Add L_2 to L_1
$A = L_1+L_2$	$\Theta(L_1 + L_2)$	Add L_2 and L_1 to A
$x \text{ in } L$	$\Theta(L)$	Search for x

$D = \{x_1 : y_1, x_2 : y_2, \dots, x_n : y_n\}$ D is a dictionary

Commands	complexity (time)	
$D[x_i]=y_i$	$\Theta(1)$	X is index, y is value
$x \text{ in } D$	$\Theta(1)$	Search for x

Document distance

- *Document* means sequence of words
- The **Problem**: Given 2 documents, find out how similar are they
- The **Algorithm**: we will talk about it


Document distance - usage

1. detect plagiarism

2. Web update check

- Simon loves iPhone. He wants to be the world first person to buy it*
- So he write a **DOCUMENT DISTANCE code** to check if the apple webpage has updated*
 - If updated, probably there are new product.*
 - So, send a email to notify Simon*

Document distance - usage



```
<!DOCTYPE html>
<html class="singapore sg nojs en en-sg apac" lang="en-SG">
  <head>
    <meta name="viewport" content="width=1024" />
    <title>Pre-order iPhone 6s and iPhone 6s Plus - Apple (SG)</title>
    <meta charset="utf-8" />
    <meta http-equiv="X-UA-Compatible"
content="IE=edge,chrome=1" />
    <meta name="format-detection" content="telephone=no" />
    <meta http-equiv="Set-Cookie"
content="as_sfa=MnxzZ3xzZ3x8ZW5fU0d8Y29uc3VtZXJ8aW50ZXJuZXR8MHwwfDE=; path=/; domain=.apple.com; expires=Mon,
15-Sep-2025 04:18:11 GMT;" />

    <meta property="og:type"
content="product" />
```

Apple.com/iphone.html
...at 11:58am

←→
COMPARE



```
<!DOCTYPE html>
<-equiv="X-UA-Compatible" content="IE=edge,chrome=1" />
<meta name="format-detection" content="telephone=no" />
<meta http-equiv="Set-Cookie"
content="as_sfa=MnxzZ3xzZ3x8ZW5fU0d8Y29uc3VtZXJ8aW50ZXJuZXR8MHwwfDE=; path=/; domain=.apple.com; expires=Mon,
15-Sep-2025 04:18:11 GMT;" />

    <meta property="og:type"
content="product" />
    <meta property="og:title" content="iPhone
6s" />

    <meta property="og:url"
content="http://www.apple.com/sg/shop/buy-iphone/
iphone6s" />

    <meta prope
```

Apple.com/iphone.html
...at 11:59am

Problem definition

- Document D : sequence of words
- Word w : sequence of characters
- **Word frequency** $D(w)$: number of occurrences of w in D
- For example
 - D : “good morning good good”
 - w : {“good”, “morning”, “good”, “good”}
 - $w[0]$ = “good”
 - $w[1]$ = “morning”
 - $w[2]$ = “good”
 - $w[3]$ = “good”
 - $D(\text{“good”}) = 3$

What we will do today

- I will show you some VERY COMPLICATED CODE
- No need to understand them (out of syllabus)
- I just want see
 - the running time of $O(1)$, $O(n)$ and $O(n^2)$ function can be very different
 - How to improve the speed of a code

Algorithm for document distance - Vector space model


- Treat each document as a vector of its words
 - one coordinate per word of the English dictionary

e.g. **doc1** = “the cat”
doc2 = “the dog”

The dot product between D1 and D2

represent their similarity

$$D_1 \circ D_2 \equiv \sum_w D_1(w) \cdot D_2(w)$$



Algorithm for document distance - Vector space model

e.g.

“the cat”。 ”the dog”

= [the x the + cat x dog]

= 1 + 0

= 1

Algorithm for document distance - Vector space model

e.g.

“the the cat cat”。 ”the the dog dog”

= the x the + the x the + cat x dog + cat x dog

= 1 + 1 + 0 + 0

= 2

Algorithm for document distance - Vector space model

... wait,

A: “the cat” vs “the dog”

B: “the the cat cat” vs “the the dog dog”

Both problem A and B are 50% similar.

Why B score more (2) than A (1)?

So, we need to **normalize** the result

Algorithm for document distance - Vector space model

e.g.

["the cat", "the dog"] / $\sqrt{2 \times 2}$

= [the x the + cat x dog] / 2

= [1 + 0] / 2

= 50%

Algorithm for document distance - Vector space model

e.g.

["the the cat cat"。 "the the dog dog"] / $\sqrt{4 \times 4}$

= [the x the + the x the + cat x dog + cat x dog]
/ 4

= [1 + 1 + 0 + 0] / 4

= 50%

Vector space model

- Normalization
 - divide by the length of the vectors

$$\frac{D_1 \circ D_2}{||D_1|| \cdot ||D_2||} \quad D_1 = aD_2$$

- measure distance by angle between vectors:

$$\theta(D_1, D_2) = \arccos \left(\frac{D_1 \circ D_2}{||D_1|| \cdot ||D_2||} \right)$$

e.g. $\theta=0$ documents “identical”
(if of the same size, permutations of each other)
 $\theta=\pi/2$ not even share a word

Algorithm

aa**b**cv**nl**bg**b**aa**nl**aaub**b**aa**nl**cv**b**xf**eof**

- Read file

Algorithm

aa**b**cv**bn**!bg**b**aa**n**!aaub**a**aa**n**!cv**b**xf**eof**

- Read file
- Make word list (divide file into words)

[aa,cv] + [bg,aa] + [aa,aa] + [cv,xf]

→ [aa, cv, bg, aa, aa, aa, cv,xf]

Algorithm

aa**bc**cv**bn**lbg**ba**an**la**au**ba**an**lc**vb**xf****eof**

- Read file
- Make word list (divide file into words)
- Count frequencies of words

[aa, cv, bg, aa, aa, aa, cv,xf]



[(aa,3), (cv,2), (bg,1), (aa,1),(xf,1)]


Algorithm

aa**b**cv**bn**lbg**b**aa**n**laau**b**aa**n**lcv**b**xf**eof**

- Read file
- Make word list (divide file into words)
- Count frequencies of words
- Compute dot product

$D_1: [(aa, 3), (aa, 1), (bg, 1), (cv, 2)]$

$D_2: [(aa, 2), (ba, 2), (bg, 2), (ca, 1), (fv, 2)]$



Algorithm

aa**b**cv**bn**lbg**b**aa**n**laaub**a**a**n**lc**v**bxf**eof**

- Read file
- Make word list (divide file into words)
- Count frequencies of words
- Compute dot product
 - for every word in the first document, check if it appears in the other document; if yes, multiply their frequencies and add to the dot product
 - worst case time: order of
$$\#words(D_1) \times \#words(D_2)$$

Algorithm

aa**bc**vb**nl**bgbaa**nl**aaubaa**nl**cvbxf**eof**

- Read file
- Make word list (divide file into words)
- Count frequencies of words
- Compute dot product
 - for every word in the first document, check if it appears in the other document; if yes, multiply their frequencies and add to the dot product
 - worst case time: order of
$$\#words(D_1) \times \#words(D_2)$$
 - micro-optimization:
 - sort documents into word order (alphabetically)
 - compute inner product in time
$$\#words(D_1) + \#words(D_2)$$

Python Implementation

- Docdist1.py (see handout)
- Read file: `read_file(filename)`
 - Output: list of lines (strings)
- Make word list: `get_words_from_line_list(L)`
 - Output: list of words (array)
- Count frequencies: `count_frequency(word list)`
 - Output: list of word-frequency pairs
- Dot product: `inner_product(D1, D2)`
 - Output: number

cProfiling.run()

- return $T(n)$
 - import profile
 - profile.run("main()")



auk:~/Class/6006/lectures/I01/

```
t1.verne.txt      t4.arabian.txt      t7.tenmillion.txt
t2.bobsey.txt     t5.churchill.txt    t8.shakespeare.txt
t3.lewis.txt      t6.onemillion.txt   t9.bacon.txt
auk:I01> python source/docdist2.py data/t2.bobsey.txt data/t3.lewis.txt
File data/t2.bobsey.txt : 6667 lines, 49785 words, 3354 distinct words
File data/t3.lewis.txt : 15996 lines, 182355 words, 8530 distinct words
The distance between the documents is: 0.574160 (radians)
```

3861660 function calls in 94.738 CPU seconds

ordered by: standard name

ncalls	tottime	percall	cumtime	percall	filename:lineno(function)
1	0.000	0.000	0.000	0.000	:0(acos)
1241849	4.320	0.000	4.320	0.000	:0(append)
1300248	4.432	0.000	4.432	0.000	:0(isalnum)
232140	0.772	0.000	0.772	0.000	:0(join)
368314	1.300	0.000	1.300	0.000	:0(len)
232140	0.760	0.000	0.760	0.000	:0(lower)
2	0.000	0.000	0.000	0.000	:0(open)
2	0.000	0.000	0.000	0.000	:0(range)
2	0.008	0.004	0.008	0.004	:0(readlines)
1	0.000	0.000	0.000	0.000	:0(setprofile)
1	0.000	0.000	0.000	0.000	:0(sqrt)
1	0.004	0.004	94.738	94.738	<string>:1(<module>)
2	34.366	17.183	34.394	17.197	docdist2.py:105(count_frequency)
2	9.781	4.890	9.781	4.890	docdist2.py:122(insertion_sort)
2	0.000	0.000	94.438	47.219	docdist2.py:144(word_frequencies_for_file)
3	0.156	0.052	0.292	0.097	docdist2.py:162(inner_product)
1	0.000	0.000	0.292	0.292	docdist2.py:188(vector_angle)
1	0.004	0.004	94.734	94.734	docdist2.py:198(main)
2	0.000	0.000	0.008	0.004	docdist2.py:49(read_file)
2	23.605	11.803	50.255	25.128	docdist2.py:65(get_words_from_line_list)
226	12.409	0.001	26.650	0.001	docdist2.py:77(get_words_from_string)
1	0.000	0.000	94.738	94.738	profile:0(main())
0	0.000	0.000	0.000	0.000	profile:0(profiler)
232140	1.424	0.000	2.184	0.000	string.py:218(lower)
232140	1.396	0.000	2.168	0.000	string.py:306(join)

auk:I01> █

docdist1


- Docdist1.py is slow
 - Docdist2.py is faster
 - Docdist3.py is even faster
 -
 - Docdist8.py is the best
-
- Now let's look at docdist1.py

76 docdist1.py - C:\Documents and Settings\David\My Doc...



File Edit Format Run Options Windows Help

```
#####  
# Operation 2: split the text lines into words ##  
#####  
def get_words_from_line_list(L):  
    """  
    Parse the given list L of text lines into words.  
    Return list of all words found.  
    """  
  
    word_list = []  
    for line in L:  
        words_in_line = get_words_from_string(line)  
        word_list = word_list + words_in_line  
    return word_list
```




Ln: 130 Col: 18

+ is slow, need to improve it

- Look at word_list = word_list + words_in_line
- + : concatenation of arrays
- running time = $T(k)$
 - $k = \text{length}(\text{word_list}) + \text{length}(\text{words_in_line})$
- Total $T(n)$ is $1+2+\dots+n = n(n+1)/2 = \Theta(n^2)$

```
for line in L:  
    words_in_line = get_words_from_string(line)  
    word_list = word_list + words_in_line
```



Solution

- word_list = word_list + words_in_line: $\Theta(n^2)$
 - docdist1.py (3.7s)
- word_list.extend(words_in_line) : $\Theta(n)$
 - docdist2.py (2.722s)
- How to run:
 - Python docdist1.py file5.txt file4.txt

Further Improvements

- Docdist3.py: sort the data first (2.657s)
- Docdist4.py: Instead of inserting words in list, insert in dictionary: (0.735s)
- Docdist5.py: Process words instead of chars (0.138s)
- Docdist6.py: better sorting algorithm (0.069s)
 - merge sort instead of insertion sort
- Docdist7.py: dictionary instead of sort. (0.052s)

Appendix - how to optimize the code

docdist<1-8>.py - Iterative improvements

- Objective
 - To arrive at the most efficient implementation in terms of running time
- Approach
 - At each iteration, analyze the running times of various parts of the code
 - Based on the biggest consumer of running time, refactor the code by
 - Introducing faster algorithms
 - Using features of the Python language
 - Simplifying and optimizing code

docdist1 - Code structure

```
1 def main():
2     if len(sys.argv) != 3:
3         print "Usage: docdist1.py filename_1 filename_2"
4     else:
5         filename_1 = sys.argv[1]
6         filename_2 = sys.argv[2]
7         document_vector_1 = word_frequencies_for_file(filename_1)
8         document_vector_2 = word_frequencies_for_file(filename_2)
9         distance = vector_angle(document_vector_1, document_vector_2)
10        print "The distance between the documents is: %0.6f (radians)"%distance
```

docdist1 - Code structure

```
1 def main():
2     if len(sys.argv) != 3:
3         print "Usage: docdist1.py filename_1 filename_2"
4     else:
5         filename_1 = sys.argv[1]
6         filename_2 = sys.argv[2]
7         document_vector_1 = word_frequencies_for_file(filename_1)
8         document_vector_2 = word_frequencies_for_file(filename_2)
9         distance = vector_angle(document_vector_1, document_vector_2)
10        print "The distance between the documents is: %.6f (radians)"%distance
```



```
1 def word_frequencies_for_file(filename):
2     line_list = read_file(filename)
3     word_list = get_words_from_line_list(line_list)
4     freq_mapping = count_frequency(word_list)
5     return freq_mapping
```

docdist1 - Code structure

```
1 def main():
2     if len(sys.argv) != 3:
3         print "Usage: docdist1.py filename_1 filename_2"
4     else:
5         filename_1 = sys.argv[1]
6         filename_2 = sys.argv[2]
7         document_vector_1 = word_frequencies_for_file(filename_1)
8         document_vector_2 = word_frequencies_for_file(filename_2)
9         distance = vector_angle(document_vector_1, document_vector_2)
10        print "The distance between the documents is: %0.6f (radians)"%distance
11
12    def word_frequencies_for_file(filename):
13        line_list = read_file(filename)
14        word_list = get_words_from_line_list(line_list)
15        freq_mapping = count_frequency(word_list)
16        return freq_mapping
17
18    def get_words_from_line_list(L):
19        word_list = []
20        for line in L:
21            words_in_line = get_words_from_string(line)
22            word_list = word_list + words_in_line
23        return word_list
24
25    def get_words_from_string(line):
26        word_list = []
27        character_list = []
28        for c in line:
29            if c.isalnum():
30                character_list.append(c)
31            elif len(character_list)>0:
32                word = "".join(character_list)
33                word = word.lower()
34                word_list.append(word)
35                character_list = []
36        if len(character_list)>0:
37            word = "".join(character_list)
38            word = word.lower()
39            word_list.append(word)
40        return word_list
```

docdist1 - Code structure

```
1 def main():
2     if len(sys.argv) != 3:
3         print "Usage: docdist1.py filename_1 filename_2"
4     else:
5         filename_1 = sys.argv[1]
6         filename_2 = sys.argv[2]
7         document_vector_1 = word_frequencies_for_file(filename_1)
8         document_vector_2 = word_frequencies_for_file(filename_2)
9         distance = vector_angle(document_vector_1, document_vector_2)
10        print "The distance between the documents is: %0.6f (radians)"%distance
11
12    def word_frequencies_for_file(filename):
13        line_list = read_file(filename)
14        word_list = get_words_from_line_list(line_list)
15        freq_mapping = count_frequency(word_list)
16        return freq_mapping
```



```
1 def count_frequency(word_list):
2     L = []
3     for new_word in word_list:
4         for entry in L:
5             if new_word == entry[0]:
6                 entry[1] = entry[1] + 1
7             break
8         else:
9             L.append([new_word, 1])
10    return L
```

docdist1 - Code structure

```
1 def main():
2     if len(sys.argv) != 3:
3         print "Usage: docdist1.py filename_1 filename_2"
4     else:
5         filename_1 = sys.argv[1]
6         filename_2 = sys.argv[2]
7         document_vector_1 = word_frequencies_for_file(filename_1)
8         document_vector_2 = word_frequencies_for_file(filename_2)
9         distance = vector_angle(document_vector_1, document_vector_2)
10        print "The distance between the documents is: %0.6f (radians)"%distance
```



```
1 def vector_angle(L1, L2):
2     numerator = inner_product(L1, L2)
3     denominator = math.sqrt(inner_product(L1, L1) * inner_product(L2, L2))
4     return math.acos(numerator/denominator)
```

docdist1 vs. docdist2

```
1 def get_words_from_line_list(L):
2     word_list = []
3     for line in L:
4         words_in_line = get_words_from_string(line)
5         word_list = word_list + words_in_line
6     return word_list
```

```
1 def get_words_from_line_list(L):
2     word_list = []
3     for line in L:
4         words_in_line = get_words_from_string(line)
5         word_list.extend(words_in_line)
6     return word_list
```


docdist1 vs. docdist2

docdist1 Performance Scorecard

Method	Time
get_words_from_line_list	$O(\frac{W^2}{k}) = O(W^2)$
count_frequency	$O(WL)$
word_frequencies_for_file	$O(W^2)$
inner_product	$O(L_1L_2)$
vector_angle	$O(L_1L_2 + L_1^2 + L_2^2) = O(L_1^2 + L_2^2)$
main	$O(W_1^2 + W_2^2)$

docdist2 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(WL)$
word_frequencies_for_file	$O(WL)$
inner_product	$O(L_1L_2)$
vector_angle	$O(L_1^2 + L_2^2)$
main	$O(W_1L_1 + W_2L_2)$

docdist2 vs. docdist3

```
1 def word_frequencies_for_file(filename):  
2     line_list = read_file(filename)  
3     word_list = get_words_from_line_list(line_list)  
4     freq_mapping = count_frequency(word_list)  
5     return freq_mapping
```

```
1 def word_frequencies_for_file(filename):  
2     line_list = read_file(filename)  
3     word_list = get_words_from_line_list(line_list)  
4     freq_mapping = count_frequency(word_list)  
5     insertion_sort(freq_mapping)  
6     return freq_mapping
```

docdist3 - Implementing insertion_sort()

```
1 def insertion_sort(A):
2     for j in range(len(A)):
3         key = A[j]
4         i = j-1
5         while i>-1 and A[i]>key:
6             A[i+1] = A[i]
7             i = i-1
8         A[i+1] = key
9     return A
```

docdist3 - Reimplementing inner_product()

```
1 def inner_product(L1,L2):
2     sum = 0.0
3     for word1, count1 in L1:
4         for word2, count2 in L2:
5             if word1 == word2:
6                 sum += count1 * count2
7     return sum
```

```
1 def inner_product(L1,L2):
2     sum = 0.0
3     i = 0
4     j = 0
5     while i<len(L1) and j<len(L2):
6         # L1[i:] and L2[j:] yet to be processed
7         if L1[i][0] == L2[j][0]:
8             # both vectors have this word
9             sum += L1[i][1] * L2[j][1]
10            i += 1
11            j += 1
12        elif L1[i][0] < L2[j][0]:
13            # word L1[i][0] is in L1 but not L2
14            i += 1
15        else:
16            # word L2[j][0] is in L2 but not L1
17            j += 1
18    return sum
```

SLIDE 10.12 Select Filters for Algorithms

docdist2 vs. docdist3

docdist2 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(WL)$
word_frequencies_for_file	$O(WL)$
inner_product	$O(L_1L_2)$
vector_angle	$O(L_1^2 + L_2^2)$
main	$O(W_1L_1 + W_2L_2)$

docdist3 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(WL)$
insertion_sort	$O(L^2)$
word_frequencies_for_file	$O(WL + L^2) = O(WL)$
inner_product	$O(L_1 + L_2)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1L_1 + W_2L_2)$

docdist4 - Refining count_frequency()

```
1 def count_frequency(word_list):
2     L = []
3     for new_word in word_list:
4         for entry in L:
5             if new_word == entry[0]:
6                 entry[1] = entry[1] + 1
7                 break
8         else:
9             L.append([new_word, 1])
10    return L
```

```
1 def count_frequency(word_list):
2     D = {}
3     for new_word in word_list:
4         if new_word in D:
5             D[new_word] = D[new_word]+1
6         else:
7             D[new_word] = 1
8     return D.items()
```

docdist3 vs. docdist4

docdist3 Performance Scorecard

Method	Time
get words from line list	$O(W)$
count_frequency	$O(WL)$
insertion_sort	$O(L^2)$
word_frequencies_for_file	$O(WL + L^2) = O(WL)$
inner_product	$O(L_1 + L_2)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1L_1 + W_2L_2)$

docdist4 Performance Scorecard

Method	Time
get words from line list	$O(W)$
count_frequency	$O(W)$
insertion_sort	$O(L^2)$
word_frequencies_for_file	$O(W + L^2) = O(L^2)$
inner_product	$O(L_1 + L_2)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2 + L_1^2 + L_2^2)$

docdist5 - Simplifying get_words_from_string()

```
8 def get_words_from_string(line):
9     word_list = []
10    character_list = []
11    for c in line:
12        if c.isalnum():
13            character_list.append(c)
14        elif len(character_list)>0:
15            word = "".join(character_list)
16            word = word.lower()
17            word_list.append(word)
18            character_list = []
19    if len(character_list)>0:
20        word = "".join(character_list)
21        word = word.lower()
22        word_list.append(word)
23    return word_list
```

```
1 translation_table = string.maketrans(string.punctuation+string.uppercase,
2                                     " "*len(string.punctuation)+string.lowercase)
3
4 def get_words_from_string(line):
5     line = line.translate(translation_table)
6     word_list = line.split()
7     return word_list
```


docdist4 vs. docdist5 (same as docdist4)

docdist4 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(W)$
insertion_sort	$O(L^2)$
word_frequencies_for_file	$O(W + L^2) = O(L^2)$
inner_product	$O(L_1 + L_2)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2 + L_1^2 + L_2^2)$

docdist4 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(W)$
insertion_sort	$O(L^2)$
word_frequencies_for_file	$O(W + L^2) = O(L^2)$
inner_product	$O(L_1 + L_2)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2 + L_1^2 + L_2^2)$

docdist6 - Replacing insertion sort by merge sort

```
1 def word_frequencies_for_file(filename):
2     line_list = read_file(filename)
3     word_list = get_words_from_line_list(line_list)
4     freq_mapping = count_frequency(word_list)
5     freq_mapping = merge_sort(freq_mapping)
6     return freq_mapping

1 def merge_sort(A):
2     n = len(A)
3     if n==1:
4         return A
5     mid = n//2
6     L = merge_sort(A[:mid])
7     R = merge_sort(A[mid:])
8     return merge(L,R)
9
10 def merge(L,R):
11     i = 0
12     j = 0
13     answer = []
14     while i<len(L) and j<len(R):
15         if L[i]<R[j]:
16             answer.append(L[i])
17             i += 1
18         else:
19             answer.append(R[j])
20             j += 1
21     if i<len(L):
22         answer.extend(L[i:])
23     if j<len(R):
24         answer.extend(R[j:])
25     return answer
```

docdist5 vs. docdist6

docdist4 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(W)$
insertion_sort	$O(L^2)$
word_frequencies_for_file	$O(W + L^2) = O(L^2)$
inner_product	$O(L_1 + L_2)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2 + L_1^2 + L_2^2)$

docdist6 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(W)$
merge_sort	$O(L \log L)$
word_frequencies_for_file	$O(W + L \log L) = O(L \log L)$
inner_product	$O(L_1 + L_2)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2 + L_1 \log L_1 + L_2 \log L_2)$

docdist7 - From sorted list to document vectors

```
1 def count_frequency(word_list):
2     D = {}
3     for new_word in word_list:
4         if new_word in D:
5             D[new_word] = D[new_word]+1
6         else:
7             D[new_word] = 1
8     return D
```

```
1 def word_frequencies_for_file(filename):
2     line_list = read_file(filename)
3     word_list = get_words_from_line_list(line_list)
4     freq_mapping = count_frequency(word_list)
5     return freq_mapping
```

```
1 def inner_product(D1,D2):
2     sum = 0.0
3     for key in D1:
4         if key in D2:
5             sum += D1[key] * D2[key]
6     return sum
```

docdist6 vs. docdist7

docdist6 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(W)$
merge_sort	$O(L \log L)$
word_frequencies_for_file	$O(W + L \log L) = O(L \log L)$
inner_product	$O(L_1 + L_2)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2 + L_1 \log L_1 + L_2 \log L_2)$

docdist7 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(W)$
word_frequencies_for_file	$O(W)$
inner_product	$O(L_1)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2)$

docdist8 - Simplifying the code

```
1 def get_words_from_string(string):  
2     string = string.translate(translation_table)  
3     word_list = string.split()  
4     return word_list  
5  
6 def word_frequencies_for_file(filename):  
7     text = read_file(filename)  
8     word_list = get_words_from_string(text)  
9     freq_mapping = count_frequency(word_list)  
10    return freq_mapping
```

docdist7 vs. docdist8

docdist7 Performance Scorecard

Method	Time
get_words_from_line_list	$O(W)$
count_frequency	$O(W)$
word_frequencies_for_file	$O(W)$
inner_product	$O(L_1)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2)$

docdist8 Performance Scorecard

Method	Time
get_words_from_text	$O(W)$
count_frequency	$O(W)$
word_frequencies_for_file	$O(W)$
inner_product	$O(L_1)$
vector_angle	$O(L_1 + L_2)$
main	$O(W_1 + W_2)$