

Student Information

Name: _____

Student ID: _____

Due Date: 27 Nov 11:59pm.

Submit answers on eDimension in pdf format. Submission without student information will **NOT** be marked! Any questions regarding the homework can be directed to the TA through email (contact information on eDimension).

Week 11

1. In comparison to other methods that do not take advantage of overlapping subproblems, dynamic programming takes far less time in finding a solution. [True/False]. Explain why.
Only half of the full marks will be awarded if answer is correct without explanation.
2. What are the changes in time and space complexities when a top-down approach of dynamic programming is applied to a problem?
 - A. Time and space complexities decrease.
 - B. Time and space complexities increase.
 - C. Time complexity increases and space complexity decreases.
 - D. Time complexity decreases and space complexity increases.
3. Modify the rod-cutting problem in Figure 1 to include for each cut, a fixed cost c in addition to the price p_i for each rod. The revenue is now the sum of the prices of the pieces minus the costs of making cuts. Show the modified dynamic programming algorithm.
Hint: Modify line 4, 5 and 6.

```
BOTTOM-UP-CUT-ROD( $p, n$ )
1  let  $r[0..n]$  be a new array
2   $r[0] = 0$ 
3  for  $j = 1$  to  $n$ 
4       $q = -\infty$ 
5      for  $i = 1$  to  $j$ 
6           $q = \max(q, p[i] + r[j - i])$ 
7       $r[j] = q$ 
8  return  $r[n]$ 
```

Figure 1: Rod-cutting algorithm

4. Dynamic programming algorithms are usually based on recursive equations. Why don't dynamic programming algorithms simply use recursion to implement those equations directly? Briefly explain.
5. Let $P(n)$ be the number of n -length binary strings that do not have any three consecutive ones (i.e. they do not have "111" as a substring). For example:
- $P(1) = 2$: 0, 1,
 $P(2) = 4$: 00, 01, 10, 11
 $P(3) = 7$: 000, 001, 010, 011, 100, 101, 110
 $P(4) = 13$: 0000, 0001, 0010, 0011, 0100, 0101, 0110, 1000, 1001, 1010, 1011, 1100, 1101
- Hint:** Each binary string has either one of the following 3 properties: a) Last bit is 0, b) Last two bits are 01, c) Last three bits are 011.
- (i) Write down the recursive formula to compute $P(n)$.
- (ii) Suppose we implement a dynamic programming algorithm using the recursive formula in (i), what is the running time of the dynamic programming algorithm?