


1. **Project Structure and Environment Verification**

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> docker --version
Docker version 29.8.1, build 4a63305
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> docker compose ver
sion
Docker Compose version v5.5.1
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> docker info
Client:
 Version:    29.8.1
 Context:    desktop-linux
 Debug Mode: false
 Plugins:
  agent: Docker AI Agent Runner (Docker Inc.)
    Version:  v1.141.0
    Path:     C:\Users\DELL\.docker\cli-plugins\docker-agent.exe
  ai: Docker AI Agent - Ask Gordon (Docker Inc.)
    Version:  v1.31.0
    Path:     C:\Users\DELL\.docker\cli-plugins\docker-ai.exe
  buildx: Docker Buildx (Docker Inc.)
    Version:  v0.37.1
    Path:     C:\Users\DELL\.docker\cli-plugins\docker-buildx.ex
```

2. Docker Compose Configuration Validation

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> docker compose con
fig
name: bookflow-week10
services:
  db-mongo:
    container_name: bookflow-mongo
    image: mongo:7
    networks:
      default: null
    ports:
      - mode: ingress
        target: 27017
        published: "27017"
        protocol: tcp
    volumes:
      - type: volume
        source: mongo-data
        target: /data/db
        volume: {}
  db-postgres:
    container_name: bookflow-postgres
    environment:
      POSTGRES_DB: bookflow
      POSTGRES_PASSWORD: postgres
      POSTGRES_USER: postgres
    image: postgres:16
    networks:
      default: null
    ports:
      - mode: ingress
```


3. Docker Images Built Successfully for All BookFlow Services

```
[+] build 3/3
 ✔Image bookflow-gateway:week10        Built                100.0s
 ✔Image bookflow-user-service:week10   Built                 99.8s
 ✔Image bookflow-stock-service:week10  Built                100.1s
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10>
```

4. BookFlow Multi-Container Stack Running Successfully

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow_Week10_Fresh_Implementation\bookflow-week10> docker compose up -d
[+]  35/3535
 ✔Image mongo:7                          Pulled            42.4s
 ✔Image postgres:16                      Pulled            37.3s
 ✔Volume bookflow-week10_postgres-data   Created            0.0s
 ✔Network bookflow-week10_default        Created            0.1s
 ✔Volume bookflow-week10_mongo-data      Created            0.0s
 ✔Container bookflow-postgres            Started            3.6s
 ✔Container bookflow-mongo               Started            2.6s
 ✔Container bookflow-user-service        Started            1.6s
 ✔Container bookflow-stock-service       Started            2.7s
 ✔Container bookflow-gateway             Started            3.1s
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow_Week10_Fresh_Implementation\bookflow-week10> docker compose ps
NAME                  IMAGE                          COMMAND                  SERVICE         CREATED          STATUS          PO
RTS
bookflow-gateway      bookflow-gateway:week10        "uvicorn app:app --h…"   gateway         24 seconds ago   Up 21 seconds   0.
0.0.0:8000->8000/tcp, [::]:8000->8000/tcp
bookflow-mongo        mongo:7                        "docker-entrypoint.s…"   db-mongo        26 seconds ago   Up 23 seconds   0.
0.0.0:27017->27017/tcp, [::]:27017->27017/tcp
bookflow-postgres     postgres:16                    "docker-entrypoint.s…"   db-postgres     26 seconds ago   Up 22 seconds   0.
0.0.0:5432->5432/tcp, [::]:5432->5432/tcp
bookflow-stock-service   bookflow-stock-service:week10   "java -jar app.jar"      stock-service   24 seconds ago   Up 22 seconds   0.
0.0.0:8080->8080/tcp, [::]:8080->8080/tcp
bookflow-user-service    bookflow-user-service:week10    "docker-entrypoint.s…"   user-service    24 seconds ago   Up 23 seconds   0.
0.0.0:3000->3000/tcp, [::]:3000->3000/tcp
```

5A. FastAPI Gateway



5B. Node.js User Service

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\curl.exe http://localhost:3000/healthmentation\bookflow-week10>
{"service":"bookflow-user-service","week":"10","author":"Kamtam Privanka","status":"UP"}
```

5C. Spring Boot Stock Service

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow_Week10_Fresh_Implementation\bookflow-week10> curl.exe http://localho
st:8080/health
{"service":"bookflow-stock-service","status":"UP","author":"Kamtam Priyanka","week":"10"}
```

6. **FastAPI Gateway Successfully Communicates with Node.js User Service**

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow_Week10_Fresh_Implementation\bookflow-week10> curl.exe http://localho
st:8000/gateway/users
[{"userId":501,"name":"Kamtam Priyanka","role":"Student"}]
```

7. **Spring Boot Stock Service — Inventory Retrieved from PostgreSQL**


```
_Week10_Fresh_Implementation\bookflow-week10> curl.exe -i "http:
//localhost:8080/inventory/101"
HTTP/1.1 200
Content-Type: application/json
Transfer-Encoding: chunked
Date: Mon, 05 Oct 2026 05:23:34 GMT

{"bookId":101,"totalStock":5,"availableStock":5}
```

8. **Spring Boot Stock Service — Inventory Retrieved from PostgreSQL**

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> docker exec -it bo
okflow-postgres psql -U postgres -d bookflow -c "SELECT * FROM i
nventory ORDER BY book_id;"
 book_id | available_stock | total_stock
---------+-----------------+-------------
     101 |               5 |           5
     102 |               3 |           3
     103 |               0 |           2
(3 rows)
```

9. **Spring Boot Stock Service — Successful Book Borrowing**




10. PostgreSQL — Inventory Updated After Successful Book Borrowing

Stock availability is changed from 5→4 for book_id = 101

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> docker exec -it bo
okflow-postgres psql -U postgres -d bookflow -c "SELECT * FROM i
nventory ORDER BY book_id;"
 book_id | available_stock | total_stock
---------+-----------------+-------------
     101 |               4 |           5
     102 |               3 |           3
     103 |               0 |           2
```

11. FastAPI Gateway — Order Successfully Forwarded to Spring Boot



12. PostgreSQL — Gateway Order and Inventory Records Verified

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> docker exec -it bo
okflow-postgres psql -U postgres -d bookflow -c "SELECT * FROM i
nventory ORDER BY book_id;"
 book_id | available_stock | total_stock
---------+-----------------+-------------
     101 |               3 |           5
     102 |               3 |           3
     103 |               0 |           2
```

13. Docker Desktop Kubernetes Cluster — Node Ready

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> kubectl get nodes
NAME                    STATUS   ROLES           AGE   VERSION
desktop-control-plane   Ready    control-plane   79s   v1.36.1
```

14. Kubernetes Deployment — BookFlow Gateway Running with 2 Replicas

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> kubectl apply -f .
\k8s\deployment.yaml
deployment.apps/bookflow-gateway created
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> kubectl get deploy
ments
NAME              READY   UP-TO-DATE   AVAILABLE   AGE
bookflow-gateway   0/2     2            0           6s
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow
_Week10_Fresh_Implementation\bookflow-week10> kubectl get pods -
o wide
NAME                               READY   STATUS    RESTARTS
AGE   IP           NODE                    NOMINATED NODE   READ
INESS GATES
bookflow-gateway-dcf45cb66-cvzpl   1/1     Running   0
12s   10.244.0.5   desktop-control-plane   <none>           <non
e>
bookflow-gateway-dcf45cb66-wcwbq   1/1     Running   0
12s   10.244.0.6   desktop-control-plane   <none>           <non
e>
```

15. **Kubernetes LoadBalancer Service and Pod Endpoints**

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow_Week10_Fresh_Implementation\bookflow-week10> kubectl get service
NAME                       TYPE           CLUSTER-IP      EXTERNAL-IP   PORT(S)          AGE
bookflow-gateway-service   LoadBalancer   10.96.245.127   <pending>     8000:31755/TCP   9s
kubernetes                 ClusterIP      10.96.0.1       <none>        443/TCP          10m
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\BookFlow_Week10_Fresh_Implementation\bookflow-week10> kubectl get endpoints b
ookflow-gateway-service
Warning: v1 Endpoints is deprecated in v1.33+; use discovery.k8s.io/v1 EndpointSlice
NAME                       ENDPOINTS                         AGE
bookflow-gateway-service   10.244.0.5:8000,10.244.0.6:8000   4m11s
```

16. **Kubernetes Service — FastAPI Gateway Health Check Successful**

```
PS C:\WINDOWS\system32> curl.exe -i "http://localhost:8000/health"
HTTP/1.1 200 OK
date: Mon, 05 Oct 2026 06:11:15 GMT
server: uvicorn
content-length: 83
content-type: application/json

{"service":"bookflow-gateway","week":"10","author":"Kamtam Priyanka","status":"UP"}
```

17. **Kubernetes Deployment Before Self-Healing Test**

```
PS C:\WINDOWS\system32> kubectl get pods
NAME                                READY   STATUS    RESTARTS
AGE
bookflow-gateway-dcf45cb66-cvzpl    1/1     Running   0
21m
bookflow-gateway-dcf45cb66-wcwbq    1/1     Running   0
21m
PS C:\WINDOWS\system32> kubectl get deployment bookflow-gateway
NAME               READY   UP-TO-DATE   AVAILABLE   AGE
bookflow-gateway   2/2     2            2           21m
```

18. **Kubernetes Self-Healing — Failed Pod Automatically Replaced**

```
PS C:\WINDOWS\system32> kubectl delete pod bookflow-gateway-dcf4
5cb66-cvzpl
pod "bookflow-gateway-dcf45cb66-cvzpl" deleted from default name
space
PS C:\WINDOWS\system32> kubectl get pods -w
NAME                                READY   STATUS    RESTARTS
AGE
bookflow-gateway-dcf45cb66-bkrp9    1/1     Running   0
11s
bookflow-gateway-dcf45cb66-wcwbq    1/1     Running   0
75m
bookflow-gateway-dcf45cb66-wcwbq    1/1     Running   0
76m
```

19. **Kubernetes Deployment Restored to 2/2 Replicas**

```
PS C:\WINDOWS\system32> kubectl get deployment bookflow-gateway
NAME               READY   UP-TO-DATE   AVAILABLE   AGE
bookflow-gateway   2/2     2            2           77m
```

Folder Structure:

```
BookFlow_Week10_Fresh_Implementation/
└── bookflow-week10/
    │
    ├── docker-compose.yml
    ├── README.md
    │
    ├── gateway/
    │   ├── Dockerfile
    │   ├── requirements.txt
    │   └── app.py
    │
    ├── user-service/
    │   ├── Dockerfile
    │   ├── package.json
    │   └── server.js
    │
    ├── stock-service/
    │   ├── Dockerfile
    │   ├── pom.xml
    │   └── src/
    │       └── main/
    │           ├── java/
    │           │   └── com/bookflow/week10/
    │           │       ├── StockServiceApplication.java
    │           │       ├── controller/
    │           │       │   └── StockController.java
    │           │       ├── entity/
    │           │       │   ├── Inventory.java
    │           │       │   └── LibraryOrder.java
    │           │       └── repository/
    │           │           ├── InventoryRepository.java
    │           │           └── LibraryOrderRepository.java
    │           │
    │           └── resources/
    │               └── application.yml
    │
    └── k8s/
        ├── deployment.yaml
        └── service.yaml
```

Codes:

- `gateway/Dockerfile`

```
FROM python:3.11-slim
WORKDIR /app
```

```
COPY requirements.txt .
RUN pip install --no-cache-dir -r requirements.txt
COPY app.py .
EXPOSE 8000
CMD ["uvicorn", "app:app", "--host", "0.0.0.0", "--port", "8000"]
```

- gateway/app.py

```
import os
import httpx
from fastapi import FastAPI, HTTPException
app = FastAPI(title="BookFlow Gateway", version="Week-10",
description="Containerized gateway by Kamtam Priyanka")
USER_SERVICE_URL = os.getenv("USER_SERVICE_URL", "http://localhost:3000")
STOCK_SERVICE_URL = os.getenv("STOCK_SERVICE_URL", "http://localhost:8080")
@app.get("/health")
async def health():
    return {"service":"bookflow-gateway","week":"10","author":"Kamtam
Priyanka","status":"UP"}
@app.get("/gateway/users")
async def get_users():
    async with httpx.AsyncClient() as client:
        r = await client.get(f"{USER_SERVICE_URL}/users")
    if r.status_code >= 400: raise HTTPException(status_code=r.status_code,
detail=r.text)
    return r.json()
@app.post("/gateway/orders")
async def create_order(order: dict):
    async with httpx.AsyncClient() as client:
        r = await client.post(f"{STOCK_SERVICE_URL}/orders", json=order)
    if r.status_code >= 400: raise HTTPException(status_code=r.status_code,
detail=r.text)
    return r.json()
```

- gateway/requirements.txt

```
fastapi==0.115.6
uvicorn[standard]==0.34.0
httpx==0.28.1
```

- user-service/Dockerfile

```
FROM node:18-alpine
WORKDIR /app
COPY package*.json ./
RUN npm install --omit=dev
COPY server.js .
EXPOSE 3000
```

```
CMD ["npm", "start"]
```

- user-service/server.js

```
const express = require('express');
const mongoose = require('mongoose');
const app = express(); app.use(express.json());
const PORT=3000,
MONGO_URL=process.env.MONGO_URL||'mongodb://localhost:27017/bookflow_users';
const User=mongoose.model('User',new
mongoose.Schema({userId:{type:Number,unique:true},name:String,role:String}));
app.get('/health',(req,res)=>res.json({service:'bookflow-user-
service',week:'10',author:'Kamtam Priyanka',status:'UP'}));
app.get('/users',async(req,res)=>res.json(await User.find().select('-_id -
__v')));
app.post('/users',async(req,res)=>{const u=await
User.create(req.body);res.status(201).json({userId:u.userId,name:u.name,role:u
.role});});
async function start(){try{await mongoose.connect(MONGO_URL);const e=await
User.findOne({userId:501});if(!e)await User.create({userId:501,name:'Kamtam
Priyanka',role:'Student'});app.listen(PORT,'0.0.0.0',()=>console.log('User
Service running on port
3000'));}catch(e){console.error(e.message);process.exit(1)}}
start();
```

- user-service/package.json

```
{"name":"bookflow-user-
service","version":"1.0.0","main":"server.js","scripts":{"start":"node
server.js"},"dependencies":{"express":"4.21.2","mongoose":"8.9.5"}}
```

- stock-service/Dockerfile

```
FROM maven:3.9-eclipse-temurin-17 AS build
WORKDIR /build
COPY pom.xml .
COPY src ./src
RUN mvn clean package -DskipTests
FROM eclipse-temurin:17-jre
WORKDIR /app
COPY --from=build /build/target/bookflow-stock-service-1.0.0.jar app.jar
EXPOSE 8080
ENTRYPOINT ["java","-jar","app.jar"]
```

- stock-service/pom.xml

```
<?xml version="1.0" encoding="UTF-8"?><project
xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-
4.0.0.xsd"><modelVersion>4.0.0</modelVersion><parent><groupId>org.springframew
ork.boot</groupId><artifactId>spring-boot-starter-
parent</artifactId><version>3.5.5</version><relativePath/></parent><groupId>co
m.bookflow.week10</groupId><artifactId>bookflow-stock-
service</artifactId><version>1.0.0</version><properties><java.version>17</java
.version></properties><dependencies><dependency><groupId>org.springframework.b
oot</groupId><artifactId>spring-boot-starter-
web</artifactId></dependency><dependency><groupId>org.springframework.boot</gr
oupId><artifactId>spring-boot-starter-data-
jpa</artifactId></dependency><dependency><groupId>org.postgresql</groupId><art
ifactId>postgresql</artifactId><scope>runtime</scope></dependency></dependenci
es><build><plugins><plugin><groupId>org.springframework.boot</groupId><artifac
tId>spring-boot-maven-plugin</artifactId></plugin></plugins></build></project>
```

- stock-service/src/main/java/com/bookflow/week10/StockServiceApplication.java

```
package com.bookflow.week10;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
@SpringBootApplication
public class StockServiceApplication { public static void main(String[]
args){SpringApplication.run(StockServiceApplication.class,args);} }
```

- stock-service/src/main/java/com/bookflow/week10/controller/StockController.java

```
package com.bookflow.week10.controller;
import com.bookflow.week10.entity.*; import com.bookflow.week10.repository.*;
import org.springframework.http.ResponseEntity; import
org.springframework.web.bind.annotation.*; import java.util.Map;
@RestController public class StockController { private final
InventoryRepository inventory; private final LibraryOrderRepository orders;
public StockController(InventoryRepository i,LibraryOrderRepository
o){inventory=i;orders=o;}
@GetMapping("/health") public Map<String,String> health(){return
Map.of("service","bookflow-stock-service","week","10","author","Kamtam
Priyanka","status","UP");}
@GetMapping("/inventory/{bookId}") public ResponseEntity<?> get(@PathVariable
Long bookId){return
inventory.findById(bookId).map(ResponseEntity::ok).orElse(ResponseEntity.notFo
und().build());}
@PostMapping("/orders") public ResponseEntity<?> order(@RequestBody
Map<String,Long> req){Long u=req.get("userId"),b=req.get("bookId"); Inventory
i=inventory.findById(b).orElse(null); if(i==null)return
ResponseEntity.notFound().build(); if(i.getAvailableStock()<=0)return
ResponseEntity.status(409).body(Map.of("status",409,"error","OUT_OF_STOCK","me
```

```
ssage","Book "+b+" is out of stock"));
i.setAvailableStock(i.getAvailableStock()-1);inventory.save(i);LibraryOrder
o=orders.save(new LibraryOrder(u,b,"BORROWED"));return
ResponseEntity.status(201).body(Map.of("id",o.getId(),"userId",o.getUserId(),"
bookId",o.getBookId(),"status",o.getStatus()));}}
```

- stock-service/src/main/java/com/bookflow/week10/entity/Inventory.java

```
package com.bookflow.week10.entity;
import jakarta.persistence.*;
@Entity @Table(name="inventory")
public class Inventory { @Id private Long bookId; private Integer totalStock;
private Integer availableStock; public Inventory(){} public Inventory(Long
id,Integer total,Integer
available){bookId=id;totalStock=total;availableStock=available;} public Long
getBookId(){return bookId;} public void setBookId(Long v){bookId=v;} public
Integer getTotalStock(){return totalStock;} public void setTotalStock(Integer
v){totalStock=v;} public Integer getAvailableStock(){return availableStock;}
public void setAvailableStock(Integer v){availableStock=v;} }
```

- stock-service/src/main/java/com/bookflow/week10/entity/LibraryOrder.java

```
package com.bookflow.week10.entity;
import jakarta.persistence.*;
@Entity @Table(name="orders")
public class LibraryOrder { @Id
@GeneratedValue(strategy=GenerationType.IDENTITY) private Long id; private
Long userId; private Long bookId; private String status; public
LibraryOrder(){} public LibraryOrder(Long u,Long b,String
s){userId=u;bookId=b;status=s;} public Long getId(){return id;} public Long
getUserId(){return userId;} public Long getBookId(){return bookId;} public
String getStatus(){return status;} }
```

- stock-service/src/main/java/com/bookflow/week10/repository/InventoryRepository.java

```
package com.bookflow.week10.repository;
import com.bookflow.week10.entity.Inventory; import
org.springframework.data.jpa.repository.JpaRepository;
public interface InventoryRepository extends JpaRepository<Inventory,Long>{}
```

- stock-service/src/main/java/com/bookflow/week10/repository/LibraryOrderRepository.java

```
package com.bookflow.week10.repository;
import com.bookflow.week10.entity.LibraryOrder; import
org.springframework.data.jpa.repository.JpaRepository;
```

```
public interface LibraryOrderRepository extends
JpaRepository<LibraryOrder,Long>{}
```

- stock-service/src/main/resources/application.yml

```
spring:
  datasource:
    url: ${DB_URL:jdbc:postgresql://localhost:5432/bookflow}
    username: ${DB_USERNAME:postgres}
    password: ${DB_PASSWORD:postgres}
  jpa:
    hibernate:
      ddl-auto: update
    show-sql: true
server:
  port: 8080
```

- docker-compose.yml

```
services:
  gateway:
    build: ./gateway
    image: bookflow-gateway:week10
    container_name: bookflow-gateway
    ports: ["8000:8000"]
    environment:
      USER_SERVICE_URL: http://user-service:3000
      STOCK_SERVICE_URL: http://stock-service:8080
    depends_on: [user-service, stock-service]
  user-service:
    build: ./user-service
    image: bookflow-user-service:week10
    container_name: bookflow-user-service
    ports: ["3000:3000"]
    environment:
      MONGO_URL: mongodb://db-mongo:27017/bookflow_users
    depends_on: [db-mongo]
  stock-service:
    build: ./stock-service
    image: bookflow-stock-service:week10
    container_name: bookflow-stock-service
    ports: ["8080:8080"]
    environment:
      DB_URL: jdbc:postgresql://db-postgres:5432/bookflow
      DB_USERNAME: postgres
      DB_PASSWORD: postgres
    depends_on: [db-postgres]
  db-postgres:
```

```
    image: postgres:16
    container_name: bookflow-postgres
    environment:
      POSTGRES_DB: bookflow
      POSTGRES_USER: postgres
      POSTGRES_PASSWORD: postgres
    ports: ["5432:5432"]
    volumes: [postgres-data:/var/lib/postgresql/data]
  db-mongo:
    image: mongo:7
    container_name: bookflow-mongo
    ports: ["27017:27017"]
    volumes: [mongo-data:/data/db]
volumes:
  postgres-data:
  mongo-data:
```

- k8s/deployment.yaml

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: bookflow-gateway
  labels:
    app: bookflow-gateway
    owner: kamtam-priyanka
spec:
  replicas: 2
  selector:
    matchLabels:
      app: bookflow-gateway
  template:
    metadata:
      labels:
        app: bookflow-gateway
        owner: kamtam-priyanka
    spec:
      containers:
        - name: gateway
          image: bookflow-gateway:week10
          imagePullPolicy: IfNotPresent
          ports:
            - containerPort: 8000
```

- k8s/service.yaml

```
apiVersion: v1
kind: Service
metadata:
```

```
  name: bookflow-gateway-service
  labels:
    app: bookflow-gateway
    owner: kamtam-priyanka
spec:
  type: LoadBalancer
  selector:
    app: bookflow-gateway
  ports:
    - protocol: TCP
      port: 8000
      targetPort: 8000
```

My practical task on docker application:

